



AccuRev Plug-In for Eclipse 2018.3

User's Guide

Micro Focus
The Lawn
22-30 Old Bath Road
Newbury, Berkshire RG14 1QN
UK
<http://www.microfocus.com>

Copyright © Micro Focus 2018.2. All rights reserved.

MICRO FOCUS, the Micro Focus logo and AccuRev Plug-In for Eclipse User's Guide are trademarks or registered trademarks of Micro Focus IP Development Limited or its subsidiaries or affiliated companies in the United States, United Kingdom and other countries.

All other marks are the property of their respective owners.

2018-10-16

Contents

Preface	5
Getting Started	6
Logging In to AccuRev	6
Setting AccuRev Preferences in Eclipse	6
General AccuRev Settings	7
Using Alternative Diff and Merge Tools	8
Setting Label Decorations	11
Executing AccuRev Commands	12
Working with Eclipse Projects	14
Techniques for Associating Eclipse Projects with AccuRev	14
Creating an Eclipse Project in an Existing AccuRev Workspace	14
How New Eclipse Project Names are Taken from Existing .project Files	18
Creating a Single Eclipse Project in a New AccuRev Workspace	19
Creating Multiple Eclipse Projects in a New AccuRev Workspace	25
Sharing an Eclipse Project with AccuRev	30
How to Share a Eclipse Project with AccuRev	30
Adding an AccuRev Server	35
Advanced Techniques for Using AccuRev Data	37
Specifying UTF-8 Encoding	37
Setting Encoding for a File	37
Setting Encoding for a Project	38
Setting Encoding for a Workspace	38
Other Preferences for Specifying Character Encoding	38
Working in the Eclipse Navigator View	40
Integrated Commands	40
Refactor	40
Compare With	41
Replace With	42
Team Menu Commands	43
Synchronize with AccuRev Repository	43
Login	44
Logout	44
Add to AccuRev Depot	44
Keep	44
Anchor	46
Promote	46
Merge	48
Version Browser	49
Annotate	49
Populate	50
Defunct	51
Revert To	51
Diff Against	51
Copy as Link/Paste as Link	52
Synchronize Time	52
AccuRev Workspace Information	53
Update AccuRev Workspace	53
AccuRev History	53
AccuRev Statuses	53
AccuRev Searches	54

Show Properties	55
Refresh	55
Web UI	56
Share/Unshare Project	56
Create Patch/Apply Patch	56
AccuRev Web UI	57
Starting the AccuRev Web UI	57
Getting Started with the Web UI	58
Toolbar Access to AccuRev Commands	59
Running Commands in the Background	60
Promote-Based Integrations with Issue Management	60
Working in the AccuRev Perspective	62
AccuRev Console View	62
AccuRev Search/Status View	63
History View	64
Synchronize View	67
Performing Operations in the Synchronize View	69
Committing Outgoing Changes	70
Updating Incoming Changes	71
Integration with Mylyn	73
Adding an AccuWork Task Repository	74
Logging In to an AccuWork Task Repository	75
Removing an AccuWork Task Repository from Your Mylyn View	76
Working with AccuWork Queries	76
AccuRev Usage Model	80
Change and Synchronization: The Four Basic Commands	81
Keep: Preserving Changes in Your Private Workspace	81
Promote: Making Your Private Changes Public	83
Update: Incorporating Others' Changes into Your Workspace	85
Merge: When Changes Would Collide	86

Preface

This book describes how to use the AccuRev Plug-In for Eclipse. The plug-in is a standard Eclipse plug-in that provides access to AccuRev version-control facilities from the Eclipse Platform IDE. It assumes that you are familiar with AccuRev and its features. A brief overview of AccuRev is provided in [AccuRev Usage Model](#).

See the *AccuRev Plug-In for Eclipse Installation and Release Notes* for information specific to the current release, including notes on platform support and a summary of changes and known issues.

Getting Started

AccuRev Plug-In for Eclipse provides access to AccuRev version-control facilities from the Eclipse Platform IDE. This chapter describes tasks that get you up and running with AccuRev Plug-In for Eclipse

For a brief overview of AccuRev, see [AccuRev Usage Model](#)

Logging In to AccuRev

You must be logged in to AccuRev in order to perform AccuRev commands using AccuRev Plug-In for Eclipse. You can log in to AccuRev in one of these ways:

- In AccuRev directly, using one of these interfaces: the AccuRev GUI, the AccuRev Web UI , or the AccuRev Command Line Interface. If you are logged in to AccuRev when you start Eclipse, AccuRev commands are available for any elements in your projects that are under AccuRev control.
- In AccuRev Plug-In for Eclipse, using the **Team > Login** menu in the **Eclipse Navigator** or **Package Explorer** views. This menu is available only for projects and elements that are under AccuRev control. If you have no Eclipse projects associated with AccuRev, you must log in to AccuRev directly.
- In AccuRev Plug-In for Eclipse, using the **Team > Share Project > AccuRev** menu. When you share a project with AccuRev, you are prompted to log in to AccuRev if you are not logged in already.

In all cases, when you log in you are required to specify the AccuRev Server, and your AccuRev user name and password, as shown in the following illustration of the login dialog box for the AccuRev GUI:




 **Note:** Logging in to a different server directly through does not affect your existing connection in Eclipse. For example, if you are currently logged in to the AccuRev Alpha server, you can continue working with Eclipse projects that are under AccuRev control on that server even if you log in to the AccuRev Beta server directly through AccuRev.

Setting AccuRev Preferences in Eclipse

The **AccuRev** page in the **Eclipse Preferences** window lets you specify general settings such as which *Diff* and *Merge* tools you want to use, and which label decorations you want to use for files under control.

To open the **Preferences** window:

1. Place the cursor in the **AccuRev Console** window in Eclipse or select **Window > View > AccuRev Console**.
2. Display the **AccuRev** page on the **Eclipse Preference** window by selecting **Window > Preferences > Team > AccuRev** from the **Eclipse** menu.



General AccuRev Settings

Use the procedure described in this section to:

Change the path of the AccuRev executable

By default, AccuRev Plug-In for Eclipse looks for the AccuRev executable (`accurev.exe`) in the default installation location. If you customized the AccuRev installation, you might need to specify the location of the AccuRev executable here.

Use F5 to perform Eclipse refresh

By default, pressing the F5 key performs the AccuRev refresh operation, which updates the status of elements under AccuRev control displayed in the Navigator view. If you want F5 to perform the Eclipse refresh operation, which refreshes Eclipse project information only, clear the **Enable AccuRev refresh via F5** checkbox. See [Refresh](#) for more information.

To modify general AccuRev settings:

1. In Eclipse, open the **Preferences** window (**Window > Preferences**).
2. In the **Preferences** window, navigate to **Team > AccuRev**.
3. Change the settings as desired and click **OK**.

Using Alternative Diff and Merge Tools

By default, AccuRev uses its own tools to diff and merge files. If you want, you can configure:

Supported Third-Party Diff and Merge Tools

Vendor	Diff Tool Support	Merge Tool Support
Araxis	Yes	Yes
BeyondCompare	Yes	No
Eclipse	Yes	Yes
Guiffy	Yes	Yes
TkDiff	Yes	Yes

AccuRev provides preformatted command parameters for supported third-party Diff and Merge tools. To use one of these tools, all you need to do is specify the location of the tool's executable when you configure it. See [Configuring a Supported Third Party Diff or Merge Tool](#).

Custom Diff or Merge Tools

In the case of custom Diff and Merge tools, you need to specify the complete command parameters in addition to the executable's location. See [Command Parameters for Diff and Merge Tools](#).

Command Parameters for Diff and Merge Tools

The following summarizes the command parameters supported by AccuRev Plug-In for Eclipse.

Diff

- {backing stream version}** Quoted pathname of the first version to be compared.
- {workspace version}** Quoted pathname of the second version to be compared.

Merge

- {common ancestor version}** Quoted filename of the closest common ancestor version.
- {backing stream version}** Quoted filename of the version in the backing stream, or other non-workspace version.
- {workspace version}** Quoted filename of the version in the workspace.
- {merge results}** Quoted name of the merge-output file, which is a temporary file for storing the results of the merge.

These command parameters are preformatted for supported third party Diff and Merge tools. If you are configuring a custom Diff or Merge tool, you must ensure that the command parameters you specify are correct for that tool. For example, if you were configuring SourceGear DiffMerge, you might configure the Diff tool as follows:

```
/c="AccuRev Diff" /ro2 /t1="First" /t2="Second" {backing stream version}
{workspace version}
```

Similarly, the Merge tool might be configured as follows:

```
/c="AccuRev Diff" -merge -result={merge results} /t1="First" /t2="Second" /  
t3="Third"  
{backing stream version} {workspace version} {common ancestor version}
```

The executable for both Diff and Merge tools might be defined as follows:


```
C:\Program Files\SourceGear\DiffMerge\DiffMerge.exe
```

Specific command parameters vary from tool to tool. See your tool's documentation for more information.

Configuring a Supported Third Party Diff or Merge Tool

To configure a third party Diff or Merge tool supported by AccuRev:

1. Display the **AccuRev** page on the **Eclipse Preference** window by selecting **Window > Preferences > Team > AccuRev** from the **Eclipse** menu.



2. Select the supported third-party tool from the **Select Diff Tool** or **Select Merge Tool** field.

3. Click the **Edit** button. The **Add/Edit Tool** dialog box appears. Values in the **Tool Name** and **Path to Tool** fields are based on the tool you selected in the previous step.
4. If the third party tool executable is not on your system's search path, specify the complete path in the **Path to Tool** field.
5. Review the command line that will be used to invoke the third party tool.


AccuRev displays the command as it will be executed in the **Command used to invoke the Diff tool** (or **Command used to invoke the Diff tool**) field.

6. Click **OK**. The **Add/Edit Tool** dialog box closes.
7. Click **Apply** if you want to change other preferences. Otherwise, click **OK**.

Configuring a Custom Diff or Merge Tool

To configure a custom Diff or Merge tool:

1. Display the **AccuRev** page on the **Eclipse Preference** window by selecting **Window > Preferences > Team > AccuRev** from the **Eclipse** menu.



2. Click the **Add** button associated with the custom Diff or Merge tool you want to configure.
3. Enter values in the **Tool Name**, **Path to Tool**, and **Command Parameters** fields appropriate for the custom Diff or Merge tool you are configuring. See [Command Parameters for Diff and Merge Tools](#) if you need help with this step.

AccuRev displays the command as it will be executed in the **Command used to invoke the Diff tool** field (or **Command used to invoke the Diff tool** field).

4. Review the command line that will be used to invoke the custom third party tool.
5. Click OK. The **Add/Edit Tool** dialog box closes.
6. Click **Apply** if you want to change other preferences. Otherwise, click **OK**.

Setting Label Decorations

In AccuRev, each element has an `AccuRev` status, which is expressed using one or more status indicators, for example, `(kept)(member)`. In AccuRev Plug-In for Eclipse, an element's `AccuRev` status is represented using label decorations. Label decorations can be optionally displayed in the **Navigator** and **Package Explorer** views. They are always displayed in the **Synchronize** view.

Types of Label Decorations

You can specify one of two types of label decorations:

- Icon decoration** A colored symbol displayed in the lower-right corner of an object's file-type icon. Icon decorations are displayed by default, but you can turn them off if you want.
- Name decoration** One or more characters appended (or prefixed) to an object's name in the **Navigator** display. Name decorations are not displayed by default. You can turn them on and, optionally, change the characters used to represent the status.

The following table shows the status indicators and the label decorations that can be used to represent them.

Status	Icon Decoration	Default Name Decoration
<code>(backed)</code>	 green computer	^
<code>(member)</code>	 blue dot	>
<code>(modified)</code>	 white wrench	*
<code>(missing)</code>	 red circle	->
<code>(overlap)</code>	 white exclamation mark	<>
<code>(stale)</code>	 white arrow	<

Status indicators are not mutually exclusive. For example, an element's status can include both the `(modified)` and `(member)` indicators. But Eclipse uses only one decoration on each icon/filename. The precedence order of the statuses determines which decoration is displayed. Statuses are listed in precedence order from highest to lowest in the table.

Folder and Project Decorations

The following shows the folder indicators:



Folder marked with an asterisk icon

One or more of the elements in that folder has one of the following statuses:

(external)
(modified)
(overlap)
(member)



Project marked with a yellow database icon

The project is shared and you are logged into AccuRev.



Project marked with a grey database icon

The project is shared and you are not logged into AccuRev.



Project not marked with an AccuRev decoration

The project is not shared with AccuRev.

Turning Off Label Decorations

Label decorations for elements are displayed by default. Use this procedure to turn them off.

1. In Eclipse, open the **Preferences** window (**Window > Preferences**).
2. In the **Preferences** window, navigate to **General > Appearance > Label Decorations**.
3. Clear the **AccuRev Decorator** check box to turn off label decorations for AccuRev elements in the **Navigator** view.
4. Click **OK**.

Displaying Name Decorations

By default, only icon decorations are displayed in Eclipse. Use the following procedure to display name decorations and, optionally, change the characters used for the decoration.



Note: You can perform this procedure only on an existing Eclipse project.

1. In Eclipse, open the **Preferences** window (**Window > Preferences**).
2. In the **Preferences** window, navigate to **Team > AccuRev > Label Decorations**.
3. Check the **Enable text labels** check box.
4. By default, name decorations are prefixed to element names. Select **Append** if you want name decorations added to the end of element names.
5. Optionally, change the characters used to represent AccuRev statuses. For more on label decorations, see [Setting Label Decorations](#).
6. Click **OK**.

Executing AccuRev Commands

There are several ways to access AccuRev functionality within Eclipse:

Integrated commands

Some AccuRev functionality is integrated with existing Eclipse commands on the context menu. See [Integrated Commands](#).

Team menu	Many AccuRev commands are available in the Team menu. See Team Menu Commands .
Web UI	Some AccuRev functionality is accessed from the AccuRev Web UI, which is also started from the context menu. See AccuRev Web UI .
Toolbar	A commonly-used subset AccuRev features, for both the AccuRev GUI and AccuRev Web UI, is available on the Eclipse toolbar. See Toolbar Access to AccuRev Commands .



Note: While Eclipse allows you to select objects from multiple projects, AccuRev commands are available only if all the selected objects belong to the same AccuRev workspace.

Output from AccuRev Commands

AccuRev uses custom **Console** and **Search/Status** views to display output from AccuRev commands. These views, along with Eclipse's own Synchronize and History views, constitute the AccuRev perspective. For a description of these views, see [Working in the AccuRev Perspective](#).

What to Do Next

Once you have configured your preferences, you are ready to start working with Eclipse projects using AccuRev Plug-In for Eclipse. See [Working with Eclipse Projects](#) for more information.

Working with Eclipse Projects

AccuRev commands allow data to be managed within the central source-code repository (called a *depot* in AccuRev) and your personal work area (called a *workspace* in AccuRev, and a *project* in Eclipse).

Techniques for Associating Eclipse Projects with AccuRev

There are several techniques for associating Eclipse projects with AccuRev. The following summarizes these techniques. They are described in detail within this chapter.

Create an Eclipse Project in an Existing AccuRev Workspace

Creates a new Eclipse project and places it in the workspace you choose. Two options are available:

- A wizard can be used to create a new project and a new `.project` file is created by Eclipse.
- If the workspace already contains a `.project` file, that file is used to create the Eclipse project.

See [Creating an Eclipse Project in an Existing AccuRev Workspace](#).

Create a Single Eclipse Project in a New AccuRev Workspace

Creates a new Eclipse project and a new AccuRev workspace and places the project in the workspace. All files from in the AccuRev stream you specify are placed into the new workspace. Two options are available:

- A wizard can be used to create a new project and a new `.project` file is created by Eclipse.
- If a `.project` file is already within the stream, that file is used to create the Eclipse project.

See [Creating a Single Eclipse Project in a New AccuRev Workspace](#).

Create Multiple Eclipse Projects in New AccuRev Workspaces

Creates a new Eclipse project for each folder you select and places the files from each of them in new AccuRev workspaces. A new `.project` file is automatically created for each Eclipse project.

See [Creating Multiple Eclipse Projects in a New AccuRev Workspace](#).

Share an Eclipse Project with AccuRev

Creates an internal Eclipse association (mapping) of an Eclipse project to AccuRev.

See [Sharing an Eclipse Project with AccuRev](#).



Note: Associating an Eclipse project with AccuRev does not copy any data into your Eclipse project folder. The data is located in the AccuRev workspace, and simply becomes accessible through the Eclipse project.


Creating an Eclipse Project in an Existing AccuRev Workspace

Use this procedure to create an Eclipse project in an existing AccuRev workspace.

1. Click the **New** button  on the **Eclipse** toolbar.

 **Tip:** Or, you can select **File > New > Project** from the Eclipse main menu or select **File > Import** from the Eclipse main menu.

The **New Project** dialog box appears.




2. In the **Wizards** field, navigate to **AccuRev > Project from AccuRev**. (If you have many wizards, simply type **A** in the **Wizards** field to go directly to **AccuRev** in the list.)
3. Click **Next**.

 **Note:** If you are not already logged in to AccuRev, you are prompted to do so. See [Logging In to AccuRev](#).

The **Checkout from AccuRev** page appears.

4. Select a server where your AccuRev files are stored if the correct server is not already displayed in the **Select a server** field. If you need to add a server, see [Adding an AccuRev Server](#).
5. Expand the **Workspaces** folder.



6. Select the AccuRev workspace where you want the new Eclipse project to be placed.

7. Click **Next**. The **Check Out As** dialog box appears and displays two checkout options:

Check out as a project configured using the New Project Wizard


This option allows you to create a new Eclipse project file using the New Project Wizard. Eclipse creates a new .project file.

Check out in the workspace as projects

This option allows you to use an existing .project file to create the new project. This option is selected by default if a .project file is detected in the workspace you selected in the previous step.



Note: The .project file must have an AccuRev status of (kept) in order to be detected.



8. Select the project checkout option you want to use.

9. Complete the **Project Name** field or leave it as displayed:


- If you selected the **Check out as a project configured using the New Project Wizard** option, the AccuRev workspace name is used as the default **Project Name**. You can change this name or leave the default.
- If you selected the **Check out in the workspace as projects** option, the **Project Name** is taken from the existing .project file. This name cannot be changed and the **Project Name** field is disabled. For more information, see *How New Eclipse Project Names are Taken from Existing .project Files*



Note: The **Project Location** field displays the workspace path you selected.

10. Click **Finish** or **Next** as appropriate:

- If you selected the **Check out in the workspace as projects** option, the **Finish** button is active. Click **Finish**. A `Creating Eclipse Projects` message appears and you are done. A new project is created.
- If you selected the **Check out as a project configured using the New Project Wizard** option in Step 8, the **Next** button is active. Click **Next**. The **New Eclipse Project Type Selection** page appears.



a) Expand the project category you want to create, and then select a specific project type.

 **Note:** The list of project types varies based on the Eclipse plug-ins you have installed.

b) Click **Next**.

The first page of the configuration wizard for the project type you selected appears.

 **Note:** The wizard pages displayed from this point forward vary based on the project type you selected.

c) Complete the remaining wizard pages for the project type and click Finish. A new project is created.

How New Eclipse Project Names are Taken from Existing .project Files

Existing `.project` files contain project names in the `<name>` tag within the file. If you use an existing `.project` file to create a new project, the name of the new Eclipse project is taken from the `<name>` line in the `.project` file as shown in the following illustration.

Creating a Single Eclipse Project in a New AccuRev Workspace


Use this procedure to create a new project and place all the files from an AccuRev stream into a new AccuRev workspace.

1. Click the **New** button  on the **Eclipse** toolbar.

 **Tip:** Or, you can select **File > New > Project** from the Eclipse main menu or select **File > Import** from the Eclipse main menu.

The **New Project** dialog box appears.

Working with Eclipse Projects | 19




2. In the **Wizards** field, navigate to **AccuRev > Project from AccuRev**. (If you have many wizards, simply type **A** in the **Wizards** field to go directly to **AccuRev** in the list.)
3. Click **Next**.

 **Note:** If you are not already logged in to AccuRev, you are prompted to do so. See [Logging In to AccuRev](#).


The **Checkout from AccuRev** page appears.

4. Select a server where your AccuRev files are stored if the correct server is not already displayed in the **Select a server field**. If you need to add a server, see [Adding an AccuRev Server](#).
5. Expand the **Streams** folder.



 **Tip:** Click tree view and then click F5 to refresh.

6. Navigate to the stream off of which you want the new AccuRev workspace to be located.
7. Select a stream.
8. Click **Next**. The **Create New Workspace** page appears.



9. In the **Workspace Name** field, enter a name for the new AccuRev workspace.

 **Note:** When the workspace is created in AccuRev, the suffix `_username` is appended to the workspace name that you enter in this field. For example, if your AccuRev username is `jsmith` and you enter `W1` as the workspace name, AccuRev creates the workspace name as `W1_jsmith`.

10. In the **Workspace Path** field, enter or browse to the path (containing no other workspaces) where the new workspace will be created.

 **Note:** The **Workspace Path** must be a unique location that contains no other workspaces, and AccuRev displays a message if it is not unique. There are several ways to try to make the **Workspace Path** unique:

- In the **Workspace Path** field, enter a unique name of a directory to be created. This new directory will be the location of the new workspace.
- Click the **Append workspace name to its location** box. In this way, a new directory will be created based on the workspace name. For example, if the **Workspace Path** you enter is `C:\Workspaces` and the **Workspace Name** you enter is `NEW_WS`, then a new directory will be

created named C:\Workspaces\NEW_WS. This new directory will be the location of a workspace named NEW_WS. (Make sure there is not already a workspace of that name already within the selected stream.)

- Create a unique directory to contain the workspace and browse to this in the **Workspace Path** field.

11. Optionally change the default values for settings for the new workspace: **Locking Options**, **Workspace Contents**, and **EOL** convention.



Note: If you choose either **Exclusive Locking** or **Anchor Required** locking options, you will need to perform an `Anchor` command on a file before editing it.

12. Select the **Workspace Contents** option based on which files from the stream are to be included in the workspace. The following options are available:

Populate workspace with everything from basis stream

This option places all the files from the basis stream in the workspace and does not provide any AccuRev *include rules*. Use this option if you want to include all files from the stream in the project. (This option may take a while if you have a very large stream.)

Populate workspace with selected projects only

This choice updates the workspace with only the files from the folders you selected. AccuRev *include rules* are used to find the files belonging to those folders only. The other files in the basis stream will be excluded. This is the default choice. Use this option if you only want to include only the files of the selected folders in your project.

13. Click **Next**. The **Check Out As** dialog box appears and displays two checkout options:

Check out as a project configured using the New Project Wizard


This option allows you to create a new Eclipse project file using the New Project Wizard. Eclipse creates a new .project file.

Check out in the workspace as projects

This option allows you to use an existing .project file to create the new project. This option is selected by default if a .project file is detected in the workspace you selected in the previous step.



Note: The .project file must have an AccuRev status of `(kept)` in order to be detected.



14. Select the project checkout option you want to use.

15. Complete the **Project Name** field or leave it as displayed:


- If you selected the **Check out as a project configured using the New Project Wizard** option, the AccuRev workspace name is used as the default **Project Name**. You can change this name or leave the default.
- If you selected the **Check out in the workspace as projects** option, the **Project Name** is taken from the existing .project file. This name cannot be changed and the **Project Name** field is disabled. For more information, see *How New Eclipse Project Names are Taken from Existing .project Files*



Note: The **Project Location** field displays the workspace path you selected.

16. Click **Finish** or **Next** as appropriate:

- If you selected the **Check out in the workspace as projects** option, the **Finish** button is active. Click **Finish**. A `Creating Eclipse Projects` message appears and you are done. A new project is created.
- If you selected the **Check out as a project configured using the New Project Wizard** option in Step 8, the **Next** button is active. Click **Next**. The **New Eclipse Project Type Selection** page appears.



- a) Expand the project category you want to create, and then select a specific project type.



Note: The list of project types varies based on the Eclipse plug-ins you have installed.

- b) Click **Next**.

The first page of the configuration wizard for the project type you selected appears.



Note: The wizard pages displayed from this point forward vary based on the project type you selected.


- c) Complete the remaining wizard pages for the project type and click Finish. A new project is created.

Creating Multiple Eclipse Projects in a New AccuRev Workspace

1. Click the **New** button  on the **Eclipse** toolbar.

 **Tip:** Or, you can select **File > New > Project** from the Eclipse main menu or select **File > Import** from the Eclipse main menu.

The **New Project** dialog box appears.




2. In the **Wizards** field, navigate to **AccuRev > Project from AccuRev**. (If you have many wizards, simply type **A** in the **Wizards** field to go directly to **AccuRev** in the list.)
3. Click **Next**.

 **Note:** If you are not already logged in to AccuRev, you are prompted to do so. See [Logging In to AccuRev](#).


The **Checkout from AccuRev** page appears.

4. Select a server where your AccuRev files are stored if the correct server is not already displayed in the **Select a server field**. If you need to add a server, see [Adding an AccuRev Server](#).
5. Expand the **Streams** folder.



 **Tip:** Click tree view and then click F5 to refresh.

6. Expand the stream where you want the new AccuRev workspaces to be created.
7. Select one or more folders within the stream. To select multiple folders, hold down the `Ctrl` key or `Shift` key and then click the relevant folders.
8. Click **Next**. The **Create New Workspace** page appears.



9. In the **Workspace Path** field, click the **Browse** button and select an existing directory. A new directory is created based on the **Workspace Name** and **Workspace Path** you enter. For example, if you specify `c:\workspaces` as the workspace path, `w1` as the workspace name, and your username is `jsmith`, AccuRev creates the directory `c:\workspaces\w1` and this directory contains the workspace named `w1_jsmith`.
 10. Optionally change the default values for settings for the new workspace: **Locking Options**, **Workspace Contents**, and **EOL** convention.
-  **Note:** If you choose either **Exclusive Locking** or **Anchor Required** locking options, you will need to perform an `Anchor` command on a file before editing it.
11. Select the **Workspace Contents** option based on which files from the stream are to be included in the workspace. The following options are available:

Populate workspace with	This option places all the files from the basis stream in the workspace and does not provide any AccuRev <i>include rules</i> . Use this option if you want to include all
--------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

everything from basis stream

files from the stream in the project. (This option may take a while if you have a very large stream.)

Populate workspace with selected projects only

This choice updates the workspace with only the files from the folders you selected. AccuRev *include rules* are used to find the files belonging to those folders only. The other files in the basis stream will be excluded. This is the default choice. Use this option if you only want to include only the files of the selected folders in your project.

12. Click **Next**. The **Check Out As** page appears. This page allows you to name the new Eclipse projects you are creating based on the names of the folders you selected. This page appears only if you selected more than one folder.

13. Optionally enter a prefix and a suffix to attach to the name of each folder. For example, if the prefix is AA and the suffix is BB, a folder named `Folder_1` will result in an Eclipse project named `AAFolder_1BB`.




Note: You can also leave the prefix and/or suffix fields empty.

14. Click **Next**.

15. The **Checkout Projects** page appears. A new project is listed for each folder you selected.

The new projects in the list have project names and project types as follows:

- If no `.project` file is detected in the folder, the project name is based on the prefix and suffix you provided. The new project has the project type of **Eclipse Project**.
- If a `.project` file is detected in the folder, the project name is taken from the `<name>` tag within the `.project` file and the **Project Type** is `Defined Type`. See [How New Eclipse Project Names are Taken from Existing .project Files](#).



16. De-select any project that you do not want to create.

17. Click **Finish**. An Eclipse project is created for each Eclipse project you selected.

Sharing an Eclipse Project with AccuRev

Sharing is the process of placing files associated with an Eclipse project under AccuRev control. You might want to share a project with AccuRev to use the configuration management capabilities of AccuRev for a project that already exists in Eclipse.



Note: Project sharing functionality is available for Eclipse 3.4 and later.

How Shared Eclipse Project Files Populate AccuRev Workspaces

The Sharing process places files from Eclipse projects in an AccuRev workspace in a way that is consistent with how the AccuRev workspace was initially created.


If your Eclipse project is not located within an AccuRev workspace prior to sharing, then a workspace is created for you during the Sharing process and you choose which files you want to place in the workspace. The new workspace is initially populated with only the files you select. Note that the basis stream of the workspace might include other files and an AccuRev `Update` command will populate the new workspace with all the files from the basis stream.

If your Eclipse project is already located within a AccuRev workspace, then the Sharing process depends on how the AccuRev workspace was initially created:


- If your Eclipse project is located within an AccuRev workspace that was created with the **InitialContents – Same as Basis Stream** option, then all the files from the Eclipse project are promoted to the workspace's basis stream during the Sharing process.
- If your Eclipse project is located within an AccuRev workspace that was created with the **Initial Contents – Pick and choose from Basis stream** option, then you choose the files from the Eclipse project that you want to promote to the basis stream of the workspace.

How to Share a Eclipse Project with AccuRev

1. In the **Eclipse Navigator** or **Project Explorer** view, right-click the project you want to share and select **Team > Share Project**. The **Share Project** dialog box appears.




2. Select `AccuRev` and click **Next**. The **Share Project with AccuRev** page appears.




3. Select the AccuRev stream in which you want to create the new workspace for your Eclipse project.

 **Note:** This stream should not contain any files that have the same filenames as files within the Eclipse project that you are sharing.

4. Click **Next**. The **Create New Workspace** page appears.




5. Optionally, change the default values for locking options and end-of-line (EOL) convention for the new workspace. If you choose either **Exclusive Locking** or **Anchor Required** locking options, you will need to perform an *Anchor* command on a file before editing it. See *Anchor* for more information.
6. Click **Finish**. The workspace is created and the **Keep** dialog box appears. This dialog box allows you to add the files in the shared project into the AccuRev depot.



7. Enter a comment or select a comment from the **Choose a previously entered comment** field. Click **OK**.

The **External Elements to Add** dialog box appears with all elements selected.



8. Click **OK**.


Adding an AccuRev Server

In the AccuRev Plug-In for Eclipse, you are asked to select the AccuRev Server where your AccuRev files are stored. If your AccuRev Server does not appear as a choice, you can add the server using this procedure.

1. Click the **New** button  on the **Eclipse** toolbar.

 **Tip:** Or, you can select **File > New > Project** from the Eclipse main menu or select **File > Import** from the Eclipse main menu.

The **New Project** dialog box appears.




2. In the **Wizards** field, navigate to **AccuRev > Project from AccuRev**. (If you have many wizards, simply type **A** in the **Wizards** field to go directly to **AccuRev** in the list.)
3. Click **Next**.


 **Note:** If you are not already logged in to AccuRev, you are prompted to do so. See [Logging In to AccuRev](#).

The **Checkout from AccuRev** page appears.


4. Click the **Add Server** button to add a server to the list of servers.



The **Available AccuRev Servers** dialog box appears.



5. Click the **Add Server** button. The **New Server** dialog box appears.



6. Complete the **Address** and **Port** fields and click **OK**. The new server is added to the list of servers.

Advanced Techniques for Using AccuRev Data

If you want to work with several distinct subtrees of an existing workspace, you must create a separate Eclipse project for each subtree. When performing AccuRev commands that search through all the files in a project, you can choose to include all such “sibling” projects in a single search. See *Searching an Entire AccuRev Workspace* in [AccuRev Search/Status View](#).

There is an alternative to creating several projects for several workspace subtrees: use AccuRev's include/exclude facility to configure the AccuRev workspace with just the files you want. Then, create an Eclipse project using the entire workspace.

Specifying UTF-8 Encoding

You can specify character encoding for the following objects in Eclipse:

- Files** You can specify the character encoding for individual files or for all files of a given content type.
- Projects** Specifying character encoding for a project sets the default for all new files created in that project. You can set character encoding for projects individually, or for all projects created in an Eclipse workspace.
- Workspaces** Specifying character encoding for a workspace sets the default for all new projects created in that workspace.

The remaining sections summarize the procedures you can use to specify UTF-8 character encoding in Eclipse. Refer to your Eclipse user documentation for additional information.

Setting Encoding for a File

To set the character encoding for an individual file:

1. In the **Package Explorer**, right-click the file whose encoding you want to set and then choose **Properties** from the shortcut menu.
2. On the **Resource** page, in the **Text file encoding** group, select **Other** and then choose UTF-8 from the list.

3. Click **OK** to save the settings and close the Properties dialog box.

 **Tip:** You can also set the character encoding based on a file's content type. See [Other Preferences for Specifying Character Encoding](#) for more information.

Setting Encoding for a Project

Setting the character encoding for a project sets the encoding for any new files created in that project.

To set the character encoding for a project:

1. In the **Package Explorer**, right-click the project whose encoding you want to set and then choose **Properties** from the shortcut menu.
2. On the **Resource** page, in the **Text file encoding** group, select **Other** and then choose UTF-8 from the list.
3. Click **OK** to save the settings and close the Properties dialog box.

Setting Encoding for a Workspace

Setting character encoding for a workspace sets the default for all new projects created in that workspace.


To set character encoding for a workspace:

1. From the main menu, select **Window > Preferences**. The **Preferences** dialog box appears.
2. Navigate **General > Workspace** to display the **Workspace** page.
3. In the **Text file encoding** group, select **Other** and then choose UTF-8 from the list.
4. Click **OK** to save the settings and close the Properties dialog box.

Other Preferences for Specifying Character Encoding

In addition to using Eclipse preferences to set character encoding for workspaces, you can also use preferences to set character encoding based on content types, and for files associated with other Eclipse plug-ins you have installed (plug-ins for Web and XML application development, for example).

To locate all the places where you can specify preferences for character encoding, type “encoding” in the **Preference** dialog box **Filter** field. As you type, titles of the preference pages containing “encoding” are displayed in the **Preferences** dialog box left pane:




Navigate the preference pages for the plug-ins you have installed and review, and optionally set character encoding on those pages.

For example, to set character encoding based on a file's content type:

1. From the main menu, select **Window > Preferences**. The **Preferences** dialog box appears.
2. Navigate **General > Content TypesGeneral** to display the **Content Types** page.
3. Scroll through the Content types field, review the corresponding file associations, and set the value in the Default encoding field as needed.
4. Click the **OK** button to save the settings and close the **Preferences** dialog box.

Working in the Eclipse Navigator View

The **Navigator** view shows all your Eclipse projects, both projects associated with AccuRev and others. You access each project's files and directories (folders) using a familiar tree control.



 **Note:** For an Eclipse project consisting of AccuRev version-controlled files and directories, the **Package Explorer** view is equivalent to the **Navigator** view. In the rest of this document, descriptions relating to the **Navigator** view apply equally to the **Package Explorer** view.

Integrated Commands

The following AccuRev commands are integrated into the main context menu in Eclipse's **Navigator** view when you install AccuRev Plug-In for Eclipse:

- [Refactor](#)
- [Compare With](#)
- [Replace With](#)

To display the context menu, right-click a file or directory in the **Navigator** view.

Refactor

Eclipse supports two types of refactoring operations:

- Moving an object to a different directory.
- Renaming an object.

When you complete either of these operations, the `Rename` command is invoked to record the change of pathname in the repository. The results are displayed in the *AccuRev Console View*.

 **Note:** The Eclipse `Delete` command removes an object from local disk storage, but does not perform any AccuRev command. (In particular, it does not perform a `Defunct` command). If you `Delete` a version-controlled element, its status becomes `(missing)`.

 **Note:** Do not use the `Move` or `Rename` commands when you are not logged in to an AccuRev Server. Doing so causes changes to the Eclipse workspace but not to the AccuRev workspace. Visual cues indicate that you are not logged in to the AccuRev Server, including a greyed-out repository

decoration on the root of the **Package Explorer** tree  and missing decorations on files and directories. See [Setting Label Decorations](#) for more information.

Move

Eclipse supports moving an object to a different directory, using either of these methods:

- Right-click the object and select **Refactor > Move** from the context menu.
- Drag-and-drop the object from one directory to another.

 **Note:** Do not use the `Move` command to move an object from one Eclipse project to a project that is part of a different AccuRev workspace. The object will be moved, but the AccuRev `Rename` command will not be invoked. The object will have `(missing)` status in the source location and `(external)` status in the destination location.

Compare With

Eclipse supports commands to compare your version of a file with prior *local history* versions of that file. AccuRev Plug-In for Eclipse adds the following commands which perform comparisons with versions that were created with `Keep` and stored in the AccuRev repository:

Most Recent Version

Same as in the **Team > Diff Against** menu. See [Diff Against](#).

Backed Version

Same as in the **Team > Diff Against** menu. See [Diff Against](#).

File On Disk

Same as in the **Team > Diff Against** menu. See [Diff Against](#).


Basis Version

Same as in the **Team > Diff Against** menu. See [Diff Against](#).

AccuRev Revision

Compares the file in the AccuRev workspace with the version created by a particular AccuRev transaction. A **File History** tab appears, containing a table of transactions involving the file. (This is the same as the upper table in the AccuRev **History** display. See [History View](#).)

Double-click a transaction to choose it for the comparison. This launches Eclipse's **Compare Editor**.



See the Eclipse help system for more information on the *Compare Editor*, in particular the topics *Compare Editor* and *Understanding the Comparison*.

Replace With

Eclipse supports commands to replace your version of a file with a prior *local history* version. AccuRev Plug-In for Eclipse adds the following commands which replace a file with a version that was created with *Keep* and stored in the AccuRev repository:

Most Recent Version

Same as in the **Team > Revert To >** menu. See [Revert To](#).


Backed Version

Same as in the **Team > Revert To >** menu. See [Revert To](#).

AccuRev Revision

Replaces the file in the AccuRev workspace with the version created by a particular AccuRev transaction. As with the **Compare With > AccuRev Revision** command, a **File History** tab appears containing a list of transactions involving the file.

Double-click a transaction to choose it for the comparison. This launches Eclipse's **Compare Editor**.



To proceed with the replacement operation, click the **Replace** button below the **Compare Editor**. To cancel the operation, just close the **File History** tab.

Team Menu Commands

The AccuRev commands in this section are integrated into the **Team** context menu in Eclipse's **Navigator** or **Package Explorer** views.

To display the **Team** menu, right-click a file or directory in the **Navigator** view.

Synchronize with AccuRev Repository

Performs an Eclipse *synchronize with the repository* operation on the current selection, which can include anything from multiple Eclipse projects to a single file. Synchronization results are displayed in the Synchronize view.

 **Note:** If you run this command on a single file, a simple file comparison is performed and the **Synchronize** view is not involved.

For each object, the synchronize operation determines the differences between the version in your project. Meaning, it includes the AccuRev workspace and the version in the backing stream. In the **Synchronize** view, you can run commands to resolve the differences: you can *promote* changes from your project to the repository and *update* changes from the repository to your project.

For details, see *Synchronize View*.

Login

You must be logged in to AccuRev in order to perform any AccuRev operation on a repository file or AccuRev workspace.

If the login is invalid or the session expires, then no AccuRev operation can be performed on the open Eclipse project files.

See [Logging In to AccuRev](#).



If AccuRev is configured to use the `accurev_login` user-authentication scheme, you must log in before performing any AccuRev operation on a file in an AccuRev workspace. If the login is invalid or fails, then no AccuRev operation can be performed.

Logout

The `Logout` command logs the current user out of AccuRev. While logged out, AccuRev commands are not available, and the AccuRev Server is not contacted. The icon on the project folder is greyed out, and label decorations are not shown for files in the workspace. Files in workspaces are still available, and their contents can be modified freely. Performing a [Synchronize with AccuRev Repository](#) operation after logging back in is recommended.

Add to AccuRev Depot

Converts the selected files in the project into AccuRev version-controlled elements. The directory containing the files is also converted to an element, if necessary.

You can undo the effect of this command with the **Revert to > Backed Version** command. This removes the selected files from the IDE project, if you have not yet Promoted them.




Note: It is not necessary to place the IDE project files (`.iws`, `.ipr` and `.iml`) under version control.

Keep

The `Keep` command saves the changes you have made to one or more files as `private` versions in the AccuRev repository. These versions are visible only in your workspace, not in the “public” backing stream or in other users' workspaces.

The `Keep` command is also available for directories. Performing this command on a directory recursively searches it for files with `(modified)` and `(external)` status to keep.

A dialog box appears, in which you can enter a comment string to be stored as part of the Keep transaction. The dialog makes it easy to reuse comment strings that you previously specified.



Advanced Keep Options

You can use advanced options when keeping files. Click the **Advanced** button ON the **Keep** dialog box to display these choices:

Choose File Type By default, AccuRev determines the element type for the newly created version automatically (`text` or `binary`). You can override the default by specifying either of these types or `p_text` (a variant of `text`).

Choose Lock Type Choosing **Enable File Locking** places a lock on the element to enforce serial development in sibling workspaces for that element. This ensures that users in sibling workspaces will not have to merge their work on this element. The lock remains on the element until you (or someone else) changes this value to **Disable File Locking** in a subsequent `Keep` command.

See [Keep: Preserving Changes in Your Private Workspace](#) and your AccuRev user documentation for more information.

Do not confuse the versions of a file created by `Keep` with the “local history” copies of the file created when you close the editor when you invoke **File > Save** in an **Editor** pane. Local history copies are maintained by Eclipse itself in the local file system. Versions created with `Keep` are saved permanently in the AccuRev repository.

Anchor

Many version control systems force you to perform a `check out` command that makes a file writable so that you can edit it. The AccuRev default is that your files are always writable.

The AccuRev `Anchor` is similar to a typical checkout. However, anchoring a file does not change whether it is writable. Rather, it *activates* the file in your workspace by adding them to the workspace's default group, so that it will be found by the **AccuRev Searches > Default Group** search.

One effect of anchoring a file is that it ensures that the file is not overwritten by an **Update AccuRev Workspace** command. Under normal circumstances, you rarely need to invoke the `Anchor` command.

If the AccuRev workspace uses the AccuRev “exclusive file locking” or “anchor-required” feature, files are initially read-only. Before editing a file, you must `Anchor` it, making it writable.

Promote

The `Promote` command converts private versions into public versions. It takes versions that you previously created in your workspace with `Keep` and sends them to the backing stream. If you have modified a file, this command first performs a `Keep` and then promotes the kept file.

See also [Promote: Making Your Private Changes Public](#).

Implicit Keep and Promote

If you execute a `Promote` command on files which have changed since they were last preserved in the repository with `Keep`, meaning they have `(modified)` status, the AccuRev Plug-In for IntelliJ IDEA runs a sequence of AccuRev commands on the selected files:


1. Performs a `Keep` on all the files in the selection with `(modified)` status.
2. Performs a `Promote` on all the files in the selection that now have `(kept)` status.

Promote and Issue Management Systems


Running the `Promote` command can activate either or both of the integrations between AccuRev's configuration management functionality and its issue management (AccuWork) functionality. The former uses change packages as the point of integration. AccuWork uses a particular issue-record field as the point of integration. Both of them record information about the `Promote` transaction in a user-specified AccuWork issue record. For more information, see [Promote-Based Integrations with Issue Management](#).

Recursive Promote

You can select individual files or folders for the `Promote` command. If you have selected a folder for the `Promote` command, you can choose to perform a recursive promote: the current folder and all subfolders for pending and external elements.



As shown in the following, the **Promote** dialog box displays all pending elements and external elements:



Pending elements are selected by default, but you need to choose any external elements you want to promote.

Merge

The `Merge` command merges your version of the file with the version in the backing stream. This command is the equivalent of `Resolve` in other source code management terminologies.

It is enabled only when a file's status is `(overlap)`. For text files, AccuRev uses the merge tool you have configured. This can be AccuRev's own merge tool, the Eclipse tool, or a third-party tool that you specify. See *Using Alternative Diff and Merge Tools* for more information.

If the element type is `binary`, you can elect to `Keep` your version or the backed version. AccuRev does not support merging binary files.

The `Merge` command can be run, perhaps multiple times, when you run the `Commit All Outgoing Changes` and the `Update All Incoming Changes` commands in the **Synchronize** view.

If the element type is `text`, executing `Merge` brings up a merge tool. By default, the merging of text-file contents is performed by AccuRev's own `Merge` tool, which uses a three-way merge algorithm.

A successful `Merge` ends with a `Keep` command, creating a new version of a file in your workspace.



Note: AccuRev uses a separate executable to perform `Merge` operations. Check that your environment variables and system path are correctly defined so this executable is available to the Integration.

See also [Merge: When Changes Would Collide](#).

Version Browser

Shows the ancestry for each element you select in the **Version Browser**. It displays the current version of the selected element, the real ancestors of that version, and the virtual versions that have one of those ancestors as a parent. By default, data for 20 transactions is shown in the list of filters on the **Version Browser** toolbar.

The **Version Browser timeline** shows when each transaction took place, as well as the number and user associated with the transaction. Note that the **timeline** proceeds left-to-right, therefore, the most recent versions will be visible on the right side of the **Version Browser**.

Year	Month	Day	Time	Transaction ID	User
2009	Sep	Tue, 01	09:54:07	1291	brad
2009	Sep	Tue, 01	10:02:32	1299	brad
2009	Sep	Tue, 01	10:02:38	1300	brad
2009	Sep	Tue, 01	11:36:53	1304	brad
2009	Sep	Tue, 01	11:37:16	1306	brad
2009	Sep	Tue, 01	11:37:56	1308	brad
2009	Sep	Tue, 01	15:20:37	1319	brad
2009	Oct	Fri, 02	16:34:49	1383	brad

Note: Available only if AccuRev Plug-In for Eclipse has been configured to provide access to the AccuRev Web UI. See the *AccuRev Plug-In for Eclipse Installation and Release Notes* for more information on this process. See the *AccuRev Web UI User's Guide* for more information on the **Version Browser**.

Note: Available only if the AccuRev Plug-In for IntelliJ IDEA has been configured to provide access to the AccuRev Web UI.

Annotate

Shows the contents of the selected version of a text file, annotating each line with:

- The timestamp of the version in which that line was added to the file.
- The number of the transaction in which that version was created.
- The user who performed that transaction.
- A line number

You can use the annotations to explore how the file has changed over time. When you click on an item in the **Date**, **#**, or **User** columns, all the lines whose value in that column matches the value of the item you clicked are highlighted. This makes it easy to:

- Find all the lines added or changed in a particular version (click in the **Date** or **#** column).
- Find all the lines created by a particular user (click in the **User** column).

A **timeline** is shown above the file contents. Each transaction involving the annotated file is represented on the **timeline**. Click a transaction to show the file as of that transaction. The lines of the file that have been added or changed by that transaction are highlighted.

Date	#	User	Line	Content
2007-03-11 22:41:34	488	brad	1	//
2007-03-11 22:43:59	490	brad	2	//
2007-03-11 22:45:05	492	brad	3	//
2007-02-08 16:01:54	357	brad	4	main()
2007-02-21 14:32:24	371	brad	5	// my changes
2007-02-21 14:32:24	371	brad	6	{
2007-03-21 14:09:18	668	brad	7	printf("hello there world, how are you doing?\n");
2007-03-21 19:06:27	673	brad	8	call_some_function();
2007-02-21 14:32:24	371	brad	9	}

Note: Available only if AccuRev Plug-In for Eclipse has been configured to provide access to the AccuRev Web UI. See the *AccuRev Plug-In for Eclipse Installation and Release Notes* for more information on this process. See the *AccuRev Web UI User's Guide* for more information on the **Version Browser**.

Note: Available only if the AccuRev Plug-In for IntelliJ IDEA has been configured to provide access to the AccuRev Web UI.

Populate

Restores a file with (missing) status to your project. To locate such files, use the *AccuRev Search/Status View*.

The `Populate` command copies the version currently in the workspace stream (in the AccuRev repository) to the workspace. For more information, see *What's the Difference between Populate and Update?* in the *AccuRev Technical Notes*.

Running the `Populate` command displays a dialog box with two options:

Recursive For each item in the list that is a directory, perform a `Populate` command on that element and on all elements below it.

Overwrite For each item in the list that is a file, replace the file (if any) currently in your workspace. If this checkbox is not selected, no files will be overwritten.

Click **OK** to proceed with populating files.

Defunct

Deletes a file from your disk, and also marks it as having `(defunct)` status in the AccuRev workspace. A comment dialog enables you to enter comments for the defuncted element. Defuncted files are not displayed in the **Navigator** view because it only displays files that are on your disk. However, defuncted files are displayed in certain AccuRev Searches: `Defunct`, `Pending`, and `Default Group`. Defuncted files disappear entirely from the AccuRev workspace when you `Promote` them to the backing stream.

Other users will continue to see the file in their workspaces. When you `Promote` a defunct element to the backing stream, it disappears entirely from the workspace stream, and from the **File Browser** display. The element then becomes `(defunct)`, hence also active, in the backing stream.

You can also `Defunct` a directory. But before doing so, consult the description of the `Defunct` command in the *AccuRev Command Line Interface User's Guide*.

 **Note:** The Eclipse `Delete` command does not invoke the AccuRev `Defunct` command. It simply removes the file from local disk storage. No change is made to the AccuRev repository. If you invoke the Eclipse `Delete` command on an AccuRev-controlled file, its AccuRev status becomes `(missing)`.

 **Note:** The IDE's `Delete` command does not run AccuRev's `Defunct` command. See *Using the IDE's Delete Command*.

Revert To

The commands on the **Revert To** menu allow you to discard changes to a file in your workspace, replacing them with another version.

Revert to > Most Recent Version Replaces your file with the version in the workspace stream (in the AccuRev depot). Typically, the workspace stream contains the version you most recently created with `Keep`. Or it might contain the version you brought into your workspace with **Update AccuRev Workspace**.

 **Note:** This command does not discard namespace changes.

Revert to > Backed Version Replaces your file with the version that was in the backing stream at the time of your most recent **Update AccuRev Workspace**, or the last version you `Promoted`, whichever is more recent.

Diff Against

Most `Diff Against` commands allow you to compare a text file in your workspace with another version of the same file. AccuRev uses the diff tool you have configured, this can be AccuRev's own diff tool, the Eclipse tool, or a third-party tool that you specify. See [Using Alternative Diff and Merge Tools](#).

Compares your file with another version. Only text files can be compared.

Diff Against > Backed Version Compares your file with the version currently in the workspace's backing stream.

Diff Against > Most Recent Version Compares your file with the version in the workspace stream (in the AccuRev depot). Typically, the workspace stream contains the version you most recently created with `Keep`, so this command helps answer the question, "What have I changed since my last `Keep`?" The workspace stream might contain the version you brought into your workspace with **Update AccuRev Workspace**, or the version

you recently `Promoted`. In these cases, the command is equivalent to **Diff Against > Backed Version**.

Diff Against > Basis Version Compares your file with the version you most recently brought into your workspace with **Update AccuRev Workspace**. However, if you have `Promoted` the file since the update, the comparison is with your most recently promoted version.

Diff Against > File on Disk Allows you to compare a text file in your workspace with some other file (either on the hard disk, or available via a networked machine).

Ignore Options for AccuRev Diff

If you are using the AccuRev Diff tool, you can specify whether or not you want AccuRev to ignore one or more of the following:


- Whitespace (whitespace is ignored by default)
- Changes in whitespace
- Case

Ignore options for AccuRev Diff are specified on the **AccuRev** page of the Preferences dialog box. See *Setting AccuRev Preferences in Eclipse* for more information.

Copy as Link/Paste as Link

Allows you to create an element link or a symbolic link from a file. To create a link:

1. Right-click the file for which you want to create a link and choose **Team > Copy as Link** from the context menu.
2. Navigate to the project in which you want to create the link.
3. Right-click the appropriate project folder and choose **Team > Paste as Link** from the context menu. The **Paste Link** dialog box appears:



By default, the link object you are creating has the same name as the target object to which it refers.

4. Optionally, change the link name.
5. Select the **Symbolic link** field if you want to create a symbolic link. Otherwise, AccuRev Plug-In for Eclipse creates an element link.
6. Click **OK**.

Synchronize Time

The `Synchronize Time` command changes a client machine's system clock to match the clock on the AccuRev Server. Some commands are disabled if the client's time does not match the server's time within a preset tolerance.



Note: You must have `root` (on Linux/UNIX) or `Administrator` (on Microsoft Windows) privileges to change the system time.

AccuRev Workspace Information

The **AccuRev Workspace Information** command displays a message box containing information about the current AccuRev context: your user name, your AccuRev workspace name and location, and so on. It also indicates whether the integrations between AccuRev's configuration management and issue management capabilities are enabled.

Update AccuRev Workspace

Update AccuRev Workspace > Entire Workspace

Copies versions from your workspace's backing stream into your workspace. This has the effect of incorporating other people's changes, which they have promoted to the backing stream, into your workspace.

Update AccuRev Workspace > Preview

Shows which files have changed and would be copied to your workspace if you issue the **Update AccuRev Workspace > Entire Workspace** command.

AccuRev History

Displays a table in the **History view** listing the AccuRev transactions (*keep*, *promote*, and so on) involving the selected element. The previous contents of this view, if any, are discarded. See *History View*.

Displays the transactions for the selected file or directory element in the **Version Control** tool window. AccuRev tracks the complete history of each version-controlled element (file, directory, or link). This history consists of the set of transactions involving that element. Most changes to a depot are logged by transactions.

This command is disabled if multiple elements are selected.

The top pane of the **Version Control** tool window (**transactions pane**) shows the transactions that this element was part of. If you select a transaction, a list of all elements involved in that transaction appears in the bottom pane (**elements pane**). The comment for the selected transaction is displayed separately in a **comments pane** to the right of the elements pane.

Typically, most of an element's transactions are created by *Keep* and *Promote* commands, as shown in the **Action** column in the transactions pane. Transactions are also logged in several other situations, for example:

- When an element is first added to an AccuRev depot (*add*).
- When you rename it or move it to a different directory (*move*). This action occurs when you use the IDE to move or rename a file, for example in a refactoring operation.
- When you incorporate someone else's changes into your work (*merge*), and some others.

The toolbar at the top of the **Version Control** tool window contains navigation buttons to move among groups of transactions: first group, previous group, and next group, and a list that controls how many transactions are displayed at a time. Right click an item to perform actions.

AccuRev Statuses

Displays a table listing information about each element in the current selection:

- Element's **Location** within the depot.
- AccuRev **Status** (one or more indicators).
- **Version** ID of this version.
- **Element ID**.

The result table is displayed in the **AccuRev Search/Status** view.

Location	Status	Version	Element ID
\\.\test.txt	(backed)	myDepot\1	3

The previous contents of this view, if any, are discarded. See *AccuRev Search/Status View*.

Icon Decorations in the Project Tool

Each file or directory object displayed in the Project tool subwindow has an AccuRev-level status, expressed as a set of status indicators, for example, (kept) (member). The Project tool does not display these status indicators, but it does display corresponding icon decorations.

The status indicators are not mutually exclusive. For example, a file's status can include both the (modified) and (member) indicators. But the IDE uses only one decoration on each icon or each filename. The following precedence order of the AccuRev statuses determines which decoration appears:


-  (overlap/underlap) highest precedence
-  (stale)
-  (missing)
-  (modified)
-  (member)
-  (ignored)
-  (backed) lowest precedence

AccuRev Searches

Searches the current folder in the AccuRev workspace for elements that satisfy the selected search type.

 **Note:** The Stranded search searches the entire workspace.

To search the entire workspace, use the **Entire AccuRev Workspace** option available from the tab. See [AccuRev Search/Status View](#).



Searches your workspace for files whose AccuRev status matches the criterion you specify: `Pending`, `Modified`, and so on. The results appear in the **AccuRev Searches/Status** window, replacing the current contents (if any).


You can select one or more elements in this window and right-click to display the **AccuRev** context menu and perform any valid AccuRev command. This makes it easy to perform such operations as:

- Promoting elements that are pending promotion.
- Keeping and Promoting (`modified`) elements.
- Promoting elements in the workspace's default group.
- Placing (`external`) files under version control.

By default, a search is conducted through the entire workspace containing the IDE project. If the project occupies a subtree of the workspace, the search results might contain files that are not in the IDE project. Clear the **Entire Workspace** checkbox to restrict the search scope to the IDE project only.

Show Properties

Displays the **Properties** dialog box for the currently selected element.



Properties listed for the element include the: **PathName**, **Element Type**, **Element ID**, **Version**, and **Status**.

Refresh

Executes the AccuRev refresh operation, which updates the AccuRev status symbol for elements displayed in the **Navigator** view. You can perform the **Team > Refresh** operation for all projects or currently selected projects.

 **Tip:** Pressing F5 (or **File > Refresh**) also performs the `Refresh` operation if you have enabled this preference. See *General AccuRev Settings* for more information. The **Refresh** choice on the **Navigator** context menu, however, performs only the Eclipse refresh operation.

Makes a call to the AccuRev Server and refreshes the statuses of the selected files and directories. Two options are available.

Refresh > Selected Content Roots

Refreshes the selection and (if it includes a directory) the subdirectories.

Refresh > Project

Refreshes the status of all AccuRev-controlled elements in the project.

The AccuRev icon decorations of the selected items are refreshed, too. If you have version-controlled items that are modified by the IDE or an external process, this command can help you to detect such changes to those items.

Web UI

Displays the AccuRev Web UI, providing a convenient way to view information from the AccuRev repository.



Note: The `Web UI` command is available only if the plug-in has been configured to provide access to the AccuRev Web UI. See the *Plug-in Installation and Release Notes* for more information on this process.

Share/Unshare Project

(Eclipse 3.4 and later only)

Run `Share Project` to create an internal Eclipse association (mapping) of an Eclipse project to AccuRev.

Run `Unshare Project` to remove the selected projects from AccuRev's control. The selected projects will no longer be associated with AccuRev workspaces. All AccuRev decorations are removed from the files and folders in that project, and the **Team** menu no longer allows access to AccuRev commands.

Use the **Team > Share Project** command to restore the project to AccuRev control.

See [Sharing an Eclipse Project with AccuRev](#) for more information about sharing projects.

Create Patch/Apply Patch

`Create Patch` creates a portable Eclipse patch file based on one or more files in your AccuRev workspace. The `Create Patch` command filters files in your workspace, displaying only those that have been modified. A file under AccuRev control is considered modified if it has one of the following statuses:

```
(modified)
(modified)(member)
(overlap)(modified)
(overlap)(modified)(member)
(kept)(member)
```

Creating a Patch


To create a patch from modified files under AccuRev control:

1. In the **Eclipse Navigator** view (from the **Project Explorer**, for example), right-click the file you want to use to create a patch and choose **Team > Create Patch** from the context menu.



Tip: You can select multiple files.

The **Create Patch** dialog box appears.



2. Specify the full path of the location where you want to create the patch file. Optionally, specify a filename. If you do not specify a file name, the patch is created as `ac_patch.txt`.

 **Note:** One patch file is created, regardless of the number of files you choose.

3. Expand the `Eclipse` project folder.
4. Select the files from which you want to create a patch.
5. Click **Create**.

The patch file is created using the name and location you specified in Step 2.

Applying a Patch

You use the `Apply Patch` command to apply a patch created using the `Create Patch` command.

Refer to your Eclipse documentation for more information about applying patches.

AccuRev Web UI

 **Note:** The AccuRev Web UI is available only if AccuRev Plug-In for Eclipse has been configured to provide access to the AccuRev Web UI. See the *AccuRev Plug-In for Eclipse Installation and Release Notes* for more information on this process.

The AccuRev Web UI lets you access both AccuRev and AccuWork data. Note that the AccuRev Web UI only interacts with data from the AccuRev Server. Data from user workspaces that has not been kept or promoted is not accessible from the AccuRev Web UI.

Starting the AccuRev Web UI

To start the AccuRev Web UI:

1. Click the **Open Web UI** button on the Eclipse toolbar:



You can also click **Team > Web UI** from the **Navigator** view context menu. The **Login to AccuRev Server** dialog box appears.




2. Enter a user name and password.



Tip: Select **Remember my login on this computer** to create a session token. Once created, you will not have to log in to the AccuRev Server when launching the AccuRev Web UI in subsequent AccuRev Plug-In for Eclipse sessions.

3. Click **Ok**. The AccuRev Web UI appears on a new tab.



Getting Started with the Web UI

To get started in the AccuRev Web UI, choose an action from the toolbar to view or open streams or issues. The status bar at the bottom of the window displays information about the AccuRev Server and depot (if any) you are currently accessing.

For more information, see the *AccuRev Web UI Online Help*.

Web UI Toolbar

The toolbar at the top of the tab contains general commands:

StreamBrowser	Displays stream options that allow you search and filter streams based on various criteria, and display them in either tabular or graphical displays.
New Query	Displays the New Query tab.
Issue Queries	Displays the Query Browser .
New Issue	Creates a new AccuWork issue.
Issue Search	Opens an existing AccuWork issue (for searches by issue number) or list of issues (for full-text searches).
Refresh	Updates the information shown in the active tab to reflect recent AccuRev activity.
User	Displays the user's name. Clicking the down-arrow displays the Change Password dialog box.
Login	Displays the Login dialog box, allowing you to log in as a different user.
Logout	Logs out the current user.
Help	Displays the online help in a Web browser.

Toolbar Access to AccuRev Commands

To provide easy access to commonly-used features, several of the AccuRev commands are available from icons that appear on the Eclipse toolbar:



The icons from left to right are:

- Add to Depot
- Keep
- Anchor
- Promote
- Merge
- Revert to Backed
- Show History
- Version Browser*
- Annotate*
- Rename
- Delete
- Defunct
- Show Properties
- Synchronize
- Update
- Open Web UI*
- Open Stream Browser*
- Create New Issue*
- Open Issue Queries*

An asterisk (*) identifies a feature that is available only if you have configured access to the AccuRev Web UI.

Running Commands in the Background

Long-running commands, `AccuRev Searches`, `AccuRev History`, `Refresh`, `Populate`, `Diff Against`, and `Merge`, can be run in the background. When the command begins execution, a pop-up window appears.

Clicking **Run in Background** closes the window and places a “show progress” button in the lower right corner of the Eclipse window.

Clicking the “show progress” button opens a standard **Eclipse Progress** view, which provides information on all background commands. You can cancel a background command in the **Progress** view, by clicking its red button.

If you click **Details** in the window, the command continues to run in the foreground. A progress view, as described above, is added to the pop-up window.

Promote-Based Integrations with Issue Management


AccuRev defines two integrations between its configuration management functionality and its issue management (AccuWork) functionality:

- Change-package-level.
- Transaction-level.

The integrations are enabled separately, through AccuRev commands that are not available in AccuRev Plug-In for Eclipse. One or both of the integrations are triggered when you invoke a Promote command on a set of elements. You are prompted to specify an AccuWork issue record in a pop-up window.

If only the transaction-level integration is enabled and you do not have a default query defined for the issues database, the prompt window contains a text field into which you type an issue number (or several numbers, separated by SPACE characters).

Otherwise, the prompt window offers a set of existing issue records, from which you can select one or more. You can also enter an issue in the **Issue #** field. When a “**3pty ITS Key**” is set in the **AccuRev Schema editor**, that key is displayed instead of the issue number.



Once you select one or more issues to associate with your changes and click **OK**, AccuRev Plug-In for Eclipse displays a dialog box that allows you to enter an optional comment that documents the nature of the change or the reason for promoting your changes.

When you click **OK** to complete the Promote operation:

- The change-package-level integration (if enabled) records the promoted versions on the **Changes** tab of the specified issue record(s).
- The transaction-level integration (if enabled) records the `Promote` transaction number in the **affectedFiles** field of the specified issue record(s).



Note: If you use AccuRev to establish one of these integrations or to set a default query for the issues database while an Eclipse session is active, you might need to restart Eclipse to see the effect of this change.

For more information, see the section titled *Integrations Between AccuRev and AccuWork* in the *AccuRev Administrator's Guide*.

Working in the AccuRev Perspective


An Eclipse perspective defines a set of views (sub-windows) that can be displayed in the **Workbench** window. AccuRev Plug-In for Eclipse defines an AccuRev perspective, which includes these views:

- AccuRev Console View
- AccuRev Search/Status View
- History View
- Synchronize View

To open the **AccuRev** perspective, select **Window > Open Perspective > Other** from the Eclipse main menu. Select **AccuRev** in the **Open Perspective** dialog box and click **OK**.

AccuRev Console View

Many AccuRev commands generate informational messages. When you run these commands using AccuRev Plug-In for Eclipse, the messages are sent to the **AccuRev Console** view. This view automatically appears (if it is not already visible) whenever an AccuRev command produces a user message. You can also display the console view using the **Show View** dialog box (**Window > Show View > Other**). Choose **AccuRev Console** under the AccuRev node on the dialog.



Each time you invoke an AccuRev command through the **Team** context submenu, a notice is appended to the contents of the **AccuRev Console** view. For example:

```
---- AccuRev command started: Keep
---- AccuRev command finished: Keep
```

If the command produces output, it is sent to the console:


```
---- AccuRev command started: Promote
Validating elements.
Promoting elements.
Promoted element \. \dir03\sub02\file02.txt
---- AccuRev command finished: Promote
```

Some commands (for example, **Team >**) both write to the **AccuRev Console** view and write to another view in the AccuRev perspective (in this example, the **History** view).

The data displayed in the **AccuRev Console** view is discarded when you close the view. It is not discarded if you switch to another view.

AccuRev Search/Status View

When you perform an AccuRev search (for example, **Team > AccuRev Searches > Modified**), the results are shown in a table in the **AccuRev Search/Status** view. By default, the results of all searches except the Stranded search display only the elements from the selected files and/or directories. (The Stranded search displays (stranded) elements from the entire workspace.)



	Location	Status	Version	Element ID
	\\.src\bigbrass.c	(modified)(member)	brass_mnt_john\4	9
	\\.src\bigbrass.h	(modified)(member)	brass_mnt_john\3	10

Each object is listed by its pathname relative to the AccuRev workspace's top-level directory. This is called a depot-relative pathname in AccuRev, and it always begins with `./` (UNIX/Linux) or `\\.` (Microsoft Windows).

Working with the Results Table

The table in the **AccuRev Search/Status** view works in the usual way:

- Resize a column by dragging its right-hand column separator.
- Resize a column to accommodate the longest value by double-clicking its right-hand column separator.
- Sort column data by clicking on a column header to sort the rows on that column's values. A second click reverses the sort order.

The **AccuRev Search/Status** view is pinned by default, meaning that results for every search are displayed in a new instance of the view. The data displayed in the view is discarded when you close or unpin the view.

Running Commands on Objects Displayed in the Results Table

You can run AccuRev commands on the objects displayed in the **AccuRev Search/Status** view. The context menu, including the **Team** submenu, provides access to the same AccuRev commands as in the **Navigator** view. This makes it easy to perform such operations as:

- Promoting some or all of the elements that are pending promotion.
- Placing under version control some or all of the workspace's external files.

You may prefer to use Eclipse's native `synchronize with the repository` interface to perform such operations. See [Synchronize View](#).

Searching an Entire AccuRev Workspace

An Eclipse project can include just part of an AccuRev workspace, called a sub-tree. You might create multiple such sub-tree projects that, as a group, span the entire AccuRev workspace. On the other hand, you might choose to omit some portions of the AccuRev workspace from the group of Eclipse projects.

To return elements that meet the search criterion throughout the entire AccuRev workspace, select **Entire AccuRev Workspace** from the list near the minimize and maximize controls.

Use the drop-down menu to toggle the **Entire AccuRev Workspace** setting. This setting persists as long as the **AccuRev Search/Status** view remains open.

Example: Suppose you have loaded just a workspace's `src` directory, not the `doc` or `tools` directory, into an Eclipse project. Running the command **Team > AccuRev Searches > Pending** displays the elements

in the Eclipse project (that is, in the `src` directory) that are pending promotion. Then, turning on the **Entire AccuRev Workspace** setting expands the display to include all pending-promotion elements in the AccuRev workspace, including those that are not loaded into the Eclipse project.

History View

The **History** view displays a table containing some or all of the AccuRev transactions involving a selected element.

When you select a transaction in the upper table, the lower table is populated with data on all the elements involved in that transaction. The data for each element includes its pathname within the depot, the AccuRev version identifiers of the version this transaction created, identifiers of the versions from which this version was derived, and any associated AccuWork issue record numbers.

controls inherited from CVS History view

load groups of transactions

restrict to transactions created by a specified user

restrict to transactions created in a specified interval

#	Action	Time	Virtual Version	User	Comment
196	keep	2008-08-20 14:18:02	plop37_dvt_mary...	mary	mary: PATCH01/01
195	promote	2008-08-20 14:17:54	plop37_dvt/16	john	
194	keep	2008-08-20 14:17:22	plop37_dvt_john/31	john	minor typos
193	promote	2008-08-20 14:15:11	plop37_dvt/15	john	
192	keep	2008-08-20 14:15:08	plop37_dvt_john/30	john	john: PATCH02/02

Element Path	Vir Ver	Real Ver	Ancestor	Merge	minor typos
.\dir02\sub03\file04.txt	plop37_dvt_jo...	plop37_dvt_john...	plop37_dvt_joh...		
.\dir02\sub01\file03.txt	plop37_dvt_jo...	plop37_dvt_john/2	plop37_dvt_john/1		
.\dir01\sub00\file03.txt	plop37_dvt_jo...	plop37_dvt_john/2	plop37_dvt_john/1		
.\dir00\sub00\file00.txt	plop37_dvt_jo...	plop37_dvt_john...	plop37_dvt_john/9		

AccuRev transactions for element

all elements involved in selected transaction

comment in selected transaction

You can manipulate the table in the usual way see *Working with the Results Table* in [AccuRev Search/Status View](#). This view is a variant of the **CVS History View**, and so inherits some of its controls:

Refresh

Pin this history view

Link with Editor and Selection

Show element history

Refresh

Checks for new transactions and displays them.

Link with Editor and Selection

A toggle switch. When linking is enabled, selecting an element in the **Package Explorer/Navigator** or switching to an element's **Editor** tab automatically displays the

element's history. Up to 15 of these histories are cached in the **History view**. You can redisplay a cached element history with the **Show element history** toolbar button.

Pin this history view Ensures that the currently displayed element history does not get overlaid. Invoking the **AccuRev History** command again creates a new instance of the History view.

 **Note:** When the **Link toggle** is enabled, the **Pin toggle** is automatically disabled, and vice-versa.

Show element history Displays the next element history in the cache enabled by the **Link with Editor and Selection** toggle, or opens a drop-down menu with all the cache entries.

The element history displayed in an **AccuRev History** view is discarded when you close the view. So is any element history cache you have accumulated. This data is also discarded if you invoke another command when the **Pin** toggle is off.

Navigating in the Transaction Table

If an element has many transactions, you can use the toolbar controls at the top of the tab to assist in navigating among them.


Initially, the most recent set of transactions is loaded into the table. Use the list to control how many transactions are included in the set.

To load a set beginning with a particular transaction into the table, type the transaction number into the input box, and click the right-arrow button.

To scroll to the next or previous set of transactions, use the or button. The button loads the first (most recent) set of transactions.

By default, the transaction table includes all transactions that involved the selected element. You can restrict the display to:

- The transactions performed by a specific user (by choosing from the list of users).
- The transactions created in a specific interval:



History View Commands

You can select a transaction in the upper table and right-click to invoke commands that operate on the version created by the selected transaction:

Open Opens an Editor tab on the file.

Export Copies the file to a location you specify.

Merge From Opens a Merge tool to merge the selected version into your workspace.

Patch From Opens the Eclipse Compare editor, which allows you to copy (patch) changes from one version of a file to another.



Note: In order to perform a `Patch From` command, the merge tool must be set to Eclipse in the **AccuRev** preferences. See [Using Alternative Diff and Merge Tools](#) for more information on setting preferences.

Diff Against>	Other Version	Enabled when two transactions are selected. Compares the versions created by the two selected transactions.
	File in the Workspace	Enabled when a single transaction is selected. Compares the version associated with the transaction with the version in the workspace. You can configure the file-comparison tool. See Using Alternative Diff and Merge Tools .

You can select an element in the lower table and right-click to invoke commands that operate on the version that this transaction created:


Open	Opens an Editor tab on the file.
Export	Copies the file to a location you specify.
Diff Against > Previous Transaction	Compare the selected version with the version that was in its workspace or stream just before the version was created.
Properties	Displays the depot-relative pathname of the selected version, as well as the element type and ID.

Patching From the History View

Use the following procedure to patch a file using changes from another version of that file. The target for the patch operation is the version in your Eclipse project (your AccuRev workspace).

Before you begin, make sure AccuRev Plug-In for Eclipse is using the Eclipse Merge tool. See [Using Alternative Diff and Merge Tools](#).

1. In the **Navigator** view, right-click the file you want to patch and choose **Team > AccuRev History**. The **History** view appears. The **Element History** section displays all of the transactions that involve the file you selected.
2. Review the transactions to find the one that contains the changes you want to patch into your version of the file. File versions associated with that transaction are displayed in the lower part of the **Element History** section.
3. Right-click the transaction and choose **Patch From** from the context menu. The **Eclipse Compare** editor appears. The **Present File** pane displays the version of the file in your Eclipse project. The **Workspace file** pane displays the version whose changes you want to patch into that file.



4. Scroll through the Workspace File to review changes. Use the:

Copy All Non-Conflicting Changes from Right-to-Left button

To copy all changes to your version of the file.

Copy Current Change from Right to Left button

to copy individual changes one at a time.



Note: Changed text must be selected for this button to be active.

5. Save your changes (**File > Save**).



Tip: Closing the **Compare editor** prompts you to save changes if you have not already.

AccuRev Plug-In for Eclipse prompts you to **Keep** the patched file.


6. Click **Yes** to **Keep** the patched file. Otherwise, click **No**.

Synchronize View

The **AccuRev** perspective includes the standard **Eclipse Team Synchronize** view. Most of the controls and commands available in this view work the same way with AccuRev as they do with the CVS version control system. This means you can use the Eclipse online help facility to learn about synchronization in general and about the specific facilities of this view. This section describes the AccuRev-specific aspects of using the **Synchronize** view.

An Eclipse synchronization is a file-by-file listing that answers the question, “What are the current differences between my projects and the repository?”.

With AccuRev, a synchronization actually takes into account three locations:



- The AccuRev “project” or workspace tree. The AccuRev workspace is typically located on your machine’s hard drive.
- The AccuRev “repository” or depot. The AccuRev depot contains two locations corresponding to a given project:
 - Your AccuRev workspace stream, which tracks your private versions, for example, those created by `Keep`.
 - Your AccuRev workspace’s backing stream, which tracks versions that you have made public with `Promote`.

Since AccuRev also version-controls directories and links, a synchronization can list these objects, as well.

Eclipse Annotations

Eclipse annotates each object in a synchronization, to indicate the type of difference:

- [incoming]** The object changed in the repository, but not in the project.
- [outgoing]** The object changed in the project, but not in the repository.
- [conflicting]** The object changed in both the project and the repository.

The following table summarizes how Eclipse annotations correspond to AccuRev statuses:

Eclipse Annotation	AccuRev Status
[incoming]	(stale)
[outgoing]	(modified)
	(kept)
	(member)
	(external)
[conflicting]	(overlap)

You can view an object’s AccuRev status by invoking the `Show Properties` command from its context menu or from the **AccuRev** toolbar.



Note:

- The AccuRev command `Anchor` changes a file’s AccuRev status to `(member)`, but does not affect the file’s contents. Such a file is classified as `[outgoing]` in a synchronization, even though there might be no difference between the file’s contents in the project and in the repository.
- AccuRev icon label decorations are included for each object in the synchronization. These decorations can help you identify the various kinds of outgoing objects, for example, to distinguish


the (overlap) files from the (modified) files. See [Setting Label Decorations](#) for more information.

- Icons for files with a status of (external) are displayed without any decoration.

Performing Operations in the Synchronize View

You can work in the **Synchronize** view by running commands from its toolbar or from the context menu of an object (or a selected set of objects). Many of these commands work with AccuRev in exactly the same way as they do with CVS. For example, the context menu commands **Open in Compare Editor** and **Remove from View**, and the toolbar commands **Pin Current Synchronization**, **Mode**, and **Presentation**.

The following provide a visual quick-reference for the standard **Synchronize** view commands. For detailed help, use the *Eclipse Help* menu.



The same AccuRev commands that are available in the **Navigator** view (*Keep*, *Promote*, *Defunct*, etc.) also appear on object context menus in the Synchronize view. These commands are described in [Team Menu Commands](#).

A common operation in the **Synchronize** view is comparing the project's version of a file with the repository's version. You can do this using Eclipse or AccuRev tools:

- To invoke the Eclipse **Compare Editor**, double-click the file or select **Open in Compare Editor** from its context menu.
- To invoke the Diff Tool, select **Diff Against Backed Version** from its context menu. (You can also access **Diff Against** from within the **Commit All** dialog box. You can configure this command to invoke the Eclipse **Compare Editor**, third party, and custom Diff tools. See [Using Alternative Diff and Merge Tools](#).)

The following sections describe the most important **Synchronize** view operations: increasing the level of synchronization between your project and the repository, either by “committing” (transferring data from the project to the repository) or by “updating” (transferring data from the repository to the project).

Committing Outgoing Changes


Eclipse uses the CVS term “commit” to mean the transferring of changes from your project to the repository. You initiate a commit operation by clicking the **Commit All Outgoing Changes** button in the **Synchronize** view toolbar.



This launches a multiple-page wizard, which leads you through the invocation of some or all of these AccuRev operations:


- Add to Depot** Creates new versions of objects with (external) status.
- Keep** Creates new versions of elements with (modified) status.
- Merge** Creates new versions of elements with (overlap) status.
- Promote** Sends the project’s (kept) or (modified) versions -- including versions created during this wizard session--to the backing stream.

These operations are organized into a series of pages. On each page, you can select none, some, or all of the eligible [outgoing] elements to be processed. The AccuRev operations take place when you click **Finish** on the wizard’s final page. The following example shows the wizard screen to keep and promote (modified) elements.



You can right-click individual elements in the Commit All Outgoing Changes dialog box to access a **Diff Against** context menu.

To add and promote external files, click **Next**.



One invocation of **Commit All Outgoing Changes** can result in many AccuRev commands being performed. If your synchronization spans multiple projects in multiple AccuRev workspaces, separate AccuRev transactions are performed for each workspace. The wizard prompts you just once for a comment string, and attaches it to each AccuRev transaction that accepts comments.

Updating Incoming Changes


Eclipse uses the CVS term *update* to mean the transferring of changes from the repository to your project. AccuRev also uses the term “update”. Sometimes, clicking the Update All Incoming Changes button in the Synchronize view toolbar simply performs an AccuRev `Update` command. But it sometimes launches a multiple-page wizard, which leads you through some operations to be performed before the AccuRev `Update` command proceeds.

The wizard’s first page handles the following “AccuRev Update restriction”:

- An AccuRev `Update` cannot proceed if any element has (modified) status but does not also have (member) status.

That is, the offending elements have not been made “active” in the workspace with the `Anchor` or `Keep` commands. You can locate such elements in the **Navigator** view with the command **Team > AccuRev Searches > Non-member**.

(This page does not appear if the synchronization contains no such “non-member” elements.)



On this page, you must process all elements whose status is (modified). You can process (overlap) (modified) elements here too, or, you can wait to process some or all of them on the next page.


You can resolve the (modified) status of elements in either of these ways:

- **Keep Changes** performs a Keep command on all the selected elements. These elements will not be overwritten in the coming Update operation.
- **Revert Changes** performs a Revert to Backed command on all the selected elements, causing them to have (backed) status. In the coming Update operation, these elements will be overwritten by the current version in the backing stream.

When the list has no more elements whose status is (modified) only, you can:

- Click **Next** to proceed to the second wizard page on which you specify Merge operations to be performed before the Update.
- Click **Finish** to proceed directly to the Update, without doing any merge work.
- Click **Cancel** to exit the wizard without performing the Update at all. (This does not cancel your **Keep Changes** and Revert Changes work, which has already taken place.)

The wizard's second page handles files with (overlap) status. If you chose not to handle one more files with (overlap)(modified) status on the preceding page, they appear here.



You must resolve files with `(overlap)(modified)` status, because of the AccuRev Update restriction discussed at the beginning of this section. Resolving files with `(overlap)(kept)(member)` status is optional, because the `Update` operation will not try to overwrite them.

You can resolve the `(overlap)` status of elements in either of these ways:

- **Merge Overlaps** performs a Merge command on all the selected elements, combining the changes in the repository (backing stream) with your project's changes. This Keeps a new version of each element. These elements will not be overwritten in the coming Update operation -- but that is OK, since you have already incorporated the changes from the repository (backing stream).
- **Purge Overlaps** performs a Revert to Backed command on all the selected elements, causing them to have (backed) status. In the coming Update operation, these elements will be overwritten by the current version in the backing stream.

When the list has no more elements whose status is `(overlap)(modified)`, you can:

- Click **Finish** to proceed to the `Update`.
- Click **Cancel** to exit the wizard without performing the `Update` at all. (This does not cancel your **Merge Overlaps** and **Purge Overlaps** work, which has already taken place.)

Integration with Mylyn

AccuRev Plug-In for Eclipse supports an integration between AccuWork and Mylyn. The Mylyn Plug-In for Eclipse manages user tasks. You can use the AccuRev Plug-In for Eclipse integration with Mylyn to perform AccuWork procedures within the Eclipse interface, such as creating and managing AccuWork queries and issues.

 **Note:** The Mylyn Plug-In for Eclipse is not included when you install AccuRev Plug-In for Eclipse. If you want to use the integration between AccuWork and Mylyn, you must separately install the Mylyn Plug-In for Eclipse.


When you install AccuRev Plug-In for Eclipse version 2013.5 or later, the integration with Mylyn is automatically active if the Mylyn Plug-In for Eclipse has been installed. The procedures described in the following sections assume that you have installed the Mylyn Plug-In for Eclipse.

Adding an AccuWork Task Repository


Before using the AccuRev Plug-In for Eclipse integration with Mylyn, you must add an AccuWork task repository.

To add an AccuWork task repository:

1. In Eclipse, open the **Mylyn** view by selecting **Window > Show View > Other > Mylyn > Task Repositories**. The **Task Repositories** tab is active.
2. Click the **Add Task Repository** button . The **Select a task repository type** page of the **Add Task Repository** wizard appears:



3. Select the **AccuWork Repository** option and click **Next**. The **AccuWork Repository Settings** page of the **Add Task Repository** wizard appears:



4. Specify the following:

- Server** Your AccuRev Server. The server information you enter should take the following form: <server_name> : <port_number>.
-  **Note:** The server must be one of the AccuRev Servers that is already available to you through the AccuRev Plug-In for Eclipse.
- Label** A name you designate for your AccuRev Server.
- Disconnected** The default state of the AccuRev Server is disconnected.
- User ID** Your AccuRev user name.
- Password** Your AccuRev password.
- Save Password** Indicates that you want Eclipse to remember your password between sessions.
- Task Editor Settings** Optional settings that specify the look and feel of the **Task Editor**.


5. Click **Validate Settings** to confirm the accuracy of the AccuRev Server settings.

6. Click **Finish** to apply the current settings and dismiss the dialog box.

Logging In to an AccuWork Task Repository

You must be connected to an AccuWork task repository before you can create and run AccuWork queries. To log in to an AccuWork Task repository:

1. In Eclipse, open the **Mylyn** view by selecting **Window > Show View > Other > Mylyn > Task Repositories**. The **Task Repositories** tab is active.
2. Right-click the name of your **AccuRev Task** repository and select **Properties**. The **Properties for Task Repository** window appears:



Make sure your connection settings are valid.

3. Click **Validate Settings** to confirm the accuracy of the AccuRev Server settings.
4. Click **Finish** to validate the settings and log in.

Removing an AccuWork Task Repository from Your Mylyn View

If you are no longer using an AccuWork task repository, you can remove it from your Mylyn view. Note that the following procedure only removes the repository from your view. The repository still exists and you can reconnect to it at a later time. See [Adding an AccuWork Task Repository](#) for more information.

To remove an AccuWork task repository from your Mylyn view:

1. In Eclipse, open the **Mylyn** view by selecting **Window > Show View > Other > Mylyn > Task Repositories**. The **Task Repositories** tab is active.
2. Right-click the name of the AccuWork task repository and select **Delete**.

Working with AccuWork Queries

The following sections contain information about creating, running, and editing AccuWork queries when using Mylyn tasks.

Before running AccuWork queries in a Mylyn view, you must specify a default query in the **AccuWork Query Browser** by right-clicking an existing query and selecting **Set as Default** from the context menu.



Note: The query results represent the AccuWork issues returned by both your Mylyn query and your AccuWork default query.


Creating an AccuWork Query

You can create and run AccuWork queries from within your Eclipse development environment by using the AccuRev Plug-In for Eclipse integration with Mylyn.


 **Note:** Before running AccuWork queries in a Mylyn view, you must specify a default query in the **AccuWork Query Browser** by right-clicking an existing query and selecting **Set as Default** from the context menu.

To create an AccuWork query:

1. In Eclipse, open the Mylyn view by selecting **Window > Show View > Other > Mylyn > Task List**. The **Task List** tab is active.
2. On the **Mylyn Task List** tab, click the **New Task** option list and select **New Query**. The **New Query** dialog box appears:



3. Select the name of your AccuRev Server and click **Next**. The **Edit Query** dialog box appears:



4. Specify settings in the **Edit Query** dialog box


Query Title	A name for your new query.
Type	The kind of query you want to construct, such as: defect, task, enhancement, story, or requirement.
Include Completed	Indicates that you want the query to return defects, tasks, enhancements, stories, or requirements that have already been completed.
Owner	The owner of the query. Typically, you would select your own user name, unless you are assigning queries to other users.
Depot	The name of the AccuRev depot that you are querying.

5. Click **Finish**. The new query appears in the **Task List** tab in your Mylyn view, followed by the name of your AccuRev Server.

Running an AccuWork Query

To run an AccuWork query in a Mylyn view:

1. In Eclipse, open the Mylyn view by selecting **Window > Show View > Other > Mylyn > Task List**. The **Task List** tab is active.
2. Select the query you want to run and press **Enter**, or double-click the name of the query. If the query conditions are satisfied, the results of the query appear in the **Mylyn Task List** tab beneath the query:




3. You can open any item that is returned by your query by selecting the item and pressing `Enter` or by double-clicking the item. You can also right-click the item and select an option from the context menu to perform a Mylyn task operation.

Editing an AccuWork Query

To edit an AccuWork query:

1. In Eclipse, open the Mylyn view by selecting **Window > Show View > Other > Mylyn > Task List**. The **Task List** tab is active.
2. On the **Mylyn Task List** tab, right-click the name of the query and select **Properties** from the context menu. The **Edit Query** dialog box appears:



3. Change the settings to edit the query.
4. Click **Finish** to commit your changes.

AccuRev Usage Model

This section introduces the basic AccuRev concepts and procedures that will enable you to be comfortable and productive using AccuRev on day one. More detailed information is always just a click away: pressing F1 or clicking the help button anywhere in the AccuRev GUI provides you with access to the entire AccuRev documentation set in both HTML and PDF formats.

AccuRev's flexibility makes it easy to use for a variety of development scenarios. But like every software system, it has usage models that were foremost in the minds of its architects. This section describes the most common usage model.

AccuRev is a software configuration management (SCM) system, designed for use by a team of people who are developing a set of files. This set of files might contain source code, images, technical and marketing documents, audio/video tracks, or any other digital content the user puts into the system. The files and directories in AccuRev are said to be "version-controlled" or "under source control".

For maximum productivity, the team's members must be able to work independently of each other, sometimes for just a few hours or days, other times for many weeks. Accordingly, each user has his own private copy of the version-controlled files. The private copies are stored on the user's own machine (or perhaps in the user's private area on a public machine), in a directory tree called a *workspace*. We can picture the independent workspaces for a three-user team comprised of John, Mary, and Derek as follows:




This set of users' workspaces uses the convention of having like names, suffixed with the individual usernames. AccuRev GUI enforces this username-suffix convention. In this example, talon_dvt might mean "development work on the Talon product"; john, mary, and derek would be the users' login names.

From AccuRev GUI's perspective, development work in this set of workspaces is a continual back-and-forth between getting "*in sync*" and "*out of sync*":

- Initially, the workspaces are completely synchronized: each workspace has copies of the same set of version-controlled files.
- The workspaces become unsynchronized as each user makes changes to some of the files.
- Periodically, users share their changes with each other. When john incorporates some or all of mary's changes into his workspace, their two workspaces become more closely (perhaps completely) synchronized.

You might assume that the workspace synchronization process involves the direct transfer of data from one workspace to another. But this is not the way AccuRev GUI organizes the work environment. Instead of transferring data directly between private areas (that is, between users' workspaces), AccuRev GUI organizes the data transfer into two steps:

1. One user makes his changes public, available to all the other members of his team. This step is called *promoting*.
2. Whenever they wish, other team members incorporate the public changes into their own workspaces. This step is called *updating*.



The first step involves a public data area, called a *stream*. A stream is an AccuRev GUI structure with two very important features that support and simplify parallel development. First, as implied by the preceding illustration, numerous individual contributors can create workspaces on a single stream, allowing them to easily share their work with others, and to get changes from them when they wish. As you will see later, AccuRev GUI has numerous safeguards that prevent one user from overwriting another user's changes, and tools that help you resolve conflicting changes when they occur. Second, in a stream hierarchy, inheritance lets child streams automatically inherit changes from the parent streams above them, reducing the need for tedious merges that might otherwise be required when several developers are working on the same code.

AccuRev GUI has several kinds of streams, but the most common one is the backing stream. Later, we will show you how the data in this public stream "is in back of" or "provides a backstop for" all the private workspaces of the team members.

Change and Synchronization: The Four Basic Commands


With the usage model described above, you will be able to accomplish most of your work with four simple commands: *Keep*, *Promote*, *Update*, and *Merge*. These commands are described in the following sections.

Keep: Preserving Changes in Your Private Workspace

A workspace is just a normal directory tree in which you make changes to version-controlled files. You can work with the files using text editors, build and test tools, IDEs, and so on, just as if the files were not version-controlled at all. For example, you might edit a source file and invoke the editor's *Save* command a dozen times over the course of an hour or two. These operations do not involve AccuRev at all, the operating system changes the contents and the timestamp of the file in your workspace.

You do not need to perform a *check out* operation or otherwise get permission before editing a file in your workspace. (Some legacy SCM systems do impose such a regimen, and AccuRev can be configured to require checkouts, if your organization requires them.)

Every so often, you want AccuRev to preserve the current contents of the file as an official new version of the file. You accomplish this using the *Keep* command.



This figure shows how to invoke the `Keep` command from the **File Browser** toolbar. `Keep` is also available from the **Actions** and context (right-click) menus. You can also keep new files, like `requirements.txt` in the preceding illustration, its status is `external` because it has not yet been added to AccuRev.

 **Tip:** The **File Browser** helps organize your workspace using **Outgoing Changes** (your work), **Incoming Changes** (others' work), and **Conflicts** modes (conflicting changes in your work and that of a teammate).

You can continue modifying the file, using `Keep` to preserve the latest changes, as often as you like. Other team members will not complain about "thrashing" because these new versions stay within your workspace and do not affect any other user's workspace. AccuRev retains all the versions that you `Keep`. This makes it possible for you to roll back to any previous version you created.

Several other operations are similar to `Keep` in that they create a new version of a file in your workspace, without affecting any other user's workspace. The most important of these are:

- Rename and Move** You can rename a file or move it to a different directory (or both), using AccuRev commands. Other users will continue to see the file at its original pathname in their workspaces.
- Defunct** You can remove a file from your workspace with the `Defunct` command. When you promote a *defuncted* file, other users will continue to see the file until they update their workspaces, at which point the file will be removed. (`Defunct` differs from a simple `delete` in that `Defunct` removes the file from your workspace, while `Delete` removes the physical file from your local directory.)

More About Keep

AccuRev retains all of the versions that you `Keep`. Each time you `Keep` a file, its current contents are copied to the AccuRev repository, located on the machine where the AccuRev Server runs. You do not need to care about the name and precise location of this copy. Each version you create has a `version-ID`, such as `myWorkspace\2` (which translates as "the 2nd version of this file created in the `myWorkspace` workspace").

AccuRev keeps track of the status of each file in a workspace. After you `Keep` a file, the **Status** column in the **File Browser** contains the indicator (kept). It also contains the indicator (member), meaning that the file belongs to the set of files you are actively working on. (See *Active and Inactive Files* in [Promote](#) for more information). The **Version** column displays the `version-ID`.

Name	Status	Version
brass.c	(backed)	hawk\3
brass.h	(backed)	hawk_dvt\11
commands.c	(backed)	hawk_dvt\7


A change to the data within a file, recorded by `Keep`, is termed a *content change*. The change made by `Rename`, `Move` or `Defunct` is termed a *namespace change*. (Many SCM systems do not handle namespace changes at all, or have very limited capabilities in this area.) As noted previously, AccuRev Server saves a new copy of the file in the repository whenever you make a content change. But it does not need to copy the file when you make a namespace change, rather, the AccuRev Server just records the change in its database.

To perform version control on directories, AccuRev Server only needs to keep track of namespace changes, such as renaming, moving, or deleting a directory. Unlike some legacy SCM systems, AccuRev does not need to record a new directory version when you make a content change. For example, when adding a new file to the directory.

Promote: Making Your Private Changes Public

At some point, after you have used `Keep` to create one or more new, private versions of a file in your workspace, you typically want to share the changes you have made with the other team members. To make your (most recent) new version *available to the public*, you *promote* it.

The following figure shows how to run the `Promote` command from the **File Browser** toolbar. `Promote` is also available from the **Actions** and context (right-click) menus.




 **Tip:** You can `Promote` files that you have not yet kept. AccuRev performs the necessary `Keep` action for you. In the case of new files, AccuRev first adds the file to the AccuRev repository.

Promoting your new version of a file does not automatically *push* it into the workspaces of the other team members. When a user decides that she is ready to incorporate versions of files that other team members have promoted, she *pulls* them into her workspace with the `Update` command. This process is described in [Update: Incorporating Others' Changes into Your Workspace](#).

Streams

The `Promote` command sends data to, and the `Update` command gets data from, an AccuRev data structure called a *stream*.



The stream (named `talon_dev` in this illustration) acts as a central data exchange for the set of workspaces used by a development team. A stream also has a bit of "traffic controller" built in, preventing team members' efforts from colliding and providing other mechanisms to control the flow of data.

A stream is not, as you might initially suppose, a set of copies of promoted files. Rather, it is more like a list of version-IDs.

- The 4th version created in workspace `talon_dvt_akp` of file `logic.xml`.
- The 7th version created in workspace `talon_dvt_mary` of file `matrix.ini`
- Etc...

In SCM vernacular, a stream is a configuration of a collection of version-controlled files. The term stream is apt, because it implies the ongoing changes happening in a development project. Each time a user promotes a version of file `logic.xml`, the stream configuration changes for that file, for example, from the 5th version created in workspace `talon_dvt_derek` to the 7th version created in workspace `talon_dvt_mary`.

Promotion and Parallel Development

Sometimes, AccuRev does not allow you to promote a file to the development team's stream, because another team member has already promoted the same file (after modifying it in their own workspace). AccuRev prevents you from overwriting your colleague's change to the team's shared stream. This situation is called an overlap: two users working at the same time on the same goal, to create the stream's next version of a particular file.

Before you can promote your changes to the stream, you must first perform a merge on the file that has an overlap. This command is described in [Merge: When Changes Would Collide](#).

Active and Inactive Files

As you work with a file using the commands described above, AccuRev considers the file to alternate between being active in your workspace and inactive:

- The file is initially inactive.
- When you create a new version in your workspace, using `Keep`, `Rename`, `Move`, or `Defunct`, the file becomes active.
- When you make your private version public, using the `Promote` command, the file becomes inactive again.

Later, you might restart this cycle, making the file active again by creating another new version of it. Alternatively, updating your workspace might overwrite your inactive file with a newer version that another team member promoted.

AccuRev keeps track of the set of active files in your workspace. Officially, this set is called the default group. You might find it easier to think of it as the workspace's "active group".

More About Promote

The `Promote` command does not copy the promoted version to the AccuRev repository. It does not need to. Promotion just gives an additional name to a version that already exists in the repository, having been placed there by a previous `Keep` command (or `Rename`, `Move`, or `Defunct`). For example, promoting the 7th version created in workspace `talon_dvt_mary` might give that version the additional name the 3rd version promoted to `stream talon_dvt`.

Just to emphasize the previous point: a stream does not reside in the file system, but in the database used by the AccuRev Server. Promoting a version to a stream does not create a copy of a file, it just creates an additional file-reference in the database.

It might seem strange at first that deleting a file with the `Defunct` command makes the file active. The **File Browser** continues to list the file, with a `defunct` status, even though the file has been removed from your workspace's disk storage. This design feature enables AccuRev to implement the file-deletion operation using the same private-change/public-change scheme as all other changes.


We have discussed the stream that is the basis for a set of workspaces. But a typical development project has many streams, organized into a hierarchy. Promoting a version to a higher-level stream from a lower level stream makes that version "even more public", for example, available to users outside your local development team.

Update: Incorporating Others' Changes into Your Workspace

As users work independently of each other, the contents of their workspaces increasingly diverge. Typically, some of the differences between workspaces are inconsistencies. For example, changes that John makes in a report-library routine might cause errors in the report program that Mary is writing. To minimize the time and effort required to resolve inconsistencies during the integration phase of a project, it makes sense to have users synchronize their workspaces on a regular basis.

Synchronization does not mean incorporating data into your workspace directly from one or more other workspaces. Instead, synchronization involves copying data into the workspace from the stream to which all team members `Promote` their changes.

This figure shows how to invoke the `Update` command from the **File Browser** toolbar. `Update` is also available from the **File** and context (right-click) menus.



 **Tip:** You can Update your workspace from any File Browser mode, but the **Incoming Changes Mode** shows you exactly how your workspace will change.

 **Note:** The stream's role as a provider of data, through `Update` operations, to a set of workspaces motivates the term *backing stream*. Think of restocking a store's shelves with merchandise retrieved from "the back room".

Note:

So updating your workspace copies versions of certain files from the backing stream to the workspace, overwriting/replacing the files currently in the workspace. But which files? Update changes a file if:

- There is a newer version in the backing stream, and
- The file is not currently active in your workspace.

Update will not overwrite an active file, even if there is a new version of it in the backing stream. No matter how good someone else's code is, you do not want his changes to wipe out the changes that you have been making! This situation is another instance of an overlap, which was introduced in [Promote: Making Your Private Changes Public](#). You can encounter an overlap during a promote (if you are trying to make your private changes public), or during an update (if you are trying to bring already public changes into your private workspace). You can use the merge operation to resolve all such overlap situations. See [Merge: When Changes Would Collide](#).

Update handles namespace changes as well as content changes. Thus, if your colleague renamed a file and promoted the change, an update will cause the file to be renamed in your workspace. And if your colleague removed a file using the `Defunct` command, an update will cause the file to disappear from your workspace.

More About Update

Here is how AccuRev prevents an update from overwriting your changes: the first thing Update does is to analyze your workspace, determining whether each version-controlled file is `active` or `inactive`. Initially, all the files in a workspace are `inactive`, each one is a copy of some version in the repository. (For each version-controlled file, AccuRev keeps track of which particular version.)

A file is deemed to be `active` in your workspace if you have created a new version of it, using the `Keep`, `Rename`, `Move`, or `Defunct` command. (There are other commands that "activate" a file.) When Update copies versions from the repository into your workspace, it skips over all active files.




Note: Update can tell if you have modified a file but have not yet stored the changes in the repository as a new `Keep` version. It uses *time-stamps* and *checksums* to determine this. The presence of such files prevents the update from proceeding if updating would overwrite one or more of them with the backing-stream versions. You can use the `Anchor` command to activate such files, enabling Update to do its work.

Merge: When Changes Would Collide

The preceding sections on the `Promote` and `Update` commands both discuss the situation in which two users concurrently work on the same file. Their changes to the file are said to overlap. Both `Promote` and `Update` decline to process a file with `(overlap)` status because doing so would cause one user's changes to overwrite another's changes. For example:

- Team members John and Mary both `Keep` one or more new private versions of `logic.xml` in their respective workspaces.
- Mary `Promotes` her latest new version of `logic.xml` to the backing stream.
- At this point, AccuRev:
 - Will not allow John to `Promote` his version of `logic.xml` to the backing stream (there is no reason to assume that John's changes should take precedence over the changes Mary has already made and promoted).
 - Will not overwrite John's copy of `logic.xml` when he updates his workspace (again, AccuRev does not assume that a version in the backing stream should take precedence over changes made to the version in the workspace). The `Update` command skips over this file, but continues its work on other files.
 - Flags the overlap condition by highlighting `logic.xml` in yellow.

Before John can either promote or update `logic.xml`, he must incorporate, or merge, the version in the backing stream, which contains Mary's changes, into his own copy of the file. The `Merge` command is essentially a text editor, which combines the contents of two versions of a text file. The resulting *merged version* replaces the file in John's workspace.



This figure shows how to run the `Merge` command from the **File Browser** toolbar. `Merge` is also available from the **Actions** and context (right-click) menus.


 **Tip:** Use the **File Browser Conflicts** mode to view overlap and other conditions that prevent files from being updated and promoted.

Often, a merge operation is unambiguous, and so can be performed automatically. For example, suppose Mary's changes to file `logic.xml` all occur in lines 30–50, and all of John's changes occur in lines 125–140.

In this case, merging the two versions involves replacing some or all of John's 20 lines with Mary's. Now, the edited version of `logic.xml` in John's workspace contains both users' changes.

 **Note:** We do not claim that the two sets of changes are semantically consistent with each other. That is what the build-and-test cycle is for!

If both John and Mary have made changes to the same part of the file, say, lines 2–10, then John must decide how to resolve this conflict. The graphical `Merge` tool makes this easy.



After performing a merge, AccuRev automatically keeps the merged version to preserve the results of the merge operation. You can then promote the merged version to the backing stream. After that, other team members can use Update, perhaps in conjunction with Merge, to bring all the changes into their workspaces.

More About Merge

The graphical **Merge** tool performs a *three-way merge*, which uses the common ancestor of the two versions being merged. This algorithm helps to automate the merge operation, often completely eliminating the need for human intervention. AccuRev performs merge operations on text files only. Binary files are merged by choosing which version to take.

AccuRev keeps track of all merge operations. This greatly simplifies subsequent merge operations on files that have been merged previously: you do not need to resolve the same conflicts over and over again.

The most common overlap situation happens when AccuRev prevents you from promoting a file, because someone else "got there first" in creating a version in the backing stream. AccuRev can also detect deep overlaps, in which another user "got there first" in creating a version in the parent of the backing stream, or in other higher-level streams.

Index

A

- AccuRev history command 53
- AccuRev perspective
 - about 62
 - console view 62
 - history view 64
 - search/status view 63
 - synchronize view 67
 - synchronize view operations 69
 - synchronize view:commit outgoing changes 70
 - synchronize view:updating incoming changes 71
- AccuRev searches command 54
- AccuRev statuses command 53
- AccuRev usage model 80
- AccuRev Web UI
 - about 57
 - getting started 58
 - starting 57
- AccuRev workspace information command 53
- add to AccuRev depot command 44
- adding an AccuRev Server 35
- advanced techniques using AccuRev data 37
- anchor command 46
- annotate command 49
- apply patch command 56
- associating Eclipse projects with AccuRev 14

C

- change and synchronization 81
- commands
 - AccuRev history 53
 - AccuRev searches 54
 - AccuRev statuses 53
 - AccuRev workspace information 53
 - add to AccuRev depot 44
 - anchor 46
 - annotate 49
 - apply patch 56
 - available on toolbar 59
 - compare with 41
 - copy as link 52
 - create patch 56
 - defunct 51
 - diff against 51
 - executing 12
 - integrated 40
 - keep 44, 81
 - login 44
 - logout 44
 - merge 48, 86
 - paste as link 52
 - populate 50
 - promote 46, 83
 - refactor 40
 - refresh 55
 - replace with 42

- revert to 51
- running in background 60
- share/unshare project 56
- show properties 55
- synchronize time 52
- synchronize with AccuRev repository 43
- update 85
- update AccuRev workspace 53
- version browser 49
- Web UI 56
- compare with command 41
- copy as link command 52
- create patch command 56
- creating
 - Eclipse project in existing AccuRev workspace 14
 - multiple Eclipse projects in a new AccuRev workspace 25
 - single Eclipse project in a new AccuRev workspace 19

D

- defunct command 51
- diff against command 51
- diff and merge tools
 - command parameters 8
 - configure custom tool 10
 - configure supported third-party tool 9
 - using 8

E

- Eclipse annotations 67
- Eclipse Navigator view 40
- Eclipse projects
 - adding an AccuRev Server 35
 - advanced techniques using AccuRev data 37
 - associating with AccuRev 14
 - creating a single in a new AccuRev workspace 19
 - creating in a new AccuRev workspace 25
 - creating in existing AccuRev workspace 14
 - how project names are taken from existing .project files 18
 - how to share with AccuRev 30
 - sharing with AccuRev 30
 - specifying UTF-8 encoding 37
 - working with 14
- executing AccuRev commands 12

G

- general settings 7
- getting started 6
- getting started with AccuRev Web UI 58

I

- integrated commands 40
- integration with Mylyn 73

K

keep command 44, 81

L

label decorations
 displaying 12
 folder and project 11
 setting 11
 turning off 12
 types 11

logging in to AccuRev 6

login command 44

logout command 44

M

merge command 48, 86

Mylyn

 add AccuWork task repository 74

 creating AccuWork queries 77

 edit an AccuWork query 79

 integration 73

 log in to AccuWork task repository 75

 remove AccuWork task repository from view 76

 run an AccuWork query 78

 working with AccuWork queries 76

P

paste as link command 52

populate command 50

preface 5

promote command 46, 83

promote-based integrations with issue management 60

R

refactor command 40

refresh command 55

replace with command 42

revert to command 51

running commands in the background 60

S

set AccuRev preferences in Eclipse 6

share/unshare project command 56

sharing Eclipse project with AccuRev 30

show properties command 55

starting the AccuRev Web UI 57

streams

 about 83

synchronize time command 52

synchronize with AccuRev repository command 43

T

team menu commands

 AccuRev history 53

 AccuRev searches 54

 AccuRev statuses 53

 AccuRev workspace information 53

 add to AccuRev depot 44

 anchor 46

 annotate 49

 apply patch 56

 copy as link 52

 create patch 56

 defunct 51

 diff against 51

 keep 44

 login 44

 logout 44

 merge 48

 paste as link 52

 populate 50

 promote 46

 refresh 55

 revert to 51

 share/unshare project 56

 show properties 55

 synchronize time 52

 synchronize with AccuRev repository 43

 update AccuRev workspace 53

 version browser 49

 Web UI 56

Team menu commands 43

U

update AccuRev workspace command 53

update command 85

UTF-8 encoding

 about 37

 other preferences 38

 setting for a file 37

 setting for a project 38

 setting for a workspace 38

V

version browser 49

W

Web UI command 56

working with Eclipse projects 14