



ArcSight ESM

Software Version: 7.9

API Reference Vol. 2: Manager-Client Services (1.1)

Document Release Date: November, 2025

Software Release Date: November, 2025

Legal Notices

Open Text Corporation

275 Frank Tompa Drive, Waterloo, Ontario, Canada, N2L 0A1

Copyright Notice

Copyright 2001-2025 Open Text.

The only warranties for products and services of Open Text and its affiliates and licensors (“Open Text”) are as may be set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Open Text shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Trademark Notices

“OpenText” and other Open Text trademarks and service marks are the property of Open Text or its affiliates. All other trademarks or service marks are the property of their respective owners.

Support

Contact Information

Phone	A list of phone numbers is available on the Technical Support Page: https://softwaresupport.softwaregrp.com/support-contact-information
Support Web Site	https://softwaresupport.softwaregrp.com/
ArcSight Product Documentation	https://www.microfocus.com/documentation/arcsight/

Package

com.arcsight.coma.bridge

com.arcsight.coma.bridge

Class AuthenticationException

```
java.lang.Object
├─ java.lang.Throwable
│   └─ java.lang.Exception
│       └─ com.arcsight.coma.bridge.AuthenticationException
```

All Implemented Interfaces:
Serializable

```
public class AuthenticationException
extends Exception
```

Constructor Summary

public	AuthenticationException (String message)
public	AuthenticationException (String service, String method)

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AuthenticationException


```
public AuthenticationException(String message)
```

AuthenticationException

```
public AuthenticationException(String service,
                               String method)
```

com.arcsight.coma.bridge

Class AuthorizationException



All Implemented Interfaces:
Serializable

public class **AuthorizationException**
extends Exception

Constructor Summary	
public	AuthorizationException (String message)
public	AuthorizationException (String service, String method, boolean classRequiresAuthentication, boolean methodRequiresAuthentication, String[] classRequiredRights, String[] methodRequiredRights)

Methods inherited from class java.lang.Throwable	
addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

AuthorizationException
public **AuthorizationException**(String message)

(continued on next page)


AuthorizationException

```
public AuthorizationException(String service,  
                             String method,  
                             boolean classRequiresAuthentication,  
                             boolean methodRequiresAuthentication,  
                             String[] classRequiredRights,  
                             String[] methodRequiredRights)
```

Package

com.arcsight.coma.client.gwt

com.arcsight.coma.client.gwt Class RemoteServiceException



All Implemented Interfaces:
Serializable, Serializable

public class **RemoteServiceException**
extends Exception
implements Serializable, Serializable

Copyright (c) 2001-2018 Micro Focus or one of its affiliates. Confidential commercial computer software. Valid license required.

Field Summary	
public static final	ERROR_UNKNOWN Value: -54188

Constructor Summary	
public	RemoteServiceException()
public	RemoteServiceException(String message, Throwable cause)
public	RemoteServiceException(String message)
public	RemoteServiceException(Throwable cause)

Method Summary	
int	getErrorCode()
String	getRemoteStacktrace()
void	setErrorCode(int errorCode)
void	setRemoteStacktrace(String remoteStacktrace)

Methods inherited from class java.lang.Throwable


```
addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage,
getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace,
printStackTrace, setStackTrace, toString
```

Methods inherited from class `java.lang.Object`

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Fields

ERROR_UNKNOWN

```
public static final int ERROR_UNKNOWN
```

Constant value: **-54188**

Constructors

RemoteServiceException

```
public RemoteServiceException()
```

RemoteServiceException

```
public RemoteServiceException(String message,
                               Throwable cause)
```

RemoteServiceException

```
public RemoteServiceException(String message)
```

RemoteServiceException

```
public RemoteServiceException(Throwable cause)
```

Methods

getRemoteStacktrace

```
public String getRemoteStacktrace()
```

setRemoteStacktrace

```
public void setRemoteStacktrace(String remoteStacktrace)
```

getErrorCode

```
public int getErrorCode()
```

setErrorCode

```
public void setErrorCode(int errorCode)
```

Package

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class AuthenticationExceptionBean

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.AuthenticationExceptionBean

public class **AuthenticationExceptionBean**
extends Object

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary

public	AuthenticationExceptionBean()

Method Summary

String	getMessage()
void	setMessage(String message)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AuthenticationExceptionBean

public **AuthenticationExceptionBean()**

Methods

getMessage

public String **getMessage()**

Returns:

returns String

setMessage

```
public void setMessage(String message)
```

Parameters:

message - the value for the message property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class AuthorizationExceptionBean

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.AuthorizationExceptionBean

public class **AuthorizationExceptionBean**
extends Object

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary

public	AuthorizationExceptionBean()

Method Summary

String	getMessage()
void	setMessage(String message)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AuthorizationExceptionBean

public **AuthorizationExceptionBean()**

Methods

getMessage

public String **getMessage()**

Returns:

returns String

setMessage

```
public void setMessage(String message)
```

Parameters:

message - the value for the message property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceAddCaseEvents

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceAddCaseEvents

```
public class CaseServiceAddCaseEvents
extends Object
```

Constructor Summary

public	CaseServiceAddCaseEvents()

Method Summary

String	getAuthToken()
String	getCaseId()
List	getEventIds()
void	setAuthToken(String authToken)
void	setCaseId(String caseId)
void	setEventIds(List eventIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceAddCaseEvents

```
public CaseServiceAddCaseEvents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getCasId

```
public String getCaseId()
```

Returns:

returns String

setCasId

```
public void setCaseId(String caseId)
```

Parameters:

caseId - the value for the casId property

getEventIds

```
public List getEventIds()
```

Returns:

returns List

setEventIds

```
public void setEventIds(List eventIds)
```

Parameters:

eventIds - the value for the eventIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceAddCaseEventsResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceAddCaseEventsResponse

public class **CaseServiceAddCaseEventsResponse**
extends Object

Constructor Summary

public	CaseServiceAddCaseEventsResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceAddCaseEventsResponse

public **CaseServiceAddCaseEventsResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceAddRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceAddRelationship

public class **CaseServiceAddRelationship**
extends Object

Constructor Summary

public	CaseServiceAddRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
String	getTargetResourceId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResourceId(String sourceResourceId)
void	setTargetResourceId(String targetResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceAddRelationship

public **CaseServiceAddRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getTargetResourceId

```
public String getTargetResourceId()
```

Returns:

returns String

setTargetResourceId

```
public void setTargetResourceId(String targetResourceId)
```

Parameters:

targetResourceId - the value for the targetResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceAddRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceAddRelationshipResponse

```
public class CaseServiceAddRelationshipResponse
extends Object
```

Constructor Summary

public	CaseServiceAddRelationshipResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceAddRelationshipResponse

```
public CaseServiceAddRelationshipResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceCaseClosureStats

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCaseClosureStats

public class **CaseServiceCaseClosureStats**
extends Object

Constructor Summary

public	CaseServiceCaseClosureStats()

Method Summary

String	getAuthToken()
String	getEndTime()
String	getGroupIds()
String	getMetricType()
String	getNumGroupResults()
String	getNumUserResults()
String	getSla()
String	getStartTime()
void	setAuthToken(String authToken)
void	setEndTime(String endTime)
void	setGroupIds(String groupIds)
void	setMetricType(String metricType)
void	setNumGroupResults(String numGroupResults)

void	setNumUserResults (String numUserResults)
void	setSla (String sla)
void	setStartTime (String startTime)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceCaseClosureStats

public **CaseServiceCaseClosureStats**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getStartTime

public String **getStartTime**()

Returns:
returns String

setStartTime

```
public void setStartTime(String startTime)
```

Parameters:

startTime - the value for the startTime property

getEndTime

```
public String getEndTime()
```

Returns:

returns String

setEndTime

```
public void setEndTime(String endTime)
```

Parameters:

endTime - the value for the endTime property

getGroupIds

```
public String getGroupIds()
```

Returns:

returns String

setGroupIds

```
public void setGroupIds(String groupIds)
```

Parameters:

groupIds - the value for the groupIds property

getNumGroupResults

```
public String getNumGroupResults()
```

Returns:

returns String

setNumGroupResults

public void **setNumGroupResults**(String numGroupResults)

Parameters:

numGroupResults - the value for the numGroupResults property

getNumUserResults

public String **getNumUserResults**()

Returns:

returns String

setNumUserResults

public void **setNumUserResults**(String numUserResults)

Parameters:

numUserResults - the value for the numUserResults property

getMetricType

public String **getMetricType**()

Returns:

returns String

setMetricType

public void **setMetricType**(String metricType)

Parameters:

metricType - the value for the metricType property

getSla

public String **getSla**()

Returns:

returns String

setSla

```
public void setSla(String sla)
```

Parameters:

sla - the value for the sla property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceCaseClosureStatsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCaseClosureStatsResponse

public class **CaseServiceCaseClosureStatsResponse**
extends Object

Constructor Summary

public	CaseServiceCaseClosureStatsResponse()

Method Summary

CaseClosureStats	getReturn()
void	setReturn(CaseClosureStats _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceCaseClosureStatsResponse

public **CaseServiceCaseClosureStatsResponse()**

Methods

getReturn

public [CaseClosureStats](#) **getReturn()**

Returns:

returns CaseClosureStats

setReturn

```
public void setReturn(CaseClosureStats _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceCaseClosureVelocity

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCaseClosureVelocity

public class **CaseServiceCaseClosureVelocity**
extends Object

Constructor Summary

public	CaseServiceCaseClosureVelocity()

Method Summary

String	getAuthToken()
String	getEndTime()
String	getStartTime()
void	setAuthToken (String authToken)
void	setEndTime (String endTime)
void	setStartTime (String startTime)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceCaseClosureVelocity

public **CaseServiceCaseClosureVelocity**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getStartTime

```
public String getStartTime()
```

Returns:

returns String

setStartTime

```
public void setStartTime(String startTime)
```

Parameters:

startTime - the value for the startTime property

getEndTime

```
public String getEndTime()
```

Returns:

returns String

setEndTime

```
public void setEndTime(String endTime)
```

Parameters:

endTime - the value for the endTime property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceCaseClosureVelocityResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCaseClosureVelocityResponse

public class **CaseServiceCaseClosureVelocityResponse**
extends Object

Constructor Summary

public	CaseServiceCaseClosureVelocityResponse()

Method Summary

CaseClosureVelocity	getReturn()
void	setReturn(CaseClosureVelocity _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceCaseClosureVelocityResponse

public **CaseServiceCaseClosureVelocityResponse()**

Methods

getReturn

public [CaseClosureVelocity](#) **getReturn()**

Returns:

returns CaseClosureVelocity

setReturn

```
public void setReturn(CaseClosureVelocity _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceContainsDirectMemberByNameOrAlias

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceContainsDirectMemberByNameOrAlias

public class **CaseServiceContainsDirectMemberByNameOrAlias**
extends Object

Constructor Summary

public	CaseServiceContainsDirectMemberByNameOrAlias()

Method Summary

String	getAuthToken()
String	getGroupId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceContainsDirectMemberByNameOrAlias

public **CaseServiceContainsDirectMemberByNameOrAlias**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceContainsDirectMemberByNameOrAliasResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceContainsDirectMemberByNameOrAliasResponse

public class **CaseServiceContainsDirectMemberByNameOrAliasResponse**
extends Object

Constructor Summary

public	CaseServiceContainsDirectMemberByNameOrAliasResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceContainsDirectMemberByNameOrAliasResponse

public **CaseServiceContainsDirectMemberByNameOrAliasResponse()**

Methods

isReturn

public boolean **isReturn()**

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceCopyResourceIntoGroup

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCopyResourceIntoGroup

```
public class CaseServiceCopyResourceIntoGroup
extends Object
```

Constructor Summary

public	CaseServiceCopyResourceIntoGroup()

Method Summary

String	getAuthToken()
String	getNewName()
String	getNewParentId()
String	getOldParentId()
String	getResourceId()
void	setAuthToken(String authToken)
void	setNewName(String newName)
void	setNewParentId(String newParentId)
void	setOldParentId(String oldParentId)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceCopyResourceIntoGroup

```
public CaseServiceCopyResourceIntoGroup()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getNewName

```
public String getNewName()
```

Returns:

returns String

setNewName

```
public void setNewName(String newName)
```

Parameters:

newName - the value for the newName property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getOldParentId

```
public String getOldParentId()
```

Returns:

returns String

setOldParentId

```
public void setOldParentId(String oldParentId)
```

Parameters:

oldParentId - the value for the oldParentId property

getNewParentId

```
public String getNewParentId()
```

Returns:

returns String

setNewParentId

```
public void setNewParentId(String newParentId)
```

Parameters:

newParentId - the value for the newParentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceCopyResourceIntoGroupResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCopyResourceIntoGroupResponse

public class **CaseServiceCopyResourceIntoGroupResponse**
extends Object

Constructor Summary

public	CaseServiceCopyResourceIntoGroupResponse()

Method Summary

Case	getReturn()

void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceCopyResourceIntoGroupResponse

public **CaseServiceCopyResourceIntoGroupResponse()**

Methods

getReturn

public [Case](#) **getReturn()**

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceCount

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCount

public class **CaseServiceCount**
extends Object

Constructor Summary

public	CaseServiceCount()

Method Summary

String	getAggBy()
String	getAggGranularity()
String	getAssignee()
String	getAuthToken()
long	getEndTime()
String	getSeverity()
String	getStage()
long	getStartTime()
String	getState()
String	getTimeZone()
void	setAggBy(String aggBy)
void	setAggGranularity(String aggGranularity)
void	setAssignee(String assignee)
void	setAuthToken(String authToken)

void	setEndTime (long endTime)
void	setSeverity (String severity)
void	setStage (String stage)
void	setStartTime (long startTime)
void	setState (String state)
void	setTimeZone (String timeZone)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

CaseServiceCount

```
public CaseServiceCount()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getStartTime

```
public long getStartTime()
```

Returns:
returns long

setStartTime

public void **setStartTime**(long startTime)

Parameters:
startTime - the value for the startTime property

getEndTime

public long **getEndTime**()

Returns:
returns long

setEndTime

public void **setEndTime**(long endTime)

Parameters:
endTime - the value for the endTime property

getAggGranularity

public String **getAggGranularity**()

Returns:
returns String

setAggGranularity

public void **setAggGranularity**(String aggGranularity)

Parameters:
aggGranularity - the value for the aggGranularity property

getTimeZone

public String **getTimeZone**()

Returns:
returns String

setTimeZone

public void **setTimeZone**(String timeZone)

Parameters:
timeZone - the value for the timeZone property

getStage

public String **getStage**()

Returns:
returns String

setStage

public void **setStage**(String stage)

Parameters:
stage - the value for the stage property

getState

public String **getState**()

Returns:
returns String

setState

public void **setState**(String state)

Parameters:
state - the value for the state property

getSeverity

public String **getSeverity**()

Returns:
returns String

setSeverity

public void **setSeverity**(String severity)

Parameters:
severity - the value for the severity property

getAssignee

public String **getAssignee**()

Returns:
returns String

setAssignee

public void **setAssignee**(String assignee)

Parameters:
assignee - the value for the assignee property

getAggBy

public String **getAggBy**()

Returns:
returns String

setAggBy

public void **setAggBy**(String aggBy)

Parameters:
aggBy - the value for the aggBy property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceCountResponse

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceCountResponse

public class **CaseServiceCountResponse**
extends Object

Constructor Summary	
public	CaseServiceCountResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceCountResponse

public **CaseServiceCountResponse**()

Methods

getReturn

public List **getReturn**()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDelete

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDelete

public class **CaseServiceDelete**
extends Object

Constructor Summary

public	CaseServiceDelete()

Method Summary

String	getAuthToken()
Case	getResource()
void	setAuthToken (String authToken)
void	setResource (Case resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDelete

public **CaseServiceDelete**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Case getResource()
```

Returns:

returns Case

setResource

```
public void setResource(Case resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteAllCaseEvents

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteAllCaseEvents

public class **CaseServiceDeleteAllCaseEvents**
extends Object

Constructor Summary

public	CaseServiceDeleteAllCaseEvents()

Method Summary

String	getAuthToken()
String	getCaseId()
void	setAuthToken(String authToken)
void	setCaseId(String caseId)

Methods inherited from class java.lang.Object

equality, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteAllCaseEvents

public **CaseServiceDeleteAllCaseEvents()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getCaseld

public String **getCaseId**()

Returns:
returns String

setCaseld

public void **setCaseId**(String caseId)

Parameters:
caseId - the value for the caseld property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteAllCaseEventsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteAllCaseEventsResponse

public class CaseServiceDeleteAllCaseEventsResponse
extends Object

Constructor Summary	
public	CaseServiceDeleteAllCaseEventsResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceDeleteAllCaseEventsResponse
public CaseServiceDeleteAllCaseEventsResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteByLocalId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteByLocalId

public class **CaseServiceDeleteByLocalId**
extends Object

Constructor Summary

public	CaseServiceDeleteByLocalId()

Method Summary

String	getAuthToken()
long	getId()
void	setAuthToken(String authToken)
void	setId(long id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteByLocalId

public **CaseServiceDeleteByLocalId**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public long **getId**()

Returns:
returns long

setId

public void **setId**(long id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceDeleteByLocalIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteByLocalIdResponse

public class **CaseServiceDeleteByLocalIdResponse**
extends Object

Constructor Summary

public	CaseServiceDeleteByLocalIdResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteByLocalIdResponse

public **CaseServiceDeleteByLocalIdResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteByUUID

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteByUUID

public class **CaseServiceDeleteByUUID**
extends Object

Constructor Summary

public	CaseServiceDeleteByUUID()

Method Summary

String	getAuthToken()
String	getId()
void	setAuthToken (String authToken)
void	setId (String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteByUUID

public **CaseServiceDeleteByUUID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getId

```
public String getId()
```

Returns:

returns String

setId

```
public void setId(String id)
```

Parameters:

id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteByUUIDResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteByUUIDResponse

```
public class CaseServiceDeleteByUUIDResponse
extends Object
```

Constructor Summary

public	CaseServiceDeleteByUUIDResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteByUUIDResponse

```
public CaseServiceDeleteByUUIDResponse()
```

Methods

getReturn

```
public Void getReturn()
```

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteCaseEvents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteCaseEvents

public class **CaseServiceDeleteCaseEvents**
extends Object

Constructor Summary

public	CaseServiceDeleteCaseEvents()

Method Summary

String	getAuthToken()
String	getCaseId()
List	getEventIds()
void	setAuthToken (String authToken)
void	setCaseId (String caseId)
void	setEventIds (List eventIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteCaseEvents

public **CaseServiceDeleteCaseEvents**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getCasId

```
public String getCaseId()
```

Returns:

returns String

setCasId

```
public void setCaseId(String caseId)
```

Parameters:

caseId - the value for the casId property

getEventIds

```
public List getEventIds()
```

Returns:

returns List

setEventIds

```
public void setEventIds(List eventIds)
```

Parameters:

eventIds - the value for the eventIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceDeleteCaseEventsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteCaseEventsResponse

public class **CaseServiceDeleteCaseEventsResponse**
extends Object

Constructor Summary

public	CaseServiceDeleteCaseEventsResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteCaseEventsResponse

public **CaseServiceDeleteCaseEventsResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteResource

public class **CaseServiceDeleteResource**
extends Object

Constructor Summary

public	CaseServiceDeleteResource()

Method Summary

String	getAuthToken()
Case	getResource()
boolean	isAbortTxOnValConflicts()
void	setAbortTxOnValConflicts (boolean abortTxOnValConflicts)
void	setAuthToken (String authToken)
void	setResource (Case resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteResource

public **CaseServiceDeleteResource**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Case getResource()
```

Returns:

returns Case

setResource

```
public void setResource(Case resource)
```

Parameters:

resource - the value for the resource property

isAbortTxOnValConflicts

```
public boolean isAbortTxOnValConflicts()
```

Returns:

returns boolean

setAbortTxOnValConflicts

```
public void setAbortTxOnValConflicts(boolean abortTxOnValConflicts)
```

Parameters:

abortTxOnValConflicts - the value for the abortTxOnValConflicts property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceDeleteResourceResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteResourceResponse

public class **CaseServiceDeleteResourceResponse**
extends Object

Constructor Summary

public	CaseServiceDeleteResourceResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteResourceResponse

public **CaseServiceDeleteResourceResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteResources

public class **CaseServiceDeleteResources**
extends Object

Constructor Summary

public	CaseServiceDeleteResources()

Method Summary

String	getAuthToken()
List	getResources()
void	setAuthToken(String authToken)
void	setResources(List resources)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteResources

public **CaseServiceDeleteResources**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceDeleteResourcesResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteResourcesResponse

```
public class CaseServiceDeleteResourcesResponse
extends Object
```

Constructor Summary

public	CaseServiceDeleteResourcesResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteResourcesResponse

```
public CaseServiceDeleteResourcesResponse()
```

Methods

getReturn

```
public Void getReturn()
```

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceDeleteResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceDeleteResponse

public class **CaseServiceDeleteResponse**
extends Object

Constructor Summary

public	CaseServiceDeleteResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceDeleteResponse

public **CaseServiceDeleteResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindAllIds

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindAllIds

public class **CaseServiceFindAllIds**
extends Object

Constructor Summary

public	CaseServiceFindAllIds()

Method Summary

String	getAuthToken()

void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindAllIds

public **CaseServiceFindAllIds()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindAllIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindAllIdsResponse

public class **CaseServiceFindAllIdsResponse**
extends Object

Constructor Summary

public	CaseServiceFindAllIdsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindAllIdsResponse

public **CaseServiceFindAllIdsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindById

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindById

public class **CaseServiceFindById**
extends Object

Constructor Summary

public	CaseServiceFindById()

Method Summary

String	getAuthToken()
long	getLocalId()
void	setAuthToken (String authToken)
void	setLocalId (long localId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindById

public **CaseServiceFindById**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getLocalId

public long **getLocalId**()

Returns:

returns long

setLocalId

public void **setLocalId**(long localId)

Parameters:

localId - the value for the localId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindByIdResponse

```
public class CaseServiceFindByIdResponse
extends Object
```

Constructor Summary

public	CaseServiceFindByIdResponse()

Method Summary

Case	getReturn()

void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindByIdResponse

```
public CaseServiceFindByIdResponse()
```

Methods

getReturn

```
public Case getReturn()
```

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindByUUID

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindByUUID

public class **CaseServiceFindByUUID**
extends Object

Constructor Summary

public	CaseServiceFindByUUID()

Method Summary

String	getAuthToken()
String	getId()
void	setAuthToken (String authToken)
void	setId (String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindByUUID

public **CaseServiceFindByUUID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getId

```
public String getId()
```

Returns:

returns String

setId

```
public void setId(String id)
```

Parameters:

id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceFindByUUIDResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceFindByUUIDResponse

public class **CaseServiceFindByUUIDResponse**
extends Object

Constructor Summary

public	CaseServiceFindByUUIDResponse()

Method Summary

Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceFindByUUIDResponse

public **CaseServiceFindByUUIDResponse()**

Methods

getReturn

public [Case](#) **getReturn()**

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetAllAttachmentOnlyResourceIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllAttachmentOnlyResourceIDs

public class **CaseServiceGetAllAttachmentOnlyResourceIDs**
extends Object

Constructor Summary

public	CaseServiceGetAllAttachmentOnlyResourceIDs()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllAttachmentOnlyResourceIDs

public **CaseServiceGetAllAttachmentOnlyResourceIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetAllAttachmentOnlyResourceIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllAttachmentOnlyResourceIdsResponse

public class **CaseServiceGetAllAttachmentOnlyResourceIdsResponse**
extends Object

Constructor Summary

public	CaseServiceGetAllAttachmentOnlyResourceIdsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllAttachmentOnlyResourceIdsResponse

public **CaseServiceGetAllAttachmentOnlyResourceIdsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetAllowedUserTypes

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllowedUserTypes

public class **CaseServiceGetAllowedUserTypes**
extends Object

Constructor Summary

public	CaseServiceGetAllowedUserTypes()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllowedUserTypes

public **CaseServiceGetAllowedUserTypes**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetAllowedUserTypesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllowedUserTypesResponse

public class **CaseServiceGetAllowedUserTypesResponse**
extends Object

Constructor Summary

public	CaseServiceGetAllowedUserTypesResponse()

Method Summary

String[]	getReturn()
void	setReturn(String[] _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllowedUserTypesResponse

public **CaseServiceGetAllowedUserTypesResponse()**

Methods

getReturn

public String[] **getReturn()**

Returns:

returns String[]

setReturn

```
public void setReturn(String[] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetAllPathsToRoot

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllPathsToRoot

public class **CaseServiceGetAllPathsToRoot**
extends Object

Constructor Summary

public	CaseServiceGetAllPathsToRoot()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllPathsToRoot

public **CaseServiceGetAllPathsToRoot**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetAllPathsToRootAsStrings

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllPathsToRootAsStrings

public class **CaseServiceGetAllPathsToRootAsStrings**
extends Object

Constructor Summary

public	CaseServiceGetAllPathsToRootAsStrings()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllPathsToRootAsStrings

public **CaseServiceGetAllPathsToRootAsStrings()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetAllPathsToRootAsStringsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllPathsToRootAsStringsResponse

public class **CaseServiceGetAllPathsToRootAsStringsResponse**
extends Object

Constructor Summary

public	CaseServiceGetAllPathsToRootAsStringsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllPathsToRootAsStringsResponse

public **CaseServiceGetAllPathsToRootAsStringsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetAllPathsToRootResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllPathsToRootResponse

public class **CaseServiceGetAllPathsToRootResponse**
extends Object

Constructor Summary

public	CaseServiceGetAllPathsToRootResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllPathsToRootResponse

public **CaseServiceGetAllPathsToRootResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetAllUnassignedResourceIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllUnassignedResourceIDs

public class **CaseServiceGetAllUnassignedResourceIDs**
extends Object

Constructor Summary

public	CaseServiceGetAllUnassignedResourceIDs()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllUnassignedResourceIDs

public **CaseServiceGetAllUnassignedResourceIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetAllUnassignedResourceIDsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetAllUnassignedResourceIDsResponse

public class **CaseServiceGetAllUnassignedResourceIDsResponse**
extends Object

Constructor Summary

public	CaseServiceGetAllUnassignedResourceIDsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetAllUnassignedResourceIDsResponse

public **CaseServiceGetAllUnassignedResourceIDsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetCaseEventIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCaseEventIDs

public class **CaseServiceGetCaseEventIDs**
extends Object

Constructor Summary

public	CaseServiceGetCaseEventIDs()

Method Summary

String	getAuthToken()
String	getCaseId()
void	setAuthToken(String authToken)
void	setCaseId(String caseId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCaseEventIDs

public **CaseServiceGetCaseEventIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getCaseId

public String **getCaseId**()

Returns:
returns String

setCaseId

public void **setCaseId**(String caseId)

Parameters:
caseId - the value for the caseId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetCaseEventIDsResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCaseEventIDsResponse

```
public class CaseServiceGetCaseEventIDsResponse  
extends Object
```

Constructor Summary

public	CaseServiceGetCaseEventIDsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCaseEventIDsResponse

```
public CaseServiceGetCaseEventIDsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetCaseEventsTimeSpan

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCaseEventsTimeSpan

```
public class CaseServiceGetCaseEventsTimeSpan
extends Object
```

Constructor Summary

public	CaseServiceGetCaseEventsTimeSpan()

Method Summary

String	getAuthToken()
String	getCaseId()
void	setAuthToken(String authToken)
void	setCaseId(String caseId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCaseEventsTimeSpan

```
public CaseServiceGetCaseEventsTimeSpan()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getCaseId

public String **getCaseId**()

Returns:
returns String

setCaseId

public void **setCaseId**(String caseId)

Parameters:
caseId - the value for the caseId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetCaseEventsTimeSpanResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCaseEventsTimeSpanResponse

public class **CaseServiceGetCaseEventsTimeSpanResponse**
extends Object

Constructor Summary

public	CaseServiceGetCaseEventsTimeSpanResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCaseEventsTimeSpanResponse

public **CaseServiceGetCaseEventsTimeSpanResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetCasesGroupID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCasesGroupID

public class **CaseServiceGetCasesGroupID**
extends Object

Constructor Summary

public	CaseServiceGetCasesGroupID()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCasesGroupID

public **CaseServiceGetCasesGroupID()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetCasesGroupIDResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCasesGroupIDResponse

```
public class CaseServiceGetCasesGroupIDResponse
extends Object
```

Constructor Summary

public	CaseServiceGetCasesGroupIDResponse()

Method Summary

String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCasesGroupIDResponse

```
public CaseServiceGetCasesGroupIDResponse()
```

Methods

getReturn

```
public String getReturn()
```

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetChildNamesAndAliases

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetChildNamesAndAliases

```
public class CaseServiceGetChildNamesAndAliases
extends Object
```

Constructor Summary

public	CaseServiceGetChildNamesAndAliases()

Method Summary

String	getAuthToken()
String	getGroupId()
List	getUnmappedIds()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setUnmappedIds (List unmappedIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetChildNamesAndAliases

```
public CaseServiceGetChildNamesAndAliases()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getUnmappedIds

```
public List getUnmappedIds()
```

Returns:

returns List

setUnmappedIds

```
public void setUnmappedIds(List unmappedIds)
```

Parameters:

unmappedIds - the value for the unmappedIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetChildNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetChildNamesAndAliasesResponse

public class CaseServiceGetChildNamesAndAliasesResponse
extends Object

Constructor Summary	
public	CaseServiceGetChildNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetChildNamesAndAliasesResponse

public CaseServiceGetChildNamesAndAliasesResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetCorruptedResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCorruptedResources

```
public class CaseServiceGetCorruptedResources
extends Object
```

Constructor Summary

public	CaseServiceGetCorruptedResources()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCorruptedResources

```
public CaseServiceGetCorruptedResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetCorruptedResourcesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetCorruptedResourcesResponse

public class **CaseServiceGetCorruptedResourcesResponse**
extends Object

Constructor Summary

public	CaseServiceGetCorruptedResourcesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetCorruptedResourcesResponse

public **CaseServiceGetCorruptedResourcesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetDependentResourceIdsForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetDependentResourceIdsForResourceId

public class **CaseServiceGetDependentResourceIdsForResourceId**
extends Object

Constructor Summary

public	CaseServiceGetDependentResourceIdsForResourceId()

Method Summary

String	getAuthToken()
String	getResourceId()
boolean	isExcludeAttachmentOnlyResources()
boolean	isExcludeHiddenResources()
void	setAuthToken(String authToken)
void	setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
void	setExcludeHiddenResources(boolean excludeHiddenResources)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetDependentResourceIdsForResourceId

public **CaseServiceGetDependentResourceIdsForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

isExcludeHiddenResources

```
public boolean isExcludeHiddenResources()
```

Returns:

returns boolean

setExcludeHiddenResources

```
public void setExcludeHiddenResources(boolean excludeHiddenResources)
```

Parameters:

`excludeHiddenResources` - the value for the `excludeHiddenResources` property

isExcludeAttachmentOnlyResources

```
public boolean isExcludeAttachmentOnlyResources()
```

Returns:

returns boolean

setExcludeAttachmentOnlyResources

```
public void setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
```

Parameters:

`excludeAttachmentOnlyResources` - the value for the `excludeAttachmentOnlyResources` property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetDependentResourceIdsForResourceIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetDependentResourceIdsForResourceIdResponse

public class CaseServiceGetDependentResourceIdsForResourceIdResponse
extends Object

Constructor Summary	
public	CaseServiceGetDependentResourceIdsForResourceIdResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetDependentResourceIdsForResourceIdResponse

public CaseServiceGetDependentResourceIdsForResourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetEnabledResourceIDs

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetEnabledResourceIDs

public class **CaseServiceGetEnabledResourceIDs**
extends Object

Constructor Summary

public	CaseServiceGetEnabledResourceIDs()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetEnabledResourceIDs

public **CaseServiceGetEnabledResourceIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetEnabledResourceIDsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetEnabledResourceIDsResponse

public class **CaseServiceGetEnabledResourceIDsResponse**
extends Object

Constructor Summary

public	CaseServiceGetEnabledResourceIDsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetEnabledResourceIDsResponse

public **CaseServiceGetEnabledResourceIDsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetESMVersion

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetESMVersion

public class **CaseServiceGetESMVersion**
extends Object

Constructor Summary	
public	CaseServiceGetESMVersion()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetESMVersion

public **CaseServiceGetESMVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetESMVersionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetESMVersionResponse

public class CaseServiceGetESMVersionResponse
extends Object

Constructor Summary	
public	CaseServiceGetESMVersionResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetESMVersionResponse
public CaseServiceGetESMVersionResponse()

Methods

getReturn
public String getReturn()

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetEventExportStatus

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetEventExportStatus

```
public class CaseServiceGetEventExportStatus
extends Object
```

Constructor Summary

public	CaseServiceGetEventExportStatus()

Method Summary

String	getAuthToken()
List	getEventIds()
void	setAuthToken(String authToken)
void	setEventIds(List eventIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetEventExportStatus

```
public CaseServiceGetEventExportStatus()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getEventIds

public List **getEventIds**()

Returns:
returns List

setEventIds

public void **setEventIds**(List eventIds)

Parameters:
eventIds - the value for the eventIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetEventExportStatusResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetEventExportStatusResponse

public class CaseServiceGetEventExportStatusResponse
extends Object

Constructor Summary	
public	CaseServiceGetEventExportStatusResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetEventExportStatusResponse
public CaseServiceGetEventExportStatusResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetExclusivelyDependentResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetExclusivelyDependentResources

```
public class CaseServiceGetExclusivelyDependentResources
extends Object
```

Constructor Summary

public	CaseServiceGetExclusivelyDependentResources()

Method Summary

String	getAuthToken()
List	getExcludePathIdList()
String	getResourceId()
void	setAuthToken (String authToken)
void	setExcludePathIdList (List excludePathIdList)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetExclusivelyDependentResources

```
public CaseServiceGetExclusivelyDependentResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getExcludePathIdList

```
public List getExcludePathIdList()
```

Returns:

returns List

setExcludePathIdList

```
public void setExcludePathIdList(List excludePathIdList)
```

Parameters:

excludePathIdList - the value for the excludePathIdList property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetExclusivelyDependentResourcesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetExclusivelyDependentResourcesResponse

```
public class CaseServiceGetExclusivelyDependentResourcesResponse
extends Object
```

Constructor Summary

public	CaseServiceGetExclusivelyDependentResourcesResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetExclusivelyDependentResourcesResponse

```
public CaseServiceGetExclusivelyDependentResourcesResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetMetaGroupID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetMetaGroupID

public class **CaseServiceGetMetaGroupID**
extends Object

Constructor Summary

public	CaseServiceGetMetaGroupID()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetMetaGroupID

public **CaseServiceGetMetaGroupID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetMetaGroupIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetMetaGroupIDResponse

public class CaseServiceGetMetaGroupIDResponse
extends Object

Constructor Summary	
public	CaseServiceGetMetaGroupIDResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetMetaGroupIDResponse
public CaseServiceGetMetaGroupIDResponse()

Methods

getReturn
public String getReturn()

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetNamesAndAliases

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetNamesAndAliases

public class **CaseServiceGetNamesAndAliases**
extends Object

Constructor Summary

public	CaseServiceGetNamesAndAliases()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetNamesAndAliases

public **CaseServiceGetNamesAndAliases**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetNamesAndAliasesResponse

public class CaseServiceGetNamesAndAliasesResponse
extends Object

Constructor Summary	
public	CaseServiceGetNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetNamesAndAliasesResponse
public CaseServiceGetNamesAndAliasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetPersonalAndSharedResourceRoots

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalAndSharedResourceRoots

public class **CaseServiceGetPersonalAndSharedResourceRoots**
extends Object

Constructor Summary

public	CaseServiceGetPersonalAndSharedResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getUserId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setUserId (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetPersonalAndSharedResourceRoots

public **CaseServiceGetPersonalAndSharedResourceRoots**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetPersonalAndSharedResourceRootsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalAndSharedResourceRootsResponse

public class CaseServiceGetPersonalAndSharedResourceRootsResponse
extends Object

Constructor Summary	
public	CaseServiceGetPersonalAndSharedResourceRootsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetPersonalAndSharedResourceRootsResponse
public CaseServiceGetPersonalAndSharedResourceRootsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetPersonalGroup

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalGroup

public class **CaseServiceGetPersonalGroup**
extends Object

Constructor Summary

public	CaseServiceGetPersonalGroup()

Method Summary

String	getAuthToken()
String	getUserId()
boolean	isThrowOnMissing()
void	setAuthToken() (String authToken)
void	setThrowOnMissing() (boolean throwOnMissing)
void	setUserId() (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetPersonalGroup

public **CaseServiceGetPersonalGroup**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

isThrowOnMissing

```
public boolean isThrowOnMissing()
```

Returns:

returns boolean

setThrowOnMissing

```
public void setThrowOnMissing(boolean throwOnMissing)
```

Parameters:

throwOnMissing - the value for the throwOnMissing property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetPersonalGroupResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalGroupResponse

public class **CaseServiceGetPersonalGroupResponse**
extends Object

Constructor Summary

public	CaseServiceGetPersonalGroupResponse()

Method Summary

String	getReturn()

void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetPersonalGroupResponse

public **CaseServiceGetPersonalGroupResponse()**

Methods

getReturn

public String **getReturn()**

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetPersonalResourceRoots

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalResourceRoots

public class **CaseServiceGetPersonalResourceRoots**
extends Object

Constructor Summary

public	CaseServiceGetPersonalResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getResourceId()
int	getResourceType()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setResourceId(String resourceId)
void	setResourceType(int resourceType)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetPersonalResourceRoots

public **CaseServiceGetPersonalResourceRoots()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetPersonalResourceRootsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetPersonalResourceRootsResponse

public class CaseServiceGetPersonalResourceRootsResponse
extends Object

Constructor Summary	
public	CaseServiceGetPersonalResourceRootsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetPersonalResourceRootsResponse
public CaseServiceGetPersonalResourceRootsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReferencePages

public class **CaseServiceGetReferencePages**
extends Object

Constructor Summary

public	CaseServiceGetReferencePages()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReferencePages

public **CaseServiceGetReferencePages**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetReferencePagesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReferencePagesResponse

```
public class CaseServiceGetReferencePagesResponse
extends Object
```

Constructor Summary

public	CaseServiceGetReferencePagesResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReferencePagesResponse

```
public CaseServiceGetReferencePagesResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetRelationshipsOfParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetRelationshipsOfParents

```
public class CaseServiceGetRelationshipsOfParents
extends Object
```

Constructor Summary

public	CaseServiceGetRelationshipsOfParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetRelationshipsOfParents

```
public CaseServiceGetRelationshipsOfParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetRelationshipsOfParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetRelationshipsOfParentsResponse

public class **CaseServiceGetRelationshipsOfParentsResponse**
extends Object

Constructor Summary

public	CaseServiceGetRelationshipsOfParentsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetRelationshipsOfParentsResponse

public **CaseServiceGetRelationshipsOfParentsResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetRelationshipsOfThisAndParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetRelationshipsOfThisAndParents

```
public class CaseServiceGetRelationshipsOfThisAndParents
extends Object
```

Constructor Summary

public	CaseServiceGetRelationshipsOfThisAndParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetRelationshipsOfThisAndParents

```
public CaseServiceGetRelationshipsOfThisAndParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetRelationshipsOfThisAndParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetRelationshipsOfThisAndParentsResponse

public class **CaseServiceGetRelationshipsOfThisAndParentsResponse**
extends Object

Constructor Summary

public	CaseServiceGetRelationshipsOfThisAndParentsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetRelationshipsOfThisAndParentsResponse

public **CaseServiceGetRelationshipsOfThisAndParentsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceById

public class **CaseServiceGetResourceById**
extends Object

Constructor Summary

public	CaseServiceGetResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceById

public **CaseServiceGetResourceById**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourceByIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceByIdResponse

public class **CaseServiceGetResourceByIdResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourceByIdResponse()

Method Summary

Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceByIdResponse

public **CaseServiceGetResourceByIdResponse()**

Methods

getReturn

public [Case](#) **getReturn()**

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourceByName

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceByName

public class **CaseServiceGetResourceByName**
extends Object

Constructor Summary

public	CaseServiceGetResourceByName()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceByName

public **CaseServiceGetResourceByName**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourceByNameResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceByNameResponse

public class CaseServiceGetResourceByNameResponse
extends Object

Constructor Summary

public	CaseServiceGetResourceByNameResponse()

Method Summary

Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceByNameResponse

public CaseServiceGetResourceByNameResponse()

Methods

getReturn

public [Case](#) getReturn()

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourceIfModified

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceIfModified

```
public class CaseServiceGetResourceIfModified
extends Object
```

Constructor Summary

public	CaseServiceGetResourceIfModified()

Method Summary

String	getAuthToken()
ResourceSignature	getSignature()
void	setAuthToken (String authToken)
void	setSignature (ResourceSignature signature)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceIfModified

```
public CaseServiceGetResourceIfModified()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSignature

public [ResourceSignature](#) **getSignature**()

Returns:
returns ResourceSignature

setSignature

public void **setSignature**([ResourceSignature](#) signature)

Parameters:
signature - the value for the signature property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourceIfModifiedResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceIfModifiedResponse

public class **CaseServiceGetResourceIfModifiedResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourceIfModifiedResponse()

Method Summary

Case	getReturn()

void	setReturn(Case _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceIfModifiedResponse

public **CaseServiceGetResourceIfModifiedResponse()**

Methods

getReturn

public [Case](#) **getReturn()**

Returns:

returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourcesByIds

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByIds

public class **CaseServiceGetResourcesByIds**
extends Object

Constructor Summary

public	CaseServiceGetResourcesByIds()

Method Summary

String	getAuthToken()
List	getIds()
void	setAuthToken(String authToken)
void	setIds(List ids)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesByIds

public **CaseServiceGetResourcesByIds**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getIds

public List **getIds**()

Returns:
returns List

setIds

public void **setIds**(List ids)

Parameters:
ids - the value for the ids property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesByIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByIdsResponse

public class **CaseServiceGetResourcesByIdsResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourcesByIdsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesByIdsResponse

public **CaseServiceGetResourcesByIdsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourcesByNames

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByNames

public class **CaseServiceGetResourcesByNames**
extends Object

Constructor Summary

public	CaseServiceGetResourcesByNames()

Method Summary

String	getAuthToken()
List	getNames()
void	setAuthToken(String authToken)
void	setNames(List names)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesByNames

public **CaseServiceGetResourcesByNames()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getNames

public List **getNames**()

Returns:
returns List

setNames

public void **setNames**(List names)

Parameters:
names - the value for the names property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesByNameSafely

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByNameSafely

public class **CaseServiceGetResourcesByNameSafely**
extends Object

Constructor Summary

public	CaseServiceGetResourcesByNameSafely()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesByNameSafely

public **CaseServiceGetResourcesByNameSafely()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesByNameSafelyResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByNameSafelyResponse

public class **CaseServiceGetResourcesByNameSafelyResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourcesByNameSafelyResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesByNameSafelyResponse

public **CaseServiceGetResourcesByNameSafelyResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetResourcesByNamesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesByNamesResponse

public class CaseServiceGetResourcesByNamesResponse
extends Object

Constructor Summary	
public	CaseServiceGetResourcesByNamesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetResourcesByNamesResponse
public CaseServiceGetResourcesByNamesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesReferencePages

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesReferencePages

```
public class CaseServiceGetResourcesReferencePages
extends Object
```

Constructor Summary

public	CaseServiceGetResourcesReferencePages()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesReferencePages

```
public CaseServiceGetResourcesReferencePages()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesReferencePagesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesReferencePagesResponse

public class **CaseServiceGetResourcesReferencePagesResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourcesReferencePagesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesReferencePagesResponse

public **CaseServiceGetResourcesReferencePagesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesWithVisibilityToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesWithVisibilityToUsers

public class **CaseServiceGetResourcesWithVisibilityToUsers**
extends Object

Constructor Summary

public	CaseServiceGetResourcesWithVisibilityToUsers()

Method Summary

String	getAuthToken()

void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesWithVisibilityToUsers

public **CaseServiceGetResourcesWithVisibilityToUsers**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourcesWithVisibilityToUsersResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourcesWithVisibilityToUsersResponse

public class **CaseServiceGetResourcesWithVisibilityToUsersResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourcesWithVisibilityToUsersResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourcesWithVisibilityToUsersResponse

public **CaseServiceGetResourcesWithVisibilityToUsersResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourceTypesVisibleToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceTypesVisibleToUsers

public class **CaseServiceGetResourceTypesVisibleToUsers**
extends Object

Constructor Summary

public	CaseServiceGetResourceTypesVisibleToUsers()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceTypesVisibleToUsers

public **CaseServiceGetResourceTypesVisibleToUsers()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetResourceTypesVisibleToUsersResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetResourceTypesVisibleToUsersResponse

public class **CaseServiceGetResourceTypesVisibleToUsersResponse**
extends Object

Constructor Summary

public	CaseServiceGetResourceTypesVisibleToUsersResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetResourceTypesVisibleToUsersResponse

public **CaseServiceGetResourceTypesVisibleToUsersResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetReverseRelationshipsOfParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReverseRelationshipsOfParents

```
public class CaseServiceGetReverseRelationshipsOfParents
extends Object
```

Constructor Summary

public	CaseServiceGetReverseRelationshipsOfParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReverseRelationshipsOfParents

```
public CaseServiceGetReverseRelationshipsOfParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetReverseRelationshipsOfParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReverseRelationshipsOfParentsResponse

public class **CaseServiceGetReverseRelationshipsOfParentsResponse**
extends Object

Constructor Summary

public	CaseServiceGetReverseRelationshipsOfParentsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReverseRelationshipsOfParentsResponse

public **CaseServiceGetReverseRelationshipsOfParentsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetReverseRelationshipsOfThisAndParents

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReverseRelationshipsOfThisAndParents
```

```
public class CaseServiceGetReverseRelationshipsOfThisAndParents
extends Object
```

Constructor Summary	
public	CaseServiceGetReverseRelationshipsOfThisAndParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReverseRelationshipsOfThisAndParents

```
public CaseServiceGetReverseRelationshipsOfThisAndParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetReverseRelationshipsOfThisAndParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetReverseRelationshipsOfThisAndParentsResponse

```
public class CaseServiceGetReverseRelationshipsOfThisAndParentsResponse
extends Object
```

Constructor Summary

public	CaseServiceGetReverseRelationshipsOfThisAndParentsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetReverseRelationshipsOfThisAndParentsResponse

```
public CaseServiceGetReverseRelationshipsOfThisAndParentsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetServiceMajorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetServiceMajorVersion

public class **CaseServiceGetServiceMajorVersion**
extends Object

Constructor Summary

public	CaseServiceGetServiceMajorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetServiceMajorVersion

public **CaseServiceGetServiceMajorVersion**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetServiceMajorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetServiceMajorVersionResponse

public class **CaseServiceGetServiceMajorVersionResponse**
extends Object

Constructor Summary

public	CaseServiceGetServiceMajorVersionResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetServiceMajorVersionResponse

public **CaseServiceGetServiceMajorVersionResponse()**

Methods

getReturn

public int **getReturn()**

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetServiceMinorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetServiceMinorVersion

public class **CaseServiceGetServiceMinorVersion**
extends Object

Constructor Summary

public	CaseServiceGetServiceMinorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetServiceMinorVersion

public **CaseServiceGetServiceMinorVersion**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetServiceMinorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetServiceMinorVersionResponse

public class **CaseServiceGetServiceMinorVersionResponse**
extends Object

Constructor Summary

public	CaseServiceGetServiceMinorVersionResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetServiceMinorVersionResponse

public **CaseServiceGetServiceMinorVersionResponse()**

Methods

getReturn

public int **getReturn()**

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByACLRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByACLRelationship

public class **CaseServiceGetSourcesWithThisTargetByACLRelationship**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByACLRelationship()

Method Summary

String	getAuthToken()
String	getSourceResourceId()
void	setAuthToken(String authToken)
void	setSourceResourceId(String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByACLRelationship

public **CaseServiceGetSourcesWithThisTargetByACLRelationship**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceResourceId

public String **getSourceResourceId**()

Returns:
returns String

setSourceResourceId

public void **setSourceResourceId**(String sourceResourceId)

Parameters:
sourceResourceId - the value for the sourceResourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse

public class **CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse

public **CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationship

public class **CaseServiceGetSourcesWithThisTargetByRelationship**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationship

public **CaseServiceGetSourcesWithThisTargetByRelationship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByRelationshipCount

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationshipCount

public class **CaseServiceGetSourcesWithThisTargetByRelationshipCount**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationshipCount

public **CaseServiceGetSourcesWithThisTargetByRelationshipCount**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse

public class **CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse

public **CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse()**

Methods

getReturn

public int **getReturn()**

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId

public class **CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId

public **CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public class CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourcesWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourcesWithThisTargetByRelationshipResponse

public class **CaseServiceGetSourcesWithThisTargetByRelationshipResponse**
extends Object

Constructor Summary

public	CaseServiceGetSourcesWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourcesWithThisTargetByRelationshipResponse

public **CaseServiceGetSourcesWithThisTargetByRelationshipResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelatiobnship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelatiobnship

public class **CaseServiceGetSourceURIWithThisTargetByRelatiobnship**
extends Object

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelatiobnship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelatiobnship

public **CaseServiceGetSourceURIWithThisTargetByRelatiobnship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

public class **CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId**
extends Object

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

public **CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public class CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse
extends Object
```

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

public class **CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse**
extends Object

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

public **CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelationship

```
public class CaseServiceGetSourceURIWithThisTargetByRelationship
extends Object
```

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelationship

```
public CaseServiceGetSourceURIWithThisTargetByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public class **CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId**
extends Object

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public **CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public class CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSourceURIWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSourceURIWithThisTargetByRelationshipResponse

public class **CaseServiceGetSourceURIWithThisTargetByRelationshipResponse**
extends Object

Constructor Summary

public	CaseServiceGetSourceURIWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSourceURIWithThisTargetByRelationshipResponse

public **CaseServiceGetSourceURIWithThisTargetByRelationshipResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetSystemCasesGroupID

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSystemCasesGroupID

```
public class CaseServiceGetSystemCasesGroupID
extends Object
```

Constructor Summary

public	CaseServiceGetSystemCasesGroupID()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSystemCasesGroupID

```
public CaseServiceGetSystemCasesGroupID()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetSystemCasesGroupIDResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetSystemCasesGroupIDResponse

public class **CaseServiceGetSystemCasesGroupIDResponse**
extends Object

Constructor Summary

public	CaseServiceGetSystemCasesGroupIDResponse()

Method Summary

String	getReturn()

void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetSystemCasesGroupIDResponse

public **CaseServiceGetSystemCasesGroupIDResponse()**

Methods

getReturn

public String **getReturn()**

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetTargetsAsURIByRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsAsURIByRelationship

public class CaseServiceGetTargetsAsURIByRelationship
extends Object

Constructor Summary	
public	CaseServiceGetTargetsAsURIByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsAsURIByRelationship
public CaseServiceGetTargetsAsURIByRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsAsURIByRelationshipForSourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsAsURIByRelationshipForSourceId

public class **CaseServiceGetTargetsAsURIByRelationshipForSourceId**
extends Object

Constructor Summary

public	CaseServiceGetTargetsAsURIByRelationshipForSourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsAsURIByRelationshipForSourceId

public **CaseServiceGetTargetsAsURIByRelationshipForSourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse

public class **CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse**
extends Object

Constructor Summary

public	CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse

public **CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsAsURIByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsAsURIByRelationshipResponse

public class **CaseServiceGetTargetsAsURIByRelationshipResponse**
extends Object

Constructor Summary

public	CaseServiceGetTargetsAsURIByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsAsURIByRelationshipResponse

public **CaseServiceGetTargetsAsURIByRelationshipResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsByRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationship

public class **CaseServiceGetTargetsByRelationship**
extends Object

Constructor Summary

public	CaseServiceGetTargetsByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsByRelationship

public **CaseServiceGetTargetsByRelationship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsByRelationshipCount

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationshipCount

public class **CaseServiceGetTargetsByRelationshipCount**
extends Object

Constructor Summary

public	CaseServiceGetTargetsByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Case sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsByRelationshipCount

public **CaseServiceGetTargetsByRelationshipCount**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetTargetsByRelationshipCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationshipCountResponse

public class CaseServiceGetTargetsByRelationshipCountResponse
extends Object

Constructor Summary	
public	CaseServiceGetTargetsByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetTargetsByRelationshipCountResponse
public CaseServiceGetTargetsByRelationshipCountResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsByRelationshipForSourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationshipForSourceId

public class **CaseServiceGetTargetsByRelationshipForSourceId**
extends Object

Constructor Summary

public	CaseServiceGetTargetsByRelationshipForSourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsByRelationshipForSourceId

public **CaseServiceGetTargetsByRelationshipForSourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationshipForSourceIdResponse

public class **CaseServiceGetTargetsByRelationshipForSourceIdResponse**
extends Object

Constructor Summary

public	CaseServiceGetTargetsByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsByRelationshipForSourceIdResponse

public **CaseServiceGetTargetsByRelationshipForSourceIdResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceGetTargetsByRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsByRelationshipResponse

public class CaseServiceGetTargetsByRelationshipResponse
extends Object

Constructor Summary	
public	CaseServiceGetTargetsByRelationshipResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceGetTargetsByRelationshipResponse
public CaseServiceGetTargetsByRelationshipResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsWithRelationshipTypeForResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsWithRelationshipTypeForResource

public class **CaseServiceGetTargetsWithRelationshipTypeForResource**
extends Object

Constructor Summary

public	CaseServiceGetTargetsWithRelationshipTypeForResource()

Method Summary

String	getAuthToken()
Case	getResource()
void	setAuthToken(String authToken)
void	setResource(Case resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsWithRelationshipTypeForResource

public **CaseServiceGetTargetsWithRelationshipTypeForResource()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResource

public [Case](#) **getResource**()

Returns:
returns Case

setResource

public void **setResource**([Case](#) resource)

Parameters:
resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsWithRelationshipTypeForResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsWithRelationshipTypeForResourceById

public class **CaseServiceGetTargetsWithRelationshipTypeForResourceById**
extends Object

Constructor Summary

public	CaseServiceGetTargetsWithRelationshipTypeForResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsWithRelationshipTypeForResourceById

public **CaseServiceGetTargetsWithRelationshipTypeForResourceById()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

```
public class CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse
extends Object
```

Constructor Summary

public	CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceGetTargetsWithRelationshipTypeForResourceResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceGetTargetsWithRelationshipTypeForResourceResponse

```
public class CaseServiceGetTargetsWithRelationshipTypeForResourceResponse
extends Object
```

Constructor Summary

public	CaseServiceGetTargetsWithRelationshipTypeForResourceResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceGetTargetsWithRelationshipTypeForResourceResponse

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceHasReadPermission

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasReadPermission

public class **CaseServiceHasReadPermission**
extends Object

Constructor Summary

public	CaseServiceHasReadPermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceHasReadPermission

public **CaseServiceHasReadPermission**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceHasReadPermissionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasReadPermissionResponse

public class **CaseServiceHasReadPermissionResponse**
extends Object

Constructor Summary

public	CaseServiceHasReadPermissionResponse()

Method Summary

boolean	isReturn()

void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceHasReadPermissionResponse

public **CaseServiceHasReadPermissionResponse()**

Methods

isReturn

public boolean **isReturn()**

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceHasReverseRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasReverseRelationship

public class **CaseServiceHasReverseRelationship**
extends Object

Constructor Summary

public	CaseServiceHasReverseRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Case	getSourceResource()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Case sourceResource)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceHasReverseRelationship

public **CaseServiceHasReverseRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Case getSourceResource()
```

Returns:

returns Case

setSourceResource

```
public void setSourceResource(Case sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getTargetId

public String **getTargetId**()

Returns:

returns String

setTargetId

public void **setTargetId**(String targetId)

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceHasReverseRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasReverseRelationshipResponse

public class CaseServiceHasReverseRelationshipResponse
extends Object

Constructor Summary	
public	CaseServiceHasReverseRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceHasReverseRelationshipResponse
public CaseServiceHasReverseRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceHasWritePermission

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasWritePermission

public class CaseServiceHasWritePermission
extends Object

Constructor Summary	
public	CaseServiceHasWritePermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceHasWritePermission
public CaseServiceHasWritePermission()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceHasWritePermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasWritePermissionResponse

public class CaseServiceHasWritePermissionResponse
extends Object

Constructor Summary	
public	CaseServiceHasWritePermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceHasWritePermissionResponse
public CaseServiceHasWritePermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn


```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceHasXPermission



```
public class CaseServiceHasXPermission
extends Object
```

Constructor Summary	
public	CaseServiceHasXPermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceHasXPermission

```
public CaseServiceHasXPermission()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceHasXPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceHasXPermissionResponse

public class CaseServiceHasXPermissionResponse
extends Object

Constructor Summary	
public	CaseServiceHasXPermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceHasXPermissionResponse
public CaseServiceHasXPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceInsert

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceInsert

public class CaseServiceInsert

extends Object

Constructor Summary	
public	CaseServiceInsert()

Method Summary	
String	getAuthToken()
Case	getResource()
void	setAuthToken (String authToken)
void	setResource (Case resource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceInsert

public CaseServiceInsert()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Case getResource()
```

Returns:

returns Case

setResource


```
public void setResource(Case resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceInsertResource



```
public class CaseServiceInsertResource
extends Object
```

Constructor Summary	
public	CaseServiceInsertResource()

Method Summary	
String	getAuthToken()
String	getParentId()
Case	getResource()
void	setAuthToken (String authToken)
void	setParentId (String parentId)
void	setResource (Case resource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceInsertResource

```
public CaseServiceInsertResource()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Case getResource()
```

Returns:

returns Case

setResource

```
public void setResource(Case resource)
```

Parameters:

resource - the value for the resource property

getParentId

```
public String getParentId()
```

Returns:

returns String

setParentId

```
public void setParentId(String parentId)
```

Parameters:

parentId - the value for the parentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceInsertResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceInsertResourceResponse

public class CaseServiceInsertResourceResponse
extends Object

Constructor Summary	
public	CaseServiceInsertResourceResponse()

Method Summary	
Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceInsertResourceResponse
public CaseServiceInsertResourceResponse()

Methods

getReturn
public [Case](#) getReturn()

Returns:
returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceInsertResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceInsertResponse

public class CaseServiceInsertResponse
extends Object

Constructor Summary	
public	CaseServiceInsertResponse()

Method Summary	
Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceInsertResponse
public CaseServiceInsertResponse()

Methods

getReturn
public [Case](#) getReturn()

Returns:
returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceIsDisabled

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceIsDisabled

public class CaseServiceIsDisabled
extends Object

Constructor Summary	
public	CaseServiceIsDisabled()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceIsDisabled
public CaseServiceIsDisabled()

Methods

getAuthToken
public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceIsDisabledResponse

java.lang.Object

└─

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceIsDisabledResponse

public class CaseServiceIsDisabledResponse

extends Object

Constructor Summary	
public	CaseServiceIsDisabledResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceIsDisabledResponse

public CaseServiceIsDisabledResponse()

Methods

isReturn

public boolean isReturn()

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceIsValidResourceID

java.lang.Object

└─

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceIsValidResourceID

public class **CaseServiceIsValidResourceID**
extends Object

Constructor Summary	
public	CaseServiceIsValidResourceID()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceIsValidResourceID

public **CaseServiceIsValidResourceID**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceIsValidResourceIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceIsValidResourceIDResponse

public class CaseServiceIsValidResourceIDResponse
extends Object

Constructor Summary	
public	CaseServiceIsValidResourceIDResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceIsValidResourceIDResponse
public CaseServiceIsValidResourceIDResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceLoadAdditional

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceLoadAdditional

public class **CaseServiceLoadAdditional**
extends Object

Constructor Summary	
public	CaseServiceLoadAdditional()

Method Summary	
String	getAuthToken()
String	getSourceId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceLoadAdditional
public **CaseServiceLoadAdditional**()

Methods

getAuthToken
public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceLoadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceLoadAdditionalResponse

public class CaseServiceLoadAdditionalResponse
extends Object

Constructor Summary	
public	CaseServiceLoadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceLoadAdditionalResponse
public CaseServiceLoadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceOpenCases

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceOpenCases

public class CaseServiceOpenCases
extends Object

Constructor Summary	
public	CaseServiceOpenCases()

Method Summary	
String	getAuthToken()
String	getUserIds()
void	setAuthToken (String authToken)
void	setUserIds (String userIds)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceOpenCases
public CaseServiceOpenCases()

Methods

getAuthToken
public String getAuthToken()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getUserIds

public String **getUserIds**()

Returns:

returns String

setUserIds

public void **setUserIds**(String userIds)

Parameters:

userIds - the value for the userIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceOpenCasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceOpenCasesResponse

public class CaseServiceOpenCasesResponse
extends Object

Constructor Summary	
public	CaseServiceOpenCasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceOpenCasesResponse
public CaseServiceOpenCasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceResetState

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceResetState

public class **CaseServiceResetState**
extends Object

Constructor Summary

public	CaseServiceResetState()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceResetState

public **CaseServiceResetState()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceResetStateResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceResetStateResponse

```
public class CaseServiceResetStateResponse
extends Object
```

Constructor Summary

public	CaseServiceResetStateResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceResetStateResponse

```
public CaseServiceResetStateResponse()
```

Methods

getReturn

```
public Void getReturn()
```

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceResolveRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceResolveRelationship

public class **CaseServiceResolveRelationship**
extends Object

Constructor Summary

public	CaseServiceResolveRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceId(String sourceId)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceResolveRelationship

public **CaseServiceResolveRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceResolveRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceResolveRelationshipResponse

public class CaseServiceResolveRelationshipResponse
extends Object

Constructor Summary	
public	CaseServiceResolveRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceResolveRelationshipResponse
public CaseServiceResolveRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceSeverities

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceSeverities

public class **CaseServiceSeverities**
extends Object

Constructor Summary	
public	CaseServiceSeverities()

Method Summary	
String	getAuthToken()
String	getLocale()
void	setAuthToken(String authToken)
void	setLocale(String locale)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceSeverities
public **CaseServiceSeverities()**

Methods

getAuthToken
public String **getAuthToken()**

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getLocale

public String **getLocale**()

Returns:

returns String

setLocale

public void **setLocale**(String locale)

Parameters:

locale - the value for the locale property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceSeveritiesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceSeveritiesResponse

public class **CaseServiceSeveritiesResponse**
extends Object

Constructor Summary

public	CaseServiceSeveritiesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceSeveritiesResponse

public **CaseServiceSeveritiesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceStageTransitions

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceStageTransitions

public class CaseServiceStageTransitions
extends Object

Constructor Summary	
public	CaseServiceStageTransitions()

Method Summary	
String	getAssignee()
String	getAuthToken()
String	getEndTime()
String	getSeverity()
String	getStartTime()
void	setAssignee(String assignee)
void	setAuthToken(String authToken)
void	setEndTime(String endTime)
void	setSeverity(String severity)
void	setStartTime(String startTime)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceStageTransitions

```
public CaseServiceStageTransitions()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getStartTime

```
public String getStartTime()
```

Returns:

returns String

setStartTime

```
public void setStartTime(String startTime)
```

Parameters:

startTime - the value for the startTime property

getEndTime

```
public String getEndTime()
```

Returns:

returns String

setEndTime

public void **setEndTime**(String endTime)

Parameters:

endTime - the value for the endTime property

getSeverity

public String **getSeverity**()

Returns:

returns String

setSeverity

public void **setSeverity**(String severity)

Parameters:

severity - the value for the severity property

getAssignee

public String **getAssignee**()

Returns:

returns String

setAssignee

public void **setAssignee**(String assignee)

Parameters:

assignee - the value for the assignee property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceStageTransitionsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceStageTransitionsResponse

public class CaseServiceStageTransitionsResponse
extends Object

Constructor Summary	
public	CaseServiceStageTransitionsResponse()

Method Summary	
CaseStageTransitions	getReturn()
void	setReturn(CaseStageTransitions _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceStageTransitionsResponse
public CaseServiceStageTransitionsResponse()

Methods

getReturn
public [CaseStageTransitions](#) getReturn()

Returns:
returns CaseStageTransitions

setReturn

```
public void setReturn(CaseStageTransitions _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUnloadAdditional

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUnloadAdditional

public class CaseServiceUnloadAdditional
extends Object

Constructor Summary	
public	CaseServiceUnloadAdditional()

Method Summary	
String	getAuthToken()
String	getSourceId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceUnloadAdditional
public CaseServiceUnloadAdditional()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUnloadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUnloadAdditionalResponse

public class CaseServiceUnloadAdditionalResponse
extends Object

Constructor Summary	
public	CaseServiceUnloadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceUnloadAdditionalResponse
public CaseServiceUnloadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUpdate

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUpdate

public class **CaseServiceUpdate**
extends Object

Constructor Summary

public	CaseServiceUpdate()

Method Summary

String	getAuthToken()
Case	getResource()
void	setAuthToken (String authToken)
void	setResource (Case resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceUpdate

public **CaseServiceUpdate**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Case getResource()
```

Returns:

returns Case

setResource

```
public void setResource(Case resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceUpdateACLForResourceById

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUpdateACLForResourceById

public class **CaseServiceUpdateACLForResourceById**
extends Object

Constructor Summary

public	CaseServiceUpdateACLForResourceById()

Method Summary

String	getAuthToken()
List	getData()
String	getResourceId()
void	setAuthToken (String authToken)
void	setData (List data)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceUpdateACLForResourceById

public **CaseServiceUpdateACLForResourceById**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getData

```
public List getData()
```

Returns:

returns List

setData

```
public void setData(List data)
```

Parameters:

data - the value for the data property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class CaseServiceUpdateACLForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUpdateACLForResourceByIdResponse

```
public class CaseServiceUpdateACLForResourceByIdResponse
extends Object
```

Constructor Summary

public	CaseServiceUpdateACLForResourceByIdResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceUpdateACLForResourceByIdResponse

```
public CaseServiceUpdateACLForResourceByIdResponse()
```

Methods

getReturn

```
public Void getReturn()
```

Returns:

returns Void

setReturn


```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUpdateResources



```
public class CaseServiceUpdateResources
extends Object
```

Constructor Summary	
public	CaseServiceUpdateResources()

Method Summary	
String	getAuthToken()
List	getResources()
void	setAuthToken(String authToken)
void	setResources(List resources)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
CaseServiceUpdateResources
public CaseServiceUpdateResources()
```

Methods

```
getAuthToken
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUpdateResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUpdateResourcesResponse

public class CaseServiceUpdateResourcesResponse
extends Object

Constructor Summary	
public	CaseServiceUpdateResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceUpdateResourcesResponse
public CaseServiceUpdateResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class CaseServiceUpdateResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.CaseServiceUpdateResponse

public class CaseServiceUpdateResponse
extends Object

Constructor Summary	
public	CaseServiceUpdateResponse()

Method Summary	
Case	getReturn()
void	setReturn(Case _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseServiceUpdateResponse
public CaseServiceUpdateResponse()

Methods

getReturn
public [Case](#) getReturn()

Returns:
returns Case

setReturn

```
public void setReturn(Case _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GetDevicesForAgentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GetDevicesForAgentsResponse

public class **GetDevicesForAgentsResponse**
extends Object

Constructor Summary	
public	GetDevicesForAgentsResponse()

Method Summary	
HashMap	getReturn()
void	setReturn (HashMap _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GetDevicesForAgentsResponse
public **GetDevicesForAgentsResponse()**

Methods

getReturn
public HashMap **getReturn()**

Returns:
returns HashMap>

setReturn

```
public void setReturn(HashMap _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceAddChild

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddChild

public class GroupServiceAddChild

extends Object

Constructor Summary	
public	GroupServiceAddChild()

Method Summary	
String	getAuthToken()
String	getChildId()
String	getGroupId()
void	setAuthToken(String authToken)
void	setChildId(String childId)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object
<code>equals</code> , <code>getClass</code> , <code>hashCode</code> , <code>notify</code> , <code>notifyAll</code> , <code>toString</code> , <code>wait</code> , <code>wait</code> , <code>wait</code>

Constructors

GroupServiceAddChild

public GroupServiceAddChild()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChildId

```
public String getChildId()
```

Returns:

returns String

setChildId

```
public void setChildId(String childId)
```

Parameters:

childId - the value for the childId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceAddChildren

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddChildren

public class GroupServiceAddChildren

extends Object

Constructor Summary	
public	GroupServiceAddChildren()

Method Summary	
String	getAuthToken()
List	getChildren()
String	getGroupId()
void	setAuthToken(String authToken)
void	setChildren(List children)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object
<code>equals</code> , <code>getClass</code> , <code>hashCode</code> , <code>notify</code> , <code>notifyAll</code> , <code>toString</code> , <code>wait</code> , <code>wait</code> , <code>wait</code>

Constructors

GroupServiceAddChildren

public GroupServiceAddChildren()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChildren

```
public List getChildren()
```

Returns:

returns List

setChildren

```
public void setChildren(List children)
```

Parameters:

children - the value for the children property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceAddChildrenResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddChildrenResponse

public class GroupServiceAddChildrenResponse
extends Object

Constructor Summary	
public	GroupServiceAddChildrenResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceAddChildrenResponse
public GroupServiceAddChildrenResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceAddChildResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddChildResponse

public class GroupServiceAddChildResponse
extends Object

Constructor Summary	
public	GroupServiceAddChildResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceAddChildResponse
public GroupServiceAddChildResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceAddRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddRelationship

public class **GroupServiceAddRelationship**
extends Object

Constructor Summary

public	GroupServiceAddRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
String	getTargetResourceId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResourceId(String sourceResourceId)
void	setTargetResourceId(String targetResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceAddRelationship

public **GroupServiceAddRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getTargetResourceId

```
public String getTargetResourceId()
```

Returns:

returns String

setTargetResourceId

```
public void setTargetResourceId(String targetResourceId)
```

Parameters:

targetResourceId - the value for the targetResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceAddRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceAddRelationshipResponse

```
public class GroupServiceAddRelationshipResponse
extends Object
```

Constructor Summary

public	GroupServiceAddRelationshipResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceAddRelationshipResponse

```
public GroupServiceAddRelationshipResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceChildAttributesChanged

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceChildAttributesChanged

public class **GroupServiceChildAttributesChanged**
extends Object

Constructor Summary

public	GroupServiceChildAttributesChanged()

Method Summary

String	getAuthToken()
Resource	getChild()
String	getGroupId()
void	setAuthToken (String authToken)
void	setChild (Resource child)
void	setGroupId (String groupId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceChildAttributesChanged

public **GroupServiceChildAttributesChanged**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChild

```
public Resource getChild()
```

Returns:

returns Resource

setChild

```
public void setChild(Resource child)
```

Parameters:

child - the value for the child property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceChildAttributesChangedResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceChildAttributesChangedResponse

public class **GroupServiceChildAttributesChangedResponse**
extends Object

Constructor Summary

public	GroupServiceChildAttributesChangedResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceChildAttributesChangedResponse

public **GroupServiceChildAttributesChangedResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceContainsDirectMemberByNameOrAlias

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceContainsDirectMemberByNameOrAlias

public class **GroupServiceContainsDirectMemberByNameOrAlias**
extends Object

Constructor Summary

public	GroupServiceContainsDirectMemberByNameOrAlias()

Method Summary

String	getAuthToken()
String	getGroupId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceContainsDirectMemberByNameOrAlias

public **GroupServiceContainsDirectMemberByNameOrAlias**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceContainsDirectMemberByNameOrAliasResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceContainsDirectMemberByNameOrAliasResponse

public class **GroupServiceContainsDirectMemberByNameOrAliasResponse**
extends Object

Constructor Summary

public	GroupServiceContainsDirectMemberByNameOrAliasResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceContainsDirectMemberByNameOrAliasResponse

public **GroupServiceContainsDirectMemberByNameOrAliasResponse()**

Methods

isReturn

public boolean **isReturn()**

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceContainsResourcesRecursively

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceContainsResourcesRecursively

public class GroupServiceContainsResourcesRecursively
extends Object

Constructor Summary	
public	GroupServiceContainsResourcesRecursively()

Method Summary	
String	getAuthToken()
String	getGroupId()
int	getResourceType()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setResourceType (int resourceType)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceContainsResourcesRecursively
public GroupServiceContainsResourcesRecursively()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceContainsResourcesRecursivelyResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceContainsResourcesRecursivelyResponse

public class GroupServiceContainsResourcesRecursivelyResponse
extends Object

Constructor Summary

public	GroupServiceContainsResourcesRecursivelyResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceContainsResourcesRecursivelyResponse

public GroupServiceContainsResourcesRecursivelyResponse()

Methods

isReturn

public boolean isReturn()

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceCopyResourceIntoGroup

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceCopyResourceIntoGroup

```
public class GroupServiceCopyResourceIntoGroup  
extends Object
```

Constructor Summary

public	GroupServiceCopyResourceIntoGroup()

Method Summary

String	getAuthToken()
String	getNewName()
String	getNewParentId()
String	getOldParentId()
String	getResourceId()
void	setAuthToken(String authToken)
void	setNewName(String newName)
void	setNewParentId(String newParentId)
void	setOldParentId(String oldParentId)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceCopyResourceIntoGroup

```
public GroupServiceCopyResourceIntoGroup()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getNewName

```
public String getNewName()
```

Returns:

returns String

setNewName

```
public void setNewName(String newName)
```

Parameters:

newName - the value for the newName property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:

resourceId - the value for the resourceId property

getOldParentId

public String **getOldParentId**()

Returns:

returns String

setOldParentId

public void **setOldParentId**(String oldParentId)

Parameters:

oldParentId - the value for the oldParentId property

getNewParentId

public String **getNewParentId**()

Returns:

returns String

setNewParentId

public void **setNewParentId**(String newParentId)

Parameters:

newParentId - the value for the newParentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceCopyResourceIntoGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceCopyResourceIntoGroupResponse

public class GroupServiceCopyResourceIntoGroupResponse
extends Object

Constructor Summary	
public	GroupServiceCopyResourceIntoGroupResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceCopyResourceIntoGroupResponse
public GroupServiceCopyResourceIntoGroupResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDelete

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDelete

public class GroupServiceDelete

extends Object

Constructor Summary	
public	GroupServiceDelete()

Method Summary	
String	getAuthToken()
Group	getResource()
void	setAuthToken (String authToken)
void	setResource (Group resource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDelete

public GroupServiceDelete()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Group getResource()
```

Returns:

returns Group

setResource

```
public void setResource(Group resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteByLocalId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteByLocalId

public class **GroupServiceDeleteByLocalId**
extends Object

Constructor Summary

public	GroupServiceDeleteByLocalId()

Method Summary

String	getAuthToken()
long	getId()
void	setAuthToken(String authToken)
void	setId(long id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceDeleteByLocalId

public **GroupServiceDeleteByLocalId()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public long **getId**()

Returns:
returns long

setId

public void **setId**(long id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteByLocalIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteByLocalIdResponse

public class GroupServiceDeleteByLocalIdResponse
extends Object

Constructor Summary	
public	GroupServiceDeleteByLocalIdResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDeleteByLocalIdResponse
public GroupServiceDeleteByLocalIdResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteByUUID

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteByUUID

public class **GroupServiceDeleteByUUID**
extends Object

Constructor Summary

public	GroupServiceDeleteByUUID()

Method Summary

String	getAuthToken()
String	getId()
void	setAuthToken (String authToken)
void	setId (String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceDeleteByUUID

public **GroupServiceDeleteByUUID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getId

public String **getId**()

Returns:

returns String

setId

public void **setId**(String id)

Parameters:

id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteByUUIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteByUUIDResponse

public class GroupServiceDeleteByUUIDResponse
extends Object

Constructor Summary	
public	GroupServiceDeleteByUUIDResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDeleteByUUIDResponse

public GroupServiceDeleteByUUIDResponse()

Methods

getReturn

public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteResource

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteResource

public class GroupServiceDeleteResource
extends Object

Constructor Summary	
public	GroupServiceDeleteResource()

Method Summary	
String	getAuthToken()
Group	getResource()
boolean	isAbortTxOnValConflicts()
void	setAbortTxOnValConflicts (boolean abortTxOnValConflicts)
void	setAuthToken (String authToken)
void	setResource (Group resource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDeleteResource
public GroupServiceDeleteResource()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Group getResource()
```

Returns:

returns Group

setResource

```
public void setResource(Group resource)
```

Parameters:

resource - the value for the resource property

isAbortTxOnValConflicts

```
public boolean isAbortTxOnValConflicts()
```

Returns:

returns boolean

setAbortTxOnValConflicts

```
public void setAbortTxOnValConflicts(boolean abortTxOnValConflicts)
```

Parameters:

abortTxOnValConflicts - the value for the abortTxOnValConflicts property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteResourceResponse

public class GroupServiceDeleteResourceResponse
extends Object

Constructor Summary	
public	GroupServiceDeleteResourceResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDeleteResourceResponse
public GroupServiceDeleteResourceResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteResources

public class **GroupServiceDeleteResources**
extends Object

Constructor Summary

public	GroupServiceDeleteResources()

Method Summary

String	getAuthToken()
List	getResources()
void	setAuthToken() (String authToken)
void	setResources() (List resources)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceDeleteResources

public **GroupServiceDeleteResources()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteResourcesResponse

public class GroupServiceDeleteResourcesResponse
extends Object

Constructor Summary	
public	GroupServiceDeleteResourcesResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceDeleteResourcesResponse
public GroupServiceDeleteResourcesResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceDeleteResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceDeleteResponse

public class **GroupServiceDeleteResponse**
extends Object

Constructor Summary

public	GroupServiceDeleteResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceDeleteResponse

public **GroupServiceDeleteResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindAllIds

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindAllIds

public class GroupServiceFindAllIds
extends Object

Constructor Summary	
public	GroupServiceFindAllIds()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceFindAllIds
public GroupServiceFindAllIds()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindAllIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindAllIdsResponse

```
public class GroupServiceFindAllIdsResponse
extends Object
```

Constructor Summary

public	GroupServiceFindAllIdsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceFindAllIdsResponse

```
public GroupServiceFindAllIdsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindById

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindById

public class GroupServiceFindById

extends Object

Constructor Summary	
public	GroupServiceFindById()

Method Summary	
String	getAuthToken()
long	getLocalId()
void	setAuthToken (String authToken)
void	setLocalId (long localId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceFindById

public GroupServiceFindById()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getLocalId

```
public long getLocalId()
```

Returns:

returns long

setLocalId

```
public void setLocalId(long localId)
```

Parameters:

localId - the value for the localId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindByIdResponse

public class **GroupServiceFindByIdResponse**
extends Object

Constructor Summary

public	GroupServiceFindByIdResponse()

Method Summary

Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceFindByIdResponse

public **GroupServiceFindByIdResponse()**

Methods

getReturn

public [Group](#) **getReturn()**

Returns:

returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindByUUID

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindByUUID

public class **GroupServiceFindByUUID**
extends Object

Constructor Summary

public	GroupServiceFindByUUID()

Method Summary

String	getAuthToken()
String	getId()
void	setAuthToken (String authToken)
void	setId (String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceFindByUUID

public **GroupServiceFindByUUID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getId

public String **getId**()

Returns:

returns String

setId

public void **setId**(String id)

Parameters:

id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceFindByUUIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceFindByUUIDResponse

public class GroupServiceFindByUUIDResponse
extends Object

Constructor Summary	
public	GroupServiceFindByUUIDResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceFindByUUIDResponse
public GroupServiceFindByUUIDResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetAllAttachmentOnlyResourceIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllAttachmentOnlyResourceIDs

public class **GroupServiceGetAllAttachmentOnlyResourceIDs**
extends Object

Constructor Summary

public	GroupServiceGetAllAttachmentOnlyResourceIDs()

Method Summary

String	getAuthToken()

void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllAttachmentOnlyResourceIDs

public **GroupServiceGetAllAttachmentOnlyResourceIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllAttachmentOnlyResourceIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllAttachmentOnlyResourceIdsResponse

public class GroupServiceGetAllAttachmentOnlyResourceIdsResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllAttachmentOnlyResourceIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllAttachmentOnlyResourceIdsResponse
public GroupServiceGetAllAttachmentOnlyResourceIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllChildIDCount

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildIDCount

```
public class GroupServiceGetAllChildIDCount
extends Object
```

Constructor Summary

public	GroupServiceGetAllChildIDCount()

Method Summary

String	getAuthToken()
String	getGroupId()
void	setAuthToken(String authToken)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllChildIDCount

```
public GroupServiceGetAllChildIDCount()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getGroupId

public String **getGroupId**()

Returns:
returns String

setGroupId

public void **setGroupId**(String groupId)

Parameters:
groupId - the value for the groupId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetAllChildIDCountResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildIDCountResponse

```
public class GroupServiceGetAllChildIDCountResponse
extends Object
```

Constructor Summary

public	GroupServiceGetAllChildIDCountResponse()

Method Summary

int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllChildIDCountResponse

```
public GroupServiceGetAllChildIDCountResponse()
```

Methods

getReturn

```
public int getReturn()
```

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllChildIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildIDs

public class **GroupServiceGetAllChildIDs**
extends Object

Constructor Summary

public	GroupServiceGetAllChildIDs()

Method Summary

String	getAuthToken()
String	getGroupId()
void	setAuthToken(String authToken)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllChildIDs

public **GroupServiceGetAllChildIDs**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getGroupId

public String **getGroupId**()

Returns:
returns String

setGroupId

public void **setGroupId**(String groupId)

Parameters:
groupId - the value for the groupId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllChildIDsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildIDsResponse

public class GroupServiceGetAllChildIDsResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllChildIDsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllChildIDsResponse
public GroupServiceGetAllChildIDsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllChildren

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildren

public class **GroupServiceGetAllChildren**
extends Object

Constructor Summary	
public	GroupServiceGetAllChildren()

Method Summary	
String	getAuthToken()
String	getGroupId()
void	setAuthToken(String authToken)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

GroupServiceGetAllChildren

public **GroupServiceGetAllChildren**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getGroupId

public String **getGroupId**()

Returns:
returns String

setGroupId

public void **setGroupId**(String groupId)

Parameters:
groupId - the value for the groupId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllChildrenResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllChildrenResponse

public class GroupServiceGetAllChildrenResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllChildrenResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllChildrenResponse
public GroupServiceGetAllChildrenResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllowedUserTypes

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllowedUserTypes

public class GroupServiceGetAllowedUserTypes
extends Object

Constructor Summary	
public	GroupServiceGetAllowedUserTypes()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllowedUserTypes
public GroupServiceGetAllowedUserTypes()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllowedUserTypesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllowedUserTypesResponse

public class GroupServiceGetAllowedUserTypesResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllowedUserTypesResponse()

Method Summary	
String[]	getReturn()
void	setReturn(String[] _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllowedUserTypesResponse
public GroupServiceGetAllowedUserTypesResponse()

Methods

getReturn
public String[] getReturn()

Returns:
returns String[]

setReturn

```
public void setReturn(String[] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllPathsToRoot

java.lang.Object

└-

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllPathsToRoot

public class **GroupServiceGetAllPathsToRoot**
extends Object

Constructor Summary	
public	GroupServiceGetAllPathsToRoot()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllPathsToRoot

public **GroupServiceGetAllPathsToRoot**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetAllPathsToRootAsStrings

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllPathsToRootAsStrings

public class **GroupServiceGetAllPathsToRootAsStrings**
extends Object

Constructor Summary

public	GroupServiceGetAllPathsToRootAsStrings()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllPathsToRootAsStrings

public **GroupServiceGetAllPathsToRootAsStrings**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllPathsToRootAsStringsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllPathsToRootAsStringsResponse

public class GroupServiceGetAllPathsToRootAsStringsResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllPathsToRootAsStringsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllPathsToRootAsStringsResponse
public GroupServiceGetAllPathsToRootAsStringsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetAllPathsToRootResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllPathsToRootResponse

public class **GroupServiceGetAllPathsToRootResponse**
extends Object

Constructor Summary

public	GroupServiceGetAllPathsToRootResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetAllPathsToRootResponse

public **GroupServiceGetAllPathsToRootResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllUnassignedResourceIDs

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllUnassignedResourceIDs

public class GroupServiceGetAllUnassignedResourceIDs
extends Object

Constructor Summary	
public	GroupServiceGetAllUnassignedResourceIDs()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllUnassignedResourceIDs
public GroupServiceGetAllUnassignedResourceIDs()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetAllUnassignedResourceIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetAllUnassignedResourceIdsResponse

public class GroupServiceGetAllUnassignedResourceIdsResponse
extends Object

Constructor Summary	
public	GroupServiceGetAllUnassignedResourceIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetAllUnassignedResourceIdsResponse
public GroupServiceGetAllUnassignedResourceIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetChildIDByChildNameOrAlias

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildIDByChildNameOrAlias

public class **GroupServiceGetChildIDByChildNameOrAlias**
extends Object

Constructor Summary

public	GroupServiceGetChildIDByChildNameOrAlias()

Method Summary

String	getAlias()
String	getAuthToken()
String	getGroupId()
String	getName()
void	setAlias (String alias)
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setName (String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildIDByChildNameOrAlias

public **GroupServiceGetChildIDByChildNameOrAlias**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getAlias

```
public String getAlias()
```

Returns:

returns String

setAlias

```
public void setAlias(String alias)
```

Parameters:

alias - the value for the alias property

getName

public String **getName**()

Returns:

returns String

setName

public void **setName**(String name)

Parameters:

name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetChildIDByChildNameOrAliasResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildIDByChildNameOrAliasResponse

public class GroupServiceGetChildIDByChildNameOrAliasResponse
extends Object

Constructor Summary

public	GroupServiceGetChildIDByChildNameOrAliasResponse()

Method Summary

String	getReturn()

void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildIDByChildNameOrAliasResponse

public GroupServiceGetChildIDByChildNameOrAliasResponse()

Methods

getReturn

public String getReturn()

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetChildNamesAndAliases

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildNamesAndAliases

```
public class GroupServiceGetChildNamesAndAliases
extends Object
```

Constructor Summary

public	GroupServiceGetChildNamesAndAliases()

Method Summary

String	getAuthToken()
String	getGroupId()
List	getUnmappedIds()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setUnmappedIds (List unmappedIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildNamesAndAliases

```
public GroupServiceGetChildNamesAndAliases()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getUnmappedIds

```
public List getUnmappedIds()
```

Returns:

returns List

setUnmappedIds

```
public void setUnmappedIds(List unmappedIds)
```

Parameters:

unmappedIds - the value for the unmappedIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetChildNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildNamesAndAliasesResponse

public class GroupServiceGetChildNamesAndAliasesResponse
extends Object

Constructor Summary	
public	GroupServiceGetChildNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetChildNamesAndAliasesResponse
public GroupServiceGetChildNamesAndAliasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetChildrenByType

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildrenByType

public class **GroupServiceGetChildrenByType**
extends Object

Constructor Summary

public	GroupServiceGetChildrenByType()

Method Summary

String	getAuthToken()
String	getGroupId()
int	getResourceType()
void	setAuthToken() (String authToken)
void	setGroupId() (String groupId)
void	setResourceType() (int resourceType)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildrenByType

public **GroupServiceGetChildrenByType**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetChildrenByTypeResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildrenByTypeResponse

public class GroupServiceGetChildrenByTypeResponse
extends Object

Constructor Summary

public	GroupServiceGetChildrenByTypeResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildrenByTypeResponse

public GroupServiceGetChildrenByTypeResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetChildResourcesByType

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildResourcesByType

public class **GroupServiceGetChildResourcesByType**
extends Object

Constructor Summary

public	GroupServiceGetChildResourcesByType()

Method Summary

String	getAuthToken()
String	getGroupId()
int	getResourceType()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setResourceType (int resourceType)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildResourcesByType

public **GroupServiceGetChildResourcesByType**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetChildResourcesByTypeResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetChildResourcesByTypeResponse

public class **GroupServiceGetChildResourcesByTypeResponse**
extends Object

Constructor Summary

public	GroupServiceGetChildResourcesByTypeResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetChildResourcesByTypeResponse

public **GroupServiceGetChildResourcesByTypeResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetCorruptedResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetCorruptedResources

```
public class GroupServiceGetCorruptedResources
extends Object
```

Constructor Summary

public	GroupServiceGetCorruptedResources()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetCorruptedResources

```
public GroupServiceGetCorruptedResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetCorruptedResourcesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetCorruptedResourcesResponse

public class **GroupServiceGetCorruptedResourcesResponse**
extends Object

Constructor Summary

public	GroupServiceGetCorruptedResourcesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetCorruptedResourcesResponse

public **GroupServiceGetCorruptedResourcesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetDependentResourceIdsForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetDependentResourceIdsForResourceId

public class **GroupServiceGetDependentResourceIdsForResourceId**
extends Object

Constructor Summary

public	GroupServiceGetDependentResourceIdsForResourceId()

Method Summary

String	getAuthToken()
String	getResourceId()
boolean	isExcludeAttachmentOnlyResources()
boolean	isExcludeHiddenResources()
void	setAuthToken(String authToken)
void	setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
void	setExcludeHiddenResources(boolean excludeHiddenResources)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetDependentResourceIdsForResourceId

public **GroupServiceGetDependentResourceIdsForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

isExcludeHiddenResources

```
public boolean isExcludeHiddenResources()
```

Returns:

returns boolean

setExcludeHiddenResources

```
public void setExcludeHiddenResources(boolean excludeHiddenResources)
```

Parameters:

`excludeHiddenResources` - the value for the `excludeHiddenResources` property

isExcludeAttachmentOnlyResources

```
public boolean isExcludeAttachmentOnlyResources()
```

Returns:

returns boolean

setExcludeAttachmentOnlyResources

```
public void setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
```

Parameters:

`excludeAttachmentOnlyResources` - the value for the `excludeAttachmentOnlyResources` property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetDependentResourceIdsForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetDependentResourceIdsForResourceIdResponse

public class **GroupServiceGetDependentResourceIdsForResourceIdResponse**
extends Object

Constructor Summary

public	GroupServiceGetDependentResourceIdsForResourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetDependentResourceIdsForResourceIdResponse

public **GroupServiceGetDependentResourceIdsForResourceIdResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetEnabledResourceIDs

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetEnabledResourceIDs

```
public class GroupServiceGetEnabledResourceIDs
extends Object
```

Constructor Summary

public	GroupServiceGetEnabledResourceIDs()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetEnabledResourceIDs

```
public GroupServiceGetEnabledResourceIDs()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetEnabledResourceIDsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetEnabledResourceIDsResponse

public class GroupServiceGetEnabledResourceIDsResponse
extends Object

Constructor Summary	
public	GroupServiceGetEnabledResourceIDsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetEnabledResourceIDsResponse
public GroupServiceGetEnabledResourceIDsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetESMVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetESMVersion

public class **GroupServiceGetESMVersion**
extends Object

Constructor Summary

public	GroupServiceGetESMVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetESMVersion

public **GroupServiceGetESMVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetESMVersionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetESMVersionResponse

public class GroupServiceGetESMVersionResponse
extends Object

Constructor Summary	
public	GroupServiceGetESMVersionResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetESMVersionResponse
public GroupServiceGetESMVersionResponse()

Methods

getReturn
public String getReturn()

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetExclusivelyDependentResources

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetExclusivelyDependentResources

public class GroupServiceGetExclusivelyDependentResources
extends Object

Constructor Summary	
public	GroupServiceGetExclusivelyDependentResources()

Method Summary	
String	getAuthToken()
List	getExcludePathIdList()
String	getResourceId()
void	setAuthToken (String authToken)
void	setExcludePathIdList (List excludePathIdList)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetExclusivelyDependentResources
public GroupServiceGetExclusivelyDependentResources()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getExcludePathIdList

```
public List getExcludePathIdList()
```

Returns:

returns List

setExcludePathIdList

```
public void setExcludePathIdList(List excludePathIdList)
```

Parameters:

excludePathIdList - the value for the excludePathIdList property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetExclusivelyDependentResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetExclusivelyDependentResourcesResponse

public class GroupServiceGetExclusivelyDependentResourcesResponse
extends Object

Constructor Summary	
public	GroupServiceGetExclusivelyDependentResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetExclusivelyDependentResourcesResponse
public GroupServiceGetExclusivelyDependentResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetGroupByID

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupByID

public class GroupServiceGetGroupByID

extends Object

Constructor Summary	
public	GroupServiceGetGroupByID()

Method Summary	
String	getAuthToken()
String	getGroupId()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetGroupByID

public GroupServiceGetGroupByID()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetGroupByIDResponse

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupByIDResponse
```

public class GroupServiceGetGroupByIDResponse
extends Object

Constructor Summary

public	GroupServiceGetGroupByIDResponse()

Method Summary

Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetGroupByIDResponse
public GroupServiceGetGroupByIDResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetGroupByURI

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupByURI

public class GroupServiceGetGroupByURI
extends Object

Constructor Summary	
public	GroupServiceGetGroupByURI()

Method Summary	
String	getAuthToken()
String	getUri()
void	setAuthToken() (String authToken)
void	setUri() (String uri)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetGroupByURI
public GroupServiceGetGroupByURI()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getUri

public String **getUri**()

Returns:
returns String

setUri

public void **setUri**(String uri)

Parameters:
uri - the value for the uri property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetGroupByURIResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupByURIResponse

public class GroupServiceGetGroupByURIResponse
extends Object

Constructor Summary	
public	GroupServiceGetGroupByURIResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetGroupByURIResponse
public GroupServiceGetGroupByURIResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetGroupChildCount

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupChildCount

```
public class GroupServiceGetGroupChildCount
extends Object
```

Constructor Summary

public	GroupServiceGetGroupChildCount()

Method Summary

String	getAuthToken()
String	getGroupId()
void	setAuthToken(String authToken)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetGroupChildCount

```
public GroupServiceGetGroupChildCount()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getGroupId

public String **getGroupId**()

Returns:
returns String

setGroupId

public void **setGroupId**(String groupId)

Parameters:
groupId - the value for the groupId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetGroupChildCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetGroupChildCountResponse

public class GroupServiceGetGroupChildCountResponse
extends Object

Constructor Summary	
public	GroupServiceGetGroupChildCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetGroupChildCountResponse
public GroupServiceGetGroupChildCountResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetMetaGroup

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetMetaGroup

public class GroupServiceGetMetaGroup

extends Object

Constructor Summary	
public	GroupServiceGetMetaGroup()

Method Summary	
String	getAuthToken()
int	getResourceType()
void	setAuthToken(String authToken)
void	setResourceType(int resourceType)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetMetaGroup

public GroupServiceGetMetaGroup()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType


```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetMetaGroupID



public class GroupServiceGetMetaGroupID
extends Object

Constructor Summary	
public	GroupServiceGetMetaGroupID()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetMetaGroupID
public GroupServiceGetMetaGroupID()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetMetaGroupIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetMetaGroupIDResponse

public class GroupServiceGetMetaGroupIDResponse
extends Object

Constructor Summary	
public	GroupServiceGetMetaGroupIDResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetMetaGroupIDResponse
public GroupServiceGetMetaGroupIDResponse()

Methods

getReturn
public String getReturn()

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetMetaGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetMetaGroupResponse

public class GroupServiceGetMetaGroupResponse
extends Object

Constructor Summary	
public	GroupServiceGetMetaGroupResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetMetaGroupResponse
public GroupServiceGetMetaGroupResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetNamesAndAliases

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetNamesAndAliases
```

public class **GroupServiceGetNamesAndAliases**
extends Object

Constructor Summary	
public	GroupServiceGetNamesAndAliases()

Method Summary	
String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetNamesAndAliases
public **GroupServiceGetNamesAndAliases()**

Methods

getAuthToken
public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetNamesAndAliasesResponse

public class GroupServiceGetNamesAndAliasesResponse
extends Object

Constructor Summary	
public	GroupServiceGetNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetNamesAndAliasesResponse
public GroupServiceGetNamesAndAliasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetPersonalAndSharedResourceRoots

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalAndSharedResourceRoots

public class GroupServiceGetPersonalAndSharedResourceRoots
extends Object

Constructor Summary	
public	GroupServiceGetPersonalAndSharedResourceRoots()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getUserId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setUserId (String userId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetPersonalAndSharedResourceRoots
public GroupServiceGetPersonalAndSharedResourceRoots()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetPersonalAndSharedResourceRootsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalAndSharedResourceRootsResponse

public class GroupServiceGetPersonalAndSharedResourceRootsResponse
extends Object

Constructor Summary	
public	GroupServiceGetPersonalAndSharedResourceRootsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetPersonalAndSharedResourceRootsResponse
public GroupServiceGetPersonalAndSharedResourceRootsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetPersonalGroup

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalGroup

public class GroupServiceGetPersonalGroup
extends Object

Constructor Summary	
public	GroupServiceGetPersonalGroup()

Method Summary	
String	getAuthToken()
String	getUserId()
boolean	isThrowOnMissing()
void	setAuthToken (String authToken)
void	setThrowOnMissing (boolean throwOnMissing)
void	setUserId (String userId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetPersonalGroup
public GroupServiceGetPersonalGroup()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

isThrowOnMissing

```
public boolean isThrowOnMissing()
```

Returns:

returns boolean

setThrowOnMissing

```
public void setThrowOnMissing(boolean throwOnMissing)
```

Parameters:

throwOnMissing - the value for the throwOnMissing property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetPersonalGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalGroupResponse

public class GroupServiceGetPersonalGroupResponse
extends Object

Constructor Summary	
public	GroupServiceGetPersonalGroupResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetPersonalGroupResponse
public GroupServiceGetPersonalGroupResponse()

Methods

getReturn
public String getReturn()

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetPersonalResourceRoots

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalResourceRoots

public class **GroupServiceGetPersonalResourceRoots**
extends Object

Constructor Summary

public	GroupServiceGetPersonalResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getResourceId()
int	getResourceType()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setResourceId(String resourceId)
void	setResourceType(int resourceType)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetPersonalResourceRoots

public **GroupServiceGetPersonalResourceRoots()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```


Parameters:

relationshipType - the value for the relationshipType property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetPersonalResourceRootsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetPersonalResourceRootsResponse

```
public class GroupServiceGetPersonalResourceRootsResponse
extends Object
```

Constructor Summary

public	GroupServiceGetPersonalResourceRootsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetPersonalResourceRootsResponse

```
public GroupServiceGetPersonalResourceRootsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReferencePages

public class **GroupServiceGetReferencePages**
extends Object

Constructor Summary

public	GroupServiceGetReferencePages()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetReferencePages

public **GroupServiceGetReferencePages**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetReferencePagesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReferencePagesResponse

public class **GroupServiceGetReferencePagesResponse**
extends Object

Constructor Summary

public	GroupServiceGetReferencePagesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetReferencePagesResponse

public **GroupServiceGetReferencePagesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetRelationshipsOfParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetRelationshipsOfParents

```
public class GroupServiceGetRelationshipsOfParents
extends Object
```

Constructor Summary

public	GroupServiceGetRelationshipsOfParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetRelationshipsOfParents

```
public GroupServiceGetRelationshipsOfParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetRelationshipsOfParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetRelationshipsOfParentsResponse

```
public class GroupServiceGetRelationshipsOfParentsResponse
extends Object
```

Constructor Summary

public	GroupServiceGetRelationshipsOfParentsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetRelationshipsOfParentsResponse

```
public GroupServiceGetRelationshipsOfParentsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetRelationshipsOfThisAndParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetRelationshipsOfThisAndParents

public class **GroupServiceGetRelationshipsOfThisAndParents**
extends Object

Constructor Summary

public	GroupServiceGetRelationshipsOfThisAndParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetRelationshipsOfThisAndParents

public **GroupServiceGetRelationshipsOfThisAndParents**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetRelationshipsOfThisAndParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetRelationshipsOfThisAndParentsResponse

public class **GroupServiceGetRelationshipsOfThisAndParentsResponse**
extends Object

Constructor Summary

public	GroupServiceGetRelationshipsOfThisAndParentsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetRelationshipsOfThisAndParentsResponse

public **GroupServiceGetRelationshipsOfThisAndParentsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceById

public class **GroupServiceGetResourceById**
extends Object

Constructor Summary

public	GroupServiceGetResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceById

public **GroupServiceGetResourceById()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourceByIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceByIdResponse

public class GroupServiceGetResourceByIdResponse
extends Object

Constructor Summary	
public	GroupServiceGetResourceByIdResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetResourceByIdResponse
public GroupServiceGetResourceByIdResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourceByName

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceByName

```
public class GroupServiceGetResourceByName
extends Object
```

Constructor Summary

public	GroupServiceGetResourceByName()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken() (String authToken)
void	setName() (String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceByName

```
public GroupServiceGetResourceByName()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourceByNameResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceByNameResponse

public class GroupServiceGetResourceByNameResponse
extends Object

Constructor Summary	
public	GroupServiceGetResourceByNameResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetResourceByNameResponse
public GroupServiceGetResourceByNameResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourceIfModified

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceIfModified

```
public class GroupServiceGetResourceIfModified
extends Object
```

Constructor Summary

public	GroupServiceGetResourceIfModified()

Method Summary

String	getAuthToken()
ResourceSignature	getSignature()
void	setAuthToken (String authToken)
void	setSignature (ResourceSignature signature)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceIfModified

```
public GroupServiceGetResourceIfModified()
```

Methods

getAuthToken

```
public String getAuthToken()
```


Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSignature

public [ResourceSignature](#) **getSignature**()

Returns:
returns ResourceSignature

setSignature

public void **setSignature**([ResourceSignature](#) signature)

Parameters:
signature - the value for the signature property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourceIfModifiedResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceIfModifiedResponse

```
public class GroupServiceGetResourceIfModifiedResponse
extends Object
```

Constructor Summary

public	GroupServiceGetResourceIfModifiedResponse()

Method Summary

Group	getReturn()

void	setReturn(Group _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceIfModifiedResponse

```
public GroupServiceGetResourceIfModifiedResponse()
```

Methods

getReturn

```
public Group getReturn()
```

Returns:

returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourcesByIds

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByIds

public class **GroupServiceGetResourcesByIds**
extends Object

Constructor Summary

public	GroupServiceGetResourcesByIds()

Method Summary

String	getAuthToken()
List	getIds()
void	setAuthToken() (String authToken)
void	setIds() (List ids)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByIds

public **GroupServiceGetResourcesByIds()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getIds

public List **getIds**()

Returns:
returns List

setIds

public void **setIds**(List ids)

Parameters:
ids - the value for the ids property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesByIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByIdsResponse

public class **GroupServiceGetResourcesByIdsResponse**
extends Object

Constructor Summary

public	GroupServiceGetResourcesByIdsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByIdsResponse

public **GroupServiceGetResourcesByIdsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourcesByNames

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByNames

```
public class GroupServiceGetResourcesByNames
extends Object
```

Constructor Summary

public	GroupServiceGetResourcesByNames()

Method Summary

String	getAuthToken()
List	getNames()
void	setAuthToken(String authToken)
void	setNames(List names)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByNames

```
public GroupServiceGetResourcesByNames()
```

Methods

getAuthToken

```
public String getAuthToken()
```


Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getNames

public List **getNames**()

Returns:
returns List

setNames

public void **setNames**(List names)

Parameters:
names - the value for the names property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesByNameSafely

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByNameSafely

public class **GroupServiceGetResourcesByNameSafely**
extends Object

Constructor Summary

public	GroupServiceGetResourcesByNameSafely()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByNameSafely

public **GroupServiceGetResourcesByNameSafely()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesByNameSafelyResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByNameSafelyResponse

public class **GroupServiceGetResourcesByNameSafelyResponse**
extends Object

Constructor Summary

public	GroupServiceGetResourcesByNameSafelyResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByNameSafelyResponse

public **GroupServiceGetResourcesByNameSafelyResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesByNamesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesByNamesResponse

public class **GroupServiceGetResourcesByNamesResponse**
extends Object

Constructor Summary

public	GroupServiceGetResourcesByNamesResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesByNamesResponse

public **GroupServiceGetResourcesByNamesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesReferencePages

```
public class GroupServiceGetResourcesReferencePages
extends Object
```

Constructor Summary

public	GroupServiceGetResourcesReferencePages()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesReferencePages

```
public GroupServiceGetResourcesReferencePages()
```

Methods

getAuthToken

```
public String getAuthToken()
```


Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourcesReferencePagesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesReferencePagesResponse

public class GroupServiceGetResourcesReferencePagesResponse
extends Object

Constructor Summary	
public	GroupServiceGetResourcesReferencePagesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetResourcesReferencePagesResponse
public GroupServiceGetResourcesReferencePagesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesWithVisibilityToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesWithVisibilityToUsers

public class **GroupServiceGetResourcesWithVisibilityToUsers**
extends Object

Constructor Summary

public	GroupServiceGetResourcesWithVisibilityToUsers()

Method Summary

String	getAuthToken()

void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourcesWithVisibilityToUsers

public **GroupServiceGetResourcesWithVisibilityToUsers()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourcesWithVisibilityToUsersResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourcesWithVisibilityToUsersResponse

public class GroupServiceGetResourcesWithVisibilityToUsersResponse
extends Object

Constructor Summary	
public	GroupServiceGetResourcesWithVisibilityToUsersResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetResourcesWithVisibilityToUsersResponse
public GroupServiceGetResourcesWithVisibilityToUsersResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetResourceTypesVisibleToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceTypesVisibleToUsers

public class **GroupServiceGetResourceTypesVisibleToUsers**
extends Object

Constructor Summary

public	GroupServiceGetResourceTypesVisibleToUsers()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceTypesVisibleToUsers

public **GroupServiceGetResourceTypesVisibleToUsers**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetResourceTypesVisibleToUsersResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetResourceTypesVisibleToUsersResponse

public class GroupServiceGetResourceTypesVisibleToUsersResponse
extends Object

Constructor Summary

public	GroupServiceGetResourceTypesVisibleToUsersResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetResourceTypesVisibleToUsersResponse

public GroupServiceGetResourceTypesVisibleToUsersResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetReverseRelationshipsOfParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReverseRelationshipsOfParents

public class GroupServiceGetReverseRelationshipsOfParents
extends Object

Constructor Summary	
public	GroupServiceGetReverseRelationshipsOfParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetReverseRelationshipsOfParents
public GroupServiceGetReverseRelationshipsOfParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetReverseRelationshipsOfParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReverseRelationshipsOfParentsResponse

public class **GroupServiceGetReverseRelationshipsOfParentsResponse**
extends Object

Constructor Summary

public	GroupServiceGetReverseRelationshipsOfParentsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetReverseRelationshipsOfParentsResponse

public **GroupServiceGetReverseRelationshipsOfParentsResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetReverseRelationshipsOfThisAndParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReverseRelationshipsOfThisAndParents

public class GroupServiceGetReverseRelationshipsOfThisAndParents
extends Object

Constructor Summary	
public	GroupServiceGetReverseRelationshipsOfThisAndParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetReverseRelationshipsOfThisAndParents
public GroupServiceGetReverseRelationshipsOfThisAndParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetReverseRelationshipsOfThisAndParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetReverseRelationshipsOfThisAndParentsResponse

```
public class GroupServiceGetReverseRelationshipsOfThisAndParentsResponse
extends Object
```

Constructor Summary

public	GroupServiceGetReverseRelationshipsOfThisAndParentsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetReverseRelationshipsOfThisAndParentsResponse

```
public GroupServiceGetReverseRelationshipsOfThisAndParentsResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetServiceMajorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetServiceMajorVersion

public class **GroupServiceGetServiceMajorVersion**
extends Object

Constructor Summary

public	GroupServiceGetServiceMajorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetServiceMajorVersion

public **GroupServiceGetServiceMajorVersion**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetServiceMajorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetServiceMajorVersionResponse

public class **GroupServiceGetServiceMajorVersionResponse**
extends Object

Constructor Summary

public	GroupServiceGetServiceMajorVersionResponse()

Method Summary

int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetServiceMajorVersionResponse

public **GroupServiceGetServiceMajorVersionResponse**()

Methods

getReturn

public int **getReturn**()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetServiceMinorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetServiceMinorVersion

public class **GroupServiceGetServiceMinorVersion**
extends Object

Constructor Summary

public	GroupServiceGetServiceMinorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetServiceMinorVersion

public **GroupServiceGetServiceMinorVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetServiceMinorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetServiceMinorVersionResponse

public class **GroupServiceGetServiceMinorVersionResponse**
extends Object

Constructor Summary

public	GroupServiceGetServiceMinorVersionResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetServiceMinorVersionResponse

public **GroupServiceGetServiceMinorVersionResponse**()

Methods

getReturn

public int **getReturn**()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByACLRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByACLRelationship

public class **GroupServiceGetSourcesWithThisTargetByACLRelationship**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByACLRelationship()

Method Summary

String	getAuthToken()
String	getSourceResourceId()
void	setAuthToken(String authToken)
void	setSourceResourceId(String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByACLRelationship

public **GroupServiceGetSourcesWithThisTargetByACLRelationship**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceResourceId

public String **getSourceResourceId**()

Returns:
returns String

setSourceResourceId

public void **setSourceResourceId**(String sourceResourceId)

Parameters:
sourceResourceId - the value for the sourceResourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse

public class GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse

public GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationship

public class **GroupServiceGetSourcesWithThisTargetByRelationship**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationship

public **GroupServiceGetSourcesWithThisTargetByRelationship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByRelationshipCount

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationshipCount

public class **GroupServiceGetSourcesWithThisTargetByRelationshipCount**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationshipCount

public **GroupServiceGetSourcesWithThisTargetByRelationshipCount**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse

public class **GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse

public **GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse**()

Methods

getReturn

public int **getReturn**()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId

public class **GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId

public **GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public class GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourcesWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourcesWithThisTargetByRelationshipResponse

public class **GroupServiceGetSourcesWithThisTargetByRelationshipResponse**
extends Object

Constructor Summary

public	GroupServiceGetSourcesWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourcesWithThisTargetByRelationshipResponse

public **GroupServiceGetSourcesWithThisTargetByRelationshipResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelatiobnship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelatiobnship

```
public class GroupServiceGetSourceURIWithThisTargetByRelatiobnship
extends Object
```

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelatiobnship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelatiobnship

```
public GroupServiceGetSourceURIWithThisTargetByRelatiobnship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public class **GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId**
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public **GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

public class **GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse**
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

public **GroupServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

public class GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

public GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelationship

public class **GroupServiceGetSourceURIWithThisTargetByRelationship**
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelationship

public **GroupServiceGetSourceURIWithThisTargetByRelationship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public class GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public class GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetSourceURIWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetSourceURIWithThisTargetByRelationshipResponse

public class GroupServiceGetSourceURIWithThisTargetByRelationshipResponse
extends Object

Constructor Summary

public	GroupServiceGetSourceURIWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetSourceURIWithThisTargetByRelationshipResponse

public GroupServiceGetSourceURIWithThisTargetByRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsAsURIByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsAsURIByRelationship

```
public class GroupServiceGetTargetsAsURIByRelationship
extends Object
```

Constructor Summary

public	GroupServiceGetTargetsAsURIByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsAsURIByRelationship

```
public GroupServiceGetTargetsAsURIByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsAsURIByRelationshipForSourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsAsURIByRelationshipForSourceId

public class **GroupServiceGetTargetsAsURIByRelationshipForSourceId**
extends Object

Constructor Summary

public	GroupServiceGetTargetsAsURIByRelationshipForSourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsAsURIByRelationshipForSourceId

public **GroupServiceGetTargetsAsURIByRelationshipForSourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse

public class GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse
extends Object

Constructor Summary

public	GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse

public GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsAsURIByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsAsURIByRelationshipResponse

public class **GroupServiceGetTargetsAsURIByRelationshipResponse**
extends Object

Constructor Summary

public	GroupServiceGetTargetsAsURIByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsAsURIByRelationshipResponse

public **GroupServiceGetTargetsAsURIByRelationshipResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationship

```
public class GroupServiceGetTargetsByRelationship
extends Object
```

Constructor Summary

public	GroupServiceGetTargetsByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Group sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsByRelationship

```
public GroupServiceGetTargetsByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetTargetsByRelationshipCount

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationshipCount

public class **GroupServiceGetTargetsByRelationshipCount**
extends Object

Constructor Summary	
public	GroupServiceGetTargetsByRelationshipCount()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Group sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsByRelationshipCount
public **GroupServiceGetTargetsByRelationshipCount**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetTargetsByRelationshipCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationshipCountResponse

public class GroupServiceGetTargetsByRelationshipCountResponse
extends Object

Constructor Summary	
public	GroupServiceGetTargetsByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetTargetsByRelationshipCountResponse
public GroupServiceGetTargetsByRelationshipCountResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class GroupServiceGetTargetsByRelationshipForSourceId

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationshipForSourceId
```

public class GroupServiceGetTargetsByRelationshipForSourceId
extends Object

Constructor Summary	
public	GroupServiceGetTargetsByRelationshipForSourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsByRelationshipForSourceId
public GroupServiceGetTargetsByRelationshipForSourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetTargetsByRelationshipForSourceIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationshipForSourceIdResponse

public class GroupServiceGetTargetsByRelationshipForSourceIdResponse
extends Object

Constructor Summary	
public	GroupServiceGetTargetsByRelationshipForSourceIdResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceGetTargetsByRelationshipForSourceIdResponse
public GroupServiceGetTargetsByRelationshipForSourceIdResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsByRelationshipResponse

public class **GroupServiceGetTargetsByRelationshipResponse**
extends Object

Constructor Summary

public	GroupServiceGetTargetsByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsByRelationshipResponse

public **GroupServiceGetTargetsByRelationshipResponse**()

Methods

getReturn

public List **getReturn**()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsWithRelationshipTypeForResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsWithRelationshipTypeForResource

public class **GroupServiceGetTargetsWithRelationshipTypeForResource**
extends Object

Constructor Summary

public	GroupServiceGetTargetsWithRelationshipTypeForResource()

Method Summary

String	getAuthToken()
Group	getResource()
void	setAuthToken(String authToken)
void	setResource(Group resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsWithRelationshipTypeForResource

public **GroupServiceGetTargetsWithRelationshipTypeForResource()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResource

public [Group](#) **getResource**()

Returns:
returns Group

setResource

public void **setResource**([Group](#) resource)

Parameters:
resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceGetTargetsWithRelationshipTypeForResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsWithRelationshipTypeForResourceById

public class **GroupServiceGetTargetsWithRelationshipTypeForResourceById**
extends Object

Constructor Summary

public	GroupServiceGetTargetsWithRelationshipTypeForResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsWithRelationshipTypeForResourceById

public **GroupServiceGetTargetsWithRelationshipTypeForResourceById()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public class **GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse**
extends Object

Constructor Summary

public	GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public **GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceGetTargetsWithRelationshipTypeForResourceResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceGetTargetsWithRelationshipTypeForResourceResponse

public class **GroupServiceGetTargetsWithRelationshipTypeForResourceResponse**
extends Object

Constructor Summary

public	GroupServiceGetTargetsWithRelationshipTypeForResourceResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceGetTargetsWithRelationshipTypeForResourceResponse

public **GroupServiceGetTargetsWithRelationshipTypeForResourceResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceHasChildWithNameOrAlias

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasChildWithNameOrAlias

public class **GroupServiceHasChildWithNameOrAlias**
extends Object

Constructor Summary

public	GroupServiceHasChildWithNameOrAlias()

Method Summary

String	getAlias()
String	getAuthToken()
String	getGroupId()
String	getName()
void	setAlias(String alias)
void	setAuthToken(String authToken)
void	setGroupId(String groupId)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasChildWithNameOrAlias

public **GroupServiceHasChildWithNameOrAlias()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getAlias

```
public String getAlias()
```

Returns:

returns String

setAlias

```
public void setAlias(String alias)
```

Parameters:

`alias` - the value for the alias property

getName

public String **getName**()

Returns:

returns String

setName

public void **setName**(String name)

Parameters:

`name` - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasChildWithNameOrAliasResponse

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasChildWithNameOrAliasResponse
```

public class **GroupServiceHasChildWithNameOrAliasResponse**
extends Object

Constructor Summary	
public	GroupServiceHasChildWithNameOrAliasResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceHasChildWithNameOrAliasResponse
public **GroupServiceHasChildWithNameOrAliasResponse()**

Methods

isReturn
public boolean **isReturn()**

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasReadPermission

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasReadPermission

public class GroupServiceHasReadPermission
extends Object

Constructor Summary	
public	GroupServiceHasReadPermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

GroupServiceHasReadPermission
public GroupServiceHasReadPermission()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasReadPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasReadPermissionResponse

public class GroupServiceHasReadPermissionResponse
extends Object

Constructor Summary	
public	GroupServiceHasReadPermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceHasReadPermissionResponse
public GroupServiceHasReadPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasReverseRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasReverseRelationship

public class GroupServiceHasReverseRelationship
extends Object

Constructor Summary	
public	GroupServiceHasReverseRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Group	getSourceResource()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Group sourceResource)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasReverseRelationship
public GroupServiceHasReverseRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Group getSourceResource()
```

Returns:

returns Group

setSourceResource

```
public void setSourceResource(Group sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getTargetId

public String **getTargetId**()

Returns:

returns String

setTargetId

public void **setTargetId**(String targetId)

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceHasReverseRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasReverseRelationshipResponse

```
public class GroupServiceHasReverseRelationshipResponse
extends Object
```

Constructor Summary

public	GroupServiceHasReverseRelationshipResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasReverseRelationshipResponse

```
public GroupServiceHasReverseRelationshipResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasWritePermission

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasWritePermission

public class GroupServiceHasWritePermission
extends Object

Constructor Summary	
public	GroupServiceHasWritePermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasWritePermission
public GroupServiceHasWritePermission()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceHasWritePermissionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasWritePermissionResponse

public class GroupServiceHasWritePermissionResponse
extends Object

Constructor Summary

public	GroupServiceHasWritePermissionResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasWritePermissionResponse

public GroupServiceHasWritePermissionResponse()

Methods

isReturn

public boolean isReturn()

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceHasXPermission

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasXPermission

public class **GroupServiceHasXPermission**
extends Object

Constructor Summary

public	GroupServiceHasXPermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasXPermission

public **GroupServiceHasXPermission**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceHasXPermissionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceHasXPermissionResponse

```
public class GroupServiceHasXPermissionResponse
extends Object
```

Constructor Summary

public	GroupServiceHasXPermissionResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceHasXPermissionResponse

```
public GroupServiceHasXPermissionResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsert

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceInsert

public class **GroupServiceInsert**
extends Object

Constructor Summary

public	GroupServiceInsert()

Method Summary

String	getAuthToken()
Group	getResource()
void	setAuthToken (String authToken)
void	setResource (Group resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceInsert

public **GroupServiceInsert**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Group getResource()
```

Returns:

returns Group

setResource

```
public void setResource(Group resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsertGroup

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceInsertGroup

public class **GroupServiceInsertGroup**
extends Object

Constructor Summary

public	GroupServiceInsertGroup()

Method Summary

String	getAuthToken()
List	getChildren()
Group	getGroup()
String	getParentId()
void	setAuthToken(String authToken)
void	setChildren(List children)
void	setGroup(Group group)
void	setParentId(String parentId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceInsertGroup

public **GroupServiceInsertGroup**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroup

```
public Group getGroup()
```

Returns:

returns Group

setGroup

```
public void setGroup(Group group)
```

Parameters:

group - the value for the group property

getChildren

```
public List getChildren()
```

Returns:

returns List

setChildren

```
public void setChildren(List children)
```

Parameters:

children - the value for the children property

getParentId

public String **getParentId**()

Returns:

returns String

setParentId

public void **setParentId**(String parentId)

Parameters:

parentId - the value for the parentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsertGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceInsertGroupResponse

public class GroupServiceInsertGroupResponse
extends Object

Constructor Summary	
public	GroupServiceInsertGroupResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceInsertGroupResponse
public GroupServiceInsertGroupResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn


```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsertResource



public class GroupServiceInsertResource
extends Object

Constructor Summary	
public	GroupServiceInsertResource()

Method Summary	
String	getAuthToken()
String	getParentId()
Group	getResource()
void	setAuthToken (String authToken)
void	setParentId (String parentId)
void	setResource (Group resource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceInsertResource
public GroupServiceInsertResource()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Group getResource()
```

Returns:

returns Group

setResource

```
public void setResource(Group resource)
```

Parameters:

resource - the value for the resource property

getParentId

```
public String getParentId()
```

Returns:

returns String

setParentId

```
public void setParentId(String parentId)
```

Parameters:

parentId - the value for the parentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsertResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceInsertResourceResponse

public class GroupServiceInsertResourceResponse
extends Object

Constructor Summary	
public	GroupServiceInsertResourceResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceInsertResourceResponse
public GroupServiceInsertResourceResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn


```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceInsertResponse



public class GroupServiceInsertResponse
extends Object

Constructor Summary	
public	GroupServiceInsertResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

GroupServiceInsertResponse
public GroupServiceInsertResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsDisabled

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsDisabled

public class GroupServiceIsDisabled
extends Object

Constructor Summary	
public	GroupServiceIsDisabled()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceIsDisabled
public GroupServiceIsDisabled()

Methods

getAuthToken
public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsDisabledResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsDisabledResponse

public class GroupServiceIsDisabledResponse
extends Object

Constructor Summary	
public	GroupServiceIsDisabledResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceIsDisabledResponse
public GroupServiceIsDisabledResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServicelsGroup

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsGroup

public class GroupServicelsGroup
extends Object

Constructor Summary	
public	GroupServiceIsGroup()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServicelsGroup
public GroupServiceIsGroup()

Methods

getAuthToken
public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsGroupResponse

public class GroupServiceIsGroupResponse
extends Object

Constructor Summary	
public	GroupServiceIsGroupResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceIsGroupResponse
public GroupServiceIsGroupResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsParentOf

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsParentOf

public class GroupServiceIsParentOf

extends Object

Constructor Summary	
public	GroupServiceIsParentOf()

Method Summary	
String	getAuthToken()
Resource	getChild()
String	getGroupId()
void	setAuthToken(String authToken)
void	setChild(Resource child)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceIsParentOf

public GroupServiceIsParentOf()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChild

```
public Resource getChild()
```

Returns:

returns Resource

setChild

```
public void setChild(Resource child)
```

Parameters:

child - the value for the child property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsParentOfResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsParentOfResponse

public class GroupServiceIsParentOfResponse
extends Object

Constructor Summary	
public	GroupServiceIsParentOfResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceIsParentOfResponse
public GroupServiceIsParentOfResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsValidResourceID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsValidResourceID

public class **GroupServiceIsValidResourceID**
extends Object

Constructor Summary

public	GroupServiceIsValidResourceID()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceIsValidResourceID

public **GroupServiceIsValidResourceID**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceIsValidResourceIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceIsValidResourceIDResponse

public class GroupServiceIsValidResourceIDResponse
extends Object

Constructor Summary	
public	GroupServiceIsValidResourceIDResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceIsValidResourceIDResponse
public GroupServiceIsValidResourceIDResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn


```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceLoadAdditional



public class **GroupServiceLoadAdditional**
extends Object

Constructor Summary	
public	GroupServiceLoadAdditional()

Method Summary	
String	getAuthToken()
String	getSourceId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceLoadAdditional

public **GroupServiceLoadAdditional**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceLoadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceLoadAdditionalResponse

public class GroupServiceLoadAdditionalResponse
extends Object

Constructor Summary	
public	GroupServiceLoadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceLoadAdditionalResponse
public GroupServiceLoadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceRemoveChild

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceRemoveChild

public class GroupServiceRemoveChild

extends Object

Constructor Summary	
public	GroupServiceRemoveChild()

Method Summary	
String	getAuthToken()
String	getChildId()
String	getGroupId()
void	setAuthToken(String authToken)
void	setChildId(String childId)
void	setGroupId(String groupId)

Methods inherited from class java.lang.Object
<code>equals</code> , <code>getClass</code> , <code>hashCode</code> , <code>notify</code> , <code>notifyAll</code> , <code>toString</code> , <code>wait</code> , <code>wait</code> , <code>wait</code>

Constructors

GroupServiceRemoveChild

public GroupServiceRemoveChild()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChildId

```
public String getChildId()
```

Returns:

returns String

setChildId

```
public void setChildId(String childId)
```

Parameters:

childId - the value for the childId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceRemoveChildren

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceRemoveChildren

public class **GroupServiceRemoveChildren**
extends Object

Constructor Summary

public	GroupServiceRemoveChildren()

Method Summary

String	getAuthToken()
List	getChildren()
String	getGroupId()
void	setAuthToken (String authToken)
void	setChildren (List children)
void	setGroupId (String groupId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceRemoveChildren

public **GroupServiceRemoveChildren**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getChildren

```
public List getChildren()
```

Returns:

returns List

setChildren

```
public void setChildren(List children)
```

Parameters:

children - the value for the children property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceRemoveChildrenResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceRemoveChildrenResponse

public class GroupServiceRemoveChildrenResponse
extends Object

Constructor Summary	
public	GroupServiceRemoveChildrenResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceRemoveChildrenResponse
public GroupServiceRemoveChildrenResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceRemoveChildResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceRemoveChildResponse

public class GroupServiceRemoveChildResponse
extends Object

Constructor Summary	
public	GroupServiceRemoveChildResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceRemoveChildResponse
public GroupServiceRemoveChildResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceResetState

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceResetState

public class GroupServiceResetState
extends Object

Constructor Summary	
public	GroupServiceResetState()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceResetState
public GroupServiceResetState()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceResetStateResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceResetStateResponse

public class GroupServiceResetStateResponse
extends Object

Constructor Summary	
public	GroupServiceResetStateResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceResetStateResponse
public GroupServiceResetStateResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceResolveRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceResolveRelationship

```
public class GroupServiceResolveRelationship
extends Object
```

Constructor Summary

public	GroupServiceResolveRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceId(String sourceId)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceResolveRelationship

```
public GroupServiceResolveRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class GroupServiceResolveRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceResolveRelationshipResponse

```
public class GroupServiceResolveRelationshipResponse
extends Object
```

Constructor Summary

public	GroupServiceResolveRelationshipResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceResolveRelationshipResponse

```
public GroupServiceResolveRelationshipResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUnloadAdditional

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUnloadAdditional

public class **GroupServiceUnloadAdditional**
extends Object

Constructor Summary

public	GroupServiceUnloadAdditional()

Method Summary

String	getAuthToken()
String	getSourceId()
void	setAuthToken(String authToken)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceUnloadAdditional

public **GroupServiceUnloadAdditional**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUnloadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUnloadAdditionalResponse

public class GroupServiceUnloadAdditionalResponse
extends Object

Constructor Summary	
public	GroupServiceUnloadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUnloadAdditionalResponse
public GroupServiceUnloadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdate

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdate

public class **GroupServiceUpdate**
extends Object

Constructor Summary

public	GroupServiceUpdate()

Method Summary

String	getAuthToken()
Group	getResource()
void	setAuthToken (String authToken)
void	setResource (Group resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceUpdate

public **GroupServiceUpdate**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Group getResource()
```

Returns:

returns Group

setResource

```
public void setResource(Group resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateACLForResourceById

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateACLForResourceById

public class GroupServiceUpdateACLForResourceById
extends Object

Constructor Summary	
public	GroupServiceUpdateACLForResourceById()

Method Summary	
String	getAuthToken()
List	getData()
String	getResourceId()
void	setAuthToken (String authToken)
void	setData (List data)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceUpdateACLForResourceById
public GroupServiceUpdateACLForResourceById()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getData

```
public List getData()
```

Returns:

returns List

setData

```
public void setData(List data)
```

Parameters:

data - the value for the data property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateACLForResourceByIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateACLForResourceByIdResponse

public class GroupServiceUpdateACLForResourceByIdResponse
extends Object

Constructor Summary	
public	GroupServiceUpdateACLForResourceByIdResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUpdateACLForResourceByIdResponse
public GroupServiceUpdateACLForResourceByIdResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateGroup

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateGroup

public class **GroupServiceUpdateGroup**
extends Object

Constructor Summary

public	GroupServiceUpdateGroup()

Method Summary

List	getAddList()
String	getAuthToken()
Group	getGroup()
List	getRemoveList()
void	setAddList (List addList)
void	setAuthToken (String authToken)
void	setGroup (Group group)
void	setRemoveList (List removeList)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceUpdateGroup

public **GroupServiceUpdateGroup**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroup

```
public Group getGroup()
```

Returns:

returns Group

setGroup

```
public void setGroup(Group group)
```

Parameters:

group - the value for the group property

getAddList

```
public List getAddList()
```

Returns:

returns List

setAddList

```
public void setAddList(List addList)
```

Parameters:

addList - the value for the addList property

getRemoveList

```
public List getRemoveList()
```

Returns:

returns List

setRemoveList

```
public void setRemoveList(List removeList)
```

Parameters:

removeList - the value for the removeList property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateGroupResponse

public class GroupServiceUpdateGroupResponse
extends Object

Constructor Summary	
public	GroupServiceUpdateGroupResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUpdateGroupResponse
public GroupServiceUpdateGroupResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateResources

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateResources

public class GroupServiceUpdateResources
extends Object

Constructor Summary	
public	GroupServiceUpdateResources()

Method Summary	
String	getAuthToken()
List	getResources()
void	setAuthToken(String authToken)
void	setResources(List resources)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUpdateResources
public GroupServiceUpdateResources()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateResourcesResponse

public class GroupServiceUpdateResourcesResponse
extends Object

Constructor Summary	
public	GroupServiceUpdateResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUpdateResourcesResponse
public GroupServiceUpdateResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class GroupServiceUpdateResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.GroupServiceUpdateResponse

public class GroupServiceUpdateResponse
extends Object

Constructor Summary	
public	GroupServiceUpdateResponse()

Method Summary	
Group	getReturn()
void	setReturn(Group _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GroupServiceUpdateResponse
public GroupServiceUpdateResponse()

Methods

getReturn
public [Group](#) getReturn()

Returns:
returns Group

setReturn

```
public void setReturn(Group _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ModelLoader

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ModelLoader

public final class **ModelLoader**
extends Object

Constructor Summary	
public	ModelLoader()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ModelLoader
public **ModelLoader()**

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ObjectFactory

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ObjectFactory

public final class **ObjectFactory**
extends Object

Constructor Summary	
public	ObjectFactory()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ObjectFactory
public **ObjectFactory**()

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceAddRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceAddRelationship

public class **ReportServiceAddRelationship**
extends Object

Constructor Summary

public	ReportServiceAddRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
String	getTargetResourceId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResourceId(String sourceResourceId)
void	setTargetResourceId(String targetResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceAddRelationship

public **ReportServiceAddRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getTargetResourceId

```
public String getTargetResourceId()
```

Returns:

returns String

setTargetResourceId

```
public void setTargetResourceId(String targetResourceId)
```


Parameters:

targetResourceId - the value for the targetResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceAddRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceAddRelationshipResponse

```
public class ReportServiceAddRelationshipResponse
extends Object
```

Constructor Summary

public	ReportServiceAddRelationshipResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceAddRelationshipResponse

```
public ReportServiceAddRelationshipResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceContainsDirectMemberByNameOrAlias

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceContainsDirectMemberByNameOrAlias

public class **ReportServiceContainsDirectMemberByNameOrAlias**
extends Object

Constructor Summary

public	ReportServiceContainsDirectMemberByNameOrAlias()

Method Summary

String	getAuthToken()
String	getGroupId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceContainsDirectMemberByNameOrAlias

public **ReportServiceContainsDirectMemberByNameOrAlias**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceContainsDirectMemberByNameOrAliasResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceContainsDirectMemberByNameOrAliasResponse

public class ReportServiceContainsDirectMemberByNameOrAliasResponse
extends Object

Constructor Summary	
public	ReportServiceContainsDirectMemberByNameOrAliasResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceContainsDirectMemberByNameOrAliasResponse

public ReportServiceContainsDirectMemberByNameOrAliasResponse()

Methods

isReturn

public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceCopyResourceIntoGroup

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceCopyResourceIntoGroup

```
public class ReportServiceCopyResourceIntoGroup
extends Object
```

Constructor Summary

public	ReportServiceCopyResourceIntoGroup()

Method Summary

String	getAuthToken()
String	getNewName()
String	getNewParentId()
String	getOldParentId()
String	getResourceId()
void	setAuthToken(String authToken)
void	setNewName(String newName)
void	setNewParentId(String newParentId)
void	setOldParentId(String oldParentId)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceCopyResourceIntoGroup

public **ReportServiceCopyResourceIntoGroup**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getNewName

public String **getNewName**()

Returns:

returns String

setNewName

public void **setNewName**(String newName)

Parameters:

newName - the value for the newName property

getResourceId

public String **getResourceId**()

Returns:

returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:

resourceId - the value for the resourceId property

getOldParentId

public String **getOldParentId**()

Returns:

returns String

setOldParentId

public void **setOldParentId**(String oldParentId)

Parameters:

oldParentId - the value for the oldParentId property

getNewParentId

public String **getNewParentId**()

Returns:

returns String

setNewParentId

public void **setNewParentId**(String newParentId)

Parameters:

newParentId - the value for the newParentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceCopyResourceIntoGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceCopyResourceIntoGroupResponse

public class ReportServiceCopyResourceIntoGroupResponse
extends Object

Constructor Summary	
public	ReportServiceCopyResourceIntoGroupResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceCopyResourceIntoGroupResponse

public ReportServiceCopyResourceIntoGroupResponse()

Methods

getReturn

public [Report](#) getReturn()

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDelete

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDelete

public class **ReportServiceDelete**
extends Object

Constructor Summary

public	ReportServiceDelete()

Method Summary

String	getAuthToken()
Report	getResource()
void	setAuthToken (String authToken)
void	setResource (Report resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceDelete

public **ReportServiceDelete**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Report getResource()
```

Returns:

returns Report

setResource

```
public void setResource(Report resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteByLocalId

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteByLocalId

public class ReportServiceDeleteByLocalId
extends Object

Constructor Summary	
public	ReportServiceDeleteByLocalId()

Method Summary	
String	getAuthToken()
long	getId()
void	setAuthToken(String authToken)
void	setId(long id)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteByLocalId
public ReportServiceDeleteByLocalId()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public long **getId**()

Returns:
returns long

setId

public void **setId**(long id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteByLocalIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteByLocalIdResponse

public class ReportServiceDeleteByLocalIdResponse
extends Object

Constructor Summary	
public	ReportServiceDeleteByLocalIdResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteByLocalIdResponse
public ReportServiceDeleteByLocalIdResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteByUUID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteByUUID

public class **ReportServiceDeleteByUUID**
extends Object

Constructor Summary

public	ReportServiceDeleteByUUID()

Method Summary

String	getAuthToken()

String	getId()

void	setAuthToken(String authToken)

void	setId(String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceDeleteByUUID

public **ReportServiceDeleteByUUID()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public String **getId**()

Returns:
returns String

setId

public void **setId**(String id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteByUUIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteByUUIDResponse

public class ReportServiceDeleteByUUIDResponse
extends Object

Constructor Summary	
public	ReportServiceDeleteByUUIDResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteByUUIDResponse
public ReportServiceDeleteByUUIDResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteResource

public class **ReportServiceDeleteResource**
extends Object

Constructor Summary

public	ReportServiceDeleteResource()

Method Summary

String	getAuthToken()
Report	getResource()
boolean	isAbortTxOnValConflicts()
void	setAbortTxOnValConflicts (boolean abortTxOnValConflicts)
void	setAuthToken (String authToken)
void	setResource (Report resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceDeleteResource

public **ReportServiceDeleteResource**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Report getResource()
```

Returns:

returns Report

setResource

```
public void setResource(Report resource)
```

Parameters:

resource - the value for the resource property

isAbortTxOnValConflicts

```
public boolean isAbortTxOnValConflicts()
```

Returns:

returns boolean

setAbortTxOnValConflicts

```
public void setAbortTxOnValConflicts(boolean abortTxOnValConflicts)
```

Parameters:

abortTxOnValConflicts - the value for the abortTxOnValConflicts property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteResourceResponse

public class ReportServiceDeleteResourceResponse
extends Object

Constructor Summary	
public	ReportServiceDeleteResourceResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteResourceResponse

public ReportServiceDeleteResourceResponse()

Methods

getReturn

public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteResources

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteResources

public class **ReportServiceDeleteResources**
extends Object

Constructor Summary	
public	ReportServiceDeleteResources()

Method Summary	
String	getAuthToken()
List	getResources()
void	setAuthToken (String authToken)
void	setResources (List resources)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteResources
public **ReportServiceDeleteResources**()

Methods

getAuthToken
public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteResourcesResponse

public class ReportServiceDeleteResourcesResponse
extends Object

Constructor Summary	
public	ReportServiceDeleteResourcesResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteResourcesResponse
public ReportServiceDeleteResourcesResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceDeleteResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceDeleteResponse

public class ReportServiceDeleteResponse
extends Object

Constructor Summary	
public	ReportServiceDeleteResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceDeleteResponse
public ReportServiceDeleteResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindAllIds

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindAllIds

public class **ReportServiceFindAllIds**
extends Object

Constructor Summary	
public	ReportServiceFindAllIds()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceFindAllIds
public **ReportServiceFindAllIds()**

Methods

getAuthToken
public String **getAuthToken()**

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindAllIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindAllIdsResponse

public class ReportServiceFindAllIdsResponse
extends Object

Constructor Summary	
public	ReportServiceFindAllIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceFindAllIdsResponse
public ReportServiceFindAllIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindById

```
java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindById
```

```
public class ReportServiceFindById
extends Object
```

Constructor Summary	
public	ReportServiceFindById()

Method Summary	
String	getAuthToken()
long	getLocalId()
void	setAuthToken (String authToken)
void	setLocalId (long localId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
ReportServiceFindById
public ReportServiceFindById()
```

Methods

```
getAuthToken
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getLocalId

```
public long getLocalId()
```

Returns:

returns long

setLocalId

```
public void setLocalId(long localId)
```

Parameters:

localId - the value for the localId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindByIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindByIdResponse

public class ReportServiceFindByIdResponse
extends Object

Constructor Summary	
public	ReportServiceFindByIdResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceFindByIdResponse
public ReportServiceFindByIdResponse()

Methods

getReturn
public [Report](#) getReturn()

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindByUUID

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindByUUID

public class **ReportServiceFindByUUID**
extends Object

Constructor Summary

public	ReportServiceFindByUUID()

Method Summary

String	getAuthToken()
String	getId()
void	setAuthToken (String authToken)
void	setId (String id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceFindByUUID

public **ReportServiceFindByUUID**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getId

```
public String getId()
```

Returns:

returns String

setId

```
public void setId(String id)
```

Parameters:

id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceFindByUUIDResponse

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceFindByUUIDResponse
```

```
public class ReportServiceFindByUUIDResponse
extends Object
```

Constructor Summary	
public	ReportServiceFindByUUIDResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
ReportServiceFindByUUIDResponse
public ReportServiceFindByUUIDResponse()
```

Methods

```
getReturn
public Report getReturn()
```

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllAttachmentOnlyResourceIDs

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllAttachmentOnlyResourceIDs

public class ReportServiceGetAllAttachmentOnlyResourceIDs
extends Object

Constructor Summary	
public	ReportServiceGetAllAttachmentOnlyResourceIDs()

Method Summary	
String	getAuthToken()
void	setAuthToken (String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllAttachmentOnlyResourceIDs
public ReportServiceGetAllAttachmentOnlyResourceIDs()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllAttachmentOnlyResourceIDsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllAttachmentOnlyResourceIDsResponse

public class ReportServiceGetAllAttachmentOnlyResourceIDsResponse
extends Object

Constructor Summary	
public	ReportServiceGetAllAttachmentOnlyResourceIDsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllAttachmentOnlyResourceIDsResponse

public ReportServiceGetAllAttachmentOnlyResourceIDsResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllowedUserTypes

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllowedUserTypes

public class ReportServiceGetAllowedUserTypes
extends Object

Constructor Summary	
public	ReportServiceGetAllowedUserTypes()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllowedUserTypes

public ReportServiceGetAllowedUserTypes()

Methods

getAuthToken

public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllowedUserTypesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllowedUserTypesResponse

public class ReportServiceGetAllowedUserTypesResponse
extends Object

Constructor Summary	
public	ReportServiceGetAllowedUserTypesResponse()

Method Summary	
String[]	getReturn()
void	setReturn(String[] _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllowedUserTypesResponse
public ReportServiceGetAllowedUserTypesResponse()

Methods

getReturn
public String[] getReturn()

Returns:
returns String[]

setReturn

```
public void setReturn(String[] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllPathsToRoot

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllPathsToRoot

```
public class ReportServiceGetAllPathsToRoot
extends Object
```

Constructor Summary

public	ReportServiceGetAllPathsToRoot()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetAllPathsToRoot

```
public ReportServiceGetAllPathsToRoot()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllPathsToRootAsStrings

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllPathsToRootAsStrings

public class ReportServiceGetAllPathsToRootAsStrings
extends Object

Constructor Summary	
public	ReportServiceGetAllPathsToRootAsStrings()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetAllPathsToRootAsStrings
public ReportServiceGetAllPathsToRootAsStrings()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllPathsToRootAsStringsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllPathsToRootAsStringsResponse

public class ReportServiceGetAllPathsToRootAsStringsResponse
extends Object

Constructor Summary	
public	ReportServiceGetAllPathsToRootAsStringsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllPathsToRootAsStringsResponse

public ReportServiceGetAllPathsToRootAsStringsResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllPathsToRootResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllPathsToRootResponse

public class ReportServiceGetAllPathsToRootResponse
extends Object

Constructor Summary	
public	ReportServiceGetAllPathsToRootResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllPathsToRootResponse
public ReportServiceGetAllPathsToRootResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllUnassignedResourceIDs

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllUnassignedResourceIDs

public class ReportServiceGetAllUnassignedResourceIDs
extends Object

Constructor Summary	
public	ReportServiceGetAllUnassignedResourceIDs()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllUnassignedResourceIDs
public ReportServiceGetAllUnassignedResourceIDs()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetAllUnassignedResourceIDsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetAllUnassignedResourceIDsResponse

public class ReportServiceGetAllUnassignedResourceIDsResponse
extends Object

Constructor Summary	
public	ReportServiceGetAllUnassignedResourceIDsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetAllUnassignedResourceIDsResponse

public ReportServiceGetAllUnassignedResourceIDsResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetChildNamesAndAliases

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetChildNamesAndAliases

public class ReportServiceGetChildNamesAndAliases
extends Object

Constructor Summary	
public	ReportServiceGetChildNamesAndAliases()

Method Summary	
String	getAuthToken()
String	getGroupId()
List	getUnmappedIds()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setUnmappedIds (List unmappedIds)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetChildNamesAndAliases
public ReportServiceGetChildNamesAndAliases()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getUnmappedIds

```
public List getUnmappedIds()
```

Returns:

returns List

setUnmappedIds

```
public void setUnmappedIds(List unmappedIds)
```

Parameters:

unmappedIds - the value for the unmappedIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetChildNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetChildNamesAndAliasesResponse

public class ReportServiceGetChildNamesAndAliasesResponse
extends Object

Constructor Summary	
public	ReportServiceGetChildNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetChildNamesAndAliasesResponse

public ReportServiceGetChildNamesAndAliasesResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetCorruptedResources

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetCorruptedResources

public class ReportServiceGetCorruptedResources
extends Object

Constructor Summary	
public	ReportServiceGetCorruptedResources()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetCorruptedResources
public ReportServiceGetCorruptedResources()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetCorruptedResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetCorruptedResourcesResponse

public class ReportServiceGetCorruptedResourcesResponse
extends Object

Constructor Summary	
public	ReportServiceGetCorruptedResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetCorruptedResourcesResponse

public ReportServiceGetCorruptedResourcesResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetDependentResourceIdsForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetDependentResourceIdsForResourceId

public class ReportServiceGetDependentResourceIdsForResourceId
extends Object

Constructor Summary

public	ReportServiceGetDependentResourceIdsForResourceId()

Method Summary

String	getAuthToken()
String	getResourceId()
boolean	isExcludeAttachmentOnlyResources()
boolean	isExcludeHiddenResources()
void	setAuthToken(String authToken)
void	setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
void	setExcludeHiddenResources(boolean excludeHiddenResources)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetDependentResourceIdsForResourceId

public ReportServiceGetDependentResourceIdsForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

isExcludeHiddenResources

```
public boolean isExcludeHiddenResources()
```

Returns:

returns boolean

setExcludeHiddenResources

```
public void setExcludeHiddenResources(boolean excludeHiddenResources)
```

Parameters:

`excludeHiddenResources` - the value for the `excludeHiddenResources` property

isExcludeAttachmentOnlyResources

```
public boolean isExcludeAttachmentOnlyResources()
```

Returns:

returns boolean

setExcludeAttachmentOnlyResources

```
public void setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
```

Parameters:

`excludeAttachmentOnlyResources` - the value for the `excludeAttachmentOnlyResources` property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetDependentResourceIdsForResourceIdResponse



public class ReportServiceGetDependentResourceIdsForResourceIdResponse
extends Object

Constructor Summary	
public	ReportServiceGetDependentResourceIdsForResourceIdResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetDependentResourceIdsForResourceIdResponse

public ReportServiceGetDependentResourceIdsForResourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetEnabledResourceIDs

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetEnabledResourceIDs

```
public class ReportServiceGetEnabledResourceIDs
extends Object
```

Constructor Summary

public	ReportServiceGetEnabledResourceIDs()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetEnabledResourceIDs

```
public ReportServiceGetEnabledResourceIDs()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetEnabledResourceIDsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetEnabledResourceIDsResponse

public class ReportServiceGetEnabledResourceIDsResponse
extends Object

Constructor Summary

public	ReportServiceGetEnabledResourceIDsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetEnabledResourceIDsResponse

public ReportServiceGetEnabledResourceIDsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetESMVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetESMVersion

public class **ReportServiceGetESMVersion**
extends Object

Constructor Summary

public	ReportServiceGetESMVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetESMVersion

public **ReportServiceGetESMVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetESMVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetESMVersionResponse

public class ReportServiceGetESMVersionResponse
extends Object

Constructor Summary

public	ReportServiceGetESMVersionResponse()

Method Summary

String	getReturn()

void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetESMVersionResponse

public ReportServiceGetESMVersionResponse()

Methods

getReturn

public String getReturn()

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetExclusivelyDependentResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetExclusivelyDependentResources

public class ReportServiceGetExclusivelyDependentResources
extends Object

Constructor Summary

public	ReportServiceGetExclusivelyDependentResources()

Method Summary

String	getAuthToken()
List	getExcludePathIdList()
String	getResourceId()
void	setAuthToken (String authToken)
void	setExcludePathIdList (List excludePathIdList)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetExclusivelyDependentResources

public **ReportServiceGetExclusivelyDependentResources**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getExcludePathIdList

```
public List getExcludePathIdList()
```

Returns:

returns List

setExcludePathIdList

```
public void setExcludePathIdList(List excludePathIdList)
```

Parameters:

excludePathIdList - the value for the excludePathIdList property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ReportServiceGetExclusivelyDependentResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetExclusivelyDependentResourcesResponse

public class ReportServiceGetExclusivelyDependentResourcesResponse
extends Object

Constructor Summary	
public	ReportServiceGetExclusivelyDependentResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetExclusivelyDependentResourcesResponse
public ReportServiceGetExclusivelyDependentResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetMetaGroupID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetMetaGroupID

public class **ReportServiceGetMetaGroupID**
extends Object

Constructor Summary

public	ReportServiceGetMetaGroupID()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetMetaGroupID

public **ReportServiceGetMetaGroupID()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetMetaGroupIDResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetMetaGroupIDResponse

```
public class ReportServiceGetMetaGroupIDResponse
extends Object
```

Constructor Summary

public	ReportServiceGetMetaGroupIDResponse()

Method Summary

String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetMetaGroupIDResponse

```
public ReportServiceGetMetaGroupIDResponse()
```

Methods

getReturn

```
public String getReturn()
```

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetNamesAndAliases

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetNamesAndAliases

public class **ReportServiceGetNamesAndAliases**
extends Object

Constructor Summary

public	ReportServiceGetNamesAndAliases()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetNamesAndAliases

public **ReportServiceGetNamesAndAliases()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetNamesAndAliasesResponse

public class ReportServiceGetNamesAndAliasesResponse
extends Object

Constructor Summary	
public	ReportServiceGetNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetNamesAndAliasesResponse
public ReportServiceGetNamesAndAliasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetPersonalAndSharedResourceRoots

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalAndSharedResourceRoots

public class ReportServiceGetPersonalAndSharedResourceRoots
extends Object

Constructor Summary

public	ReportServiceGetPersonalAndSharedResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getUserId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setUserId(String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetPersonalAndSharedResourceRoots

public ReportServiceGetPersonalAndSharedResourceRoots()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetPersonalAndSharedResourceRootsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalAndSharedResourceRootsResponse

public class ReportServiceGetPersonalAndSharedResourceRootsResponse
extends Object

Constructor Summary

public	ReportServiceGetPersonalAndSharedResourceRootsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetPersonalAndSharedResourceRootsResponse

public ReportServiceGetPersonalAndSharedResourceRootsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetPersonalGroup

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalGroup

public class **ReportServiceGetPersonalGroup**
extends Object

Constructor Summary

public	ReportServiceGetPersonalGroup()

Method Summary

String	getAuthToken()
String	getUserId()
boolean	isThrowOnMissing()
void	setAuthToken (String authToken)
void	setThrowOnMissing (boolean throwOnMissing)
void	setUserId (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetPersonalGroup

public **ReportServiceGetPersonalGroup**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

isThrowOnMissing

```
public boolean isThrowOnMissing()
```

Returns:

returns boolean

setThrowOnMissing

```
public void setThrowOnMissing(boolean throwOnMissing)
```

Parameters:

throwOnMissing - the value for the throwOnMissing property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetPersonalGroupResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalGroupResponse

public class ReportServiceGetPersonalGroupResponse
extends Object

Constructor Summary

public	ReportServiceGetPersonalGroupResponse()

Method Summary

String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetPersonalGroupResponse

public ReportServiceGetPersonalGroupResponse()

Methods

getReturn

public String getReturn()

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetPersonalResourceRoots

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalResourceRoots

public class ReportServiceGetPersonalResourceRoots
extends Object

Constructor Summary	
public	ReportServiceGetPersonalResourceRoots()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getResourceId()
int	getResourceType()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setResourceId(String resourceId)
void	setResourceType(int resourceType)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetPersonalResourceRoots
public ReportServiceGetPersonalResourceRoots()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetPersonalResourceRootsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetPersonalResourceRootsResponse

public class ReportServiceGetPersonalResourceRootsResponse
extends Object

Constructor Summary

public	ReportServiceGetPersonalResourceRootsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetPersonalResourceRootsResponse

public ReportServiceGetPersonalResourceRootsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReferencePages

```
public class ReportServiceGetReferencePages
extends Object
```

Constructor Summary

public	ReportServiceGetReferencePages()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetReferencePages

```
public ReportServiceGetReferencePages()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetReferencePagesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReferencePage
sResponse

public class ReportServiceGetReferencePagesResponse
extends Object

Constructor Summary	
public	ReportServiceGetReferencePagesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetReferencePagesResponse
public ReportServiceGetReferencePagesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetRelationshipsOfParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetRelationshipsOfParents

public class ReportServiceGetRelationshipsOfParents
extends Object

Constructor Summary	
public	ReportServiceGetRelationshipsOfParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetRelationshipsOfParents
public ReportServiceGetRelationshipsOfParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetRelationshipsOfParentsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetRelationshipsOfParentsResponse

public class ReportServiceGetRelationshipsOfParentsResponse
extends Object

Constructor Summary

public	ReportServiceGetRelationshipsOfParentsResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetRelationshipsOfParentsResponse

public ReportServiceGetRelationshipsOfParentsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetRelationshipsOfThisAndParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetRelationshipsOfThisAndParents

public class **ReportServiceGetRelationshipsOfThisAndParents**
extends Object

Constructor Summary

public	ReportServiceGetRelationshipsOfThisAndParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetRelationshipsOfThisAndParents

public **ReportServiceGetRelationshipsOfThisAndParents**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetRelationshipsOfThisAndParentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetRelationshipsOfThisAndParentsResponse

public class ReportServiceGetRelationshipsOfThisAndParentsResponse
extends Object

Constructor Summary	
public	ReportServiceGetRelationshipsOfThisAndParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetRelationshipsOfThisAndParentsResponse
public ReportServiceGetRelationshipsOfThisAndParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourceById

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceById

public class **ReportServiceGetResourceById**
extends Object

Constructor Summary	
public	ReportServiceGetResourceById()

Method Summary	
String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourceById
public **ReportServiceGetResourceById**()

Methods

getAuthToken
public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourceByIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceByIdResponse

public class ReportServiceGetResourceByIdResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourceByIdResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourceByIdResponse
public **ReportServiceGetResourceByIdResponse()**

Methods

getReturn
public [Report](#) **getReturn()**

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourceByName

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceByName

```
public class ReportServiceGetResourceByName
extends Object
```

Constructor Summary

public	ReportServiceGetResourceByName()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourceByName

```
public ReportServiceGetResourceByName()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourceByNameResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceByNameResponse

public class ReportServiceGetResourceByNameResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourceByNameResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourceByNameResponse
public **ReportServiceGetResourceByNameResponse()**

Methods

getReturn
public [Report](#) **getReturn()**

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourceIfModified

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceIfModified

```
public class ReportServiceGetResourceIfModified
extends Object
```

Constructor Summary

public	ReportServiceGetResourceIfModified()

Method Summary

String	getAuthToken()
ResourceSignature	getSignature()
void	setAuthToken(String authToken)
void	setSignature(ResourceSignature signature)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourceIfModified

```
public ReportServiceGetResourceIfModified()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSignature

public [ResourceSignature](#) **getSignature**()

Returns:
returns ResourceSignature

setSignature

public void **setSignature**([ResourceSignature](#) signature)

Parameters:
signature - the value for the signature property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourceIfModifiedResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceIfModifiedResponse

public class ReportServiceGetResourceIfModifiedResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourceIfModifiedResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourceIfModifiedResponse

public **ReportServiceGetResourceIfModifiedResponse()**

Methods

getReturn

public [Report](#) **getReturn()**

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourcesByIds

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByIds

public class ReportServiceGetResourcesByIds
extends Object

Constructor Summary

public	ReportServiceGetResourcesByIds()

Method Summary

String	getAuthToken()
List	getIds()
void	setAuthToken(String authToken)
void	setIds(List ids)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourcesByIds

public ReportServiceGetResourcesByIds()

Methods

getAuthToken

public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getIds

public List **getIds**()

Returns:
returns List

setIds

public void **setIds**(List ids)

Parameters:
ids - the value for the ids property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourcesByIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByIdsResponse

public class ReportServiceGetResourcesByIdsResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourcesByIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesByIdsResponse
public ReportServiceGetResourcesByIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourcesByNames

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByNames

public class ReportServiceGetResourcesByNames
extends Object

Constructor Summary	
public	ReportServiceGetResourcesByNames()

Method Summary	
String	getAuthToken()
List	getNames()
void	setAuthToken(String authToken)
void	setNames(List names)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesByNames
public ReportServiceGetResourcesByNames()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getNames

public List **getNames**()

Returns:
returns List

setNames

public void **setNames**(List names)

Parameters:
names - the value for the names property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourcesByNameSafely

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByNameSafely

public class ReportServiceGetResourcesByNameSafely
extends Object

Constructor Summary

public	ReportServiceGetResourcesByNameSafely()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourcesByNameSafely

public ReportServiceGetResourcesByNameSafely()

Methods

getAuthToken

public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourcesByNameSafelyResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByNameSafelyResponse

public class ReportServiceGetResourcesByNameSafelyResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourcesByNameSafelyResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesByNameSafelyResponse

public ReportServiceGetResourcesByNameSafelyResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetResourcesByNamesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesByNamesResponse

public class ReportServiceGetResourcesByNamesResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourcesByNamesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesByNamesResponse
public ReportServiceGetResourcesByNamesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourcesReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesReferencePages

public class ReportServiceGetResourcesReferencePages
extends Object

Constructor Summary

public	ReportServiceGetResourcesReferencePages()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourcesReferencePages

public ReportServiceGetResourcesReferencePages()

Methods

getAuthToken

public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourcesReferencePagesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesReferencePagesResponse

public class ReportServiceGetResourcesReferencePagesResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourcesReferencePagesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesReferencePagesResponse
public ReportServiceGetResourcesReferencePagesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourcesWithVisibilityToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesWithVisibilityToUsers

public class **ReportServiceGetResourcesWithVisibilityToUsers**
extends Object

Constructor Summary

public	ReportServiceGetResourcesWithVisibilityToUsers()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourcesWithVisibilityToUsers

public **ReportServiceGetResourcesWithVisibilityToUsers()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ReportServiceGetResourcesWithVisibilityToUsersResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourcesWithVisibilityToUsersResponse

public class ReportServiceGetResourcesWithVisibilityToUsersResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourcesWithVisibilityToUsersResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourcesWithVisibilityToUsersResponse
public ReportServiceGetResourcesWithVisibilityToUsersResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourceTypesVisibleToUsers

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceTypesVisibleToUsers

public class ReportServiceGetResourceTypesVisibleToUsers
extends Object

Constructor Summary

public	ReportServiceGetResourceTypesVisibleToUsers()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetResourceTypesVisibleToUsers

public ReportServiceGetResourceTypesVisibleToUsers()

Methods

getAuthToken

public String getAuthToken()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetResourceTypesVisibleToUsersResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetResourceTypesVisibleToUsersResponse

public class ReportServiceGetResourceTypesVisibleToUsersResponse
extends Object

Constructor Summary	
public	ReportServiceGetResourceTypesVisibleToUsersResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetResourceTypesVisibleToUsersResponse

public ReportServiceGetResourceTypesVisibleToUsersResponse()

Methods

getReturn

public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetReverseRelationshipsOfParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReverseRelationshipsOfParents

public class ReportServiceGetReverseRelationshipsOfParents
extends Object

Constructor Summary	
public	ReportServiceGetReverseRelationshipsOfParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetReverseRelationshipsOfParents
public ReportServiceGetReverseRelationshipsOfParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetReverseRelationshipsOfParentsResponse

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReverseRelationshipsOfParentsResponse
```

```
public class ReportServiceGetReverseRelationshipsOfParentsResponse
extends Object
```

Constructor Summary	
public	ReportServiceGetReverseRelationshipsOfParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
ReportServiceGetReverseRelationshipsOfParentsResponse
public ReportServiceGetReverseRelationshipsOfParentsResponse()
```

Methods

```
getReturn
public List getReturn()
```

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetReverseRelationshipsOfThisAndParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReverseRelationshipsOfThisAndParents

public class ReportServiceGetReverseRelationshipsOfThisAndParents
extends Object

Constructor Summary	
public	ReportServiceGetReverseRelationshipsOfThisAndParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetReverseRelationshipsOfThisAndParents
public ReportServiceGetReverseRelationshipsOfThisAndParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetReverseRelationshipsOfThisAndParentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetReverseRelationshipsOfThisAndParentsResponse

public class ReportServiceGetReverseRelationshipsOfThisAndParentsResponse
extends Object

Constructor Summary	
public	ReportServiceGetReverseRelationshipsOfThisAndParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetReverseRelationshipsOfThisAndParentsResponse
public ReportServiceGetReverseRelationshipsOfThisAndParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetServiceMajorVersion

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetServiceMajorVersion

public class **ReportServiceGetServiceMajorVersion**
extends Object

Constructor Summary

public	ReportServiceGetServiceMajorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetServiceMajorVersion

public **ReportServiceGetServiceMajorVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetServiceMajorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetServiceMajorVersionResponse

public class ReportServiceGetServiceMajorVersionResponse
extends Object

Constructor Summary

public	ReportServiceGetServiceMajorVersionResponse()

Method Summary

int	getReturn()

void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetServiceMajorVersionResponse

public ReportServiceGetServiceMajorVersionResponse()

Methods

getReturn

public int getReturn()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetServiceMinorVersion

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetServiceMinorVersion

```
public class ReportServiceGetServiceMinorVersion
extends Object
```

Constructor Summary

public	ReportServiceGetServiceMinorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetServiceMinorVersion

```
public ReportServiceGetServiceMinorVersion()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetServiceMinorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetServiceMinorVersionResponse

public class **ReportServiceGetServiceMinorVersionResponse**
extends Object

Constructor Summary

public	ReportServiceGetServiceMinorVersionResponse()

Method Summary

int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetServiceMinorVersionResponse

public **ReportServiceGetServiceMinorVersionResponse**()

Methods

getReturn

public int **getReturn**()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourcesWithThisTargetByACLRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByACLRelationship

public class **ReportServiceGetSourcesWithThisTargetByACLRelationship**
extends Object

Constructor Summary

public	ReportServiceGetSourcesWithThisTargetByACLRelationship()

Method Summary

String	getAuthToken()
String	getSourceResourceId()
void	setAuthToken(String authToken)
void	setSourceResourceId(String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByACLRelationship

public **ReportServiceGetSourcesWithThisTargetByACLRelationship()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceResourceId

public String **getSourceResourceId**()

Returns:
returns String

setSourceResourceId

public void **setSourceResourceId**(String sourceResourceId)

Parameters:
sourceResourceId - the value for the sourceResourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse

```
public class ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse
extends Object
```

Constructor Summary

public	ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse

```
public ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetSourcesWithThisTargetByRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationship

public class ReportServiceGetSourcesWithThisTargetByRelationship
extends Object

Constructor Summary	
public	ReportServiceGetSourcesWithThisTargetByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByRelationship
public ReportServiceGetSourcesWithThisTargetByRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourcesWithThisTargetByRelationshipCount

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationshipCount

```
public class ReportServiceGetSourcesWithThisTargetByRelationshipCount
extends Object
```

Constructor Summary

public	ReportServiceGetSourcesWithThisTargetByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByRelationshipCount

```
public ReportServiceGetSourcesWithThisTargetByRelationshipCount()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse

public class ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse

extends Object

Constructor Summary	
public	ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse

public ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Methods

getReturn

public int getReturn()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId

public class ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId
extends Object

Constructor Summary	
public	ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId

public ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

public class ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

extends Object

Constructor Summary	
public	ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

public ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourcesWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourcesWithThisTargetByRelationshipResponse

public class ReportServiceGetSourcesWithThisTargetByRelationshipResponse
extends Object

Constructor Summary

public	ReportServiceGetSourcesWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourcesWithThisTargetByRelationshipResponse

public ReportServiceGetSourcesWithThisTargetByRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourceURIWithThisTargetByRelatiobnship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelatiobnship

```
public class ReportServiceGetSourceURIWithThisTargetByRelatiobnship
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelatiobnship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelatiobnship

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

public class ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId
extends Object

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId

public **ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceId**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public class ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

```
public class ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourceURIWithThisTargetByRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelationship

```
public class ReportServiceGetSourceURIWithThisTargetByRelationship
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelationship

```
public ReportServiceGetSourceURIWithThisTargetByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public class ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId
extends Object

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public class ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetSourceURIWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public class ReportServiceGetSourceURIWithThisTargetByRelationshipResponse
extends Object
```

Constructor Summary

public	ReportServiceGetSourceURIWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsAsURIByRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsAsURIByRelationship

public class ReportServiceGetTargetsAsURIByRelationship
extends Object

Constructor Summary	
public	ReportServiceGetTargetsAsURIByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetTargetsAsURIByRelationship
public **ReportServiceGetTargetsAsURIByRelationship()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsAsURIByRelationshipForSourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsAsURIByRelationshipForSourceId

public class ReportServiceGetTargetsAsURIByRelationshipForSourceId
extends Object

Constructor Summary

public	ReportServiceGetTargetsAsURIByRelationshipForSourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsAsURIByRelationshipForSourceId

public ReportServiceGetTargetsAsURIByRelationshipForSourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse

```
public class ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse
extends Object
```

Constructor Summary

public	ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse

```
public ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsAsURIByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsAsURIByRelationshipResponse

public class ReportServiceGetTargetsAsURIByRelationshipResponse
extends Object

Constructor Summary

public	ReportServiceGetTargetsAsURIByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsAsURIByRelationshipResponse

public ReportServiceGetTargetsAsURIByRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsByRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationship

public class ReportServiceGetTargetsByRelationship
extends Object

Constructor Summary	
public	ReportServiceGetTargetsByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Report sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsByRelationship
public ReportServiceGetTargetsByRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ReportServiceGetTargetsByRelationshipCount

java.lang.Object
└-
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationshipCount

public class ReportServiceGetTargetsByRelationshipCount
extends Object

Constructor Summary

public	ReportServiceGetTargetsByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Report sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsByRelationshipCount
public ReportServiceGetTargetsByRelationshipCount()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsByRelationshipCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationshipCountResponse

public class ReportServiceGetTargetsByRelationshipCountResponse
extends Object

Constructor Summary	
public	ReportServiceGetTargetsByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetTargetsByRelationshipCountResponse
public ReportServiceGetTargetsByRelationshipCountResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsByRelationshipForSourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationshipForSourceId

public class ReportServiceGetTargetsByRelationshipForSourceId
extends Object

Constructor Summary

public	ReportServiceGetTargetsByRelationshipForSourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsByRelationshipForSourceId

public ReportServiceGetTargetsByRelationshipForSourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationshipForSourceIdResponse

```
public class ReportServiceGetTargetsByRelationshipForSourceIdResponse
extends Object
```

Constructor Summary

public	ReportServiceGetTargetsByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsByRelationshipForSourceIdResponse

```
public ReportServiceGetTargetsByRelationshipForSourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsByRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsByRelationshipResponse

public class ReportServiceGetTargetsByRelationshipResponse
extends Object

Constructor Summary	
public	ReportServiceGetTargetsByRelationshipResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetTargetsByRelationshipResponse
public ReportServiceGetTargetsByRelationshipResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsWithRelationshipTypeForResource

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsWithRelationshipTypeForResource

public class **ReportServiceGetTargetsWithRelationshipTypeForResource**
extends Object

Constructor Summary	
public	ReportServiceGetTargetsWithRelationshipTypeForResource()

Method Summary	
String	getAuthToken()
Report	getResource()
void	setAuthToken(String authToken)
void	setResource(Report resource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceGetTargetsWithRelationshipTypeForResource

public **ReportServiceGetTargetsWithRelationshipTypeForResource()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResource

public [Report](#) **getResource**()

Returns:
returns Report

setResource

public void **setResource**([Report](#) resource)

Parameters:
resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsWithRelationshipTypeForResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsWithRelationshipTypeForResourceById

```
public class ReportServiceGetTargetsWithRelationshipTypeForResourceById
extends Object
```

Constructor Summary

public	ReportServiceGetTargetsWithRelationshipTypeForResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsWithRelationshipTypeForResourceById

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceById()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public class ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse
extends Object

Constructor Summary

public	ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceGetTargetsWithRelationshipTypeForResourceResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceGetTargetsWithRelationshipTypeForResourceResponse

```
public class ReportServiceGetTargetsWithRelationshipTypeForResourceResponse
extends Object
```

Constructor Summary

public	ReportServiceGetTargetsWithRelationshipTypeForResourceResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceGetTargetsWithRelationshipTypeForResourceResponse

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasReadPermission

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasReadPermission

public class ReportServiceHasReadPermission
extends Object

Constructor Summary	
public	ReportServiceHasReadPermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceHasReadPermission
public ReportServiceHasReadPermission()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasReadPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasReadPermissionResponse

public class ReportServiceHasReadPermissionResponse
extends Object

Constructor Summary	
public	ReportServiceHasReadPermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceHasReadPermissionResponse
public ReportServiceHasReadPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceHasReverseRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasReverseRelationship

public class ReportServiceHasReverseRelationship
extends Object

Constructor Summary

public	ReportServiceHasReverseRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Report	getSourceResource()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Report sourceResource)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceHasReverseRelationship

public ReportServiceHasReverseRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Report getSourceResource()
```

Returns:

returns Report

setSourceResource

```
public void setSourceResource(Report sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```


Parameters:

relationshipType - the value for the relationshipType property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasReverseRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasReverseRelationshipResponse

public class ReportServiceHasReverseRelationshipResponse
extends Object

Constructor Summary	
public	ReportServiceHasReverseRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceHasReverseRelationshipResponse
public ReportServiceHasReverseRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceHasWritePermission

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasWritePermission

```
public class ReportServiceHasWritePermission
extends Object
```

Constructor Summary

public	ReportServiceHasWritePermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceHasWritePermission

```
public ReportServiceHasWritePermission()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasWritePermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasWritePermissionResponse

public class ReportServiceHasWritePermissionResponse
extends Object

Constructor Summary	
public	ReportServiceHasWritePermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceHasWritePermissionResponse
public ReportServiceHasWritePermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasXPermission

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasXPermission

public class **ReportServiceHasXPermission**
extends Object

Constructor Summary

public	ReportServiceHasXPermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceHasXPermission

public **ReportServiceHasXPermission()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceHasXPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceHasXPermissionResponse

public class ReportServiceHasXPermissionResponse
extends Object

Constructor Summary

public	ReportServiceHasXPermissionResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceHasXPermissionResponse
public ReportServiceHasXPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceInsert

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceInsert

public class **ReportServiceInsert**
extends Object

Constructor Summary

public	ReportServiceInsert()

Method Summary

String	getAuthToken()
Report	getResource()
void	setAuthToken (String authToken)
void	setResource (Report resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceInsert

public **ReportServiceInsert**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getResource

public [Report](#) **getResource**()

Returns:

returns Report

setResource

public void **setResource**([Report](#) resource)

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceInsertResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceInsertResource

public class **ReportServiceInsertResource**
extends Object

Constructor Summary

public	ReportServiceInsertResource()

Method Summary

String	getAuthToken()
String	getParentId()
Report	getResource()
void	setAuthToken (String authToken)
void	setParentId (String parentId)
void	setResource (Report resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceInsertResource

public **ReportServiceInsertResource**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Report getResource()
```

Returns:

returns Report

setResource

```
public void setResource(Report resource)
```

Parameters:

resource - the value for the resource property

getParentId

```
public String getParentId()
```

Returns:

returns String

setParentId

```
public void setParentId(String parentId)
```

Parameters:

parentId - the value for the parentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceInsertResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceInsertResourceResponse

public class ReportServiceInsertResourceResponse
extends Object

Constructor Summary	
public	ReportServiceInsertResourceResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceInsertResourceResponse
public **ReportServiceInsertResourceResponse()**

Methods

getReturn
public [Report](#) **getReturn()**

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceInsertResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceInsertResponse

public class ReportServiceInsertResponse
extends Object

Constructor Summary	
public	ReportServiceInsertResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceInsertResponse
public ReportServiceInsertResponse()

Methods

getReturn
public [Report](#) getReturn()

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceIsDisabled

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceIsDisabled

public class **ReportServiceIsDisabled**
extends Object

Constructor Summary

public	ReportServiceIsDisabled()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken (String authToken)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceIsDisabled

public **ReportServiceIsDisabled**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceIsDisabledResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceIsDisabledResponse

```
public class ReportServiceIsDisabledResponse
extends Object
```

Constructor Summary

public	ReportServiceIsDisabledResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceIsDisabledResponse

```
public ReportServiceIsDisabledResponse()
```

Methods

isReturn

```
public boolean isReturn()
```

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceIsValidResourceID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceIsValidResourceID

public class **ReportServiceIsValidResourceID**
extends Object

Constructor Summary

public	ReportServiceIsValidResourceID()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceIsValidResourceID

public **ReportServiceIsValidResourceID()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceIsValidResourceIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceIsValidResourceIDResponse

public class ReportServiceIsValidResourceIDResponse
extends Object

Constructor Summary	
public	ReportServiceIsValidResourceIDResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceIsValidResourceIDResponse
public **ReportServiceIsValidResourceIDResponse()**

Methods

isReturn
public boolean **isReturn()**

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceLoadAdditional

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceLoadAdditional

public class **ReportServiceLoadAdditional**
extends Object

Constructor Summary

public	ReportServiceLoadAdditional()

Method Summary

String	getAuthToken()
String	getSourceId()
void	setAuthToken(String authToken)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceLoadAdditional

public **ReportServiceLoadAdditional()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceLoadAdditionalResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceLoadAdditionalResponse

```
public class ReportServiceLoadAdditionalResponse
extends Object
```

Constructor Summary

public	ReportServiceLoadAdditionalResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceLoadAdditionalResponse

```
public ReportServiceLoadAdditionalResponse()
```

Methods

getReturn

```
public Void getReturn()
```

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceResetState

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceResetState

public class **ReportServiceResetState**
extends Object

Constructor Summary

public	ReportServiceResetState()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceResetState

public **ReportServiceResetState()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceResetStateResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceResetStateResponse

public class **ReportServiceResetStateResponse**
extends Object

Constructor Summary

public	ReportServiceResetStateResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceResetStateResponse

public **ReportServiceResetStateResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceResolveRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceResolveRelationship

public class ReportServiceResolveRelationship
extends Object

Constructor Summary

public	ReportServiceResolveRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceId(String sourceId)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceResolveRelationship

public ReportServiceResolveRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceResolveRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceResolveRelationshipResponse

public class ReportServiceResolveRelationshipResponse
extends Object

Constructor Summary	
public	ReportServiceResolveRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceResolveRelationshipResponse
public ReportServiceResolveRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUnloadAdditional

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUnloadAdditional

public class ReportServiceUnloadAdditional
extends Object

Constructor Summary	
public	ReportServiceUnloadAdditional()

Method Summary	
String	getAuthToken()
String	getSourceId()
void	setAuthToken(String authToken)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceUnloadAdditional
public ReportServiceUnloadAdditional()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUnloadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUnloadAdditionalResponse

public class ReportServiceUnloadAdditionalResponse
extends Object

Constructor Summary	
public	ReportServiceUnloadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceUnloadAdditionalResponse
public ReportServiceUnloadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUpdate

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdate

public class **ReportServiceUpdate**
extends Object

Constructor Summary

public	ReportServiceUpdate()

Method Summary

String	getAuthToken()
Report	getResource()
void	setAuthToken (String authToken)
void	setResource (Report resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceUpdate

public **ReportServiceUpdate**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Report getResource()
```

Returns:

returns Report

setResource

```
public void setResource(Report resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceUpdateACLForResourceById

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdateACLForResourceById

public class ReportServiceUpdateACLForResourceById
extends Object

Constructor Summary

public	ReportServiceUpdateACLForResourceById()

Method Summary

String	getAuthToken()
List	getData()
String	getResourceId()
void	setAuthToken (String authToken)
void	setData (List data)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceUpdateACLForResourceById

public ReportServiceUpdateACLForResourceById()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getData

```
public List getData()
```

Returns:

returns List

setData

```
public void setData(List data)
```

Parameters:

data - the value for the data property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ReportServiceUpdateACLForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdateACLForResourceByIdResponse

public class ReportServiceUpdateACLForResourceByIdResponse
extends Object

Constructor Summary

public	ReportServiceUpdateACLForResourceByIdResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceUpdateACLForResourceByIdResponse

public ReportServiceUpdateACLForResourceByIdResponse()

Methods

getReturn

public Void getReturn()

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUpdateResources

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdateResources

public class ReportServiceUpdateResources
extends Object

Constructor Summary	
public	ReportServiceUpdateResources()

Method Summary	
String	getAuthToken()
List	getResources()
void	setAuthToken (String authToken)
void	setResources (List resources)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceUpdateResources
public ReportServiceUpdateResources()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUpdateResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdateResourcesResponse

public class ReportServiceUpdateResourcesResponse
extends Object

Constructor Summary	
public	ReportServiceUpdateResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportServiceUpdateResourcesResponse
public ReportServiceUpdateResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ReportServiceUpdateResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ReportServiceUpdateResponse

public class ReportServiceUpdateResponse
extends Object

Constructor Summary	
public	ReportServiceUpdateResponse()

Method Summary	
Report	getReturn()
void	setReturn(Report _return)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceUpdateResponse
public ReportServiceUpdateResponse()

Methods

getReturn
public [Report](#) getReturn()

Returns:
returns Report

setReturn

```
public void setReturn(Report _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceAddRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceAddRelationship

public class ResourceServiceAddRelationship
extends Object

Constructor Summary	
public	ResourceServiceAddRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
String	getTargetResourceId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResourceId(String sourceResourceId)
void	setTargetResourceId(String targetResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceAddRelationship
public ResourceServiceAddRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getTargetResourceId

```
public String getTargetResourceId()
```

Returns:

returns String

setTargetResourceId

```
public void setTargetResourceId(String targetResourceId)
```

Parameters:

targetResourceId - the value for the targetResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceAddRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceAddRelationshipResponse

public class ResourceServiceAddRelationshipResponse
extends Object

Constructor Summary	
public	ResourceServiceAddRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceAddRelationshipResponse
public ResourceServiceAddRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceContainsDirectMemberByNameOrAlias

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceContainsDirectMemberByNameOrAlias

public class ResourceServiceContainsDirectMemberByNameOrAlias
extends Object

Constructor Summary	
public	ResourceServiceContainsDirectMemberByNameOrAlias()

Method Summary	
String	getAuthToken()
String	getGroupId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceContainsDirectMemberByNameOrAlias
public ResourceServiceContainsDirectMemberByNameOrAlias()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceContainsDirectMemberByNameOrAliasResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceContainsDirectMemberByNameOrAliasResponse

public class ResourceServiceContainsDirectMemberByNameOrAliasResponse
extends Object

Constructor Summary

public	ResourceServiceContainsDirectMemberByNameOrAliasResponse()

Method Summary

boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceContainsDirectMemberByNameOrAliasResponse

public ResourceServiceContainsDirectMemberByNameOrAliasResponse()

Methods

isReturn

public boolean isReturn()

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceCopyResourceIntoGroup

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceCopyResourceIntoGroup

public class ResourceServiceCopyResourceIntoGroup
extends Object

Constructor Summary

public	ResourceServiceCopyResourceIntoGroup()

Method Summary

String	getAuthToken()
String	getNewName()
String	getNewParentId()
String	getOldParentId()
String	getResourceId()
void	setAuthToken(String authToken)
void	setNewName(String newName)
void	setNewParentId(String newParentId)
void	setOldParentId(String oldParentId)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceCopyResourceIntoGroup

public ResourceServiceCopyResourceIntoGroup()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getNewName

public String **getNewName**()

Returns:

returns String

setNewName

public void **setNewName**(String newName)

Parameters:

newName - the value for the newName property

getResourceId

public String **getResourceId**()

Returns:

returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:

resourceId - the value for the resourceId property

getOldParentId

public String **getOldParentId**()

Returns:

returns String

setOldParentId

public void **setOldParentId**(String oldParentId)

Parameters:

oldParentId - the value for the oldParentId property

getNewParentId

public String **getNewParentId**()

Returns:

returns String

setNewParentId

public void **setNewParentId**(String newParentId)

Parameters:

newParentId - the value for the newParentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceCopyResourceIntoGroupResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceCopyResourceIntoGroupResponse

public class ResourceServiceCopyResourceIntoGroupResponse
extends Object

Constructor Summary	
public	ResourceServiceCopyResourceIntoGroupResponse()

Method Summary	
Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceCopyResourceIntoGroupResponse
public ResourceServiceCopyResourceIntoGroupResponse()

Methods

getReturn
public [Resource](#) getReturn()

Returns:
returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDelete

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDelete

public class **ResourceServiceDelete**
extends Object

Constructor Summary

public	ResourceServiceDelete()

Method Summary

String	getAuthToken()
Resource	getResource()
void	setAuthToken (String authToken)
void	setResource (Resource resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceDelete

public **ResourceServiceDelete**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Resource getResource()
```

Returns:

returns Resource

setResource

```
public void setResource(Resource resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteByLocalId

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteByLocalId

```
public class ResourceServiceDeleteByLocalId
extends Object
```

Constructor Summary

public	ResourceServiceDeleteByLocalId()

Method Summary

String	getAuthToken()
long	getId()
void	setAuthToken(String authToken)
void	setId(long id)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceDeleteByLocalId

```
public ResourceServiceDeleteByLocalId()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public long **getId**()

Returns:
returns long

setId

public void **setId**(long id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteByLocalIdResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteByLocalIdResponse

public class ResourceServiceDeleteByLocalIdResponse
extends Object

Constructor Summary	
public	ResourceServiceDeleteByLocalIdResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceDeleteByLocalIdResponse
public ResourceServiceDeleteByLocalIdResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteByUUID

java.lang.Object

└-

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteByUUID

public class ResourceServiceDeleteByUUID

extends Object

Constructor Summary	
public	ResourceServiceDeleteByUUID()

Method Summary	
String	getAuthToken()
String	getId()
void	setAuthToken(String authToken)
void	setId(String id)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

ResourceServiceDeleteByUUID

public ResourceServiceDeleteByUUID()

Methods

getAuthToken

public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public String **getId**()

Returns:
returns String

setId

public void **setId**(String id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteByUUIDResponse

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteByUUIDResponse
```

```
public class ResourceServiceDeleteByUUIDResponse
extends Object
```

Constructor Summary	
public	ResourceServiceDeleteByUUIDResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
ResourceServiceDeleteByUUIDResponse
public ResourceServiceDeleteByUUIDResponse()
```

Methods

```
getReturn
public Void getReturn()
```

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteResource

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteResource

public class **ResourceServiceDeleteResource**
extends Object

Constructor Summary	
public	ResourceServiceDeleteResource()

Method Summary	
String	getAuthToken()
Resource	getResource()
boolean	isAbortTxOnValConflicts()
void	setAbortTxOnValConflicts (boolean abortTxOnValConflicts)
void	setAuthToken (String authToken)
void	setResource (Resource resource)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceDeleteResource
public **ResourceServiceDeleteResource**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Resource getResource()
```

Returns:

returns Resource

setResource

```
public void setResource(Resource resource)
```

Parameters:

resource - the value for the resource property

isAbortTxOnValConflicts

```
public boolean isAbortTxOnValConflicts()
```

Returns:

returns boolean

setAbortTxOnValConflicts

```
public void setAbortTxOnValConflicts(boolean abortTxOnValConflicts)
```

Parameters:

abortTxOnValConflicts - the value for the abortTxOnValConflicts property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteResourceResponse

public class ResourceServiceDeleteResourceResponse
extends Object

Constructor Summary	
public	ResourceServiceDeleteResourceResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceDeleteResourceResponse
public ResourceServiceDeleteResourceResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteResources

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteResources

```
public class ResourceServiceDeleteResources  
extends Object
```

Constructor Summary

public	ResourceServiceDeleteResources()

Method Summary

String	getAuthToken()
List	getResources()
void	setAuthToken(String authToken)
void	setResources(List resources)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceDeleteResources

```
public ResourceServiceDeleteResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteResource
sResponse

public class ResourceServiceDeleteResourcesResponse
extends Object

Constructor Summary	
public	ResourceServiceDeleteResourcesResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceDeleteResourcesResponse
public ResourceServiceDeleteResourcesResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceDeleteResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceDeleteResponse

public class **ResourceServiceDeleteResponse**
extends Object

Constructor Summary

public	ResourceServiceDeleteResponse()

Method Summary

Void	getReturn()

void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceDeleteResponse

public **ResourceServiceDeleteResponse()**

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceFindAllIds

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindAllIds

public class **ResourceServiceFindAllIds**
extends Object

Constructor Summary

public	ResourceServiceFindAllIds()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceFindAllIds

public **ResourceServiceFindAllIds**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceFindAllIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindAllIdsResponse

public class ResourceServiceFindAllIdsResponse
extends Object

Constructor Summary	
public	ResourceServiceFindAllIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceFindAllIdsResponse
public ResourceServiceFindAllIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceFindById

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindById

public class **ResourceServiceFindById**
extends Object

Constructor Summary

public	ResourceServiceFindById()

Method Summary

String	getAuthToken()
long	getLocalId()
void	setAuthToken (String authToken)
void	setLocalId (long localId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceFindById

public **ResourceServiceFindById**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getLocalId

```
public long getLocalId()
```

Returns:

returns long

setLocalId

```
public void setLocalId(long localId)
```

Parameters:

localId - the value for the localId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceFindByIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindByIdResponse

```
public class ResourceServiceFindByIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceFindByIdResponse()

Method Summary

Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceFindByIdResponse

```
public ResourceServiceFindByIdResponse()
```

Methods

getReturn

```
public Resource getReturn()
```

Returns:

returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceFindByUUID

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindByUUID

public class **ResourceServiceFindByUUID**
extends Object

Constructor Summary	
public	ResourceServiceFindByUUID()

Method Summary	
String	getAuthToken()
String	getId()
void	setAuthToken(String authToken)
void	setId(String id)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

ResourceServiceFindByUUID
public **ResourceServiceFindByUUID()**

Methods

getAuthToken
public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getId

public String **getId**()

Returns:
returns String

setId

public void **setId**(String id)

Parameters:
id - the value for the id property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceFindByUUIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceFindByUUIDResponse

public class ResourceServiceFindByUUIDResponse
extends Object

Constructor Summary	
public	ResourceServiceFindByUUIDResponse()

Method Summary	
Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceFindByUUIDResponse
public ResourceServiceFindByUUIDResponse()

Methods

getReturn
public [Resource](#) getReturn()

Returns:
returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetAllAttachmentOnlyResourceIDs

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllAttachmentOnlyResourceIDs

public class ResourceServiceGetAllAttachmentOnlyResourceIDs
extends Object

Constructor Summary	
public	ResourceServiceGetAllAttachmentOnlyResourceIDs()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllAttachmentOnlyResourceIDs
public ResourceServiceGetAllAttachmentOnlyResourceIDs()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllAttachmentOnlyResourceIDsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllAttachmentOnlyResourceIDsResponse

public class ResourceServiceGetAllAttachmentOnlyResourceIDsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetAllAttachmentOnlyResourceIDsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllAttachmentOnlyResourceIDsResponse
public ResourceServiceGetAllAttachmentOnlyResourceIDsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllowedUserTypes

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllowedUserTypes

public class **ResourceServiceGetAllowedUserTypes**
extends Object

Constructor Summary

public	ResourceServiceGetAllowedUserTypes()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetAllowedUserTypes

public **ResourceServiceGetAllowedUserTypes**()

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllowedUserTypesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllowedUserTypesResponse

public class ResourceServiceGetAllowedUserTypesResponse
extends Object

Constructor Summary	
public	ResourceServiceGetAllowedUserTypesResponse()

Method Summary	
String[]	getReturn()
void	setReturn(String[] _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllowedUserTypesResponse
public ResourceServiceGetAllowedUserTypesResponse()

Methods

getReturn
public String[] getReturn()

Returns:
returns String[]

setReturn

```
public void setReturn(String[] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllPathsToRoot

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllPathsToRoot

public class **ResourceServiceGetAllPathsToRoot**
extends Object

Constructor Summary

public	ResourceServiceGetAllPathsToRoot()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetAllPathsToRoot

public **ResourceServiceGetAllPathsToRoot**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllPathsToRootAsStrings

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllPathsToRootAsStrings

public class **ResourceServiceGetAllPathsToRootAsStrings**
extends Object

Constructor Summary

public	ResourceServiceGetAllPathsToRootAsStrings()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetAllPathsToRootAsStrings

public **ResourceServiceGetAllPathsToRootAsStrings()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllPathsToRootAsStringsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllPathsToRootAsStringsResponse

public class ResourceServiceGetAllPathsToRootAsStringsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetAllPathsToRootAsStringsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllPathsToRootAsStringsResponse
public ResourceServiceGetAllPathsToRootAsStringsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllPathsToRootResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllPathsToRootResponse

public class ResourceServiceGetAllPathsToRootResponse
extends Object

Constructor Summary	
public	ResourceServiceGetAllPathsToRootResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllPathsToRootResponse
public ResourceServiceGetAllPathsToRootResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllUnassignedResourceIDs

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllUnassignedResourceIDs

public class ResourceServiceGetAllUnassignedResourceIDs
extends Object

Constructor Summary	
public	ResourceServiceGetAllUnassignedResourceIDs()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllUnassignedResourceIDs
public ResourceServiceGetAllUnassignedResourceIDs()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetAllUnassignedResourceIdsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetAllUnassignedResourceIdsResponse

public class ResourceServiceGetAllUnassignedResourceIdsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetAllUnassignedResourceIdsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetAllUnassignedResourceIdsResponse
public ResourceServiceGetAllUnassignedResourceIdsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetChildNamesAndAliases

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetChildNamesAndAliases

public class ResourceServiceGetChildNamesAndAliases
extends Object

Constructor Summary	
public	ResourceServiceGetChildNamesAndAliases()

Method Summary	
String	getAuthToken()
String	getGroupId()
List	getUnmappedIds()
void	setAuthToken (String authToken)
void	setGroupId (String groupId)
void	setUnmappedIds (List unmappedIds)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetChildNamesAndAliases
public ResourceServiceGetChildNamesAndAliases()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getGroupId

```
public String getGroupId()
```

Returns:

returns String

setGroupId

```
public void setGroupId(String groupId)
```

Parameters:

groupId - the value for the groupId property

getUnmappedIds

```
public List getUnmappedIds()
```

Returns:

returns List

setUnmappedIds

```
public void setUnmappedIds(List unmappedIds)
```

Parameters:

unmappedIds - the value for the unmappedIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetChildNamesAndAliasesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetChildNamesAndAliasesResponse

public class **ResourceServiceGetChildNamesAndAliasesResponse**
extends Object

Constructor Summary

public	ResourceServiceGetChildNamesAndAliasesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetChildNamesAndAliasesResponse

public **ResourceServiceGetChildNamesAndAliasesResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetCorruptedResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetCorruptedResources

```
public class ResourceServiceGetCorruptedResources
extends Object
```

Constructor Summary

public	ResourceServiceGetCorruptedResources()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetCorruptedResources

```
public ResourceServiceGetCorruptedResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetCorruptedResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetCorruptedResourcesResponse

public class ResourceServiceGetCorruptedResourcesResponse
extends Object

Constructor Summary	
public	ResourceServiceGetCorruptedResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetCorruptedResourcesResponse
public ResourceServiceGetCorruptedResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetDependentResourceIdsForResourceId

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetDependentResourceIdsForResourceId

public class ResourceServiceGetDependentResourceIdsForResourceId
extends Object

Constructor Summary	
public	ResourceServiceGetDependentResourceIdsForResourceId()

Method Summary	
String	getAuthToken()
String	getResourceId()
boolean	isExcludeAttachmentOnlyResources()
boolean	isExcludeHiddenResources()
void	setAuthToken(String authToken)
void	setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
void	setExcludeHiddenResources(boolean excludeHiddenResources)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetDependentResourceIdsForResourceId
public ResourceServiceGetDependentResourceIdsForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

isExcludeHiddenResources

```
public boolean isExcludeHiddenResources()
```

Returns:

returns boolean

setExcludeHiddenResources

```
public void setExcludeHiddenResources(boolean excludeHiddenResources)
```

Parameters:

`excludeHiddenResources` - the value for the `excludeHiddenResources` property

isExcludeAttachmentOnlyResources

```
public boolean isExcludeAttachmentOnlyResources()
```

Returns:

returns boolean

setExcludeAttachmentOnlyResources

```
public void setExcludeAttachmentOnlyResources(boolean excludeAttachmentOnlyResources)
```

Parameters:

`excludeAttachmentOnlyResources` - the value for the `excludeAttachmentOnlyResources` property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetDependentResourceIdsForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetDependentResourceIdsForResourceIdResponse

```
public class ResourceServiceGetDependentResourceIdsForResourceIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetDependentResourceIdsForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetDependentResourceIdsForResourceIdResponse

```
public ResourceServiceGetDependentResourceIdsForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetEnabledResourceIDs

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetEnabledResourceIDs

public class **ResourceServiceGetEnabledResourceIDs**
extends Object

Constructor Summary

public	ResourceServiceGetEnabledResourceIDs()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetEnabledResourceIDs

public **ResourceServiceGetEnabledResourceIDs**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetEnabledResourceIDsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetEnabledResourceIDsResponse

public class ResourceServiceGetEnabledResourceIDsResponse
extends Object

Constructor Summary

public	ResourceServiceGetEnabledResourceIDsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetEnabledResourceIDsResponse

public ResourceServiceGetEnabledResourceIDsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetESMVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetESMVersion

public class **ResourceServiceGetESMVersion**
extends Object

Constructor Summary

public	ResourceServiceGetESMVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetESMVersion

public **ResourceServiceGetESMVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetESMVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetESMVersionResponse

```
public class ResourceServiceGetESMVersionResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetESMVersionResponse()

Method Summary

String	getReturn()

void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetESMVersionResponse

```
public ResourceServiceGetESMVersionResponse()
```

Methods

getReturn

```
public String getReturn()
```

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetExclusivelyDependentResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetExclusivelyDependentResources

public class **ResourceServiceGetExclusivelyDependentResources**
extends Object

Constructor Summary

public	ResourceServiceGetExclusivelyDependentResources()

Method Summary

String	getAuthToken()
List	getExcludePathIdList()
String	getResourceId()
void	setAuthToken (String authToken)
void	setExcludePathIdList (List excludePathIdList)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetExclusivelyDependentResources

public **ResourceServiceGetExclusivelyDependentResources**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getExcludePathIdList

```
public List getExcludePathIdList()
```

Returns:

returns List

setExcludePathIdList

```
public void setExcludePathIdList(List excludePathIdList)
```

Parameters:

excludePathIdList - the value for the excludePathIdList property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetExclusivelyDependentResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetExclusivelyDependentResourcesResponse

public class ResourceServiceGetExclusivelyDependentResourcesResponse
extends Object

Constructor Summary	
public	ResourceServiceGetExclusivelyDependentResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetExclusivelyDependentResourcesResponse
public ResourceServiceGetExclusivelyDependentResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetMetaGroupID

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetMetaGroupID

public class **ResourceServiceGetMetaGroupID**
extends Object

Constructor Summary

public	ResourceServiceGetMetaGroupID()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetMetaGroupID

public **ResourceServiceGetMetaGroupID()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetMetaGroupIDResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetMetaGroupIDResponse

public class ResourceServiceGetMetaGroupIDResponse
extends Object

Constructor Summary	
public	ResourceServiceGetMetaGroupIDResponse()

Method Summary	
String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetMetaGroupIDResponse
public ResourceServiceGetMetaGroupIDResponse()

Methods

getReturn
public String **getReturn()**

Returns:
returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetNamesAndAliases

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetNamesAndAliases

public class **ResourceServiceGetNamesAndAliases**
extends Object

Constructor Summary

public	ResourceServiceGetNamesAndAliases()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetNamesAndAliases

public **ResourceServiceGetNamesAndAliases()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetNamesAndAliasesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetNamesAndAliasesResponse

public class ResourceServiceGetNamesAndAliasesResponse
extends Object

Constructor Summary	
public	ResourceServiceGetNamesAndAliasesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetNamesAndAliasesResponse
public ResourceServiceGetNamesAndAliasesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetPersonalAndSharedResourceRoots

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalAndSharedResourceRoots

public class **ResourceServiceGetPersonalAndSharedResourceRoots**
extends Object

Constructor Summary

public	ResourceServiceGetPersonalAndSharedResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getUserId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setUserId (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetPersonalAndSharedResourceRoots

public **ResourceServiceGetPersonalAndSharedResourceRoots**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetPersonalAndSharedResourceRootsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalAndSharedResourceRootsResponse

public class ResourceServiceGetPersonalAndSharedResourceRootsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetPersonalAndSharedResourceRootsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetPersonalAndSharedResourceRootsResponse
public ResourceServiceGetPersonalAndSharedResourceRootsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetPersonalGroup

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalGroup

public class **ResourceServiceGetPersonalGroup**
extends Object

Constructor Summary

public	ResourceServiceGetPersonalGroup()

Method Summary

String	getAuthToken()
String	getUserId()
boolean	isThrowOnMissing()
void	setAuthToken (String authToken)
void	setThrowOnMissing (boolean throwOnMissing)
void	setUserId (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetPersonalGroup

public **ResourceServiceGetPersonalGroup**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getUserId

```
public String getUserId()
```

Returns:

returns String

setUserId

```
public void setUserId(String userId)
```

Parameters:

userId - the value for the userId property

isThrowOnMissing

```
public boolean isThrowOnMissing()
```

Returns:

returns boolean

setThrowOnMissing

```
public void setThrowOnMissing(boolean throwOnMissing)
```

Parameters:

throwOnMissing - the value for the throwOnMissing property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetPersonalGroupResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalGroupResponse

public class ResourceServiceGetPersonalGroupResponse
extends Object

Constructor Summary

public	ResourceServiceGetPersonalGroupResponse()

Method Summary

String	getReturn()
void	setReturn(String _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetPersonalGroupResponse

public ResourceServiceGetPersonalGroupResponse()

Methods

getReturn

public String **getReturn()**

Returns:

returns String

setReturn

```
public void setReturn(String _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetPersonalResourceRoots

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalResourceRoots

public class **ResourceServiceGetPersonalResourceRoots**
extends Object

Constructor Summary

public	ResourceServiceGetPersonalResourceRoots()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getResourceId()
int	getResourceType()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setResourceId(String resourceId)
void	setResourceType(int resourceType)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetPersonalResourceRoots

public **ResourceServiceGetPersonalResourceRoots()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getResourceType

```
public int getResourceType()
```

Returns:

returns int

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the value for the resourceType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetPersonalResourceRootsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetPersonalResourceRootsResponse

public class ResourceServiceGetPersonalResourceRootsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetPersonalResourceRootsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetPersonalResourceRootsResponse
public ResourceServiceGetPersonalResourceRootsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetReferencePages

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReferencePages

```
public class ResourceServiceGetReferencePages
extends Object
```

Constructor Summary

public	ResourceServiceGetReferencePages()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetReferencePages

```
public ResourceServiceGetReferencePages()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetReferencePagesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReferencePagesResponse

```
public class ResourceServiceGetReferencePagesResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetReferencePagesResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetReferencePagesResponse

```
public ResourceServiceGetReferencePagesResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetRelationshipsOfParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetRelationshipsOfParents

public class ResourceServiceGetRelationshipsOfParents
extends Object

Constructor Summary	
public	ResourceServiceGetRelationshipsOfParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetRelationshipsOfParents
public ResourceServiceGetRelationshipsOfParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetRelationshipsOfParentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetRelationshipsOfParentsResponse

public class ResourceServiceGetRelationshipsOfParentsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetRelationshipsOfParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetRelationshipsOfParentsResponse
public ResourceServiceGetRelationshipsOfParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetRelationshipsOfThisAndParents

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetRelationshipsOfThisAndParents

public class ResourceServiceGetRelationshipsOfThisAndParents
extends Object

Constructor Summary	
public	ResourceServiceGetRelationshipsOfThisAndParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetRelationshipsOfThisAndParents
public ResourceServiceGetRelationshipsOfThisAndParents()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetRelationshipsOfThisAndParentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetRelationshipsOfThisAndParentsResponse

public class ResourceServiceGetRelationshipsOfThisAndParentsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetRelationshipsOfThisAndParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetRelationshipsOfThisAndParentsResponse
public ResourceServiceGetRelationshipsOfThisAndParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourceById

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceById

```
public class ResourceServiceGetResourceById  
extends Object
```

Constructor Summary

public	ResourceServiceGetResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceById

```
public ResourceServiceGetResourceById()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourceByIdResponse

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceByIdResponse

```
public class ResourceServiceGetResourceByIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetResourceByIdResponse()

Method Summary

Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceByIdResponse

```
public ResourceServiceGetResourceByIdResponse()
```

Methods

getReturn

```
public Resource getReturn()
```

Returns:

returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourceByName

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceByName

public class **ResourceServiceGetResourceByName**
extends Object

Constructor Summary

public	ResourceServiceGetResourceByName()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceByName

public **ResourceServiceGetResourceByName()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourceByNameResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceByNameResponse

public class ResourceServiceGetResourceByNameResponse
extends Object

Constructor Summary	
public	ResourceServiceGetResourceByNameResponse()

Method Summary	
Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourceByNameResponse
public ResourceServiceGetResourceByNameResponse()

Methods

getReturn
public [Resource](#) getReturn()

Returns:
returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourceIfModified

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceIfModified

public class **ResourceServiceGetResourceIfModified**
extends Object

Constructor Summary

public	ResourceServiceGetResourceIfModified()

Method Summary

String	getAuthToken()
ResourceSignature	getSignature()
void	setAuthToken(String authToken)
void	setSignature(ResourceSignature signature)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceIfModified

public **ResourceServiceGetResourceIfModified()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSignature

public [ResourceSignature](#) **getSignature**()

Returns:
returns ResourceSignature

setSignature

public void **setSignature**([ResourceSignature](#) signature)

Parameters:
signature - the value for the signature property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourceIfModifiedResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceIfModifiedResponse

public class **ResourceServiceGetResourceIfModifiedResponse**
extends Object

Constructor Summary

public	ResourceServiceGetResourceIfModifiedResponse()

Method Summary

Resource	getReturn()

void	setReturn(Resource _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceIfModifiedResponse

public **ResourceServiceGetResourceIfModifiedResponse**()

Methods

getReturn

public [Resource](#) **getReturn**()

Returns:

returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourcesByIds

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByIds

```
public class ResourceServiceGetResourcesByIds
extends Object
```

Constructor Summary

public	ResourceServiceGetResourcesByIds()

Method Summary

String	getAuthToken()
List	getIds()
void	setAuthToken() (String authToken)
void	setIds() (List ids)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesByIds

```
public ResourceServiceGetResourcesByIds()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getIds

public List **getIds**()

Returns:
returns List

setIds

public void **setIds**(List ids)

Parameters:
ids - the value for the ids property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourcesByIdsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByIdsResponse

public class ResourceServiceGetResourcesByIdsResponse
extends Object

Constructor Summary

public	ResourceServiceGetResourcesByIdsResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesByIdsResponse

public ResourceServiceGetResourcesByIdsResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourcesByNames

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByNames

public class ResourceServiceGetResourcesByNames
extends Object

Constructor Summary	
public	ResourceServiceGetResourcesByNames()

Method Summary	
String	getAuthToken()
List	getNames()
void	setAuthToken(String authToken)
void	setNames(List names)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourcesByNames
public ResourceServiceGetResourcesByNames()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getNames

public List **getNames**()

Returns:
returns List

setNames

public void **setNames**(List names)

Parameters:
names - the value for the names property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourcesByNameSafely

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByNameSafely

```
public class ResourceServiceGetResourcesByNameSafely
extends Object
```

Constructor Summary

public	ResourceServiceGetResourcesByNameSafely()

Method Summary

String	getAuthToken()
String	getName()
void	setAuthToken(String authToken)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesByNameSafely

```
public ResourceServiceGetResourcesByNameSafely()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getName

public String **getName**()

Returns:
returns String

setName

public void **setName**(String name)

Parameters:
name - the value for the name property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourcesByNameSafelyResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByNameSafelyResponse

public class ResourceServiceGetResourcesByNameSafelyResponse
extends Object

Constructor Summary	
public	ResourceServiceGetResourcesByNameSafelyResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourcesByNameSafelyResponse
public ResourceServiceGetResourcesByNameSafelyResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourcesByNamesResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesByNamesResponse

public class ResourceServiceGetResourcesByNamesResponse
extends Object

Constructor Summary

public	ResourceServiceGetResourcesByNamesResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesByNamesResponse

public ResourceServiceGetResourcesByNamesResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourcesReferencePages

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesReferencePages

public class **ResourceServiceGetResourcesReferencePages**
extends Object

Constructor Summary

public	ResourceServiceGetResourcesReferencePages()

Method Summary

String	getAuthToken()
List	getResourceIds()
void	setAuthToken(String authToken)
void	setResourceIds(List resourceIds)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesReferencePages

public **ResourceServiceGetResourcesReferencePages()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceIds

public List **getResourceIds**()

Returns:
returns List

setResourceIds

public void **setResourceIds**(List resourceIds)

Parameters:
resourceIds - the value for the resourceIds property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourcesReferencePagesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesReferencePagesResponse

public class ResourceServiceGetResourcesReferencePagesResponse
extends Object

Constructor Summary	
public	ResourceServiceGetResourcesReferencePagesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourcesReferencePagesResponse
public ResourceServiceGetResourcesReferencePagesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourcesWithVisibilityToUsers

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesWithVisibilityToUsers

public class ResourceServiceGetResourcesWithVisibilityToUsers
extends Object

Constructor Summary	
public	ResourceServiceGetResourcesWithVisibilityToUsers()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourcesWithVisibilityToUsers
public ResourceServiceGetResourcesWithVisibilityToUsers()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourcesWithVisibilityToUsersResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourcesWithVisibilityToUsersResponse

public class **ResourceServiceGetResourcesWithVisibilityToUsersResponse**
extends Object

Constructor Summary

public	ResourceServiceGetResourcesWithVisibilityToUsersResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourcesWithVisibilityToUsersResponse

public **ResourceServiceGetResourcesWithVisibilityToUsersResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetResourceTypesVisibleToUsers

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceTypesVisibleToUsers

public class ResourceServiceGetResourceTypesVisibleToUsers
extends Object

Constructor Summary	
public	ResourceServiceGetResourceTypesVisibleToUsers()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetResourceTypesVisibleToUsers
public ResourceServiceGetResourceTypesVisibleToUsers()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetResourceTypesVisibleToUsersResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetResourceTypesVisibleToUsersResponse

public class **ResourceServiceGetResourceTypesVisibleToUsersResponse**
extends Object

Constructor Summary

public	ResourceServiceGetResourceTypesVisibleToUsersResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetResourceTypesVisibleToUsersResponse

public **ResourceServiceGetResourceTypesVisibleToUsersResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetReverseRelationshipsOfParents

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReverseRelationshipsOfParents

public class **ResourceServiceGetReverseRelationshipsOfParents**
extends Object

Constructor Summary

public	ResourceServiceGetReverseRelationshipsOfParents()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetReverseRelationshipsOfParents

public **ResourceServiceGetReverseRelationshipsOfParents**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetReverseRelationshipsOfParentsResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReverseRelationshipsOfParentsResponse

public class ResourceServiceGetReverseRelationshipsOfParentsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetReverseRelationshipsOfParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetReverseRelationshipsOfParentsResponse
public ResourceServiceGetReverseRelationshipsOfParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetReverseRelationshipsOfThisAndParents

```
java.lang.Object
└-
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReverseRelationshipsOfThisAndParents
```

```
public class ResourceServiceGetReverseRelationshipsOfThisAndParents
extends Object
```

Constructor Summary	
public	ResourceServiceGetReverseRelationshipsOfThisAndParents()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceId (String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
ResourceServiceGetReverseRelationshipsOfThisAndParents
public ResourceServiceGetReverseRelationshipsOfThisAndParents()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse

public class ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse
extends Object

Constructor Summary	
public	ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse
public ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetServiceMajorVersion

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetServiceMajorVersion

public class ResourceServiceGetServiceMajorVersion
extends Object

Constructor Summary	
public	ResourceServiceGetServiceMajorVersion()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetServiceMajorVersion
public ResourceServiceGetServiceMajorVersion()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetServiceMajorVersionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetServiceMajorVersionResponse

public class ResourceServiceGetServiceMajorVersionResponse
extends Object

Constructor Summary	
public	ResourceServiceGetServiceMajorVersionResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetServiceMajorVersionResponse
public ResourceServiceGetServiceMajorVersionResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetServiceMinorVersion

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetServiceMinorVersion

public class ResourceServiceGetServiceMinorVersion
extends Object

Constructor Summary	
public	ResourceServiceGetServiceMinorVersion()

Method Summary	
String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetServiceMinorVersion
public ResourceServiceGetServiceMinorVersion()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetServiceMinorVersionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetServiceMinorVersionResponse

public class ResourceServiceGetServiceMinorVersionResponse
extends Object

Constructor Summary	
public	ResourceServiceGetServiceMinorVersionResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetServiceMinorVersionResponse

public ResourceServiceGetServiceMinorVersionResponse()

Methods

getReturn

public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetSourcesWithThisTargetByACLRelationship

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByACLRelationship

public class **ResourceServiceGetSourcesWithThisTargetByACLRelationship**
extends Object

Constructor Summary

public	ResourceServiceGetSourcesWithThisTargetByACLRelationship()

Method Summary

String	getAuthToken()
String	getSourceResourceId()
void	setAuthToken(String authToken)
void	setSourceResourceId(String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourcesWithThisTargetByACLRelationship

public **ResourceServiceGetSourcesWithThisTargetByACLRelationship**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceResourceId

public String **getSourceResourceId**()

Returns:
returns String

setSourceResourceId

public void **setSourceResourceId**(String sourceResourceId)

Parameters:
sourceResourceId - the value for the sourceResourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse

public class ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse

extends Object

Constructor Summary	
public	ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse

public ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetSourcesWithThisTargetByRelationship



```
public class ResourceServiceGetSourcesWithThisTargetByRelationship
extends Object
```

Constructor Summary	
public	ResourceServiceGetSourcesWithThisTargetByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

```
ResourceServiceGetSourcesWithThisTargetByRelationship
public ResourceServiceGetSourcesWithThisTargetByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetSourcesWithThisTargetByRelationshipCount

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByRelationshipCount

public class **ResourceServiceGetSourcesWithThisTargetByRelationshipCount**
extends Object

Constructor Summary

public	ResourceServiceGetSourcesWithThisTargetByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourcesWithThisTargetByRelationshipCount

public **ResourceServiceGetSourcesWithThisTargetByRelationshipCount**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse

public class ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse

extends Object

Constructor Summary	
public	ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse

public ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse()

Methods

getReturn

public int getReturn()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId

public class ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId
extends Object

Constructor Summary	
public	ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId

public ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public class ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetSourcesWithThisTargetByRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourcesWithThisTargetByRelationshipResponse

public class ResourceServiceGetSourcesWithThisTargetByRelationshipResponse
extends Object

Constructor Summary	
public	ResourceServiceGetSourcesWithThisTargetByRelationshipResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetSourcesWithThisTargetByRelationshipResponse
public ResourceServiceGetSourcesWithThisTargetByRelationshipResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetSourceURIWithThisTargetByRelatiobnship

```
java.lang.Object
├-
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelatiobnship
```

public class ResourceServiceGetSourceURIWithThisTargetByRelatiobnship
extends Object

Constructor Summary	
public	ResourceServiceGetSourceURIWithThisTargetByRelatiobnship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelatiobnship
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

```
public class ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId
extends Object
```

Constructor Summary

public	ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public class ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse

```
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

public void **setReturn**(List _return)

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public class ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetSourceURIWithThisTargetByRelationship

```
java.lang.Object
├-
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelationship
```

```
public class ResourceServiceGetSourceURIWithThisTargetByRelationship
extends Object
```

Constructor Summary	
public	ResourceServiceGetSourceURIWithThisTargetByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationship

```
public ResourceServiceGetSourceURIWithThisTargetByRelationship()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

java.lang.Object

↓

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public class ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

extends Object

Constructor Summary	
public	ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId

public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class

ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse



public class ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

extends Object

Constructor Summary	
public	ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse

public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public class ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetTargetsAsURIByRelationship



public class ResourceServiceGetTargetsAsURIByRelationship
extends Object

Constructor Summary	
public	ResourceServiceGetTargetsAsURIByRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsAsURIByRelationship
public ResourceServiceGetTargetsAsURIByRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws
Class ResourceServiceGetTargetsAsURIByRelationshipForSourceId

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsAsURIByRelationshipForSourceId

public class ResourceServiceGetTargetsAsURIByRelationshipForSourceId
extends Object

Constructor Summary	
public	ResourceServiceGetTargetsAsURIByRelationshipForSourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetTargetsAsURIByRelationshipForSourceId
public ResourceServiceGetTargetsAsURIByRelationshipForSourceId()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse

```
public class ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse

```
public ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsAsURIByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsAsURIByRelationshipResponse

public class ResourceServiceGetTargetsAsURIByRelationshipResponse
extends Object

Constructor Summary

public	ResourceServiceGetTargetsAsURIByRelationshipResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsAsURIByRelationshipResponse

public ResourceServiceGetTargetsAsURIByRelationshipResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsByRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationship

public class **ResourceServiceGetTargetsByRelationship**
extends Object

Constructor Summary

public	ResourceServiceGetTargetsByRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsByRelationship

public **ResourceServiceGetTargetsByRelationship**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsByRelationshipCount

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationshipCount

```
public class ResourceServiceGetTargetsByRelationshipCount
extends Object
```

Constructor Summary

public	ResourceServiceGetTargetsByRelationshipCount()

Method Summary

String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResource (Resource sourceResource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsByRelationshipCount

```
public ResourceServiceGetTargetsByRelationshipCount()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetTargetsByRelationshipCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationshipCountResponse

public class ResourceServiceGetTargetsByRelationshipCountResponse
extends Object

Constructor Summary	
public	ResourceServiceGetTargetsByRelationshipCountResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetTargetsByRelationshipCountResponse

public ResourceServiceGetTargetsByRelationshipCountResponse()

Methods

getReturn

public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsByRelationshipForSourceId

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationshipForSourceId
```

```
public class ResourceServiceGetTargetsByRelationshipForSourceId
extends Object
```

Constructor Summary	
public	ResourceServiceGetTargetsByRelationshipForSourceId()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
String	getSourceResourceId()
void	setAuthToken (String authToken)
void	setRelationshipType (int relationshipType)
void	setSourceResourceId (String sourceResourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

```
ResourceServiceGetTargetsByRelationshipForSourceId
public ResourceServiceGetTargetsByRelationshipForSourceId()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResourceId

```
public String getSourceResourceId()
```

Returns:

returns String

setSourceResourceId

```
public void setSourceResourceId(String sourceResourceId)
```

Parameters:

sourceResourceId - the value for the sourceResourceId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsByRelationshipForSourceIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationshipForSourceIdResponse

public class ResourceServiceGetTargetsByRelationshipForSourceIdResponse
extends Object

Constructor Summary

public	ResourceServiceGetTargetsByRelationshipForSourceIdResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsByRelationshipForSourceIdResponse

public ResourceServiceGetTargetsByRelationshipForSourceIdResponse()

Methods

getReturn

public List getReturn()

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsByRelationshipResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsByRelationshipResponse

```
public class ResourceServiceGetTargetsByRelationshipResponse
extends Object
```

Constructor Summary

public	ResourceServiceGetTargetsByRelationshipResponse()

Method Summary

List	getReturn()

void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsByRelationshipResponse

```
public ResourceServiceGetTargetsByRelationshipResponse()
```

Methods

getReturn

```
public List getReturn()
```

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsWithRelationshipForResource

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsWithRelationshipForResource

public class **ResourceServiceGetTargetsWithRelationshipTypeForResource**
extends Object

Constructor Summary

public	ResourceServiceGetTargetsWithRelationshipTypeForResource()

Method Summary

String	getAuthToken()
Resource	getResource()
void	setAuthToken(String authToken)
void	setResource(Resource resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsWithRelationshipTypeForResource

public **ResourceServiceGetTargetsWithRelationshipTypeForResource()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResource

public [Resource](#) **getResource**()

Returns:
returns Resource

setResource

public void **setResource**([Resource](#) resource)

Parameters:
resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceGetTargetsWithRelationshipTypeForResourceById

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsWithRelationshipTypeForResourceById

public class **ResourceServiceGetTargetsWithRelationshipTypeForResourceById**
extends Object

Constructor Summary

public	ResourceServiceGetTargetsWithRelationshipTypeForResourceById()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsWithRelationshipTypeForResourceById

public **ResourceServiceGetTargetsWithRelationshipTypeForResourceById**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public class **ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse**
extends Object

Constructor Summary

public	ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()

Method Summary

List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse

public **ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse()**

Methods

getReturn

public List **getReturn()**

Returns:

returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

public class ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse
extends Object

Constructor Summary	
public	ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse
public ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceHasReadPermission

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasReadPermission

public class **ResourceServiceHasReadPermission**
extends Object

Constructor Summary

public	ResourceServiceHasReadPermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceHasReadPermission

public **ResourceServiceHasReadPermission**()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasReadPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasReadPermissionResponse

public class ResourceServiceHasReadPermissionResponse
extends Object

Constructor Summary	
public	ResourceServiceHasReadPermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceHasReadPermissionResponse
public ResourceServiceHasReadPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasReverseRelationship

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasReverseRelationship

public class ResourceServiceHasReverseRelationship
extends Object

Constructor Summary	
public	ResourceServiceHasReverseRelationship()

Method Summary	
String	getAuthToken()
int	getRelationshipType()
Resource	getSourceResource()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceResource(Resource sourceResource)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceHasReverseRelationship
public ResourceServiceHasReverseRelationship()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceResource

```
public Resource getSourceResource()
```

Returns:

returns Resource

setSourceResource

```
public void setSourceResource(Resource sourceResource)
```

Parameters:

sourceResource - the value for the sourceResource property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

getTargetId

public String **getTargetId**()

Returns:

returns String

setTargetId

public void **setTargetId**(String targetId)

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasReverseRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasReverseRelationshipResponse

public class ResourceServiceHasReverseRelationshipResponse
extends Object

Constructor Summary	
public	ResourceServiceHasReverseRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceHasReverseRelationshipResponse

public ResourceServiceHasReverseRelationshipResponse()

Methods

isReturn

public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasWritePermission

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasWritePermission

public class ResourceServiceHasWritePermission
extends Object

Constructor Summary	
public	ResourceServiceHasWritePermission()

Method Summary	
String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceHasWritePermission
public ResourceServiceHasWritePermission()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasWritePermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasWritePermissionResponse

public class ResourceServiceHasWritePermissionResponse
extends Object

Constructor Summary	
public	ResourceServiceHasWritePermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceHasWritePermissionResponse
public ResourceServiceHasWritePermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasXPermission

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasXPermission

public class **ResourceServiceHasXPermission**
extends Object

Constructor Summary

public	ResourceServiceHasXPermission()

Method Summary

String	getAuthToken()
String	getSourceId()
String	getTargetId()
void	setAuthToken (String authToken)
void	setSourceId (String sourceId)
void	setTargetId (String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceHasXPermission

public **ResourceServiceHasXPermission()**

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getSourceId

```
public String getSourceId()
```

Returns:

returns String

setSourceId

```
public void setSourceId(String sourceId)
```

Parameters:

sourceId - the value for the sourceId property

getTargetId

```
public String getTargetId()
```

Returns:

returns String

setTargetId

```
public void setTargetId(String targetId)
```

Parameters:

targetId - the value for the targetId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceHasXPermissionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceHasXPermissionResponse

public class ResourceServiceHasXPermissionResponse
extends Object

Constructor Summary	
public	ResourceServiceHasXPermissionResponse()

Method Summary	
boolean	isReturn()
void	setReturn (boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceHasXPermissionResponse
public ResourceServiceHasXPermissionResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceInsert

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceInsert

public class **ResourceServiceInsert**
extends Object

Constructor Summary

public	ResourceServiceInsert()

Method Summary

String	getAuthToken()
Resource	getResource()
void	setAuthToken (String authToken)
void	setResource (Resource resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceInsert

public **ResourceServiceInsert**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Resource getResource()
```

Returns:

returns Resource

setResource

```
public void setResource(Resource resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceInsertResource

java.lang.Object

└─

com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceInsertResource

public class ResourceServiceInsertResource

extends Object

Constructor Summary	
public	ResourceServiceInsertResource()

Method Summary	
String	getAuthToken()
String	getParentId()
Resource	getResource()
void	setAuthToken (String authToken)
void	setParentId (String parentId)
void	setResource (Resource resource)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

ResourceServiceInsertResource

public ResourceServiceInsertResource()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Resource getResource()
```

Returns:

returns Resource

setResource

```
public void setResource(Resource resource)
```

Parameters:

resource - the value for the resource property

getParentId

```
public String getParentId()
```

Returns:

returns String

setParentId

```
public void setParentId(String parentId)
```

Parameters:

parentId - the value for the parentId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceInsertResourceResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceInsertResourceResponse

public class ResourceServiceInsertResourceResponse
extends Object

Constructor Summary	
public	ResourceServiceInsertResourceResponse()

Method Summary	
Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceInsertResourceResponse
public ResourceServiceInsertResourceResponse()

Methods

getReturn
public [Resource](#) getReturn()

Returns:
returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceInsertResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceInsertResponse

public class **ResourceServiceInsertResponse**
extends Object

Constructor Summary

public	ResourceServiceInsertResponse()

Method Summary

Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceInsertResponse

public **ResourceServiceInsertResponse()**

Methods

getReturn

public [Resource](#) **getReturn()**

Returns:

returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceIsDisabled

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceIsDisabled

public class **ResourceServiceIsDisabled**
extends Object

Constructor Summary

public	ResourceServiceIsDisabled()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceIsDisabled

public **ResourceServiceIsDisabled()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceIsDisabledResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceIsDisabledResponse

public class ResourceServiceIsDisabledResponse
extends Object

Constructor Summary	
public	ResourceServiceIsDisabledResponse()

Method Summary	
boolean	isReturn()
void	setReturn (boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceIsDisabledResponse
public ResourceServiceIsDisabledResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceIsValidResourceID

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceIsValidResourceID

```
public class ResourceServiceIsValidResourceID
extends Object
```

Constructor Summary

public	ResourceServiceIsValidResourceID()

Method Summary

String	getAuthToken()
String	getResourceId()
void	setAuthToken(String authToken)
void	setResourceId(String resourceId)

Methods inherited from class java.lang.Object

equality, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceIsValidResourceID

```
public ResourceServiceIsValidResourceID()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResourceId

public String **getResourceId**()

Returns:
returns String

setResourceId

public void **setResourceId**(String resourceId)

Parameters:
resourceId - the value for the resourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceIsValidResourceIDResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceIsValidResourceIDResponse

public class ResourceServiceIsValidResourceIDResponse
extends Object

Constructor Summary

public	ResourceServiceIsValidResourceIDResponse()

Method Summary

boolean	isReturn()

void	setReturn(boolean _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceIsValidResourceIDResponse

public ResourceServiceIsValidResourceIDResponse()

Methods

isReturn

public boolean isReturn()

Returns:

returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceLoadAdditional

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceLoadAdditional

public class **ResourceServiceLoadAdditional**
extends Object

Constructor Summary

public	ResourceServiceLoadAdditional()

Method Summary

String	getAuthToken()
String	getSourceId()
void	setAuthToken(String authToken)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceLoadAdditional

public **ResourceServiceLoadAdditional()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceLoadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceLoadAdditionalResponse

public class ResourceServiceLoadAdditionalResponse
extends Object

Constructor Summary	
public	ResourceServiceLoadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceLoadAdditionalResponse
public ResourceServiceLoadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceResetState

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceResetState

public class **ResourceServiceResetState**
extends Object

Constructor Summary

public	ResourceServiceResetState()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceResetState

public **ResourceServiceResetState()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceResetStateResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceResetStateResponse

public class ResourceServiceResetStateResponse
extends Object

Constructor Summary

public	ResourceServiceResetStateResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceResetStateResponse

public ResourceServiceResetStateResponse()

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceResolveRelationship

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceResolveRelationship

```
public class ResourceServiceResolveRelationship
extends Object
```

Constructor Summary

public	ResourceServiceResolveRelationship()

Method Summary

String	getAuthToken()
int	getRelationshipType()
String	getSourceId()
String	getTargetId()
void	setAuthToken(String authToken)
void	setRelationshipType(int relationshipType)
void	setSourceId(String sourceId)
void	setTargetId(String targetId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceResolveRelationship

```
public ResourceServiceResolveRelationship()
```

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getSourceId

public String **getSourceId()**

Returns:

returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:

sourceId - the value for the sourceId property

getTargetId

public String **getTargetId()**

Returns:

returns String

setTargetId

public void **setTargetId**(String targetId)

Parameters:

targetId - the value for the targetId property

getRelationshipType

```
public int getRelationshipType()
```

Returns:

returns int

setRelationshipType

```
public void setRelationshipType(int relationshipType)
```

Parameters:

relationshipType - the value for the relationshipType property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceResolveRelationshipResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceResolveRelationshipResponse

public class ResourceServiceResolveRelationshipResponse
extends Object

Constructor Summary	
public	ResourceServiceResolveRelationshipResponse()

Method Summary	
boolean	isReturn()
void	setReturn(boolean _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceResolveRelationshipResponse
public ResourceServiceResolveRelationshipResponse()

Methods

isReturn
public boolean isReturn()

Returns:
returns boolean

setReturn

```
public void setReturn(boolean _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUnloadAdditional

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUnloadAdditional

public class ResourceServiceUnloadAdditional
extends Object

Constructor Summary	
public	ResourceServiceUnloadAdditional()

Method Summary	
String	getAuthToken()
String	getSourceId()
void	setAuthToken(String authToken)
void	setSourceId(String sourceId)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceUnloadAdditional
public ResourceServiceUnloadAdditional()

Methods

getAuthToken
public String getAuthToken()

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getSourceId

public String **getSourceId**()

Returns:
returns String

setSourceId

public void **setSourceId**(String sourceId)

Parameters:
sourceId - the value for the sourceId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUnloadAdditionalResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUnloadAdditionalResponse

public class ResourceServiceUnloadAdditionalResponse
extends Object

Constructor Summary	
public	ResourceServiceUnloadAdditionalResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceUnloadAdditionalResponse
public ResourceServiceUnloadAdditionalResponse()

Methods

getReturn
public Void getReturn()

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUpdate

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdate

public class **ResourceServiceUpdate**
extends Object

Constructor Summary

public	ResourceServiceUpdate()

Method Summary

String	getAuthToken()
Resource	getResource()
void	setAuthToken (String authToken)
void	setResource (Resource resource)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceUpdate

public **ResourceServiceUpdate**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResource

```
public Resource getResource()
```

Returns:

returns Resource

setResource

```
public void setResource(Resource resource)
```

Parameters:

resource - the value for the resource property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUpdateACLForResourceById

```
java.lang.Object
├
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdateACLForResourceById
```

```
public class ResourceServiceUpdateACLForResourceById
extends Object
```

Constructor Summary	
public	ResourceServiceUpdateACLForResourceById()

Method Summary	
String	getAuthToken()
List	getData()
String	getResourceId()
void	setAuthToken (String authToken)
void	setData (List data)
void	setResourceId (String resourceId)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

```
ResourceServiceUpdateACLForResourceById
public ResourceServiceUpdateACLForResourceById()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getResourceId

```
public String getResourceId()
```

Returns:

returns String

setResourceId

```
public void setResourceId(String resourceId)
```

Parameters:

resourceId - the value for the resourceId property

getData

```
public List getData()
```

Returns:

returns List

setData

```
public void setData(List data)
```

Parameters:

data - the value for the data property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class ResourceServiceUpdateACLForResourceByIdResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdateACLForResourceByIdResponse

public class ResourceServiceUpdateACLForResourceByIdResponse
extends Object

Constructor Summary

public	ResourceServiceUpdateACLForResourceByIdResponse()

Method Summary

Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceUpdateACLForResourceByIdResponse

public ResourceServiceUpdateACLForResourceByIdResponse()

Methods

getReturn

public Void **getReturn()**

Returns:

returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUpdateResources

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdateResources

```
public class ResourceServiceUpdateResources
extends Object
```

Constructor Summary

public	ResourceServiceUpdateResources()

Method Summary

String	getAuthToken()
List	getResources()
void	setAuthToken(String authToken)
void	setResources(List resources)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceUpdateResources

```
public ResourceServiceUpdateResources()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:
returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:
authToken - the value for the authToken property

getResources

public List **getResources**()

Returns:
returns List

setResources

public void **setResources**(List resources)

Parameters:
resources - the value for the resources property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUpdateResourcesResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdateResource
sResponse

public class ResourceServiceUpdateResourcesResponse
extends Object

Constructor Summary	
public	ResourceServiceUpdateResourcesResponse()

Method Summary	
List	getReturn()
void	setReturn(List _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ResourceServiceUpdateResourcesResponse
public ResourceServiceUpdateResourcesResponse()

Methods

getReturn
public List getReturn()

Returns:
returns List

setReturn

```
public void setReturn(List _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ResourceServiceUpdateResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ResourceServiceUpdateResponse

public class ResourceServiceUpdateResponse
extends Object

Constructor Summary	
public	ResourceServiceUpdateResponse()

Method Summary	
Resource	getReturn()
void	setReturn(Resource _return)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceUpdateResponse
public ResourceServiceUpdateResponse()

Methods

getReturn
public [Resource](#) getReturn()

Returns:
returns Resource

setReturn

```
public void setReturn(Resource _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceCount

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceCount

public class SecurityEventServiceCount
extends Object

Constructor Summary	
public	SecurityEventServiceCount()

Method Summary	
String	getAuthToken()
long	getEndTime()
long	getStartTime()
void	setAuthToken (String authToken)
void	setEndTime (long endTime)
void	setStartTime (long startTime)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceCount
public SecurityEventServiceCount()

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getStartTime

```
public long getStartTime()
```

Returns:

returns long

setStartTime

```
public void setStartTime(long startTime)
```

Parameters:

startTime - the value for the startTime property

getEndTime

```
public long getEndTime()
```

Returns:

returns long

setEndTime

```
public void setEndTime(long endTime)
```

Parameters:

endTime - the value for the endTime property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceCountResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceCountResponse

public class SecurityEventServiceCountResponse
extends Object

Constructor Summary	
public	SecurityEventServiceCountResponse()

Method Summary	
EventStatistics	getReturn()
void	setReturn(EventStatistics _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceCountResponse
public SecurityEventServiceCountResponse()

Methods

getReturn
public [EventStatistics](#) getReturn()

Returns:
returns EventStatistics

setReturn

```
public void setReturn(EventStatistics _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetSecurityEvents

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEvents

public class **SecurityEventServiceGetSecurityEvents**
extends Object

Constructor Summary

public	SecurityEventServiceGetSecurityEvents()

Method Summary

String	getAuthToken()
long	getEndMillis()
List	getIds()
long	getStartMillis()
ArcField	getTimeField()
void	setAuthToken (String authToken)
void	setEndMillis (long endMillis)
void	setIds (List ids)
void	setStartMillis (long startMillis)
void	setTimeField (ArcField timeField)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetSecurityEvents

public SecurityEventServiceGetSecurityEvents()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getIds

public List **getIds**()

Returns:

returns List

setIds

public void **setIds**(List ids)

Parameters:

ids - the value for the ids property

getTimeField

public [ArcField](#) **getTimeField**()

Returns:

returns ArcField

setTimeField

public void **setTimeField**([ArcField](#) timeField)

Parameters:

timeField - the value for the timeField property

getStartMillis

public long **getStartMillis**()

Returns:

returns long

setStartMillis

public void **setStartMillis**(long startMillis)

Parameters:

startMillis - the value for the startMillis property

getEndMillis

public long **getEndMillis**()

Returns:

returns long

setEndMillis

public void **setEndMillis**(long endMillis)

Parameters:

endMillis - the value for the endMillis property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetSecurityEventsByProfile

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEventsByProfile

public class **SecurityEventServiceGetSecurityEventsByProfile**
extends Object

Constructor Summary

public	SecurityEventServiceGetSecurityEventsByProfile()

Method Summary

String	getAuthToken()
long	getEndMillis()
List	getIds()
SecurityEventFieldProfile	getProfile()
long	getStartMillis()
ArcField	getTimeField()
void	setAuthToken(String authToken)
void	setEndMillis(long endMillis)
void	setIds(List ids)
void	setProfile(SecurityEventFieldProfile profile)
void	setStartMillis(long startMillis)
void	setTimeField(ArcField timeField)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetSecurityEventsByProfile

```
public SecurityEventServiceGetSecurityEventsByProfile()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getIds

```
public List getId()
```

Returns:

returns List

setIds

```
public void setId(List ids)
```

Parameters:

ids - the value for the ids property

getTimeField

```
public ArcField getTimeField()
```

Returns:

returns ArcField

setTimeField

```
public void setTimeField(ArcField timeField)
```

Parameters:

timeField - the value for the timeField property

getStartMillis

```
public long getStartMillis()
```

Returns:

returns long

setStartMillis

```
public void setStartMillis(long startMillis)
```

Parameters:

startMillis - the value for the startMillis property

getEndMillis

```
public long getEndMillis()
```

Returns:

returns long

setEndMillis

```
public void setEndMillis(long endMillis)
```

Parameters:

endMillis - the value for the endMillis property

getProfile

public [SecurityEventFieldProfile](#) **getProfile()**

Returns:

returns SecurityEventFieldProfile

setProfile

public void **setProfile**([SecurityEventFieldProfile](#) profile)

Parameters:

profile - the value for the profile property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetSecurityEventsByProfileResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEventsByProfileResponse

public class SecurityEventServiceGetSecurityEventsByProfileResponse
extends Object

Constructor Summary	
public	SecurityEventServiceGetSecurityEventsByProfileResponse()

Method Summary	
SecurityEvent[]	getReturn()
void	setReturn(SecurityEvent[] _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceGetSecurityEventsByProfileResponse

public SecurityEventServiceGetSecurityEventsByProfileResponse()

Methods

getReturn

public [SecurityEvent\[\]](#) getReturn()

Returns:
returns SecurityEvent[]

setReturn

```
public void setReturn(SecurityEvent\[\] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetSecurityEventsResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEventsResponse

public class SecurityEventServiceGetSecurityEventsResponse
extends Object

Constructor Summary

public	SecurityEventServiceGetSecurityEventsResponse()

Method Summary

SecurityEvent[]	getReturn()
void	setReturn(SecurityEvent[] _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetSecurityEventsResponse

public SecurityEventServiceGetSecurityEventsResponse()

Methods

getReturn

public [SecurityEvent\[\]](#) getReturn()

Returns:

returns SecurityEvent[]

setReturn

```
public void setReturn(SecurityEvent\[\] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetSecurityEventsWithTimeout

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEventsWithTimeout

public class SecurityEventServiceGetSecurityEventsWithTimeout
extends Object

Constructor Summary

public	SecurityEventServiceGetSecurityEventsWithTimeout()

Method Summary

String	getAuthToken()
long	getEndMillis()
List	getIds()
SecurityEventFieldProfile	getProfile()
int	getQueryTimeout()
long	getStartMillis()
ArcField	getTimeField()
void	setAuthToken(String authToken)
void	setEndMillis(long endMillis)
void	setIds(List ids)
void	setProfile(SecurityEventFieldProfile profile)
void	setQueryTimeout(int queryTimeout)
void	setStartMillis(long startMillis)

void	setTimeField (ArcField timeField)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

SecurityEventServiceGetSecurityEventsWithTimeout

```
public SecurityEventServiceGetSecurityEventsWithTimeout()
```

Methods

getAuthToken

```
public String getAuthToken()
```

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

getIds

```
public List getId()
```

Returns:

returns List

setIds

```
public void setId(List ids)
```

Parameters:

ids - the value for the ids property

getTimeField

public [ArcField](#) getTimeField()

Returns:

returns ArcField

setTimeField

public void setTimeField([ArcField](#) timeField)

Parameters:

timeField - the value for the timeField property

getStartMillis

public long getStartMillis()

Returns:

returns long

setStartMillis

public void setStartMillis(long startMillis)

Parameters:

startMillis - the value for the startMillis property

getEndMillis

public long getEndMillis()

Returns:

returns long

setEndMillis

public void setEndMillis(long endMillis)

Parameters:

endMillis - the value for the endMillis property

getProfile

public [SecurityEventFieldProfile](#) getProfile()

Returns:

returns SecurityEventFieldProfile

setProfile

public void setProfile([SecurityEventFieldProfile](#) profile)

Parameters:

profile - the value for the profile property

getQueryTimeout

public int getQueryTimeout()

Returns:

returns int

setQueryTimeout

public void setQueryTimeout(int queryTimeout)

Parameters:

queryTimeout - the value for the queryTimeout property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceGetSecurityEventsWithTimeoutResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetSecurityEventsWithTimeoutResponse

public class SecurityEventServiceGetSecurityEventsWithTimeoutResponse
extends Object

Constructor Summary	
public	SecurityEventServiceGetSecurityEventsWithTimeoutResponse()

Method Summary	
SecurityEvent[]	getReturn()
void	setReturn(SecurityEvent[] _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceGetSecurityEventsWithTimeoutResponse
public SecurityEventServiceGetSecurityEventsWithTimeoutResponse()

Methods

getReturn
public [SecurityEvent\[\]](#) getReturn()

Returns:
returns SecurityEvent[]

setReturn

```
public void setReturn(SecurityEvent\[\] _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetServiceMajorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetServiceMajorVersion

public class **SecurityEventServiceGetServiceMajorVersion**
extends Object

Constructor Summary

public	SecurityEventServiceGetServiceMajorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetServiceMajorVersion

public **SecurityEventServiceGetServiceMajorVersion()**

Methods

getAuthToken

public String **getAuthToken()**

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetServiceMajorVersionResponse

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetServiceMajorVersionResponse

public class SecurityEventServiceGetServiceMajorVersionResponse
extends Object

Constructor Summary

public	SecurityEventServiceGetServiceMajorVersionResponse()

Method Summary

int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetServiceMajorVersionResponse

public SecurityEventServiceGetServiceMajorVersionResponse()

Methods

getReturn

public int getReturn()

Returns:

returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws Class SecurityEventServiceGetServiceMinorVersion

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetServiceMinorVersion

public class **SecurityEventServiceGetServiceMinorVersion**
extends Object

Constructor Summary

public	SecurityEventServiceGetServiceMinorVersion()

Method Summary

String	getAuthToken()
void	setAuthToken(String authToken)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceGetServiceMinorVersion

public **SecurityEventServiceGetServiceMinorVersion**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

```
public void setAuthToken(String authToken)
```

Parameters:

authToken - the value for the authToken property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceGetServiceMinorVersionResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceGetServiceMinorVersionResponse

public class SecurityEventServiceGetServiceMinorVersionResponse
extends Object

Constructor Summary	
public	SecurityEventServiceGetServiceMinorVersionResponse()

Method Summary	
int	getReturn()
void	setReturn(int _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceGetServiceMinorVersionResponse
public SecurityEventServiceGetServiceMinorVersionResponse()

Methods

getReturn
public int getReturn()

Returns:
returns int

setReturn

```
public void setReturn(int _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceSetAnnotationStage

java.lang.Object



com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceSetAnnotationStage

```
public class SecurityEventServiceSetAnnotationStage
extends Object
```

Constructor Summary

public	SecurityEventServiceSetAnnotationStage()

Method Summary

String	getAuthToken()
String	getComment()
Long	getEventId()
String	getStageId()
String	getUserId()
void	setAuthToken(String authToken)
void	setComment(String comment)
void	setEventId(Long eventId)
void	setStageId(String stageId)
void	setUserId(String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventServiceSetAnnotationStage

public **SecurityEventServiceSetAnnotationStage**()

Methods

getAuthToken

public String **getAuthToken**()

Returns:

returns String

setAuthToken

public void **setAuthToken**(String authToken)

Parameters:

authToken - the value for the authToken property

getEventId

public Long **getEventId**()

Returns:

returns Long

setEventId

public void **setEventId**(Long eventId)

Parameters:

eventId - the value for the eventId property

getStageId

public String **getStageId**()

Returns:

returns String

setStageId

public void **setStageId**(String stageId)

Parameters:

stageId - the value for the stageId property

getComment

public String **getComment**()

Returns:

returns String

setComment

public void **setComment**(String comment)

Parameters:

comment - the value for the comment property

getUserId

public String **getUserId**()

Returns:

returns String

setUserId

public void **setUserId**(String userId)

Parameters:

userId - the value for the userId property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class SecurityEventServiceSetAnnotationStageResponse

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.axis2.jaxws.SecurityEventServiceSetAnnotationStageResponse

public class SecurityEventServiceSetAnnotationStageResponse
extends Object

Constructor Summary	
public	SecurityEventServiceSetAnnotationStageResponse()

Method Summary	
Void	getReturn()
void	setReturn(Void _return)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

SecurityEventServiceSetAnnotationStageResponse
public SecurityEventServiceSetAnnotationStageResponse()

Methods

getReturn
public Void **getReturn()**

Returns:
returns Void

setReturn

```
public void setReturn(Void _return)
```

Parameters:

_return - the value for the _return property

com.arcsight.product.manager.resource.service.v1.axis2.jaxws

Class ServiceExceptionBean

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.axis2.jaxws.ServiceExceptionBean

```
public class ServiceExceptionBean
extends Object
```

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary

public	ServiceExceptionBean()

Method Summary

int	getErrorCode()
String	getMessage()
void	setErrorCode(int errorCode)
void	setMessage(String message)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ServiceExceptionBean

```
public ServiceExceptionBean()
```

Methods

getErrorCode

```
public int getErrorCode()
```

Returns:
returns int

setErrorCode

public void **setErrorCode**(int errorCode)

Parameters:
errorCode - the value for the errorCode property

getMessage

public String **getMessage**()

Returns:
returns String

setMessage

public void **setMessage**(String message)

Parameters:
message - the value for the message property

Package

com.arcsight.product.manager.resource.service.v1.model

com.arcsight.product.manager.resource.service.v1.model

Class ACLDataHolder

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ACLDataHolder

All Implemented Interfaces:

Comparable, Serializable

```
public class ACLDataHolder
extends Object
implements Serializable, Comparable
```

Describes read/write permissions between a resource and other resources. Depending on [isForSourceRelationship\(\)](#) the instances of this class represent either sources or targets end-points of the relations.

JSON prototype

Nested Class Summary

class	ACLDataHolder.UpdateType ACLDataHolder.UpdateType

Constructor Summary

public	ACLDataHolder()

Method Summary

int	compareTo(ACLDataHolder o) Implementation of Comparable API.
int	getContainedResourceType() Gets the contained resource type of this ACL Data.
String	getId() Gets the id of this ACL Data.
int	getOtherRelationshipType() Gets the other relationship type.
ACLDataHolder.UpdateType	getUpdateType() Gets the update type of this ACL Data.
String	getUri() Gets URI for this ACL data.
boolean	isEditable() Return true if the ACL data is editable.

boolean	<code>isForSourceRelationship()</code> Returns true if this ACL data is for source relationship.
boolean	<code>isOtherRelationshipTypeSet()</code> Returns True if there is a relationship type set.
boolean	<code>isReadable()</code> Return true if the ACL data is readable.
boolean	<code>isReadEditable()</code> Return true if the ACL data is readEditable.
boolean	<code>isWritable()</code> Return true if the ACL data is writable.
boolean	<code>isWriteEditable()</code> Return true if the ACL data is writeEditable.
void	<code>setContainedResourceType(int containedResourceType)</code> Sets the contained resource type for this ACL Data.
void	<code>setEditable(boolean editable)</code> * Sets whether the ACL data is editable.
void	<code>setForSourceRelationship(boolean forSourceRelationship)</code> Sets whether this ACL data is for source relationship.
void	<code>setId(String id)</code> Sets the id for this ACL Data.
void	<code>setOtherRelationshipType(int otherRelationshipType)</code> Sets the other relationship type.
void	<code>setOtherRelationshipTypeSet(boolean otherRelationshipTypeSet)</code> Sets whether there is a relationship type.
void	<code>setReadable(boolean read)</code> Sets whether the ACL data is readable.
void	<code>setReadEditable(boolean readEditable)</code> * Sets whether the ACL data is readEditable.
void	<code>setUpdateType(ACLDataHolder.UpdateType updateType)</code> Sets the update type for this ACL Data.
void	<code>setUri(String uri)</code> Sets URI for this ACL data.
void	<code>setWritable(boolean write)</code> Sets whether the ACL data is writable.
void	<code>setWriteEditable(boolean writeEditable)</code> * Sets whether the ACL data is writeEditable.

Methods inherited from class `java.lang.Object`

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

compareTo

Constructors

ACLDataHolder

```
public ACLDataHolder()
```

Methods

compareTo

```
public int compareTo(ACLDataHolder o)
```

Implementation of Comparable API.

Parameters:

o

Returns:

getOtherRelationshipType

```
public int getOtherRelationshipType()
```

Gets the other relationship type.

Returns:

The otherRelationshipType

setOtherRelationshipType

```
public void setOtherRelationshipType(int otherRelationshipType)
```

Sets the other relationship type.

Parameters:

otherRelationshipType - The other relationship type to set.

isOtherRelationshipTypeSet

```
public boolean isOtherRelationshipTypeSet()
```

Returns True if there is a relationship type set.

Returns:

True if there is a relationship type set; otherwise, false.

setOtherRelationshipTypeSet

```
public void setOtherRelationshipTypeSet(boolean otherRelationshipTypeSet)
```

Sets whether there is a relationship type.

Parameters:

otherRelationshipTypeSet - If true, there is a relationship type set.

isReadable

```
public boolean isReadable()
```

Return true if the ACL data is readable. Otherwise, return false.

Returns:

True if the ACL data is readable. Otherwise, return false.

setReadable

```
public void setReadable(boolean read)
```

Sets whether the ACL data is readable.

Parameters:

read - If true, the ACL data is readable.

isWritable

```
public boolean isWritable()
```

Return true if the ACL data is writable. Otherwise, return false.

Returns:

True if the ACL data is writable. Otherwise, return false.

setWritable

```
public void setWritable(boolean write)
```

Sets whether the ACL data is writable.

Parameters:

write - If true, the ACL data is writable.

isEditable

```
public boolean isEditable()
```

Return true if the ACL data is editable. Otherwise, return false.

Returns:

True if the ACL data is editable. Otherwise, return false.

setEditable

```
public void setEditable(boolean editable)
```

* Sets whether the ACL data is editable.

Parameters:

`editable` - If true, the ACL data is editable.

isReadEditable

```
public boolean isReadEditable()
```

Return true if the ACL data is readEditable. Otherwise, return false.

Returns:

True if the ACL data is readEditable. Otherwise, return false.

setReadEditable

```
public void setReadEditable(boolean readEditable)
```

* Sets whether the ACL data is readEditable.

Parameters:

`readEditable` - If true, the ACL data is readEditable.

isWriteEditable

```
public boolean isWriteEditable()
```

Return true if the ACL data is writeEditable. Otherwise, return false.

Returns:

True if the ACL data is writeEditable. Otherwise, return false.

setWriteEditable

```
public void setWriteEditable(boolean writeEditable)
```

* Sets whether the ACL data is writeEditable.

Parameters:

`readEditable` - If true, the ACL data is writeEditable.

setUri

```
public void setUri(String uri)
```

Sets URI for this ACL data.

Parameters:

uri - The URI to set for this ACL data.

getUri

```
public String getUri()
```

Gets URI for this ACL data.

Returns:

URI for this ACL data.

setUpdateType

```
public void setUpdateType(ACLDataHolder.UpdateType updateType)
```

Sets the update type for this ACL Data.

Parameters:

updateType - The update type for this ACL Data.

getUpdateType

```
public ACLDataHolder.UpdateType getUpdateType()
```

Gets the update type of this ACL Data.

Returns:

The update type of this ACL Data.

setId

```
public void setId(String id)
```

Sets the id for this ACL Data.

Parameters:

id - The id to set for this ACL Data.

getId

```
public String getId()
```

Gets the id of this ACL Data.

Returns:

The id of this ACL Data.

setContainedResourceType

```
public void setContainedResourceType(int containedResourceType)
```

Sets the contained resource type for this ACL Data.

Parameters:

containedResourceType - The contained resource type to set for this ACL Data.

getContainedResourceType

```
public int getContainedResourceType()
```

Gets the contained resource type of this ACL Data.

Returns:

The contained resource type of this ACL Data.

isForSourceRelationship

```
public boolean isForSourceRelationship()
```

Returns true if this ACL data is for source relationship.

Returns:

True if this ACL data is for source relationship; otherwise, false.

setForSourceRelationship

```
public void setForSourceRelationship(boolean forSourceRelationship)
```

Sets whether this ACL data is for source relationship.

Parameters:

forSourceRelationship - If true, this ACL data is for source relationship.

com.arcsight.product.manager.resource.service.v1.model

Class ACLDataHolder.UpdateType

java.lang.Object

└ java.lang.Enum

└ com.arcsight.product.manager.resource.service.v1.model.ACLDataHolder.UpdateType

All Implemented Interfaces:

Serializable, Comparable

public static final class **ACLDataHolder.UpdateType**
extends Enum

Field Summary

public static final	NEW New ACL Data
public static final	REMOVE Removing ACL Data
public static final	UPDATE Updating ACL Data

Method Summary

static ACLDataHolder.UpdateType	valueOf (String name)
static ACLDataHolder.UpdateType[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

NEW

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ACLDataHolder.UpdateType NEW
```

New ACL Data

UPDATE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ACLDataHolder.UpdateType UPDATE
```

Updating ACL Data

REMOVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ACLDataHolder.UpdateType REMOVE
```

Removing ACL Data

Methods

values

```
public static ACLDataHolder.UpdateType\[\] values()
```

valueOf

```
public static ACLDataHolder.UpdateType valueOf(String name)
```


com.arcsight.product.manager.resource.service.v1.model

Class AdminFeatureAvailability

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability

All Implemented Interfaces:
Serializable

public class **AdminFeatureAvailability**
extends Object
implements Serializable

This class represents the availability of an admin feature

Nested Class Summary

class	AdminFeatureAvailability.AdminFeature AdminFeatureAvailability.AdminFeature

Constructor Summary

public	AdminFeatureAvailability()

Method Summary

AdminFeatureAvailability.AdminFeature	getFeature()
boolean	isAvailable()
void	setAvailable (boolean available)
void	setFeature (AdminFeatureAvailability.AdminFeature feature)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

AdminFeatureAvailability
public **AdminFeatureAvailability()**

Methods

getFeature

public [AdminFeatureAvailability.AdminFeature](#) **getFeature()**

Returns:

the feature

setFeature

public void **setFeature**([AdminFeatureAvailability.AdminFeature](#) feature)

Parameters:

feature - the feature to set

isAvailable

public boolean **isAvailable**()

Returns:

the available

setAvailable

public void **setAvailable**(boolean available)

Parameters:

available - the available to set

com.arcsight.product.manager.resource.service.v1.model

Class AdminFeatureAvailability.AdminFeature

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeature

All Implemented Interfaces:

Serializable, Comparable

public static final class **AdminFeatureAvailability.AdminFeature**
extends Enum

Field Summary

public static final	Feature_Configuration
public static final	Feature_Configuration_Authentication
public static final	Feature_Configuration_License
public static final	Feature_Configuration_Server
public static final	Feature_Connector
public static final	Feature_Main_Admin
public static final	Feature_Main_AdvancedAdmin
public static final	Feature_Main_ArcSightWeb
public static final	Feature_Main_ConApp
public static final	Feature_Main_Dashboard
public static final	Feature_Main_GetStarted
public static final	Feature_Main_Preference
public static final	Feature_Storage

public static final	Feature_Storage_AllStorage
public static final	Feature_Storage_EventArchive
public static final	Feature_User

Method Summary

<code>static AdminFeatureAvailability.AdminFeature</code>	<code>valueOf(String name)</code>
<code>static AdminFeatureAvailability.AdminFeature[]</code>	<code>values()</code>

Methods inherited from class `java.lang.Enum`

`compareTo`, `equals`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

Feature_Main_GetStarted

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Main_GetStarted
```

Feature_Main_Admin

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Main_Admin
```

Feature_Main_Preference

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Main_Preference
```

Feature_Main_ArcSightWeb

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Main_ArcSightWeb
```

Feature_Main_AdvancedAdmin

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Main_AdvancedAdmin
```

Feature_Main_Dashboard

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Main_Dashboard
```

Feature_Main_ConApp

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Main_ConApp
```

Feature_User

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_User
```

Feature_Storage

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Storage
```

Feature_Connector

```
public static final
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat
ure Feature_Connector
```

Feature_Configuration

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Configuration
```

Feature_Storage_AllStorage

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Storage_AllStorage
```

Feature_Storage_EventArchive

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Storage_EventArchive
```

Feature_Configuration_Authentication

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Configuration_Authentication
```

Feature_Configuration_Server

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Configuration_Server
```

Feature_Configuration_License

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.AdminFeatureAvailability.AdminFeat  
ure Feature_Configuration_License
```

Methods

values

```
public static AdminFeatureAvailability.AdminFeature\[\] values()
```

valueOf

public static [AdminFeatureAvailability.AdminFeature](#) **valueOf**(String name)

com.arcsight.product.manager.resource.service.v1.model

Class ArchiveReport

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ [com.arcsight.product.manager.resource.service.v1.model.ArchiveReport](#)

All Implemented Interfaces:

Serializable, Serializable

public class **ArchiveReport**

extends [Resource](#)

implements Serializable, Serializable

Represents an archived report.

A report's definition is stored in the report resource. When a report is run, the report engine uses the report definition (and possible the runtime report parameters to override the default values) to produce the result. This result called an archived report is stored as another resource and can be downloaded later.

Constructor Summary

public	ArchiveReport()

Method Summary

String	getArchiveType() Returns the type of the report.

Long	getExpireDate() Returns the expiration date of the report.

String	getOwner() Returns the name of the user who owns the report.

String	getReportDefName() Returns the report definition name.

String	getReportFileName() Returns the name of the file containing the report.

String	getUploaded() Returns "Y" if the report has been uploaded; otherwise, "N".

boolean	isValid() Returns true if the archived report is valid.

void	setArchiveType(String type) Sets the type of the report.

void	<u>setExpireDate</u> (Long date) Sets the expiration date of the report.
void	<u>setOwner</u> (String owner) Sets the report owner's user name.
void	<u>setReportDefName</u> (String reportDefName) Sets the report definition name.
void	<u>setReportFileName</u> (String reportFileName) Sets the name of the file containing the report.
void	<u>setUploaded</u> (String uploaded) Sets the value of the report's uploaded flag.
void	<u>setValid</u> (boolean valid) Sets the validity flag of the report.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ArchiveReport

```
public ArchiveReport()
```

Methods

isValid

```
public boolean isValid()
```

Returns true if the archived report is valid.

For instance, a report is invalid if the file its pointing to is not available.

Returns:

if the archived report is valid.

setValid

```
public void setValid(boolean valid)
```

Sets the validity flag of the report.

Parameters:

valid - true if the report is valid.

getReportFileName

```
public String getReportFileName()
```

Returns the name of the file containing the report.

Returns:

the report file name.

setReportFileName

```
public void setReportFileName(String reportFileName)
```

Sets the name of the file containing the report.

Parameters:

reportFileName - the report file name.

getOwner

```
public String getOwner()
```

Returns the name of the user who owns the report.

Returns:

the name of the user who owns the report.

setOwner

```
public void setOwner(String owner)
```

Sets the report owner's user name.

Parameters:

owner - the name of the user who owns the report.

getArchiveType

```
public String getArchiveType()
```

Returns the type of the report.

Possible values: "Manual", "Scheduled" or "ManualSaveOutput".

Returns:

the type of the report.

setArchiveType

```
public void setArchiveType(String type)
```

Sets the type of the report.

Parameters:

type - the type of the report: "Manual", "Scheduled" or "ManualSaveOutput".

getExpireDate

```
public Long getExpireDate()
```

Returns the expiration date of the report.

Returns:

the expiration date of the report in milliseconds.

setExpireDate

```
public void setExpireDate(Long date)
```

Sets the expiration date of the report.

Parameters:

date - the expiration date of the report in milliseconds.

getReportDefName

```
public String getReportDefName()
```

Returns the report definition name.

Returns:

the report definition name.

setReportDefName

```
public void setReportDefName(String reportDefName)
```

Sets the report definition name.

Parameters:

reportDefName - the report definition name.

getUploaded

public String **getUpLoaded**()

Returns "Y" if the report has been uploaded; otherwise, "N".

Returns:

"Y" if the report has been uploaded; otherwise, "N".

setUploaded

public void **setUpLoaded**(String uploaded)

Sets the value of the report's uploaded flag.

Parameters:

uploaded - "Y" if the report has been uploaded; otherwise, "N".

com.arcsight.product.manager.resource.service.v1.model

Class AssignedCase

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.AssignedCase

public class **AssignedCase**
extends Object

Constructor Summary

public	AssignedCase()

Method Summary

String	getCaseId()
String	getCaseName()
long	getCreatedTime()
long	getLastUpdated()
long	getOwnedSince()
int	getSeverity()
String	getStage()
void	setCaseId(String caseId)
void	setCaseName(String caseName)
void	setCreatedTime(long createdTime)
void	setLastUpdated(long lastUpdated)
void	setOwnedSince(long ownedSince)
void	setSeverity(int severity)
void	setStage(String stage)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

AssignedCase

```
public AssignedCase()
```

Methods

getCaseId

```
public String getCaseId()
```

setCaseId

```
public void setCaseId(String caseId)
```

getCaseName

```
public String getCaseName()
```

setCaseName

```
public void setCaseName(String caseName)
```

getCreatedTime

```
public long getCreatedTime()
```

setCreatedTime

```
public void setCreatedTime(long createdTime)
```

getLastUpdated

```
public long getLastUpdated()
```

setLastUpdated

```
public void setLastUpdated(long lastUpdated)
```

getOwnedSince

```
public long getOwnedSince()
```

setOwnedSince

```
public void setOwnedSince(long ownedSince)
```

getSeverity

```
public int getSeverity()
```

setSeverity

```
public void setSeverity(int severity)
```

getStage


```
public String getStage()
```

setStage

```
public void setStage(String stage)
```

com.arcsight.product.manager.resource.service.v1.model

Class Case



All Implemented Interfaces:
Serializable, Serializable

```
public class Case
extends Resource
implements Serializable, Serializable
```

This class represents a Case resource.

JSON prototype

Nested Class Summary	
class	Case.Action Case.Action
class	Case.AssociatedImpact Case.AssociatedImpact
class	Case.AttackAgent Case.AttackAgent
class	Case.AttackMechanism Case.AttackMechanism
class	Case.ConsequenceSeverity Case.ConsequenceSeverity
class	Case.Frequency Case.Frequency
class	Case.History Case.History
class	Case.OperationalImpact Case.OperationallImpact
class	Case.Resistance Case.Resistance
class	Case.SecurityClassification Case.SecurityClassification

class	Case.Sensitivity Case.Sensitivity
class	Case.Stage Case.Stage
class	Case.TicketType Case.TicketType
class	Case.Vulnerability Case.Vulnerability
class	Case.VulnerabilityType1 Case.VulnerabilityType1
class	Case.VulnerabilityType2 Case.VulnerabilityType2

Constructor Summary

public	Case()

Method Summary

Case.Action	getAction() Gets action of this case.
String	getActionsTaken() Gets the description of the taken actions for this case.
String	getAffectedElements() Gets the description about the affected elements of this case.
String	getAffectedServices() Gets the description about the affected services of this case.
String	getAffectedSites() Gets the description about the affected sites of this case.
Case.AssociatedImpact	getAssociatedImpact() Gets associated impact of this case.
List	getAttachmentIDs()
String	getAttackAddress() Gets the attack address related to the attack agent associated with this case.
Case.AttackAgent	getAttackAgent() Gets attack agent of this case.
String	getAttackImpact() Gets the attack impact associated with this case.

String	<u>getAttackLocationID()</u> Gets the attack location ID for the attack agent associated with this case.
<u>Case.AttackMechanism</u>	<u>getAttackMechanism()</u> Gets attach mechanism of this case.
String	<u>getAttackNode()</u> Gets the attack node related to the attack agent associated with this case.
String	<u>getAttackOS()</u> Gets the attack OS associated with this case.
String	<u>getAttackProgram()</u> Gets the attack program associated with this case.
String	<u>getAttackProtocol()</u> Gets the attack protocol associated with this case.
String	<u>getAttackService()</u> Gets the attack service associated with a case.
String	<u>getAttackTarget()</u> Gets the attack agent associated with a case.
com.arcsight.coma.model.client.ServiceDate	<u>getAttackTime()</u> Gets the attack time associated with this case.
String	<u>getConclusions()</u> Gets the conclusions of this case, which provides miscellaneous tickets resolution and final reporting information.
<u>Case.ConsequenceSeverity</u>	<u>getConsequenceSeverity()</u> Gets consequence severity, whose values assigned are 0 (None), 1 (Insignificant), 2 (Marginal), 3 (Critical), 4 (Catastrophic).
com.arcsight.coma.model.client.ServiceDate	<u>getDetectionTime()</u> Gets detection time, which is automatically assigned from event info.
long	<u>getDisplayID()</u> Gets the display ID of this case.
String	<u>getEstimatedImpact()</u> Gets the description about the estimated impact of this case.
com.arcsight.coma.model.client.ServiceDate	<u>getEstimatedRestoreTime()</u> Gets the estimated restore time, which is automatically assigned from event info.
com.arcsight.coma.model.client.ServiceDate	<u>getEstimatedStartTime()</u> Gets the estimated start time, which is automatically assigned from event info.
List	<u>getEventIDs()</u> Gets the event IDs associated with this case.
String	<u>getFinalReportAction()</u> Gets the final report action associated with this case.

String	getFollowupContact() Gets the description of the follow-up contact for this case.
Case.Frequency	getFrequency() Get the frequency, which cases how often reported issue occurs.
Case.History	getHistory() Gets the history of final reporting information for this case.
String	getIncidentSource1() Gets incident source 1, which auto-populated from Security Classification tab.
String	getIncidentSource2() Gets incident source 2, which auto-populated from Security Classification tab.
String	getInspectionResults() Gets the inspection results of this case, which provides miscellaneous tickets resolution and final reporting information.
com.arcsight.coma.model.client.ServiceDate	getLastOccurenceTime() Gets the last occurrence time of this case.
int	getNumberOfOccurrences() Gets the number of occurrences of this case.
Case.OperationalImpact	getOperationalImpact() Gets operational impact, which classifies the impact of reported case.
String	getOriginator() Gets the originator.
String	getPlannedActions() Gets the description of the planned actions for this case.
String	getRecommendedActions() Gets the description of the recommended actions for this case.
String	getRecordedData() Gets the recorded data of this case, which provides miscellaneous tickets resolution and final reporting information.
int	getReportingLevel() Gets reporting level, which is number calculated based on Ticket info values entered.
Case.Resistance	getResistance() Gets the resistance of this case, which provides miscellaneous tickets resolution and final reporting information.
Case.SecurityClassification	getSecurityClassification() Gets security classification.
String	getSecurityClassificationCode() Gets security classification code of this case.
Case.Sensitivity	getSensitivity() Gets the sensitivity of this case.

static long	getSerialversionuid()
String	getSourceAddress() Gets the source address associated with this case.
Case.Stage	getStage() Gets the stage, which Indicates work flow stage of ticket; default selections include Queued, Initial, Follow-Up, Final, and Closed.
Case.TicketType	getTicketType() Gets the ticket type.
Case.Vulnerability	getVulnerability() Gets vulnerability of this case.
String	getVulnerabilityData() Gets the vulnerability data associated with this case.
String	getVulnerabilityEvidence() Gets the vulnerability evidence associated with this case.
String	getVulnerabilitySource() Gets the vulnerability source associated with this case.
Case.VulnerabilityType1	getVulnerabilityType1() Gets the vulnerability type associated with this case.
Case.VulnerabilityType2	getVulnerabilityType2() Gets the vulnerability type associated with this case.
void	setAction(Case.Action action) Sets action of this case.
void	setActionsTaken(String actionsTaken) Sets the description of the taken actions for this case.
void	setAffectedElements(String affectedElements) Sets the description about the affected elements of this case.
void	setAffectedServices(String affectedServices) Sets the description about the affected services of this case.
void	setAffectedSites(String affectedSites) Sets the description about the affected sites of this case.
void	setAssociatedImpact(Case.AssociatedImpact associatedImpact) Sets associated impact of this case.
void	setAttachmentIDs(List attachmentIDs)
void	setAttackAddress(String attackAddress) Sets the attack address related to the attack agent associated with this case.

void	<u>setAttackAgent</u> (<u>Case.AttackAgent</u> attackAgent) Sets attack agent.
void	<u>setAttackImpact</u> (String attackImpact) Sets the attack program associated with this case.
void	<u>setAttackLocationID</u> (String attackLocationID) Sets the attack location ID for the attack agent associated with this case.
void	<u>setAttackMechanism</u> (<u>Case.AttackMechanism</u> attackMechanism) Sets attach mechanism.
void	<u>setAttackNode</u> (String attackNode) Sets the attack node related to the attack agent associated with this case.
void	<u>setAttackOS</u> (String attackOS) Sets the attack OS associated with this case.
void	<u>setAttackProgram</u> (String attackProgram) Sets the attack program associated with this case.
void	<u>setAttackProtocol</u> (String attackProtocol) Sets the attack protocol associated with this case.
void	<u>setAttackService</u> (String attackService) Sets the attack service associated with a case.
void	<u>setAttackTarget</u> (String attackTarget) Sets the attack agent associated with a case.
void	<u>setAttackTime</u> (com.arcsight.coma.model.client.ServiceDate attackTime) Sets the attack time associated with this case.
void	<u>setConclusions</u> (String conclusions) Sets the conclusions of this case, which provides miscellaneous tickets resolution and final reporting information.
void	<u>setConsequenceSeverity</u> (<u>Case.ConsequenceSeverity</u> consequenceSeverity) Sets consequence severity, whose values assigned can be 0 (None), 1 (Insignificant), 2 (Marginal), 3 (Critical), or 4 (Catastrophic).
void	<u>setDetectionTime</u> (com.arcsight.coma.model.client.ServiceDate detectionTime) Set detection time, which is automatically assigned from event info.
void	<u>setDisplayID</u> (long displayID) Sets the display ID of this case.
void	<u>setEstimatedImpact</u> (String estimatedImpact) Sets the description about the estimated impact of this case.
void	<u>setEstimatedRestoreTime</u> (com.arcsight.coma.model.client.ServiceDate estimatedRestoreTime) Sets the estimated restore time, which is automatically assigned from event info.

void	<u>setEstimatedStartTime</u> (com.arcsight.coma.model.client.ServiceDate estimatedStartTime) Sets the estimated start time, which is automatically assigned from event info.
void	<u>setEventIDs</u> (List eventIDs) Sets the event IDs associated with this case.
void	<u>setFinalReportAction</u> (String finalReportAction) Sets the final report action associated with this case.
void	<u>setFollowupContact</u> (String followupContact) Sets the description of the follow-up contact for this case.
void	<u>setFrequency</u> (<u>Case.Frequency</u> frequency) Set the frequency, which cases how often reported issue occurs.
void	<u>setHistory</u> (<u>Case.History</u> history) Sets the history of final reporting information for this case.
void	<u>setIncidentSource1</u> (String incidentSource1) Sets incident source 1, which auto-populated from Security Classification tab.
void	<u>setIncidentSource2</u> (String incidentSource2) Sets incident source 2, which auto-populated from Security Classification tab.
void	<u>setInspectionResults</u> (String inspectionResults) Sets the inspection results of this case, which provides miscellaneous tickets resolution and final reporting information.
void	<u>setLastOccurenceTime</u> (com.arcsight.coma.model.client.ServiceDate lastOccurenceTime) Sets the last occurrence time of this case.
void	<u>setNumberOfOccurrences</u> (int numberOfOccurrences) Sets the number of occurrences of this case.
void	<u>setOperationalImpact</u> (<u>Case.OperationalImpact</u> operationalImpact) Sets operational impact, which classifies the impact of reported case.
void	<u>setOriginator</u> (String originator)
void	<u>setPlannedActions</u> (String plannedActions) Sets the description of the planned actions for this case.
void	<u>setRecommendedActions</u> (String recommendedActions) Sets the description of the recommended actions for this case.
void	<u>setRecordedData</u> (String recordedData) Sets the recorded data of this case, which provides miscellaneous tickets resolution and final reporting information.
void	<u>setReportingLevel</u> (int reportingLevel) Sets Gets reporting level, which is number calculated based on Ticket info values entered.

void	<u>setResistance</u> (<u>Case.Resistance</u> resistance) Sets the resistance of this case, which provides miscellaneous tickets resolution and final reporting information.
void	<u>setSecurityClassification</u> (<u>Case.SecurityClassification</u> securityClassification) Sets security classification.
void	<u>setSecurityClassificationCode</u> (String securityClassificationCode) Sets security classification code of this case.
void	<u>setSensitivity</u> (<u>Case.Sensitivity</u> sensitivity) Sets the sensitivity of this case.
void	<u>setSourceAddress</u> (String sourceAddress) Sets the source address associated with this case.
void	<u>setStage</u> (<u>Case.Stage</u> stage) Sets the stage, which Indicates work flow stage of ticket; default selections include Queued, Initial, Follow-Up, Final, and Closed.
void	<u>setTicketType</u> (<u>Case.TicketType</u> ticketType) Sets the ticket type.
void	<u>setVulnerability</u> (<u>Case.Vulnerability</u> vulnerability) Sets vulnerability.
void	<u>setVulnerabilityData</u> (String vulnerabilityData) Sets the vulnerability data associated with this case.
void	<u>setVulnerabilityEvidence</u> (String vulnerabilityEvidence) Sets the vulnerability evidence associated with this case.
void	<u>setVulnerabilitySource</u> (String vulnerabilitySource) Sets the vulnerability source associated with this case.
void	<u>setVulnerabilityType1</u> (<u>Case.VulnerabilityType1</u> vulnerabilityType1) Sets the vulnerability type associated with this case.
void	<u>setVulnerabilityType2</u> (<u>Case.VulnerabilityType2</u> vulnerabilityType2) Sets the vulnerability type associated with this case.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

Case

```
public Case()
```

Methods

getDisplayID

```
public long getDisplayID()
```

Gets the display ID of this case. Display ID is an identification provided by an external tracking system.

Returns:

The display ID of this case.

setDisplayID

```
public void setDisplayID(long displayID)
```

Sets the display ID of this case.

Parameters:

displayID - The displayID to set.

getTicketType

```
public Case.TicketType getTicketType()
```

Gets the ticket type. Ticket Type is one of the Drop-down list includes Internal, Client, and Incident types.

Returns:
the ticketType

setTicketType

public void **setTicketType**([Case.TicketType](#) ticketType)

Sets the ticket type. Ticket Type can be one of the Drop-down list includes Internal, Client, or Incident types.

Parameters:
ticketType - The ticketType to set

getStage

public [Case.Stage](#) **getStage**()

Gets the stage, which Indicates work flow stage of ticket; default selections include Queued, Initial, Follow-Up, Final, and Closed.

Returns:
The stage of ticket. It can be Queued, Initial, Follow-Up, Final, or Closed.

setStage

public void **setStage**([Case.Stage](#) stage)

Sets the stage, which Indicates work flow stage of ticket; default selections include Queued, Initial, Follow-Up, Final, and Closed.

Parameters:
stage - The stage to set

getFrequency

public [Case.Frequency](#) **getFrequency**()

Get the frequency, which cases how often reported issue occurs. Values assigned are 0 (never or once), 1 (less than 10 times), 2 (10 to 15 times), 3 (15 times), 4 (more than 15).

Returns:
The frequency

setFrequency

public void **setFrequency**([Case.Frequency](#) frequency)

Set the frequency, which cases how often reported issue occurs. Values assigned are 0 (never or once), 1 (less than 10 times), 2 (10 to 15 times), 3 (15 times), 4 (more than 15).

Parameters:
frequency - The frequency to set.

getOperationalImpact

public [Case.OperationalImpact](#) getOperationalImpact()

Gets operational impact, which classifies the impact of reported case. Values assigned are 0 (no impact), 1 (no immediate impact), 2 (low priority impact), 3 (high priority impact), 4 (immediate impact).

Returns:

The operational impact object.

setOperationalImpact

public void setOperationalImpact([Case.OperationalImpact](#) operationalImpact)

Sets operational impact, which classifies the impact of reported case. Values assigned are 0 (no impact), 1 (no immediate impact), 2 (low priority impact), 3 (high priority impact), 4 (immediate impact).

Parameters:

operationalImpact - The operationalImpact to set.

getSecurityClassification

public [Case.SecurityClassification](#) getSecurityClassification()

Gets security classification. Values assigned are 1 (Unclassified), 2 (Confidential), 3 (Secret), 4 (Top Secret).

Returns:

the securityClassification

setSecurityClassification

public void setSecurityClassification([Case.SecurityClassification](#) securityClassification)

Sets security classification. Values assigned can be 1 (Unclassified), 2 (Confidential), 3 (Secret), or 4 (Top Secret).

Parameters:

securityClassification - The securityClassification to set.

getConsequenceSeverity

public [Case.ConsequenceSeverity](#) getConsequenceSeverity()

Gets consequence severity, whose values assigned are 0 (None), 1 (Insignificant), 2 (Marginal), 3 (Critical), 4 (Catastrophic).

Returns:

The consequenceSeverity

setConsequenceSeverity

public void setConsequenceSeverity([Case.ConsequenceSeverity](#) consequenceSeverity)

Sets consequence severity, whose values assigned can be 0 (None), 1 (Insignificant), 2 (Marginal), 3 (Critical), or 4 (Catastrophic).

Parameters:

consequenceSeverity - The consequenceSeverity to set.

getReportingLevel

```
public int getReportingLevel()
```

Gets reporting level, which is number calculated based on Ticket info values entered.

Returns:

The reportingLevel.

setReportingLevel

```
public void setReportingLevel(int reportingLevel)
```

Sets Gets reporting level, which is number calculated based on Ticket info values entered.

Parameters:

reportingLevel - the reportingLevel to set

getOriginator

```
public String getOriginator()
```

Gets the originator.

Returns:

The originator.

setOriginator

```
public void setOriginator(String originator)
```

Parameters:

originator - the originator to set

getDetectionTime

```
public com.arcsight.coma.model.client.ServiceDate getDetectionTime()
```

Gets detection time, which is automatically assigned from event info.

Returns:

The detectionTime

setDetectionTime

```
public void setDetectionTime(com.arcsight.coma.model.client.ServiceDate detectionTime)
```

Set detection time, which is automatically assigned from event info.

Parameters:

detectionTime - The detectionTime to set

getEstimatedStartTime

```
public com.arcsight.coma.model.client.ServiceDate getEstimatedStartTime()
```

Gets the estimated start time, which is automatically assigned from event info.

Returns:

The estimatedStartTime

setEstimatedStartTime

```
public void setEstimatedStartTime(com.arcsight.coma.model.client.ServiceDate  
estimatedStartTime)
```

Sets the estimated start time, which is automatically assigned from event info.

Parameters:

estimatedStartTime - The estimatedStartTime to set

getEstimatedRestoreTime

```
public com.arcsight.coma.model.client.ServiceDate getEstimatedRestoreTime()
```

Gets the estimated restore time, which is automatically assigned from event info.

Returns:

The estimatedRestoreTime

setEstimatedRestoreTime

```
public void setEstimatedRestoreTime(com.arcsight.coma.model.client.ServiceDate  
estimatedRestoreTime)
```

Sets the estimated restore time, which is automatically assigned from event info.

Parameters:

estimatedRestoreTime - The estimatedRestoreTime to set

getAffectedServices

```
public String getAffectedServices()
```

Gets the description about the affected services of this case.

Returns:

The affectedServices

setAffectedServices

```
public void setAffectedServices(String affectedServices)
```

Sets the description about the affected services of this case.

Parameters:

affectedServices - The affectedServices to set

getAffectedElements

```
public String getAffectedElements()
```

Gets the description about the affected elements of this case.

Returns:

The affectedElements

setAffectedElements

```
public void setAffectedElements(String affectedElements)
```

Sets the description about the affected elements of this case.

Parameters:

affectedElements - The affectedElements to set

getEstimatedImpact

```
public String getEstimatedImpact()
```

Gets the description about the estimated impact of this case.

Returns:

The estimatedImpact

setEstimatedImpact

```
public void setEstimatedImpact(String estimatedImpact)
```

Sets the description about the estimated impact of this case.

Parameters:

estimatedImpact - The estimatedImpact to set

getAffectedSites

```
public String getAffectedSites()
```

Gets the description about the affected sites of this case.

Returns:

the affectedSites

setAffectedSites

```
public void setAffectedSites(String affectedSites)
```

Sets the description about the affected sites of this case.

Parameters:

affectedSites - The affectedSites to set

getAttackMechanism

public [Case.AttackMechanism](#) getAttackMechanism()

Gets attach mechanism of this case. The selections include: P (Physical), O (Operational), I(Informational), and U (Unknown).

Returns:

The attack mechanism.

setAttackMechanism

public void setAttackMechanism([Case.AttackMechanism](#) attackMechanism)

Sets attach mechanism. The selections include: P (Physical), O (Operational), I(Informational), and U (Unknown).

Parameters:

attackMechanism - The attack mechanism to set.

getAttackAgent

public [Case.AttackAgent](#) getAttackAgent()

Gets attack agent of this case. Selections include: I (Insider), C (Collaborative), O (Outsider), and U (Unknown).

Returns:

The attack agent.

setAttackAgent

public void setAttackAgent([Case.AttackAgent](#) attackAgent)

Sets attack agent. Selections include: I (Insider), C (Collaborative), O (Outsider), and U (Unknown).

Parameters:

attackAgent - The attack agent to set.

getVulnerability

public [Case.Vulnerability](#) getVulnerability()

Gets vulnerability of this case. Selections include: D (Design), O (Operational), E (Operational Environment), and U (Unknown).

Returns:

The vulnerability.

setVulnerability

public void setVulnerability([Case.Vulnerability](#) vulnerability)

Sets vulnerability. Selections include: D (Design), O (Operational), E (Operational Environment), and U (Unknown).

Parameters:

vulnerability - The vulnerability to set.

getSensitivity

```
public Case.Sensitivity getSensitivity()
```

Gets the sensitivity of this case. Selections include: U (Unclassified), C (Confidential), S (Secret), and T (Top Secret).

Returns:

The sensitivity.

setSensitivity

```
public void setSensitivity(Case.Sensitivity sensitivity)
```

Sets the sensitivity of this case. Selections include: U (Unclassified), C (Confidential), S (Secret), and T (Top Secret).

Parameters:

sensitivity - The sensitivity to set.

getAssociatedImpact

```
public Case.AssociatedImpact getAssociatedImpact()
```

Gets associated impact of this case. Selections include: A (Availability), C (Confidentiality), I (Integrity), and U (Unknown).

Returns:

The associatedImpact

setAssociatedImpact

```
public void setAssociatedImpact(Case.AssociatedImpact associatedImpact)
```

Sets associated impact of this case. Selections include: A (Availability), C (Confidentiality), I (Integrity), and U (Unknown).

Parameters:

associatedImpact - The associatedImpact to set.

getAction

```
public Case.Action getAction()
```

Gets action of this case. Selections include: B (Block/Shutdown), M (Monitoring), and O (Other).

Returns:

The action

setAction

```
public void setAction(Case.Action action)
```

Sets action of this case. Selections include: B (Block/Shutdown), M (Monitoring), and O (Other).

Parameters:

action - The action to set.

getSecurityClassificationCode

```
public String getSecurityClassificationCode()
```

Gets security classification code of this case. Code value is automatically calculated from other security classification field entries.

Returns:

The security classification code.

setSecurityClassificationCode

```
public void setSecurityClassificationCode(String securityClassificationCode)
```

Sets security classification code of this case.

Parameters:

securityClassificationCode - The security classification code to set.

getActionsTaken

```
public String getActionsTaken()
```

Gets the description of the taken actions for this case.

Returns:

The description of actions taken.

setActionsTaken

```
public void setActionsTaken(String actionsTaken)
```

Sets the description of the taken actions for this case.

Parameters:

actionsTaken - The description of actions taken to set.

getPlannedActions

```
public String getPlannedActions()
```

Gets the description of the planned actions for this case.

Returns:

the planned actions.

setPlannedActions

```
public void setPlannedActions(String plannedActions)
```


Sets the description of the planned actions for this case.

Parameters:

plannedActions - The planned actions to set.

getRecommendedActions

```
public String getRecommendedActions()
```

Gets the description of the recommended actions for this case.

Returns:

The recommendedActions.

setRecommendedActions

```
public void setRecommendedActions(String recommendedActions)
```

Sets the description of the recommended actions for this case.

Parameters:

recommendedActions - The recommended actions to set.

getFollowupContact

```
public String getFollowupContact()
```

Gets the description of the follow-up contact for this case.

Returns:

The follow-up contact.

setFollowupContact

```
public void setFollowupContact(String followupContact)
```

Sets the description of the follow-up contact for this case.

Parameters:

followupContact - The follow-up contact to set.

getAttackTarget

```
public String getAttackTarget()
```

Gets the attack agent associated with a case.

Returns:

The attack target.

setAttackTarget

```
public void setAttackTarget(String attackTarget)
```

Sets the attack agent associated with a case.

Parameters:

attackTarget - The attack target to set.

getAttackService

```
public String getAttackService()
```

Gets the attack service associated with a case.

Returns:

The attack service

setAttackService

```
public void setAttackService(String attackService)
```

Sets the attack service associated with a case.

Parameters:

attackService - The attack service to set.

getAttackProtocol

```
public String getAttackProtocol()
```

Gets the attack protocol associated with this case.

Returns:

The attack protocol.

setAttackProtocol

```
public void setAttackProtocol(String attackProtocol)
```

Sets the attack protocol associated with this case.

Parameters:

attackProtocol - The attack protocol to set.

getAttackOS

```
public String getAttackOS()
```

Gets the attack OS associated with this case.

Returns:

The attack OS.

setAttackOS

```
public void setAttackOS(String attackOS)
```

Sets the attack OS associated with this case.

Parameters:

attackOS - The attackOS to set.

getAttackProgram

```
public String getAttackProgram()
```

Gets the attack program associated with this case.

Returns:

The attack program.

setAttackProgram

```
public void setAttackProgram(String attackProgram)
```

Sets the attack program associated with this case.

Parameters:

attackProgram - The attack program to set.

getAttackImpact

```
public String getAttackImpact()
```

Gets the attack impact associated with this case.

Returns:

The attack impact.

setAttackImpact

```
public void setAttackImpact(String attackImpact)
```

Sets the attack program associated with this case.

Parameters:

attackImpact - The attack impact to set.

getAttackTime

```
public com.arcsight.coma.model.client.ServiceDate getAttackTime()
```

Gets the attack time associated with this case.

Returns:

The attack time.

setAttackTime

```
public void setAttackTime(com.arcsight.coma.model.client.ServiceDate attackTime)
```

Sets the attack time associated with this case.

Parameters:

attackTime - The attack time to set.

getFinalReportAction

```
public String getFinalReportAction()
```

Gets the final report action associated with this case.

Returns:

The final report action.

setFinalReportAction

```
public void setFinalReportAction(String finalReportAction)
```

Sets the final report action associated with this case.

Parameters:

finalReportAction - The final report action to set.

getAttackLocationID

```
public String getAttackLocationID()
```

Gets the attack location ID for the attack agent associated with this case.

Returns:

The attack location ID for the attack agent.

setAttackLocationID

```
public void setAttackLocationID(String attackLocationID)
```

Sets the attack location ID for the attack agent associated with this case.

Parameters:

attackLocationID - The attack location ID for the attack agent to set.

getAttackNode

```
public String getAttackNode()
```

Gets the attack node related to the attack agent associated with this case.

Returns:

The attack node related to the attack agent.

setAttackNode

```
public void setAttackNode(String attackNode)
```

Sets the attack node related to the attack agent associated with this case.

Parameters:

attackNode - The attack node to set.

getAttackAddress

```
public String getAttackAddress()
```

Gets the attack address related to the attack agent associated with this case.

Returns:

The attack address related to the attack agent.

setAttackAddress

```
public void setAttackAddress(String attackAddress)
```

Sets the attack address related to the attack agent associated with this case.

Parameters:

attackAddress - The attack address related to the attack agent to set.

getVulnerabilityType1

```
public Case.VulnerabilityType1 getVulnerabilityType1()
```

Gets the vulnerability type associated with this case. Selections include: Accidental or Intentional.

Returns:

The vulnerability type.

setVulnerabilityType1

```
public void setVulnerabilityType1(Case.VulnerabilityType1 vulnerabilityType1)
```

Sets the vulnerability type associated with this case. Selections include: Accidental or Intentional.

Parameters:

vulnerabilityType1 - The vulnerabilityType1 to set.

getVulnerabilityType2

```
public Case.VulnerabilityType2 getVulnerabilityType2()
```

Gets the vulnerability type associated with this case. Selections include: EMI/RFI, Insertion of Data, Theft of Service, Unauthorized, Probes, Root Compromise, DoS Attack, User Account.

Returns:

The vulnerability type.

setVulnerabilityType2

```
public void setVulnerabilityType2(Case.VulnerabilityType2 vulnerabilityType2)
```

Sets the vulnerability type associated with this case. Selections include: EMI/RFI, Insertion of Data, Theft of Service, Unauthorized, Probes, Root Compromise, DoS Attack, User Account.

Parameters:

vulnerabilityType2 - The vulnerability type to set.

getVulnerabilityEvidence

```
public String getVulnerabilityEvidence()
```

Gets the vulnerability evidence associated with this case.

Returns:

the vulnerability evidence.

setVulnerabilityEvidence

```
public void setVulnerabilityEvidence(String vulnerabilityEvidence)
```

Sets the vulnerability evidence associated with this case.

Parameters:

vulnerabilityEvidence - The vulnerability Evidence to set.

getVulnerabilitySource

```
public String getVulnerabilitySource()
```

Gets the vulnerability source associated with this case.

Returns:

the vulnerabilitySource

setVulnerabilitySource

```
public void setVulnerabilitySource(String vulnerabilitySource)
```

Sets the vulnerability source associated with this case.

Parameters:

vulnerabilitySource - the vulnerabilitySource to set

getVulnerabilityData

```
public String getVulnerabilityData()
```

Gets the vulnerability data associated with this case.

Returns:

The vulnerability data.

setVulnerabilityData

```
public void setVulnerabilityData(String vulnerabilityData)
```

Sets the vulnerability data associated with this case.

Parameters:

vulnerabilityData - The vulnerability data to set.

getHistory

```
public Case.History getHistory()
```

Gets the history of final reporting information for this case. Selections include: Known Occurrence and Unknown.

Returns:

The history of this case.

setHistory

```
public void setHistory(Case.History history)
```

Sets the history of final reporting information for this case. Selections include: Known Occurrence and Unknown.

Parameters:

history - the history to set

getNumberOfOccurrences

```
public int getNumberOfOccurrences()
```

Gets the number of occurrences of this case.

Returns:

The number of occurrences.

setNumberOfOccurrences

```
public void setNumberOfOccurrences(int numberOfOccurrences)
```

Sets the number of occurrences of this case.

Parameters:

numberOfOccurrences - The number of occurrences to set.

getLastOccurrenceTime

```
public com.arcsight.coma.model.client.ServiceDate getLastOccurrenceTime()
```

Gets the last occurrence time of this case.

Returns:

the lastOccurrenceTime

setLastOccurenceTime

```
public void setLastOccurenceTime(com.arcsight.coma.model.client.ServiceDate  
lastOccurenceTime)
```

Sets the last occurrence time of this case.

Parameters:

lastOccurenceTime - The last occurrence time of this case to set.

getResistance

```
public Case.Resistance getResistance()
```

Gets the resistance of this case, which provides miscellaneous tickets resolution and final reporting information. Selections include: High, Low, Unknown.

Returns:

The resistance of this case.

setResistance

```
public void setResistance(Case.Resistance resistance)
```

Sets the resistance of this case, which provides miscellaneous tickets resolution and final reporting information. Selections include: High, Low, Unknown.

Parameters:

resistance - The resistance fo this case to set.

getRecordedData

```
public String getRecordedData()
```

Gets the recorded data of this case, which provides miscellaneous tickets resolution and final reporting information.

Returns:

The recorded data of this case.

setRecordedData

```
public void setRecordedData(String recordedData)
```

Sets the recorded data of this case, which provides miscellaneous tickets resolution and final reporting information.

Parameters:

recordedData - The recorded Data to set.

getInspectionResults

```
public String getInspectionResults()
```

Gets the inspection results of this case, which provides miscellaneous tickets resolution and final reporting information.

Returns:

The inspection results.

setInspectionResults

```
public void setInspectionResults(String inspectionResults)
```

Sets the inspection results of this case, which provides miscellaneous tickets resolution and final reporting information.

Parameters:

inspectionResults - The inspection results to set.

getConclusions

```
public String getConclusions()
```

Gets the conclusions of this case, which provides miscellaneous tickets resolution and final reporting information.

Returns:

The conclusions of this case.

setConclusions

```
public void setConclusions(String conclusions)
```

Sets the conclusions of this case, which provides miscellaneous tickets resolution and final reporting information.

Parameters:

conclusions - The conclusions to set.

getIncidentSource1

```
public String getIncidentSource1()
```

Gets incident source 1, which auto-populated from Security Classification tab.

Returns:

The incident source 1.

setIncidentSource1

```
public void setIncidentSource1(String incidentSource1)
```

Sets incident source 1, which auto-populated from Security Classification tab.

Parameters:

incidentSource1 - The incident source 1 to set.

getIncidentSource2

```
public String getIncidentSource2()
```

Gets incident source 2, which auto-populated from Security Classification tab.

Returns:

The incident source 2.

setIncidentSource2

```
public void setIncidentSource2(String incidentSource2)
```

Sets incident source 2, which auto-populated from Security Classification tab.

Parameters:

incidentSource2 - The incident source 2 to set

getSourceAddress

```
public String getSourceAddress()
```

Gets the source address associated with this case.

Returns:

the sourceAddress

setSourceAddress

```
public void setSourceAddress(String sourceAddress)
```

Sets the source address associated with this case.

Parameters:

sourceAddress - The source address to set.

getSerialversionuid

```
public static long getSerialversionuid()
```

Returns:

the serialversionuid

getEventIDs

```
public List getEventIDs()
```

Gets the event IDs associated with this case.

Returns:

the security event IDs associated with this case.

setEventIDs

```
public void setEventIDs(List eventIDs)
```

Sets the event IDs associated with this case.

Parameters:

eventIDs - The security event IDs to set.

getAttachmentIDs

```
public List getAttachmentIDs()
```

Returns:

the attachmentIDs

setAttachmentIDs

```
public void setAttachmentIDs(List attachmentIDs)
```

Parameters:

attachmentIDs - the attachmentIDs to set

com.arcsight.product.manager.resource.service.v1.model

Class Case.TicketType

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Case.TicketType

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.TicketType**
extends Enum

Case Ticket Type.

Field Summary

public static final	CLIENT Client case ticket type.
public static final	INCIDENT Incident case ticket type.
public static final	INTERNAL Internal case ticket type.

Method Summary

Case.TicketType static	valueOf (String name)
Case.TicketType[] static	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

INTERNAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.TicketType INTERNAL
```

Internal case ticket type.

CLIENT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.TicketType CLIENT
```

Client case ticket type.

INCIDENT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.TicketType INCIDENT
```

Incident case ticket type.

Methods

values

```
public static Case.TicketType\[\] values()
```

valueOf

```
public static Case.TicketType valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class Case.Stage

java.lang.Object
└- java.lang.Enum
 └- com.arcsight.product.manager.resource.service.v1.model.Case.Stage

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.Stage**
extends Enum

Indicates workflow stage of case ticket.

Field Summary	
public static final	CLOSED Closed workflow stage of case ticket.
public static final	FINAL Final workflow stage of case ticket.
public static final	FOLLOW_UP Follow-up workflow stage of case ticket.
public static final	INITIAL Initial workflow stage of case ticket.
public static final	QUEUED Queued workflow stage of case ticket.

Method Summary	
static Case.Stage	valueOf (String name)
static Case.Stage[]	values ()

Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Methods inherited from interface java.lang.Comparable	

compareTo

Fields

QUEUED

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Stage  
QUEUED
```

Queued workflow stage of case ticket.

INITIAL

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Stage  
INITIAL
```

Initial workflow stage of case ticket.

FOLLOW_UP

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Stage  
FOLLOW_UP
```

Follow-up workflow stage of case ticket.

FINAL

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Stage  
FINAL
```

Final workflow stage of case ticket.

CLOSED

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Stage  
CLOSED
```

Closed workflow stage of case ticket.

Methods

values

```
public static Case.Stage\[\] values()
```

valueOf

```
public static Case.Stage valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class Case.Frequency

java.lang.Object
└- java.lang.Enum
└- com.arcsight.product.manager.resource.service.v1.model.Case.Frequency

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.Frequency**
extends Enum

Indicates how often the reported issue occurs.

Field Summary	
public static final	FIFTEEN Occurs fifteen.
public static final	LESS_THAN_TEN Occurs less than then.
public static final	MORE_THAN_FIFTEEN Occurs more than fifteen.
public static final	NEVER_OR_ONCE Occurs never or once.
public static final	TEN_TO_FIFTEEN Occurs ten to fifteen.
Method Summary	
int	intValue() Returns an internal code of the constant.
static Case.Frequency	valueOf(int code) Creates a constant from the internal code.
static Case.Frequency	valueOf(String name)
static Case.Frequency[]	values()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

NEVER_OR_ONCE

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Frequency  
NEVER_OR_ONCE
```

Occurs never or once.

LESS_THAN_TEN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Frequency  
LESS_THAN_TEN
```

Occurs less than ten.

TEN_TO_FIFTEEN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Frequency  
TEN_TO_FIFTEEN
```

Occurs ten to fifteen.

FIFTEEN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Frequency  
FIFTEEN
```

Occurs fifteen.

MORE_THAN_FIFTEEN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Frequency  
MORE_THAN_FIFTEEN
```

Occurs more than fifteen.

Methods

values

```
public static Case.Frequency\[\] values()
```

valueOf

public static [Case.Frequency](#) **valueOf**(String name)

intValue

public int **intValue**()

Returns an internal code of the constant.

Returns:

an internal code of the constant.

valueOf

public static [Case.Frequency](#) **valueOf**(int code)

Creates a constant from the internal code.

Parameters:

code - the internal code of a constant.

Returns:

the constant corresponding to the code.

Throws:

`IllegalArgumentException` - if there is no constant corresponds to the code.

com.arcsight.product.manager.resource.service.v1.model Class Case.OperationalImpact

java.lang.Object

└ java.lang.Enum

└ com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.OperationalImpact**
extends Enum

Impact of the reported case.

Field Summary

public static final	HIGH_PRIORITY_IMPACT High priority impact.
public static final	IMMEDIATE_IMPACT Immediate impact.
public static final	LOW_PRIORITY_IMPACT Low priority impact.
public static final	NO_IMMEDIATE_IMPACT No immediate impact.
public static final	NO_IMPACT No impact.

Method Summary

int	intValue() Returns an internal code of the constant.
static Case.OperationalImpact t	valueOf(int code) Creates a constant from the internal code.
static Case.OperationalImpact t	valueOf(String name)
static Case.OperationalImpact t[]	values()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

NO_IMPACT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact NO_IMPACT
```

No impact.

NO_IMMEDIATE_IMPACT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact  
NO_IMMEDIATE_IMPACT
```

No immediate impact.

LOW_PRIORITY_IMPACT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact  
LOW_PRIORITY_IMPACT
```

Low priority impact.

HIGH_PRIORITY_IMPACT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact  
HIGH_PRIORITY_IMPACT
```

High priority impact.

IMMEDIATE_IMPACT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.OperationalImpact  
IMMEDIATE_IMPACT
```

Immediate impact.

Methods

values

```
public static Case.OperationalImpact\[\] values()
```

valueOf

```
public static Case.OperationalImpact valueOf(String name)
```

intValue

```
public int intValue()
```

Returns an internal code of the constant.

Returns:

An internal code of the constant.

valueOf

```
public static Case.OperationalImpact valueOf(int code)
```

Creates a constant from the internal code.

Parameters:

code - the internal code of a constant.

Returns:

the constant corresponding to the code.

Throws:

`IllegalArgumentException` - if there is no constant corresponds to the code.

com.arcsight.product.manager.resource.service.v1.model Class Case.SecurityClassification

java.lang.Object

└ java.lang.Enum

└ com.arcsight.product.manager.resource.service.v1.model.Case.SecurityClassification

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.SecurityClassification**
extends Enum

The enum types of Security classification of the issue.

Field Summary

public static final	CONFIDENTIAL Confidential security classification.
public static final	SECRET Secret security classification.
public static final	TOP_SECRET Top secret security classification.
public static final	UNCLASSIFIED Unclassified security classification.

Method Summary

int	intValue() Returns an internal code of the constant.
static Case.SecurityClassification	valueOf(int code) Creates a constant from the internal code.
static Case.SecurityClassification	valueOf(String name)
static Case.SecurityClassification[]	values()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

compareTo

Fields

UNCLASSIFIED

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.SecurityClassification
UNCLASSIFIED
```

Unclassified security classification.

CONFIDENTIAL

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.SecurityClassification
CONFIDENTIAL
```

Confidential security classification.

SECRET

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.SecurityClassification SECRET
```

Secret security classification.

TOP_SECRET

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.SecurityClassification
TOP_SECRET
```

Top secret security classification.

Methods

values

```
public static Case.SecurityClassification\[\] values()
```

valueOf

```
public static Case.SecurityClassification valueOf(String name)
```

intValue

public int **intValue**()

Returns an internal code of the constant.

Returns:

an internal code of the constant.

valueOf

public static [Case.SecurityClassification](#) **valueOf**(int code)

Creates a constant from the internal code.

Parameters:

code - the internal code of a constant.

Returns:

the constant corresponding to the code.

Throws:

`IllegalArgumentException` - if there is no constant corresponds to the code.

com.arcsight.product.manager.resource.service.v1.model Class Case.ConsequenceSeverity

java.lang.Object
└─ java.lang.Enum
 └─ com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.ConsequenceSeverity**
extends Enum

The enum types of severity of the issue consequences.

Field Summary	
public static final	CATASTROPHIC Catastrophic consequence severity.
public static final	CRITICAL Critical consequence severity.
public static final	INSIGNIFICANT Insignificant consequence severity.
public static final	MARGINAL Marginal consequence severity.
public static final	NONE None consequence severity.

Method Summary	
int	intValue() Returns an internal code of the constant.
static Case.ConsequenceSeverity	valueOf(int code) Creates a constant from the internal code.
static Case.ConsequenceSeverity	valueOf(String name)
static Case.ConsequenceSeverity[]	values()

Methods inherited from class java.lang.Enum	

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class `java.lang.Object`

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

compareTo

Fields

NONE

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity NONE
```

None consequence severity.

INSIGNIFICANT

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity
INSIGNIFICANT
```

Insignificant consequence severity.

MARGINAL

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity MARGINAL
```

Marginal consequence severity.

CRITICAL

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity CRITICAL
```

Critical consequence severity.

CATASTROPHIC

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.ConsequenceSeverity
CATASTROPHIC
```

Catastrophic consequence severity.

Methods

values

```
public static Case.ConsequenceSeverity\[\] values()
```

valueOf

```
public static Case.ConsequenceSeverity valueOf(String name)
```

intValue

```
public int intValue()
```

Returns an internal code of the constant.

Returns:

an internal code of the constant.

valueOf

```
public static Case.ConsequenceSeverity valueOf(int code)
```

Creates a constant from the internal code.

Parameters:

code - The internal code of a constant.

Returns:

The constant corresponding to the code.

Throws:

`IllegalArgumentException` - If there is no constant corresponds to the code.

com.arcsight.product.manager.resource.service.v1.model Class Case.AttackMechanism

java.lang.Object
└─ java.lang.Enum
 └─ com.arcsight.product.manager.resource.service.v1.model.Case.AttackMechanism

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.AttackMechanism**
extends Enum

The enum values for the field attack_mechanism of the table extended case.

Field Summary	
public static final	INFORMATIONAL Informational attack mechanism.
public static final	OPERATIONAL Operational attack mechanism.
public static final	PHYSICAL Physical attack mechanism.
public static final	UNKNOWN Unknown attack mechanism.

Method Summary	
Case.AttackMechanism static	valueOf (String name)
Case.AttackMechanism static	values ()

Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Methods inherited from interface java.lang.Comparable	
compareTo	

Fields

PHYSICAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackMechanism PHYSICAL
```

Physical attack mechanism.

OPERATIONAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackMechanism OPERATIONAL
```

Operational attack mechanism.

INFORMATIONAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackMechanism INFORMATIONAL
```

Informational attack mechanism.

UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackMechanism UNKNOWN
```

Unknown attack mechanism.

Methods

values

```
public static Case.AttackMechanism\[\] values()
```

valueOf

```
public static Case.AttackMechanism valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Case.AttackAgent

java.lang.Object
└─ java.lang.Enum
 └─ com.arcsight.product.manager.resource.service.v1.model.Case.AttackAgent

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.AttackAgent**
extends Enum

The enum values for the field attack_agent of the table extended case.

Field Summary	
public static final	COLLABORATIVE Collaborative attack agent.
public static final	INSIDER Insider attack agent.
public static final	OUTSIDER Outside attack agent
public static final	UNKNOWN Unknown attack agent.
Method Summary	
static Case.AttackAgent	valueOf (String name)
static Case.AttackAgent[]	values ()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface java.lang.Comparable	
compareTo	

Fields

INSIDER

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackAgent INSIDER  
  
Insider attack agent.
```

COLLABORATIVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackAgent COLLABORATIVE  
  
Collaborative attack agent.
```

OUTSIDER

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackAgent OUTSIDER  
  
Outside attack agent
```

UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AttackAgent UNKNOWN  
  
Unknown attack agent.
```

Methods

values

```
public static Case.AttackAgent\[\] values()
```

valueOf

```
public static Case.AttackAgent valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Case.Vulnerability

java.lang.Object
└- java.lang.Enum
└- com.arcsight.product.manager.resource.service.v1.model.Case.Vulnerability

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.Vulnerability**
extends Enum

The enum values for the field vulnerability of the table extended case.

Field Summary	
public static final	DESIGN Design vulnerability.
public static final	ENVIRONMENT Environment vulnerability.
public static final	OPERATIONAL Operational vulnerability.
public static final	UNKNOWN Unknown vulnerability.
Method Summary	
Case.Vulnerability static	valueOf (String name)
Case.Vulnerability[] static	values ()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface java.lang.Comparable	
compareTo	

Fields

DESIGN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Vulnerability DESIGN
```

Design vulnerability.

OPERATIONAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Vulnerability OPERATIONAL
```

Operational vulnerability.

ENVIRONMENT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Vulnerability ENVIRONMENT
```

Environment vulnerability.

UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Vulnerability UNKNOWN
```

Unknown vulnerability.

Methods

values

```
public static Case.Vulnerability\[\] values()
```

valueOf

```
public static Case.Vulnerability valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class Case.Sensitivity

java.lang.Object
└- java.lang.Enum
└- com.arcsight.product.manager.resource.service.v1.model.Case.Sensitivity

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.Sensitivity**
extends Enum

The enum values for the field sensitivity of the table extended case.

Field Summary	
public static final	CONFIDENTIAL Confidential sensitivity.
public static final	SECRET Secret sensitivity.
public static final	TOP_SECRET Top secret sensitivity.
public static final	UNCLASSIFIED Unclassified sensitivity.

Method Summary	
int	intValue() Returns an internal code of the constant.
static Case.Sensitivity	valueOf(int code) Creates a constant from the internal code.
static Case.Sensitivity	valueOf(String name)
static Case.Sensitivity[]	values()

Methods inherited from class java.lang.Enum
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

UNCLASSIFIED

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Sensitivity UNCLASSIFIED
```

Unclassified sensitivity.

CONFIDENTIAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Sensitivity CONFIDENTIAL
```

Confidential sensitivity.

SECRET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Sensitivity SECRET
```

Secret sensitivity.

TOP_SECRET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Sensitivity TOP_SECRET
```

Top secret sensitivity.

Methods

values

```
public static Case.Sensitivity\[\] values()
```

valueOf

```
public static Case.Sensitivity valueOf(String name)
```

intValue

```
public int intValue()
```

Returns an internal code of the constant.

Returns:

an internal code of the constant.

valueOf

public static [Case.Sensitivity](#) **valueOf**(int code)

Creates a constant from the internal code.

Parameters:

code - the internal code of a constant.

Returns:

the constant corresponding to the code.

Throws:

`IllegalArgumentException` - if there is no constant corresponds to the code.

com.arcsight.product.manager.resource.service.v1.model

Class Case.AssociatedImpact

java.lang.Object
└─ java.lang.Enum
 └─ com.arcsight.product.manager.resource.service.v1.model.Case.AssociatedImpact

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.AssociatedImpact**
extends Enum

The enum values for the field associated_impact of the table extended case, which classify the associated impact of the case.

Field Summary	
public static final	AVAILABILITY Availability of associated impact of the issue.
public static final	CONFIDENTIALITY Confidentiality of associated impact of the issue.
public static final	INTEGRITY Integrity of associated impact of the issue.
public static final	UNKNOWN Unknown of associated impact of the issue.
Method Summary	
static Case.AssociatedImpact	valueOf (String name)
static Case.AssociatedImpact []	values ()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface java.lang.Comparable	
compareTo	

Fields

AVAILABILITY

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AssociatedImpact AVAILABILITY
```

Availability of associated impact of the issue.

CONFIDENTIALITY

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AssociatedImpact  
CONFIDENTIALITY
```

Confidentiality of associated impact of the issue.

INTEGRITY

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AssociatedImpact INTEGRITY
```

Integrity of associated impact of the issue.

UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.AssociatedImpact UNKNOWN
```

Unknown of associated impact of the issue.

Methods

values

```
public static Case.AssociatedImpact\[\] values()
```

valueOf

```
public static Case.AssociatedImpact valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class Case.Action

java.lang.Object
└- java.lang.Enum
 └- com.arcsight.product.manager.resource.service.v1.model.Case.Action

All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.Action**
extends Enum

The enum values for the field action of the table extended case, which specify the action on the case.

Field Summary	
public static final	BLOCK_OR_SHUTDOWN Block_or_shutdown action on the case.
public static final	MONITORING Monitoring action on the case.
public static final	OTHER Other action on the case.
Method Summary	
static Case.Action	valueOf (String name)
static Case.Action[]	values ()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface java.lang.Comparable	
compareTo	
Fields	

BLOCK_OR_SHUTDOWN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Action  
BLOCK_OR_SHUTDOWN
```

Block_or_shutdown action on the case.

MONITORING

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Action  
MONITORING
```

Monitoring action on the case.

OTHER

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.Action  
OTHER
```

Other action on the case.

Methods

values


```
public static Case.Action\[\] values()
```

valueOf

```
public static Case.Action valueOf(String name)
```


com.arcsight.product.manager.resource.service.v1.model

Class Case.VulnerabilityType1



All Implemented Interfaces:
Serializable, Comparable

public static final class **Case.VulnerabilityType1**
extends Enum

The enum values for the field vulnerability_type1 of the table extended case.

Field Summary	
public static final	ACCIDENTAL Accidental vulnerability type.
public static final	INTENTIONAL Intentional vulnerability type.

Method Summary	
Case.VulnerabilityType1 static	valueOf (String name)
Case.VulnerabilityType1 static	values ()

Methods inherited from class java.lang.Enum
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable
compareTo

Fields

ACCIDENTAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType1 ACCIDENTAL
```

Accidental vulnerability type.

INTENTIONAL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType1  
INTENTIONAL
```

Intentional vulnerability type.

Methods

values

```
public static Case.VulnerabilityType1\[\] values()
```

valueOf

```
public static Case.VulnerabilityType1 valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Case.VulnerabilityType2

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.VulnerabilityType2**
extends Enum

The enum values for the field vulnerability_type2 of the table extended case.

Field Summary

public static final	DOS_ATTACK Dos_attack vulnerability type.
public static final	EMI_RFI Emi_rfi vulnerability type.
public static final	INSERTION_OF_DATA Insertion of data vulnerability type.
public static final	PROBES Probes vulnerability type.
public static final	ROOT_COMPROMISE Root_compromise vulnerability type.
public static final	THEFT_OF_SERVICE Theft_of_service vulnerability type.
public static final	UNAUTHORIZED Unauthorized vulnerability type.
public static final	USER_ACCOUNT User_account vulnerability type.

Method Summary

static Case.VulnerabilityType2	valueOf (String name)
static Case.VulnerabilityType2[]	values ()

Methods inherited from class `java.lang.Enum`

`compareTo`, `equals`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

EMI_RFI

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2 EMI_RFI
```

Emi_rfi vulnerability type.

INSERTION_OF_DATA

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2
INSERTION_OF_DATA
```

Insertion of data vulnerability type.

THEFT_OF_SERVICE

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2
THEFT_OF_SERVICE
```

Theft_of_service vulnerability type.

UNAUTHORIZED

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2
UNAUTHORIZED
```

Unauthorized vulnerability type.

PROBES

```
public static final
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2 PROBES
```

Probes vulnerability type.

ROOT_COMPROMISE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2  
ROOT_COMPROMISE
```

Root_compromise vulnerability type.

DOS_ATTACK

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2 DOS_ATTACK
```

Dos_attack vulnerability type.

USER_ACCOUNT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.VulnerabilityType2  
USER_ACCOUNT
```

User_account vulnerability type.

Methods

values

```
public static Case.VulnerabilityType2\[\] values()
```

valueOf

```
public static Case.VulnerabilityType2 valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Case.History

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Case.History

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.History**
extends Enum

The enum values for the field history of the table extended case, which is ticket resolution history.

Field Summary

public static final	KNOWN_OCCURENCE Known_occurence history
public static final	UNKNOWN Unknown history

Method Summary

static Case.History	valueOf (String name)
static Case.History[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

KNOWN_OCCURENCE

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.History  
KNOWN_OCCURENCE
```

Known_occurence history

UNKNOWN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Case.History  
UNKNOWN
```

Unknown history

Methods

values

```
public static Case.History\[\] values()
```

valueOf

```
public static Case.History valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Case.Resistance

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Case.Resistance

All Implemented Interfaces:

Serializable, Comparable

public static final class **Case.Resistance**
extends Enum

The enum values for the field history of the table extended case, which specify ticket resolution resistance.

Field Summary

public static final	HIGH High resistance.
public static final	LOW Low resistance.
public static final	UNKNOWN Unknown resistance.

Method Summary

Case.Resistance static	valueOf (String name)
Case.Resistance[] static	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

HIGH

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Resistance HIGH
```

High resistance.

LOW

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Resistance LOW
```

Low resistance.

UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Case.Resistance UNKNOWN
```

Unknown resistance.

Methods

values

```
public static Case.Resistance\[\] values()
```

valueOf

```
public static Case.Resistance valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class CaseAggregateData

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.CaseAggregateData

```
public class CaseAggregateData
extends Object
```

Simple POJO that represents the case count api results.

Constructor Summary

public	CaseAggregateData()

Method Summary

CaseAggregateData	clone()
String	getAggregationType()
String	getAggregationValue()
int	getCount()
List	getSubAggregation()
CaseAggregateData	merge(CaseAggregateData otherAggData)
void	setAggregationType(String aggregationType)
void	setAggregationValue(String aggregationValue)
void	setCount(int count)
void	setSubAggregation(List subAggregation)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseAggregateData

```
public CaseAggregateData()
```

Methods

getAggregationType

```
public String getAggregationType()
```

setAggregationType

```
public void setAggregationType(String aggregationType)
```

getAggregationValue

```
public String getAggregationValue()
```

setAggregationValue

```
public void setAggregationValue(String aggregationValue)
```

getCount

```
public int getCount()
```

setCount

```
public void setCount(int count)
```

getSubAggregation

```
public List getSubAggregation()
```

setSubAggregation

```
public void setSubAggregation(List subAggregation)
```

merge

public [CaseAggregateData](#) merge([CaseAggregateData](#) otherAggData)

clone

public [CaseAggregateData](#) clone()

com.arcsight.product.manager.resource.service.v1.model

Class CaseClosureVelocity

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.CaseClosureVelocity

public class CaseClosureVelocity

extends Object

Constructor Summary	
public	CaseClosureVelocity()

Method Summary	
long	getAverageTimeToCloseAfterCreation()
long	getAverageTimeToCloseAfterLastAnnotation()
float	getClosedCasesTrend()
long	getEndTime()
long	getStartTime()
void	setAverageTimeToCloseAfterCreation (long averageTimeToCloseAfterCreation)
void	setAverageTimeToCloseAfterLastAnnotation (long averageTimeToCloseAfterLastAnnotation)
void	setClosedCasesTrend (float closedCasesTrend)
void	setEndTime (long endTime)
void	setStartTime (long startTime)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseClosureVelocity

```
public CaseClosureVelocity()
```

Methods

getAverageTimeToCloseAfterCreation

```
public long getAverageTimeToCloseAfterCreation()
```

setAverageTimeToCloseAfterCreation

```
public void setAverageTimeToCloseAfterCreation(long averageTimeToCloseAfterCreation)
```

getAverageTimeToCloseAfterLastAnnotation

```
public long getAverageTimeToCloseAfterLastAnnotation()
```

setAverageTimeToCloseAfterLastAnnotation

```
public void setAverageTimeToCloseAfterLastAnnotation(long averageTimeToCloseAfterLastAnnotation)
```

getClosedCasesTrend

```
public float getClosedCasesTrend()
```

setClosedCasesTrend

```
public void setClosedCasesTrend(float closedCasesTrend)
```

getEndTime

```
public long getEndTime()
```

setEndTime

```
public void setEndTime(long endTime)
```

getStartTime

```
public long getStartTime()
```

setStartTime

```
public void setStartTime(long startTime)
```

com.arcsight.product.manager.resource.service.v1.model Class CasesClosed

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.CasesClosed

public class **CasesClosed**
extends Object

Constructor Summary

public	CasesClosed (long startTime, long endTime, int count)
public	CasesClosed ()

Method Summary

int	getCount ()
long	getEndTime ()
long	getStartTime ()
void	setCount (int count)
void	setEndTime (long endTime)
void	setStartTime (long startTime)
String	toString ()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CasesClosed

```
public CasesClosed(long startTime,  
                   long endTime,  
                   int count)
```

CasesClosed

public **CasesClosed**()

Methods

getStartTime

public long **getStartTime**()

setStartTime

public void **setStartTime**(long startTime)

getEndTime

public long **getEndTime**()

setEndTime

public void **setEndTime**(long endTime)

getCount

public int **getCount**()

setCount

public void **setCount**(int count)

toString

public String **toString**()

com.arcsight.product.manager.resource.service.v1.model Class CaseStageTransition

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.CaseStageTransition

public class **CaseStageTransition**
extends Object

Constructor Summary

public	CaseStageTransition()

Method Summary

void	addToTimeTaken (long timeTaken)
void	averageTheTimeTaken ()
String	getFrom ()
int	getNumberOfCases ()
long	getTimeTaken ()
String	getTo ()
void	incrementNumberOfCases ()
void	setFrom (String from)
void	setNumberOfCases (int numberOfCases)
void	setTimeTaken (long timeTaken)
void	setTo (String to)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseStageTransition

```
public CaseStageTransition()
```

Methods

getFrom

```
public String getFrom()
```

setFrom

```
public void setFrom(String from)
```

getTo

```
public String getTo()
```

setTo

```
public void setTo(String to)
```

getTimeTaken

```
public long getTimeTaken()
```

setTimeTaken

```
public void setTimeTaken(long timeTaken)
```

getNumberOfCases

```
public int getNumberOfCases()
```

setNumberOfCases

```
public void setNumberOfCases(int numberOfCases)
```

incrementNumberOfCases

```
public void incrementNumberOfCases()
```

addToTimeTaken

```
public void addToTimeTaken(long timeTaken)
```

averageTheTimeTaken

```
public void averageTheTimeTaken()
```

com.arcsight.product.manager.resource.service.v1.model

Class CaseStageTransitions

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.CaseStageTransitions

public class **CaseStageTransitions**
extends Object

Constructor Summary	
public	CaseStageTransitions()

Method Summary	
long	getEndTime()
List	getStageTransitions()
long	getStartTime()
void	setEndTime(long endTime)
void	setStageTransitions(List stageTransitions)
void	setStartTime(long startTime)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseStageTransitions
public **CaseStageTransitions()**

Methods

getStartTime

```
public long getStartTime()
```

setStartTime

```
public void setStartTime(long startTime)
```

getEndTime

```
public long getEndTime()
```

setEndTime

```
public void setEndTime(long endTime)
```

getStageTransitions

```
public List getStageTransitions()
```

setStageTransitions

```
public void setStageTransitions(List stageTransitions)
```

com.arcsight.product.manager.resource.service.v1.model

Class CompactResourceID

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.CompactResourceID

All Implemented Interfaces:
Serializable

public class **CompactResourceID**
extends Object
implements Serializable

Constructor Summary

public	CompactResourceID()

Method Summary

long	getLong1()
long	getLong2()
boolean	isHexEncoding()
void	setHexEncoding (boolean isHexEncoding)
void	setLong1 (long _long1)
void	setLong2 (long _long2)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CompactResourceID
public **CompactResourceID()**

Methods

getLong1

public long **getLong1**()

setLong1

public void **setLong1**(long _long1)

getLong2

public long **getLong2**()

setLong2

public void **setLong2**(long _long2)

isHexEncoding

public boolean **isHexEncoding**()

setHexEncoding

public void **setHexEncoding**(boolean isHexEncoding)

com.arcsight.product.manager.resource.service.v1.model

Class Config

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.Config

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[GenericServerConfig](#)

public class **Config**
extends Object
implements Serializable

Nested Class Summary

class	Config.ConfigTypes Config.ConfigTypes

Constructor Summary

public	Config()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

Config
public **Config()**

com.arcsight.product.manager.resource.service.v1.model

Class Config.ConfigTypes

java.lang.Object
└- java.lang.Enum
└- com.arcsight.product.manager.resource.service.v1.model.Config.ConfigTypes

All Implemented Interfaces:
Serializable, Comparable

public static final class **Config.ConfigTypes**
extends Enum

The enum of Config Types.

Field Summary	
public static final	ConfigTypes_GenericServer Generic server configure type.
Method Summary	
Class	getConfigClass() Gets this configure class.
static Config.ConfigTypes	getConfigType(int value) Gets the configure type specified by type's int value.
static Config.ConfigTypes	getConfigType(String classname) Gets the configure type specified by type's name.
int	getValue() Gets the configure type.
static Config.ConfigTypes	valueOf(String name)
static Config.ConfigTypes[]	values()
Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface java.lang.Comparable	

compareTo

Fields

ConfigTypes_GenericServer

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Config.ConfigTypes  
ConfigTypes_GenericServer
```

Generic server configure type.

Methods

values

```
public static Config.ConfigTypes\[\] values()
```

valueOf

```
public static Config.ConfigTypes valueOf(String name)
```

getValue

```
public int getValue()
```

Gets the configure type.

Returns:

The configure type.

getConfigClass

```
public Class getConfigClass()
```

Gets this configure class.

Returns:

The configure class.

getConfigType

```
public static Config.ConfigTypes getConfigType(int value)
```

Gets the configure type specified by type's int value.

Parameters:

value - The value of config type.

Returns:

The ConfigTypes for this type value.

getConfigType

public static [Config.ConfigTypes](#) getConfigType(String classname)

Gets the configure type specified by type's name.

Parameters:

classname - The name of config class.

Returns:

The ConfigTypes for this class name.

com.arcsight.product.manager.resource.service.v1.model

Class ConfigTimeInterval

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ConfigTimeInterval

All Implemented Interfaces:
Serializable

```
public class ConfigTimeInterval
extends Object
implements Serializable
```

Constructor Summary

public	ConfigTimeInterval (int fromYear, int fromMonth, int fromDay, int fromHour24, int fromMinute, int fromSecond, int toYear, int toMonth, int toDay, int toHour24, int toMinute, int toSecond, String timeZoneId)
public	ConfigTimeInterval ()

Method Summary

int	getFromDay ()
int	getFromHour24 ()
int	getFromMinute ()
int	getFromMonth ()
int	getFromSecond ()
int	getFromYear ()
String	getTimeZoneId ()
int	getToDay ()
int	getToHour24 ()
int	getToMinute ()

int	getToMonth()
int	getToSecond()
int	getToYear()

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ConfigTimeInterval

```
public ConfigTimeInterval(int fromYear,
                        int fromMonth,
                        int fromDay,
                        int fromHour24,
                        int fromMinute,
                        int fromSecond,
                        int toYear,
                        int toMonth,
                        int toDay,
                        int toHour24,
                        int toMinute,
                        int toSecond,
                        String timeZoneId)
```

Parameters:

```
fromYear
fromMonth
fromDay
fromHour24
fromMinute
fromSecond
toYear
toMonth
toDay
toHour24
toMinute
toSecond
timeZoneId
```

ConfigTimeInterval

```
public ConfigTimeInterval()
```

Methods

getFromYear

```
public int getFromYear()
```

Returns:

the fromYear

getFromMonth

```
public int getFromMonth()
```

Returns:

the fromMonth

getFromDay

```
public int getFromDay()
```

Returns:

the fromDay

getFromHour24

```
public int getFromHour24()
```

Returns:

the fromHour24

getFromMinute

```
public int getFromMinute()
```

Returns:

the fromMinute

getFromSecond

```
public int getFromSecond()
```

Returns:

the fromSecond

getToYear

public int **getToYear()**

Returns:
the toYear

getToMonth

public int **getToMonth()**

Returns:
the toMonth

getToDay

public int **getToDay()**

Returns:
the toDay

getToHour24

public int **getToHour24()**

Returns:
the toHour24

getToMinute

public int **getToMinute()**

Returns:
the toMinute

getToSecond

public int **getToSecond()**

Returns:
the toSecond

getTimeZoneld

public String **getTimeZoneId()**

Returns:

the timeZoneld

com.arcsight.product.manager.resource.service.v1.model Class ConfigurationItem

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ [com.arcsight.product.manager.resource.service.v1.model.ConfigurationItem](#)

All Implemented Interfaces:
Serializable

public class **ConfigurationItem**
extends [Resource](#)

Nested Class Summary

class	ConfigurationItem.ConfigFormat ConfigurationItem.ConfigFormat

Constructor Summary

public	ConfigurationItem()

Method Summary

Config	getConfig()
String	getConfigFormat()
int	getConfigType()
void	setConfig(Config config)
void	setConfigFormat(String configFormat)
void	setConfigType(int configType)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setTypeNames](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ConfigurationItem

```
public ConfigurationItem()
```

Methods

getConfigType

```
public int getConfigType()
```

setConfigType

```
public void setConfigType(int configType)
```

getConfigFormat

```
public String getConfigFormat()
```

setConfigFormat

```
public void setConfigFormat(String configFormat)
```


setConfig

public void **setConfig**([Config](#) config)

getConfig

public [Config](#) **getConfig**()

com.arcsight.product.manager.resource.service.v1.model Class ConfigurationItem.ConfigFormat



public static final class ConfigurationItem.ConfigFormat
extends Enum

Field Summary	
public static final	json
public static final	xml

Method Summary	
static ConfigurationItem.ConfigFormat	valueOf (String name)
static ConfigurationItem.ConfigFormat[]	values ()

Methods inherited from class java.lang.Enum
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable
compareTo

Fields

json

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ConfigurationItem.ConfigFormat  
json
```

xml

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ConfigurationItem.ConfigFormat xml
```

Methods

values

```
public static ConfigurationItem.ConfigFormat\[\] values()
```

valueOf

```
public static ConfigurationItem.ConfigFormat valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model Class Connector

java.lang.Object

└- [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└- com.arcsight.product.manager.resource.service.v1.model.Connector

All Implemented Interfaces:
Serializable

public class **Connector**
extends [Resource](#)

Nested Class Summary

class	Connector.OperationalStatusTypes Connector.OperationalStatusTypes
class	Connector.SendCommand Connector.SendCommand

Constructor Summary

public	Connector ()

Method Summary

ConnectorConfig	getAgentConfig()
String	getCodeVersion()
String	getConfigDefinition()
String	getConfigVersion()
User	getLinkedUser()
List	getNetworks()
String	getOperationalStatus()
String	getOwningServer()

boolean	<u>isAlive()</u>
void	<u>setAgentConfig(ConnectorConfig agentConfig)</u>
void	<u>setAlive(boolean isAlive)</u>
void	<u>setCodeVersion(String codeVersion)</u>
void	<u>setConfigDefinition(String configDefinition)</u>
void	<u>setConfigVersion(String configVersion)</u>
void	<u>setLinkedUser(User linkedUser)</u>
void	<u>setNetworks(List networks)</u>
void	<u>setOperationalStatus(String operationalStatus)</u>
void	<u>setOwningServer(String owningServer)</u>

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class [java.lang.Object](#)

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

Connector

```
public Connector()
```


Methods

getConfigDefinition

```
public String getConfigDefinition()
```

setConfigDefinition

```
public void setConfigDefinition(String configDefinition)
```

getConfigVersion

```
public String getConfigVersion()
```

setConfigVersion

```
public void setConfigVersion(String configVersion)
```

getOperationalStatus

```
public String getOperationalStatus()
```

setOperationalStatus

```
public void setOperationalStatus(String operationalStatus)
```

getOwningServer

```
public String getOwningServer()
```

setOwningServer

```
public void setOwningServer(String owningServer)
```

isAlive

```
public boolean isAlive()
```

setAlive

```
public void setAlive(boolean isAlive)
```

getCodeVersion

```
public String getCodeVersion()
```

setCodeVersion

```
public void setCodeVersion(String codeVersion)
```

getNetworks

```
public List getNetworks()
```

setNetworks

```
public void setNetworks(List networks)
```

setLinkedUser

```
public void setLinkedUser(User linkedUser)
```

getLinkedUser

```
public User getLinkedUser()
```

setAgentConfig

```
public void setAgentConfig(ConnectorConfig agentConfig)
```

getAgentConfig

public [ConnectorConfig](#) getAgentConfig()

com.arcsight.product.manager.resource.service.v1.model Class Connector.SendCommand

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand

All Implemented Interfaces:

Serializable, Comparable

public static final class **Connector.SendCommand**
extends Enum

Field Summary

public static final	CONTINUE
public static final	PAUSE
public static final	RESTART
public static final	START
public static final	STOP
public static final	TERMINATE

Method Summary

static Connector.SendCommand	valueOf (String name)
static Connector.SendCommand []	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

START

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand START
```

STOP

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand STOP
```

PAUSE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand PAUSE
```

RESTART

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand RESTART
```

CONTINUE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand CONTINUE
```

TERMINATE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.SendCommand TERMINATE
```

Methods

values

```
public static Connector.SendCommand\[\] values()
```

valueOf

public static [Connector.SendCommand](#) **valueOf**(String name)

com.arcsight.product.manager.resource.service.v1.model

Class Connector.OperationalStatusTypes

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.Connector.OperationalStatusTypes

All Implemented Interfaces:

Serializable, Comparable

public static class **Connector.OperationalStatusTypes**
extends Enum

Field Summary

public static final	SENSOR_PAUSED
public static final	SENSOR_RUNNING
public static final	SENSOR_STOPPED
public static final	SENSOR_UNKNOWN

Method Summary

static String	getStatusFromInt (int statusNum)
static int	getValue (String status)
static Connector.OperationalStatusTypes	valueOf (String name)
static Connector.OperationalStatusTypes[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

SENSOR_STOPPED

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.OperationalStatusTypes  
SENSOR_STOPPED
```

SENSOR_RUNNING

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.OperationalStatusTypes  
SENSOR_RUNNING
```

SENSOR_PAUSED

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.OperationalStatusTypes  
SENSOR_PAUSED
```

SENSOR_UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Connector.OperationalStatusTypes  
SENSOR_UNKNOWN
```

Methods

values

```
public static Connector.OperationalStatusTypes\[\] values()
```

valueOf

```
public static Connector.OperationalStatusTypes valueOf(String name)
```

getValue

```
public static int getValue(String status)
```

getStatusFromInt

```
public static String getStatusFromInt(int statusNum)
```

com.arcsight.product.manager.resource.service.v1.model

Class ConnectorCommandAction

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ConnectorCommandAction

All Implemented Interfaces:

Serializable

public class **ConnectorCommandAction**
extends Object
implements Serializable

Constructor Summary

public	ConnectorCommandAction()

Method Summary

String	getCmdGroupDisplayName()
String	getCmdGroupName()
String	getCmdName()
String	getDisplayName()
String	getMarshalledValues()
ArrayList	getParameterDescriptorList()
boolean	isParameterRequired()
void	setCmdGroupDisplayName(String cmdGroupDisplayName)
void	setCmdGroupName(String cmdGroupName)
void	setCmdName(String cmdName)
void	setDisplayName(String displayName)
void	setMarshalledValues(String marshalledValues)

void	<u>setParameterDescriptorList</u> (ArrayList parameterDescriptorList)
void	<u>setParameterRequired</u> (boolean parameterRequired)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ConnectorCommandAction

public ConnectorCommandAction()

Methods

getDisplayName

public String getDisplayName()

Returns:
the displayName

setDisplayName

public void setDisplayName(String displayName)

Parameters:
displayName - the displayName to set

getMarshaledValues

public String getMarshaledValues()

Returns:
the marshalledValues

setMarshaledValues

public void setMarshaledValues(String marshalledValues)

Parameters:

marshalledValues - the marshalledValues to set

isParameterRequired

```
public boolean isParameterRequired()
```

setParameterRequired

```
public void setParameterRequired(boolean parameterRequired)
```

getParameterDescriptorList

```
public ArrayList getParameterDescriptorList()
```

setParameterDescriptorList

```
public void setParameterDescriptorList(ArrayList parameterDescriptorList)
```

getCmdName

```
public String getCmdName()
```

setCmdName

```
public void setCmdName(String cmdName)
```

getCmdGroupName

```
public String getCmdGroupName()
```

setCmdGroupName

```
public void setCmdGroupName(String cmdGroupName)
```

getCmdGroupDisplayName

```
public String getCmdGroupDisplayName()
```

setCmdGroupDisplayName

```
public void setCmdGroupDisplayName(String cmdGroupDisplayName)
```

com.arcsight.product.manager.resource.service.v1.model

Class ConnectorCommandGroup

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.ConnectorCommandGroup

All Implemented Interfaces:
Serializable

Deprecated. *Not really implemented*

JSON prototype

public class **ConnectorCommandGroup**
extends Object
implements Serializable

Constructor Summary

public	ConnectorCommandGroup() Deprecated.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ConnectorCommandGroup

public **ConnectorCommandGroup()**
Deprecated.

com.arcsight.product.manager.resource.service.v1.model Class ConnectorConfig

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ConnectorConfig

All Implemented Interfaces:
Serializable

public class **ConnectorConfig**
extends Object
implements Serializable

Constructor Summary

public	ConnectorConfig()

Method Summary

List	getAlternateConnectorConfig()
List	getCommandGroups()
String	getComment()
String	getConnectorId()
String	getConnectorLocation()
String	getConnectorName()
String	getConnectorType()
String	getConnectorVersion()
int	getCurrentConfig()
ConnectorConfig	getDefaultConnectorConfig()
String	getDeviceLocation()
int	getHeartbeatFreq()

long	getLastModified()
int	getLastStatus()
String	getModifiedBy()
ConnectorConfig	getParentConfig()
String	getPassword()
ConfigTimeInterval	getTimeInterval()
byte	getTransportMode()
String	getVersion()
List	getvPreprocessors()
boolean	isDefault()
boolean	isExplicitUTF8()
boolean	isParent()
void	setAlternateConnectorConfig (List alternateConnectorConfig)
void	setCommandGroups (List commandGroups)
void	setComment (String comment)
void	setConnectorId (String connectorId)
void	setConnectorLocation (String connectorLocation)
void	setConnectorName (String connectorName)
void	setConnectorType (String connectorType)
void	setConnectorVersion (String connectorVersion)
void	setCurrentConfig (int currentConfig)
void	setDefault (boolean isDefault)

void	<u>setDefaultConnectorConfig</u> (<u>ConnectorConfig</u> defaultConnectorConfig)
void	<u>setDeviceLocation</u> (String deviceLocation)
void	<u>setExplicitUTF8</u> (boolean explicitUTF8)
void	<u>setHeartbeatFreq</u> (int heartbeatFreq)
void	<u>setLastModified</u> (long lastModified)
void	<u>setLastStatus</u> (int lastStatus)
void	<u>setModifiedBy</u> (String modifiedBy)
void	<u>setParent</u> (boolean isParent)
void	<u>setParentConfig</u> (<u>ConnectorConfig</u> parentConfig)
void	<u>setPassword</u> (String password)
void	<u>setTimeInterval</u> (<u>ConfigTimeInterval</u> timeInterval)
void	<u>setTransportMode</u> (byte transportMode)
void	<u>setVersion</u> (String version)
void	<u>setvPreprocessors</u> (List vPreprocessors)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ConnectorConfig

public **ConnectorConfig**()

Methods

getConnectorType

public String **getConnectorType**()

setConnectorType

public void **setConnectorType**(String connectorType)

getConnectorVersion

public String **getConnectorVersion**()

setConnectorVersion

public void **setConnectorVersion**(String connectorVersion)

getCommandGroups

public List **getCommandGroups**()

Returns:

setCommandGroups

public void **setCommandGroups**(List commandGroups)

getTransportMode

public byte **getTransportMode**()

setTransportMode

public void **setTransportMode**(byte transportMode)

getCurrentConfig

public int **getCurrentConfig**()

setCurrentConfig

public void **setCurrentConfig**(int currentConfig)

isParent

public boolean **isParent**()

setParent

public void **setParent**(boolean isParent)

getAlternateConnectorConfig

public List **getAlternateConnectorConfig**()

setAlternateConnectorConfig

public void **setAlternateConnectorConfig**(List alternateConnectorConfig)

getDefaultConnectorConfig

public [ConnectorConfig](#) **getDefaultConnectorConfig**()

setDefaultConnectorConfig

public void **setDefaultConnectorConfig**([ConnectorConfig](#) defaultConnectorConfig)

getParentConfig

public [ConnectorConfig](#) **getParentConfig**()

setParentConfig

public void **setParentConfig**([ConnectorConfig](#) parentConfig)

getConnectorName

public String **getConnectorName**()

setConnectorName

public void **setConnectorName**(String connectorName)

getConnectorId

public String **getConnectorId**()

setConnectorId

public void **setConnectorId**(String connectorId)

getPassword

public String **getPassword**()

setPassword

public void **setPassword**(String password)

getComment

public String **getComment**()

setComment

public void **setComment**(String comment)

getVersion

public String **getVersion**()

setVersion

public void **setVersion**(String version)

getModifiedBy

public String **getModifiedBy**()

setModifiedBy

public void **setModifiedBy**(String modifiedBy)

getLastModified

public long **getLastModified**()

setLastModified

public void **setLastModified**(long lastModified)

getDeviceLocation

public String **getDeviceLocation**()

setDeviceLocation

public void **setDeviceLocation**(String deviceLocation)

getConnectorLocation

public String **getConnectorLocation**()

setConnectorLocation

public void **setConnectorLocation**(String connectorLocation)

isExplicitUTF8

public boolean **isExplicitUTF8**()

setExplicitUTF8

public void **setExplicitUTF8**(boolean explicitUTF8)

getvPreprocessors

public List **getvPreprocessors**()

setvPreprocessors

public void **setvPreprocessors**(List vPreprocessors)

getHeartbeatFreq

public int **getHeartbeatFreq**()

setHeartbeatFreq

public void **setHeartbeatFreq**(int heartbeatFreq)

getLastStatus

public int **getLastStatus**()

setLastStatus

public void **setLastStatus**(int lastStatus)

setDefault

public void **setDefault**(boolean isDefault)

Parameters:

isDefault - the isDefault to set

isDefault

public boolean **isDefault**()

Returns:

the isDefault

getTimeInterval

public [ConfigTimeInterval](#) **getTimeInterval**()

Returns:

the timeInterval

setTimeInterval

public void **setTimeInterval**([ConfigTimeInterval](#) timeInterval)

Parameters:

timeInterval - the timeInterval to set

com.arcsight.product.manager.resource.service.v1.model

Class ConnectorStatus

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.ConnectorStatus

All Implemented Interfaces:
Serializable

```
public class ConnectorStatus
extends Object
implements Serializable
```

Describes the status of a connector.

JSON prototype

Constructor Summary

public	ConnectorStatus()

Method Summary

String	getFilePath() Deprecated. Method's name is misleading. Please use getProcessId() instead.
String	getMessage()
String	getProcessId() Returns ID of the process created for command execution.
String	getResponseId()
String	getStatus()
long	getTimestamp()
boolean	isFileAvailable()
boolean	isProcessCompleted()
void	setFileAvailable(boolean fileAvailable) Set the flag whether there is file available to download
void	setFilePath(String filePath) Deprecated. Method's name is misleading. Please use setProcessId(String) instead.

void	setMessage (String message)
void	setProcessCompleted (boolean processCompleted)
void	setProcessId (String processId) Sets the processId associated with this process.
void	setResponseId (String responseId) Set current response id
void	setStatus (String status)
void	setTimestamp (long timestamp)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ConnectorStatus

```
public ConnectorStatus()
```

Methods

getStatus

```
public String getStatus()
```

Returns:

the status

setStatus

```
public void setStatus(String status)
```

Parameters:

status - the status to set

getMessage

```
public String getMessage()
```

Returns:
the message

setMessage

```
public void setMessage(String message)
```

Parameters:
message - the message to set

setTimestamp

```
public void setTimestamp(long timestamp)
```

Parameters:
timestamp - the timestamp to set

getTimestamp

```
public long getTimestamp()
```

Returns:
the timestamp

setProcessCompleted

```
public void setProcessCompleted(boolean processCompleted)
```

Parameters:
processCompleted - the processCompleted to set

isProcessCompleted

```
public boolean isProcessCompleted()
```

Returns:
the processCompleted

getResponseId

```
public String getResponseId()
```

Returns:

the last message's response id

setResponseId

```
public void setResponseId(String responseId)
```

Set current response id

Parameters:

responseId - the response id to set

isFileAvailable

```
public boolean isFileAvailable()
```

Returns:

true if there is file available to download

setFileAvailable

```
public void setFileAvailable(boolean fileAvailable)
```

Set the flag whether there is file available to download

Parameters:

fileAvailable - the flag to set

getFilePath

```
public String getFilePath()
```

Deprecated. *Method's name is misleading. Please use [getProcessId\(\)](#) instead.*

PLEASE READ. This method returns internal task Id, not file path. Access to files is controlled by ConnectorService To download artifacts associated with taskId use `ConnectorService.initiateDownloadFile(java.lang.String)`

Returns:

ID of the internal task created for a command.

getProcessId

```
public String getProcessId()
```

Returns ID of the process created for command execution. Use the ID to check the state of process execution by calling `ConnectorService.getConnectorExecStatus(java.lang.String)`.

Returns:

ID of the internal process for command execution

setFilePath

```
public void setFilePath(String filePath)
```

Deprecated. *Method's name is misleading. Please use [setProcessId\(String\)](#) instead.*

PLEASE READ. This method stores internal task Id, not file path. Access to files is controlled by ConnectorService To download artifacts associated with taskId use `ConnectorService.initiateDownloadFile(java.lang.String)`

Parameters:

filePath - ID of the internal task created for a command.

setProcessId

```
public void setProcessId(String processId)
```

Sets the processId associated with this process. Use the ID to check the state of process execution by calling `ConnectorService.getConnectorExecStatus(java.lang.String)`.

Parameters:

processId

com.arcsight.product.manager.resource.service.v1.model

Class CorruptedResource

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.CorruptedResource

```
public class CorruptedResource
extends Object
```

Describes a corrupted resource.

Field Summary

public static final	CORRUPTION_DISPLAY_NAMES
public static final	CORRUPTION_ID_MISSING_CONCRETE The explanation ID for a resource that has been corrupted where the concrete attributes are missing. Value: 1
public static final	CORRUPTION_ID_UNKNOWN The reason for corruption is unknown. Value: 0
public static final	RELATIONSHIP_TYPES_MAX The max for relationship ints. Value: 62

Constructor Summary

public	CorruptedResource() Default constructor to make Axis happy.
public	CorruptedResource (int corruptionType, String id, String name, String alias, String externalID, String description, boolean isDisabled, long modificationCount, long createTimestamp, long modifiedTimestamp, String referencePage, String disabledReason, boolean inactive, String inactiveReason)

Method Summary

String	getAlias() Returns the alias of the resource.
int	getCorruptionType() Returns the reason for corruption of the described resource
long	getCreateTimestamp() Returns the time when the Resource was created.

String	<u>getDescription()</u> Returns the description of the resource.
String	<u>getDisabledReason()</u> For disabled resources it returns the reason why the resource was disabled.
String	<u>getExternalID()</u> Returns the external ID of the resource.
String	<u>getID()</u> Returns the ID of the resource.
String	<u>getInactiveReason()</u> For inactive resources it returns the reason why the resource is inactive.
long	<u>getModificationCount()</u> Returns the modification count of the resource.
long	<u>getModifiedTimestamp()</u> Returns the time when the Resource was last time modified.
String	<u>getName()</u> Returns the name of the resource.
String	<u>getReferencePage()</u> Returns the reference page of the resource.
boolean	<u>isDisabled()</u> Returns whether or not the resource is disabled.
boolean	<u>isInactive()</u> Returns whether or not the resource is inactive.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

CORRUPTION_ID_UNKNOWN

```
public static final int CORRUPTION_ID_UNKNOWN
```

The reason for corruption is unknown.
Constant value: **0**

CORRUPTION_ID_MISSING_CONCRETE

```
public static final int CORRUPTION_ID_MISSING_CONCRETE
```

The explanation ID for a resource that has been corrupted where the concrete attributes are missing.
Constant value: **1**

CORRUPTION_DISPLAY_NAMES

```
public static final java.lang.String CORRUPTION_DISPLAY_NAMES
```

RELATIONSHIP_TYPES_MAX

```
public static final int RELATIONSHIP_TYPES_MAX
```

The max for relationship ints.
Constant value: **62**

Constructors

CorruptedResource

```
public CorruptedResource()
```

Default constructor to make Axis happy.

CorruptedResource

```
public CorruptedResource(int corruptionType,  
                          String id,  
                          String name,  
                          String alias,  
                          String externalID,  
                          String description,  
                          boolean isDisabled,  
                          long modificationCount,  
                          long createTimeStamp,  
                          long modifiedTimestamp,  
                          String referencePage,  
                          String disabledReason,  
                          boolean inactive,  
                          String inactiveReason)
```

Methods

getCorruptionType

```
public int getCorruptionType()
```

Returns the reason for corruption of the described resource

Returns:

Corruption reason

getID

```
public String getID()
```

Returns the ID of the resource.

Returns:
ID of the resource

getName

```
public String getName()
```

Returns the name of the resource.

Returns:
Resource name

getAlias

```
public String getAlias()
```

Returns the alias of the resource.

Returns:
The alias of the resource

getExternalID

```
public String getExternalID()
```

Returns the external ID of the resource.

Returns:
The external ID of the resource

getDescription

```
public String getDescription()
```

Returns the description of the resource.

Returns:
The description of the resource

isDisabled

```
public boolean isDisabled()
```

Returns whether or not the resource is disabled.

Returns:
Disable flag

getModificationCount

```
public long getModificationCount()
```


Returns the modification count of the resource.

Returns:

The modification count of the resource

getCreateTimestamp

```
public long getCreateTimestamp()
```

Returns the time when the Resource was created.

Returns:

Creation timestamp

getModifiedTimestamp

```
public long getModifiedTimestamp()
```

Returns the time when the Resource was last time modified.

Returns:

Modification timestamp

getReferencePage

```
public String getReferencePage()
```

Returns the reference page of the resource.

Returns:

Reference page

getDisabledReason

```
public String getDisabledReason()
```

For disabled resources it returns the reason why the resource was disabled.

Returns:

The reason why the resource was disabled

isInactive

```
public boolean isInactive()
```

Returns whether or not the resource is inactive.

Returns:

Inactive flag

getInactiveReason

```
public String getInactiveReason()
```


For inactive resources it returns the reason why the resource is inactive.

Returns:

The reason why the resource is inactive

com.arcsight.product.manager.resource.service.v1.model

Class CustomReportParameter



All Implemented Interfaces:
Serializable, Serializable

public class CustomReportParameter
extends ReportParameter
implements Serializable, Serializable

Represents a custom report parameter specified by user. The custom report parameter maps to one of the report parameters of a report component.

Constructor Summary	
public	CustomReportParameter()

Method Summary	
ReportComponentParameter[]	getMappedToParameters()
String	getOriginalValue() Returns the original value of the parameter, before it was evaluated.
void	setMappedToParameters(ReportComponentParameter[] mappedToParameters)
void	setOriginalValue(String originalValue) Sets the original value of the parameter.

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.ReportParameter	
getDisplayname , getFieldName , getName , getParameterType , getSavedInheritedValue , getType , getValue , setDisplayname , setFieldName , setName , setParameterType , setSavedInheritedValue , setType , setValue	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CustomReportParameter

```
public CustomReportParameter()
```

Methods

getMappedToParameters

```
public ReportComponentParameter\[\] getMappedToParameters()
```

setMappedToParameters

```
public void setMappedToParameters(ReportComponentParameter\[\] mappedToParameters)
```

getOriginalValue

```
public String getOriginalValue()
```

Returns the original value of the parameter, before it was evaluated. This is used to save the dynamic dates before their value is evaluated to preserve their original format, which is useful in Velocity processing for reports.

Returns:

the original value of the parameter.

setOriginalValue

```
public void setOriginalValue(String originalValue)
```

Sets the original value of the parameter.

Parameters:

originalValue - the original value of the parameter.

com.arcsight.product.manager.resource.service.v1.model

Class DeviceDetail

```
java.lang.Object
└─com.arcsight.product.manager.resource.service.v1.model.DeviceDetail
```

```
public class DeviceDetail
extends Object
```

Describes a Device. It usually contains information about vendor, product and the version.

JSON prototype

Constructor Summary	
public	DeviceDetail()

Method Summary	
String	getDeviceProduct()
String	getDeviceVendor()
String	getDeviceVersion()
void	setDeviceProduct(String deviceProduct)
void	setDeviceVendor(String deviceVendor)
void	setDeviceVersion(String deviceVersion)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

```
DeviceDetail
public DeviceDetail()
```

Methods

setDeviceVersion

```
public void setDeviceVersion(String deviceVersion)
```

Parameters:

deviceVersion - the deviceVersion to set

getDeviceVersion

```
public String getDeviceVersion()
```

Returns:

the deviceVersion

setDeviceProduct

```
public void setDeviceProduct(String deviceProduct)
```

Parameters:

deviceProduct - the deviceProduct to set

getDeviceProduct

```
public String getDeviceProduct()
```

Returns:

the deviceProduct

setDeviceVendor

```
public void setDeviceVendor(String deviceVendor)
```

Parameters:

deviceVendor - the deviceVendor to set

getDeviceVendor

```
public String getDeviceVendor()
```

Returns:

the deviceVendor

com.arcsight.product.manager.resource.service.v1.model Class ErrorCode

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.ErrorCode

All Implemented Interfaces:
Serializable

public class **ErrorCode**
extends Object
implements Serializable

Field Summary	
public static final	AccessDeniedException Value: 10
public static final	ActiveListGlobalCapacityExceededException Value: 20
public static final	BrokerFactoryException Value: 30
public static final	ConcurrentResourceModificationException Value: 40
public static final	CycleDetectedException Value: 50
public static final	DatabaseTableSchemaAlreadyRegisteredException Value: 60
public static final	DatabaseTableSchemaException Value: 70
public static final	DeleteNotAvailableException Value: 80
public static final	DupFieldNameException Value: 90

public static final	DuplicateIDException Value: 100
public static final	DuplicateIndexNameException Value: 110
public static final	DuplicateResourceException Value: 120
public static final	FileContentTooLargeException Value: 130
public static final	FileContentTotalTooLargeException Value: 140
public static final	FileContentUnavailableException Value: 150
public static final	IncompatibleTableSchemaException Value: 170
public static final	InvalidCapacityException Value: 190
public static final	InvalidResourceException Value: 200
public static final	InvalidResourceIDException Value: 210
public static final	InvalidResourceNameException Value: 220
public static final	InvalidURIException Value: 230
public static final	ObjectNotFoundException Value: 240
public static final	PackageInstalledException Value: 250
public static final	RecoverableFileTransferException Value: 260

public static final	RedundantNameException Value: 270
public static final	ResourceCreationException Value: 280
public static final	ResourceNotFoundException Value: 290
public static final	UNKNOWN Value: -1
public static final	UnknownColumnException Value: 300
public static final	UnknownDatabaseTableSchemaAttributeFactoryException Value: 310
public static final	UnknownDatabaseTableSchemaException Value: 320
public static final	UnsupportedColumnTypeException Value: 330

Constructor Summary

public	ErrorCode()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

UNKNOWN

public static final int **UNKNOWN**

Constant value: **-1**

AccessDeniedException

public static final int **AccessDeniedException**

Constant value: 10

ActiveListGlobalCapacityExceededException

public static final int **ActiveListGlobalCapacityExceededException**

Constant value: 20

BrokerFactoryException

public static final int **BrokerFactoryException**

Constant value: 30

ConcurrentResourceModificationException

public static final int **ConcurrentResourceModificationException**

Constant value: 40

CycleDetectedException

public static final int **CycleDetectedException**

Constant value: 50

DatabaseTableSchemaAlreadyRegisteredException

public static final int **DatabaseTableSchemaAlreadyRegisteredException**

Constant value: 60

DatabaseTableSchemaException

public static final int **DatabaseTableSchemaException**

Constant value: 70

DeleteNotAvailableException

public static final int **DeleteNotAvailableException**

Constant value: 80

DupFieldNameException

public static final int **DupFieldNameException**

Constant value: **90**

DuplicateIDException

public static final int **DuplicateIDException**

Constant value: **100**

DuplicateIndexNameException

public static final int **DuplicateIndexNameException**

Constant value: **110**

DuplicateResourceException

public static final int **DuplicateResourceException**

Constant value: **120**

FileContentTooLargeException

public static final int **FileContentTooLargeException**

Constant value: **130**

FileContentTotalTooLargeException

public static final int **FileContentTotalTooLargeException**

Constant value: **140**

FileContentUnavailableException

public static final int **FileContentUnavailableException**

Constant value: **150**

IncompatibleTableSchemaException

public static final int **IncompatibleTableSchemaException**

Constant value: **170**

InvalidCapacityException

public static final int **InvalidCapacityException**

Constant value: **190**

InvalidResourceException

public static final int **InvalidResourceException**

Constant value: **200**

InvalidResourceIDException

public static final int **InvalidResourceIDException**

Constant value: **210**

InvalidResourceNameException

public static final int **InvalidResourceNameException**

Constant value: **220**

InvalidURIException

public static final int **InvalidURIException**

Constant value: **230**

ObjectNotFoundException

public static final int **ObjectNotFoundException**

Constant value: **240**

PackageInstalledException

public static final int **PackageInstalledException**

Constant value: **250**

RecoverableFileTransferException

public static final int **RecoverableFileTransferException**

Constant value: **260**

RedundantNameException

public static final int **RedundantNameException**

Constant value: **270**

ResourceCreationException

public static final int **ResourceCreationException**

Constant value: **280**

ResourceNotFoundException

public static final int **ResourceNotFoundException**

Constant value: **290**

UnknownColumnException

public static final int **UnknownColumnException**

Constant value: **300**

UnknownDatabaseTableSchemaAttributeFactoryException

public static final int **UnknownDatabaseTableSchemaAttributeFactoryException**

Constant value: **310**

UnknownDatabaseTableSchemaException

public static final int **UnknownDatabaseTableSchemaException**

Constant value: **320**

UnsupportedColumnTypeException

public static final int **UnsupportedColumnTypeException**

Constant value: **330**

Constructors

ErrorCode

public **ErrorCode**()

com.arcsight.product.manager.resource.service.v1.model

Class EventAction

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.EventAction

All Implemented Interfaces:
Serializable

public class **EventAction**
extends Object
implements Serializable

Describes the action specifying command and parameters. You would see such actions on the Filter edit panel in ArcSight Console.

JSON prototype

Constructor Summary	
public	EventAction()

Method Summary	
String	getActionCommand() Returns a constant from a list of the supported commands.
String	getActionParams() Get the parameter specified for the action.
void	setActionCommand(String actionCommand) Sets the action command.
void	setActionParams(String actionParams) Sets parameter string that will be used during command execution.

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

EventAction
public **EventAction()**

Methods

getActionCommand

```
public String getActionCommand()
```

Returns a constant from a list of the supported commands.

Returns:

the actionCommand

setActionCommand

```
public void setActionCommand(String actionCommand)
```

Sets the action command. Please note that ESM processes only supported commands.

Parameters:

actionCommand - the actionCommand to set

getActionParams

```
public String getActionParams()
```

Get the parameter specified for the action.

Returns:

the actionParams

setActionParams

```
public void setActionParams(String actionParams)
```

Sets parameter string that will be used during command execution. For example, that might be a substring for Startswith comparison.

Parameters:

actionParams - the actionParams to set

com.arcsight.product.manager.resource.service.v1.model

Class EventBasicCondition

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.EventBasicCondition

All Implemented Interfaces:
Serializable

```
public class EventBasicCondition
extends Object
implements Serializable
```

Describes a single filter basic condition.

JSON prototype

Constructor Summary

public	EventBasicCondition()

Method Summary

String	getName()
int	getObject()
int	getOperator()
int	getType()
String	getValue()
boolean	isIgnoreCase()
void	setIgnoreCase(boolean ignoreCase)
void	setName(String name)
void	setObject(int object)
void	setOperator(int operator)
void	setType(int type)

void	setValue (String value)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

EventBasicCondition

```
public EventBasicCondition()
```

Methods

getName

```
public String getName()
```

Returns:

the name

setName

```
public void setName(String name)
```

Parameters:

name - the name to set

getObject

```
public int getObject()
```

Returns:

the object

setObject

```
public void setObject(int object)
```

Parameters:

object - the object to set

getType

public int **getType**()

Returns:

the type

setType

public void **setType**(int type)

Parameters:

type - the type to set

getOperator

public int **getOperator**()

Returns:

the operator

setOperator

public void **setOperator**(int operator)

Parameters:

operator - the operator to set

isIgnoreCase

public boolean **isIgnoreCase**()

Returns:

the ignoreCase

setIgnoreCase

public void **setIgnoreCase**(boolean ignoreCase)

Parameters:

ignoreCase - the ignoreCase to set

getValue

```
public String getValue()
```

Returns:

the value

setValue

```
public void setValue(String value)
```

Parameters:

value - the value to set

com.arcsight.product.manager.resource.service.v1.model

Class EventCommonCondition

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.EventCommonCondition

All Implemented Interfaces:
Serializable

```
public class EventCommonCondition
extends Object
implements Serializable
```

Describes a single filter common condition.

JSON prototype

Constructor Summary

public	EventCommonCondition()

Method Summary

int	getCode()
void	setCode(int code) Sets supported Common condition filter code Please note that ESM will perform operations for supported codes only.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

EventCommonCondition

```
public EventCommonCondition()
```

Methods

getCode

```
public int getCode()
```

Returns:

Common condition filter code

setCode

```
public void setCode(int code)
```

Sets supported Common condition filter code Please note that ESM will perform operations for supported codes only.

Parameters:

code - the code to set

com.arcsight.product.manager.resource.service.v1.model

Class EventCondition

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.EventCondition

All Implemented Interfaces:
Serializable

public class **EventCondition**
extends Object
implements Serializable

Describes a complex filter condition.

JSON prototype

Constructor Summary

public	EventCondition()

Method Summary

List	getBasicConditions() Returns the collection of basic conditions included into this complex condition.
int	getConditionOperator() Returns the code or condition's operator.
String	getName()
void	setBasicConditions(List basicConditions) Sets the set of basic conditions that this complex condition comprises of.
void	setConditionOperator(int conditionOperator) Sets condition's operator.
void	setName(String name) Sets the name of the condition.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

EventCondition

```
public EventCondition()
```

Methods

getName

```
public String getName()
```

Returns:

the name

setName

```
public void setName(String name)
```

Sets the name of the condition.

Parameters:

name - the name to set

getConditionOperator

```
public int getConditionOperator()
```

Returns the code or condition's operator. For example 1 (CO_NEED_ALL), 2 (CO_NEED_ANY), 3 (CO_NEED_NOT).

Returns:

the conditionOperator

setConditionOperator

```
public void setConditionOperator(int conditionOperator)
```

Sets condition's operator. For example 1 (CO_NEED_ALL), 2 (CO_NEED_ANY), 3 (CO_NEED_NOT).

Parameters:

conditionOperator - the conditionOperator to set

getBasicConditions

```
public List getBasicConditions()
```

Returns the collection of basic conditions included into this complex condition.

Returns:

the basicConditions

setBasicConditions

public void **setBasicConditions**(List basicConditions)

Sets the set of basic conditions that this complex condition comprises of.

Parameters:

basicConditions - the basicConditions to set

com.arcsight.product.manager.resource.service.v1.model Class EventPreprocessor

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.EventPreprocessor

All Implemented Interfaces:
Serializable

```
public class EventPreprocessor
extends Object
implements Serializable
```

Describes an event filter.

JSON prototype

Constructor Summary

public	EventPreprocessor()

Method Summary

List	getActions()
List	getCommonConditions()
int	getConditionOperator()
List	getConditions()
String	getDesc()
String	getName()
boolean	isActive()
void	setActions() (List Actions)
void	setActive() (boolean Active)
void	setCommonConditions() (List CommonConditions)
void	setConditionOperator() (int ConditionOperator)

void	setConditions (List Conditions)
void	setDesc (String Desc)
void	setName (String Name)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

EventPreprocessor

```
public EventPreprocessor()
```

Methods

getName

```
public String getName()
```

Returns:

the Name

setName

```
public void setName(String Name)
```

Parameters:

Name - the Name to set

getDesc

```
public String getDesc()
```

Returns:

the Desc

setDesc

```
public void setDesc(String Desc)
```

Parameters:

Desc - the Desc to set

getConditionOperator

```
public int getConditionOperator()
```

Returns:

the ConditionOperator

setConditionOperator

```
public void setConditionOperator(int ConditionOperator)
```

Parameters:

ConditionOperator - the ConditionOperator to set

isActive

```
public boolean isActive()
```

Returns:

the Active

setActive

```
public void setActive(boolean Active)
```

Parameters:

Active - the Active to set

getConditions

```
public List getConditions()
```

Returns:

the Conditions

setConditions

public void **setConditions**(List Conditions)

Parameters:

Conditions - the Conditions to set

getCommonConditions

public List **getCommonConditions**()

Returns:

the CommonConditions

setCommonConditions

public void **setCommonConditions**(List CommonConditions)

Parameters:

CommonConditions - the CommonConditions to set

getActions

public List **getActions**()

Returns:

the Actions

setActions

public void **setActions**(List Actions)

Parameters:

Actions - the Actions to set

com.arcsight.product.manager.resource.service.v1.model

Class EventStatistics

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.EventStatistics

public class **EventStatistics**
extends Object

Constructor Summary

public	EventStatistics()

Method Summary

long	getCorrelationEvents()
long	getEndTime() return the specified end for the time range
long	getEvents()
long	getStartTime() return the specified start for the time range
void	setCorrelationEvents(long correlationEvents)
void	setEndTime(long endTime)
void	setEvents(long events)
void	setStartTime(long startTime)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

EventStatistics

public **EventStatistics()**

Methods

getCorrelationEvents

public long **getCorrelationEvents**()

Returns:

total correlated events for the specified range of time

setCorrelationEvents

public void **setCorrelationEvents**(long correlationEvents)

getEndTime

public long **getEndTime**()

return the specified end for the time range

Returns:

setEndTime

public void **setEndTime**(long endTime)

getEvents

public long **getEvents**()

Returns:

total events for the specified range of time

setEvents

public void **setEvents**(long events)

getStartTime

public long **getStartTime**()

return the specified start for the time range


Returns:

setStartTime

```
public void setStartTime(long startTime)
```


com.arcsight.product.manager.resource.service.v1.model Class FieldSet

java.lang.Object



All Implemented Interfaces:
Serializable, Serializable

Deprecated. NOT IMPLEMENTED

JSON prototype

public class **FieldSet**
extends [Resource](#)
implements Serializable, Serializable

Describes a set of Event fields. Field sets are helpful when you work with a subset of the fields, for example, as part of a request. For example, as part of request.

Constructor Summary

public	FieldSet() Deprecated.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setName](#), [setURI](#), [setVersionID](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

FieldSet

`public FieldSet()`

Deprecated.

com.arcsight.product.manager.resource.service.v1.model Class FieldType

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.FieldType

All Implemented Interfaces:
Serializable

public class **FieldType**
extends Object
implements Serializable

Describes an event field including its name, type and the corresponding Java type.

Nested Class Summary

class	FieldType.DataTypes FieldType.DataTypes

Constructor Summary

public	FieldType()

Method Summary

String	getJavaTypeName() Returns the Java type name for the field.
String	getName() Returns the name of the field.
String	getSubType() Returns the subtype
int	getType() Returns the type of the field.
void	setJavaTypeName(String javaTypeName) Sets the the Java type name for the field.
void	setName(String name) Sets the name of the field.
void	setSubType(String subType) Sets the subtype
void	setType(int type) Sets the type of the field.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

FieldType

```
public FieldType()
```

Methods

getType

```
public int getType()
```

Returns the type of the field.

Returns:

the type of the field. See the `TYPE_*` constants for the list of possible values.

setType

```
public void setType(int type)
```

Sets the type of the field.

Parameters:

`type` - the type of the field. See the `TYPE_*` constants for the list of possible values.

getName

```
public String getName()
```

Returns the name of the field.

Returns:

the name of the field.

setName

```
public void setName(String name)
```

Sets the name of the field.

Parameters:

`name` - the name of the field.

getSubType

```
public String getSubType()
```

Returns the subtype

Returns:

subType

setSubType

```
public void setSubType(String subType)
```

Sets the subtype

Parameters:

subType - the subtype to be set

getJavaTypeName

```
public String getJavaTypeName()
```

Returns the Java type name for the field.

Returns:

the type name. See the JAVA_TYPE_* constants for the list of possible values.

setJavaTypeName

```
public void setJavaTypeName(String javaTypeName)
```

Sets the the Java type name for the field.

Parameters:

javaTypeName - the type name. See the JAVA_TYPE_* constants for the list of possible values.

com.arcsight.product.manager.resource.service.v1.model

Class FieldType.DataTypes

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes

All Implemented Interfaces:

Serializable, Comparable

public static final class **FieldType.DataTypes**
extends Enum

Field Summary

public static final	TYPE_ADDRESS
public static final	TYPE_BITSET
public static final	TYPE_BLOB
public static final	TYPE_BOOLEAN
public static final	TYPE_BYTE
public static final	TYPE_CLASS
public static final	TYPE_CLOB
public static final	TYPE_COMPLEX
public static final	TYPE_DATE
public static final	TYPE_DATETIME
public static final	TYPE_DOUBLE
public static final	TYPE_ENUMERATION
public static final	TYPE_ID
public static final	TYPE_INTEGER

public static final	TYPE_IPADDRESS
public static final	TYPE_IPV6ADDRESS
public static final	TYPE_LIST
public static final	TYPE_LONG
public static final	TYPE_MACADDRESS
public static final	TYPE_RESOURCE_ID
public static final	TYPE_STRING
public static final	TYPE_SUBNET
public static final	TYPE_TIME
public static final	TYPE_UNION

Method Summary

FieldType.DataTypes static	forValue (int value)
int	getValue ()
FieldType.DataTypes static	valueOf (String name)
FieldType.DataTypes[] static	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

TYPE_STRING

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_STRING
```

TYPE_DATETIME

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_DATETIME
```

TYPE_ADDRESS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_ADDRESS
```

TYPE_RESOURCE_ID

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes  
TYPE_RESOURCE_ID
```

TYPE_INTEGER

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_INTEGER
```

TYPE_LONG

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_LONG
```

TYPE_DOUBLE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_DOUBLE
```

TYPE_ENUMERATION

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes  
TYPE_ENUMERATION
```

TYPE_CLASS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_CLASS
```

TYPE_LIST

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_LIST
```

TYPE_COMPLEX

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_COMPLEX
```

TYPE_BOOLEAN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_BOOLEAN
```

TYPE_DATE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_DATE
```

TYPE_TIME

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_TIME
```

TYPE_BYTE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_BYTE
```

TYPE_SUBNET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_SUBNET
```

TYPE_ID

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_ID
```

TYPE_BITSET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_BITSET
```

TYPE_UNION

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_UNION
```

TYPE_IPV6ADDRESS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes  
TYPE_IPV6ADDRESS
```

TYPE_BLOB

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_BLOB
```

TYPE_CLOB

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_CLOB
```

TYPE_IPADDRESS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes TYPE_IPADDRESS
```

TYPE_MACADDRESS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FieldType.DataTypes  
TYPE_MACADDRESS
```

Methods

values

```
public static FieldType.DataTypes\[\] values()
```

valueOf

```
public static FieldType.DataTypes valueOf(String name)
```

getValue

```
public int getValue()
```

forValue

```
public static FieldType.DataTypes forValue(int value)
```

com.arcsight.product.manager.resource.service.v1.model

Class FileResource

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ [com.arcsight.product.manager.resource.service.v1.model.FileResource](#)

All Implemented Interfaces:

Serializable

public class **FileResource**

extends [Resource](#)

This class represents a file resource.

Constructor Summary

public	FileResource()

Method Summary

long	getContentLength() Returns an approximate number of bytes in the file.
long	getExpirationDate() Returns the file expiration date.
String	getFileName() Returns the filename associated with this file resource.
String	getMimeEncoding() Returns the encoding from the MIME type of this file.
String	getMimePrimaryType() Returns the primary portion of the MIME type of this file.
String	getMimeSecondaryType() Returns the secondary portion of the MIME type of this file.
String	getMimeType() Returns the full MIME type for this resource.
Map	getMimeTypeAttributes() Returns the map of MIME attributes of this file.
int	getUploadSourceId() Returns the upload source of this file.

boolean	<u>isFileContentsAvaliable()</u> Returns true if there is a file content available for this file resource.
boolean	<u>isFileValidOnFileSystem()</u> Returns true if this is a valid file resource and it is stored on the file system.
boolean	<u>isStoredOnFileSystem()</u> Returns true if this resource is synchronized with a file on the Manager machine as well as stored in the database.
boolean	<u>isValid()</u> Returns true if this is a valid file resource.
void	<u>setContentLength()</u> (long contentLength) Sets an approximate number of bytes in the file.
void	<u>setExpirationDate()</u> (long expirationDate) Sets the file expiration date.
void	<u>setFileContentsAvaliable()</u> (boolean fileContentsAvaliable) Sets the flag indicating whether there is a file content available for this file resource.
void	<u>setFileName()</u> (String fileName) Sets the filename associated with this file resource.
void	<u>setFileValidOnFileSystem()</u> (boolean fileValidOnFileSystem)
void	<u>setMimeEncoding()</u> (String mimeType) Sets the encoding from the MIME type of this file; for instance, "UTF-8".
void	<u>setMimePrimaryType()</u> (String mimeType) Sets the primary portion of the MIME type of this file.
void	<u>setMimeSecondaryType()</u> (String mimeType) Sets the secondary portion of the MIME type of this file.
void	<u>setMimeType()</u> (String mimeType) Sets the full MIME type for this resource.
void	<u>setMimeTypeAttributes()</u> (Map mimeTypeAttributes) Sets the map of MIME attributes of this file.
void	<u>setStoredOnFileSystem()</u> (boolean storedOnFileSystem) Sets the flag indicating whether this resource is synchronized with a file on the Manager machine as well as stored in the database.
void	<u>setUploadSourceId()</u> (int uploadSourceId) Sets the upload source of this file.
void	<u>setValid()</u> (boolean valid)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

FileResource

```
public FileResource()
```

Methods

getContentLength

```
public long getContentLength()
```

Returns an approximate number of bytes in the file.

Returns:

the `getContentLength` the number of bytes in the file.

setContentLength

```
public void setContentLength(long contentLength)
```

Sets an approximate number of bytes in the file.

Parameters:

`contentLength` - the `setContentLength` to set

getExpirationDate

```
public long getExpirationDate()
```

Returns the file expiration date. If this value is not greater than 0, then it can be assumed that the file will not expire.

Returns:

the file expiration date.

See Also:

`System.currentTimeMillis()`

setExpirationDate

```
public void setExpirationDate(long expirationDate)
```

Sets the file expiration date. If this value is not greater than 0, then it can be assumed that the file will not expire.

Parameters:

`expirationDate` - the file expiration date.

See Also:

`System.currentTimeMillis()`

getFileName

```
public String getFileName()
```

Returns the filename associated with this file resource. This is used when the data for a file resource is being downloaded.

Returns:

the filename associated with this file resource.

setFileName

```
public void setFileName(String fileName)
```

Sets the filename associated with this file resource. This is used when the data for a file resource is being downloaded.

Parameters:

`fileName` - the filename associated with this file resource.

getMimeTypeAttributes

```
public Map getMimeTypeAttributes()
```

Returns the map of MIME attributes of this file.

For instance, for the MIME type `text/plain; charset="UTF-8"`, the map would contain `{"charset"="UTF-8"}`. For a MIME type that does not specify any attributes, this method will return `null`. For example, for the MIME type `application/x-zip-compressed`, `null` would be returned.

Returns:

the map of MIME attributes of this file or `null` if there are no such attributes.

setMimeTypeAttributes

```
public void setMimeTypeAttributes(Map mimeTypeAttributes)
```

Sets the map of MIME attributes of this file. See [getMimeTypeAttributes\(\)](#) for the map description.

Parameters:

`contentTypeAttributes` - the map of MIME attributes of this file or **null** if there are no such attributes.

getMimeTypeEncoding

```
public String getMimeTypeEncoding()
```

Returns the encoding from the MIME type of this file. For the MIME type `text/plain; charset="UTF-8"`, this would return `"UTF-8"`. For a MIME type that does not specify the encoding, this will return `null`. For the MIME type `application/x-zip-compressed`, this would return `null`.

Returns:

the MIME encoding of this file.

setMimeTypeEncoding

```
public void setMimeTypeEncoding(String mimeTypeEncoding)
```

Sets the encoding from the MIME type of this file; for instance, `"UTF-8"`.

Parameters:

`mimeTypeEncoding` - the MIME encoding of this file.

getMimeTypePrimaryType

```
public String getMimeTypePrimaryType()
```

Returns the primary portion of the MIME type of this file.

The MIME type is formatted as: `<Primary Type>/<Secondary Type>[<attribute name>=<attribute value>]*`

Returns:

the primary portion of the MIME type of this file.

setMimeTypePrimaryType

```
public void setMimeTypePrimaryType(String mimeTypePrimaryType)
```

Sets the primary portion of the MIME type of this file. For the the MIME type format description see [getMimeTypePrimaryType\(\)](#).

Parameters:

`mimeTypePrimaryType` - the primary portion of the MIME type of this file.

getMimeTypeSecondaryType

```
public String getMimeTypeSecondaryType()
```

Returns the secondary portion of the MIME type of this file.

The MIME type is formatted as: `<Primary Type>/<Secondary Type>[<attribute name>=<attribute value>]*`

Returns:

the secondary portion of the MIME type of this file.

setMimeTypeSecondaryType

```
public void setMimeTypeSecondaryType(String mimeTypeSecondaryType)
```

Sets the secondary portion of the MIME type of this file. For the the MIME type format description see [getMimeTypeSecondaryType\(\)](#).

Parameters:

mimeTypeSecondaryType - the secondary portion of the MIME type of this file.

getMimeType

```
public String getMimeType()
```

Returns the full MIME type for this resource. For the details of the MIME format, see [getMimeTypePrimaryType\(\)](#) and [getMimeTypeSecondaryType\(\)](#).

Returns:

the full MIME type for this resource.

setMimeType

```
public void setMimeType(String mimeType)
```

Sets the full MIME type for this resource. For the details of the MIME format, see [getMimeTypePrimaryType\(\)](#) and [getMimeTypeSecondaryType\(\)](#).

Parameters:

mimeType - the full MIME type for this resource.

getUploadSourceId

```
public int getUploadSourceId()
```

Returns the upload source of this file. This must be one of UPLOAD_SOURCE_ID_NONE, UPLOAD_SOURCE_ID_CONSOLE, UPLOAD_SOURCE_ID_WEB or UPLOAD_SOURCE_ID_MANAGER_GENERATED.

Returns:

the upload source of this file.

setUploadSourceId

```
public void setUploadSourceId(int uploadSourceId)
```

Sets the upload source of this file. This must be one of UPLOAD_SOURCE_ID_NONE, UPLOAD_SOURCE_ID_CONSOLE, UPLOAD_SOURCE_ID_WEB or UPLOAD_SOURCE_ID_MANAGER_GENERATED.

Parameters:

uploadSourceId - the upload source of this file.

isFileContentsAvailable

```
public boolean isFileContentsAvailable()
```

Returns true if there is a file content available for this file resource.

Returns:

true if there is a file content available for this file resource.

setFileContentsAvaliable

```
public void setFileContentsAvaliable(boolean fileContentsAvaliable)
```

Sets the flag indicating whether there is a file content available for this file resource.

Parameters:

fileContentsAvaliable - true if there is a file content available for this file resource.

isStoredOnFileSystem

```
public boolean isStoredOnFileSystem()
```

Returns true if this resource is synchronized with a file on the Manager machine as well as stored in the database.

Returns:

true if this resource is synchronized with a file on the Manager machine.

setStoredOnFileSystem

```
public void setStoredOnFileSystem(boolean storedOnFileSystem)
```

Sets the flag indicating whether this resource is synchronized with a file on the Manager machine as well as stored in the database.

Parameters:

storedOnFileSystem - true if this resource is synchronized with a file on the Manager machine.

isFileValidOnFileSystem

```
public boolean isFileValidOnFileSystem()
```

Returns true if this is a valid file resource and it is stored on the file system.

Returns:

true if this is a valid file resource and it is stored on the file system.

setFileValidOnFileSystem

```
public void setFileValidOnFileSystem(boolean fileValidOnFileSystem)
```

isValid

```
public boolean isValid()
```

Returns true if this is a valid file resource.

Returns:

true if this is a valid file resource.

setValid

public void **setValid**(boolean valid)

com.arcsight.product.manager.resource.service.v1.model Class FileUploadStatus

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.FileUploadStatus

All Implemented Interfaces:
Serializable

```
public class FileUploadStatus
extends Object
implements Serializable
```

The file upload status which provides the success/failure status and the failure error message.

JSON prototype

Nested Class Summary

class	FileUploadStatus.FileStatus FileUploadStatus.FileStatus

Constructor Summary

public	FileUploadStatus ()
public	FileUploadStatus (FileUploadStatus.FileStatus status, String errorMsg)

Method Summary

String	getErrorMsg ()
FileUploadStatus.FileStatus	getStatus ()
void	setErrorMsg (String errorMsg)
void	setStatus (FileUploadStatus.FileStatus status)
String	toString ()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

FileUploadStatus

```
public FileUploadStatus()
```

FileUploadStatus

```
public FileUploadStatus(FileUploadStatus.FileStatus status,  
                        String errorMsg)
```

Methods

getStatus

```
public FileUploadStatus.FileStatus getStatus()
```

setStatus

```
public void setStatus(FileUploadStatus.FileStatus status)
```

getErrorMsg

```
public String getErrorMsg()
```

setErrorMsg

```
public void setErrorMsg(String errorMsg)
```

toString

```
public String toString()
```

com.arcsight.product.manager.resource.service.v1.model

Class FileUploadStatus.FileStatus



All Implemented Interfaces:
Serializable, Comparable

public static final class **FileUploadStatus.FileStatus**
extends Enum

Field Summary	
public static final	UPLOAD_FAILURE
public static final	UPLOAD_SUCCESS
public static final	UPLOAD_UNKNOWN

Method Summary	
static FileUploadStatus.FileStatus	valueOf (String name)
static FileUploadStatus.FileStatus[]	values ()

Methods inherited from class java.lang.Enum
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable
compareTo

Fields

UPLOAD_SUCCESS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FileUploadStatus.FileStatus  
UPLOAD_SUCCESS
```

UPLOAD_FAILURE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FileUploadStatus.FileStatus  
UPLOAD_FAILURE
```

UPLOAD_UNKNOWN

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.FileUploadStatus.FileStatus  
UPLOAD_UNKNOWN
```

Methods

values

```
public static FileUploadStatus.FileStatus\[\] values()
```

valueOf

```
public static FileUploadStatus.FileStatus valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class GenericServerConfig

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Config](#)

└ [com.arcsight.product.manager.resource.service.v1.model.GenericServerConfig](#)

All Implemented Interfaces:

Serializable, Serializable

public class **GenericServerConfig**
extends [Config](#)
implements Serializable, Serializable

Constructor Summary

public	GenericServerConfig()

Method Summary

String	getDescription()
String	getIp()
String	getPassword()
String	getPort()
String	getServerLocation()
String	getUsername() Deprecated. Please use #getUserName() instead.
String	getUserName()
void	setDescription() (String description)
void	setIp() (String serverIp)
void	setPassword() (String password)
void	setPort() (String port)

void	setServerLocation (String serverLocation)
void	setUsername (String userName) Deprecated. <i>Please use #setUserName(String) instead.</i>
void	setUserName (String userName)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

GenericServerConfig

public **GenericServerConfig**()

Methods

getIp

public String **getIp**()

getDescription

public String **getDescription**()

setDescription

public void **setDescription**(String description)

getPort

public String **getPort**()

setPort

public void **setPort**(String port)

setIp

public void **setIp**(String serverIp)

getUserName

public String **getUserName**()

setUserName

public void **setUserName**(String userName)

getPassword

public String **getPassword**()

setPassword

public void **setPassword**(String password)

getServerLocation

public String **getServerLocation**()

setServerLocation

public void **setServerLocation**(String serverLocation)

getUsername

public String **getUsername**()

Deprecated. *Please use #getUserName() instead.*

DEPRECATED. This method will be removed in the next API version.

setUsername


public void **setUsername**(String userName)

Deprecated. *Please use #setUserName(String) instead.*

DEPRECATED. This method will be removed in the next API version.

com.arcsight.product.manager.resource.service.v1.model Class Group

java.lang.Object



All Implemented Interfaces:
Serializable

public class **Group**
extends [Resource](#)

This class represents a Group resource.

Constructor Summary

public	Group() constructor

Method Summary

int[]	getAttributeIDs() Returns an array of all attribute IDs for this group.
int	getContainedResourceType() Gets an integer indicating the type of this resource contained by this group.
String	getDescriptiveString() Gets the description of this group.
String	getDisplayName() Sets the name to display for this group.
String	getMemberReferencePage() Returns the member reference page of this group.
int	getSubGroupCount() Gets the number of the sub groups for this group.
int	getType() Gets the type of this group.
String	getTypeName() Gets the resource type name of this group.
boolean	hasSubGroup() Returns the result whether this group has sub group.

boolean	<u>isVirtual()</u> Returns whether or not this is a virtual group.
void	<u>setAttributeIDs(int[] attributeIDs)</u> Sets an array of all attribute IDs for this group.
void	<u>setContainedResourceType(int containedResourceType)</u> Sets the integer indicating the type of this resource contained by this group.
void	<u>setDescriptionString(String str)</u> Sets the description for this group.
void	<u>setDisplayDisplayName(String name)</u> Sets the name or alias to display for this group.
void	<u>setMemberReferencePage(String page)</u> Sets the member reference page of this group.
void	<u>setSubGroupCount(int subGroupCount)</u> Sets the number of the sub groups for this group.
void	<u>setType(int type)</u> Set the type of this group.
void	<u>setTypeNames(String typeName)</u> Sets the resource type name for this group.
void	<u>setVirtual(boolean isVirtual)</u> Sets this group as a virtual one or not.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setTypeNames](#), [setURI](#), [setVersionID](#)

Methods inherited from class [java.lang.Object](#)

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

Group

```
public Group()
```

constructor

Methods

getType

```
public int getType()
```

Gets the type of this group.

Returns:

The type of this group.

setType

```
public void setType(int type)
```

Set the type of this group.

Parameters:

type - The type of this group

getContainedResourceType

```
public int getContainedResourceType()
```

Gets an integer indicating the type of this resource contained by this group. Sees [@link{com.arcsight.product.manager.resource.service.v1.model.ResourceTypes}](#).

Returns:

An integer indicating the type of this resource contained.

setContainedResourceType

```
public void setContainedResourceType(int containedResourceType)
```

Sets the integer indicating the type of this resource contained by this group. Sees [@link{com.arcsight.product.manager.resource.service.v1.model.ResourceTypes}](#).

Parameters:

An - integer indicating the type of this resource contained.

getTypeName

```
public String getTypeName()
```

Gets the resource type name of this group.

Returns:

The resource type name of this group

setName

public void **setName**(String typeName)

Sets the resource type name for this group.

Parameters:

typeName - The resource type name for this group.

getDisplayname

public String **getDisplayname**()

Sets the name to display for this group. If there is an alias, then that will be returned; otherwise, the name is returned. This is also what is used by the toString() method.

Returns:

The name to display for this group.

setDisplayname

public void **setDisplayname**(String name)

Sets the name or alias to display for this group.

Parameters:

name - The name to display for this group.

getMemberReferencePage

public String **getMemberReferencePage**()

Returns the member reference page of this group.

Returns:

The member reference page of this group.

setMemberReferencePage

public void **setMemberReferencePage**(String page)

Sets the member reference page of this group.

Parameters:

The - member reference page of this group.

getDescriptionString

public String **getDescriptionString**()

Gets the description of this group.

Returns:

The description of this group.

setDescriptionString

```
public void setDescriptionString(String str)
```

Sets the description for this group.

Parameters:

str - The description for this group.

getAttributeIDs

```
public int[] getAttributeIDs()
```

Returns an array of all attribute IDs for this group.

Returns:

An array of all attribute IDs for this group.

setAttributeIDs

```
public void setAttributeIDs(int[] attributeIDs)
```

Sets an array of all attribute IDs for this group.

Returns:

An array of all attribute IDs for this group.

getSubGroupCount

```
public int getSubGroupCount()
```

Gets the number of the sub groups for this group.

Returns:

The number of the sub group for this group.

setSubGroupCount

```
public void setSubGroupCount(int subGroupCount)
```

Sets the number of the sub groups for this group.

Parameters:

subGroupCount - The number of the sub groups for this group.

hasSubGroup

```
public boolean hasSubGroup()
```

Returns the result whether this group has sub group.

Returns:

True if this group has any sub group; otherwise, false.

isVirtual

public boolean **isVirtual**()

Returns whether or not this is a virtual group. A virtual group is a resource that does not have a representation in the persistent store.

Returns:

Whether or not this is a virtual group.

setVirtual

public void **setVirtual**(boolean isVirtual)

Sets this group as a virtual one or not.

Parameters:

`isVirtual` - Whether this group is a virtual group.

com.arcsight.product.manager.resource.service.v1.model Class Module

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.Module

All Implemented Interfaces:
Serializable

public class **Module**
extends Object
implements Serializable

The Module is the object which contents the information data for the user preference.

Constructor Summary

public	Module()

Method Summary

String	getDescription() Gets the description of this module.
String	getGwtModuleClassName() Gets the GWT module class name.
String	getIconUrl() Gets icon URL of this module.
String	getId() Gets the ID of this module in a user preference.
String	getName() Gets the name of this module in a user preference.
String	getType() Gets the type of this module.
String	getUrl() Gets the URL of this module.
boolean	isGwtModule() Return true if this is GWT module.
void	setDescription(String description) Sets the description for this module.

void	<code>setGwtModule</code> (boolean gwtModule) Sets whether this is GWT module.
void	<code>setGwtModuleClassName</code> (String gwtModuleClassName) Sets the GWT module class name for this module.
void	<code>setIconUrl</code> (String iconUrl) Sets the icon URL of this module.
void	<code>setId</code> (String id) Sets the ID of this module in a user preference.
void	<code>setName</code> (String name) Sets the name of this module in a user preference.
void	<code>setType</code> (String type) Sets the type for this module.
void	<code>setUrl</code> (String url) Sets the URL for this module.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

Module

```
public Module()
```

Methods

setId

```
public void setId(String id)
```

Sets the ID of this module in a user preference.

Parameters:

`id` - The id to set.

getId

```
public String getId()
```

Gets the ID of this module in a user preference.

Returns:

the id of this module in a user preference.

setName

public void **setName**(String name)

Sets the name of this module in a user preference.

Parameters:

name - The name to set.

getName

public String **getName**()

Gets the name of this module in a user preference.

Returns:

The name of this module in a user preference.

getType

public String **getType**()

Gets the type of this module.

Returns:

The type of this module.

setType

public void **setType**(String type)

Sets the type for this module.

Parameters:

type - The type to set for this module.

isGwtModule

public boolean **isGwtModule**()

Return true if this is GWT module.

Returns:

True if this is GWT module.

setGwtModule

public void **setGwtModule**(boolean gwtModule)

Sets whether this is GWT module.

Parameters:

gwtModule - If true, this is GWT module.

getUrl

public String **getUrl**()

Gets the URL of this module.

Returns:

The URL of this module.

setUrl

public void **setUrl**(String url)

Sets the URL for this module.

Parameters:

url - The URL of this module to set.

getGwtModuleClassName

public String **getGwtModuleClassName**()

Gets the GWT module class name.

Returns:

The name of GWT module.

setGwtModuleClassName

public void **setGwtModuleClassName**(String gwtModuleClassName)

Sets the GWT module class name for this module.

Parameters:

gwtModuleClassName - The GWT module class name to set for this module.

getDescription

public String **getDescription**()

Gets the description of this module.

Returns:

The description of this module.

setDescription

public void **setDescription**(String description)

Sets the description for this module.

Parameters:

description - The description of this module to set.

getIconUrl

```
public String getIconUrl()
```

Gets icon URL of this module.

Returns:

The icon URL of this module.

setIconUrl

```
public void setIconUrl(String iconUrl)
```

Sets the icon URL of this module.


Parameters:

iconUrl - The icon URL of this module to set.

com.arcsight.product.manager.resource.service.v1.model

Class Network

java.lang.Object



All Implemented Interfaces:
Serializable

public class **Network**
extends [Resource](#)

Describes a network Resource.

JSON prototype

Constructor Summary

public	Network ()

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setTypeNames](#), [setURI](#), [setVersionID](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

Network

public **Network**()

com.arcsight.product.manager.resource.service.v1.model

Class OpenCases

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.OpenCases

public class **OpenCases**
extends Object

Constructor Summary

public	OpenCases()

Method Summary

List	getAssignedCases()
String	getUserId()
void	setAssignedCases (List assignedCases)
void	setUserId (String userId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

OpenCases

public **OpenCases**()

Methods

getAssignedCases

public List **getAssignedCases**()

setAssignedCases

```
public void setAssignedCases(List assignedCases)
```

getUserId

```
public String getUserId()
```

setUserId

```
public void setUserId(String userId)
```

com.arcsight.product.manager.resource.service.v1.model Class ParameterDescriptor

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor

All Implemented Interfaces:
Serializable

public class **ParameterDescriptor**
extends Object
implements Serializable

Describes a parameter that could be used in various operations.

JSON prototype

Nested Class Summary

class	ParameterDescriptor.ContentTypes ParameterDescriptor.ContentTypes

Constructor Summary

public	ParameterDescriptor()

Method Summary

String	getContentOptions()
int	getContentType()
String	getDefaultValue()
String	getDescription()
String[]	getDisplayValues()
String	getName()
String[]	getPossibleValues()
char[]	getPrivateValue()

String	getPrompt()
String	getValue()
boolean	isInternal()
boolean	isPrivate()
boolean	isRequired()
void	setContentOptions (String contentOptions)
void	setContentType (int contentType)
void	setDefaultValue (String defaultValue)
void	setDescription (String description)
void	setDisplayValues (String[] displayValues)
void	setInternal (boolean internal)
void	setName (String name)
void	setPossibleValues (String[] possibleValues)
void	setPrivate (boolean isPrivate)
void	setPrivateValue (char[] privateValue)
void	setPrompt (String prompt)
void	setRequired (boolean required)
void	setValue (String value)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ParameterDescriptor

```
public ParameterDescriptor()
```

Methods

getName

```
public String getName()
```

Returns:

the name

setName

```
public void setName(String name)
```

Parameters:

name - the name to set

getDefaultValue

```
public String getDefaultValue()
```

Returns:

the defaultValue

setDefaultValue

```
public void setDefaultValue(String defaultValue)
```

Parameters:

defaultValue - the defaultValue to set

getPossibleValues

```
public String[] getPossibleValues()
```

Returns:

the possibleValues

setPossibleValues

```
public void setPossibleValues(String[] possibleValues)
```

Parameters:

possibleValues - the possibleValues to set

getDisplayValues

```
public String[] getDisplayValues()
```

Returns:

the displayValues

setDisplayValues

```
public void setDisplayValues(String[] displayValues)
```

Parameters:

displayValues - the displayValues to set

getDescription

```
public String getDescription()
```

Returns:

the description

setDescription

```
public void setDescription(String description)
```

Parameters:

description - the description to set

getPrompt

```
public String getPrompt()
```

Returns:

the prompt

setPrompt

public void **setPrompt**(String prompt)

Parameters:

prompt - the prompt to set

isPrivate

public boolean **isPrivate**()

Returns:

the isPrivate

setPrivate

public void **setPrivate**(boolean isPrivate)

Parameters:

isPrivate - the isPrivate to set

isRequired

public boolean **isRequired**()

Returns:

the required

setRequired

public void **setRequired**(boolean required)

Parameters:

required - the required to set

isInternal

public boolean **isInternal**()

Returns:

the internal

setInternal

public void **setInternal**(boolean internal)

Parameters:

internal - the internal to set

getValue

public String **getValue**()

Returns:

the value

setValue

public void **setValue**(String value)

Parameters:

value - the value to set

getPrivateValue

public char[] **getPrivateValue**()

Returns:

the privateValue

setPrivateValue

public void **setPrivateValue**(char[] privateValue)

Parameters:

privateValue - the privateValue to set

getContentType

public int **getContentType**()

Returns:

the contentType

setContentType

public void **setContentType**(int contentType)

Parameters:

contentType - the contentType to set

getContentOptions

public String **getContentOptions**()

Returns:

the contentOptions

setContentOptions

public void **setContentOptions**(String contentOptions)

Parameters:

contentOptions - the contentOptions to set

com.arcsight.product.manager.resource.service.v1.model Class ParameterDescriptor.ContentTypes

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes

All Implemented Interfaces:

Serializable, Comparable

public static class **ParameterDescriptor.ContentTypes**
extends Enum

Field Summary

public static final	AGENT_VERSIONS
public static final	CSV_EVENT_FIELD_SET
public static final	CSV_TABLE
public static final	DATETIME
public static final	DIRECTORY
public static final	DOUBLE
public static final	FILE
public static final	INTEGER
public static final	IPADDRESS
public static final	LONG
public static final	MACADDRESS
public static final	RESOURCE
public static final	TABLE
public static final	TEXT

Method Summary

ParameterDescriptor.ContentType	getEnum (int value)
static ParameterDescriptor.ContentType	valueOf (String name)
static ParameterDescriptor.ContentType[]	values ()

Methods inherited from class `java.lang.Enum`

`compareTo`, `equals`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

TEXT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentType  
TEXT
```

DIRECTORY

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentType  
DIRECTORY
```

FILE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentType  
FILE
```

INTEGER

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
INTEGER

TABLE

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
TABLE

LONG

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
LONG

IPADDRESS

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
IPADDRESS

MACADDRESS

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
MACADDRESS

CSV_TABLE

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
CSV_TABLE

CSV_EVENT_FIELD_SET

public static final
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes
CSV_EVENT_FIELD_SET

RESOURCE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes  
RESOURCE
```

DATETIME

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes  
DATETIME
```

AGENT_VERSIONS

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes  
AGENT_VERSIONS
```

DOUBLE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.ParameterDescriptor.ContentTypes  
DOUBLE
```

Methods

values

```
public static ParameterDescriptor.ContentTypes\[\] values()
```

valueOf

```
public static ParameterDescriptor.ContentTypes valueOf(String name)
```

getEnum

```
public ParameterDescriptor.ContentTypes getEnum(int value)
```

com.arcsight.product.manager.resource.service.v1.model

Class Query

java.lang.Object
└─ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)
 └─ [com.arcsight.product.manager.resource.service.v1.model.Query](#)

All Implemented Interfaces:
Serializable, Serializable

public class **Query**
extends [Resource](#)
implements Serializable, Serializable

Interface representing a query resource, identified by ID.

JSON prototype

Constructor Summary

public	Query()

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

Query

`public Query()`

com.arcsight.product.manager.resource.service.v1.model Class ReferencePage

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ReferencePage

All Implemented Interfaces:
Serializable

public class **ReferencePage**
extends Object
implements Serializable

This class represents a reference page describing a resource.

Constructor Summary

public	ReferencePage() Creates a instance of the reference page.
public	ReferencePage(String referencePage, String resourceURI) Creates a instance of the reference page for the resource identified by its URI.

Method Summary

String	getReferencePage() Returns the description.
String	getResourceURI() Returns the URI of the described resource.
void	setReferencePage(String referencePage) Sets the description.
void	setResourceURI(String resourceURI) Sets the URI of the described resource.
String	toString() Returns a string representation of the reference page.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReferencePage

```
public ReferencePage()
```

Creates a instance of the reference page.

ReferencePage

```
public ReferencePage(String referencePage,  
                     String resourceURI)
```

Creates a instance of the reference page for the resource identified by its URI.

Parameters:

referencePage - the description of the resource.

resourceURI - the URI of the resource this reference page describes.

Methods

getReferencePage

```
public String getReferencePage()
```

Returns the description.

Returns:

the text of the description.

setReferencePage

```
public void setReferencePage(String referencePage)
```

Sets the description.

Parameters:

referencePage - the text of the description.

getResourceURI

```
public String getResourceURI()
```

Returns the URI of the described resource.

Returns:

the URI of the described resource.

setResourceURI

```
public void setResourceURI(String resourceURI)
```

Sets the URI of the described resource.

Parameters:

resourceURI - the URI of the described resource.

toString

```
public String toString()
```

Returns a string representation of the reference page.

Returns:

a string representation of the reference page.

com.arcsight.product.manager.resource.service.v1.model

Class RelationshipTypes

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.RelationshipTypes

All Implemented Interfaces:
Serializable

public class **RelationshipTypes**
extends Object
implements Serializable

Field Summary

public static final	COLUMN_SET_OF Links a dyna channel with the named column set Value: 33
public static final	CREATED_BY The user that created a resource. Value: 11
public static final	DEPENDS_ON Links one resource to another, dependent might become invalid once the resource it depends on is deleted. Value: 17
public static final	DEPENDS_ON_USER Resource depends on user Value: 52
public static final	DESTINATION_OF Links a destination to a user or a group Value: 37
public static final	DRILLS_DOWN_TO Drills down to Drilldown to a resource Value: 61
public static final	HAS_ALTERNATE_INTERFACE Links an asset to another asset(really an interface). Value: 21
public static final	HAS_ARTICLE Identifies that this group (knowledge base folder) has a knowledge base article. Value: 6

public static final	<u>HAS_CASE_ATTACHMENT</u> Case attachments. Value: 45
public static final	<u>HAS_COMMAND</u> Configuration has a Command Value: 53
public static final	<u>HAS_CUSTOMER</u> Links a resource with a customer Value: 36
public static final	<u>HAS_DISCOVERY_CONFIGURATION</u> Value: 23
public static final	<u>HAS_DRILLDOWN</u> Drilldown List has one (or more) Drilldown(s) Value: 60
public static final	<u>HAS_DRILLDOWN_LIST</u> Resource (e.g.: DM or QV) has a Drilldown List Value: 59
public static final	<u>HAS_LOCATION</u> Links an asset/asset-range/zone/network with a location Value: 34
public static final	<u>HAS_NOTIFICATION_GROUP</u> The notification group associated with a resource. Value: 14
public static final	<u>HAS_OPTIONAL_PACKAGE</u> A package has a dependent package. Value: 47
public static final	<u>HAS_PACKAGE_ARCHIVE</u> Package content archive file. Value: 51
public static final	<u>HAS_PACKAGE_ATTACHMENT</u> Package content archive file. Value: 50
public static final	<u>HAS_PACKAGE_CONTENT</u> Package content archive file. Value: 48
public static final	<u>HAS_PACKAGE_TRANSLATION</u> Package content archive file. Value: 49

public static final	<u>HAS_PARENT_FIELDSET</u> Field (or FieldSet) has a parent FieldSet Value: 58
public static final	<u>HAS_QUERYVIEWER_ATTACHMENT</u> Query Viewer has a baseline / attachment Value: 55
public static final	<u>HAS_REQUIRED_PACKAGE</u> A package has a dependent package. Value: 46
public static final	<u>HAS_SCANNER_REPORT</u> Links a scanned report to an asset. Value: 30
public static final	<u>HAS_SCHEDULED_TASK</u> Relates resource to associated scheduled task Value: 9
public static final	<u>HAS_SORTABLE_FIELDSET</u> Links a user group to a sortable field set Value: 39
public static final	<u>HAS_START_VIEW</u> Links the dashaobard, dynachannel and user groups. Value: 29
public static final	<u>HAS_TARGET</u> Configuration has a Target Value: 54
public static final	<u>HAS_USER</u> Agent has a user Value: 57
public static final	<u>HAS_VULNERABILITY</u> The vulnerability associated with a device. Value: 15
public static final	<u>IN_CATEGORY</u> Links an asset/address-range/zone to a asset-category. Value: 20
public static final	<u>IN_NETWORK</u> Links a zone/zone-group/network with a network Value: 35
public static final	<u>IN_ZONE</u> Links an asset/address range to the zone where they belong. Value: 19

public static final	<u>INCLUDES_IN_USE_CASE</u> Use case refer to a resource Value: 56
public static final	<u>IS_ACCOUNT_MANAGER_OF</u> Links a user to a customer as an account manager. Value: 28
public static final	<u>IS_ASSET_OF</u> Links an asset to the agent for representing the machine on which the agent is running. Value: 22
public static final	<u>IS_EMPLOYEE_OF</u> Links a user to a customer as an employee. Value: 27
public static final	<u>IS_ENFORCED_ZONE</u> Identifies that this user or user group must always apply this Zone to every alert view. Value: 7
public static final	<u>IS_MARK_SIMILAR_STAGE_OF</u> Links a disposition to another to model similar dispositions. Value: 26
public static final	<u>IS_NOTE_OF</u> Identifies the IS_NOTE_OF relationship. Value: 5
public static final	<u>IS_PARENT_OF</u> Identifies the IS_PARENT_OF relationship. Value: 4
public static final	<u>IS_PERMISSION_INHERITANCE_RELATIONSHIP</u> This tells whether the relationship type is SYMMETRIC or not.
public static final	<u>IS_SAVED_REPORT_PARAMETER_REPORT_OF</u> Links a saved report parameter report with a report Value: 38
public static final	<u>IS_SUBSEQUENT_STAGE_OF</u> Links a disposition to another to model a workflow. Value: 25
public static final	<u>LOCKED_BY</u> Links the user resource to the resource which is locked by it. Value: 18
public static final	<u>MAX</u> The max for relationship ints. Value: 62

public static final	MODIFIED_BY The most recent user that modified a resource. Value: 12
public static final	OWNED_BY The user or group of users that own a resource. Value: 13
public static final	PERMISSION_INHERITANCE_RELATIONSHIPS Symmetric relationships comprising of: #IS_PARENT_OF, #HAS_CASE_ATTACHMENT, #HAS_REQUIRED_PACKAGE, #HAS_OPTIONAL_PACKAGE, #HAS_PACKAGE_CONTENT, #HAS_PACKAGE_TRANSLATION, #HAS_PACKAGE_ATTACHMENT, #HAS_PACKAGE_ARCHIVE, #HAS_QUERYVIEWER_ATTACHMENT, #HAS_DRILLDOWN_LIST, #HAS_DRILLDOWN, #DRILLS_DOWN_TO
public static final	READ_PERMISSION Identifies the READ_PERMISSION relationship. Value: 1
public static final	RELATIONSHIP_LABELS The relationship names.
public static final	RELATIONSHIP_NAMES The relationship names.
public static final	REVERSE_RELATIONSHIP_LABELS The reverse relationship names.
public static final	REVERSE_RELATIONSHIP_NAMES The relationship names.
public static final	SCAN_DETECTED Links a scanned report to Vulnerability/Open port (Asset Category). Value: 31
public static final	SCAN_REPORTED_BY Links a scanned report to an agent. Value: 32
public static final	UNKNOWN Identifies an unknown relationship. Value: 0
public static final	USER_HOTLIST_ZONE Links a user to his/her hotlist Value: 8
public static final	USER_MARKED_ZONE Links a user to his marked zone. Value: 16
public static final	USES_RULE_FOR_REPLAY Relates a user to rules used for replay Value: 10

public static final	WAS_DISCOVERED_IN_RUN Value: 24
public static final	WRITE_PERMISSION Identifies the WRITE_PERMISSION relationship. Value: 2
public static final	X_PERMISSION Identifies the X_PERMISSION relationship. Value: 3

Constructor Summary

public	RelationshipTypes()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

UNKNOWN

public static final int **UNKNOWN**

Identifies an unknown relationship.
Constant value: **0**

READ_PERMISSION

public static final int **READ_PERMISSION**

Identifies the READ_PERMISSION relationship.
Constant value: **1**

WRITE_PERMISSION

public static final int **WRITE_PERMISSION**

Identifies the WRITE_PERMISSION relationship.
Constant value: **2**

X_PERMISSION

public static final int **X_PERMISSION**

Identifies the X_PERMISSION relationship.
Constant value: **3**

IS_PARENT_OF

public static final int **IS_PARENT_OF**

Identifies the IS_PARENT_OF relationship.
Constant value: 4

IS_NOTE_OF

public static final int **IS_NOTE_OF**

Identifies the IS_NOTE_OF relationship.
Constant value: 5

HAS_ARTICLE

public static final int **HAS_ARTICLE**

Identifies that this group (knowledge base folder) has a knowledge base article.
Constant value: 6

IS_ENFORCED_ZONE

public static final int **IS_ENFORCED_ZONE**

Identifies that this user or user group must always apply this Zone to every alert view.
Constant value: 7

USER_HOTLIST_ZONE

public static final int **USER_HOTLIST_ZONE**

Links a user to his/her hotlist
Constant value: 8

HAS_SCHEDULED_TASK

public static final int **HAS_SCHEDULED_TASK**

Relates resource to associated scheduled task
Constant value: 9

USES_RULE_FOR_REPLAY

public static final int **USES_RULE_FOR_REPLAY**

Relates a user to rules used for replay
Constant value: 10

CREATED_BY

public static final int **CREATED_BY**

The user that created a resource.
Constant value: 11

MODIFIED_BY

public static final int **MODIFIED_BY**

The most recent user that modified a resource.
Constant value: **12**

OWNED_BY

public static final int **OWNED_BY**

The user or group of users that own a resource.
Constant value: **13**

HAS_NOTIFICATION_GROUP

public static final int **HAS_NOTIFICATION_GROUP**

The notification group associated with a resource.
Constant value: **14**

HAS_VULNERABILITY

public static final int **HAS_VULNERABILITY**

The vulnerability associated with a device.
Constant value: **15**

USER_MARKED_ZONE

public static final int **USER_MARKED_ZONE**

Links a user to his marked zone.
Constant value: **16**

DEPENDS_ON

public static final int **DEPENDS_ON**

Links one resource to another, dependent might become invalid once the resource it depends on is deleted.
Constant value: **17**

LOCKED_BY

public static final int **LOCKED_BY**

Links the user resource to the resource which is locked by it.
Constant value: **18**

IN_ZONE

public static final int **IN_ZONE**

Links an asset/address range to the zone where they belong.

Constant value: 19

IN_CATEGORY

public static final int **IN_CATEGORY**

Links an asset/address-range/zone to a asset-category.
Constant value: 20

HAS_ALTERNATE_INTERFACE

public static final int **HAS_ALTERNATE_INTERFACE**

Links an asset to another asset(really an interface).
Constant value: 21

IS_ASSET_OF

public static final int **IS_ASSET_OF**

Links an asset to the agent for representing the machine on which the agent is running.
Constant value: 22

HAS_DISCOVERY_CONFIGURATION

public static final int **HAS_DISCOVERY_CONFIGURATION**

Constant value: 23

WAS_DISCOVERED_IN_RUN

public static final int **WAS_DISCOVERED_IN_RUN**

Constant value: 24

IS_SUBSEQUENT_STAGE_OF

public static final int **IS_SUBSEQUENT_STAGE_OF**

Links a disposition to another to model a workflow.
Constant value: 25

IS_MARK_SIMILAR_STAGE_OF

public static final int **IS_MARK_SIMILAR_STAGE_OF**

Links a disposition to another to model similar dispositions.
Constant value: 26

IS_EMPLOYEE_OF

public static final int **IS_EMPLOYEE_OF**

Links a user to a customer as an employee.
Constant value: 27

IS_ACCOUNT_MANAGER_OF

public static final int **IS_ACCOUNT_MANAGER_OF**

Links a user to a customer as an account manager.
Constant value: 28

HAS_START_VIEW

public static final int **HAS_START_VIEW**

Links the dashboard, dynachannel and user groups.
Constant value: 29

HAS_SCANNER_REPORT

public static final int **HAS_SCANNER_REPORT**

Links a scanned report to an asset.
Constant value: 30

SCAN_DETECTED

public static final int **SCAN_DETECTED**

Links a scanned report to Vulnerability/Open port (Asset Category).
Constant value: 31

SCAN_REPORTED_BY

public static final int **SCAN_REPORTED_BY**

Links a scanned report to an agent.
Constant value: 32

COLUMN_SET_OF

public static final int **COLUMN_SET_OF**

Links a dyna channel with the named column set
Constant value: 33

HAS_LOCATION

public static final int **HAS_LOCATION**

Links an asset/asset-range/zone/network with a location
Constant value: 34

IN_NETWORK

public static final int **IN_NETWORK**

Links a zone/zone-group/network with a network
Constant value: 35

HAS_CUSTOMER

public static final int **HAS_CUSTOMER**

Links a resource with a customer
Constant value: 36

DESTINATION_OF

public static final int **DESTINATION_OF**

Links a destination to a user or a group
Constant value: 37

IS_SAVED_REPORT_PARAMETER_REPORT_OF

public static final int **IS_SAVED_REPORT_PARAMETER_REPORT_OF**

Links a saved report parameter report with a report
Constant value: 38

HAS_SORTABLE_FIELDSET

public static final int **HAS_SORTABLE_FIELDSET**

Links a user group to a sortable field set
Constant value: 39

HAS_CASE_ATTACHMENT

public static final int **HAS_CASE_ATTACHMENT**

Case attachments.
Constant value: 45

HAS_REQUIRED_PACKAGE

public static final int **HAS_REQUIRED_PACKAGE**

A package has a dependent package.
Constant value: 46

HAS_OPTIONAL_PACKAGE

public static final int **HAS_OPTIONAL_PACKAGE**

A package has a dependent package.
Constant value: 47

HAS_PACKAGE_CONTENT

public static final int **HAS_PACKAGE_CONTENT**

Package content archive file.
Constant value: **48**

HAS_PACKAGE_TRANSLATION

public static final int **HAS_PACKAGE_TRANSLATION**

Package content archive file.
Constant value: **49**

HAS_PACKAGE_ATTACHMENT

public static final int **HAS_PACKAGE_ATTACHMENT**

Package content archive file.
Constant value: **50**

HAS_PACKAGE_ARCHIVE

public static final int **HAS_PACKAGE_ARCHIVE**

Package content archive file.
Constant value: **51**

DEPENDS_ON_USER

public static final int **DEPENDS_ON_USER**

Resource depends on user
Constant value: **52**

HAS_COMMAND

public static final int **HAS_COMMAND**

Configuration has a Command
Constant value: **53**

HAS_TARGET

public static final int **HAS_TARGET**

Configuration has a Target
Constant value: **54**

HAS_QUERYVIEWER_ATTACHMENT

public static final int **HAS_QUERYVIEWER_ATTACHMENT**

Query Viewer has a baseline / attachment
Constant value: **55**

INCLUDES_IN_USE_CASE

public static final int **INCLUDES_IN_USE_CASE**

Use case refer to a resource
Constant value: **56**

HAS_USER

public static final int **HAS_USER**

Agent has a user
Constant value: **57**

HAS_PARENT_FIELDSET

public static final int **HAS_PARENT_FIELDSET**

Field (or FieldSet) has a parent FieldSet
Constant value: **58**

HAS_DRILLDOWN_LIST

public static final int **HAS_DRILLDOWN_LIST**

Resource (e.g.: DM or QV) has a Drilldown List
Constant value: **59**

HAS_DRILLDOWN

public static final int **HAS_DRILLDOWN**

Drilldown List has one (or more) Drilldown(s)
Constant value: **60**

DRILLS_DOWN_TO

public static final int **DRILLS_DOWN_TO**

Drills down to Drilldown to a resource
Constant value: **61**

MAX

public static final int **MAX**

The max for relationship ints.
Constant value: **62**

RELATIONSHIP_LABELS

public static final java.lang.String **RELATIONSHIP_LABELS**

The relationship names.

REVERSE_RELATIONSHIP_LABELS

```
public static final java.lang.String REVERSE_RELATIONSHIP_LABELS
```

The reverse relationship names.

RELATIONSHIP_NAMES

```
public static final java.lang.String RELATIONSHIP_NAMES
```

The relationship names. forward - Of | has | edBy reverse - edBy | Of | Of See
\$ARCSIGHT_HOME/config/archive/handler/default.resource.xml Add the appropriate forward or reversed relationship
names, for package / archive framework.

REVERSE_RELATIONSHIP_NAMES

```
public static final java.lang.String REVERSE_RELATIONSHIP_NAMES
```

The relationship names. forward - Of | has | edBy reverse - edBy | Of | Of See
\$ARCSIGHT_HOME/config/archive/handler/default.resource.xml Add the appropriate forward or reversed relationship
names, for package / archive framework.

IS_PERMISSION_INHERITANCE_RELATIONSHIP

```
public static final boolean IS_PERMISSION_INHERITANCE_RELATIONSHIP
```

This tells whether the relationship type is SYMMETRIC or not.

PERMISSION_INHERITANCE_RELATIONSHIPS

```
public static final int PERMISSION_INHERITANCE_RELATIONSHIPS
```

Symmetric relationships comprising of: #IS_PARENT_OF, #HAS_CASE_ATTACHMENT, #HAS_REQUIRED_PACKAGE,
#HAS_OPTIONAL_PACKAGE, #HAS_PACKAGE_CONTENT, #HAS_PACKAGE_TRANSLATION, #HAS_PACKAGE_ATTACHMENT,
#HAS_PACKAGE_ARCHIVE, #HAS_QUERYVIEWER_ATTACHMENT, #HAS_DRILLDOWN_LIST, #HAS_DRILLDOWN,
#DRILLS_DOWN_TO

Constructors

RelationshipTypes

```
public RelationshipTypes()
```


com.arcsight.product.manager.resource.service.v1.model

Class Report

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ **com.arcsight.product.manager.resource.service.v1.model.Report**

All Implemented Interfaces:

Serializable, Serializable

public class **Report**

extends [Resource](#)

implements Serializable, Serializable

Represents a report.

Field Summary

public static final	ARCSIGHT_REPORT_V4 String constant identifying V4 reports. Value: Reports V4
public static final	ATTR_TYPE Value: 0
public static final	CUSTOM_ARCSIGHT_REPORT String constant identifying custom reports. Value: ArcSight Reports

Constructor Summary

public	Report()

Method Summary

String[]	getColumnDisplayTemplates() Returns an array of Velocity templates for the columns of the report.
ReportParameter[]	getCommonParameters() Returns the report parameters common to the entire report.
String[]	getComponentIDs() Returns an array of all component IDs in the report.
ReportComponentParameter[]	getComponentParameters() Returns all report component parameters.

CustomReportParameter[]	getCustomParameters() Returns an array of the custom report parameters.
ReportComponentParameter[]	getDeltaParameters() Returns an array of delta parameters of the report.
String	getReportType() Returns report type as it's defined in ESM.
String	getReportXML() Returns the XML specification of the report.
ReportParameter[]	getSaveOutputParameters() Returns the report parameters related to the archived report property.
boolean	isCanRunDeltaReport() Returns true if this report can be run as a delta report.
boolean	isCustomReport() Returns true if this report is a custom report.
boolean	isHasPermissionToArchive() Returns true if the current user has permissions to all of the resources in the report.
void	setCanRunDeltaReport(boolean canRunDeltaReport) Sets the flag indicating whether this report can be run as a delta report.
void	setColumnDisplayTemplates(String[] columnDisplayTemplates) Sets the array of Velocity templates for the columns of the report.
void	setCommonParameters(ReportParameter[] commonParameters) Sets the report parameters common to the entire report.
void	setComponentIDs(String[] componentIDs) Sets the array of all component IDs in the report.
void	setComponentParameters(ReportComponentParameter[] componentParameters) Returns all report component parameters.
void	setCustomParameters(CustomReportParameter[] customParameters) Sets the array of the custom report parameters.
void	setCustomReport(boolean customReport) Sets the flag indicating whether this report is a custom report.
void	setDeltaParameters(ReportComponentParameter[] deltaParameters) Sets the array of delta parameters of the report.
void	setHasPermissionToArchive(boolean hasPermissionToArchive) Sets that flag indicating whether the current user has permissions to all of the resources in the report.
void	setReportXML(String reportXML) Sets the XML specification of the report.

void	setSaveOutputParameters (ReportParameter[] saveOutputParameters) Sets the report parameters related to the archived report property.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

getAlias , getContentVersionID , getCreatedTime , getCreatedTimestamp , getCreatorName , getDescription , getDisabledReason , getDisplayName , getExternalID , getInactiveReason , getInCache , getLocalID , getModificationCount , getModifiedTime , getModifiedTimestamp , getModifierName , getName , getNotificationGroupIDs , getReference , getReferencePage , getResourceid , getSignature , getState , getSubType , getType , getTypeName , getURI , getVersionID , isAttributeInitializationInProgress , isDeprecated , isDisabled , isInactive , isInitialized , isIsAdditionalLoaded , setAlias , setAttributeInitializationInProgress , setContentVersionID , setCreatedTime , setCreatedTimestamp , setCreatorName , setDeprecated , setDescription , setDisabled , setDisabledReason , setExternalID , setInactive , setInactiveReason , setInCache , setInitialized , setIsAdditionalLoaded , setLocalID , setModificationCount , setModifiedTime , setModifiedTimestamp , setModifierName , setName , setNotificationGroupIDs , setReference , setReferencePage , setResourceid , setState , setSubType , setType , setTypeName , setURI , setVersionID

Methods inherited from class [java.lang.Object](#)

equals , getClass , hashCode , notify , notifyAll , toString , wait , wait , wait

Fields

ATTR_TYPE

public static final int **ATTR_TYPE**

Constant value: 0

CUSTOM_ARCSIGHT_REPORT

public static final java.lang.String **CUSTOM_ARCSIGHT_REPORT**

String constant identifying custom reports.
Constant value: **ArcSight Reports**

ARCSIGHT_REPORT_V4

public static final java.lang.String **ARCSIGHT_REPORT_V4**

String constant identifying V4 reports.
Constant value: **Reports V4**

Constructors

Report

public **Report**()

Methods

isCanRunDeltaReport

```
public boolean isCanRunDeltaReport()
```

Returns true if this report can be run as a delta report.

Returns:

true if this report can be run as a delta report.

setCanRunDeltaReport

```
public void setCanRunDeltaReport(boolean canRunDeltaReport)
```

Sets the flag indicating whether this report can be run as a delta report.

Parameters:

canRunDeltaReport - true if this report can be run as a delta report.

getComponentParameters

```
public ReportComponentParameter\[\] getComponentParameters()
```

Returns all report component parameters. Each report component contains the ID of the report component it belongs.

Returns:

???

setComponentParameters

```
public void setComponentParameters(ReportComponentParameter\[\] componentParameters)
```

Returns all report component parameters. Each report component contains the ID of the report component it belongs.

Parameters:

componentParameters

getColumnDisplayTemplates

```
public String[] getColumnDisplayTemplates()
```

Returns an array of Velocity templates for the columns of the report.

Returns:

an array of Velocity templates for the columns of the report.

setColumnDisplayTemplates

```
public void setColumnDisplayTemplates(String[] columnDisplayTemplates)
```

Sets the array of Velocity templates for the columns of the report.

Parameters:

columnDisplayTemplates - the array of Velocity templates for the columns of the report.

getCommonParameters

```
public ReportParameter\[\] getCommonParameters()
```

Returns the report parameters common to the entire report.

Returns:

the report parameters common to the entire report.

setCommonParameters

```
public void setCommonParameters(ReportParameter\[\] commonParameters)
```

Sets the report parameters common to the entire report.

Parameters:

commonParameters - the report parameters common to the entire report.

getComponentIDs

```
public String[] getComponentIDs()
```

Returns an array of all component IDs in the report.

Returns:

an array of all component IDs in the report.

setComponentIDs

```
public void setComponentIDs(String[] componentIDs)
```

Sets the array of all component IDs in the report.

Parameters:

componentIDs

getCustomParameters

```
public CustomReportParameter\[\] getCustomParameters()
```

Returns an array of the custom report parameters.

Returns:

an array of the custom report parameters.

setCustomParameters

```
public void setCustomParameters(CustomReportParameter\[\] customParameters)
```

Sets the array of the custom report parameters.

Parameters:

customParameters - the array of the custom report parameters.

getDeltaParameters

```
public ReportComponentParameter\[\] getDeltaParameters()
```

Returns an array of delta parameters of the report.

Returns:

an array of delta parameters of the report; null is returned if this report cannot be run as a delta report.

setDeltaParameters

```
public void setDeltaParameters(ReportComponentParameter\[\] deltaParameters)
```

Sets the array of delta parameters of the report.

Parameters:

deltaParameters - the array of delta parameters of the report.

getReportXML

```
public String getReportXML()
```

Returns the XML specification of the report.

Returns:

the XML specification of the report.

setReportXML

```
public void setReportXML(String reportXML)
```

Sets the XML specification of the report.

Parameters:

reportXML - the XML specification of the report.

getSaveOutputParameters

```
public ReportParameter\[\] getSaveOutputParameters()
```

Returns the report parameters related to the archived report property.

Returns:

the report parameters related to the archived report property.

setSaveOutputParameters

```
public void setSaveOutputParameters(ReportParameter\[\] saveOutputParameters)
```

Sets the report parameters related to the archived report property.

Parameters:

saveOutputParameters - the report parameters related to the archived report property.

isHasPermissionToArchive

```
public boolean isHasPermissionToArchive()
```

Returns true if the current user has permissions to all of the resources in the report.

Returns:

true if the current user has permissions to all of the resources in the report.

setHasPermissionToArchive

```
public void setHasPermissionToArchive(boolean hasPermissionToArchive)
```

Sets that flag indicating whether the current user has permissions to all of the resources in the report.

Parameters:

hasPermissionToArchive - true if the current user has permissions to all of the resources in the report.

isCustomReport

```
public boolean isCustomReport()
```

Returns true if this report is a custom report.

Returns:

true if this report is a custom report.

setCustomReport

```
public void setCustomReport(boolean customReport)
```

Sets the flag indicating whether this report is a custom report.

Parameters:

customReport - true if this report is a custom report.

getReportType

```
public String getReportType()
```

Returns report type as it's defined in ESM. Report types are string constants defined in ESM classes.

Returns:

report type

com.arcsight.product.manager.resource.service.v1.model

Class ReportComponentParameter

java.lang.Object

↳ [com.arcsight.product.manager.resource.service.v1.model.ReportParameter](#)

↳ [com.arcsight.product.manager.resource.service.v1.model.ReportComponentParameter](#)

All Implemented Interfaces:

Serializable, Serializable

public class **ReportComponentParameter**

extends [ReportParameter](#)

implements Serializable, Serializable

Represents a parameter for a report component.

Constructor Summary

public	ReportComponentParameter ()

Method Summary

String	getId () Returns the ID of the report component this parameter associated with.

String	getOriginalValue () Returns the original (i.e.

void	setId (String id) Sets the ID of the report component this parameter associated with.

void	setOriginalValue (String originalValue) Sets the original (i.e.

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.ReportParameter](#)

[getDisplayname](#), [getFieldName](#), [getName](#), [getParameterType](#), [getSavedInheritedValue](#),
[getType](#), [getValue](#), [setDisplayname](#), [setFieldName](#), [setName](#), [setParameterType](#),
[setSavedInheritedValue](#), [setType](#), [setValue](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ReportComponentParameter

public **ReportComponentParameter**()

Methods

getId

public String **getId**()

Returns the ID of the report component this parameter associated with.

Returns:

the ID of the report component this parameter associated with.

setId

public void **setId**(String id)

Sets the ID of the report component this parameter associated with.

Parameters:

id - the ID of the report component this parameter associated with.

getOriginalValue

public String **getOriginalValue**()

Returns the original (i.e. dynamic) value of the parameter.

Returns:

the original (i.e. dynamic) value of the parameter.

setOriginalValue

public void **setOriginalValue**(String originalValue)

Sets the original (i.e. dynamic) value of the parameter.

Parameters:

originalValue - the original (i.e. dynamic) value of the parameter.

com.arcsight.product.manager.resource.service.v1.model

Class ReportParameter

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.ReportParameter

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

[ReportComponentParameter](#), [CustomReportParameter](#)

```
public class ReportParameter
extends Object
implements Serializable
```

Represents a parameter of a report.

Constructor Summary

public	ReportParameter()

Method Summary

String	getDisplayName() Returns the display name of the parameter.

String	getFieldName() Returns the field name of the parameter.

String	getName() Returns the parameter name.

int	getParameterType() Returns the type of the parameter.

String	getSavedInheritedValue() Returns the saved inherited value of the parameter.

FieldType	getType() Returns the FieldType of the parameter.

String	getValue() Returns the value of the parameter.

void	setDisplayName(String displayName) Sets the display name of the parameter.

void	<code>setFieldName</code> (String fieldName) Sets the field name of the parameter.
void	<code>setName</code> (String name) Sets the parameter name.
void	<code>setParameterType</code> (int parameterType) Sets the type of the parameter.
void	<code>setSavedInheritedValue</code> (String savedInheritedValue) Sets the saved inherited value of the parameter.
void	<code>setType</code> (<code>FieldType</code> type) Sets the <code>FieldType</code> of the parameter.
void	<code>setValue</code> (String value) Sets the value of the parameter.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ReportParameter

```
public ReportParameter()
```

Methods

getFieldName

```
public String getFieldName()
```

Returns the field name of the parameter.

Returns:

the field name.

setFieldName

```
public void setFieldName(String fieldName)
```

Sets the field name of the parameter.

Parameters:

fieldName - the field name.

getName

```
public String getName()
```

Returns the parameter name.

Returns:
the parameter name.

setName

```
public void setName(String name)
```

Sets the parameter name.

Parameters:
name - the parameter name.

getDisplayName

```
public String getDisplayName()
```

Returns the display name of the parameter.

Returns:
the display name.

setDisplayName

```
public void setDisplayName(String displayName)
```

Sets the display name of the parameter.

Parameters:
displayName - the display name.

getType

```
public FieldType getType()
```

Returns the [FieldType](#) of the parameter.

Returns:
the FieldType of the parameter.

setType

```
public void setType(FieldType type)
```

Sets the [FieldType](#) of the parameter.

Parameters:
type - the FieldType of the parameter.

getValue

```
public String getValue()
```

Returns the value of the parameter.

Returns:
the value of the parameter.

setValue

```
public void setValue(String value)
```

Sets the value of the parameter.

Parameters:
value - the value of the parameter.

getParameterType

```
public int getParameterType()
```

Returns the type of the parameter.

Possible values:

- 0: top-level parameter
- 1: inherited from a parent
- 2: overwritten parent's value
-

Returns:
the type of the parameter.

setParameterType

```
public void setParameterType(int parameterType)
```

Sets the type of the parameter.

Possible values:

- 0: top-level parameter
- 1: inherited from a parent
- 2: overwritten parent's value
-

Parameters:
parameterType - the type of the parameter.

getSavedInheritedValue

```
public String getSavedInheritedValue()
```

Returns the saved inherited value of the parameter.

Returns:

the saved inherited value of the parameter.

setSavedInheritedValue

```
public void setSavedInheritedValue(String savedInheritedValue)
```

Sets the saved inherited value of the parameter.

Parameters:

savedInheritedValue - the saved inherited value of the parameter.

com.arcsight.product.manager.resource.service.v1.model

Class Resource

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.Resource

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[DefaultFieldSet](#), [DrillDownList](#), [Drilldown](#), [ViewerConfiguration](#), [ViewableResource](#), [Portlet](#), [Dashboard](#), [ActiveList](#), [User](#), [Report](#), [Query](#), [Network](#), [Group](#), [FileResource](#), [FieldSet](#), [Connector](#), [ConfigurationItem](#), [Case](#), [ArchiveReport](#)

public class **Resource**
extends Object
implements Serializable

Represents a resource: a value object that is identified by its ID, has name and type, and also may have relationships with other resources.

Nested Class Summary	
class	Resource.State Resource.State
class	Resource.SubType Resource.SubType

Constructor Summary	
public	Resource()

Method Summary	
String	getAlias() Returns the alias of this resource.
String	getContentVersionID() Returns the globally unique version ID for this resource as a Base64 encoded string.
com.arcsight.coma.model.client.ServiceDate	getCreatedTime() Gets the time when this resource is created.
long	getCreatedTimestamp() Returns the timestamp of the resource creation.
String	getCreatorName() Gets the name of the creator for this resource.

String	getDescription() Returns the description of the resource.
String	getDisabledReason() Returns the description of the reason why this resource has been disabled.
String	getDisplayName() Get the display name for the resource.
String	getExternalID() Returns the external ID of this resource.
String	getInactiveReason() Returns the description of the reason why this resource is inactive.
boolean	getInCache() Returns true if the resource is in the resource cache.
long	getLocalID() Returns the local ID of the resource.
long	getModificationCount() Returns the number of times that this resource has been modified.
com.arcsight.coma.model.client.ServiceDate	getModifiedTime() Gets the time when this resource is modified.
long	getModifiedTimestamp() Returns the timestamp of the resource most recent resource modification.
String	getModifierName() Gets the name of modifier of this resource.
String	getName() Returns the name of the resource.
String[]	getNotificationGroupIDs() Gets the array of the notification group IDs of this resource.
ResourceReference	getReference() Returns the reference to the resource.
String	getReferencePage() Returns the reference (description) page for this resource.
String	getResourceid() Returns the ID of this resource .
ResourceSignature	getSignature() Returns the signature for this resource.
int	getState() Returns the state of the resource.

Resource.SubType	getSubType() Gets the sub type for this resource.
int	getType() Returns the type of the resource.
String	getTypeName() Returns the name of this type of resource.
String	getURI() Gets URI for this resource.
String	getVersionID() Returns the globally unique version ID for this resource as a Base64 encoded string.
boolean	isAttributeInitializationInProgress() Returns the transient flag in the resource for whether the attribute initialization is currently taking place.
boolean	isDeprecated() Returns true if the resource has been marked as deprecated.
boolean	isDisabled() Returns true if the resource is disabled.
boolean	isInactive() Returns true if the resource is inactive.
boolean	isInitialized() Returns true if the call to initialize this resource has been made since it was created.
boolean	isIsAdditionalLoaded() Returns true if the resource has the additional fields loaded.
void	setAlias(String alias) Sets the alias of this resource.
void	setAttributeInitializationInProgress(boolean attributeInitializationInProgress) Sets the transient flag in the resource for whether the attribute initialization is currently taking place.
void	setContentVersionID(String versionID) Sets the globally unique version ID for this resource as a Base64 encoded string.
void	setCreatedTime(com.arcsight.coma.model.client.ServiceDate createdTime) Sets the time when this resource is created.
void	setCreatedTimestamp(long timestamp) Sets the timestamp of the resource creation.
void	setCreatorName(String creatorName) Sets the name of the creator for this resource.
void	setDeprecated(boolean deprecated) Sets the flag indicating whether the resource has been marked as deprecated.

void	<u>setDescription</u> (String description) Sets the description of the resource.
void	<u>setDisabled</u> (boolean disabled) Sets the flag indicating that the resource is disabled.
void	<u>setDisabledReason</u> (String reason) Sets the description of the reason why this resource has been disabled.
void	<u>setExternalID</u> (String externalid) Sets the external ID of this resource.
void	<u>setInactive</u> (boolean inactive) Sets the flag indicating that the resource is inactive.
void	<u>setInactiveReason</u> (String reason) Sets the description of the reason why this resource is inactive.
void	<u>setInCache</u> (boolean inCache) Sets the flag indicating whether the resource is in the resource cache.
void	<u>setInitialized</u> (boolean initialized) Sets the flag indicating whether the call to initialize this resource has been made since it was created.
void	<u>setIsAdditionalLoaded</u> (boolean additionalLoaded) Sets the flag indicating whether the additional fields have been loaded.
void	<u>setLocalID</u> (long localid) Returns the local ID of the resource.
void	<u>setModificationCount</u> (long count) Sets the number of times that this resource has been modified.
void	<u>setModifiedTime</u> (com.arcsight.coma.model.client.ServiceDate modifiedTime) Sets the time when this resource is modified.
void	<u>setModifiedTimestamp</u> (long timestamp) Sets the timestamp of the resource most recent resource modification.
void	<u>setModifierName</u> (String modifierName) Sets the name of modifier for this resource.
void	<u>setName</u> (String name) Sets the name of the resource.
void	<u>setNotificationGroupIDs</u> (String[] notificationGroupIDs) Sets the array of the notification group IDs for this resource.
void	<u>setReference</u> (<u>ResourceReference</u> reference) Sets <u>the reference</u> to the resource.
void	<u>setReferencePage</u> (String page) Sets the reference (description) page for this resource.

void	<code>setResourceid</code> (String resourceid) Sets the resource ID.
void	<code>setState</code> (int state) Sets the state of the resource.
void	<code>setSubType</code> (<code>Resource.SubType</code> subType) Sets the sub type for this resource.
void	<code>setType</code> (int type) Sets the type of the resource.
void	<code>setTypeNames</code> (String typeName) Sets the name of this type of resource.
void	<code>setURI</code> (String uRI) Sets URI for this resource.
void	<code>setVersionID</code> (String versionid) Returns the globally unique version ID for this resource as a Base64 encoded string.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

Resource

`public Resource()`

Methods

`getResourceid`

`public String getResourceid()`

Returns the ID of this resource .

Returns:

The resource ID.

`setResourceid`

`public void setResourceid(String resourceid)`

Sets the resource ID.

Parameters:

`resourceid` - The resource ID.

getName

public String **getName**()

Returns the name of the resource.

Returns:

The resource name.

setName

public void **setName**(String name)

Sets the name of the resource. The name needs to be unique for all the resources within a group.

Parameters:

name - The resource name.

getAlias

public String **getAlias**()

Returns the alias of this resource.

Returns:

The resource alias.

setAlias

public void **setAlias**(String alias)

Sets the alias of this resource. The alias needs to be unique for all the resources within a group.

Parameters:

alias - The alias of this resource to set.

getDescription

public String **getDescription**()

Returns the description of the resource.

Returns:

The description of the resource.

setDescription

public void **setDescription**(String description)

Sets the description of the resource.

Parameters:

description - The description of the resource.

getReference

public [ResourceReference](#) **getReference()**

Returns [the reference](#) to the resource.

Returns:

The reference to the resource.

setReference

public void **setReference**([ResourceReference](#) reference)

Sets [the reference](#) to the resource.

Parameters:

reference - The reference to the resource.

isIsAdditionalLoaded

public boolean **isIsAdditionalLoaded()**

Returns true if the resource has the additional fields loaded. The additional fields are the fields that are not loaded by default.

Returns:

True if the resource has additional fields loaded.

setIsAdditionalLoaded

public void **setIsAdditionalLoaded**(boolean additionalLoaded)

Sets the flag indicating whether the additional fields have been loaded. The additional fields are the fields that are not loaded by default.

Parameters:

additionalLoaded - The boolean value to set whether the additional fields have been loaded.

getModificationCount

public long **getModificationCount()**

Returns the number of times that this resource has been modified.

Returns:

The number of times that this resource has been modified.

setModificationCount

public void **setModificationCount**(long count)

Sets the number of times that this resource has been modified.

Parameters:

count - The number of times that this resource has been modified.

getExternalID

```
public String getExternalID()
```

Returns the external ID of this resource. The external ID is used to link a resource to its counterpart in an external system.

Returns:

The external ID of this resource.

setExternalID

```
public void setExternalID(String externalid)
```

Sets the external ID of this resource. The external ID is used to link a resource to its counterpart in an external system.

Parameters:

externalid - The external ID of this resource.

getCreatedTimestamp

```
public long getCreatedTimestamp()
```

Returns the timestamp of the resource creation. The timestamp is determined upon inserting the resource into the persistent store.

Returns:

The timestamp of the resource creation.

setCreatedTimestamp

```
public void setCreatedTimestamp(long timestamp)
```

Sets the timestamp of the resource creation. The timestamp is determined upon inserting the resource into the persistent store.

Parameters:

timestamp - The timestamp of the resource creation.

getModifiedTimestamp

```
public long getModifiedTimestamp()
```

Returns the timestamp of the resource most recent resource modification. The timestamp is determined upon updating the resource into the persistent store.

Returns:

The timestamp of the resource most recent resource modification.

setModifiedTimestamp

```
public void setModifiedTimestamp(long timestamp)
```

Sets the timestamp of the resource most recent resource modification. The timestamp is determined upon updating the resource into the persistent store.

Parameters:

timestamp - The timestamp of the resource most recent resource modification.

getVersionID

```
public String getVersionID()
```

Returns the globally unique version ID for this resource as a Base64 encoded string. This version is only initialized as part of exporting an resource to a package.

Returns:

The version ID.

setVersionID

```
public void setVersionID(String versionid)
```

Returns the globally unique version ID for this resource as a Base64 encoded string. This version is only initialized as part of exporting an resource to a package.

Parameters:

versionid - The version ID.

getContentVersionID

```
public String getContentVersionID()
```

Returns the globally unique version ID for this resource as a Base64 encoded string. This version is only initialized as part of exporting an resource to a package. Content is defined as data associated with the resource that changes frequently and is independent of the basic configuration of the resource. Example of content would be active list values or trend data.

Returns:

The content version ID.

setContentVersionID

```
public void setContentVersionID(String versionID)
```

Sets the globally unique version ID for this resource as a Base64 encoded string. This version is only initialized as part of exporting an resource to a package. Content is defined as data associated with the resource that changes frequently and is independent of the basic configuration of the resource. Example of content would be active list values or trend data.

Parameters:

versionID - The content version ID.

getReferencePage

```
public String getReferencePage()
```

Returns the reference (description) page for this resource.

Returns:

the reference page for this resource.

setReferencePage

public void **setReferencePage**(String page)

Sets the reference (description) page for this resource.

Parameters:

page - The reference page for this resource.

isDisabled

public boolean **isDisabled**()

Returns true if the resource is disabled.

Returns:

True if the resource is disabled; otherwise, false.

setDisabled

public void **setDisabled**(boolean disabled)

Sets the flag indicating that the resource is disabled.

Parameters:

disabled - True if the resource is disabled; otherwise, false.

getDisabledReason

public String **getDisabledReason**()

Returns the description of the reason why this resource has been disabled.

Returns:

The description of the reason why this resource has been disabled.

setDisabledReason

public void **setDisabledReason**(String reason)

Sets the description of the reason why this resource has been disabled.

Parameters:

reason - The description of the reason why this resource has been disabled.

getDisplayName

public String **getDisplayName**()

Get the display name for the resource. The display name is the alias for the resource if an alias has been set; otherwise the display name is the resource name.

Returns:

isInactive

```
public boolean isInactive()
```

Returns true if the resource is inactive.

Returns:

True if the resource is inactive; otherwise, false.

setInactive

```
public void setInactive(boolean inactive)
```

Sets the flag indicating that the resource is inactive.

Parameters:

`inactive` - True if the resource is inactive; otherwise, false.

getInactiveReason

```
public String getInactiveReason()
```

Returns the description of the reason why this resource is inactive.

Returns:

The description of the reason why this resource is inactive.

setInactiveReason

```
public void setInactiveReason(String reason)
```

Sets the description of the reason why this resource is inactive.

Parameters:

`reason` - The description of the reason why this resource is inactive.

isDeprecated

```
public boolean isDeprecated()
```

Returns true if the resource has been marked as deprecated.

Returns:

True if the resource has been marked as deprecated; otherwise, false.

setDeprecated

```
public void setDeprecated(boolean deprecated)
```

Sets the flag indicating whether the resource has been marked as deprecated.

Parameters:

deprecated - True if the resource has been marked as deprecated; otherwise, false.

getLocalID

public long **getLocalID**()

Returns the local ID of the resource. The local ID is valid as long as the resource stays in the persistence store.

Returns:

the local ID of the resource.

setLocalID

public void **setLocalID**(long localid)

Returns the local ID of the resource. The local ID is valid as long as the resource stays in the persistence store.

Parameters:

localid - the local ID of the resource.

getState

public int **getState**()

Returns the state of the resource. See the state constants definition for the list of all available states.

Returns:

the state of the resource.

setState

public void **setState**(int state)

Sets the state of the resource. See the state constants definition for the list of all available states.

Parameters:

state - the state of the resource.

getInCache

public boolean **getInCache**()

Returns true if the resource is in the resource cache.

Returns:

true if the resource is in the resource cache.

setInCache

public void **setInCache**(boolean inCache)

Sets the flag indicating whether the resource is in the resource cache.

Parameters:

inCache - true if the resource is in the resource cache.

isInitialized

```
public boolean isInitialized()
```

Returns true if the call to initialize this resource has been made since it was created.

Returns:

true if the call to initialize this resource has been made.

setInitialized

```
public void setInitialized(boolean initialized)
```

Sets the flag indicating whether the call to initialize this resource has been made since it was created.

Parameters:

initialized - true if the call to initialize this resource has been made.

isAttributeInitializationInProgress

```
public boolean isAttributeInitializationInProgress()
```

Returns the transient flag in the resource for whether the attribute initialization is currently taking place. This is used by the resources that react to changes in attributes by changing other attributes. For example, there may be some synchronization between the resource attributes and the relationships.

Returns:

true if the attribute initialization is in progress.

setAttributeInitializationInProgress

```
public void setAttributeInitializationInProgress(boolean  
attributeInitializationInProgress)
```

Sets the transient flag in the resource for whether the attribute initialization is currently taking place. This is used by the resources that react to changes in attributes by changing other attributes. For example, there may be some synchronization between the resource attributes and the relationships.

Parameters:

attributeInitializationInProgress - true if the attribute initialization is in progress.

getType

```
public int getType()
```

Returns the type of the resource. See the resource type constants for the list of all available types.

Returns:

the type of the resource.

setType

```
public void setType(int type)
```

Sets the type of the resource. See the resource type constants for the list of all available types.

Parameters:
type

getTypeName

```
public String getTypeName()
```

Returns the name of this type of resource. See the resource type name constants for the list of all available type names.

Returns:
the name of this type of resource.

setName

```
public void setName(String typeName)
```

Sets the name of this type of resource. See the resource type name constants for the list of all available type names.

Parameters:
typeName - the name of this type of resource.

getSignature

```
public ResourceSignature getSignature()
```

Returns the signature for this resource. The signature identifies the resource and its version.

Returns:
the resource signature.

setCreatorName

```
public void setCreatorName(String creatorName)
```

Sets the name of the creator for this resource.

Parameters:
creatorName - The name of the creator to set for this resource.

getCreatorName

```
public String getCreatorName()
```

Gets the name of the creator for this resource.

Returns:
The name of the creator for this resource.

setURI

```
public void setURI(String uRI)
```

Sets URI for this resource.

Parameters:

uri - The URI to set for this resource.

getURI

```
public String getURI()
```

Gets URI for this resource.

Returns:

The URI for this resource.

getSubType

```
public Resource.SubType getSubType()
```

Gets the sub type for this resource.

Returns:

The sub type for this resource.

setSubType

```
public void setSubType(Resource.SubType subType)
```

Sets the sub type for this resource.

Parameters:

subType - The sub type to set for this resource.

getNotificationGroupIDs

```
public String[] getNotificationGroupIDs()
```

Gets the array of the notification group IDs of this resource.

Returns:

The array of the notification group IDs of this resource.

setNotificationGroupIDs

```
public void setNotificationGroupIDs(String[] notificationGroupIDs)
```

Sets the array of the notification group IDs for this resource.

Parameters:

notificationGroupIDs - The array of the notification group IDs to set for this resource.

getModifierName

```
public String getModifierName()
```

Gets the name of modifier of this resource.

Returns:

The name of modifier of this resource.

setModifierName

```
public void setModifierName(String modifierName)
```

Sets the name of modifier for this resource.

Parameters:

modifierName - The name of modifier to set for this resource.

getCreatedTime

```
public com.arcsight.coma.model.client.ServiceDate getCreatedTime()
```

Gets the time when this resource is created.

Returns:

The time when this resource is created.

setCreatedTime

```
public void setCreatedTime(com.arcsight.coma.model.client.ServiceDate createdTime)
```

Sets the time when this resource is created.

Parameters:

createdTime - The time when this resource is created.

getModifiedTime

```
public com.arcsight.coma.model.client.ServiceDate getModifiedTime()
```

Gets the time when this resource is modified.

Returns:

The time when this resource is modified.

setModifiedTime

```
public void setModifiedTime(com.arcsight.coma.model.client.ServiceDate modifiedTime)
```

Sets the time when this resource is modified.

Parameters:

modifiedTime - The time when this resource is modified.

com.arcsight.product.manager.resource.service.v1.model

Class Resource.State

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Resource.State

All Implemented Interfaces:

Serializable, Comparable

public static class **Resource.State**
extends Enum

Defines the enum types for the resource states.

Field Summary

public static final	STATE_DELETED Identifies the deleted state.
public static final	STATE_IN_DELETE Identifies the in-delete state.
public static final	STATE_KNOWN Identifies the known state.
public static final	STATE_NEW Identifies the newly created state.
public static final	STATE_UNKNOWN Identifies the unknown state

Method Summary

static int	getValue (String state) Gets the value of the given state.
static Resource.State	valueOf (String name)
static Resource.State[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

STATE_UNKNOWN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Resource.State  
STATE_UNKNOWN
```

Identifies the unknown state

STATE_NEW

```
public static final com.arcsight.product.manager.resource.service.v1.model.Resource.State  
STATE_NEW
```

Identifies the newly created state.

STATE_KNOWN

```
public static final com.arcsight.product.manager.resource.service.v1.model.Resource.State  
STATE_KNOWN
```

Identifies the known state.

STATE_IN_DELETE

```
public static final com.arcsight.product.manager.resource.service.v1.model.Resource.State  
STATE_IN_DELETE
```

Identifies the in-delete state.

STATE_DELETED

```
public static final com.arcsight.product.manager.resource.service.v1.model.Resource.State  
STATE_DELETED
```

Identifies the deleted state.

Methods

values

```
public static Resource.State\[\] values()
```


valueOf

```
public static Resource.State valueOf(String name)
```

getValue

```
public static int getValue(String state)
```

Gets the value of the given state.

Parameters:

state - The string of the given state.

Returns:

The value of the given state.

com.arcsight.product.manager.resource.service.v1.model

Class Resource.SubType

java.lang.Object

└- java.lang.Enum

└- com.arcsight.product.manager.resource.service.v1.model.Resource.SubType

All Implemented Interfaces:

Serializable, Comparable

public static final class **Resource.SubType**
extends Enum

It provides the additional typing information for resource. *

Field Summary

public static final	FieldSet_NonSortable
public static final	FieldSet_Sortable

Method Summary

static Resource.SubType	valueOf (String name)
static Resource.SubType[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

FieldSet_NonSortable

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Resource.SubType  
FieldSet_NonSortable
```

FieldSet_Sortable

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.Resource.SubType FieldSet_Sortable
```

Methods

values

```
public static Resource.SubType\[\] values()
```

valueOf

```
public static Resource.SubType valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class ResourceReference

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ResourceReference

All Implemented Interfaces:

Comparable, Serializable

public class **ResourceReference**
extends Object
implements Serializable, Comparable

Constructor Summary

public	ResourceReference()

Method Summary

int	compareTo(ResourceReference ref) Gets the result of the comparison of this ResourceReference with the given ResourceReference.
String	getExternalID() Returns the external ID for this resource reference.
String	getId() Returns the ID for the resource in this resource reference.
boolean	getIsModifiable() Tests whether this resource reference is modifiable.
String	getManagerID() Gets the unique ID of the manager on which this resource reference is valid.
Long	getReferenceID() Gets the descriptor id of this resource reference.
String	getReferenceName() Gets the string of reference name.
String	getReferenceString() Gets the string representation of this resource reference.
int	getReferenceType() Gets the type of resource this reference references.

String	<code>getUri()</code> Returns the URI for this resource reference.
void	<code>setExternalID(String id)</code> Sets external ID of the resource for this resource reference.
void	<code>setId(String id)</code> Sets ID of the resource for this resource reference.
void	<code>setIsModifiable(boolean modifiable)</code> Sets whether this resource reference is modifiable or not.
void	<code>setManagerID(String managerid)</code> Sets the unique ID of the manager on which this resource reference is valid.
void	<code>setReferenceID(Long referenceid)</code> Sets the descriptor id for this resource reference.
void	<code>setReferenceName(String name)</code> Sets the name for this resource reference.
void	<code>setReferenceString(String reference)</code> Sets the string representation for this resource reference.
void	<code>setReferenceType(int type)</code> Sets the type of resource this reference references.
void	<code>setUri(String uri)</code> Sets the URI for this resource reference.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Constructors

ResourceReference

```
public ResourceReference()
```

Methods

getId

```
public String getId()
```

Returns the ID for the resource in this resource reference.

Returns:

ID for the resource in this resource reference.

setId

```
public void setId(String id)
```

Sets ID of the resource for this resource reference.

Parameters:

`id` - The ID of the resource for this reference.

getUri

```
public String getUri()
```

Returns the URI for this resource reference.

Returns:

URI for this reference.

setUri

```
public void setUri(String uri)
```

Sets the URI for this resource reference.

Parameters:

`uri` - The URI for this resource reference.

getExternalID

```
public String getExternalID()
```

Returns the external ID for this resource reference.

Returns:

The external ID for this resource reference.

setExternalID

```
public void setExternalID(String id)
```

Sets external ID of the resource for this resource reference.

Parameters:

`id` - The External ID of the resource for this resource reference.

getReferenceString

```
public String getReferenceString()
```

Gets the string representation of this resource reference.

Returns:

The string representation of this resource reference.

setReferenceString

```
public void setReferenceString(String reference)
```

Sets the string representation for this resource reference.

Parameters:

reference - The string representation to set for this resource reference.

getReferenceID

```
public Long getReferenceID()
```

Gets the descriptor id of this resource reference.

Returns:

The descriptor id of this resource reference.

setReferenceID

```
public void setReferenceID(Long referenceid)
```

Sets the descriptor id for this resource reference.

Parameters:

referenceid - The descriptor id to set.

getManagerID

```
public String getManagerID()
```

Gets the unique ID of the manager on which this resource reference is valid.

Returns:

The unique ID of the manager on which this resource reference is valid.

setManagerID

```
public void setManagerID(String managerid)
```

Sets the unique ID of the manager on which this resource reference is valid.

Parameters:

The - unique ID of the manager.

getReferenceType

```
public int getReferenceType()
```

Gets the type of resource this reference references.

Returns:

The type of resource this reference references.

setReferenceType

```
public void setReferenceType(int type)
```

Sets the type of resource this reference references.

Parameters:

The - type of resource this reference references.

getIsModifiable

```
public boolean getIsModifiable()
```

Tests whether this resource reference is modifiable.

Returns:

True if this resource reference is modifiable.

setIsModifiable

```
public void setIsModifiable(boolean modifiable)
```

Sets whether this resource reference is modifiable or not.

Parameters:

The - boolean value to set whether this resource reference is modifiable or not

getReferenceName

```
public String getReferenceName()
```

Gets the string of reference name.

Returns:

The reference name.

setReferenceName

```
public void setReferenceName(String name)
```

Sets the name for this resource reference.

Parameters:

name - The reference name to set.

compareTo

```
public int compareTo(ResourceReference ref)
```


Gets the result of the comparison of this ResourceReference with the given ResourceReference. First, compares their resources' URIs. If they have the same URI, then compares their resources' ID. If having the same resource ID, compares their external IDs. Last, compares their reference ID.

Parameters:

ref - The given ResourceReference.

Returns:

The result of the comparison of this ResourceReference with the given ResourceReference. A negative integer, zero, or a positive integer as this ResourceReference is less than, equal to, or greater than the given ResourceReference.

com.arcsight.product.manager.resource.service.v1.model

Class ResourceSignature

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.ResourceSignature

All Implemented Interfaces:
Serializable

public class **ResourceSignature**
extends Object
implements Serializable

Represents a certain version of a resource.

Constructor Summary

public	ResourceSignature() Default constructor to make Axis happy.
public	ResourceSignature(String id, long modificationCount) Creates an instance of the resource signature.

Method Summary

String	getId() Returns the ID of the resource represented by this signature.
long	getModificationCount() Returns the modification count of the resource represented by this signature.
boolean	isNewer(ResourceSignature other) Returns true if the resource represented by this signature is newer (its modification counter is greater) than the resource represented by other.
void	setId(String id) Sets resource ID for this resource signature.
void	setModificationCount(long modificationCount) Sets the number of modification count to be modificationCount.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceSignature

```
public ResourceSignature()
```

Default constructor to make Axis happy.

ResourceSignature

```
public ResourceSignature(String id,  
                        long modificationCount)
```

Creates an instance of the resource signature.

Parameters:

id - The resource UUID.

modificationCount - The resource modification count.

Methods

getId

```
public String getId()
```

Returns the ID of the resource represented by this signature.

Returns:

The ID of the resource represented by this signature.

getModificationCount

```
public long getModificationCount()
```

Returns the modification count of the resource represented by this signature.

Returns:

The modification count of the resource represented by this signature.

isNewer

```
public boolean isNewer(ResourceSignature other)
```

Returns true if the resource represented by this signature is newer (its modification counter is greater) than the resource represented by other.

Returns:

True if the resource represented by this signature is newer.

setId

```
public void setId(String id)
```

Sets resource ID for this resource signature.

Parameters:

id - Resource ID.

setModificationCount

```
public void setModificationCount(long modificationCount)
```

Sets the number of modification count to be modificationCount.

Parameters:

modificationCount - Number of time the resource was changed.

com.arcsight.product.manager.resource.service.v1.model

Class ResourceTypes

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.ResourceTypes

public class **ResourceTypes**
extends Object

Constants identifying various types of Resources

Field Summary	
public static final	ACTIVE_LIST Identifies a resource as being of type ActiveList. Value: 24
public static final	ACTOR Identifies a resource as being of type Actor Value: 56
public static final	AGENT Identifies a resource as being of type AGENT. Value: 3
public static final	ARCHIVEREPORT Identifies a resource as being of type REPORTARCHIVE. Value: 10
public static final	ARCSIGHT_QUERY Identifies a resource as being of type ArcSightQuery Value: 43
public static final	ATTACHMENT_ONLY_GROUP Value: 50
public static final	CASE Identifies a resource as being of type CASE. Value: 7
public static final	CATEGORY_MODEL Identifies a resource as being of type Category Model Value: 57
public static final	CONFIGURATION_ITEM Value: 61

public static final	<u>CUSTOMER</u> Identifies a resource as being of type Customer. Value: 35
public static final	<u>DASHBOARD</u> Identifies a resource as being of type Dashboard. Value: 22
public static final	<u>DATA_MONITOR</u> Identifies a resource as being of type DataMonitor. Value: 19
public static final	<u>DATABASE_TABLE_SCHEMA</u> Identifies a resource as being of type DatabaseTableSchema (previously MetaGroup). Value: 15
public static final	<u>DESTINATION</u> Identifies a resource as being of type Notification Destination Value: 23
public static final	<u>DEVICE</u> Identifies a resource as being of type DEVICE. Value: 4
public static final	<u>DEVICE_RANGE</u> Identifies a resource as being of type Device Range. Value: 30
public static final	<u>DRILLDOWN</u> Value: 59
public static final	<u>DRILLDOWN_LIST</u> Value: 60
public static final	<u>DYNA_CHANNEL</u> Identifies a resource as being of type Dyna Channl. Value: 33
public static final	<u>ESCALATION_LEVEL</u> Identifies a resource as being of type Escalation Level. Value: 42
public static final	<u>FIELD</u> Identifies a resource as being of type Named Column. Value: 36
public static final	<u>FIELD_SET</u> Identifies a resource as being of type Named Column List. Value: 37

public static final	<u>FILE</u> Identifies a resource as being of type FILE (not yet implemented). Value: 17
public static final	<u>GROUP</u> Identifies a resource as being of type GROUP. Value: 0
public static final	<u>GROUP_TYPES</u> A Set containing resource types considered Group types.
public static final	<u>GROUP_TYPES_ARRAY</u> An array describing all of the resources that are of type group.
public static final	<u>INTEGRATION_COMMAND</u> Value: 54
public static final	<u>INTEGRATION_CONFIGURATION</u> Value: 53
public static final	<u>INTEGRATION_TARGET</u> Value: 55
public static final	<u>KBASE</u> Identifies a resource as being of type KBASE. Value: 6
public static final	<u>LOCATION</u> Identifies a resource as being of type Location. Value: 39
public static final	<u>NETWORK</u> Identifies a resource as being of type Pseudo Network. Value: 40
public static final	<u>NETWORK_CATEGORY</u> Identifies a resource as being of type Asset Category (previously network category). Value: 31
public static final	<u>NETWORK_ZONE</u> Identifies a resource as being of type Network (aka Zone). Value: 29
public static final	<u>NOTE</u> Identifies a resource as being of type NOTE. Value: 8
public static final	<u>PACKAGE</u> Identifies a resource as being of type Content Packages Value: 47

public static final	<u>PARTITION</u> Identifies a resource as being of type Partition. Value: 32
public static final	<u>PATTERN</u> Identifies patterns Value: 28
public static final	<u>PATTERN_DISCOVERY_RUN</u> Identifies a resource as being of type pattern discovery result. Value: 18
public static final	<u>PDE_CONFIGURATION</u> Identifies a resource as being of type PDE_CONFIGURATION...PDE = Pattern Discovery Engine (aka Profiles) Value: 12
public static final	<u>PERMISSION</u> Value: 58
public static final	<u>PORTLET</u> Identifies a resource as being of type Portlet. Value: 21
public static final	<u>PROJECT_TEMPLATE</u> Value: 49
public static final	<u>QUERY_GROUP</u> Identifies the query groups Value: 27
public static final	<u>QUERY_VIEWER</u> Identifies a resource as being of type Query Viewer Value: 51
public static final	<u>REPORT</u> Identifies a resource as being of type REPORT. Value: 9
public static final	<u>REPORT_TEMPLATE</u> Identifies a resource as being of type Report Template. Value: 44
public static final	<u>RESERVED_TICK</u> Value: 48
public static final	<u>RULE</u> Identifies a resource as being of type RULE. Value: 5

public static final	<u>SAVED_REPORT_PARAMETER_REPORT</u> Identifies a resource as being of type Focused REPORT. Value: 41
public static final	<u>SAVED_SEARCH</u> Value: 62
public static final	<u>SCANNED_REPORT</u> Identifies a resource as being of type Scanned Report. Value: 38
public static final	<u>SCHEDULEDTASK</u> Identifies a resource as being of type SCHEDULETASK. Value: 11
public static final	<u>SEARCH</u> Value: 63
public static final	<u>SESSION_LIST</u> Identifies a resource as being of type Session List. Value: 45
public static final	<u>STAGE</u> Identifies a resource as being of type Stage. Value: 34
public static final	<u>TREND</u> Identifies a resource as being of type Trend Value: 46
public static final	<u>UNASSIGNED_RESOURCES_GROUP</u> Identifies a resource as being of type UnassignedResourcesGroup. Value: 16
public static final	<u>UNKNOWN</u> Identifies a resource as being of an unknown type. Value: -1
public static final	<u>USE_CASE</u> Identifies a resource as being of type Use Case Value: 52
public static final	<u>USER</u> Identifies a resource as being of type USER. Value: 1
public static final	<u>USER_ACCESSIBLE_GROUP</u> Identifies a resource as being of type UserSharedAccessibleGroup. Value: 14

public static final	USER_SHARED_ACCESSIBLE_GROUP Identifies a resource as being of type UserSharedAccessibleGroup. Value: 13
public static final	VIEWER_CONFIGURATION Identifies a resource as being of type ViewerConfiguration. Value: 20
public static final	VIRTUAL_ROOT Identifies a resource as being of type Virtual Root. Value: 25
public static final	VULNERABILITY Identifies a resource as being of type Vulnerability. Value: 26
public static final	ZONE Identifies a resource as being of type ZONE (aka Filter). Value: 2

Constructor Summary

public	ResourceTypes()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

UNKNOWN

public static final int **UNKNOWN**

Identifies a resource as being of an unknown type.
Constant value: **-1**

GROUP

public static final int **GROUP**

Identifies a resource as being of type GROUP.
Constant value: **0**

USER

public static final int **USER**

Identifies a resource as being of type USER.
Constant value: **1**

ZONE

public static final int **ZONE**

Identifies a resource as being of type ZONE (aka Filter).
Constant value: 2

AGENT

public static final int **AGENT**

Identifies a resource as being of type AGENT.
Constant value: 3

DEVICE

public static final int **DEVICE**

Identifies a resource as being of type DEVICE.
Constant value: 4

RULE

public static final int **RULE**

Identifies a resource as being of type RULE.
Constant value: 5

KBASE

public static final int **KBASE**

Identifies a resource as being of type KBASE.
Constant value: 6

CASE

public static final int **CASE**

Identifies a resource as being of type CASE.
Constant value: 7

NOTE

public static final int **NOTE**

Identifies a resource as being of type NOTE.
Constant value: 8

REPORT

public static final int **REPORT**

Identifies a resource as being of type REPORT.

Constant value: **9**

ARCHIVEREPORT

public static final int **ARCHIVEREPORT**

Identifies a resource as being of type REPORTARCHIVE.
Constant value: **10**

SCHEDULEDTASK

public static final int **SCHEDULEDTASK**

Identifies a resource as being of type SCHEDULETASK.
Constant value: **11**

PDE_CONFIGURATION

public static final int **PDE_CONFIGURATION**

Identifies a resource as being of type PDE_CONFIGURATION...PDE = Pattern Discovery Engine (aka Profiles)
Constant value: **12**

USER_SHARED_ACCESSIBLE_GROUP

public static final int **USER_SHARED_ACCESSIBLE_GROUP**

Identifies a resource as being of type UserSharedAccessibleGroup.
Constant value: **13**

USER_ACCESSIBLE_GROUP

public static final int **USER_ACCESSIBLE_GROUP**

Identifies a resource as being of type UserSharedAccessibleGroup.
Constant value: **14**

DATABASE_TABLE_SCHEMA

public static final int **DATABASE_TABLE_SCHEMA**

Identifies a resource as being of type DatabaseTableSchema (previously MetaGroup).
Constant value: **15**

UNASSIGNED_RESOURCES_GROUP

public static final int **UNASSIGNED_RESOURCES_GROUP**

Identifies a resource as being of type UnassignedResourcesGroup.
Constant value: **16**

FILE

public static final int **FILE**

Identifies a resource as being of type FILE (not yet implemented).
Constant value: **17**

PATTERN_DISCOVERY_RUN

public static final int **PATTERN_DISCOVERY_RUN**

Identifies a resource as being of type pattern discovery result. (aka Snapshots)
Constant value: **18**

DATA_MONITOR

public static final int **DATA_MONITOR**

Identifies a resource as being of type DataMonitor.
Constant value: **19**

VIEWER_CONFIGURATION

public static final int **VIEWER_CONFIGURATION**

Identifies a resource as being of type ViewerConfiguration.
Constant value: **20**

PORTLET

public static final int **PORTLET**

Identifies a resource as being of type Portlet.
Constant value: **21**

DASHBOARD

public static final int **DASHBOARD**

Identifies a resource as being of type Dashboard.
Constant value: **22**

DESTINATION

public static final int **DESTINATION**

Identifies a resource as being of type Notification Destination
Constant value: **23**

ACTIVE_LIST

public static final int **ACTIVE_LIST**

Identifies a resource as being of type ActiveList.
Constant value: **24**

VIRTUAL_ROOT

public static final int **VIRTUAL_ROOT**

Identifies a resource as being of type Virtual Root.
Constant value: **25**

VULNERABILITY

public static final int **VULNERABILITY**

Identifies a resource as being of type Vulnerability.
Constant value: **26**

QUERY_GROUP

public static final int **QUERY_GROUP**

Identifies the query groups
Constant value: **27**

PATTERN

public static final int **PATTERN**

Identifies patterns
Constant value: **28**

NETWORK_ZONE

public static final int **NETWORK_ZONE**

Identifies a resource as being of type Network (aka Zone).
Constant value: **29**

DEVICE_RANGE

public static final int **DEVICE_RANGE**

Identifies a resource as being of type Device Range.
Constant value: **30**

NETWORK_CATEGORY

public static final int **NETWORK_CATEGORY**

Identifies a resource as being of type Asset Category (previously network category).
Constant value: **31**

PARTITION

public static final int **PARTITION**

Identifies a resource as being of type Partition.
Constant value: **32**

DYNA_CHANNEL

public static final int **DYNA_CHANNEL**

Identifies a resource as being of type Dyna Channl.
Constant value: **33**

STAGE

public static final int **STAGE**

Identifies a resource as being of type Stage.
Constant value: **34**

CUSTOMER

public static final int **CUSTOMER**

Identifies a resource as being of type Customer.
Constant value: **35**

FIELD

public static final int **FIELD**

Identifies a resource as being of type Named Column.
Constant value: **36**

FIELD_SET

public static final int **FIELD_SET**

Identifies a resource as being of type Named Column List.
Constant value: **37**

SCANNED_REPORT

public static final int **SCANNED_REPORT**

Identifies a resource as being of type Scanned Report.
Constant value: **38**

LOCATION

public static final int **LOCATION**

Identifies a resource as being of type Location.
Constant value: **39**

NETWORK

public static final int **NETWORK**

Identifies a resource as being of type Pseudo Network.
Constant value: **40**

SAVED_REPORT_PARAMETER_REPORT

public static final int **SAVED_REPORT_PARAMETER_REPORT**

Identifies a resource as being of type Focused REPORT.
Constant value: **41**

ESCALATION_LEVEL

public static final int **ESCALATION_LEVEL**

Identifies a resource as being of type Escalation Level.
Constant value: **42**

ARCSIGHT_QUERY

public static final int **ARCSIGHT_QUERY**

Identifies a resource as being of type ArcSightQuery
Constant value: **43**

REPORT_TEMPLATE

public static final int **REPORT_TEMPLATE**

Identifies a resource as being of type Report Template.
Constant value: **44**

SESSION_LIST

public static final int **SESSION_LIST**

Identifies a resource as being of type Session List.
Constant value: **45**

TREND

public static final int **TREND**

Identifies a resource as being of type Trend
Constant value: **46**

PACKAGE

public static final int **PACKAGE**

Identifies a resource as being of type Content Packages
Constant value: **47**

RESERVED_TICK

public static final int **RESERVED_TICK**

Constant value: 48

PROJECT_TEMPLATE

public static final int **PROJECT_TEMPLATE**

Constant value: 49

ATTACHMENT_ONLY_GROUP

public static final int **ATTACHMENT_ONLY_GROUP**

Constant value: 50

QUERY_VIEWER

public static final int **QUERY_VIEWER**

Identifies a resource as being of type Query Viewer
Constant value: 51

USE_CASE

public static final int **USE_CASE**

Identifies a resource as being of type Use Case
Constant value: 52

INTEGRATION_CONFIGURATION

public static final int **INTEGRATION_CONFIGURATION**

Constant value: 53

INTEGRATION_COMMAND

public static final int **INTEGRATION_COMMAND**

Constant value: 54

INTEGRATION_TARGET

public static final int **INTEGRATION_TARGET**

Constant value: 55

ACTOR

public static final int **ACTOR**

Identifies a resource as being of type Actor
Constant value: **56**

CATEGORY_MODEL

public static final int **CATEGORY_MODEL**

Identifies a resource as being of type Category Model
Constant value: **57**

PERMISSION

public static final int **PERMISSION**

Constant value: **58**

DRILLDOWN

public static final int **DRILLDOWN**

Constant value: **59**

DRILLDOWN_LIST

public static final int **DRILLDOWN_LIST**

Constant value: **60**

CONFIGURATION_ITEM

public static final int **CONFIGURATION_ITEM**

Constant value: **61**

SAVED_SEARCH

public static final int **SAVED_SEARCH**

Constant value: **62**

SEARCH

public static final int **SEARCH**

Constant value: **63**

GROUP_TYPES_ARRAY

public static final int **GROUP_TYPES_ARRAY**

An array describing all of the resources that are of type group. #GROUP, #USER_SHARED_ACCESSIBLE_GROUP, #USER_ACCESSIBLE_GROUP, #UNASSIGNED_RESOURCES_GROUP, #QUERY_GROUP, #NETWORK_CATEGORY, #ATTACHMENT_ONLY_GROUP,

GROUP_TYPES

public static final java.util.Set **GROUP_TYPES**

A Set containing resource types considered Group types.

See Also:

[GROUP_TYPES_ARRAY](#)

Constructors

ResourceTypes

public **ResourceTypes**()

com.arcsight.product.manager.resource.service.v1.model Class SessionProfile

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.SessionProfile

All Implemented Interfaces:
Serializable

public class **SessionProfile**
extends Object
implements Serializable

This class the profile for current login session

Constructor Summary

public	SessionProfile()

Method Summary

List	getAdminFeatureAvailabilities() Gets the list of AdminFeatureAvailability of this session profile.
UserPreference	getManagementPreference() Gets the user preference of this session profile.
String	getManagerVersionString() Gets the string value of manager version for this session profile.
User	getUser() Gets this session profile's user.
boolean	isAdministrator() Tests whether this session profile's user belongs to the administrator group.
void	setAdminFeatureAvailabilities(List adminFeatureAvailabilities) Sets the list of AdminFeatureAvailability for this session profile.
void	setAdministrator(boolean administrator) Sets whether this session profile's user belongs to the administrator group.
void	setManagementPreference(UserPreference managementPreference) Sets the user preference for this session profile.
void	setManagerVersionString(String managerVersionString) Sets the string value of manager version for this session profile.

void	setUser (User user) Sets the user for this session profile.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

SessionProfile

`public SessionProfile()`

Methods

isAdministrator

`public boolean isAdministrator()`

Tests whether this session profile's user belongs to the administrator group.

Returns:

True if this session profile's user belongs to the administrator group.

setAdministrator

`public void setAdministrator(boolean administrator)`

Sets whether this session profile's user belongs to the administrator group.

Parameters:

`administrator` - If true, this session profile's user belongs to the administrator group.

getUser

`public User getUser()`

Gets this session profile's user.

Returns:

This session profile's user.

setUser

`public void setUser(User user)`

Sets the user for this session profile.

Parameters:

user - The user of this session profile to set.

getManagementPreference

```
public UserPreference getManagementPreference()
```

Gets the user preference of this session profile.

Returns:

The user preference of this session profile.

setManagementPreference

```
public void setManagementPreference(UserPreference managementPreference)
```

Sets the user preference for this session profile.

Parameters:

managementPreference - The user preference to set for this session profile.

getAdminFeatureAvailabilities

```
public List getAdminFeatureAvailabilities()
```

Gets the list of AdminFeatureAvailability of this session profile.

Returns:

List of AdminFeatureAvailability of this session profile.

setAdminFeatureAvailabilities

```
public void setAdminFeatureAvailabilities(List adminFeatureAvailabilities)
```

Sets the list of AdminFeatureAvailability for this session profile.

Parameters:

adminFeatureAvailabilities - List of AdminFeatureAvailability to set for this session profile.

getManagerVersionString

```
public String getManagerVersionString()
```

Gets the string value of manager version for this session profile.

Returns:

The string value of manager version.

setManagerVersionString

```
public void setManagerVersionString(String managerVersionString)
```

Sets the string value of manager version for this session profile.

Parameters:

`managerVersionString` - The string value of manager version to set for this session profile.

com.arcsight.product.manager.resource.service.v1.model

Class Severity

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.Severity

public class **Severity**
extends Object

Constructor Summary

public	Severity() Default constructor to make Axis happy.

Method Summary

String	getLevel()
String	getName()
void	setLevel(String level)
void	setName(String name)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

Severity

public **Severity()**

Default constructor to make Axis happy.

Methods

getLevel

public String **getLevel()**

Returns:
the severity level

setLevel

public void **setLevel**(String level)

Parameters:
level

getName

public String **getName**()

Returns:
the severity name

setName

public void **setName**(String name)

Parameters:
name

com.arcsight.product.manager.resource.service.v1.model

Interface Typeable

public interface **Typeable**
extends

Field Summary	
public static final	ACTIVE_TUPLE_TARGET_NAME The target object name for a active tuple definition. Value: ActiveTuple
public static final	AGENT_MESSAGE_TYPE_LABEL The target object name for an alert page serializer. Value: Agent Messages
public static final	ALERT_TARGET_NAME The target object name for an alert serializer. Value: Alert
public static final	ANNOTATION_UPDATE HOLDER_TYPE_LABEL the target object name for patterns Value: EventAnnotationUpdateHolder
public static final	ARC_FIELD_VALUE_ARRAY_LIST_TARGET_NAME The target object name for an arc field value array list. Value: ArcFieldValueArrayList
public static final	DATABASE_TABLE_COLUMN_DESCRIPTOR_TARGET_NAME The target object name for a table column descriptors. Value: TableColumnDescriptor
public static final	DATABASE_TABLE_INDEX_TARGET_NAME The target object name for a DatabaseTableRows. Value: TableIndex
public static final	DATABASE_TABLE_PRIMARY_KEY_TARGET_NAME The target object name for a DatabaseTableRows. Value: TablePrimaryKey
public static final	DATABASE_TABLE_ROW_LIST_TARGET_NAME The target object name for a DatabaseTableRows. Value: TableRowList
public static final	DYNA_CHANNEL_BUCKET_LIST_TARGET_NAME The target object name for a DynaChannelBucketList. Value: DynaChannelBucketList

public static final	DYNA_CHANNEL_RANGE_DESCRIPTOR_TARGET_NAME The type name for Dyna Channel range descriptor Value: DynaChannelRangeDescriptor
public static final	EVENT_GRAPH_TARGET_NAME The target object name for an event graph. Value: EventGraph
public static final	EVENT_TYPE_LABEL The target object name for an alert serializer. Value: Events
public static final	GRAPH_TYPE_LABEL The target object name for a graph. Value: Graph
public static final	GUI_ALERT_TARGET_NAME The target object name for an alert serializer. Value: GuiAlert
public static final	GUI_EVENT_TYPE_LABEL The target object name for an alert serializer. Value: Gui Alerts
public static final	HEARTBEAT_TARGET_NAME The target object name for a Hearbeat serializer. Value: Heartbeat
public static final	HEARTBEAT_TYPE_LABEL The target object name for a Hearbeat serializer. Value: Heartbeats
public static final	INTER_COMPONENT_MESSAGE_TARGET_NAME The target object name for an alert page serializer. Value: AgentMessage
public static final	LONG_TARGET_NAME The target object name for a long object within a cache. Value: Long
public static final	MARK_SIMILAR_CONFIG_TYPE_LABEL the target object name for patterns Value: MarkSimilarConfig
public static final	MODULUS_PAGE_TYPE_LABEL The target object name for an alert page serializer. Value: Alert Pages
public static final	NULL_TARGET_NAME The target name to use when there is not one available. Value: SecurityEvent

public static final	<u>PACKAGE_BUNDLE_TARGET_NAME</u> The type name for the package system. Value: PackageBundle
public static final	<u>PATTERN_OBJECT_TYPE_NAME</u> the target object name for patterns Value: PatternObj
public static final	<u>PAYLOAD_REQUEST_EVENT_STATUS_TARGET_NAME</u> The target object name for a PayloadRequestEventStatus. Value: PayloadRequestEventStatus
public static final	<u>PAYLOAD_REQUEST_EVENT_STATUS_TYPE_LABEL</u> The target object name for a PayloadRequestEventStatus. Value: Payload Request Event Statuses
public static final	<u>PAYLOAD_TARGET_NAME</u> The target object name for a payload. Value: Payload
public static final	<u>PAYLOAD_TYPE_LABEL</u> The target object name for a payload. Value: Payloads
public static final	<u>PENDING_ALERT_OBJECT_TYPE_NAME</u> the target object name for patterns Value: PendingAlert
public static final	<u>RESOURCE_CHANGE_TARGET_NAME</u> The target object name for a resource change. Value: ResourceChange
public static final	<u>RESOURCE_CHANGE_TYPE_LABEL</u> The target object name for a resource change. Value: Resource Changes
public static final	<u>RESOURCE_SEARCH_HITS_TARGET_NAME</u> The target object name for resource search hits. Value: ResSearchHits
public static final	<u>RESOURCE_VALIDATION_RESULT_TARGET_NAME</u> The target object name for resource validation result. Value: ResourceValidationResult
public static final	<u>SECURITY_EVENT_TARGET_NAME</u> The target object name for a security event serializer. Value: SecurityEvent
public static final	<u>SEQUENTIAL_PAGE_TARGET_NAME</u> The target object name for a string message. Value: SequentialAlertPage

public static final	SEQUENTIAL_PAGE_TYPE_LABEL The target object name for a string message. Value: Sequential Alert Pages
public static final	SEQUENTIAL_SECURITY_EVENT_TARGET_NAME The target object name for a sequential security event serializer. Value: SequentialSecurityEvent
public static final	SET_CHANNEL_FILTER_MESSAGE_TARGET_NAME The target object name for a set channel filter message. Value: SetChannelFilterMessage
public static final	SET_CHANNEL_FILTER_MESSAGE_TYPE_LABEL The target object name for a set channel filter message. Value: Set Channel Filter Messages
public static final	STRING_MESSAGE_TARGET_NAME The target object name for a string message. Value: StringMessage
public static final	STRING_MESSAGE_TYPE_LABEL The target object name for a string message. Value: String Messages
public static final	STRING_TARGET_NAME The target object name for a key within a cache. Value: String
public static final	TYPE_ID_PACKAGE_BUNDLE Broker type value for an security event broker Value: -2
public static final	TYPE_ID_SECURITY_EVENT Broker type value for an security event broker Value: -1

Method Summary

abstract String	getObjectTypeName() Returns the object target id type for this object.

Fields

SECURITY_EVENT_TARGET_NAME

public static final java.lang.String **SECURITY_EVENT_TARGET_NAME**

The target object name for a security event serializer.
Constant value: **SecurityEvent**

SEQUENTIAL_SECURITY_EVENT_TARGET_NAME

```
public static final java.lang.String SEQUENTIAL_SECURITY_EVENT_TARGET_NAME
```

The target object name for a sequential security event serializer.
Constant value: **SequentialSecurityEvent**

NULL_TARGET_NAME

```
public static final java.lang.String NULL_TARGET_NAME
```

The target name to use when there is not one available.
Constant value: **SecurityEvent**

ALERT_TARGET_NAME

```
public static final java.lang.String ALERT_TARGET_NAME
```

The target object name for an alert serializer.
Constant value: **Alert**

GUI_ALERT_TARGET_NAME

```
public static final java.lang.String GUI_ALERT_TARGET_NAME
```

The target object name for an alert serializer.
Constant value: **GuiAlert**

HEARTBEAT_TARGET_NAME

```
public static final java.lang.String HEARTBEAT_TARGET_NAME
```

The target object name for a Hearbeat serializer.
Constant value: **Heartbeat**

SEQUENTIAL_PAGE_TARGET_NAME

```
public static final java.lang.String SEQUENTIAL_PAGE_TARGET_NAME
```

The target object name for a string message.
Constant value: **SequentialAlertPage**

INTER_COMPONENT_MESSAGE_TARGET_NAME

```
public static final java.lang.String INTER_COMPONENT_MESSAGE_TARGET_NAME
```

The target object name for an alert page serializer.
Constant value: **AgentMessage**

RESOURCE_CHANGE_TARGET_NAME

```
public static final java.lang.String RESOURCE_CHANGE_TARGET_NAME
```

The target object name for a resource change.
Constant value: **ResourceChange**

STRING_TARGET_NAME

public static final java.lang.String **STRING_TARGET_NAME**

The target object name for a key within a cache.
Constant value: **String**

LONG_TARGET_NAME

public static final java.lang.String **LONG_TARGET_NAME**

The target object name for a long object within a cache.
Constant value: **Long**

SET_CHANNEL_FILTER_MESSAGE_TARGET_NAME

public static final java.lang.String **SET_CHANNEL_FILTER_MESSAGE_TARGET_NAME**

The target object name for a set channel filter message.
Constant value: **SetChannelFilterMessage**

STRING_MESSAGE_TARGET_NAME

public static final java.lang.String **STRING_MESSAGE_TARGET_NAME**

The target object name for a string message.
Constant value: **StringMessage**

RESOURCE_SEARCH_HITS_TARGET_NAME

public static final java.lang.String **RESOURCE_SEARCH_HITS_TARGET_NAME**

The target object name for resource search hits.
Constant value: **ResSearchHits**

PAYLOAD_TARGET_NAME

public static final java.lang.String **PAYLOAD_TARGET_NAME**

The target object name for a payload.
Constant value: **Payload**

PAYLOAD_REQUEST_EVENT_STATUS_TARGET_NAME

public static final java.lang.String **PAYLOAD_REQUEST_EVENT_STATUS_TARGET_NAME**

The target object name for a PayloadRequestEventStatus.
Constant value: **PayloadRequestEventStatus**

DATABASE_TABLE_ROW_LIST_TARGET_NAME

public static final java.lang.String **DATABASE_TABLE_ROW_LIST_TARGET_NAME**

The target object name for a DatabaseTableRows.

Constant value: **TableRowList**

DATABASE_TABLE_COLUMN_DESCRIPTOR_TARGET_NAME

```
public static final java.lang.String DATABASE_TABLE_COLUMN_DESCRIPTOR_TARGET_NAME
```

The target object name for a table column descriptors.
Constant value: **TableColumnDescriptor**

DATABASE_TABLE_PRIMARY_KEY_TARGET_NAME

```
public static final java.lang.String DATABASE_TABLE_PRIMARY_KEY_TARGET_NAME
```

The target object name for a DatabaseTableRows.
Constant value: **TablePrimaryKey**

DATABASE_TABLE_INDEX_TARGET_NAME

```
public static final java.lang.String DATABASE_TABLE_INDEX_TARGET_NAME
```

The target object name for a DatabaseTableRows.
Constant value: **TableIndex**

ACTIVE_TUPLE_TARGET_NAME

```
public static final java.lang.String ACTIVE_TUPLE_TARGET_NAME
```

The target object name for a active tuple definition.
Constant value: **ActiveTuple**

EVENT_GRAPH_TARGET_NAME

```
public static final java.lang.String EVENT_GRAPH_TARGET_NAME
```

The target object name for an event graph.
Constant value: **EventGraph**

DYNA_CHANNEL_BUCKET_LIST_TARGET_NAME

```
public static final java.lang.String DYNA_CHANNEL_BUCKET_LIST_TARGET_NAME
```

The target object name for a DynaChannelBucketList.
Constant value: **DynaChannelBucketList**

ARC_FIELD_VALUE_ARRAY_LIST_TARGET_NAME

```
public static final java.lang.String ARC_FIELD_VALUE_ARRAY_LIST_TARGET_NAME
```

The target object name for an arc field value array list.
Constant value: **ArcFieldValueArrayList**

EVENT_TYPE_LABEL

```
public static final java.lang.String EVENT_TYPE_LABEL
```


The target object name for an alert serializer.
Constant value: **Events**

GUI_EVENT_TYPE_LABEL

```
public static final java.lang.String GUI_EVENT_TYPE_LABEL
```

The target object name for an alert serializer.
Constant value: **Gui Alerts**

HEARTBEAT_TYPE_LABEL

```
public static final java.lang.String HEARTBEAT_TYPE_LABEL
```

The target object name for a Hearbeat serializer.
Constant value: **Heartbeats**

MODULUS_PAGE_TYPE_LABEL

```
public static final java.lang.String MODULUS_PAGE_TYPE_LABEL
```

The target object name for an alert page serializer.
Constant value: **Alert Pages**

SEQUENTIAL_PAGE_TYPE_LABEL

```
public static final java.lang.String SEQUENTIAL_PAGE_TYPE_LABEL
```

The target object name for a string message.
Constant value: **Sequential Alert Pages**

AGENT_MESSAGE_TYPE_LABEL

```
public static final java.lang.String AGENT_MESSAGE_TYPE_LABEL
```

The target object name for an alert page serializer.
Constant value: **Agent Messages**

RESOURCE_CHANGE_TYPE_LABEL

```
public static final java.lang.String RESOURCE_CHANGE_TYPE_LABEL
```

The target object name for a resource change.
Constant value: **Resource Changes**

SET_CHANNEL_FILTER_MESSAGE_TYPE_LABEL

```
public static final java.lang.String SET_CHANNEL_FILTER_MESSAGE_TYPE_LABEL
```

The target object name for a set channel filter message.
Constant value: **Set Channel Filter Messages**

STRING_MESSAGE_TYPE_LABEL

```
public static final java.lang.String STRING_MESSAGE_TYPE_LABEL
```

The target object name for a string message.
Constant value: **String Messages**

PAYLOAD_TYPE_LABEL

public static final java.lang.String **PAYLOAD_TYPE_LABEL**

The target object name for a payload.
Constant value: **Pay loads**

PAYLOAD_REQUEST_EVENT_STATUS_TYPE_LABEL

public static final java.lang.String **PAYLOAD_REQUEST_EVENT_STATUS_TYPE_LABEL**

The target object name for a PayloadRequestEventStatus.
Constant value: **Payload Request Event Statuses**

GRAPH_TYPE_LABEL

public static final java.lang.String **GRAPH_TYPE_LABEL**

The target object name for a graph.
Constant value: **Graph**

PATTERN_OBJECT_TYPE_NAME

public static final java.lang.String **PATTERN_OBJECT_TYPE_NAME**

the target object name for patterns
Constant value: **PatternObj**

MARK_SIMILAR_CONFIG_TYPE_LABEL

public static final java.lang.String **MARK_SIMILAR_CONFIG_TYPE_LABEL**

the target object name for patterns
Constant value: **MarkSimilarConfig**

ANNOTATION_UPDATE HOLDER_TYPE_LABEL

public static final java.lang.String **ANNOTATION_UPDATE HOLDER_TYPE_LABEL**

the target object name for patterns
Constant value: **EventAnnotationUpdateHolder**

TYPE_ID_SECURITY_EVENT

public static final int **TYPE_ID_SECURITY_EVENT**

Broker type value for an security event broker
Constant value: **-1**

TYPE_ID_PACKAGE_BUNDLE

```
public static final int TYPE_ID_PACKAGE_BUNDLE
```

Broker type value for an security event broker
Constant value: **-2**

PENDING_ALERT_OBJECT_TYPE_NAME

```
public static final java.lang.String PENDING_ALERT_OBJECT_TYPE_NAME
```

the target object name for patterns
Constant value: **PendingAlert**

RESOURCE_VALIDATION_RESULT_TARGET_NAME

```
public static final java.lang.String RESOURCE_VALIDATION_RESULT_TARGET_NAME
```

The target object name for resource validation result.
Constant value: **ResourceValidationResult**

PACKAGE_BUNDLE_TARGET_NAME

```
public static final java.lang.String PACKAGE_BUNDLE_TARGET_NAME
```

The type name for the package system. These are not stored in the database or serialized, but the type name is needed by the package framework.
Constant value: **PackageBundle**

See Also:

```
createArchivalHandler(String,String,String)  
com.arcsight.common.packageresource.bundle.ZipImportPackageBundle  
com.arcsight.common.packageresource.bundle.ZipExportPackageBundle
```

DYNA_CHANNEL_RANGE_DESCRIPTOR_TARGET_NAME

```
public static final java.lang.String DYNA_CHANNEL_RANGE_DESCRIPTOR_TARGET_NAME
```

The type name for Dyna Channel range descriptor
Constant value: **DynaChannelRangeDescriptor**

Methods

getObjectTypeName

```
public abstract String getObjectTypeName()
```

Returns the object target id type for this object. This is based upon the constants in this class and the ResourceTypes class.

See Also:

```
com.arcsight.common.resource.ResourceTypes
```

com.arcsight.product.manager.resource.service.v1.model Class TypeConstants

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.TypeConstants

public class **TypeConstants**
extends Object

Represents some common type specific constants used through the code.

See Also:

com.arcsight.common.introspection.TypeConstants

Field Summary

public static final	MAX_DATETIME Value: 9223372036854775807
public static final	UNKNOWN_ADDRESS Value: -9223372036854775808
public static final	UNKNOWN_BOOLEAN Value: false
public static final	UNKNOWN_BYTE Value: -128
public static final	UNKNOWN_DATETIME Value: -9223372036854775808
public static final	UNKNOWN_DOUBLE Value: 4.9E-324
public static final	UNKNOWN_INTEGER Value: -2147483648
public static final	UNKNOWN_LONG Value: -9223372036854775808

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

UNKNOWN_INTEGER

public static final int UNKNOWN_INTEGER

Constant value: -2147483648

UNKNOWN_LONG

public static final long UNKNOWN_LONG

Constant value: -9223372036854775808

UNKNOWN_ADDRESS

public static final long UNKNOWN_ADDRESS

Constant value: -9223372036854775808

UNKNOWN_DATETIME

public static final long UNKNOWN_DATETIME

Constant value: -9223372036854775808

MAX_DATETIME

public static final long MAX_DATETIME

Constant value: 9223372036854775807

UNKNOWN_DOUBLE

public static final double UNKNOWN_DOUBLE

Constant value: 4.9E-324

UNKNOWN_BYTE

public static final byte UNKNOWN_BYTE

Constant value: -128

UNKNOWN_BOOLEAN


public static final boolean UNKNOWN_BOOLEAN

Constant value: **false**

com.arcsight.product.manager.resource.service.v1.model

Class User

java.lang.Object



All Implemented Interfaces:
Serializable

public class **User**
extends [Resource](#)

This class represents a User

Nested Class Summary

class	User.UserTypeEnum User.UserTypeEnum

Constructor Summary

public	User()

Method Summary

String	getAuthenticationState() Gets the state of authentication for the user
String	getDepartment() Gets the name of the department the user belongs to
String	getEmail() Gets the email of the user
long[]	getFailedLoginTimes() Gets the array of the long values of failed login times
String	getFax() Gets the fax of the user
String	getFirstName() Returns the first name of the user.
Group[]	getGroups() Gets the array of groups which are/were the parents of the user.
String	getIntegrationParametersXML()

long	<u>getLastFailedLoginTime()</u> Gets the long value of the last failed login time.
String	<u>getLastName()</u> Gets the last name of the user
long	<u>getLastPasswordChangeDate()</u> Gets the date when the password is changed last time.
String	<u>getPager()</u> Gets the pager of the user
String	<u>getPassword()</u> Gets the password(phash) of the user
String	<u>getPhone()</u> Gets the string of the phone of the user
String[]	<u>getPreviousPasswordHashes()</u> Gets the array of the string values of the previous password hash values.
static long	<u>getSerialVersionUID()</u> Gets the serial version UID
long[]	<u>getSuccessfulLoginTimes()</u> Gets the array of the successfully login times.
String	<u>getTitle()</u> Gets the title of the user
String	<u>getUserType()</u> Gets the type of user
boolean	<u>isEnabled()</u> Determines whether this user is allowed to login
boolean	<u>isHasNotification()</u> Determines whether the user has notification
void	<u>setAuthenticationState()</u> (String authenticationState) Sets the state of authentication for the user
void	<u>setDepartment()</u> (String department) Sets the department of the user
void	<u>setEmail()</u> (String email) Sets the email of the user
void	<u>setEnabled()</u> (boolean enabled) Sets whether the user is allowed to login
void	<u>setFailedLoginTimes()</u> (long[] failedLoginTimes) Sets the array of the long values of failed login times.

void	<u>setFax</u> (String fax) Sets the fax of the user
void	<u>setFirstName</u> (String firstName) Sets the first name of the user.
void	<u>setGroups</u> (Group[] groups) Sets the array of groups which are/were the parents of the user
void	<u>setHasNotification</u> (boolean hasNotification) Sets whether the user has notification
void	<u>setIntegrationParametersXML</u> (String integrationParametersXML) Sets the integrationParametersXML for the user
void	<u>setLastFailedLoginTime</u> (long lastFailedLoginTime) Sets the long value of the last failed login time.
void	<u>setLastName</u> (String lastName) Sets the last name of the user
void	<u>setLastPasswordChangeDate</u> (long lastPasswordChangeDate) Sets the long value of the date when the password is changed last time.
void	<u>setPager</u> (String pager) Sets the pager of the user
void	<u>setPassword</u> (String password) Sets the password(phash) of the user
void	<u>setPhone</u> (String phone) Sets the phone of the user
void	<u>setPreviousPasswordHashes</u> (String[] previousPasswordHashes) Set the array of the string values of the previous password hash values
void	<u>setSuccessfulLoginTimes</u> (long[] successfulLoginTimes) Sets the array of the long values for successfully login times.
void	<u>setTitle</u> (String title) Sets the title of the user
void	<u>setUserType</u> (String userType) Sets the type of user

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

User

```
public User()
```

Methods

isEnabled

```
public boolean isEnabled()
```

Determines whether this user is allowed to login

Returns:

True if the user is enabled; otherwise, false.

setEnabled

```
public void setEnabled(boolean enabled)
```

Sets whether the user is allowed to login

Parameters:

`enabled` - The enabled to be set

getFirstName

```
public String getFirstName()
```

Returns the first name of the user.

Returns:

The firstName

setFirstName

```
public void setFirstName(String firstName)
```

Sets the first name of the user.

Parameters:

firstName - The firstName to set

getLastName

```
public String getLastName()
```

Gets the last name of the user

Returns:

The lastName

setLastName

```
public void setLastName(String lastName)
```

Sets the last name of the user

Parameters:

lastName - The lastName to set

getTitle

```
public String getTitle()
```

Gets the title of the user

Returns:

The title

setTitle

```
public void setTitle(String title)
```

Sets the title of the user

Parameters:

title - The title to set

getDepartment

```
public String getDepartment()
```

Gets the name of the department the user belongs to

Returns:

The name department which the user belongs to

setDepartment

```
public void setDepartment(String department)
```

Sets the department of the user

Parameters:

department - The department to set

getEmail

```
public String getEmail()
```

Gets the email of the user

Returns:

The email of the user

setEmail

```
public void setEmail(String email)
```

Sets the email of the user

Parameters:

email - The email to set

getPhone

```
public String getPhone()
```

Gets the string of the phone of the user

Returns:

The phone of the user

setPhone

```
public void setPhone(String phone)
```

Sets the phone of the user

Parameters:

phone - The phone to set

getFax

```
public String getFax()
```

Gets the fax of the user

Returns:
The fax

setFax

public void **setFax**(String fax)

Sets the fax of the user

Parameters:
fax - The fax to set

getPager

public String **getPager**()

Gets the pager of the user

Returns:
The pager

setPager

public void **setPager**(String pager)

Sets the pager of the user

Parameters:
pager - The pager to set

getPassword

public String **getPassword**()

Gets the password(phrase) of the user

Returns:
The password(phrase) of the user

setPassword

public void **setPassword**(String password)

Sets the password(phrase) of the user

Parameters:
password - The password(phrase) to set

isHasNotification

public boolean **isHasNotification**()

Determines whether the user has notification

Returns:

True if the user has Notification

setHasNotification

```
public void setHasNotification(boolean hasNotification)
```

Sets whether the user has notification

Parameters:

hasNotification - The hasNotification to set

getAuthenticationState

```
public String getAuthenticationState()
```

Gets the state of authentication for the user

Returns:

The state of authentication

setAuthenticationState

```
public void setAuthenticationState(String authenticationState)
```

Sets the state of authentication for the user

Parameters:

authenticationState - The authenticationState to set

getIntegrationParametersXML

```
public String getIntegrationParametersXML()
```

Returns:

the integrationParametersXML

setIntegrationParametersXML

```
public void setIntegrationParametersXML(String integrationParametersXML)
```

Sets the integrationParametersXML for the user

Parameters:**getUserType**

```
public String getUserType()
```

Gets the type of user

Returns:

The type of user, the string of one of UserTypeEnums. See [User .UserTypeEnum](#)

setUserType

```
public void setUserType(String userType)
```

Sets the type of user

Parameters:

userType - The type of the user. See [User .UserTypeEnum](#)

getLastPasswordChangeDate

```
public long getLastPasswordChangeDate()
```

Gets the date when the password is changed last time.

Returns:

The date when the password is changed last time.

setLastPasswordChangeDate

```
public void setLastPasswordChangeDate(long lastPasswordChangeDate)
```

Sets the long value of the date when the password is changed last time.

Parameters:

lastPasswordChangeDate - The long value of the date when the password is changed last time.

getSuccessfulLoginTimes

```
public long[] getSuccessfulLoginTimes()
```

Gets the array of the successfully login times.

Returns:

The array of the successfully login times.

setSuccessfulLoginTimes

```
public void setSuccessfulLoginTimes(long[] successfulLoginTimes)
```

Sets the array of the long values for successfully login times.

Parameters:

successfulLoginTimes - The array of the long values for successfully login times.

getFailedLoginTimes

```
public long[] getFailedLoginTimes()
```

Gets the array of the long values of failed login times

Returns:
the failedLoginTimes

setFailedLoginTimes

```
public void setFailedLoginTimes(long[] failedLoginTimes)
```

Sets the array of the long values of failed login times.

Parameters:
failedLoginTimes - The array of the long values of failed login times

getLastFailedLoginTime

```
public long getLastFailedLoginTime()
```

Gets the long value of the last failed login time.

Returns:
The long value of the last failed login time.

setLastFailedLoginTime

```
public void setLastFailedLoginTime(long lastFailedLoginTime)
```

Sets the long value of the last failed login time.

Parameters:
lastFailedLoginTime - The long value of the last failed login time.

getPreviousPasswordHashes

```
public String[] getPreviousPasswordHashes()
```

Gets the array of the string values of the previous password hash values.

Returns:
the previousPasswordHashes

setPreviousPasswordHashes

```
public void setPreviousPasswordHashes(String[] previousPasswordHashes)
```

Set the array of the string values of the previous password hash values

Parameters:
previousPasswordHashes - The array of the string values of the previous password hash values

getSerialversionuid

```
public static long getSerialversionuid()
```

Gets the serial version UID

Returns:
the serialversionuid

setGroups

public void **setGroups**([Group\[\]](#) groups)

Sets the array of groups which are/were the parents of the user

Parameters:
groups - The groups with the parent relationship to the user

getGroups

public [Group\[\]](#) **getGroups**()

Gets the array of groups which are/were the parents of the user. The groups could be enabled or disabled.

Returns:
The array of groups which are/were the parents of the user.

com.arcsight.product.manager.resource.service.v1.model

Class User.UserTypeEnum

java.lang.Object
└ java.lang.Enum
└ com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum

All Implemented Interfaces:
Serializable, Comparable

public static class **User.UserTypeEnum**
extends Enum

Defines the enum types for user types.

Field Summary	
public static final	USERTYPE_AGENT_INSTALLER User type for a connector installer.
public static final	USERTYPE_ARCHIVE User type for an archive utility.
public static final	USERTYPE_INTERACTIVE User type for a normal user, who has privileges to use features & functions in ArcSight Console, ArcSight Web, & ArcSight Command Center.
public static final	USERTYPE_INTERNAL User type for a server internal user, that is, the root user.
public static final	USERTYPE_MANAGEMENT_TOOL User type for a management tool.
public static final	USERTYPE_REMOTE_SYSTEM User type for a remote system user, which isn't an actual user.
public static final	USERTYPE_SUPERAGENT User type for a forwarding connector.
public static final	USERTYPE_WEB_ONLY User type for a web user, who has privilege to use ArcSight Web & Command Center but not ArcSight Console.

Method Summary	
static User.UserTypeEnum	valueOf (String name)
static User.UserTypeEnum[]	values ()

Methods inherited from class `java.lang.Enum`

`compareTo`, `equals`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

USERTYPE_INTERNAL

```
public static final
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum
USERTYPE_INTERNAL
```

User type for a server internal user, that is, the root user.

USERTYPE_REMOTE_SYSTEM

```
public static final
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum
USERTYPE_REMOTE_SYSTEM
```

User type for a remote system user, which isn't an actual user.

USERTYPE_INTERACTIVE

```
public static final
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum
USERTYPE_INTERACTIVE
```

User type for a normal user, who has privileges to use features & functions in ArcSight Console, ArcSight Web, & ArcSight Command Center.

USERTYPE_MANAGEMENT_TOOL

```
public static final
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum
USERTYPE_MANAGEMENT_TOOL
```

User type for a management tool. It only has privilege to run certain management tools used in conjunction with network management products.

USERTYPE_SUPERAGENT

```
public static final
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum
USERTYPE_SUPERAGENT
```

User type for a forwarding connector. That is, (non human) account for forwarding events to a destination.

USERTYPE_ARCHIVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum USERTYPE_ARCHIVE
```

User type for an archive utility. It only has privilege to run the archive utility.

USERTYPE_AGENT_INSTALLER

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum  
USERTYPE_AGENT_INSTALLER
```

User type for a connector installer. That is, (non human) account for adding/registering SmartConnectors in ESM.

USERTYPE_WEB_ONLY

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.User.UserTypeEnum  
USERTYPE_WEB_ONLY
```

User type for a web user, who has privilege to use ArcSight Web & Command Center but not ArcSight Console.

Methods

values

```
public static User.UserTypeEnum\[\] values()
```

valueOf

```
public static User.UserTypeEnum valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model

Class UserPreference

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.UserPreference

All Implemented Interfaces:
Serializable

```
public class UserPreference
extends Object
implements Serializable
```

User preferences stores the data that drives the Home Page. It is a big BLOB field that contains several preferences, including also ManagementConsole.

JSON prototype

Field Summary

public static final transient	MANAGEMENT_UI_ID The static string value "MANAGEMENT_UI_ID" Value: MANAGEMENT_UI_ID

Constructor Summary

public	UserPreference()

Method Summary

int	getDashboardRefreshRate() Gets the dashboard refresh rate for this user preference.
String	getId() Gets the ID of this user preference.
String	getLocale() Gets the locale (ID) of this user preference.
List	getModules() Gets the list of Modules for this user preference.
String	getSkin() Gets the information about the skin of this user preference.
boolean	isEffectsEnabled() Returns true if this user preference' effects is enabled.

boolean	<u>isEnabledAnimationChart()</u> Tests whether animation chart of this user preference is enabled.
boolean	<u>isLoggingDebugEnabled()</u> Tests whether this user preference's logging debug is enabled.
boolean	<u>isLoggingEnabled()</u> Returns if this user preference's logging is enabled.
boolean	<u>isLoggingPanelEnabled()</u> Test whether this user preference's logging panel is enabled.
boolean	<u>isLoggingPopupEnabled()</u> Tests whether this user preference's logging pop-up is enabled.
void	<u>setDashboardRefreshRate(int dashboardRefreshRate)</u> Sets the dashboard refresh rate for this user preference.
void	<u>setEffectsEnabled(boolean effectsEnabled)</u> Sets whether this user preference's effects is enabled.
void	<u>setEnabledAnimationChart(boolean enableAnimationChart)</u> Sets whether animation chart of this user preference is enabled.
void	<u>setId(String id)</u> Sets the ID of this user preference.
void	<u>setLocale(String locale)</u> Sets the locale (ID) for this user preference.
void	<u>setLoggingDebugEnabled(boolean loggingDebugEnabled)</u> Sets whether this user preference's logging debug is enabled.
void	<u>setLoggingEnabled(boolean loggingEnabled)</u> Sets whether this user preference's effects is enabled.
void	<u>setLoggingPanelEnabled(boolean loggingPanelEnabled)</u> Sets whether this user preference's logging panel is enabled.
void	<u>setLoggingPopupEnabled(boolean loggingPopupEnabled)</u> Sets whether this user preference's logging pop-up is enabled.
void	<u>setModules(List modules)</u> Sets the list of Modules for this user preference.
void	<u>setSkin(String skin)</u> Sets the information about the skin of this user preference.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

MANAGEMENT_UI_ID

```
public static final transient java.lang.String MANAGEMENT_UI_ID
```

The static string value "MANAGEMENT_UI_ID"
Constant value: **MANAGEMENT_UI_ID**

Constructors

UserPreference

```
public UserPreference()
```

Methods

isEffectsEnabled

```
public boolean isEffectsEnabled()
```

Returns true if this user preference' effects is enabled. Otherwise, returns false.

Returns:

Returns true if this user preference' effects is enabled.

setEffectsEnabled

```
public void setEffectsEnabled(boolean effectsEnabled)
```

Sets whether this user preference's effects is enabled.

Parameters:

effectsEnabled - If true, enables this user preference's effects.

isLoggingEnabled

```
public boolean isLoggingEnabled()
```

Returns if this user preference's logging is enabled.

Returns:

the loggingEnabled

setLoggingEnabled

```
public void setLoggingEnabled(boolean loggingEnabled)
```

Sets whether this user preference's effects is enabled.

Parameters:

loggingEnabled - If true, enables this user preference's logging.

isLoggingPanelEnabled

public boolean **isLoggingPanelEnabled**()

Test whether this user preference's logging panel is enabled.

Returns:

True if this user preference's logging panel is enabled; otherwise, false.

setLoggingPanelEnabled

public void **setLoggingPanelEnabled**(boolean loggingPanelEnabled)

Sets whether this user preference's logging panel is enabled.

Parameters:

loggingPanelEnabled - If true, this user preference's logging panel is enabled.

isLoggingPopupEnabled

public boolean **isLoggingPopupEnabled**()

Tests whether this user preference's logging pop-up is enabled.

Returns:

True if this user preference's logging pop-up is enabled.

setLoggingPopupEnabled

public void **setLoggingPopupEnabled**(boolean loggingPopupEnabled)

Sets whether this user preference's logging pop-up is enabled.

Parameters:

loggingPopupEnabled - If true, this user preference's logging pop-up is enabled.

isLoggingDebugEnabled

public boolean **isLoggingDebugEnabled**()

Tests whether this user preference's logging debug is enabled.

Returns:

True if this user preference's logging debug is enabled; otherwise, false.

setLoggingDebugEnabled

public void **setLoggingDebugEnabled**(boolean loggingDebugEnabled)

Sets whether this user preference's logging debug is enabled.

Parameters:

loggingDebugEnabled - If true, this user preference's logging debug is enabled.

getId

public String **getId**()

Gets the ID of this user preference.

Returns:

The ID of this user preference.

setId

public void **setId**(String id)

Sets the ID of this user preference.

Parameters:

id - ID of this user preference to set.

getModules

public List **getModules**()

Gets the list of Modules for this user preference.

Returns:

List of Modules for this user preference.

setModules

public void **setModules**(List modules)

Sets the list of Modules for this user preference.

Parameters:

modules - List of Modules to set for this user preference.

getSkin

public String **getSkin**()

Gets the information about the skin of this user preference.

Returns:

The information about the skin of this user preference.

setSkin

public void **setSkin**(String skin)

Sets the information about the skin of this user preference.

Parameters:

skin - Information about the skin to set for this user preference.

getLocale

```
public String getLocale()
```

Gets the locale (ID) of this user preference.

Returns:

The locale (ID) of this user preference.

setLocale

```
public void setLocale(String locale)
```

Sets the locale (ID) for this user preference.

Parameters:

locale - Locale (ID) of this user preference to set.

getDashboardRefreshRate

```
public int getDashboardRefreshRate()
```

Gets the dashboard refresh rate for this user preference.

Returns:

The dashboard refresh rate for this user preference. Note: the int value -1 will disable refresh.

setDashboardRefreshRate

```
public void setDashboardRefreshRate(int dashboardRefreshRate)
```

Sets the dashboard refresh rate for this user preference.

Parameters:

dashboardRefreshRate - The dashboard refresh rate for this user preference. Note: the int value -1 will disable refresh.

isEnabledAnimationChart

```
public boolean isEnabledAnimationChart()
```

Tests whether animation chart of this user preference is enabled.

Returns:

True if animation chart is enabled; otherwise, false.

setEnabledAnimationChart

```
public void setEnabledAnimationChart(boolean enableAnimationChart)
```

Sets whether animation chart of this user preference is enabled.

Parameters:

enableAnimationChart - If true, enables animation chart for this user preference.

Package

com.arcsight.product.manager.resource.service.v1.model.activelist

com.arcsight.product.manager.resource.service.v1.model.activelist

Class ActiveList

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ [com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList](#)

All Implemented Interfaces:

Serializable

public class **ActiveList**

extends [Resource](#)

Represents an Active List resource.

JSON prototype

Nested Class Summary

class	ActiveList.ActiveListFieldType ActiveList.ActiveListFieldType
class	ActiveList.ActiveListType ActiveList.ActiveListType
class	ActiveList.CaseType ActiveList.CaseType

Constructor Summary

public	ActiveList()

Method Summary

ActiveList.ActiveListType	getActiveListType() Gets the active list type.
int	getCapacity() Gets the maximum number of active list entries the system is to keep in memory.
ActiveList.CaseType	getCaseSensitiveType() Gets the case sensitivity type of the active list.
long	getEntryTimeToLive() Retrieves the amount of time in milliseconds that an entry can remain on this active list before it is removed.
String[]	getFieldNames() Gets the column names of this active list.

String[]	getFieldSubTypes() Gets the subtype of columns of this active list.
ActiveList.ActiveListFieldType[]	getFieldTypes() Gets the field types of the list's columns.
Boolean[]	getKeyFields() Gets the key field information for this active list.
boolean	isMultiMap() Informs whether the active list allows entries such that a single key maps to multiple values.
boolean	isOptimizeData() Specifies whether this is a hash optimized active list.
boolean	isPartialCache() Informs whether additional entries beyond the in-memory capacity are stored and retrieved from the database for this active list.
boolean	isTimePartitioned() Informs whether a partially-cached field based active list is time partitioned.
void	setActiveListType(ActiveList.ActiveListType activeListType) Specifies the type of active list.
void	setCapacity(int capacity) Specifies the maximum number of active list entries the system is to keep in memory.
void	setCaseSensitiveType(ActiveList.CaseType caseSensitiveType) Configures the list to be case-sensitive or case-insensitive.
void	setEntryTimeToLive(long entryTimeToLive) Specifies the amount of time that an entry can remain on this active list before it is removed.
void	setFieldNames(String[] fieldNames) Specifies the column names of this active list.
void	setFieldSubTypes(String[] fieldSubTypes) Specifies the subtype of columns of this active list.
void	setFieldTypes(ActiveList.ActiveListFieldType[] fieldTypes) Specifies the field types of the entries in this active list.
void	setKeyFields(Boolean[] keyFields) Specifies the key fields for the active list.
void	setMultiMap(boolean multiMap) Specifies that the active list allows entries such that a single key may map to multiple values.
void	setOptimizeData(boolean optimizeData) Specifies whether the active list should be hash optimized or not.
void	setPartialCache(boolean partialCache) Specifies that additional entries beyond the in-memory capacity are to be stored and retrieved from the database for this active list.

void	<u>setTimePartitioned</u> (boolean timePartitioned) Specifies whether a partially-cached, field-based active list is time partitioned.

Methods inherited from class <u>com.arcsight.product.manager.resource.service.v1.model.Resource</u>
<u>getAlias</u> , <u>getContentVersionID</u> , <u>getCreatedTime</u> , <u>getCreatedTimestamp</u> , <u>getCreatorName</u> , <u>getDescription</u> , <u>getDisabledReason</u> , <u>getDisplayName</u> , <u>getExternalID</u> , <u>getInactiveReason</u> , <u>getInCache</u> , <u>getLocalID</u> , <u>getModificationCount</u> , <u>getModifiedTime</u> , <u>getModifiedTimestamp</u> , <u>getModifierName</u> , <u>getName</u> , <u>getNotificationGroupIDs</u> , <u>getReference</u> , <u>getReferencePage</u> , <u>getResourceid</u> , <u>getSignature</u> , <u>getState</u> , <u>getSubType</u> , <u>getType</u> , <u>getTypeName</u> , <u>getURI</u> , <u>getVersionID</u> , <u>isAttributeInitializationInProgress</u> , <u>isDeprecated</u> , <u>isDisabled</u> , <u>isInactive</u> , <u>isInitialized</u> , <u>isIsAdditionalLoaded</u> , <u>setAlias</u> , <u>setAttributeInitializationInProgress</u> , <u>setContentVersionID</u> , <u>setCreatedTime</u> , <u>setCreatedTimestamp</u> , <u>setCreatorName</u> , <u>setDeprecated</u> , <u>setDescription</u> , <u>setDisabled</u> , <u>setDisabledReason</u> , <u>setExternalID</u> , <u>setInactive</u> , <u>setInactiveReason</u> , <u>setInCache</u> , <u>setInitialized</u> , <u>setIsAdditionalLoaded</u> , <u>setLocalID</u> , <u>setModificationCount</u> , <u>setModifiedTime</u> , <u>setModifiedTimestamp</u> , <u>setModifierName</u> , <u>setName</u> , <u>setNotificationGroupIDs</u> , <u>setReference</u> , <u>setReferencePage</u> , <u>setResourceid</u> , <u>setState</u> , <u>setSubType</u> , <u>setType</u> , <u>setTypeName</u> , <u>setURI</u> , <u>setVersionID</u>

Methods inherited from class <code>java.lang.Object</code>
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ActiveList

public **ActiveList**()

Methods

isOptimizeData

public boolean **isOptimizeData**()

Specifies whether this is a hash optimized active list.

Returns:
Returns true if this is a hash optimized active list.

setOptimizeData

public void **setOptimizeData**(boolean optimizeData)

Specifies whether the active list should be hash optimized or not. Such an active list stores only the hash code (a number), count, and last modified time in memory. If needed, the complete entry will be retrieved from the database.

Parameters:
optimizeData - True value means this active list will be hash optimized.

getCapacity

public int **getCapacity**()

Gets the maximum number of active list entries the system is to keep in memory.

Returns:

The maximum number of entries which the system keeps in memory for this active list.

setCapacity

public void **setCapacity**(int capacity)

Specifies the maximum number of active list entries the system is to keep in memory.

Parameters:

capacity - The in-memory capacity of this active list.

getEntryTimeToLive

public long **getEntryTimeToLive**()

Retrieves the amount of time in milliseconds that an entry can remain on this active list before it is removed.

Returns:

the amount of time in milliseconds. A value of 0 (zero) means that entries will never expire.

setEntryTimeToLive

public void **setEntryTimeToLive**(long entryTimeToLive)

Specifies the amount of time that an entry can remain on this active list before it is removed.

Parameters:

entryTimeToLive - The amount of time in milliseconds. A value of 0 (zero) means that entries will never expire.

isMultiMap

public boolean **isMultiMap**()

Informs whether the active list allows entries such that a single key maps to multiple values.

Returns:

Returns true if the active list allows entries such that a single key maps to multiple values.

setMultiMap

public void **setMultiMap**(boolean multiMap)

Specifies that the active list allows entries such that a single key may map to multiple values. This setting is not allowed for time partitioned active lists.

Parameters:

multiMap - A true value means that this active list allows a single key to map to multiple values.

isPartialCache

```
public boolean isPartialCache()
```

Informs whether additional entries beyond the in-memory capacity are stored and retrieved from the database for this active list.

Returns:

Returns true if additional entries beyond the in-memory capacity are stored and retrieved from the database.

setPartialCache

```
public void setPartialCache(boolean partialCache)
```

Specifies that additional entries beyond the in-memory capacity are to be stored and retrieved from the database for this active list. This increases capacity but can impact performance. This is a required setting for time partitioned active lists.

Parameters:

partialCache - A true value means that additional entries beyond the in-memory capacity are to be stored and retrieved from the database.

isTimePartitioned

```
public boolean isTimePartitioned()
```

Informs whether a partially-cached field based active list is time partitioned. In a time partitioned active list, older data are the first to age out of the memory to database.

Returns:

Returns true if a partially-cached field based active list is time partitioned.

setTimePartitioned

```
public void setTimePartitioned(boolean timePartitioned)
```

Specifies whether a partially-cached, field-based active list is time partitioned. In such an active list, older data are the first to age out of the memory to database. Fields must include at least a date and a string field that are set as key fields. Without a date key field, the time partitioned setting is ignored.

Parameters:

timePartitioned - A true value means that this active list is to be time partitioned.

getActiveListType

```
public ActiveList.ActiveListType getActiveListType()
```

Gets the active list type. Active lists are either event-based or field-based.

Returns:

Whether active list is EVENT_BASED or FIELD_BASED.

setActiveListType

```
public void setActiveListType(ActiveList.ActiveListType activeListType)
```

Specifies the type of active list.

Parameters:

activeListType - the type of the active list.

getCaseSensitiveType

```
public ActiveList.CaseType getCaseSensitiveType()
```

Gets the case sensitivity type of the active list.

Returns:

The case sensitivity type of the active list.

setCaseSensitiveType

```
public void setCaseSensitiveType(ActiveList.CaseType caseSensitiveType)
```

Configures the list to be case-sensitive or case-insensitive.

Parameters:

caseSensitiveType - The case sensitivity type of this active list.

getFieldNames

```
public String[] getFieldNames()
```

Gets the column names of this active list.

Returns:

The column names of this active list.

setFieldNames

```
public void setFieldNames(String[] fieldNames)
```

Specifies the column names of this active list.

Parameters:

fieldNames - An array of column names of the entries.

getFieldTypes

```
public ActiveList.ActiveListFieldType\[\] getFieldTypes()
```

Gets the field types of the list's columns. This would be in the same order as field names.

Returns:

The type of columns of the entries in this active list.

setFieldTypes

public void **setFieldTypes**([ActiveList.ActiveListFieldType\[\]](#) fieldTypes)

Specifies the field types of the entries in this active list.

Parameters:

fieldTypes - The type of columns of the entries in this active list in the same order as fieldNames.

getFieldSubTypes

public String[] **getFieldSubTypes**()

Gets the subtype of columns of this active list. This would be in the same order as field names.

Returns:

The subtype of columns of this active list.

setFieldSubTypes

public void **setFieldSubTypes**(String[] fieldSubTypes)

Specifies the subtype of columns of this active list.

Parameters:

fieldSubTypes - The subtype of columns in the same order as field types.

getKeyFields

public Boolean[] **getKeyFields**()

Gets the key field information for this active list.

Returns:

A boolean array with true value representing a key field.

setKeyFields

public void **setKeyFields**(Boolean[] keyFields)


Specifies the key fields for the active list.

Parameters:

keyFields - A true value in the array means that corresponding field is a key field.

com.arcsight.product.manager.resource.service.v1.model.activelist

Class ActiveList.ActiveListFieldType



All Implemented Interfaces:
Serializable, Comparable

public static final class **ActiveList.ActiveListFieldType**
extends Enum

Type of a specific column of an active list entry

Field Summary	
public static final	ArchiveableSubobject
public static final	Blob
public static final	Boolean
public static final	Byte
public static final	ByteArray
public static final	Clob
public static final	Date
public static final	Double
public static final	Integer
public static final	IntegerArray
public static final	IPAddress
public static final	IPSubnet
public static final	List

public static final	Long
public static final	LongString
public static final	MacAddress
public static final	Map
public static final	ResourceID
public static final	ResourceReference
public static final	String

Method Summary

static ActiveList.ActiveListFieldType	valueOf (String name)
static ActiveList.ActiveListFieldType[]	values ()

Methods inherited from class `java.lang.Enum`

`compareTo`, `equals`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

String

```
public static final
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField
Type String
```

Integer

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Integer
```

ResourceReference

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType ResourceReference
```

Long

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Long
```

Date

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Date
```

LongString

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType LongString
```

Boolean

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Boolean
```

Map

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Map
```

List

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType List
```

IntegerArray

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType IntegerArray
```

IPSubnet

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType IPSubnet
```

Byte

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Byte
```

Double

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType Double
```

ArchiveableSubobject

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType ArchiveableSubobject
```

ByteArray

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListFi  
eldType ByteArray
```

Blob

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField  
eldType Blob
```

Clob

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField  
eldType Clob
```

ResourceID

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField  
eldType ResourceID
```

IPAddress

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField  
eldType IPAddress
```

MacAddress

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListField  
eldType MacAddress
```

Methods

values

```
public static ActiveList.ActiveListFieldType\[\] values()
```

valueOf

```
public static ActiveList.ActiveListFieldType valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model.activelist

Class **ActiveList.ActiveListType**

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListType

All Implemented Interfaces:

Serializable, Comparable

public static final class **ActiveList.ActiveListType**
extends Enum

Type of the active list. If this active list is event based, then the entries have only fields from event table.

Field Summary

public static final	EVENT_BASED
public static final	FIELD_BASED

Method Summary

static ActiveList.ActiveListType	valueOf (String name)
static ActiveList.ActiveListType[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

EVENT_BASED

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListTy  
pe EVENT_BASED
```

FIELD_BASED

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.ActiveListTy  
pe FIELD_BASED
```

Methods

values

```
public static ActiveList.ActiveListType\[\] values()
```

valueOf

```
public static ActiveList.ActiveListType valueOf(String name)
```

com.arcsight.product.manager.resource.service.v1.model.activelist

Class **ActiveList.CaseType**

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.CaseType

All Implemented Interfaces:

Serializable, Comparable

public static final class **ActiveList.CaseType**
extends Enum

Case sensitivity type of the active list.

Field Summary

public static final	CASE_SENSITIVE
public static final	KEY_AND_VALUE_INSENSITIVE
public static final	KEY_CASE_INSENSITIVE

Method Summary

static ActiveList.CaseType	fromOrdinal (int n)
static ActiveList.CaseType	valueOf (String name)
static ActiveList.CaseType[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

CASE_SENSITIVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.CaseType  
CASE_SENSITIVE
```

KEY_CASE_INSENSITIVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.CaseType  
KEY_CASE_INSENSITIVE
```

KEY_AND_VALUE_INSENSITIVE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveList.CaseType  
KEY_AND_VALUE_INSENSITIVE
```

Methods

values

```
public static ActiveList.CaseType\[\] values()
```

valueOf

```
public static ActiveList.CaseType valueOf(String name)
```

fromOrdinal

```
public static ActiveList.CaseType fromOrdinal(int n)
```

com.arcsight.product.manager.resource.service.v1.model.activelist

Class ActiveListEntry

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveListEntry

All Implemented Interfaces:
Serializable

public class **ActiveListEntry**
extends Object
implements Serializable

This class represents field values of a single active list entry in string format.

Constructor Summary

public	ActiveListEntry()
public	ActiveListEntry (String[] entry)

Method Summary

String[]	getEntry() Returns string representation of the field values of a entry.
void	setEntry (String[] entry) Sets field values in string format.

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ActiveListEntry
public **ActiveListEntry**()

ActiveListEntry
public **ActiveListEntry**(String[] entry)

Methods

getEntry

```
public String[] getEntry()
```

Returns string representation of the field values of a entry.

Returns:

array of string representation of fields.

setEntry

```
public void setEntry(String[] entry)
```

Sets field values in string format.

Parameters:

entry - array of field values.

com.arcsight.product.manager.resource.service.v1.model.activelist

Class ActiveListEntryList

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.activelist.ActiveListEntryList

All Implemented Interfaces:
Serializable

public class **ActiveListEntryList**
extends Object
implements Serializable

This class represents an array of active list entries.

Constructor Summary

public	ActiveListEntryList()
public	ActiveListEntryList (String[] columns, ActiveListEntry[] entryList)

Method Summary

String[]	getColumns() Returns field names of the active list.
ActiveListEntry[]	getEntryList() Returns array of entry values.
void	setColumns (String[] columns) Set field names of the active list.
void	setEntryList (ActiveListEntry[] entryList) Sets the array of entry values

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ActiveListEntryList
public **ActiveListEntryList**()

ActiveListEntryList

```
public ActiveListEntryList(String[] columns,  
    ActiveListEntry\[\] entryList)
```

Methods

getColumns

```
public String[] getColumns()
```

Returns field names of the active list.

Returns:
array of field names.

setColumns

```
public void setColumns(String[] columns)
```

Set field names of the active list.

Parameters:
columns - The field names of the active list.

getEntryList

```
public ActiveListEntry\[\] getEntryList()
```

Returns array of entry values.

Returns:
An array of active list entry values.

setEntryList

```
public void setEntryList(ActiveListEntry\[\] entryList)
```

Sets the array of entry values

Parameters:
entryList - An array of active list entry values.

Package

com.arcsight.product.manager.resource.service.v1.model.cases

com.arcsight.product.manager.resource.service.v1.model.cases

Class CaseClosureStats

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.cases.CaseClosureStats

public class **CaseClosureStats**
extends Object

Constructor Summary	
public	CaseClosureStats()

Method Summary	
long	getEndTime()
List	getGroupCaseStats()
long	getStartTime()
void	setEndTime(long endTime)
void	setGroupCaseStats(List groupCaseStats)
void	setStartTime(long startTime)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

CaseClosureStats
public **CaseClosureStats()**

Methods

getStartTime

```
public long getStartTime()
```

setStartTime

```
public void setStartTime(long startTime)
```

getEndTime

```
public long getEndTime()
```

setEndTime

```
public void setEndTime(long endTime)
```

getGroupCaseStats

```
public List getGroupCaseStats()
```

setGroupCaseStats

```
public void setGroupCaseStats(List groupCaseStats)
```

com.arcsight.product.manager.resource.service.v1.model.cases

Class ClosureStats

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.cases.ClosureStats

```
public class ClosureStats
extends Object
```

POJO to model case closure stats.

Constructor Summary

public	ClosureStats()

Method Summary

double	getAverageDaysToClose()
int	getCasesClosed()
List	getClosedCaseCountsBySeverity()
Float	getTrend()
void	setAverageDaysToClose (double averageDaysToClose)
void	setCasesClosed (int casesClosed)
void	setClosedCaseCountsBySeverity (List closedCountBySeverity)
void	setClosedCaseCountsBySeverity (Map closedCountBySeverity)
void	setTrend (Float trend)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ClosureStats

```
public ClosureStats()
```

Methods

getCasesClosed

```
public int getCasesClosed()
```

setCasesClosed

```
public void setCasesClosed(int casesClosed)
```

getAverageDaysToClose

```
public double getAverageDaysToClose()
```

setAverageDaysToClose

```
public void setAverageDaysToClose(double averageDaysToClose)
```

getClosedCaseCountsBySeverity

```
public List getClosedCaseCountsBySeverity()
```

setClosedCaseCountsBySeverity

```
public void setClosedCaseCountsBySeverity(List closedCountBySeverity)
```

setClosedCaseCountsBySeverity

```
public void setClosedCaseCountsBySeverity(Map closedCountBySeverity)
```

getTrend

```
public Float getTrend()
```

setTrend

public void **setTrend**(Float trend)

com.arcsight.product.manager.resource.service.v1.model.cases

Class GroupCaseClosureStats

java.lang.Object
└─com.arcsight.product.manager.resource.service.v1.model.cases.GroupCaseClosureStats

public class **GroupCaseClosureStats**
extends Object

POJO to model group (a.k.a. owner group) case closure stats.

Constructor Summary	
public	GroupCaseClosureStats()

Method Summary	
ClosureStats	getClosureStats()
String	getOwnerGroupId()
List	getUserCaseStats()
void	setClosureStats(ClosureStats closureStats)
void	setOwnerGroupId(String ownerGroupId)
void	setUserCaseStats(List userStats)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupCaseClosureStats
public **GroupCaseClosureStats()**

Methods

getOwnerId

```
public String getOwnerId()
```

setOwnerId

```
public void setOwnerId(String ownerId)
```

getClosureStats

```
public ClosureStats getClosureStats()
```

setClosureStats

```
public void setClosureStats(ClosureStats closureStats)
```

getUserCaseStats

```
public List getUserCaseStats()
```

setUserCaseStats

```
public void setUserCaseStats(List userStats)
```

com.arcsight.product.manager.resource.service.v1.model.cases

Class SeverityCount

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.cases.SeverityCount

public class **SeverityCount**
extends Object

Constructor Summary

public	SeverityCount (int severityLevel, int count)

Method Summary

int	getCount ()

int	getSeverityLevel ()

void	setCount (int count)

void	setSeverityLevel (int severityLevel)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SeverityCount

public **SeverityCount**(int severityLevel,
int count)

Methods

getSeverityLevel

public int **getSeverityLevel**()

setSeverityLevel

public void **setSeverityLevel**(int severityLevel)

getCount

public int **getCount**()

setCount

public void **setCount**(int count)

com.arcsight.product.manager.resource.service.v1.model.cases

Class UserCaseClosureStats

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.cases.UserCaseClosureStats

public class **UserCaseClosureStats**
extends Object

POJO to model user (a.k.a. owner) case closure stats.

Constructor Summary	
public	UserCaseClosureStats()

Method Summary	
ClosureStats	getClosureStats()
int[]	getPossiblyDelayedIn()
String	getUserId()
void	setClosureStats(ClosureStats closureStats)
void	setPossiblyDelayedIn(int[] possiblyDelayedIn)
void	setUserId(String userId)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

UserCaseClosureStats

public **UserCaseClosureStats()**

Methods

getUserId

```
public String getUserId()
```

setUserId

```
public void setUserId(String userId)
```

getClosureStats

```
public ClosureStats getClosureStats()
```

setClosureStats

```
public void setClosureStats(ClosureStats closureStats)
```

getPossiblyDelayedIn

```
public int[] getPossiblyDelayedIn()
```

setPossiblyDelayedIn


```
public void setPossiblyDelayedIn(int[] possiblyDelayedIn)
```

Package

com.arcsight.product.manager.resource.service.v1.model.dashboard

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class Dashboard



All Implemented Interfaces:
Serializable, Serializable

```
public class Dashboard
extends Resource
implements Serializable, Serializable
```

This class represents a Dashboard, a collection of dashboard entries.

Field Summary

public static final	PROPERTY_KEY_DARK_BACKGROUND Value: darkBackground

Constructor Summary

public	Dashboard()

Method Summary

int[]	getColumnSizes() Returns an array of the column sizes for all the columns of the dashboard.
Map	getDashboardEntries() Returns a map of dashboard entries.
Map	getProperties() Returns a map that maps the property names to the property values.
int[]	getRowSizes() Returns an array of the row sizes for all the rows of the dashboard.
void	setColumnSizes(int[] columnSizes) Sets the array of the column sizes for all the rows of the dashboard.
void	setDashboardEntries(Map dashboardEntries) Sets the map of dashboard entries.
void	setPropertyies(Map properties) Sets a map that maps the property names to the property values.

void	setRowSizes (int[] rowSizes) Sets the array of the row sizes for all the rows of the dashboard.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class [java.lang.Object](#)

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Fields

PROPERTY_KEY_DARK_BACKGROUND

public static final java.lang.String **PROPERTY_KEY_DARK_BACKGROUND**

Constant value: **darkBackground**

Constructors

Dashboard

public **Dashboard**()

Methods

getDashboardEntries

public Map **getDashboardEntries**()

Returns a map of dashboard entries.

Returns:

a map dashboard entries.

setDashboardEntries

public void **setDashboardEntries**(Map dashboardEntries)

Sets the map of dashboard entries.

Parameters:

dashboardEntries - the map dashboard entries.

getRowSizes

public int[] **getRowSizes**()

Returns an array of the row sizes for all the rows of the dashboard.

Returns:

an array of the row sizes (in pixels) for all the rows of the dashboard.

setRowSizes

public void **setRowSizes**(int[] rowSizes)

Sets the array of the row sizes for all the rows of the dashboard.

Parameters:

rowSizes - the array of the row sizes (in pixels) for all the rows of the dashboard.

getColumnSizes

public int[] **getColumnSizes**()

Returns an array of the column sizes for all the columns of the dashboard.

Returns:

an array of the column sizes (in pixels) for all the columns of the dashboard.

setColumnSizes

public void **setColumnSizes**(int[] columnSizes)

Sets the array of the column sizes for all the rows of the dashboard.

Parameters:

columnSizes - the array of the column sizes (in pixels) for all the rows of the dashboard.

getProperties

public Map **getProperties**()

Returns a map that maps the property names to the property values.

Returns:

a map that maps the property names to the property values.

setProperties

public void **setProperties**(Map properties)

Sets a map that maps the property names to the property values.

Parameters:

properties - a map that maps the property names to the property values.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class DashboardEntry

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.dashboard.DashboardEntry

All Implemented Interfaces:
Serializable

public class **DashboardEntry**
extends Object
implements Serializable

A dashboard entry that can be placed into a dashboard.

Constructor Summary

public	DashboardEntry() Creates a new instance of a dashboard entry.

Method Summary

int	getColumnIndex() Returns the column index of the dashboard entry.
int	getColumnSpan() Returns the column span of the dashboard entry.
String	getPortletID() Returns the portlet ID for the dashboard entry.
Set	getPropertyNames() Returns the names for all properties.
ParameterBase	getPropertyValue(String name) Returns the value of the specified properties.
int	getRowIndex() Returns the row index of the dashboard entry.
int	getRowSpan() Returns the row span of the dashboard entry.
void	removePropertyValue(String name) Removes the specified property.
void	setColumnIndex(int columnIndex) Sets the column index of the dashboard entry.

void	setColumnSpan (int columnSpan) Sets the column span of the dashboard entry.
void	setPortletID (String portletID) Sets the portlet ID for the dashboard entry.
void	setPropertyValue (String name, ParameterBase value) Sets the value of the specified property.
void	setRowIndex (int rowIndex) Sets the row index of the dashboard entry.
void	setRowSpan (int rowSpan) Sets the row span of the dashboard entry.
String	toString () Returns a string representation of the dashboard entry.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

DashboardEntry

`public DashboardEntry()`

Creates a new instance of a dashboard entry.

Methods

getRowIndex

`public int getRowIndex()`

Returns the row index of the dashboard entry.

Returns:

the row index of the dashboard entry.

setRowIndex

`public void setRowIndex(int rowIndex)`

Sets the row index of the dashboard entry.

Parameters:

`rowIndex` - the row index of the dashboard entry.

getColumnIndex

```
public int getColumnIndex()
```

Returns the column index of the dashboard entry.

Returns:
the column index of the dashboard entry.

setColumnIndex

```
public void setColumnIndex(int columnIndex)
```

Sets the column index of the dashboard entry.

Parameters:
columnIndex - the column index of the dashboard entry.

getRowSpan

```
public int getRowSpan()
```

Returns the row span of the dashboard entry.

Returns:
the row span of the dashboard entry.

setRowSpan

```
public void setRowSpan(int rowSpan)
```

Sets the row span of the dashboard entry.

Parameters:
rowSpan - the row span of the dashboard entry.

getColumnSpan

```
public int getColumnSpan()
```

Returns the column span of the dashboard entry.

Returns:
the column span of the dashboard entry.

setColumnSpan

```
public void setColumnSpan(int columnSpan)
```

Sets the column span of the dashboard entry.

Parameters:
columnSpan - the column span of the dashboard entry.

getPortletID

```
public String getPortletID()
```

Returns the portlet ID for the dashboard entry.

Returns:
the portlet for the dashboard entry.

setPortletID

```
public void setPortletID(String portletID)
```

Sets the portlet ID for the dashboard entry.

Parameters:
portletID - the portlet ID for the dashboard entry.

getPropertyNames

```
public Set getPropertyNames()
```

Returns the names for all properties.

Returns:
the names of all properties.

getPropertyValue

```
public ParameterBase getPropertyValue(String name)
```

Returns the value of the specified properties.

Parameters:
name - the name of the property to return the value for.

Returns:
the value of the property.

setPropertyValue

```
public void setPropertyValue(String name,  
    ParameterBase value)
```

Sets the value of the specified property.

Parameters:
name - the name of the property to set the value for.
value - the new value of the property.

removePropertyValue

```
public void removePropertyValue(String name)
```

Removes the specified property.

Parameters:

name - the name of the property to remove.

toString

public String **toString()**

Returns a string representation of the dashboard entry. In general, the `toString` method returns a string that "textually represents" this object. The result should be a concise but informative representation that is easy for a person to read.

Returns:

a string representation of the dashboard entry.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class Data

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.dashboard.Data

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[StatsData](#), [MatrixData](#), [ListData](#), [GraphData](#)

public class **Data**
extends Object
implements Serializable

This is a base class representing the data returned by a Data Monitor probe. The descendants of this class are the concrete types of data returned by the probes.

Constructor Summary

public	Data()

Method Summary

long	getEndTimestamp() Returns the end timestamp of the data.
long	getStartTimestamp() Returns the start timestamp of the data.
long	getTimestamp() Returns the timestamp of the data.
void	setEndTimestamp(long endTimestamp) Sets the end timestamp.
void	setStartTimestamp(long startTimestamp) Sets the start timestamp.
void	setTimestamp(long timestamp) Sets the timestamp of the data.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

Data

```
public Data()
```

Methods

getTimestamp

```
public long getTimestamp()
```

Returns the timestamp of the data.

Returns:
the timestamp of the data.

setTimestamp

```
public void setTimestamp(long timestamp)
```

Sets the timestamp of the data.

Parameters:
timestamp - the timestamp to set.

getStartTimestamp

```
public long getStartTimestamp()
```

Returns the start timestamp of the data. The start timestamp is the time of the start of the validity of the data.

Returns:
the start timestamp of the data.

setStartTimestamp

```
public void setStartTimestamp(long startTimestamp)
```

Sets the start timestamp. The start timestamp is the time of the start of the validity of the data.

Parameters:
startTimestamp - the start timestamp.

getEndTimestamp

```
public long getEndTimestamp()
```

Returns the end timestamp of the data. The end timestamp is the time of the end of the validity of the data.

Returns:

the end timestamp of the data.

setEndTimestamp

```
public void setEndTimestamp(long endTimestamp)
```


Sets the end timestamp. The end timestamp is the time of the end of the validity of the data.

Parameters:

endTimestamp - the end timestamp.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class DataMonitor



All Implemented Interfaces:
Serializable, Serializable, Serializable

```
public class DataMonitor
extends ViewableResource
implements Serializable, Serializable, Serializable
```

A data monitor controls a data monitor probe.

Field Summary	
public static	DM_INVALID

Constructor Summary	
public	DataMonitor()

Method Summary	
Data	getData() Returns the data from the data monitor probe.
String	getDataMonitorType() Returns the data monitor type.
DrilldownList	getDrilldownList()
Map	getFieldDisplayNameMap()
String	getInstanceId()
Map	getProperties() Returns the map of the data monitor properties.
String[]	getSupportedDataTypes()

void	<u>setData</u> (<u>Data</u> data) Returns the data from the data monitor probe.
void	<u>setDataMonitorType</u> (String dataMonitorType) Sets the data monitor type.
void	<u>setDrilldownList</u> (<u>DrilldownList</u> drilldownList)
void	<u>setFieldDisplayNameMap</u> (Map fieldDisplayNameMap)
void	<u>setInstanceId</u> (String instanceId)
void	<u>setProperties</u> (Map properties) Sets the map of the data monitor properties.
void	<u>setSupportedDataTypes</u> (String[] supportedDataTypes)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.dashboard.ViewableResource](#)

[getSupportedDataTypes](#), [isEnabled](#), [isSupportsToggle](#), [setEnabled](#), [setSupportedDataTypes](#), [setSupportsToggle](#)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class [java.lang.Object](#)

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Fields

DM_INVALID

public static [java.lang.Long](#) **DM_INVALID**

Constructors

DataMonitor

```
public DataMonitor()
```

Methods

getData

```
public Data getData()
```

Returns the data from the data monitor probe.

Returns:
the data from the data monitor probe.

setData

```
public void setData(Data data)
```

Returns the data from the data monitor probe.

Parameters:
data

getProperties

```
public Map getProperties()
```

Returns the map of the data monitor properties.

Returns:
the map of the data monitor properties.

setProperties

```
public void setProperties(Map properties)
```

Sets the map of the data monitor properties.

Parameters:
properties - the map of the data monitor properties.

getDataMonitorType

```
public String getDataMonitorType()
```

Returns the data monitor type.

Returns:

the data monitor type.

setDataMonitorType

```
public void setDataMonitorType(String dataMonitorType)
```

Sets the data monitor type.

Parameters:

dataMonitorType - the new data monitor type.

getSupportedDataTypes

```
public String[] getSupportedDataTypes()
```

Returns:

the supportedDataTypes

setSupportedDataTypes

```
public void setSupportedDataTypes(String[] supportedDataTypes)
```

Parameters:

supportedDataTypes - the supportedDataTypes to set

getFieldDisplayNameMap

```
public Map getFieldDisplayNameMap()
```

setFieldDisplayNameMap

```
public void setFieldDisplayNameMap(Map fieldDisplayNameMap)
```

getDrilldownList

```
public DrilldownList getDrilldownList()
```

Returns:

the drilldownList

setDrilldownList

```
public void setDrilldownList(DrilldownList drilldownList)
```

Parameters:

drillDownList - the drillDownList to set

getInstanceId

```
public String getInstanceId()
```

Returns:

the instanceId

setInstanceId

```
public void setInstanceId(String instanceId)
```

Parameters:

instanceId - the instanceId to set

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class Edge

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.dashboard.Edge

All Implemented Interfaces:
Serializable

public class **Edge**
extends Object
implements Serializable

Represents and edge connecting two nodes

Constructor Summary

public	Edge()
public	Edge(Node nodeOne, Node nodeTwo)

Method Summary

boolean	equals (Object obj) Indicates whether some other object is "equal to" this one.
Node[]	getNodes ()
String	getTypeId ()
int	hashCode () Returns a hash code value for the object.
void	setNodes (Node[] nodes)
void	setTypeId (String typeId)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

Edge

```
public Edge()
```

Edge

```
public Edge(Node nodeOne,  
           Node nodeTwo)
```

Methods

getNodes

```
public Node\[\] getNodes()
```

setNodes

```
public void setNodes(Node\[\] nodes)
```

getTypeId

```
public String getTypeId()
```

setTypeId

```
public void setTypeId(String typeId)
```

equals

```
public boolean equals(Object obj)
```

Indicates whether some other object is "equal to" this one.

Parameters:

obj - The reference object with which to compare.

Returns:

true if this object is the same as the obj argument; false otherwise.

hashCode

`public int hashCode()`


Returns a hash code value for the object. This method is supported for the benefit of hashtables such as those provided by `java.util.Hashtable`.

Returns:

A hash code value for this object.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class EventGraph



All Implemented Interfaces:
Serializable, Serializable

```
public class EventGraph
extends Graph
implements Serializable, Serializable
```

An event graph represents relations among events.

Nested Class Summary	
class	EventGraph.NodeType EventGraph.NodeType
class	EventGraph.SplitEventsMode EventGraph.SplitEventsMode

Field Summary	
public static final	PROPERTY_NAME_EVENT_FIELDS Property name EVENT_FIELD_INDICES. Value: event-graph.event-field-indices
public static final	PROPERTY_NAME_SOURCE_FIELDS Property name SOURCE_FIELD_INDICES. Value: event-graph.source-field-indices
public static final	PROPERTY_NAME_SPLIT_EVENTS_MODE Property name SPLIT_EVENTS_MODE. Value: event-graph.split-events-mode
public static final	PROPERTY_NAME_SPLIT_SOURCE_TARGET Property name SPLIT_SOURCE_TARGET. Value: event-graph.split-source-target
public static final	PROPERTY_NAME_TARGET_FIELDS Property name TARGET_FIELD_INDICES. Value: event-graph.target-field-indices

Constructor Summary

public	EventGraph()

Method Summary

ArcField[]	getEventFields()
ArcField[]	getSourceEventFields()
EventGraph.SplitEventsMode	getSplitEventsMode()
ArcField[]	getTargetEventFields()
void	setEventFields(ArcField[] eventEventFields)
void	setEventFields(ArcField[] sourceEventFields, ArcField[] eventEventFields, ArcField[] targetEventFields) Sets the event field indices.
void	setSourceEventFields(ArcField[] sourceEventFields)
void	setSplitEventsMode(EventGraph.SplitEventsMode splitEventsMode)
void	setTargetEventFields(ArcField[] targetEventFields)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Graph](#)

[addEdge](#), [addNode](#), [clear](#), [clearEdges](#), [getConfigurationDescription](#), [getEdges](#), [getNodes](#), [getPropertyMap](#), [removeNode](#), [setConfigurationDescription](#), [setNodes](#), [setPropertyArray](#), [setPropertyInteger](#), [setPropertyString](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

PROPERTY_NAME_SPLIT_EVENTS_MODE

public static final java.lang.String **PROPERTY_NAME_SPLIT_EVENTS_MODE**

Property name SPLIT_EVENTS_MODE.
Constant value: **event-graph.split-events-mode**

PROPERTY_NAME_SPLIT_SOURCE_TARGET

public static final java.lang.String **PROPERTY_NAME_SPLIT_SOURCE_TARGET**

Property name SPLIT_SOURCE_TARGET.
Constant value: `event-graph.split-source-target`

PROPERTY_NAME_SOURCE_FIELDS

`public static final java.lang.String PROPERTY_NAME_SOURCE_FIELDS`

Property name SOURCE_FIELD_INDICES.
Constant value: `event-graph.source-field-indices`

PROPERTY_NAME_EVENT_FIELDS

`public static final java.lang.String PROPERTY_NAME_EVENT_FIELDS`

Property name EVENT_FIELD_INDICES.
Constant value: `event-graph.event-field-indices`

PROPERTY_NAME_TARGET_FIELDS

`public static final java.lang.String PROPERTY_NAME_TARGET_FIELDS`

Property name TARGET_FIELD_INDICES.
Constant value: `event-graph.target-field-indices`

Constructors

EventGraph

`public EventGraph()`

Methods

getSplitEventsMode

`public EventGraph.SplitEventsMode getSplitEventsMode()`

setSplitEventsMode

`public void setSplitEventsMode(EventGraph.SplitEventsMode splitEventsMode)`

getSourceEventFields

`public ArcField\[\] getSourceEventFields()`

setSourceEventFields

```
public void setSourceEventFields(ArcField\[\] sourceEventFields)
```

getEventFields

```
public ArcField\[\] getEventFields()
```

setEventFields

```
public void setEventFields(ArcField\[\] eventEventFields)
```

setEventFields

```
public void setEventFields(ArcField\[\] sourceEventFields,  
    ArcField\[\] eventEventFields,  
    ArcField\[\] targetEventFields)
```

Sets the event field indices.

Parameters:

sourceEventFields - The source event fields.

eventEventFields - The event event fields.

targetEventFields - The target event fields.

getTargetEventFields

```
public ArcField\[\] getTargetEventFields()
```

setTargetEventFields

```
public void setTargetEventFields(ArcField\[\] targetEventFields)
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class EventGraph.NodeType

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.NodeType

All Implemented Interfaces:

Serializable, Comparable

public static final class **EventGraph.NodeType**
extends Enum

Field Summary

public static final	NODE_TYPE_EVENT The node type event.
public static final	NODE_TYPE_SOURCE The node type source.
public static final	NODE_TYPE_SOURCE_AND_TARGET The node type source/target.
public static final	NODE_TYPE_TARGET The node type target.

Method Summary

int	value()
static EventGraph.NodeType	valueOf() (String name)
static EventGraph.NodeType[]	values()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

NODE_TYPE_SOURCE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.NodeType  
NODE_TYPE_SOURCE
```

The node type source.

NODE_TYPE_TARGET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.NodeType  
NODE_TYPE_TARGET
```

The node type target.

NODE_TYPE_EVENT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.NodeType  
NODE_TYPE_EVENT
```

The node type event.

NODE_TYPE_SOURCE_AND_TARGET

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.NodeType  
NODE_TYPE_SOURCE_AND_TARGET
```

The node type source/target.

Methods

values

```
public static EventGraph.NodeType\[\] values()
```

valueOf

```
public static EventGraph.NodeType valueOf(String name)
```

value

```
public int value()
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class EventGraph.SplitEventsMode

java.lang.Object

└ java.lang.Enum

└ com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.SplitEventsMode

All Implemented Interfaces:

Serializable, Comparable

public static final class **EventGraph.SplitEventsMode**
extends Enum

Field Summary

public static final	SPLIT_EVENTS_MODE_NONE The split mode none.
public static final	SPLIT_EVENTS_MODE_SOURCES The split mode sources.
public static final	SPLIT_EVENTS_MODE_SOURCES_AND_TARGETS The split mode sources and targets.
public static final	SPLIT_EVENTS_MODE_TARGETS The split mode targets.

Method Summary

int	value()
static EventGraph.SplitEventsMode	valueOf() (String name)
static EventGraph.SplitEventsMode[]	values()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Fields

SPLIT_EVENTS_MODE_NONE

```
public static final
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.SplitEventsMo
de SPLIT_EVENTS_MODE_NONE
```

The split mode none.

SPLIT_EVENTS_MODE_SOURCES

```
public static final
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.SplitEventsMo
de SPLIT_EVENTS_MODE_SOURCES
```

The split mode sources.

SPLIT_EVENTS_MODE_SOURCES_AND_TARGETS

```
public static final
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.SplitEventsMo
de SPLIT_EVENTS_MODE_SOURCES_AND_TARGETS
```

The split mode sources and targets.

SPLIT_EVENTS_MODE_TARGETS

```
public static final
com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraph.SplitEventsMo
de SPLIT_EVENTS_MODE_TARGETS
```

The split mode targets.

Methods

values

```
public static EventGraph.SplitEventsMode\[\] values()
```

valueOf


```
public static EventGraph.SplitEventsMode valueOf(String name)
```

value

```
public int value()
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class EventGraphNode



All Implemented Interfaces:
Serializable, Serializable, Serializable

Direct Known Subclasses:
[GeoInfoEventGraphNode](#)

```
public class EventGraphNode
extends TypedNode
implements Serializable, Serializable, Serializable
```

Constructor Summary	
public	EventGraphNode()
public	EventGraphNode (String id, String name, int type, int weight)

Method Summary	
int	getWeight()
void	setWeight (int weight)

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.TypedNode	
getType , setType	

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.Node	
equals , getId , getName , hashCode , setId , setName	

Methods inherited from class java.lang.Object	
equals , getClass , hashCode , notify , notifyAll , toString , wait , wait , wait	

Constructors

EventGraphNode

```
public EventGraphNode()
```

EventGraphNode

```
public EventGraphNode(String id,  
                      String name,  
                      int type,  
                      int weight)
```

Methods

getWeight

```
public int getWeight()
```

setWeight

```
public void setWeight(int weight)
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class GeographicInformation

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.model.dashboard.GeographicInformation

All Implemented Interfaces:
Serializable

public class **GeographicInformation**
extends Object
implements Serializable

Describes the geo-location.

JSON prototype

Constructor Summary	
public	GeographicInformation()
public	GeographicInformation (double longitude, double latitude, String countryCode, String region, String zip, String city)

Method Summary	
String	getCity()
String	getCountryCode()
String	getCountryName()
double	getLatitude()
double	getLongitude()
String	getRegion()
String	getZip()
void	setCity (String city)
void	setCountryCode (String countryCode)

void	<u>setCountryName</u> (String countryName)
void	<u>setLatitude</u> (double latitude)
void	<u>setLongitude</u> (double longitude)
void	<u>setRegion</u> (String region)
void	<u>setZip</u> (String zip)
String	<u>toString</u> ()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GeographicInformation

```
public GeographicInformation()
```

GeographicInformation

```
public GeographicInformation(double longitude,
                             double latitude,
                             String countryCode,
                             String region,
                             String zip,
                             String city)
```

Methods

getLongitude

```
public double getLongitude()
```

setLongitude

```
public void setLongitude(double longitude)
```

getLatitude

```
public double getLatitude()
```

setLatitude

```
public void setLatitude(double latitude)
```

getCountryCode

```
public String getCountryCode()
```

setCountryCode

```
public void setCountryCode(String countryCode)
```

getCountryName

```
public String getCountryName()
```

setCountryName

```
public void setCountryName(String countryName)
```

getRegion

```
public String getRegion()
```

setRegion

```
public void setRegion(String region)
```

getZip

```
public String getZip()
```

setZip

public void **setZip**(String zip)

getCity

public String **getCity**()

setCity


public void **setCity**(String city)

toString

public String **toString**()

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class GeoInfoEventGraphNode



```
public class GeoInfoEventGraphNode
extends EventGraphNode
implements Serializable, Serializable, Serializable, Serializable
```

Describes a graph node that represents geo-location.

JSON prototype

Constructor Summary	
public	GeoInfoEventGraphNode()
public	GeoInfoEventGraphNode(String id, String name, int type, int weight, GeographicInformation geographicInformation)
Method Summary	
GeographicInformation	getGeographicInformation()
void	setGeographicInformation(GeographicInformation geographicInformation)
Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.EventGraphNode	
getWeight , setWeight	
Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.TypedNode	
getType , setType	
Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.Node	
equals , getId , getName , hashCode , setId , setName	

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

GeoInfoEventGraphNode

```
public GeoInfoEventGraphNode()
```

GeoInfoEventGraphNode

```
public GeoInfoEventGraphNode(String id,  
                             String name,  
                             int type,  
                             int weight,  
                             GeographicInformation geographicInformation)
```

Methods

getGeographicInformation

```
public GeographicInformation getGeographicInformation()
```

setGeographicInformation

```
public void setGeographicInformation(GeographicInformation geographicInformation)
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class Graph

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.dashboard.Graph

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[EventGraph](#)

public class **Graph**
extends Object
implements Serializable

A graph has nodes and edges.

Constructor Summary	
public	Graph()

Method Summary	
void	addEdge(Edge edge) Adds the specified edge to the graph.
void	addNode(Node node) Adds the specified node to the graph.
void	clear() Clear the graph
void	clearEdges() Clear just the edges
String	getConfigurationDescription()
List	getEdges()
Map	getNodes()
Map	getPropertyMap()
void	removeNode(Node node) Removes the specified node from the graph.

void	<u>setConfigurationDescription</u> (String configurationDescription)
void	<u>setNodes</u> (Map nodes)
void	<u>setPropertyArray</u> (String name, String[] values) Sets the specified property values.
void	<u>setPropertyInteger</u> (String name, Integer value) Sets the specified property values.
void	<u>setPropertyString</u> (String name, String value) Sets the specified property value.

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

Graph

public **Graph**()

Methods

getNodes

public Map **getNodes**()

setNodes

public void **setNodes**(Map nodes)

getEdges

public List **getEdges**()

getConfigurationDescription

public String **getConfigurationDescription**()

setConfigurationDescription

```
public void setConfigurationDescription(String configurationDescription)
```

getPropertyMap

```
public Map getPropertyMap()
```

setPropertyString

```
public void setPropertyString(String name,  
    String value)
```

Sets the specified property value.

Parameters:

name - The name of the property to set the value for.
value - The value to set for the specified property.

setPropertyArray

```
public void setPropertyArray(String name,  
    String[] values)
```

Sets the specified property values.

Parameters:

name - The name of the property to set the value for.
values - The values to set for the specified property.

setPropertyInteger

```
public void setPropertyInteger(String name,  
    Integer value)
```

Sets the specified property values.

Parameters:

name - The name of the property to set the value for.
value - The value to set for the specified property.

addNode

```
public void addNode(Node node)
```

Adds the specified node to the graph.

Parameters:

node - The node to add.

removeNode

```
public void removeNode(Node node)
```

Removes the specified node from the graph.

Parameters:

node - The node to add.

addEdge

```
public void addEdge(Edge edge)
```

Adds the specified edge to the graph.

Parameters:

edge - The edge to add.

clear

```
public void clear()
```

Clear the graph


clearEdges

```
public void clearEdges()
```

Clear just the edges

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class GraphData



All Implemented Interfaces:
Serializable, Serializable

```
public class GraphData
extends Data
implements Serializable, Serializable
```

Constructor Summary

public	GraphData()

Method Summary

Graph	getGraph()
void	setGraph(Graph graph)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

[getEndTimestamp](#), [getStartTimestamp](#), [getTimestamp](#), [setEndTimestamp](#), [setStartTimestamp](#), [setTimestamp](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

```
GraphData
public GraphData()
```

Methods

getGraph


public [Graph](#) getGraph()

setGraph

public void setGraph([Graph](#) graph)

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class ListData



All Implemented Interfaces:
Serializable, Serializable

```
public class ListData
extends Data
implements Serializable, Serializable
```

Represents data returned by a Data Monitor probe as a list of elements. The implementation encapsulates multiple rows with one columns per row.

Constructor Summary	
public	ListData()

Method Summary	
List	getListData() Returns a list of data elements.
void	setListData(List data) Sets the list of data elements.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

[getEndTimestamp](#), [getStartTimestamp](#), [getTimestamp](#), [setEndTimestamp](#), [setStartTimestamp](#), [setTimestamp](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ListData

```
public ListData()
```

Methods

getListData

`public List getListData()`

Returns a list of data elements.

Returns:

a list of data elements.

setListData

`public void setListData(List data)`


Sets the list of data elements.

Parameters:

data - the list of data elements.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class ListPropertyHolder



```
public class ListPropertyHolder
extends PropertyHolder
implements Serializable, Serializable
```

A generic Java bean that holds a list of values of the specified type.

Parameters:

E - the type of values in the list.

JSON prototype

Constructor Summary

public	ListPropertyHolder()

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.PropertyHolder
getPropertyValue , setPropertyValue

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ListPropertyHolder

```
public ListPropertyHolder()
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class MatrixData

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

└ [com.arcsight.product.manager.resource.service.v1.model.dashboard.MatrixData](#)

All Implemented Interfaces:

Serializable, Serializable

public class **MatrixData**

extends [Data](#)

implements Serializable, Serializable

Represents data returned by a Data Monitor probe as a list of elements. The implementation encapsulates multiple rows with multiple columns per row.

Constructor Summary

public	MatrixData()

Method Summary

long	getColHeaderTS() Returns the column header timestamp.
List	getColumnHeaders() Returns a list of column headers.
int	getMaxColumns() Returns the maximum number of columns across all rows.
Map	getProperties() Returns the property map.
List	getRows() Returns the data rows.
void	setColHeaderTS(long colHeaderTS) Sets the column header timestamp.
void	setColumnHeaders(List columnHeaders) Sets the list of column headers.
void	setMaxColumns(int maxColumns) Sets the maximum number of columns across all rows.
void	setProperties(Map properties) Sets the property map.

void	setRows (List rows) Sets the data rows.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

[getEndTimeStamp](#), [getStartTimeStamp](#), [getTimestamp](#), [setEndTimeStamp](#), [setStartTimeStamp](#), [setTimestamp](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

MatrixData

`public MatrixData()`

Methods

getRows

`public List getRows()`

Returns the data rows.

Returns:
the data rows.

setRows

`public void setRows(List rows)`

Sets the data rows.

Parameters:
rows - the data rows to set.

getColumnHeaders

`public List getColumnHeaders()`

Returns a list of column headers.

Returns:
a list of column headers.

setColumnHeaders

```
public void setColumnHeaders(List columnHeaders)
```

Sets the list of column headers.

Parameters:

columnHeaders - the column header list to set.

getColHeaderTS

```
public long getColHeaderTS()
```

Returns the column header timestamp.

Returns:

the column header timestamp.

setColHeaderTS

```
public void setColHeaderTS(long colHeaderTS)
```

Sets the column header timestamp.

Parameters:

colHeaderTS - the column header timestamp.

getMaxColumns

```
public int getMaxColumns()
```

Returns the maximum number of columns across all rows.

Returns:

the maximum number of columns across all rows.

setMaxColumns

```
public void setMaxColumns(int maxColumns)
```

Sets the maximum number of columns across all rows.

Parameters:

maxColumns - the maxColumns to set

getProperties

```
public Map getProperties()
```

Returns the property map.

Returns:

the propertiy map.

setProperties

public void **setProperties**(Map properties)

Sets the property map.

Parameters:

properties - the property map to set.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class Node

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.dashboard.Node

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

[TypedNode](#)

```
public class Node
extends Object
implements Serializable
```

A node in a graph

Constructor Summary

public	Node()
public	Node (String id, String name)

Method Summary

boolean	equals (Node node)
String	getId ()
String	getName ()
int	hashCode ()
void	setId (String id)
void	setName (String name)

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

Node

```
public Node()
```

Node

```
public Node(String id,  
            String name)
```

Methods

getId

```
public String getId()
```

setId

```
public void setId(String id)
```

getName

```
public String getName()
```

setName

```
public void setName(String name)
```

equals

```
public boolean equals(Node node)
```

hashCode

```
public int hashCode()
```

com.arcsight.product.manager.resource.service.v1.model.dashboard Class Portlet

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└ **com.arcsight.product.manager.resource.service.v1.model.dashboard.Portlet**

All Implemented Interfaces:

Serializable, Serializable

public class **Portlet**

extends [Resource](#)

implements Serializable, Serializable

Represents a Portlet, an aggregate of a viewable resource and a viewer configuration that can be added to a dashboard.

Constructor Summary

public	Portlet () Creates an instance of the Portlet.

Method Summary

Set	getPropertyNames () Returns a set of the Portlet property names.
ParameterBase	getPropertyValue (String name) Returns the value of the specified property.
ViewableResource	getViewableResource () Returns the viewable resource.
ViewerConfiguration	getViewerConfiguration () Returns the viewer configuration.
void	removePropertyValue (String name) Removes the specified property.
void	setPropertyValue (String name, ParameterBase value) Sets the value of the specified property.
void	setViewableResource (ViewableResource viewableResource) Sets the viewable resource.
void	setViewerConfiguration (ViewerConfiguration viewerConfiguration) Sets the viewer configuration.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

Portlet

```
public Portlet()
```

Creates an instance of the Portlet.

Methods

getPropertyNames

```
public Set getPropertyNames()
```

Returns a set of the Portlet property names.

Returns:

a set of the Portlet property names.

getPropertyValue

```
public ParameterBase getPropertyValue(String name)
```

Returns the value of the specified property.

Parameters:

name - the name of the property.

Returns:

the value of the specified property.

setPropertyValue

```
public void setPropertyValue(String name,  
    ParameterBase value)
```

Sets the value of the specified property.

Parameters:

name - the name of the property.

value - the new value of the property.

removePropertyValue

```
public void removePropertyValue(String name)
```

Removes the specified property.

Parameters:

name - the name of the property.

getViewableResource

```
public ViewableResource getViewableResource()
```

Returns the viewable resource.

Returns:

the viewable resource.

setViewableResource

```
public void setViewableResource(ViewableResource viewableResource)
```

Sets the viewable resource.

Parameters:

viewableResource - the viewable resource to set.

getViewerConfiguration

```
public ViewerConfiguration getViewerConfiguration()
```

Returns the viewer configuration.

Returns:

the viewer configuration.

setViewerConfiguration

```
public void setViewerConfiguration(ViewerConfiguration viewerConfiguration)
```

Sets the viewer configuration.

Parameters:

viewerConfiguration - the new viewer configuration.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class PropertyHolder

java.lang.Object
└─com.arcsight.product.manager.resource.service.v1.model.dashboard.PropertyHolder

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[StringPropertyHolder](#), [ListPropertyHolder](#)

public class **PropertyHolder**
extends Object
implements Serializable

A generic Java bean that holds a value of the specified type.

Parameters:
T - the type of value to hold.

[JSON prototype](#)

Constructor Summary

public	PropertyHolder() Creates an instance of the bean.

Method Summary

Object	getPropertyValue() Returns the value of the bean.
void	setPropertyValue(Object propertyValue) Sets the value of the bean.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

PropertyHolder

public **PropertyHolder()**

Creates an instance of the bean.

Methods

getPropertyValue

`public Object getPropertyValue()`

Returns the value of the bean.

Returns:

the value of the bean.

setPropertyValue

`public void setPropertyValue(Object propertyValue)`


Sets the value of the bean.

Parameters:

propertyValue - the new value of the bean.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class QueryViewer



All Implemented Interfaces:
Serializable, Serializable, Serializable

public class **QueryViewer**
extends [ViewableResource](#)
implements Serializable, Serializable, Serializable

DESCRIBE ME

[JSON prototype](#)

Constructor Summary	
public	QueryViewer()

Method Summary	
Map	getColumnAliasMap()
MatrixData	getData()
DrilldownList	getDrilldownList()
String	getQueryViewerId()
long	getRefreshInterval()
boolean	isEnabled() Query Viewers are always enabled
void	setColumnAliasMap(Map columnAliasMap)
void	setData(MatrixData data)
void	setDrilldownList(DrilldownList drilldownList)

void	<u>setQueryViewerId</u> (String queryViewerId)
void	<u>setRefreshInterval</u> (long refreshInterval)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.dashboard.ViewableResource](#)

[getSupportedDataTypes](#), [isEnabled](#), [isSupportsToggle](#), [setEnabled](#), [setSupportedDataTypes](#), [setSupportsToggle](#)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class [java.lang.Object](#)

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

QueryViewer

public **QueryViewer**()

Methods

getQueryViewerId

public String **getQueryViewerId**()

setQueryViewerId

public void **setQueryViewerId**(String queryViewerId)

getData

public [MatrixData](#) **getData**()

setData

public void **setData**([MatrixData](#) data)

getColumnAliasMap

public Map **getColumnAliasMap**()

setColumnAliasMap

public void **setColumnAliasMap**(Map columnAliasMap)

getRefreshInterval

public long **getRefreshInterval**()

setRefreshInterval

public void **setRefreshInterval**(long refreshInterval)

isEnabled

public boolean **isEnabled**()

Query Viewers are always enabled

getDrilldownList

public [DrilldownList](#) **getDrilldownList**()

Returns:

the drilldownList

setDrilldownList

```
public void setDrilldownList(DrilldownList drilldownList)
```

Parameters:

drilldownList - the drilldownList to set

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class StatsData

java.lang.Object

└ [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

└ **com.arcsight.product.manager.resource.service.v1.model.dashboard.StatsData**

All Implemented Interfaces:

Serializable, Serializable

public class **StatsData**

extends [Data](#)

implements Serializable, Serializable

Represents statistical data returned by a Data Monitor probe.

Constructor Summary

public	StatsData()

Method Summary

long[]	getCellBoundaries() Returns an array of the cell boundaries.

List	getCellCounts() Returns a list of cell counts.

String[]	getFieldNames() Returns an array of field names.

List	getFieldValues() Returns a list of field values.

List	getMovingAverageCounts() Returns a list of moving averages.

String	getStatsType() Returns the type of the statistics.

void	setCellBoundaries(long[] cellBoundaries) Returns the array of the cell boundaries.

void	setCellCounts(List cellCounts) Sets the list of cell counts.

void	setFieldNames(String[] fieldNames) Sets the array of field names.

void	setFieldValues (List fieldValues) Sets the list of field values.
void	setMovingAverageCounts (List movingAverageCounts) Sets the list of moving averages.
void	setStatsType (String statsType) Returns the type of the statistics.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Data](#)

[getEndTimestamp](#), [getStartTimestamp](#), [getTimestamp](#), [setEndTimestamp](#), [setStartTimestamp](#), [setTimestamp](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

StatsData

`public StatsData()`

Methods

getFieldValues

`public List getFieldValues()`

Returns a list of field values.

Returns:

a list of field values.

setFieldValues

`public void setFieldValues(List fieldValues)`

Sets the list of field values.

Parameters:

fieldValues - the list of field values.

getMovingAverageCounts

`public List getMovingAverageCounts()`

Returns a list of moving averages.

Returns:
the a list of moving averages.

setMovingAverageCounts

```
public void setMovingAverageCounts(List movingAverageCounts)
```

Sets the list of moving averages.

Parameters:
movingAverageCounts - the list of moving averages.

getCellCounts

```
public List getCellCounts()
```

Returns a list of cell counts.

Returns:
a list of cell counts.

setCellCounts

```
public void setCellCounts(List cellCounts)
```

Sets the list of cell counts.

Parameters:
cellCounts - the list of cell counts.

getFieldNames

```
public String[] getFieldNames()
```

Returns an array of field names.

Returns:
an array of field names.

setFieldNames

```
public void setFieldNames(String[] fieldNames)
```

Sets the array of field names.

Parameters:
fieldNames - the array of field names.

getCellBoundaries

```
public long[] getCellBoundaries()
```

Returns an array of the cell boundaries.

Returns:

an array of the cell boundaries.

setCellBoundaries

```
public void setCellBoundaries(long[] cellBoundaries)
```

Returns the array of the cell boundaries.

Parameters:

`cellBoundaries` - the array of the cell boundaries.

getStatsType

```
public String getStatsType()
```

Returns the type of the statistics.

Returns:

the type of the statistics.

setStatsType

```
public void setStatsType(String statsType)
```


Returns the type of the statistics.

Parameters:

`statsType` - the type of the statistics.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class StringPropertyHolder



```
public class StringPropertyHolder
extends PropertyHolder
```

A Java bean that holds a String value.

Constructor Summary	
public	StringPropertyHolder()
Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.dashboard.PropertyHolder	
getPropertyValue , setPropertyValue	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	


Constructors

StringPropertyHolder

```
public StringPropertyHolder()
```


com.arcsight.product.manager.resource.service.v1.model.dashboard

Class TypedNode



All Implemented Interfaces:
Serializable, Serializable

Direct Known Subclasses:
[EventGraphNode](#)

public class **TypedNode**
extends [Node](#)
implements Serializable, Serializable

A node that has a type.

Constructor Summary

public	TypedNode ()
public	TypedNode (String id, String name, int type) Creates a new instance.

Method Summary

int	getType ()
void	setType (int type)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.dashboard.Node](#)
[equals](#), [getId](#), [getName](#), [hashCode](#), [setId](#), [setName](#)

Methods inherited from class java.lang.Object
[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

TypedNode
public **TypedNode**()

TypedNode

```
public TypedNode(String id,  
                 String name,  
                 int type)
```

Creates a new instance.

Parameters:

id - The ID of the node.
name - The name of the node.
type - The type.

Methods

getType

```
public int getType()
```

setType

```
public void setType(int type)
```

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class ViewableResource



All Implemented Interfaces:
Serializable, Serializable

Direct Known Subclasses:
[QueryViewer](#), [DataMonitor](#)

```
public class ViewableResource
extends Resource
implements Serializable, Serializable
```

Represents a viewable resource -- a resource that can be added to a portlet which in turn can be added to a dashboard.

Constructor Summary

public	ViewableResource()

Method Summary

String[]	getSupportedDataTypes()
boolean	isEnabled() Returns true if the resource is enabled.
boolean	isSupportsToggle() Returns true if this resource supports enable/disable operations.
void	setEnabled(boolean enabled) Sets the flag indicating whether the resource is enabled.
void	setSupportedDataTypes(String[] supportedDataTypes)
void	setSupportsToggle(boolean supportsToggle) Sets the flag indication whether this resource supports enable/disable operations.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ViewableResource

```
public ViewableResource()
```

Methods

isSupportsToggle

```
public boolean isSupportsToggle()
```

Returns true if this resource supports enable/disable operations.

Returns:

true if this resource supports enable/disable operations.

setSupportsToggle

```
public void setSupportsToggle(boolean supportsToggle)
```

Sets the flag indication whether this resource supports enable/disable operations.

Parameters:

`supportsToggle` - true if this resource supports enable/disable operations.

isEnabled

```
public boolean isEnabled()
```

Returns true if the resource is enabled.

Returns:

true if the resource is enabled.

setEnabled

```
public void setEnabled(boolean enabled)
```

Sets the flag indicating whether the resource is enabled.

Parameters:

enabled - true if the resource is enabled.

getSupportedDataTypes

```
public String[] getSupportedDataTypes()
```

Returns:

the supportedDataTypes

setSupportedDataTypes

```
public void setSupportedDataTypes(String[] supportedDataTypes)
```

Parameters:

supportedDataTypes - the supportedDataTypes to set

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class ViewableResourceIntrospector

java.lang.Object

↓
com.arcsight.product.manager.resource.service.v1.model.dashboard.ViewableResourceIntrospector

All Implemented Interfaces:
Serializable

public class **ViewableResourceIntrospector**
extends Object
implements Serializable

A ViewableResourceIntrospector reveals additional information about a ViewableResource.

Constructor Summary

public	ViewableResourceIntrospector()

Method Summary

Map	getAliasToNameMap() Returns a map that maps field aliases into the original field display names.
int[]	getColumnDataTypes() Returns the data types for the columns (matrix data only).
String	getRestrictingFilter() Returns the restricting filter for the resource.
String	getTypeID() Returns the type ID of data this resource provides.
boolean	isSupportsDrillDown() Returns true if this viewable resource supports drill-down.
void	setAliasToNameMap(Map aliasToNameMap) Sets the map that maps field aliases into the original field display names.
void	setColumnDataTypes(int[] columnDataTypes) Sets the data types for the columns (matrix data only).
void	setRestrictingFilter(String restrictingFilter) Sets the restricting filter for the resource.
void	setSupportsDrillDown(boolean supportsDrillDown) Sets the flag indication whether this viewable resource supports drill-down.

void	<code>setTypeID</code> (String typeId) Sets the type ID of data this resource provides.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ViewableResourceIntrospector

`public ViewableResourceIntrospector()`

Methods

getTypeID

`public String getTypeID()`

Returns the type ID of data this resource provides.

Returns:
the type ID of data this resource provides.

setTypeID

`public void setTypeID(String typeId)`

Sets the type ID of data this resource provides.

Parameters:
`typeID` - the type ID of data this resource provides.

getRestrictingFilter

`public String getRestrictingFilter()`

Returns the restricting filter for the resource.

Returns:
the restricting filter for the resource.

setRestrictingFilter

`public void setRestrictingFilter(String restrictingFilter)`

Sets the restricting filter for the resource.

Parameters:

restrictingFilter - the restricting filter for the resource.

isSupportsDrillDown

public boolean **isSupportsDrillDown**()

Returns true if this viewable resource supports drill-down.

Returns:

true if this viewable resource supports drill-down.

setSupportsDrillDown

public void **setSupportsDrillDown**(boolean supportsDrillDown)

Sets the flag indication whether this viewable resource supports drill-down.

Parameters:

supportsDrillDown - true if this viewable resource supports drill-down.

getColumnDataTypes

public int[] **getColumnDataTypes**()

Returns the data types for the columns (matrix data only). Uses FieldTypes values.

Returns:

a list of the supported data types.

setColumnDataTypes

public void **setColumnDataTypes**(int[] columnDataTypes)

Sets the data types for the columns (matrix data only). Uses FieldTypes values.

Parameters:

columnDataTypes - the list of the supported data types.

getAliasToNameMap

public Map **getAliasToNameMap**()

Returns a map that maps field aliases into the original field display names.

Returns:

the a map that maps field aliases into the original field display names.

setAliasToNameMap

public void **setAliasToNameMap**(Map aliasToNameMap)


Sets the map that maps field aliases into the original field display names.

Parameters:

`aliasToNameMap` - the map that maps field aliases into the original field display names.

com.arcsight.product.manager.resource.service.v1.model.dashboard

Class ViewerConfiguration



```
public class ViewerConfiguration
extends Resource
implements Serializable, Serializable
```

Represents a configuration for a viewer.

Constructor Summary	
public	ViewerConfiguration()

Method Summary	
Map	getProperties() Returns the map of the data monitor properties.
String[]	getSupportedDataTypes()
String	getViewerConfigurationType() Returns the viewer type ID; for instance "3D Bar Chart".
void	setProperties() (Map properties) Sets the map of the data monitor properties.
void	setSupportedDataTypes() (String[] supportedDataTypes)
void	setViewerConfigurationType() (String viewerConfigurationType) Sets the viewer type ID; for instance "3D Bar Chart".

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ViewerConfiguration

```
public ViewerConfiguration()
```

Methods

getViewerConfigurationType

```
public String getViewerConfigurationType()
```

Returns the viewer type ID; for instance "3D Bar Chart".

Returns:

the viewerConfigurationType

setViewerConfigurationType

```
public void setViewerConfigurationType(String viewerConfigurationType)
```

Sets the viewer type ID; for instance "3D Bar Chart".

Parameters:

viewerConfigurationType - the new viewer type ID to set.

getProperties

```
public Map getProperties()
```

Returns the map of the data monitor properties.

Returns:

the map of the data monitor properties.

setProperties

```
public void setProperties(Map properties)
```

Sets the map of the data monitor properties.

Parameters:

`properties` - the map of the data monitor properties.

getSupportedDataTypes

```
public String[] getSupportedDataTypes()
```

Returns:

the supportedDataTypes

setSupportedDataTypes

```
public void setSupportedDataTypes(String[] supportedDataTypes)
```

Parameters:


`supportedDataTypes` - the supportedDataTypes to set

Package

com.arcsight.product.manager.resource.service.v1.model.drilldown

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class ActiveChannelDrilldownDefinition



All Implemented Interfaces:
Serializable

public class **ActiveChannelDrilldownDefinition**
extends [DrilldownDefinition](#)

Constructor Summary	
public	ActiveChannelDrilldownDefinition()

Method Summary	
FieldSet	getFieldSet()
String	getSortCriterion()
DrilldownType	getType()
void	setFieldSet(FieldSet fieldSet)
void	setSortCriterion (String sortCriterion)

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition	
getDestinationDisplayName , getDestinationID , getDestinationType , getMenuPrompt , getType , setDestinationDisplayName , setDestinationID , setDestinationType , setMenuPrompt	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ActiveChannelDrilldownDefinition

public **ActiveChannelDrilldownDefinition**()

Methods

getType

public [DrilldownType](#) **getType**()

getFieldSet

public [FieldSet](#) **getFieldSet**()

Returns:
the fieldSet

setFieldSet

public void **setFieldSet**([FieldSet](#) fieldSet)

Parameters:
fieldSet - the fieldSet to set

getSortCriterion

public String **getSortCriterion**()


Returns:
the sortCriterion

setSortCriterion

public void **setSortCriterion**(String sortCriterion)

Parameters:
sortCriterion - the sortCriterion to set

com.arcsight.product.manager.resource.service.v1.model.drilldown Class DashboardDrilldownDefinition



All Implemented Interfaces:
Serializable

public class **DashboardDrilldownDefinition**
extends [DrilldownDefinition](#)

Constructor Summary

public	DashboardDrilldownDefinition()

Method Summary

DrilldownType	getType()

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition](#)

[getDestinationDisplayName](#), [getDestinationID](#), [getDestinationType](#), [getMenuPrompt](#), [getType](#), [setDestinationDisplayName](#), [setDestinationID](#), [setDestinationType](#), [setMenuPrompt](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

DashboardDrilldownDefinition
public **DashboardDrilldownDefinition()**

Methods

getType

public [DrilldownType](#) **getType()**

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class Drilldown

java.lang.Object

└- [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

└- [com.arcsight.product.manager.resource.service.v1.model.drilldown.Drilldown](#)

All Implemented Interfaces:

Serializable, Serializable

public class **Drilldown**

extends [Resource](#)

implements Serializable, Serializable

Constructor Summary

public	Drilldown()

Method Summary

DrilldownDefinition	getDrilldownDefinition()

void	setDrilldownDefinition(DrilldownDefinition drilldownDefinition)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setTypeName](#), [setURI](#), [setVersionID](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

Drilldown

```
public Drilldown()
```

Methods

getDrilldownDefinition

```
public DrilldownDefinition getDrilldownDefinition()
```

Returns:

setDrilldownDefinition

```
public void setDrilldownDefinition(DrilldownDefinition drilldownDefinition)
```

Parameters:

drilldownDefinition

com.arcsight.product.manager.resource.service.v1.model.drilldown Class DrilldownDefinition

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

[ReportDrilldownDefinition](#), [QueryViewerDrilldownDefinition](#), [DashboardDrilldownDefinition](#),
[ActiveChannelDrilldownDefinition](#)

public class **DrilldownDefinition**

extends Object

implements Serializable

Constructor Summary

public	DrilldownDefinition()

Method Summary

String	getDestinationDisplayName()

String	getDestinationID()

int	getDestinationType()

String	getMenuPrompt()

DrilldownType	getType()

void	setDestinationDisplayName(String destinationDisplayName)

void	setDestinationID(String destinationID)

void	setDestinationType(int destinationType)

void	setMenuPrompt(String menuPrompt)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

DrilldownDefinition

```
public DrilldownDefinition()
```

Methods

getDestinationID

```
public String getDestinationID()
```

Returns:
the destination

setDestinationID

```
public void setDestinationID(String destinationID)
```

Parameters:
destinationID - the destination to set

getDestinationDisplayName

```
public String getDestinationDisplayName()
```

Returns:

setDestinationDisplayName

```
public void setDestinationDisplayName(String destinationDisplayName)
```

Parameters:
destinationDisplayName

getDestinationType

```
public int getDestinationType()
```

Returns:

setDestinationType

```
public void setDestinationType(int destinationType)
```

Parameters:

destinationType

getMenuPrompt

```
public String getMenuPrompt()
```

Returns:

the menuPrompt

setMenuPrompt

```
public void setMenuPrompt(String menuPrompt)
```

Parameters:

menuPrompt - the menuPrompt to set

getType

```
public DrilldownType getType()
```

Returns:

the type

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class DrilldownList



All Implemented Interfaces:
Serializable, Serializable

```
public class DrilldownList
extends Resource
implements Serializable, Serializable
```

Constructor Summary

public	DrilldownList()

Method Summary

Drilldown	getDefaultDrilldown()
List	getDrilldowns()
String	getRole()
boolean	isDefault()
void	setDefault(boolean isDefault)
void	setDefaultDrilldown(Drilldown defaultDrilldown)
void	setDrilldowns(List drilldowns)
void	setRole(String role)

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

DrillDownList

```
public DrillDownList()
```

Methods

getRole

```
public String getRole()
```

Returns:

the role

setRole

```
public void setRole(String role)
```

Parameters:

role - the role to set

isDefault

```
public boolean isDefault()
```


Returns:
the isDefault

setDefault

```
public void setDefault(boolean isDefault)
```

Parameters:
isDefault - the isDefault to set

getDrilldowns

```
public List getDrilldowns()
```

Returns:
the drilldowns

setDrilldowns

```
public void setDrilldowns(List drilldowns)
```

Parameters:
drilldowns - the drilldowns to set

getDefaultDrilldown

```
public Drilldown getDefaultDrilldown()
```

Returns:
the defaultDrilldown

setDefaultDrilldown

```
public void setDefaultDrilldown(Drilldown defaultDrilldown)
```

Parameters:
defaultDrilldown - the defaultDrilldown to set

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class DrilldownType

java.lang.Object
└- java.lang.Enum
 └- com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownType

All Implemented Interfaces:
Serializable, Comparable

public final class **DrilldownType**
extends Enum

Field Summary	
public static final	ACTIVE_CHANNEL
public static final	DASHBOARD
public static final	QUERY_VIEWER
public static final	REPORT

Method Summary	
DrilldownDefinition	getEmptyDefinition()
static DrilldownType	valueOf (String name)
static DrilldownType[]	values ()

Methods inherited from class java.lang.Enum	
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Methods inherited from interface java.lang.Comparable	
compareTo	

Fields

ACTIVE_CHANNEL

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownType  
ACTIVE_CHANNEL
```

DASHBOARD

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownType DASHBOARD
```

QUERY_VIEWER

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownType  
QUERY_VIEWER
```

REPORT

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownType REPORT
```

Methods

values

```
public static DrilldownType\[\] values()
```

valueOf

```
public static DrilldownType valueOf(String name)
```

getEmptyDefinition

```
public DrilldownDefinition getEmptyDefinition()
```

Returns:

new instance of drilldown definition of the specified type

Throws:
ServiceException

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class FilterFields

java.lang.Object

└─com.arcsight.product.manager.resource.service.v1.model.drilldown.FilterFields

All Implemented Interfaces:

Serializable

```
public class FilterFields
extends Object
implements Serializable
```

Constructor Summary

public	FilterFields()
public	FilterFields (String baseFieldName, String drilldownFieldName)
public	FilterFields (String[] fieldNames)

Method Summary

boolean	equals (Object obj)
static FilterFields	fromString (String str)
String	getBaseFieldName ()
String	getDrilldownFieldName ()
int	hashCode ()
void	setBaseFieldName (String baseFieldName)
void	setDrilldownFieldName (String drilldownFieldName)
String	toString ()

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

FilterFields

```
public FilterFields()
```

FilterFields

```
public FilterFields(String baseFieldName,  
                    String drilldownFieldName)
```

Parameters:

baseFieldName
drilldownFieldName

FilterFields

```
public FilterFields(String[] fieldNames)
```

Parameters:

fieldNames

Methods

getBaseFieldName

```
public String getBaseFieldName()
```

Returns:

setBaseFieldName

```
public void setBaseFieldName(String baseFieldName)
```

Parameters:

baseFieldName - the baseFieldName to set

getDrilldownFieldName

```
public String getDrilldownFieldName()
```

Returns:

setDrilldownFieldName

```
public void setDrilldownFieldName(String drilldownFieldName)
```

Parameters:

drilldownFieldName - the drilldownFieldName to set

equals

```
public boolean equals(Object obj)
```

hashCode

```
public int hashCode()
```

toString

```
public String toString()
```

fromString

```
public static FilterFields fromString(String str)
```

Parameters:

str

Returns:

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class MapEntry

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.drilldown.MapEntry

All Implemented Interfaces:
Serializable

```
public class MapEntry
extends Object
implements Serializable
```

Constructor Summary

public	MapEntry()
public	MapEntry (String key, ArrayList value)

Method Summary

String	getKey()
ArrayList	getValue()
void	setKey (String key)
void	setValue (ArrayList value)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MapEntry

```
public MapEntry()
```

MapEntry

```
public MapEntry(String key,  
                ArrayList value)
```

Parameters:

key
value

Methods

getKey

```
public String getKey()
```

Returns:

the key

setKey

```
public void setKey(String key)
```

Parameters:

key - the key to set

getValue

```
public ArrayList getValue()
```

Returns:

the value


setValue

```
public void setValue(ArrayList value)
```

Parameters:

value - the value to set

com.arcsight.product.manager.resource.service.v1.model.drilldown Class QueryViewerDrilldownDefinition



public class **QueryViewerDrilldownDefinition**
extends [DrilldownDefinition](#)

Constructor Summary	
public	QueryViewerDrilldownDefinition()

Method Summary	
HashMap	getColumnAliases()
ArrayList	getFilterFields()
ArrayList	getShowColumns()
ArrayList	getSortOrder()
DrilldownType	getType()
void	setColumnAliases (HashMap columnAliases)
void	setFilterFields (ArrayList filterFields)
void	setShowColumns (ArrayList showColumns)
void	setSortOrder (ArrayList sortOrder)

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition	
getDestinationDisplayName , getDestinationID , getDestinationType , getMenuPrompt , getType , setDestinationDisplayName , setDestinationID , setDestinationType , setMenuPrompt	

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

QueryViewerDrilldownDefinition

```
public QueryViewerDrilldownDefinition()
```

Methods

getType

```
public DrilldownType getType()
```

getFilterFields

```
public ArrayList getFilterFields()
```

Returns:

the filterFields

setFilterFields

```
public void setFilterFields(ArrayList filterFields)
```

Parameters:

filterFields - the filterFields to set

getSortOrder

```
public ArrayList getSortOrder()
```

Returns:

the sortOrder

setSortOrder

```
public void setSortOrder(ArrayList sortOrder)
```

Parameters:

sortOrder - the sortOrder to set

getShowColumns

```
public ArrayList getShowColumns()
```

Returns:

the showColumns

setShowColumns

```
public void setShowColumns(ArrayList showColumns)
```

Parameters:

showColumns - the showColumns to set

getColumnAliases

```
public HashMap getColumnAliases()
```

Returns:

the columnAliases

setColumnAliases

```
public void setColumnAliases(HashMap columnAliases)
```

Parameters:

columnAliases - the columnAliases to set

com.arcsight.product.manager.resource.service.v1.model.drilldown

Class ReportDrilldownDefinition

java.lang.Object
└- [com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition](#)
└- **com.arcsight.product.manager.resource.service.v1.model.drilldown.ReportDrilldownDefinition**
All Implemented Interfaces:
 Serializable

public class **ReportDrilldownDefinition**
extends [DrilldownDefinition](#)

Constructor Summary	
public	ReportDrilldownDefinition()

Method Summary	
ArrayList	getFilterFields()
DrilldownType	getType()
void	setFilterFields (ArrayList filterFields)

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.drilldown.DrilldownDefinition	
getDestinationDisplayName , getDestinationID , getDestinationType , getMenuPrompt , getType , setDestinationDisplayName , setDestinationID , setDestinationType , setMenuPrompt	

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

ReportDrilldownDefinition
public **ReportDrilldownDefinition()**

Methods

getType

public [DrilldownType](#) **getType()**

getFilterFields

public ArrayList **getFilterFields()**

Returns:

the filterFields

setFilterFields

public void **setFilterFields**(ArrayList filterFields)

Parameters:

filterFields - the filterFields to set

Package

com.arcsight.product.manager.resource.service.v1.model.event

com.arcsight.product.manager.resource.service.v1.model.event Class AdditionalData

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.event.AdditionalData

All Implemented Interfaces:

Comparable, Serializable

```
public class AdditionalData
extends Object
implements Serializable, Comparable
```

Definition of additional data field. Fields are defined by their name, type, and the value.

JSON prototype

Nested Class Summary

class	AdditionalData.DataType AdditionalData.DataType

Constructor Summary

public	AdditionalData()

Method Summary

int	compareTo(AdditionalData key) Compares this object with the specified object for order.
boolean	equals(AdditionalData additionalData) Returns whether this additional data is equal to the given additional data additionalData.
static String	getDefaultValue() Returns the default value of the field.
String	getName() Returns the name of the field.
byte	getType() Returns the type of the field.
String	getValue() Returns the value of the field.
int	hashCode()

void	setName (String name) Sets the name of the field.
void	setType (byte type) Sets the type of the field.
void	setValue (String value) Sets the value of the field.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Constructors

AdditionalData

```
public AdditionalData()
```

Methods

getName

```
public String getName()
```

Returns the name of the field.

Returns:

name of the field

setName

```
public void setName(String name)
```

Sets the name of the field.

Parameters:

name

getType

```
public byte getType()
```

Returns the type of the field.

Returns:

The type of the field

See Also:

[AdditionalData.DataType](#)

setType

```
public void setType(byte type)
```

Sets the type of the field.

Parameters:

type - The type of the field

See Also:

[AdditionalData.DataType](#)

getValue

```
public String getValue()
```

Returns the value of the field.

Returns:

The value of the field

setValue

```
public void setValue(String value)
```

Sets the value of the field.

Parameters:

value - The value of the field

getDefaultValue

```
public static String getDefaultValue()
```

Returns the default value of the field. That value will be used if no value is specified explicitly.

Returns:

The default value of the field.

equals

```
public boolean equals(AdditionalData additionalData)
```

Returns whether this additional data is equal to the given additional data additionalData.

Parameters:

additionalData - Another field

hashCode

```
public int hashCode()
```

compareTo

```
public int compareTo(AdditionalData key)
```

Compares this object with the specified object for order.

Returns:

A negative integer, zero, or a positive integer as this object is less than, equal to, or greater than the specified object.

com.arcsight.product.manager.resource.service.v1.model.event Interface AdditionalData.DataType

public interface **AdditionalData.DataType**
extends

Definitions of data types

Field Summary	
public static final	DATATYPE_BLOB BLOB entry Value: 12
public static final	DATATYPE_BOOLEAN A true/false or yes/no Value: 0
public static final	DATATYPE_BYTE A single byte Value: 1
public static final	DATATYPE_BYTE_ARRAY A java byte array Value: 10
public static final	DATATYPE_CHARACTER A single character Value: 2
public static final	DATATYPE_CLOB CLOB entry Value: 11
public static final	DATATYPE_DATE A date byte DATATYPE_as per IDMEF Section 5 Value: 3
public static final	DATATYPE_INTEGER An integer Value: 4
public static final	DATATYPE_IPv4_ADDRESS IPv4 Address Value: 15
public static final	DATATYPE_IPv6_ADDRESS IPv6 Address Value: 13

public static final	DATATYPE_LONG A long Value: 9
public static final	DATATYPE_NTPSTAMP An NTP timestamp as per IDMEF Section 5 Value: 5
public static final	DATATYPE_REAL A floating-point number Value: 6
public static final	DATATYPE_RESOURCE_REFERENCE_URI Resource Reference URI Value: 14
public static final	DATATYPE_STRING A String of characters Value: 7
public static final	DATATYPE_XML An XML string for extensions Value: 8

Fields

DATATYPE_BOOLEAN

public static final byte **DATATYPE_BOOLEAN**

A true/false or yes/no
Constant value: **0**

DATATYPE_BYTE

public static final byte **DATATYPE_BYTE**

A single byte
Constant value: **1**

DATATYPE_CHARACTER

public static final byte **DATATYPE_CHARACTER**

A single character
Constant value: **2**

DATATYPE_DATE

public static final byte **DATATYPE_DATE**

A date byte **DATATYPE**_as per IDMEF Section 5

Constant value: 3

DATATYPE_INTEGER

public static final byte **DATATYPE_INTEGER**

An integer
Constant value: 4

DATATYPE_NTPSTAMP

public static final byte **DATATYPE_NTPSTAMP**

An NTP timestamp as per IDMEF Section 5
Constant value: 5

DATATYPE_REAL

public static final byte **DATATYPE_REAL**

A floating-point number
Constant value: 6

DATATYPE_STRING

public static final byte **DATATYPE_STRING**

A String of characters
Constant value: 7

DATATYPE_XML

public static final byte **DATATYPE_XML**

An XML string for extensions
Constant value: 8

DATATYPE_LONG

public static final byte **DATATYPE_LONG**

A long
Constant value: 9

DATATYPE_BYTE_ARRAY

public static final byte **DATATYPE_BYTE_ARRAY**

A java byte array
Constant value: 10

DATATYPE_CLOB

public static final byte **DATATYPE_CLOB**

CLOB entry
Constant value: 11

DATATYPE_BLOB

public static final byte **DATATYPE_BLOB**

BLOB entry
Constant value: 12

DATATYPE_IPv6_ADDRESS

public static final byte **DATATYPE_IPv6_ADDRESS**

IPv6 Address
Constant value: 13

DATATYPE_RESOURCE_REFERENCE_URI

public static final byte **DATATYPE_RESOURCE_REFERENCE_URI**

Resource Reference URI
Constant value: 14

DATATYPE_IPv4_ADDRESS

public static final byte **DATATYPE_IPv4_ADDRESS**

IPv4 Address
Constant value: 15

com.arcsight.product.manager.resource.service.v1.model.event

Class AddressableDescriptorBase

java.lang.Object

└─ [com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

└─

com.arcsight.product.manager.resource.service.v1.model.event.AddressableDescriptorBase

All Implemented Interfaces:

Comparable, Serializable, Serializable

Direct Known Subclasses:

[SensorRelatedDescriptorBase](#), [EndPointDescriptor](#)

public class **AddressableDescriptorBase**

extends [MutableBase](#)

implements Serializable, Serializable, Comparable

The base part of descriptors for various network nodes.

JSON prototype

Constructor Summary

public	AddressableDescriptorBase()

Method Summary

int	compareTo (AddressableDescriptorBase d) Compares this object with the specified object for order.

boolean	equalsDescriptorBase (AddressableDescriptorBase descriptor) Returns whether this object is equal to the another object descriptor.

long	getAddress () Deprecated. This method doesn't provide support for IPv6 addresses. Rather use new method getAddressAsBytes () .

byte[]	getAddressAsBytes () Returns byte array representation the network address of the endpoint.

String	getAssetId () Returns the assetId representing the addressable object's host.

long	getAssetLocalId () Returns the assetLocalId representing the addressable object's host.

String	getAssetName () Returns asset's name.

String	getDnsDomain() Returns the DNS domain this endpoint is part of.
String	getHostName() Returns host name of the endpoint.
long	getMacAddress() Returns the MAC address of the end point.
String	getNtDomain() Returns the NT domain of which this endpoint is part of.
long	getTranslatedAddress() Deprecated. <i>This method doesn't provide support for IPv6 addresses. Rather use new method getTranslatedAddressAsBytes().</i>
byte[]	getTranslatedAddressAsBytes() Returns byte array representation of the translated address of the end point.
ResourceReference	getTranslatedZone() Returns the translated Network Identifier.
ResourceReference	getZone() Returns the reference to endpoint's zone.
int	hashCode()
void	setAddress(long address) Deprecated. <i>This method doesn't provide support for IPv6 addresses. Rather use new method setAddressAsBytes(byte[]).</i>
void	setAddressAsBytes(byte[] address) Sets the network address of the endpoint.
void	setAssetId(String assetId) Sets the assetId representing the addressable object's host.
void	setAssetLocalId(long assetLocalId) Sets the assetLocalId representing the addressable object's host.
void	setAssetName(String assetName) Sets asset's name.
void	setDnsDomain(String dnsDomain) Sets the DNS domain this endpoint is part of.
void	setHostName(String hostName) Sets host name of the endpoint.
void	setMacAddress(long macAddress) Sets the MAC address of the end point.
void	setNtDomain(String ntDomain) Sets the NT domain of which this endpoint is part of.

void	setTranslatedAddress (long translatedAddress) Deprecated. <i>This method doesn't provide support for IPv6 addresses. Rather use new method setTranslatedAddressAsBytes(byte[]).</i>
void	setTranslatedAddressAsBytes (byte[] translatedAddress) Sets the translated address of the end point.
void	setTranslatedZone (ResourceReference translatedZone) Sets the Translated Network Identifier.
void	setZone (ResourceReference zone) Sets the reference to zone.

Methods inherited from class
[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Constructors

AddressableDescriptorBase

```
public AddressableDescriptorBase()
```

Methods

getHostName

```
public String getHostName()
```

Returns host name of the endpoint.

Returns:

The host name of the endpoint

setHostName

```
public void setHostName(String hostName)
```

Sets host name of the endpoint.

Parameters:

getAddress

```
public long getAddress()
```

Deprecated. *This method doesn't provide support for IPv6 addresses. Rather use new method [getAddressAsBytes\(\)](#).*

Returns the network address as a long number.

Returns:

The network address

getAddressAsBytes

```
public byte[] getAddressAsBytes()
```

Returns byte array representation the network address of the endpoint.

Returns:

Byte array representation of the network address

setAddress

```
public void setAddress(long address)
```

Deprecated. *This method doesn't provide support for IPv6 addresses. Rather use new method [setAddressAsBytes\(byte\[\]\)](#).*

Sets the network address of the endpoint.

Parameters:

address - the network address.

setAddressAsBytes

```
public void setAddressAsBytes(byte[] address)
```

Sets the network address of the endpoint. Generally, IPv6 address strings may contain a "scope ID", such as "%9" or "%eth0", however these scopes are ignored by ArcSight code, and they are removed when parsing IPv6 strings.

Parameters:

address - Byte array representation of the network address. For example, 2001:0db8:1111:4444:8888:cccc:eeee:ffff or 192.0.20.255.

getZone

```
public ResourceReference getZone()
```

Returns the reference to endpoint's zone.

Returns:

Reference to the zone

setZone

public void **setZone**([ResourceReference](#) zone)

Sets the reference to zone.

Parameters:

zone - Reference to the zone

getNtDomain

public String **getNtDomain**()

Returns the NT domain of which this endpoint is part of.

Returns:

NT domain

setNtDomain

public void **setNtDomain**(String ntDomain)

Sets the NT domain of which this endpoint is part of.

Parameters:

ntDomain - NT domain

getDnsDomain

public String **getDnsDomain**()

Returns the DNS domain this endpoint is part of.

Returns:

DNS domain

setDnsDomain

public void **setDnsDomain**(String dnsDomain)

Sets the DNS domain this endpoint is part of.

Parameters:

dnsDomain - DNS domain

getAssetId

public String **getAssetId**()

Returns the assetId representing the addressable object's host.

Returns:

asset ID of the host

setAssetId

```
public void setAssetId(String assetId)
```

Sets the assetId representing the addressable object's host.

Parameters:

assetId - ID of the host

getAssetLocalId

```
public long getAssetLocalId()
```

Returns the assetLocalId representing the addressable object's host.

Returns:

localId of the host

setAssetLocalId

```
public void setAssetLocalId(long assetLocalId)
```

Sets the assetLocalId representing the addressable object's host.

Parameters:

assetLocalId - localId of the host

getTranslatedAddress

```
public long getTranslatedAddress()
```

Deprecated. *This method doesn't provide support for IPv6 addresses. Rather use new method [getTranslatedAddressAsBytes\(\)](#).*

Returns the translated address of the end point as a long number. If network address translation is an issue, this is the translated IP address of the device hosting the SmartConnector.

Returns:

Long representation of the translated address

getTranslatedAddressAsBytes

```
public byte[] getTranslatedAddressAsBytes()
```

Returns byte array representation of the translated address of the end point. If network address translation is an issue, this is the translated IP address of the device hosting the SmartConnector.

Returns:

Byte array representation of the translated address

setTranslatedAddress

```
public void setTranslatedAddress(long translatedAddress)
```

Deprecated. *This method doesn't provide support for IPv6 addresses. Rather use new method [setTranslatedAddressAsBytes\(byte\[\]\)](#).*

Sets the translated address of the end point.

Parameters:

translatedAddress - Long representation of the translated address

setTranslatedAddressAsBytes

```
public void setTranslatedAddressAsBytes(byte[] translatedAddress)
```

Sets the translated address of the end point.

Parameters:

translatedAddress - Byte array representation of the translated address. For example, 2001:0db8:1111:4444:8888:cccc:eeee:ffff or 192.0.20.255.

getMacAddress

```
public long getMacAddress()
```

Returns the MAC address of the end point.

Returns:

MAC address

setMacAddress

```
public void setMacAddress(long macAddress)
```

Sets the MAC address of the end point.

Parameters:

macAddress - MAC address

getTranslatedZone

```
public ResourceReference getTranslatedZone()
```

Returns the translated Network Identifier.

Returns:

Translated Network Identifier

setTranslatedZone

```
public void setTranslatedZone(ResourceReference translatedZone)
```

Sets the Translated Network Identifier.

Parameters:

translatedZone - Translated Network Identifier

getAssetName

```
public String getAssetName()
```

Returns asset's name.

Returns:

asset name

setAssetName

```
public void setAssetName(String assetName)
```

Sets asset's name.

Parameters:

assetName - Asset name

equalsDescriptorBase

```
public boolean equalsDescriptorBase(AddressableDescriptorBase descriptor)
```

Returns whether this object is equal to the another object descriptor.

Parameters:

descriptor - another object to compare with

hashCode

```
public int hashCode()
```

compareTo

```
public int compareTo(AddressableDescriptorBase d)
```


Compares this object with the specified object for order.

Returns:

A negative integer, zero, or a positive integer as this object is less than, equal to, or greater than the specified object.

com.arcsight.product.manager.resource.service.v1.model.event

Class AgentDescriptor



All Implemented Interfaces:
Serializable, Comparable, Serializable, Serializable

```
public class AgentDescriptor
extends SensorRelatedDescriptorBase
implements Serializable, Comparable, Serializable, Serializable
```

Description of Connector

JSON prototype

Constructor Summary	
public	AgentDescriptor()

Method Summary	
boolean	equals (AgentDescriptor agentDescriptor) Returns whether this object is equal to the another object agentDescriptor.
String	getId () Returns the string uniquely identifying this agent.
String	getName () Returns the user-supplied name associated with this Connector.
String	getType () Returns the description of the type of this Connector.
int	hashCode ()
void	setId (String id) Sets the string uniquely identifying this agent.
void	setName (String name) Sets the user-supplied name associated with this Connector.

void	setType (String type) Sets the description of the type of this Connector.

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.event.SensorRelatedDescriptorBase
equals , getDescriptorId , getTimeZone , getVersion , hashCode , setDescriptorId , setTimeZone , setVersion

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.event.AddressableDescriptorBase
compareTo , equalsDescriptorBase , getAddress , getAddressAsBytes , getAssetId , getAssetLocalId , getAssetName , getDnsDomain , getHostName , getMacAddress , getNtDomain , getTranslatedAddress , getTranslatedAddressAsBytes , getTranslatedZone , getZone , hashCode , setAddress , setAddressAsBytes , setAssetId , setAssetLocalId , setAssetName , setDnsDomain , setHostName , setMacAddress , setNtDomain , setTranslatedAddress , setTranslatedAddressAsBytes , setTranslatedZone , setZone

Methods inherited from class com.arcsight.product.manager.resource.service.v1.model.event.MutableBase
isMutable , setMutable

Methods inherited from class java.lang.Object
equals , getClass , hashCode , notify , notifyAll , toString , wait , wait , wait

Methods inherited from interface java.lang.Comparable
compareTo

Constructors

AgentDescriptor

public AgentDescriptor()

Methods

getId

public String getId()

Returns the string uniquely identifying this agent.

Returns:

Agent ID

setId

```
public void setId(String id)
```

Sets the string uniquely identifying this agent.

Parameters:

id - Agent ID

getType

```
public String getType()
```

Returns the description of the type of this Connector.

Returns:

The type of the Connector

setType

```
public void setType(String type)
```

Sets the description of the type of this Connector.

Parameters:

type - The type of the Connector

getName

```
public String getName()
```

Returns the user-supplied name associated with this Connector.

Returns:

The name of the Connector

setName

```
public void setName(String name)
```

Sets the user-supplied name associated with this Connector.

Parameters:

name - The name of the Connector

equals

```
public boolean equals(AgentDescriptor agentDescriptor)
```

Returns whether this object is equal to the another object agentDescriptor.

Parameters:

agentDescriptor - another object to compare with

hashCode

```
public int hashCode()
```

com.arcsight.product.manager.resource.service.v1.model.event

Class ArcField

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.model.event.ArcField

All Implemented Interfaces:

Comparable, Serializable

```
public class ArcField
extends Object
implements Serializable, Comparable
```

This class describes the field concept in the system. it has the following main contents. 1. field name, 2. the display name (used to be Label) 3. type 4. the database info of the field. 5. The grouping info such as the group name and the short name. the internal implementation fields are 1. containing class, the class which contains this field. 2. the field index, (this is assigned by the original introspector, which created this field.)

Note: this class has a natural ordering that is inconsistent with equals .. this is ordered by fieldIndex

Constructor Summary

public	ArcField() A constructor to create a field with default values.
public	ArcField(String fieldName) A constructor to create a field with default values and specified name.
public	ArcField(String fieldName, int fieldIndex) A constructor to create a field with default values and the specified name and index.

Method Summary

int	compareTo(ArcField o)
String	getConstantShortFieldName() Returns an optional display name, which will be used when short display name is needed.
String	getCopyOfFieldName() Returns the internal field name.
String	getFieldDisplayName() Returns the display name that could used in dialogs.
int	getFieldIndex() Returns the index of the field.
String	getFieldName() Returns the name of this ArcField.

FieldType	getFieldType() Returns the type of the field.
String	getGroupDisplayName() Returns the display name of the group containing this field.
String	getGroupName() Returns the name of the group containing this field.
boolean	isDerived() Checks if the field is derived field or not...
boolean	isReference() Checks if the field is reference field or not...
boolean	isSidetable() if this is a sidetable field.
boolean	isSimple() If this field is a simple field, that is just a column in the table returned by getDbTableName.
void	setConstantShortFieldName(String constantShortFieldName) Sets the optional display name, which will be used when short display name is needed.
void	setCopyOfFieldName(String copyOfFieldName) Sets the internal field name.
void	setDerived(boolean derived) Set the flag to indicate that the field is derived or not.
void	setFieldDisplayName(String fieldDisplayName) Sets the display name that could be used in dialogs.
void	setFieldIndex(int fieldIndex) Sets the index of the field.
void	setFieldName(String fieldName) Sets the name of this ArcField.
void	setFieldType(FieldType fieldType) Sets the type of the field.
void	setGroupDisplayName(String groupDisplayName) Sets the display name of the group containing this field.
void	setGroupName(String groupName) Sets the name of the group containing this field.
void	setReference(boolean reference) Set the flag to indicate that the field is reference to another ArcField or not.
void	setSidetable(boolean sidetableField) Set the flag to indicate that the field is sidetable or not.

void	setSimple (boolean simple) Set the flag to indicate that the field is simple or not.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Constructors

ArcField

```
public ArcField()
```

A constructor to create a field with default values.

ArcField

```
public ArcField(String fieldName)
```

A constructor to create a field with default values and specified name.

Parameters:

fieldName - The name of ArcField

ArcField

```
public ArcField(String fieldName,
                int fieldIndex)
```

A constructor to create a field with default values and the specified name and index.

Parameters:

fieldName - The name of ArcField

fieldIndex - The index

Methods

getFieldName

```
public String getFieldName()
```

Returns the name of this ArcField.

Returns:

setFieldName

```
public void setFieldName(String fieldName)
```

Sets the name of this ArcField.

Parameters:

fieldName - The name

getCopyOfFieldName

```
public String getCopyOfFieldName()
```

Returns the internal field name. For domain field, this will return the attribute name corresponding to the internal db column.

Returns:

The internal field name

setCopyOfFieldName

```
public void setCopyOfFieldName(String copyOfFieldName)
```

Sets the internal field name. For domain field it contains the attribute name corresponding to the internal db column.

Parameters:

copyOfFieldName - The internal field name.

getFieldDisplayName

```
public String getFieldDisplayName()
```

Returns the display name that could used in dialogs.

Returns:

The display name

setFieldDisplayName

```
public void setFieldDisplayName(String fieldDisplayName)
```

Sets the display name that could used in dialogs.

Parameters:

fieldDisplayName - The display name

getFieldType

```
public FieldType getFieldType()
```

Returns the type of the field.

Returns:

The type

setFieldType

```
public void setFieldType(FieldType fieldType)
```

Sets the type of the field.

Parameters:

fieldType - The type

getGroupDisplayName

```
public String getGroupDisplayName()
```

Returns the display name of the group containing this field.

Returns:

Group's display name

setGroupDisplayName

```
public void setGroupDisplayName(String groupDisplayName)
```

Sets the display name of the group containing this field.

Parameters:

groupDisplayName - Group's display name

getGroupName

```
public String getGroupName()
```

Returns the name of the group containing this field.

Returns:

Group's name

setGroupName

```
public void setGroupName(String groupName)
```

Sets the name of the group containing this field.

Parameters:

groupName - Group's name

getConstantShortFieldName

```
public String getConstantShortFieldName()
```

Returns an optional display name, which will be used when short display name is needed. When a field shown in a group its not necessary to show the full field display name. they instead show the following name.

Returns:

Optional short display name

setConstantShortFieldName

```
public void setConstantShortFieldName(String constantShortFieldName)
```

Sets the optional display name, which will be used when short display name is needed. When a field shown in a group its not necessary to show the full field display name. they instead show the following name.

Parameters:

constantShortFieldName - Optional short display name

getFieldIndex

```
public int getFieldIndex()
```

Returns the index of the field. NOTE: don't use this index in anything, they are subject to change.

Returns:

The index of the field

setFieldIndex

```
public void setFieldIndex(int fieldIndex)
```

Sets the index of the field. NOTE: don't use this index in anything, they are subject to change.

Parameters:

fieldIndex - The index of the field

isSimple

```
public boolean isSimple()
```

If this field is a simple field, that is just a column in teh table returned by getDbTableName.

Returns:

if its a simple field.

setSimple

```
public void setSimple(boolean simple)
```

Set the flag to indicate that the field is simple or not.

Parameters:

simple - Whether the field is simple

isDerived

```
public boolean isDerived()
```

Checks if the field is derived field or not...

Returns:

true if the arcfield is derived from another arcfield.

setDerived

```
public void setDerived(boolean derived)
```

Set the flag to indicate that the field is derived or not.

Parameters:

derived - Whether the field is derived

isReference

```
public boolean isReference()
```

Checks if the field is reference field or not... A reference field is one which refers to another ArcSight table. An example would be source asset id which refers to a arc_resource table

Returns:

true if the ArcField is a reference to another ArcSight table.

setReference

```
public void setReference(boolean reference)
```

Set the flag to indicate that the field is reference to another ArcField or not.

Parameters:

derived - Whether the field is reference

isSidetable

```
public boolean isSidetable()
```

if this is a sidetable field. The side table field could be based on another sidetable field, a derived field, or a simple field.

Returns:

true if its a sidetable field.

setSidetable

```
public void setSidetable(boolean sidetableField)
```

Set the flag to indicate that the field is sidetable or not.

Parameters:

derived - Whether the field is sidetable

compareTo

```
public int compareTo(ArcField o)
```

com.arcsight.product.manager.resource.service.v1.model.event

Class BaseAnnotation

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.event.BaseAnnotation

All Implemented Interfaces:
Comparable, Serializable

Direct Known Subclasses:
[EventAnnotation](#)

public class **BaseAnnotation**
extends Object
implements Serializable, Comparable

Event Annotation contains any user workflow assignments that ESM users have added to an event after it was received and stored at the Manager.

JSON prototype

Constructor Summary	
public	BaseAnnotation()

Method Summary	
int	compareTo (BaseAnnotation d)
String	getAuditTrail () Returns a string that represents the audit trail for this event annotation.
String	getComment () Returns a comment added to the annotation.
int	getFlags () Returns the flags which are set in the annotation.
long	getModificationTime () Returns the time of the last modification of this annotation.
ResourceReference	getModifiedBy () Returns the reference to the user that made the last change to this annotation.
ResourceReference	getStage () Returns the current disposition of the event.
Long	getStageUpdateTime () Returns the last time the stage of this event was changed.

ResourceReference	getStageUser() Returns a reference to a Resource describing stage user.
int	getVersion() Returns the version of this event annotation.
void	setAuditTrail(String auditTrail) Sets the string that represents the audit trail for this event annotation.
void	setComment(String comment) Sets the comment to this annotation.
void	setFlags(int flags) Sets the flags which are set in the annotation.
void	setModificationTime(long modificationTime) Sets the time of the last modification of this annotation.
void	setModifiedBy(ResourceReference modifiedBy) Sets the reference to the user that made the last change to this annotation.
void	setStage(ResourceReference stage) Sets the current disposition of the event.
void	setStageUpdateTime(Long lastStageUpdateTime) Sets the last time the stage of this event was changed.
void	setStageUser(ResourceReference stageUser) Sets the reference to a Resource describing stage user.
void	setVersion(int version) Sets the version of this event annotation.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Constructors

BaseAnnotation

`public BaseAnnotation()`

Methods

getStage

public [ResourceReference](#) **getStage()**

Returns the current disposition of the event.

Returns:

The current stage of the event

setStage

public void **setStage**([ResourceReference](#) stage)

Sets the current disposition of the event. Stage is used in annotation workflow.

Parameters:

stage - The current stage of the event

getFlags

public int **getFlags()**

Returns the flags which are set in the annotation.

Returns:

The flags

setFlags

public void **setFlags**(int flags)

Sets the flags which are set in the annotation.

Parameters:

flags - The flags

getComment

public String **getComment()**

Returns a comment added to the annotation.

Returns:

A comment

setComment

public void **setComment**(String comment)

Sets the comment to this annotation.

Parameters:

comment - The comment

getStageUser

public [ResourceReference](#) **getStageUser()**

Returns a reference to a Resource describing stage user.

Returns:

Stage user

setStageUser

public void **setStageUser**([ResourceReference](#) stageUser)

Sets the reference to a Resource describing stage user.

Parameters:

stageUser - Stage User

getStageUpdateTime

public Long **getStageUpdateTime()**

Returns the last time the stage of this event was changed.

Returns:

Update time

setStageUpdateTime

public void **setStageUpdateTime**(Long lastStageUpdateTime)

Sets the last time the stage of this event was changed.

Parameters:

lastStageUpdateTime - Update time

getModifiedBy

public [ResourceReference](#) **getModifiedBy()**

Returns the reference to the user that made the last change to this annotation.

Returns:

The user that made last change

setModifiedBy

public void **setModifiedBy**([ResourceReference](#) modifiedBy)

Sets the reference to the user that made the last change to this annotation.

Parameters:

modifiedBy - The user that made last change

getModificationTime

```
public long getModificationTime()
```

Returns the time of the last modification of this annotation.

Returns:

The time of the last update

setModificationTime

```
public void setModificationTime(long modificationTime)
```

Sets the time of the last modification of this annotation.

Parameters:

modificationTime - The time of the last update

getAuditTrail

```
public String getAuditTrail()
```

Returns a string that represents the audit trail for this event annotation.

Returns:

Audit trail of the annotation

setAuditTrail

```
public void setAuditTrail(String auditTrail)
```

Sets the string that represents the audit trail for this event annotation.

Parameters:

auditTrail - Audit trail of the annotation

getVersion

```
public int getVersion()
```

Returns the version of this event annotation.

Returns:

The version

setVersion

```
public void setVersion(int version)
```

Sets the version of this event annotation.

Parameters:

version - The version

compareTo

public int **compareTo**([BaseAnnotation](#) d)

com.arcsight.product.manager.resource.service.v1.model.event

Class CategoryDescriptor

java.lang.Object

↳ [com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

↳ [com.arcsight.product.manager.resource.service.v1.model.event.CategoryDescriptor](#)

All Implemented Interfaces:

Comparable, Serializable, Serializable

```
public class CategoryDescriptor
```

```
extends MutableBase
```

```
implements Serializable, Serializable, Comparable
```

Category is a general description of the event as defined by the ESM event categories applied to it by the SmartConnector that received it. Categories are Object, Behavior, Outcome, Technique, Device Group, and Significance.

[JSON prototype](#)

Constructor Summary

public	CategoryDescriptor()

Method Summary

int	compareTo (CategoryDescriptor d)

boolean	equals (CategoryDescriptor categoryDescriptor) Returns whether this object is equal to the another object categoryDescriptor.

String	getBehavior () Returns the action taken with or by the object.

String	getCustomFormatField () Returns the description of the content of a custom formatted field, if present.

Long	getDescriptorId () Returns the unique ID for the category.

String	getDeviceGroup () Returns device group of the event.

String	getDeviceType () Returns device type of event.

String	getObject () Returns the physical or virtual object that was the focus of the event.

String	getOutcome() Reflects whether or not the action was successfully applied to the object.
String	getSignificance() Characterizes the event from a network-intrusion-detection perspective.
String	getTechnique() Returns the method used to apply the action to the object.
String	getTupleDescription() Returns the description of the event category, assembled from the category components.
int	hashCode()
void	setBehavior() (String behavior) Sets the action taken with or by the object.
void	setCustomFormatField() (String customFormatField) Sets the description of the content of a custom formatted field.
void	setDescriptorId() (Long descriptorId) Sets the unique ID for the category.
void	setDeviceGroup() (String deviceGroup) Sets the device group of the event.
void	setDeviceType() (String deviceType) Sets device type of event.
void	setObject() (String object) Sets the physical or virtual object that was the focus of the event.
void	setOutcome() (String outcome) Sets the indications of whether or not the action was successfully applied to the object.
void	setSignificance() (String significance) Sets the significance that characterizes the event from a network-intrusion-detection perspective.
void	setTechnique() (String technique) Sets the method used to apply the action to the object.
void	setTupleDescription() (String tupleDescription) Sets the description of the event category, assembled from the category components.

Methods inherited from class
[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

compareTo

Constructors

CategoryDescriptor

```
public CategoryDescriptor()
```

Methods

getDescriptorId

```
public Long getDescriptorId()
```

Returns the unique ID for the category.

Returns:

Category ID

setDescriptorId

```
public void setDescriptorId(Long descriptorId)
```

Sets the unique ID for the category.

Parameters:

descriptorId - category ID

getObject

```
public String getObject()
```

Returns the physical or virtual object that was the focus of the event.

Returns:

Object that the event focused on

setObject

```
public void setObject(String object)
```

Sets the physical or virtual object that was the focus of the event.

Parameters:

object - Object that the event focused on

getBehavior

```
public String getBehavior()
```

Returns the action taken with or by the object.

Returns:

The action

setBehavior

```
public void setBehavior(String behavior)
```

Sets the action taken with or by the object.

Parameters:

behavior - The action

getTechnique

```
public String getTechnique()
```

Returns the method used to apply the action to the object.

Returns:

The method

setTechnique

```
public void setTechnique(String technique)
```

Sets the method used to apply the action to the object.

Parameters:

technique - The method

getSignificance

```
public String getSignificance()
```

Characterizes the event from a network-intrusion-detection perspective.

Returns:

The significance

setSignificance

```
public void setSignificance(String significance)
```

Sets the significance that characterizes the event from a network-intrusion-detection perspective.

Parameters:

significance - The significance

getOutcome

```
public String getOutcome()
```

Reflects whether or not the action was successfully applied to the object.

Returns:

The outcome

setOutcome

```
public void setOutcome(String outcome)
```

Sets the indications of whether or not the action was successfully applied to the object.

Parameters:

outcome - The outcome

getDeviceGroup

```
public String getDeviceGroup()
```

Returns device group of the event. Many security devices serve multiple purposes. For example, Intrusion Prevention Systems generate firewall events as well as intrusion detection events. The Device group category indicates whether an event is one type or another.

Returns:

Device group of the event

setDeviceGroup

```
public void setDeviceGroup(String deviceGroup)
```

Sets the device group of the event. Many security devices serve multiple purposes. For example, Intrusion Prevention Systems generate firewall events as well as intrusion detection events. The Device group category indicates whether an event is one type or another.

Parameters:

deviceGroup - Device group of the event

getDeviceType

```
public String getDeviceType()
```

Returns device type of event. For example, logging into a firewall is an Operating System type of event.

Returns:

The type of the event

setDeviceType

```
public void setDeviceType(String deviceType)
```

Sets device type of event. For example, logging into a firewall is an Operating System type of event.

Parameters:
deviceType

getTupleDescription

public String **getTupleDescription**()

Returns the description of the event category, assembled from the category components.

Returns:
The description of the event category

setTupleDescription

public void **setTupleDescription**(String tupleDescription)

Sets the description of the event category, assembled from the category components.

Parameters:
tupleDescription - The description of the event category

getCustomFormatField

public String **getCustomFormatField**()

Returns the description of the content of a custom formatted field, if present.

Returns:
The description of custom field

setCustomFormatField

public void **setCustomFormatField**(String customFormatField)

Sets the description of the content of a custom formatted field.

Parameters:
customFormatField - The description of custom field

equals

public boolean **equals**([CategoryDescriptor](#) categoryDescriptor)

Returns whether this object is equal to the another object categoryDescriptor.

Parameters:
categoryDescriptor - another object to compare with

hashCode


public int **hashCode**()

compareTo

public int **compareTo**([CategoryDescriptor](#) d)

com.arcsight.product.manager.resource.service.v1.model.event

Class DefaultFieldSet



All Implemented Interfaces:
Serializable, Serializable

```
public class DefaultFieldSet
extends Resource
implements Serializable, Serializable
```

A default implementation of a resource of type Field Set.

JSON prototype

Constructor Summary	
public	DefaultFieldSet()

Method Summary	
ArrayList	getFieldArchivalReferenceList() Returns a collection of references to objects in a archive.
ArrayList	getFieldReferenceList() Returns the fields assigned to this field set.
void	setFieldArchivalReferenceList(ArrayList fieldArchivalReferenceList) Sets the collection of references to objects in a archive.
void	setFieldReferenceList(ArrayList fieldReferenceList) Sets the fields assigned to this field set.

Methods inherited from class [com.arcsight.product.manager.resource.service.v1.model.Resource](#)

[getAlias](#), [getContentVersionID](#), [getCreatedTime](#), [getCreatedTimestamp](#), [getCreatorName](#), [getDescription](#), [getDisabledReason](#), [getDisplayName](#), [getExternalID](#), [getInactiveReason](#), [getInCache](#), [getLocalID](#), [getModificationCount](#), [getModifiedTime](#), [getModifiedTimestamp](#), [getModifierName](#), [getName](#), [getNotificationGroupIDs](#), [getReference](#), [getReferencePage](#), [getResourceid](#), [getSignature](#), [getState](#), [getSubType](#), [getType](#), [getTypeName](#), [getURI](#), [getVersionID](#), [isAttributeInitializationInProgress](#), [isDeprecated](#), [isDisabled](#), [isInactive](#), [isInitialized](#), [isIsAdditionalLoaded](#), [setAlias](#), [setAttributeInitializationInProgress](#), [setContentVersionID](#), [setCreatedTime](#), [setCreatedTimestamp](#), [setCreatorName](#), [setDeprecated](#), [setDescription](#), [setDisabled](#), [setDisabledReason](#), [setExternalID](#), [setInactive](#), [setInactiveReason](#), [setInCache](#), [setInitialized](#), [setIsAdditionalLoaded](#), [setLocalID](#), [setModificationCount](#), [setModifiedTime](#), [setModifiedTimestamp](#), [setModifierName](#), [setName](#), [setNotificationGroupIDs](#), [setReference](#), [setReferencePage](#), [setResourceid](#), [setState](#), [setSubType](#), [setType](#), [setType_name](#), [setURI](#), [setVersionID](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

DefaultFieldSet

```
public DefaultFieldSet()
```

Methods

getFieldReferenceList

```
public ArrayList getFieldReferenceList()
```

Returns the fields assigned to this field set.

Returns:

The collection of fields

setFieldReferenceList

```
public void setFieldReferenceList(ArrayList fieldReferenceList)
```

Sets the fields assigned to this field set.

Parameters:

`fieldReferenceList` - The collection of fields

getFieldArchivalReferenceList

```
public ArrayList getFieldArchivalReferenceList()
```

Returns a collection of references to objects in a archive.

Returns:

Collection of references

setFieldArchivalReferenceList

```
public void setFieldArchivalReferenceList(ArrayList fieldArchivalReferenceList)
```


Sets the collection of references to objects in a archive.

Parameters:

fieldArchivalReferenceList - Collection of references

com.arcsight.product.manager.resource.service.v1.model.event

Class DeviceDescriptor



```
public class DeviceDescriptor
extends SensorRelatedDescriptorBase
implements Serializable, Serializable, Comparable, Serializable, Serializable
```

Description of the Device

JSON prototype

Constructor Summary	
public	DeviceDescriptor()

Method Summary	
boolean	equals(DeviceDescriptor deviceDescriptor) Returns whether this object is equal to the another object deviceDescriptor.
String	getExternalId() Returns the external identifier associated with this sensor device, if provided by the vendor.
String	getFacility() Returns the sensor submodule that reported the event.
String	getInboundInterface() Returns the NIC card on the sensor device that received the network traffic associated with the event.
String	getOutboundInterface() Returns the NIC card on the sensor device that transmitted the network traffic associated with the event.
String	getProcessName() Returns the name of the sensor device process that reported the event.

String	<u>getProduct()</u> Returns the product name of the sensor device.
String	<u>getVendor()</u> Returns the vendor who manufactured or sold the sensor device.
int	<u>hashCode()</u>
void	<u>setExternalId(String externalId)</u> Sets the external identifier associated with this sensor device, if provided by the vendor.
void	<u>setFacility(String facility)</u> Sets the sensor submodule that reported the event.
void	<u>setInboundInterface(String inboundInterface)</u> Sets the NIC card on the sensor device that received the network traffic associated with the event.
void	<u>setOutboundInterface(String outboundInterface)</u> Sets the NIC card on the sensor device that transmitted the network traffic associated with the event.
void	<u>setProcessName(String processName)</u> Sets the name of the sensor device process that reported the event.
void	<u>setProduct(String product)</u> Sets the product name of the sensor device.
void	<u>setVendor(String vendor)</u> Sets the vendor who manufactured or sold the sensor device.

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.SensorRelatedDescriptorBase](#)

[equals](#), [getDescriptorId](#), [getTimeZone](#), [getVersion](#), [hashCode](#), [setDescriptorId](#), [setTimeZone](#), [setVersion](#)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.AddressableDescriptorBase](#)

[compareTo](#), [equalsDescriptorBase](#), [getAddress](#), [getAddressAsBytes](#), [getAssetId](#), [getAssetLocalId](#), [getAssetName](#), [getDnsDomain](#), [getHostName](#), [getMacAddress](#), [getNtDomain](#), [getTranslatedAddress](#), [getTranslatedAddressAsBytes](#), [getTranslatedZone](#), [getZone](#), [hashCode](#), [setAddress](#), [setAddressAsBytes](#), [setAssetId](#), [setAssetLocalId](#), [setAssetName](#), [setDnsDomain](#), [setHostName](#), [setMacAddress](#), [setNtDomain](#), [setTranslatedAddress](#), [setTranslatedAddressAsBytes](#), [setTranslatedZone](#), [setZone](#)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Constructors

DeviceDescriptor

`public DeviceDescriptor()`

Methods

getExternalId

`public String getExternalId()`

Returns the external identifier associated with this sensor device, if provided by the vendor.

Returns:

The external identifier

setExternalId

`public void setExternalId(String externalId)`

Sets the external identifier associated with this sensor device, if provided by the vendor.

Parameters:

`externalId` - The external identifier

getVendor

`public String getVendor()`

Returns the vendor who manufactured or sold the sensor device.

Returns:

The vendor of the device

setVendor

`public void setVendor(String vendor)`

Sets the vendor who manufactured or sold the sensor device.

Parameters:

`vendor` - The vendor of the device

getProduct

```
public String getProduct()
```

Returns the product name of the sensor device.

Returns:

The product name

setProduct

```
public void setProduct(String product)
```

Sets the product name of the sensor device.

Parameters:

product - The product name

getFacility

```
public String getFacility()
```

Returns the sensor submodule that reported the event.

Returns:

The submodule reported the event

setFacility

```
public void setFacility(String facility)
```

Sets the sensor submodule that reported the event.

Parameters:

facility - The submodule reported the event

getInboundInterface

```
public String getInboundInterface()
```

Returns the NIC card on the sensor device that received the network traffic associated with the event.

Returns:

The NIC card on the sensor

setInboundInterface

```
public void setInboundInterface(String inboundInterface)
```

Sets the NIC card on the sensor device that received the network traffic associated with the event.

Parameters:

inboundInterface - The NIC card on the sensor

getOutboundInterface

public String **getOutboundInterface**()

Returns the NIC card on the sensor device that transmitted the network traffic associated with the event.

Returns:

The NIC card on the sensor

setOutboundInterface

public void **setOutboundInterface**(String outboundInterface)

Sets the NIC card on the sensor device that transmitted the network traffic associated with the event.

Parameters:

outboundInterface - The NIC card on the sensor

getProcessName

public String **getProcessName**()

Returns the name of the sensor device process that reported the event.

Returns:

The name of the sensor reported the event

setProcessName

public void **setProcessName**(String processName)

Sets the name of the sensor device process that reported the event.

Parameters:

processName - The name of the sensor reported the event

equals

public boolean **equals**([DeviceDescriptor](#) deviceDescriptor)

Returns whether this object is equal to the another object deviceDescriptor.

Parameters:

deviceDescriptor - another object to compare with


hashCode

public int **hashCode**()

com.arcsight.product.manager.resource.service.v1.model.event

Class EndPointDescriptor

java.lang.Object



All Implemented Interfaces:

Serializable, Serializable, Comparable, Serializable

public class **EndPointDescriptor**

extends [AddressableDescriptorBase](#)

implements Serializable, Comparable, Serializable, Serializable

Description of communication end-point.

JSON prototype

Constructor Summary

public	EndPointDescriptor ()

Method Summary

boolean	equals (EndPointDescriptor endPointDescriptor) Returns whether this object is equal to the another object endPointDescriptor.
GeoDescriptor	getGeo () Returns a reference to an object describing geo-location.
int	getPort () Returns the port number for this communication end-point.
int	getProcessId () Returns PID of the process running on that communication end-point.
String	getProcessName () Returns the name of the process.
static String	getSeparatorToken () Returns a string that is used as a separator between fields.
String	getServiceName () Returns the name of the service.
int	getTranslatedPort () Returns the translated port for this communication end-point

String	<u>getUserId()</u> Returns the user ID for this communication end-point.
String	<u>getUserName()</u> Returns the user name for this communication end-point.
String	<u>getUserPrivileges()</u> Returns user privileges
int	<u>hashCode()</u>
void	<u>setGeo()</u> (<u>GeoDescriptor</u> geo) Sets a reference to an object describing geo-location.
void	<u>setPort()</u> (int port) Sets the port number for this communication end-point.
void	<u>setProcessId()</u> (int processId) Sets the process ID.
void	<u>setProcessName()</u> (String processName) Sets the name of the process
void	<u>setServiceName()</u> (String serviceName) Sets the name of the service.
void	<u>setTranslatedPort()</u> (int translatedPort) Sets the translated port for this communication end-point.
void	<u>setUserId()</u> (String userId) Sets the user ID for this communication end-point.
void	<u>setUserName()</u> (String userName) Sets the user name for this communication end-point.
void	<u>setUserPrivileges()</u> (String userPrivileges) Saves information about user privileges

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.AddressableDescriptorBase](#)

[compareTo](#), [equalsDescriptorBase](#), [getAddress](#), [getAddressAsBytes](#), [getAssetId](#), [getAssetLocalId](#), [getAssetName](#), [getDnsDomain](#), [getHostName](#), [getMacAddress](#), [getNtDomain](#), [getTranslatedAddress](#), [getTranslatedAddressAsBytes](#), [getTranslatedZone](#), [getZone](#), [hashCode](#), [setAddress](#), [setAddressAsBytes](#), [setAssetId](#), [setAssetLocalId](#), [setAssetName](#), [setDnsDomain](#), [setHostName](#), [setMacAddress](#), [setNtDomain](#), [setTranslatedAddress](#), [setTranslatedAddressAsBytes](#), [setTranslatedZone](#), [setZone](#)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class `java.lang.Object`

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

compareTo

Constructors

EndPointDescriptor

```
public EndPointDescriptor()
```

Methods

getProcessId

```
public int getProcessId()
```

Returns PID of the process running on that communication end-point.

Returns:

Process ID

setProcessId

```
public void setProcessId(int processId)
```

Sets the process ID.

Parameters:

processId - process ID

getPort

```
public int getPort()
```

Returns the port number for this communication end-point.

Returns:

port number

setPort

```
public void setPort(int port)
```

Sets the port number for this communication end-point.

Parameters:

port - port number

getTranslatedPort

public int **getTranslatedPort**()

Returns the translated port for this communication end-point

Returns:

The translated port

setTranslatedPort

public void **setTranslatedPort**(int translatedPort)

Sets the translated port for this communication end-point.

Parameters:

translatedPort - The translated port

getUserName

public String **getUserName**()

Returns the user name for this communication end-point.

Returns:

The user name

setUserName

public void **setUserName**(String userName)

Sets the user name for this communication end-point.

Parameters:

userName - The user name

getUserId

public String **getUserId**()

Returns the user ID for this communication end-point.

Returns:

user ID

setUserId

public void **setUserId**(String userId)

Sets the user ID for this communication end-point.

Parameters:

userId - user ID

getProcessName

public String **getProcessName**()

Returns the name of the process.

Returns:

Name of the process

setProcessName

public void **setProcessName**(String processName)

Sets the name of the process

Parameters:

processName - Name of the process

getServiceName

public String **getServiceName**()

Returns the name of the service.

Returns:

Name of the service

setServiceName

public void **setServiceName**(String serviceName)

Sets the name of the service.

Parameters:

serviceName - Name of the service

getUserPrivileges

public String **getUserPrivileges**()

Returns user privileges

Returns:

User privileges

setUserPrivileges

public void **setUserPrivileges**(String userPrivileges)

Saves information about user privileges

Parameters:

userPrivileges - User privileges

getGeo

public [GeoDescriptor](#) **getGeo()**

Returns a reference to an object describing geo-location.

Returns:

Description of geo-location

setGeo

public void **setGeo**([GeoDescriptor](#) geo)

Sets a reference to an object describing geo-location.

Parameters:

geo - Description of geo-location

getSeparatorToken

public static String **getSeparatorToken()**

Returns a string that is used as a separator between fields.

Returns:

Field's separator

equals

public boolean **equals**([EndPointDescriptor](#) endPointDescriptor)

Returns whether this object is equal to the another object endPointDescriptor.

Parameters:

endPointDescriptor - another object to compare with

hashCode

public int **hashCode()**

com.arcsight.product.manager.resource.service.v1.model.event

Class EventAnnotation

java.lang.Object

↳ [com.arcsight.product.manager.resource.service.v1.model.event.BaseAnnotation](#)

↳ [com.arcsight.product.manager.resource.service.v1.model.event.EventAnnotation](#)

All Implemented Interfaces:

Serializable, Comparable, Serializable

public class **EventAnnotation**

extends [BaseAnnotation](#)

implements Serializable, Comparable, Serializable

Event Annotation contains any user workflow assignments that ESM users have added to an event after it was received and stored at the Manager.

JSON prototype

Constructor Summary

public	EventAnnotation()

Method Summary

long	getEndTime() Returns the end time of the event.

Long	getEventId() Returns the identifier of the event to which this annotation is attached.

long	getManagerReceiptTime() Returns the time when the event was received by ESM Manager.

Long	getStageEventId() Returns the reference to an internal identifier for another event.

void	setEndTime(long endTime) Sets the end time of the event.

void	setEventId(Long eventId) Sets the identifier of the event to which this annotation is attached.

void	setManagerReceiptTime(long managerReceiptTime) Sets the time when the event was received by ESM Manager.

void	setStageEventId(Long stageEventId) Sets the reference to an internal identifier for another event.

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.BaseAnnotation](#)

[compareTo](#), [getAuditTrail](#), [getComment](#), [getFlags](#), [getModificationTime](#), [getModifiedBy](#), [getStage](#), [getStageUpdateTime](#), [getStageUser](#), [getVersion](#), [setAuditTrail](#), [setComment](#), [setFlags](#), [setModificationTime](#), [setModifiedBy](#), [setStage](#), [setStageUpdateTime](#), [setStageUser](#), [setVersion](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Constructors

EventAnnotation

```
public EventAnnotation()
```

Methods

getEventId

```
public Long getEventId()
```

Returns the identifier of the event to which this annotation is attached.

Returns:

ID of the event

setEventId

```
public void setEventId(Long eventId)
```

Sets the identifier of the event to which this annotation is attached.

Parameters:

`eventId` - ID of the event

getEndTime

```
public long getEndTime()
```

Returns the end time of the event.

Returns:

The end time

setEndTime

public void **setEndTime**(long endTime)

Sets the end time of the event.

Parameters:

endTime - The end time

getManagerReceiptTime

public long **getManagerReceiptTime**()

Returns the time when the event was received by ESM Manager.

Returns:

The time received by ESM manager

setManagerReceiptTime

public void **setManagerReceiptTime**(long managerReceiptTime)

Sets the time when the event was received by ESM Manager.

Parameters:

managerReceiptTime - The time received by ESM manager

getStageEventId

public Long **getStageEventId**()

Returns the reference to an internal identifier for another event. It is used by 'Mark Similar'.

Returns:

ID of the internal event used for 'Mark Similar'

setStageEventId

public void **setStageEventId**(Long stageEventId)

Sets the reference to an internal identifier for another event. It is used by 'Mark Similar'.

Parameters:

stageEventId - ID of the internal event used for 'Mark Similar'

com.arcsight.product.manager.resource.service.v1.model.event

Class FieldFilter

java.lang.Object
└─com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter

All Implemented Interfaces:
Serializable

public class **FieldFilter**
extends Object
implements Serializable

Description of a filter that could be added to a field. Use filters to specify criteria that narrows the scope of monitored data.

JSON prototype

Nested Class Summary	
class	FieldFilter.FilterType FieldFilter.FilterType

Constructor Summary	
public	FieldFilter() Constructor to create an empty filter.
public	FieldFilter(FieldFilter.FilterType type) Constructor to create a filter of the type type.
public	FieldFilter(FieldFilter.FilterType type, String fieldName) Constructor to create a filter of the type type and with field name fieldName.
public	FieldFilter(FieldFilter.FilterType type, String[] fieldNames) Constructor to create a filter of the type type and with field names fieldNames.

Method Summary	
String	getFieldName() Returns a single field used by the filter.
String[]	getFieldNames() Returns names of the fields used by the filter
FieldType	getFieldType() Returns the type of the field assigned to the filter.
FieldFilter.FilterType	getFilterType() Returns the type of the filter.

boolean	getStrict()
void	setFieldName (String fieldName) Sets the single name of field to be used in filter as a parameter.
void	setFieldNames (String[] fieldNames) Sets names of the fields to be used by the filter as parameters.
void	setFieldType (FieldType fieldType) Sets the type of the field to be used along with the filter.
void	setFilterType (FieldFilter.FilterType type) Sets the type of the filter.
void	setStrict (boolean isStrict)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

FieldFilter

`public FieldFilter()`

Constructor to create an empty filter.

FieldFilter

`public FieldFilter(FieldFilter.FilterType type)`

Constructor to create a filter of the type `type`.

Parameters:

`type` - The type of the filter

FieldFilter

`public FieldFilter(FieldFilter.FilterType type,
String fieldName)`

Constructor to create a filter of the type `type` and with field name `fieldName`. The name of the field might be used by filter as an additional parameter during verifications.

Parameters:

`type` - The type of the filter

`fieldName` - The name of the field where to assign the filter

FieldFilter

```
public FieldFilter(FieldFilter.FilterType type,  
                  String[] fieldNames)
```

Constructor to create a filter of the type `type` and with field names `fieldNames`. The names of the fields might be used by filter as an additional parameter during verifications.

Parameters:

`type` - The type of the filter

`fieldNames` - The names of the fields

Methods

getFilterType

```
public FieldFilter.FilterType getFilterType()
```

Returns the type of the filter.

Returns:

The type

setFilterType

```
public void setFilterType(FieldFilter.FilterType type)
```

Sets the type of the filter.

Parameters:

`type` - The type

getFieldName

```
public String getFieldName()
```

Returns a single field used by the filter.

Returns:

Field name

setFieldName

```
public void setFieldName(String fieldName)
```

Sets the single name of field to be used in filter as a parameter. The filter will accept different items based on that value.

Parameters:

`fieldName` - Field name

getFieldNames

```
public String[] getFieldNames()
```

Returns names of the fields used by the filter

Returns:

Names of the fields

setFieldNames

```
public void setFieldNames(String[] fieldNames)
```

Sets names of the fields to be used by the filter as parameters. The filter will accept different items based on that values.

Parameters:

fieldNames

getStrict

```
public boolean getStrict()
```

setStrict

```
public void setStrict(boolean isStrict)
```

getFieldType

```
public FieldType getFieldType()
```

Returns the type of the field assigned to the filter.

Returns:

The type of the field

setFieldType

```
public void setFieldType(FieldType fieldType)
```

Sets the type of the field to be used along with the filter.

Parameters:

fieldType - The type of the field

com.arcsight.product.manager.resource.service.v1.model.event

Class FieldFilter.FilterType

java.lang.Object

└─ java.lang.Enum

└─

com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType

All Implemented Interfaces:

Serializable, Comparable

public static final class **FieldFilter.FilterType**
extends Enum

List of available filter types.

Field Summary	
public static final	AcceptAllFieldFilter A field filter that accepts all fields.
public static final	AggregatableFieldFilter A field filter that accepts all computationally safe fields.
public static final	AllowItemDefinitionFieldFilter Filter for pattern item definitions.
public static final	ArchiveFieldFilter The filter that sifts out sidetable fields.
public static final	CaseOnlyFieldFilter This filter accepts only pure case related fields and not the fields from preserved events attached to the case.
public static final	CCEFieldSetFilter Filter for a FieldSet (allows through all the fields in a field set).
public static final	CompositeFieldFilter A composite field filter uses other simpler field filters to compose filtering logic.
public static final	FieldListFilter To accept fields specified in the list based on either display name of field name.
public static final	FieldNameFilter To accept fields specified in the list based on field name.
public static final	GroupBySetEventFieldFilter To accept fields from a standard field set (not from INVALID_FIELDS).
public static final	InvalidGroupByFieldFilter To accept fields from another standard field set INVALID_FIELDS.

public static final	OmitFieldFilter The filter that allows to specify which field to omit.
public static final	SessionListFieldFilter It filters out the time fields that cannot be used for populating a session list.
public static final	SetEventFieldFilter Similar to GroupBySetEventFieldFilter.
public static final	SimpleFieldFilter A filter to accept only fields of simple type.
public static final	SortableFieldFilter To accept only fields of the type FieldType.TYPE_CLASS
public static final	SpecialCaseValidGroupByFieldFilter A filter to accept fields from another undocumented array VALID_FIELDS
public static final	TimeFieldFilter A field filter that accepts endTime and managerReceiptTime fields only.
public static final	TypeFieldFilter FieldFilter for allowing only a specified type.
public static final	UIGroupFieldFilter A field filter to get the fields belonging to a UI Group.
public static final	VirtualEventSchemaFieldFilter To accept fields from VirtualEventSchema

Method Summary

FieldFilter.FilterType static e	valueOf (String name)
FieldFilter.FilterType static e[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

AcceptAllFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
AcceptAllFieldFilter
```

A field filter that accepts all fields.

AggregatableFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
AggregatableFieldFilter
```

A field filter that accepts all computationally safe fields.

AllowItemDefinitionFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
AllowItemDefinitionFieldFilter
```

Filter for pattern item definitions.

ArchiveFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
ArchiveFieldFilter
```

The filter that sifts out sidetable fields.

CaseOnlyFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
CaseOnlyFieldFilter
```

This filter accepts only pure case related fields and not the fields from preserved events attached to the case.

CCEFieldSetFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
CCEFieldSetFilter
```

Filter for a FieldSet (allows through all the fields in a field set).

CompositeFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
CompositeFieldFilter
```

A composite field filter uses other simpler field filters to compose filtering logic.

FieldListFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
FieldListFilter
```

To accept fields specified in the list based on either display name of field name.

FieldNameFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
FieldNameFilter
```

To accept fields specified in the list based on field name.

GroupBySetEventFieldFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
GroupBySetEventFieldFilter
```

To accept fields from a standard field set (not from INVALID_FIELDS).

InvalidGroupByFieldFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
InvalidGroupByFieldFilter
```

To accept fields from another standard field set INVALID_FIELDS.

OmitFieldFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
OmitFieldFilter
```

The filter that allows to specify which field to omit.

SessionListFieldFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
SessionListFieldFilter
```

It filters out the time fields that cannot be used for populating a session list.

SetEventFieldFilter

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType
SetEventFieldFilter
```

Similar to GroupBySetEventFieldFilter. To accept fields from a standard field set (not from INVALID_FIELDS).

SimpleFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
SimpleFieldFilter
```

A filter to accept only fields of simple type.

SortableFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
SortableFieldFilter
```

To accept only fields of the type `FieldType.CLASS`

SpecialCaseValidGroupByFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
SpecialCaseValidGroupByFieldFilter
```

A filter to accept fields from another undocumented array `VALID_FIELDS`

TimeFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
TimeFieldFilter
```

A field filter that accepts `endTime` and `managerReceiptTime` fields only.

TypeFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
TypeFieldFilter
```

FieldFilter for allowing only a specified type.

UIGroupFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
UIGroupFieldFilter
```

A field filter to get the fields belonging to a UI Group.

VirtualEventSchemaFieldFilter

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.FieldFilter.FilterType  
VirtualEventSchemaFieldFilter
```

To accept fields from `VirtualEventSchema`

Methods

values

public static [FieldFilter.FilterType\[\]](#) **values**()

valueOf

public static [FieldFilter.FilterType](#) **valueOf**(String name)

com.arcsight.product.manager.resource.service.v1.model.event

Class FileDescriptor

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.event.FileDescriptor

All Implemented Interfaces:
Serializable

public class **FileDescriptor**
extends Object
implements Serializable

Constructor Summary	
public	FileDescriptor()

Method Summary	
boolean	equals(FileDescriptor fileDescriptor) Returns whether this object is equal to the another object agentDescriptor.
long	getCreateTime() Returns the time when the resource, file were created.
String	getHash() Returns the hash code associated with the file's contents (for example, MD5).
String	getId() Returns the external identifier associated with the file.
long	getModificationTime() Returns the time when the resource was modified.
String	getName() Returns the file name, resource name or vulnerability id etc.
String	getPath() Returns the directory path to the file in the file system.
String	getPermission() Returns user permissions associated with the file (sensor specific).
long	getSize() The size of the file (typically in bytes; sensor specific).
String	getType() Returns sensor specific type of the file, resource etc.

int	hashCode()
void	setCreateTime (long createTime) Sets the time when the resource, file were created.
void	setHash (String hash) Sets the hash code associated with the file's contents (for example, MD5).
void	setId (String id) Sets the external identifier associated with the file.
void	setModificationTime (long modificationTime) Sets the time when the resource was modified.
void	setName (String name) Sets file name.
void	setPath (String path) Sets the directory path to the file in the file system.
void	setPermission (String permission) Sets user permissions associated with the file (sensor specific).
void	setSize (long size) Sets the size of the file (typically in bytes; sensor specific).
void	setType (String type) Sets sensor specific type of the file, resource.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

FileDescriptor

```
public FileDescriptor()
```

Methods

getName

```
public String getName()
```

Returns the file name, resource name or vulnerability id etc.

Returns:

File name

setName

public void **setName**(String name)

Sets file name.

Parameters:

name - File name

getPath

public String **getPath**()

Returns the directory path to the file in the file system.

Returns:

File path

setPath

public void **setPath**(String path)

Sets the directory path to the file in the file system.

Parameters:

path - File path

getId

public String **getId**()

Returns the external identifier associated with the file.

setId

public void **setId**(String id)

Sets the external identifier associated with the file.

Parameters:

id - Identifier

getType

public String **getType**()

Returns sensor specific type of the file, resource etc.

Returns:

The type of the file

setType

```
public void setType(String type)
```

Sets sensor specific type of the file, resource.

Parameters:

type - The type

getSize

```
public long getSize()
```

The size of the file (typically in bytes; sensor specific).

Returns:

File size

setSize

```
public void setSize(long size)
```

Sets the size of the file (typically in bytes; sensor specific).

Parameters:

size - File size

getCreateTime

```
public long getCreateTime()
```

Returns the time when the resource, file were created.

Returns:

Creation time (in UTC).

setCreateTime

```
public void setCreateTime(long createTime)
```

Sets the time when the resource, file were created.

Parameters:

createTime - Creation time (in UTC).

getModificationTime

```
public long getModificationTime()
```

Returns the time when the resource was modified.

Returns:

Modification time (in UTC).

setModificationTime

```
public void setModificationTime(long modificationTime)
```

Sets the time when the resource was modified.

Parameters:

modificationTime - Modification time (in UTC).

getPermission

```
public String getPermission()
```

Returns user permissions associated with the file (sensor specific).

Returns:

permission User permissions

setPermission

```
public void setPermission(String permission)
```

Sets user permissions associated with the file (sensor specific).

Parameters:

permission - User permissions

getHash

```
public String getHash()
```

Returns the hash code associated with the file's contents (for example, MD5).

Returns:

The hash of the file

setHash

```
public void setHash(String hash)
```

Sets the hash code associated with the file's contents (for example, MD5).

Parameters:

hash - The hash code

equals

```
public boolean equals(FileDescriptor fileDescriptor)
```

Returns whether this object is equal to the another object agentDescriptor.

Parameters:

agentDescriptor - another object to compare with


hashCode

```
public int hashCode()
```


com.arcsight.product.manager.resource.service.v1.model.event

Class GeoDescriptor

java.lang.Object



All Implemented Interfaces:

Comparable, Serializable, Serializable

```
public class GeoDescriptor
extends MutableBase
implements Serializable, Serializable, Comparable
```

Description of geo-location that could be use to identify various geographical information like location of device, server, attacker, others.

JSON prototype

Constructor Summary

public	GeoDescriptor()

Method Summary

int	compareTo (GeoDescriptor d)
boolean	equals (GeoDescriptor geoDescriptor) Returns whether this object is equal to the another object endPointDescriptor.
String	getCountryCode () Returns the code of country associated with this geo-location.
String	getCountryName () Returns the country name associated with this geo-location.
Long	getDescriptorId () Returns the ID of this description.
String	getFlagImageType () Returns internal data representing part of complete URL to resource.
String	getFlagUrlBase () Returns internal data representing part of complete URL to resource.
double	getLatitude () Returns the latitude of this geo-location.

long	<u>getLatitudeLong()</u> Returns the latitude of this geo-location rounded to integers.
String	<u>getLocationInfo()</u> Returns the additional information associated with this geo-location..
double	<u>getLongitude()</u> Returns the longitude of this geo-location.
long	<u>getLongitudeLong()</u> Returns the longitude of this geo-location rounded to integers.
String	<u>getPostalCode()</u> Returns the postal code associated with this geo-location.
String	<u>getRegionCode()</u> Returns code of the region associated with this geo-location.
int	<u>hashCode()</u>
void	<u>setCountryCode()</u> (String countryCode) Sets the code of the country associated with this geo-location.
void	<u>setCountryName()</u> (String name) Sets the country name information associated with this geo-location.
void	<u>setDescriptorId()</u> (Long descriptorId) Sets the ID of the description.
void	<u>setLatitude()</u> (double latitude) Sets the latitude of this geo-location.
void	<u>setLatitudeLong()</u> (long latitudeLong) Sets the latitude of this geo-location rounded to integers.
void	<u>setLocationInfo()</u> (String locationInfo) Sets the additional information associated with this geo-location.
void	<u>setLongitude()</u> (double longitude) Sets the longitude of this geo-location.
void	<u>setLongitudeLong()</u> (long longitudeLong) Sets rounded to integers longitude of this geo-location.
void	<u>setPostalCode()</u> (String postalCode) Sets the postal code associated with this geo-location.
void	<u>setRegionCode()</u> (String regionCode) Sets the code of the region associated with this geo-location.

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Comparable`

`compareTo`

Constructors

GeoDescriptor

```
public GeoDescriptor()
```

Methods

getDescriptorId

```
public Long getDescriptorId()
```

Returns the ID of this description.

Returns:

Description ID

setDescriptorId

```
public void setDescriptorId(Long descriptorId)
```

Sets the ID of the description.

Parameters:

`descriptorId` - Description ID

getLongitude

```
public double getLongitude()
```

Returns the longitude of this geo-location.

Returns:

The longitude

setLongitude

```
public void setLongitude(double longitude)
```

Sets the longitude of this geo-location.

Parameters:

getLongitudeLong

public long **getLongitudeLong**()

Returns the longitude of this geo-location rounded to integers.

Returns:

The longitude

setLongitudeLong

public void **setLongitudeLong**(long longitudeLong)

Sets rounded to integers longitude of this geo-location.

Parameters:

longitude - The longitude

getLatitude

public double **getLatitude**()

Returns the latitude of this geo-location.

Returns:

The latitude

setLatitude

public void **setLatitude**(double latitude)

Sets the latitude of this geo-location.

Parameters:

latitude - The latitude

getLatitudeLong

public long **getLatitudeLong**()

Returns the latitude of this geo-location rounded to integers.

Returns:

The latitude

setLatitudeLong

public void **setLatitudeLong**(long latitudeLong)

Sets the latitude of this geo-location rounded to integers.

Parameters:

getPostalCode

```
public String getPostalCode()
```

Returns the postal code associated with this geo-location.

Returns:

Postal code

setPostalCode

```
public void setPostalCode(String postalCode)
```

Sets the postal code associated with this geo-location.

Parameters:

postalCode

getRegionCode

```
public String getRegionCode()
```

Returns code of the region associated with this geo-location.

Returns:

Code of the region

setRegionCode

```
public void setRegionCode(String regionCode)
```

Sets the code of the region associated with this geo-location.

Parameters:

regionCode

getCountryCode

```
public String getCountryCode()
```

Returns the code of country associated with this geo-location.

Returns:

Code of the country

setCountryCode

```
public void setCountryCode(String countryCode)
```

Sets the code of the country associated with this geo-location.

Parameters:

getLocationInfo

```
public String getLocationInfo()
```

Returns the additional information associated with this geo-location..

Returns:

Additional information

setLocationInfo

```
public void setLocationInfo(String locationInfo)
```

Sets the additional information associated with this geo-location.

Parameters:

locationInfo - Additional information

getFlagUrlBase

```
public String getFlagUrlBase()
```

Returns internal data representing part of complete URL to resource.

Returns:

The string "/arcsight/web/images/flags/"

getFlagImageType

```
public String getFlagImageType()
```

Returns internal data representing part of complete URL to resource.

Returns:

The string ".gif"

getCountryName

```
public String getCountryName()
```

Returns the country name associated with this geo-location.

Returns:

The name of the country

setCountryName

```
public void setCountryName(String name)
```

Sets the country name information associated with this geo-location.

Parameters:

string - of the country's name

equals

```
public boolean equals(GeoDescriptor geoDescriptor)
```

Returns whether this object is equal to the another object endPointDescriptor.

Parameters:

endPointDescriptor - another object to compare with

hashCode


```
public int hashCode()
```

compareTo

```
public int compareTo(GeoDescriptor d)
```

com.arcsight.product.manager.resource.service.v1.model.event

Class LabelsDescriptor



All Implemented Interfaces:
Comparable, Serializable, Serializable

```
public class LabelsDescriptor
extends MutableBase
implements Serializable, Serializable, Comparable
```

Description of labels for various custom fields.

JSON prototype

Constructor Summary	
public	LabelsDescriptor()

Method Summary	
int	compareTo (LabelsDescriptor d)
boolean	equals (LabelsDescriptor labelsDescriptor) Returns whether this object is equal to the another object labelsDescriptor.
String	getDate1Label () Returns a label for the first custom date field.
String	getDate2Label () Returns a label for the second custom date field.
Long	getDescriptorId () Returns the unique identifier for this description.
String	getFloatingPoint1Label () Returns a label for the first custom floating point field.
String	getFloatingPoint2Label () Returns a label for the second custom floating point field.
String	getFloatingPoint3Label () Returns a label for the third custom floating point field.

String	<u>getFloatingPoint4Label()</u> Returns a label for the fourth custom floating point field.
String	<u>getIPv6Address1Label()</u> Returns a label for the first custom IPV6 address field.
String	<u>getIPv6Address2Label()</u> Returns a label for the second custom IPV6 address field.
String	<u>getIPv6Address3Label()</u> Returns a label for the third custom IPV6 address field.
String	<u>getIPv6Address4Label()</u> Returns a label for the fourth custom IPV6 address field.
String	<u>getNumber1Label()</u> Returns a label for the first custom number field.
String	<u>getNumber2Label()</u> Returns a label for the second custom number field.
String	<u>getNumber3Label()</u> Returns a label for the third custom number field.
String	<u>getString1Label()</u> Returns a label for the first custom string field.
String	<u>getString2Label()</u> Returns a label for the second custom string field.
String	<u>getString3Label()</u> Returns a label for the third custom string field.
String	<u>getString4Label()</u> Returns a label for the fourth custom string field.
String	<u>getString5Label()</u> Returns a label for the fifth custom string field.
String	<u>getString6Label()</u> Returns a label for the sixth custom string field.
int	<u>hashCode()</u>
void	<u>setDate1Label()</u> (String date1Label) Sets the label for the first custom date field.
void	<u>setDate2Label()</u> (String date2Label) Sets the label for the first custom date field.
void	<u>setDescriptorId()</u> (Long descriptorId) Sets the unique identifier for this description.
void	<u>setFloatingPoint1Label()</u> (String floatingPoint1Label) Sets the label for the first custom floating point field.

void	<u>setFloatingPoint2Label</u> (String floatingPoint2Label) Sets the label for the second custom floating point field.
void	<u>setFloatingPoint3Label</u> (String floatingPoint3Label) Sets the label for the third custom floating point field.
void	<u>setFloatingPoint4Label</u> (String floatingPoint4Label) Sets the label for the fourth custom floating point field.
void	<u>setIPv6Address1Label</u> (String ipv6Address1Label) Sets the label for the first custom IPV6 address field.
void	<u>setIPv6Address2Label</u> (String ipv6Address2Label) Sets the label for the second custom IPV6 address field.
void	<u>setIPv6Address3Label</u> (String ipv6Address3Label) Sets the label for the third custom IPV6 address field.
void	<u>setIPv6Address4Label</u> (String ipv6Address4Label) Sets the label for the fourth custom IPV6 address field.
void	<u>setNumber1Label</u> (String number1Label) Sets the label for the first custom number field.
void	<u>setNumber2Label</u> (String number2Label) Sets the label for the second custom number field.
void	<u>setNumber3Label</u> (String number3Label) Sets the label for the third custom number field.
void	<u>setString1Label</u> (String string1Label) Sets the label for the first custom string field.
void	<u>setString2Label</u> (String string2Label) Sets the label for the second custom string field.
void	<u>setString3Label</u> (String string3Label) Sets the label for the third custom string field.
void	<u>setString4Label</u> (String string4Label) Sets the label for the fourth custom string field.
void	<u>setString5Label</u> (String string5Label) Sets the label for the fifth custom string field.
void	<u>setString6Label</u> (String string6Label) Sets the label for the sixth custom string field.

Methods inherited from class
[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface `java.lang.Comparable`

compareTo

Constructors

LabelsDescriptor

```
public LabelsDescriptor()
```

Methods

getDescriptorId

```
public Long getDescriptorId()
```

Returns the unique identifier for this description.

Returns:

ID of the description

setDescriptorId

```
public void setDescriptorId(Long descriptorId)
```

Sets the unique identifier for this description.

Parameters:

descriptorId - ID of the description

getString1Label

```
public String getString1Label()
```

Returns a label for the first custom string field.

Returns:

A label

setString1Label

```
public void setString1Label(String string1Label)
```

Sets the label for the first custom string field.

Parameters:

string1Label - A label to set

getString2Label

public String **getString2Label**()

Returns a label for the second custom string field.

Returns:

A label

setString2Label

public void **setString2Label**(String string2Label)

Sets the label for the second custom string field.

Parameters:

string2Label - A label to set

getString3Label

public String **getString3Label**()

Returns a label for the third custom string field.

Returns:

A label

setString3Label

public void **setString3Label**(String string3Label)

Sets the label for the third custom string field.

Parameters:

string3Label - A label to set

getString4Label

public String **getString4Label**()

Returns a label for the fourth custom string field.

Returns:

A label

setString4Label

public void **setString4Label**(String string4Label)

Sets the label for the fourth custom string field.

Parameters:

string4Label - A label to set

getString5Label

public String **getString5Label**()

Returns a label for the fifth custom string field.

Returns:
A label

setString5Label

public void **setString5Label**(String string5Label)

Sets the label for the fifth custom string field.

Parameters:
string5Label - A label to set

getString6Label

public String **getString6Label**()

Returns a label for the sixth custom string field.

Returns:
A label

setString6Label

public void **setString6Label**(String string6Label)

Sets the label for the sixth custom string field.

Parameters:
string6Label - A label to set

getNumber1Label

public String **getNumber1Label**()

Returns a label for the first custom number field.

Returns:
A label

setNumber1Label

public void **setNumber1Label**(String number1Label)

Sets the label for the first custom number field.

Parameters:
number1Label - A label to set

getNumber2Label

public String **getNumber2Label**()

Returns a label for the second custom number field.

Returns:

A label

setNumber2Label

public void **setNumber2Label**(String number2Label)

Sets the label for the second custom number field.

Parameters:

number2Label - A label to set

getNumber3Label

public String **getNumber3Label**()

Returns a label for the third custom number field.

Returns:

A label

setNumber3Label

public void **setNumber3Label**(String number3Label)

Sets the label for the third custom number field.

Parameters:

number3Label - A label to set

getDate1Label

public String **getDate1Label**()

Returns a label for the first custom date field.

Returns:

A label

setDate1Label

public void **setDate1Label**(String date1Label)

Sets the label for the first custom date field.

Parameters:

date1Label - A label to set

getDate2Label

public String **getDate2Label**()

Returns a label for the second custom date field.

Returns:

A label

setDate2Label

public void **setDate2Label**(String date2Label)

Sets the label for the first custom date field.

Parameters:

date2Label - A label to set

getFloatingPoint1Label

public String **getFloatingPoint1Label**()

Returns a label for the first custom floating point field.

Returns:

A label

setFloatingPoint1Label

public void **setFloatingPoint1Label**(String floatingPoint1Label)

Sets the label for the first custom floating point field.

Parameters:

floatingPoint1Label - A label to set

getFloatingPoint2Label

public String **getFloatingPoint2Label**()

Returns a label for the second custom floating point field.

Returns:

A label

setFloatingPoint2Label

public void **setFloatingPoint2Label**(String floatingPoint2Label)

Sets the label for the second custom floating point field.

Parameters:

floatingPoint2Label - A label to set

getFloatingPoint3Label

public String **getFloatingPoint3Label**()

Returns a label for the third custom floating point field.

Returns:

A label

setFloatingPoint3Label

public void **setFloatingPoint3Label**(String floatingPoint3Label)

Sets the label for the third custom floating point field.

Parameters:

floatingPoint3Label - A label to set

getFloatingPoint4Label

public String **getFloatingPoint4Label**()

Returns a label for the fourth custom floating point field.

Returns:

A label

setFloatingPoint4Label

public void **setFloatingPoint4Label**(String floatingPoint4Label)

Sets the label for the fourth custom floating point field.

Parameters:

floatingPoint4Label - A label to set

getIPv6Address1Label

public String **getIPv6Address1Label**()

Returns a label for the first custom IPV6 address field.

Returns:

A label

setIPv6Address1Label

public void **setIPv6Address1Label**(String ipv6Address1Label)

Sets the label for the first custom IPV6 address field.

Parameters:

ipv6Address1Label - A label to set

getIPv6Address2Label

```
public String getIPv6Address2Label()
```

Returns a label for the second custom IPV6 address field.

Returns:

A label

setIPv6Address2Label

```
public void setIPv6Address2Label(String ipv6Address2Label)
```

Sets the label for the second custom IPV6 address field.

Parameters:

ipv6Address2Label - A label to set

getIPv6Address3Label

```
public String getIPv6Address3Label()
```

Returns a label for the third custom IPV6 address field.

Returns:

A label

setIPv6Address3Label

```
public void setIPv6Address3Label(String ipv6Address3Label)
```

Sets the label for the third custom IPV6 address field.

Parameters:

ipv6Address3Label - A label to set

getIPv6Address4Label

```
public String getIPv6Address4Label()
```

Returns a label for the fourth custom IPV6 address field.

Returns:

A label

setIPv6Address4Label

```
public void setIPv6Address4Label(String ipv6Address4Label)
```

Sets the label for the fourth custom IPV6 address field.

Parameters:

ipv6Address4Label - A label to set

equals

public boolean **equals**([LabelsDescriptor](#) labelsDescriptor)

Returns whether this object is equal to the another object labelsDescriptor.

Parameters:

labelsDescriptor - another object to compare with

hashCode

public int **hashCode**()

compareTo

public int **compareTo**([LabelsDescriptor](#) d)

com.arcsight.product.manager.resource.service.v1.model.event

Class MutableBase

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.event.MutableBase

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[LabelsDescriptor](#), [GeoDescriptor](#), [CategoryDescriptor](#), [AddressableDescriptorBase](#)

public class **MutableBase**
extends Object
implements Serializable

Base class that deals with mutability. Resources with immutable flag cannot be modified.

JSON prototype

Constructor Summary	
public	MutableBase()

Method Summary	
boolean	isMutable() Returns whether the object is mutable or could be modified.
void	setMutable (boolean mutable) Sets mutability flag to mutable.

Methods inherited from class java.lang.Object
<code>equals</code> , <code>getClass</code> , <code>hashCode</code> , <code>notify</code> , <code>notifyAll</code> , <code>toString</code> , <code>wait</code> , <code>wait</code> , <code>wait</code>

Constructors

MutableBase
public **MutableBase**()

Methods

isMutable

```
public boolean isMutable()
```

Returns whether the object is mutable or could be modified.

Returns:

Mutability flag

setMutable

```
public void setMutable(boolean mutable)
```

Sets mutability flag to mutable. Immutable objects cannot be modified

Parameters:

mutable

com.arcsight.product.manager.resource.service.v1.model.event

Class RequestDescriptor

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.event.RequestDescriptor

All Implemented Interfaces:
Serializable

```
public class RequestDescriptor
extends Object
implements Serializable
```

Description of an HttpRequest associated with the event.

JSON prototype

Constructor Summary

public	RequestDescriptor()

Method Summary

boolean	equals(RequestDescriptor requestDescriptor) Returns whether this object is equal to the another object requestDescriptor.
String	getClientApplication() Returns a string that describes client application (such as a web browser) used to issue the request.
String	getContext() Returns a description of the content from which the request originated, for example, the HTTP Referrer.
String	getCookies() Returns the cookies provided along with the request.
String	getMethod() Returns the style of the request, i.e., for an HTTP request this could be PUT or GET.
String	getProtocol() Returns a string of the protocol used
String	getUrl() Returns a universal resource locator associated with the event.
String	getUrlAuthority() Returns a string of the url authority

String	<u>getUrlFileName()</u> Returns a string of the url authority of the request
String	<u>getUrlHost()</u> Returns a string of the url host
int	<u>getUrlPort()</u> Returns an int of the url port
String	<u>getUrlQuery()</u> Returns a string of the url query of the request
int	<u>hashCode()</u>
void	<u>setClientApplication()</u> (String clientApplication) Sets the string that describes client application (such as a web browser) used to issue the request.
void	<u>setContext()</u> (String context) Sets the description of the content from which the request originated, for example, the HTTP Referrer.
void	<u>setCookies()</u> (String cookies) Sets the cookies provided along with the request.
void	<u>setMethod()</u> (String method) Sets the method of the request (GET, PUT, UPDATE, others)
void	<u>setProtocol()</u> (String protocol) Sets the protocol used by the request.
void	<u>setUrl()</u> (String url) Sets the universal resource locator associated with the event.
void	<u>setUrlAuthority()</u> (String authority) Sets the url authority provided along with the request.
void	<u>setUrlFileName()</u> (String urlFileName) Sets the url filename associated with the request
void	<u>setUrlHost()</u> (String host) Sets the url host associated with the request.
void	<u>setUrlPort()</u> (int port) Sets the url port provided
void	<u>setUrlQuery()</u> (String query) Sets the url query provided along with the request.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

RequestDescriptor

```
public RequestDescriptor()
```

Methods

getUrl

```
public String getUrl()
```

Returns a universal resource locator associated with the event.

Returns:

The universal resource locator

setUrl

```
public void setUrl(String url)
```

Sets the universal resource locator associated with the event.

Parameters:

url - The universal resource locator

getMethod

```
public String getMethod()
```

Returns the style of the request, i.e., for an HTTP request this could be PUT or GET.

Returns:

Method used in the request

setMethod

```
public void setMethod(String method)
```

Sets the method of the request (GET, PUT, UPDATE, others)

Parameters:

method - The method

getContext

```
public String getContext()
```

Returns a description of the content from which the request originated, for example, the HTTP Referrer.

Returns:

setContext

```
public void setContext(String context)
```

Sets the description of the content from which the request originated, for example, the HTTP Referrer.

Parameters:

context - Context of the request

getClientApplication

```
public String getClientApplication()
```

Returns a string that describes client application (such as a web browser) used to issue the request.

Returns:

Client application

setClientApplication

```
public void setClientApplication(String clientApplication)
```

Sets the string that describes client application (such as a web browser) used to issue the request.

Parameters:

clientApplication - Client application

getCookies

```
public String getCookies()
```

Returns the cookies provided along with the request.

Returns:

The cookies

setCookies

```
public void setCookies(String cookies)
```

Sets the cookies provided along with the request.

Parameters:

cookies - The cookies

getUrlAuthority

```
public String getUrlAuthority()
```

Returns a string of the url authority

Returns:

setUrlAuthority

```
public void setUrlAuthority(String authority)
```

Sets the url authority provided along with the request.

Parameters:

authority - The urlAuthority

getUrlFileName

```
public String getUrlFileName()
```

Returns a string of the url authority of the request

Returns:

The url filename

setUrlFileName

```
public void setUrlFileName(String urlFileName)
```

Sets the url filename associated with the request

Parameters:

urlFileName - The url file name

getUrlPort

```
public int getUrlPort()
```

Returns an int of the url port

Returns:

The url authority

setUrlPort

```
public void setUrlPort(int port)
```

Sets the url port provided

Parameters:

port - The url port associated with the request url

getUrlHost

```
public String getUrlHost()
```

Returns a string of the url host

Returns:

setUrlHost

```
public void setUrlHost(String host)
```

Sets the url host associated with the request.

Parameters:

urlHost - The url host

getUrlQuery

```
public String getUrlQuery()
```

Returns a string of the url query of the request

Returns:

The url query

setQuery

```
public void setQuery(String query)
```

Sets the url query provided along with the request.

Parameters:

query - The url query

getProtocol

```
public String getProtocol()
```

Returns a string of the protocol used

Returns:

The protocol

setProtocol

```
public void setProtocol(String protocol)
```

Sets the protocol used by the request.

Parameters:

protocol - The protocol

equals

```
public boolean equals(RequestDescriptor requestDescriptor)
```

Returns whether this object is equal to the another object requestDescriptor.

Parameters:

requestDescriptor - another object to compare with

hashCode

```
public int hashCode()
```

com.arcsight.product.manager.resource.service.v1.model.event

Class SecurityEvent

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent

All Implemented Interfaces:

Serializable

```
public class SecurityEvent
extends Object
implements Serializable
```

Description of Security Event object. Apart from standard fields there are number of Device Custom fields are reserved for attributes specific to the device that generated the event that the rest of the event schema does not already capture. These fields are defined by ArcSight or by a SmartConnector author who develops custom SmartConnectors to customer specifications. End-users should not modify these fields.

JSON prototype

Nested Class Summary

class	SecurityEvent.Originator SecurityEvent.Originator
class	SecurityEvent.TypeEnumeration SecurityEvent.TypeEnumeration

Field Summary

public static final	DUMMY_FIELD_NAME Value: dummyField
public static final	UNKNOWN_INTEGER Value: -2147483648

Constructor Summary

public	SecurityEvent()

Method Summary

void	appendConcentratorAgent (AgentDescriptor agent) addes an agent to the list of agent descriptors...
void	appendConcentratorDevice (DeviceDescriptor device) addes a device to the list of device descriptors...

AdditionalData[]	getAdditionalData() Reference to additional data.
AgentDescriptor	getAgent() Reference to an Agent.
long	getAgentReceiptTime() Returns the time at which information about the event was received by the agent.
int	getAgentSeverity() Returns agent severity assigned to the event.
int	getAggregatedEventCount() Returns the number of events in an aggregated event.
String	getApplicationProtocol() Returns the description of the application layer protocol.
int	getAssetCriticality() Returns the relative measure of the importance of the targeted device, on a scale of 0 to 10.
int	getBaseEventCount() Returns the number of events on which this event is based.
Long[]	getBaseEventIds() Returns the array of event IDs which contributed the generation of this correlated event.
int	getBytesIn() Returns number of bytes transferred into the device during transaction described by the event.
int	getBytesOut() Returns the number of bytes transferred out of the device during transaction described by the event.
CategoryDescriptor	getCategory() Return the reference to Event Category.
AgentDescriptor[]	getConcentratorAgents() Returns the chain of concentrators that have forwarded this event.
DeviceDescriptor[]	getConcentratorDevices() Returns the list of devices that concentrate events, if applicable.
int	getCorrelatedEventCount() Sets the number of events in the correlated event.
String	getCryptoSignature() Returns a crypto signature for this event.
ResourceReference	getCustomer() Returns the reference to Customer Resource.
EndPointDescriptor	getDestination() Returns a reference to Destination Resource.

<u>DeviceDescriptor</u>	<u>getDevice()</u> Resource Reference to Device.
String	<u>getDeviceAction()</u> Returns the device-specific description of some activity associated with the event (i.e.
<u>LabelsDescriptor</u>	<u>getDeviceCustom()</u> Resource Reference to deviceCustom.
long	<u>getDeviceCustomDate1()</u> First customDate
long	<u>getDeviceCustomDate2()</u> Second customDate
double	<u>getDeviceCustomFloatingPoint1()</u>
double	<u>getDeviceCustomFloatingPoint2()</u>
double	<u>getDeviceCustomFloatingPoint3()</u>
double	<u>getDeviceCustomFloatingPoint4()</u>
byte[]	<u>getDeviceCustomIPv6Address1()</u> First customIPv6
byte[]	<u>getDeviceCustomIPv6Address2()</u> Second customIPv6
byte[]	<u>getDeviceCustomIPv6Address3()</u> Third customIPv6
byte[]	<u>getDeviceCustomIPv6Address4()</u> Fourth customIPv6
long	<u>getDeviceCustomNumber1()</u> Returns the first device custom number.
long	<u>getDeviceCustomNumber2()</u> Returns the second device custom number.
long	<u>getDeviceCustomNumber3()</u> Returns the third device custom number.
String	<u>getDeviceCustomString1()</u> Returns the first customString.
String	<u>getDeviceCustomString2()</u> Returns the second customString.
String	<u>getDeviceCustomString3()</u> Returns the third customString.

String	getDeviceCustomString4() Returns the fourth customString.
String	getDeviceCustomString5() Returns the fifth customString.
String	getDeviceCustomString6() Returns the sixth customString.
int	getDeviceDirection() Returns whether the traffic was inbound (0) or outbound (1).
String	getDeviceDomain() Returns the specific domain containing the sensor device associated with the event.
String	getDeviceEventCategory() Returns the category provided by the original event.
String	getDeviceEventClassId() Returns the device-specific identifier associated with this type of event.
String	getDevicePayloadId() Returns the internal identifier associated with a payload object linked to this event.
int	getDeviceProcessId() Returns the ID of the sensor device process that reported the event.
long	getDeviceReceiptTime() Returns the time when the event was created by device (defaults to Start Time).
String	getDeviceSeverity() Returns the device-specific assessment of event severity.
ResourceReference	getDomain() Returns a reference to the specific domain containing the sensor device associated with the event.
byte[]	getDomainBlob1() First domain blob
byte[]	getDomainBlob2() Second domain blob
byte[]	getDomainBlob3() Third domain blob
byte[]	getDomainBlob4() Fourth domain blob
char[]	getDomainClob1() First domain Clob
char[]	getDomainClob2()

char[]	getDomainClob3()
char[]	getDomainClob4()
long	getDomainDate1()
long	getDomainDate2()
long	getDomainDate3()
long	getDomainDate4()
long	getDomainDate5()
long	getDomainDate6()
double	getDomainFp1()
double	getDomainFp2()
double	getDomainFp3()
double	getDomainFp4()
double	getDomainFp5()
double	getDomainFp6()
double	getDomainFp7()
double	getDomainFp8()
long	getDomainIpv4addr1()
long	getDomainIpv4addr2()
long	getDomainIpv4addr3()
long	getDomainIpv4addr4()
byte[]	getDomainIpv6addr1()
byte[]	getDomainIpv6addr2()

byte[]	getDomainIpv6addr3()
byte[]	getDomainIpv6addr4()
long	getDomainNumber1() Returns the first domain number.
long	getDomainNumber10() Returns the tenth domain number.
long	getDomainNumber11() Returns the eleventh domain number.
long	getDomainNumber12() Returns the twelve domain number.
long	getDomainNumber13() Returns the thirteen domain number.
long	getDomainNumber2() Returns the second domain number.
long	getDomainNumber3() Returns the third domain number.
long	getDomainNumber4() Returns the fourth domain number.
long	getDomainNumber5() Returns the fifth domain number.
long	getDomainNumber6() Returns the sixth domain number.
long	getDomainNumber7() Returns the seventh domain number.
long	getDomainNumber8() Returns the eighth domain number.
long	getDomainNumber9() Returns the ninth domain number.
ResourceReference	getDomainResourceRef1() Resource Reference to DomainResourceReference.
ResourceReference	getDomainResourceRef2() Resource Reference to DomainResourceReference.
ResourceReference	getDomainResourceRef3() Resource Reference to DomainResourceReference.
ResourceReference	getDomainResourceRef4() Resource Reference to DomainResourceReference.

String	getDomainString1()
String	getDomainString10()
String	getDomainString11()
String	getDomainString12()
String	getDomainString13()
String	getDomainString14()
String	getDomainString15()
String	getDomainString16()
String	getDomainString17()
String	getDomainString18()
String	getDomainString19()
String	getDomainString2()
String	getDomainString20()
String	getDomainString21()
String	getDomainString22()
String	getDomainString23()
String	getDomainString24()
String	getDomainString25()
String	getDomainString26()
String	getDomainString27()
String	getDomainString28()
String	getDomainString29()

String	getDomainString3()
String	getDomainString30()
String	getDomainString31()
String	getDomainString32()
String	getDomainString33()
String	getDomainString34()
String	getDomainString4()
String	getDomainString5()
String	getDomainString6()
String	getDomainString7()
String	getDomainString8()
String	getDomainString9()
String	getDummyField() Returns a dummy field.
long	getEndTime() Returns the end time of the event.
EventAnnotation	getEventAnnotation() Resource Reference to EventAnnotation.
Long	getEventId() Returns the ID of the event.
String	getEventOutcome() Returns the outcome of the event as reported by the device (when applicable).
String	getExternalId() Returns the external ID of the event.
FileDescriptor	getFile() Returns a reference to a File Resource associated with the event.
DeviceDescriptor	getFinalDevice() The device which sent the event to arcsight.

long	<u>getFlexDate1()</u> First flexDate
String	<u>getFlexDate1Label()</u> Label of first flexDate
long	<u>getFlexNumber1()</u> First flexNumber
String	<u>getFlexNumber1Label()</u> Label of the first FlexNumber.
long	<u>getFlexNumber2()</u> Second flexNumber
String	<u>getFlexNumber2Label()</u> Label of the second FlexNumber.
String	<u>getFlexString1()</u> Returns the first flexString.
String	<u>getFlexString1Label()</u> Label of the first FlexString.
String	<u>getFlexString2()</u> Returns the second flexString.
String	<u>getFlexString2Label()</u> Label of the second FlexString.
<u>ResourceReference</u>	<u>getGenerator()</u> Returns a reference to Resource Generator.
int	<u>getLocality()</u> One of Local, Forwarded, or Remote - events forwarded to a Manager from most Agents are considered Local; events forwarded to a Manager by a Super Agent (aka Manager Agent) are considered Forwarded; events fetched from a remote Manager (to display a Rule chain, for instance) are considered Remote.
byte	<u>getManagerId()</u> Returns the ID of the manager, which generated the event.
long	<u>getManagerReceiptTime()</u> Returns the time at which event was received by local ArcSight Manager.
String	<u>getMessage()</u> A brief comment associated with this event.
int	<u>getModelConfidence()</u> Returns Model Confidence level.
String	<u>getName()</u> Arbitrary string that describes this TYPE of event; event details included in other parts of the event should NOT be copied into the event name.

String	getObjectTypeName() Returns the object target id type for this object.
FileDescriptor	getOldFile() Returns a reference to a OldFile Resource associated with the event.
AgentDescriptor	getOriginalAgent() The agent which received the first event from the device.
SecurityEvent.Originator	getOriginator() Returns the Originator of the event whether it was Source or Destination.
int	getPersistence() One of Persisted or Transient; events default to being Transient and are marked as Persisted as soon as they reach the Batch Alert Persistor or when they are loaded by the Alert Broker.
int	getPriority() Returns the relative measure of importance of investigating this event on a scale of 0 to 10.
String	getRawEvent() When applicable, returns the source log line that generated the event (i.e.
String	getReason() Returns the cause of the event when applicable.
int	getRelevance() Returns the relative measure of likelihood that this event succeeded.
RequestDescriptor	getRequest() Returns a reference to Request.
String	getRuleThreadId() Returns optional thread id associated with event.
long	getSessionId() Returns a tag created by a correlation simulation, as part of a particular simulation.
int	getSeverity() Sets a relative measure of possible damage to network security.
EndPointDescriptor	getSource() Returns a reference to Source Resource.
long	getStartTime() Returns the start time of the event.
String	getTransportProtocol() Returns the description of the transport layer protocol (TCP, UDP, ICMP, IGMP, etc)
int	getTtl() TBD Internal field defining the time to live for an event.
SecurityEvent.TypeEnumeration	getType() Returns one of the event types: Base, Correlation, Aggregated, or Action.

String	getUuid() Deprecated. <i>The field will be removed in the next releases</i>
ResourceReference	getVulnerability() Returns reference to vulnerability Resource.
void	setAdditionalData() (AdditionalData[] additionalData)
void	setAgent() (AgentDescriptor agent)
void	setAgentReceiptTime() (long agentReceiptTime) Sets the time at which information about the event was received by the agent.
void	setAgentSeverity() (int agentSeverity) Sets agent severity assigned to the event.
void	setAggregatedEventCount() (int count) Sets the number of events in the aggregated event.
void	setApplicationProtocol() (String applicationProtocol) Sets the application layer protocol.
void	setAssetCriticality() (int assetCriticality) Sets the relative measure of the importance of the targeted device, on a scale of 0 to 10.
void	setBaseEventCount() (int baseEventCount) Sets the number of events on which this event is based.
void	setBaseEventIds() (Long[] baseEventIds) Sets the array of event IDs which contributed the generation of this correlated event.
void	setBytesIn() (int bytesIn) Sets the number of bytes transferred into the device during transaction described by the event.
void	setBytesOut() (int bytesOut) Sets the number of bytes transferred out of the device during transaction described by the event.
void	setCategory() (CategoryDescriptor category) Sets the reference to Event Category.
void	setConcentratorAgents() (AgentDescriptor[] concentratorAgents) Sets the chain of concentrators that have forwarded this event.
void	setConcentratorDevices() (DeviceDescriptor[] concentratorDevices) Sets the list of devices that concentrate events.
void	setCorrelatedEventCount() (int count) Sets the number of events in the correlated event.
void	setCryptoSignature() (String cryptoSignature) Sets a crypto signature for this event.

void	setCustomer (ResourceReference customer) Sets the reference to Customer Resource.
void	setDestination (EndPointDescriptor destination) Sets the reference to Destination Resource.
void	setDevice (DeviceDescriptor device)
void	setDeviceAction (String deviceAction) Sets the device-specific description of some activity associated with the event (i.e.
void	setDeviceCustom (LabelsDescriptor deviceCustom)
void	setDeviceCustomDate1 (long deviceCustomDate1)
void	setDeviceCustomDate2 (long deviceCustomDate2)
void	setDeviceCustomFloatingPoint1 (double deviceCustomFloatingPoint1)
void	setDeviceCustomFloatingPoint2 (double deviceCustomFloatingPoint2)
void	setDeviceCustomFloatingPoint3 (double deviceCustomFloatingPoint3)
void	setDeviceCustomFloatingPoint4 (double deviceCustomFloatingPoint4)
void	setDeviceCustomIPv6Address1 (byte[] deviceCustomIPv6Address1)
void	setDeviceCustomIPv6Address2 (byte[] deviceCustomIPv6Address2)
void	setDeviceCustomIPv6Address3 (byte[] deviceCustomIPv6Address3)
void	setDeviceCustomIPv6Address4 (byte[] deviceCustomIPv6Address4)
void	setDeviceCustomNumber1 (long deviceCustomNumber1) Sets the first device custom number.
void	setDeviceCustomNumber2 (long deviceCustomNumber2) Sets the second device custom number.
void	setDeviceCustomNumber3 (long deviceCustomNumber3) Sets the third device custom number.
void	setDeviceCustomString1 (String deviceCustomString1) Sets the first device custom string.
void	setDeviceCustomString2 (String deviceCustomString2) Sets the second device custom string.

void	<u>setDeviceCustomString3</u> (String deviceCustomString3) Sets the third device custom string.
void	<u>setDeviceCustomString4</u> (String deviceCustomString4) Sets the fourth device custom string.
void	<u>setDeviceCustomString5</u> (String deviceCustomString5) Sets the fifth device custom string.
void	<u>setDeviceCustomString6</u> (String deviceCustomString6) Sets the sixth device custom string.
void	<u>setDeviceDirection</u> (int deviceDirection) Sets traffic direction to either inbound (0) or outbound (1).
void	<u>setDeviceDomain</u> (String deviceDomain) Sets the specific domain containing the sensor device associated with the event.
void	<u>setDeviceEventCategory</u> (String deviceEventCategory) Sets the category provided by the original event.
void	<u>setDeviceEventClassId</u> (String deviceEventClassId) Sets the device-specific identifier associated with this type of event.
void	<u>setDevicePayloadId</u> (String devicePayloadId) Sets the internal identifier associated with a payload object linked to this event.
void	<u>setDeviceProcessId</u> (int deviceProcessId) Sets the ID of the sensor device process that reported the event.
void	<u>setDeviceReceiptTime</u> (long deviceReceiptTime) Sets the time when the event was created by device (defaults to Start Time).
void	<u>setDeviceSeverity</u> (String deviceSeverity) Sets the device-specific assessment of event severity.
void	<u>setDomain</u> (<u>ResourceReference</u> domain) Sets the reference to the specific domain containing the sensor device associated with the event.
void	<u>setDomainBlob1</u> (byte[] domainBlob1)
void	<u>setDomainBlob2</u> (byte[] domainBlob2)
void	<u>setDomainBlob3</u> (byte[] domainBlob3)
void	<u>setDomainBlob4</u> (byte[] domainBlob4)
void	<u>setDomainClob1</u> (char[] domainClob1)
void	<u>setDomainClob2</u> (char[] domainClob2)

void	<u>setDomainClob3</u> (char[] domainClob3)
void	<u>setDomainClob4</u> (char[] domainClob4)
void	<u>setDomainDate1</u> (long domainDate1)
void	<u>setDomainDate2</u> (long domainDate2)
void	<u>setDomainDate3</u> (long domainDate3)
void	<u>setDomainDate4</u> (long domainDate4)
void	<u>setDomainDate5</u> (long domainDate5)
void	<u>setDomainDate6</u> (long domainDate6)
void	<u>setDomainFp1</u> (double domainFp1)
void	<u>setDomainFp2</u> (double domainFp2)
void	<u>setDomainFp3</u> (double domainFp3)
void	<u>setDomainFp4</u> (double domainFp4)
void	<u>setDomainFp5</u> (double domainFp5)
void	<u>setDomainFp6</u> (double domainFp6)
void	<u>setDomainFp7</u> (double domainFp7)
void	<u>setDomainFp8</u> (double domainFp8)
void	<u>setDomainIpv4addr1</u> (long domainIpv4addr1)
void	<u>setDomainIpv4addr2</u> (long domainIpv4addr2)
void	<u>setDomainIpv4addr3</u> (long domainIpv4addr3)
void	<u>setDomainIpv4addr4</u> (long domainIpv4addr4)
void	<u>setDomainIpv6addr1</u> (byte[] domainIpv6addr1)
void	<u>setDomainIpv6addr2</u> (byte[] domainIpv6addr2)

void	<u>setDomainIpv6addr3</u> (byte[] domainIpv6addr3)
void	<u>setDomainIpv6addr4</u> (byte[] domainIpv6addr4)
void	<u>setDomainNumber1</u> (long domainNumber1) Sets the first domain number.
void	<u>setDomainNumber10</u> (long domainNumber10) Sets the tenth domain number.
void	<u>setDomainNumber11</u> (long domainNumber11) Sets the eleventh domain number.
void	<u>setDomainNumber12</u> (long domainNumber12) Sets the twelve domain number.
void	<u>setDomainNumber13</u> (long domainNumber13) Sets the thirteen domain number.
void	<u>setDomainNumber2</u> (long domainNumber2) Sets the second domain number.
void	<u>setDomainNumber3</u> (long domainNumber3) Sets the third domain number.
void	<u>setDomainNumber4</u> (long domainNumber4) Sets the fourth domain number.
void	<u>setDomainNumber5</u> (long domainNumber5) Sets the fifth domain number.
void	<u>setDomainNumber6</u> (long domainNumber6) Sets the sixth domain number.
void	<u>setDomainNumber7</u> (long domainNumber7) Sets the seventh domain number.
void	<u>setDomainNumber8</u> (long domainNumber8) Sets the eighth domain number.
void	<u>setDomainNumber9</u> (long domainNumber9) Sets the ninth domain number.
void	<u>setDomainResourceRef1</u> (<u>ResourceReference</u> domainResourceRef1)
void	<u>setDomainResourceRef2</u> (<u>ResourceReference</u> domainResourceRef2)
void	<u>setDomainResourceRef3</u> (<u>ResourceReference</u> domainResourceRef3)
void	<u>setDomainResourceRef4</u> (<u>ResourceReference</u> domainResourceRef4)
void	<u>setDomainString1</u> (String domainString1)

void	<u>setDomainString10</u> (String domainString10)
void	<u>setDomainString11</u> (String domainString11)
void	<u>setDomainString12</u> (String domainString12)
void	<u>setDomainString13</u> (String domainString13)
void	<u>setDomainString14</u> (String domainString14)
void	<u>setDomainString15</u> (String domainString15)
void	<u>setDomainString16</u> (String domainString16)
void	<u>setDomainString17</u> (String domainString17)
void	<u>setDomainString18</u> (String domainString18)
void	<u>setDomainString19</u> (String domainString19)
void	<u>setDomainString2</u> (String domainString2)
void	<u>setDomainString20</u> (String domainString20)
void	<u>setDomainString21</u> (String domainString21)
void	<u>setDomainString22</u> (String domainString22)
void	<u>setDomainString23</u> (String domainString23)
void	<u>setDomainString24</u> (String domainString24)
void	<u>setDomainString25</u> (String domainString25)
void	<u>setDomainString26</u> (String domainString26)
void	<u>setDomainString27</u> (String domainString27)
void	<u>setDomainString28</u> (String domainString28)
void	<u>setDomainString29</u> (String domainString29)
void	<u>setDomainString3</u> (String domainString3)

void	setDomainString30 (String domainString30)
void	setDomainString31 (String domainString31)
void	setDomainString32 (String domainString32)
void	setDomainString33 (String domainString33)
void	setDomainString34 (String domainString34)
void	setDomainString4 (String domainString4)
void	setDomainString5 (String domainString5)
void	setDomainString6 (String domainString6)
void	setDomainString7 (String domainString7)
void	setDomainString8 (String domainString8)
void	setDomainString9 (String domainString9)
void	setEndTime (long endTime) Sets the end time of the event.
void	setEventAnnotation (EventAnnotation eventAnnotation)
void	setEventId (Long eventId) Sets the ID of event to eventId.
void	setEventOutcome (String eventOutcome) Sets the outcome of the event as reported by the device (when applicable).
void	setExternalId (String externalId) It specifies the external ID of the event.
void	setFile (FileDescriptor file) Sets a reference to a File Resource.
void	setFinalDevice (DeviceDescriptor device)
void	setFlexDate1 (long flexDate1)
void	setFlexDate1Label (String flexDate1Label)
void	setFlexNumber1 (long flexNumber1)

void	<u>setFlexNumber1Label</u> (String flexNumber1Label)
void	<u>setFlexNumber2</u> (long flexNumber2)
void	<u>setFlexNumber2Label</u> (String flexNumber2Label)
void	<u>setFlexString1</u> (String flexString1) Sets the first flex string.
void	<u>setFlexString1Label</u> (String flexString1Label)
void	<u>setFlexString2</u> (String flexString2) Sets the second flex string.
void	<u>setFlexString2Label</u> (String flexString2Label)
void	<u>setGenerator</u> (<u>ResourceReference</u> generator) Sets the reference to Resource Generator.
void	<u>setLocality</u> (int locality)
void	<u>setManagerId</u> (byte managerId) Sets the ID of the ESM manager that created the event in question.
void	<u>setManagerReceiptTime</u> (long managerReceiptTime) Sets the time when ESM Manager received the event.
void	<u>setMessage</u> (String message) Sets a comment to be associated with the event.
void	<u>setModelConfidence</u> (int modelConfidence) Sets the Model Confidence level.
void	<u>setName</u> (String name) Set the type of the event.
void	<u>setOldFile</u> (<u>FileDescriptor</u> oldFile) Sets a reference to a OldFile Resource.
void	<u>setOriginalAgent</u> (<u>AgentDescriptor</u> agent)
void	<u>setOriginator</u> (<u>SecurityEvent.Originator</u> originator) Sets the Originator of the event whether it was Source or Destination.
void	<u>setPersistence</u> (int persistence)
void	<u>setPriority</u> (int priority) Sets the relative measure of importance of investigating this event on a scale of 0 to 10.
void	<u>setRawEvent</u> (String rawEvent) Sets raw data for the event.

void	setReason (String reason) Sets the cause of the event when applicable.
void	setRelevance (int relevance) Sets the relative measure of likelihood that this event succeeded.
void	setRequest (RequestDescriptor request) Sets a reference to Request.
void	setRuleThreadId (String ruleThreadId) Sets the optional thread id associated with event.
void	setSessionId (long sessionId) Sets a tag created by a correlation simulation, as part of a particular simulation.
void	setSeverity (int severity) Sets the relative measure of possible damage to network security.
void	setSource (EndPointDescriptor source) Sets the reference to Source Resource.
void	setStartTime (long startTime) Sets the start time of the event.
void	setTransportProtocol (String transportProtocol) Sets the transport layer protocol (TCP, UDP, ICMP, IGMP, etc)
void	setTtl (int ttl)
void	setType (SecurityEvent.TypeEnumeration type) Sets the type of the event.
void	setUuid (String uuid) Deprecated. <i>The field will be removed in the next releases</i>
void	setVulnerability (ResourceReference vulnerability) Sets the reference to a vulnerability Resource for this event.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

UNKNOWN_INTEGER

```
public static final int UNKNOWN_INTEGER
```

Constant value: **-2147483648**

DUMMY_FIELD_NAME

```
public static final java.lang.String DUMMY_FIELD_NAME
```

Constant value: `dummyField`

Constructors

SecurityEvent

```
public SecurityEvent()
```

Methods

getEventId

```
public Long getEventId()
```

Returns the ID of the event.

Returns:

Long value identifying an event

setEventId

```
public void setEventId(Long eventId)
```

Sets the ID of event to eventId. By setting the ID you specify which of the existing events your request will have affect on.

Parameters:

eventId - Long value to be set as ID of the event

getManagerId

```
public byte getManagerId()
```

Returns the ID of the manager, which generated the event.

Returns:

Byte representing an instance of ESM

setManagerId

```
public void setManagerId(byte managerId)
```

Sets the ID of the ESM manager that created the event in question.

Parameters:

managerId - Byte identifying ESM Manager

getExternalId

```
public String getExternalId()
```

Returns the external ID of the event. External ID is a string used by an external device created the event.

Returns:

String representing an external ID of the event

setExternalId

```
public void setExternalId(String externalId)
```

It specifies the external ID of the event. External ID is a string used by an external device created the event.

Parameters:

externalId - String representing the external ID of the event

getName

```
public String getName()
```

Arbitrary string that describes this TYPE of event; event details included in other parts of the event should NOT be copied into the event name.

setName

```
public void setName(String name)
```

Set the type of the event.

Parameters:

name - String that describes this TYPE of event

getMessage

```
public String getMessage()
```

A brief comment associated with this event.

Returns:

comment associated with the event

setMessage

```
public void setMessage(String message)
```

Sets a comment to be associated with the event.

Parameters:

message - that will be associated with the event

getType

public [SecurityEvent.TypeEnumeration](#) **getType()**

Returns one of the event types: Base, Correlation, Aggregated, or Action.

Returns:
type of the event

setType

public void **setType**([SecurityEvent.TypeEnumeration](#) type)

Sets the type of the event. Type could be one of the following: Base, Correlation, Aggregated, or Action

Parameters:
type - Type of the event

getStartTime

public long **getStartTime()**

Returns the start time of the event.

Returns:
DateTime of when event begins in milliseconds since from January 1, 1970

setStartTime

public void **setStartTime**(long startTime)

Sets the start time of the event. Event start time (defaults to deviceReceiptTime)

Parameters:
startTime - of event beginning in milliseconds since from January 1, 1970

getEndTime

public long **getEndTime()**

Returns the end time of the event.

Returns:
The end time of the event in milliseconds since from January 1, 1970

setEndTime

public void **setEndTime**(long endTime)

Sets the end time of the event. Event end time (defaults to deviceReceiptTime)

Parameters:
endTime - Event end time in milliseconds since from January 1, 1970

getManagerReceiptTime

public long **getManagerReceiptTime**()

Returns the time at which event was received by local ArcSight Manager.

Returns:

Time in milliseconds since from January 1, 1970

setManagerReceiptTime

public void **setManagerReceiptTime**(long managerReceiptTime)

Sets the time when ESM Manager received the event.

Parameters:

managerReceiptTime - Time in milliseconds since from January 1, 1970

getApplicationProtocol

public String **getApplicationProtocol**()

Returns the description of the application layer protocol.

Returns:

String describing application layer protocol

setApplicationProtocol

public void **setApplicationProtocol**(String applicationProtocol)

Sets the application layer protocol. The default value is Target Port lookup (FTP, HTTP, SNMP, etc)

Parameters:

applicationProtocol

getTransportProtocol

public String **getTransportProtocol**()

Returns the description of the transport layer protocol (TCP, UDP, ICMP, IGMP, etc)

Returns:

String description of the transport layer protocol

setTransportProtocol

public void **setTransportProtocol**(String transportProtocol)

Sets the transport layer protocol (TCP, UDP, ICMP, IGMP, etc)

Parameters:

transportProtocol - String description of the transport layer protocol

getVulnerability

public [ResourceReference](#) **getVulnerability**()

Returns reference to vulnerability Resource. Event vulnerability represents the vulnerability or exposure that may be exploited by this event and is present on the targeted device according to our network model.

Returns:

resource vulnerability

setVulnerability

public void **setVulnerability**([ResourceReference](#) vulnerability)

Sets the reference to a vulnerability Resource for this event. Event vulnerability represents the vulnerability or exposure that may be exploited by this event and is present on the targeted device according to our network model.

Parameters:

vulnerability

getRawEvent

public String **getRawEvent**()

When applicable, returns the source log line that generated the event (i.e. pix messages or syslog message) Raw data is the original log entry reported by the sensor (synthesized when the sensor does not log to a file or text stream).

Returns:

raw data of the original event if any

setRawEvent

public void **setRawEvent**(String rawEvent)

Sets raw data for the event. Raw data is the original log entry reported by the sensor (synthesized when the sensor does not log to a file or text stream).

Parameters:

rawEvent - Raw data of the original event

getBytesIn

public int **getBytesIn**()

Returns number of bytes transferred into the device during transaction described by the event. (this would typically be associated with entries in HTTP logs, firewall and VPN logs, or other logs involving file or data transfer)

Returns:

Number of bytes transferred into the device

setBytesIn

public void **setBytesIn**(int bytesIn)

Sets the number of bytes transferred into the device during transaction described by the event.

Parameters:

bytesIn - The number of bytes transferred into the device

getBytesOut

```
public int getBytesOut()
```

Returns the number of bytes transferred out of the device during transaction described by the event. (this would typically be associated with entries in HTTP logs, firewall and VPN logs, or other logs involving file or data transfer)

Returns:

Number of bytes transferred out of the device

setBytesOut

```
public void setBytesOut(int bytesOut)
```

Sets the number of bytes transferred out of the device during transaction described by the event.

Parameters:

bytesOut - The number of bytes transferred out of the device

getSessionId

```
public long getSessionId()
```

Returns a tag created by a correlation simulation, as part of a particular simulation. TBD: Session Id, represents the replay session in which the event were generated. This is an internal field, should not be shown in the CCE.

Returns:

Tag created by a correlation simulation

setSessionId

```
public void setSessionId(long sessionId)
```

Sets a tag created by a correlation simulation, as part of a particular simulation.

Parameters:

sessionId - Tag created by a correlation simulation

getGenerator

```
public ResourceReference getGenerator()
```

Returns a reference to Resource Generator. Resource Generator is the subcomponent in the agent which generates the event, for example in the arcsight manager agent, this is Rule, report, data monitor etc.

Returns:

reference to Resource Generator

setGenerator

```
public void setGenerator(ResourceReference generator)
```

Sets the reference to Resource Generator. Resource Generator is the subcomponent in the agent which generates the event, for example in the arcsight manager agent, this is Rule, report, data monitor etc.

Parameters:
generator

getCryptoSignature

```
public String getCryptoSignature()
```

Returns a crypto signature for this event. Not yet supported.

Returns:
signature for this event

setCryptoSignature

```
public void setCryptoSignature(String cryptoSignature)
```

Sets a crypto signature for this event. Not yet supported.

Parameters:
cryptoSignature - signature for this event

getConcentratorAgents

```
public AgentDescriptor\[\] getConcentratorAgents()
```

Returns the chain of concentrators that have forwarded this event. This is not yet exposed to the CCE. Note that in the hierarchical Manager case, not all descriptors will be available locally. Externally, a list of Agent Descriptors with a possible null values appearing in the list. This is where you would find super-Agents that forward from one Manager to another.

Returns:
the chain of concentrators

setConcentratorAgents

```
public void setConcentratorAgents(AgentDescriptor\[\] concentratorAgents)
```

Sets the chain of concentrators that have forwarded this event. This is not yet exposed to the CCE. Note that in the hierarchical Manager case, not all descriptors will be available locally. Externally, a list of Agent Descriptors with a possible null values appearing in the list. This is where you would find super-Agents that forward from one Manager to another.

Parameters:
concentratorAgents - the chain of concentrators

getConcentratorDevices

```
public DeviceDescriptor\[\] getConcentratorDevices()
```

Returns the list of devices that concentrate events, if applicable. There could be a device which is concentrating events. This is the list of such devices. This is not yet exposed in the CCE.

Returns:

list of devices that concentrate events

setConcentratorDevices

```
public void setConcentratorDevices(DeviceDescriptor\[\] concentratorDevices)
```

Sets the list of devices that concentrate events. There could be a device which is concentrating events. This is the list of such devices. This is not yet exposed in the CCE

Parameters:

concentratorDevices - the list of devices that concentrate events

getCustomer

```
public ResourceReference getCustomer()
```

Returns the reference to Customer Resource. It's used in the MSSP environments to describe the customer for whom the event is generated.

Returns:

The reference to Customer Resource

setCustomer

```
public void setCustomer(ResourceReference customer)
```

Sets the reference to Customer Resource. It's used in the MSSP environments to describe the customer for whom the event is generated.

Parameters:

customer - The reference to Customer Resource

getCategory

```
public CategoryDescriptor getCategory()
```

Return the reference to Event Category. Used to categorize an event. The category description included with the event as reported by the device

Returns:

the reference to Event Category

setCategory

```
public void setCategory(CategoryDescriptor category)
```

Sets the reference to Event Category. The category description included with the event as reported by the device

Parameters:

category - The reference to Event Category

getModelConfidence

```
public int getModelConfidence()
```

Returns Model Confidence level. It's a relative measure of ArcSight's confidence in its model of the attacked device, on a scale of 0 to 10.

Returns:

Model Confidence level

setModelConfidence

```
public void setModelConfidence(int modelConfidence)
```

Sets the Model Confidence level. It's a relative measure of ArcSight's confidence in its model of the attacked device, on a scale of 0 to 10.

Parameters:

modelConfidence - Model Confidence level

getSeverity

```
public int getSeverity()
```

Sets a relative measure of possible damage to network security. The relative measure of possible damage to network security represented by the event on a scale of 0 to 10. Event severity is supplied by the device. 0 - 10 - How badly could this attack damage our network. [Was Attack Severity] To sum up we have three severities: Event Severity is supplied by the Device; ArcSight Severity is supplied by the Agent; and Attack Severity is supplied by the threat evaluation process.

Returns:

relative measure of possible damage to network security.

setSeverity

```
public void setSeverity(int severity)
```

Sets the relative measure of possible damage to network security. The relative measure of possible damage to network security represented by the event on a scale of 0 to 10. Event severity is supplied by the device.

Parameters:

severity - relative measure of possible damage to network security

getRelevance

```
public int getRelevance()
```

Returns the relative measure of likelihood that this event succeeded. The relative measure of likelihood that this event succeeded, on a scale of 0 to 10. 0-10 - Does the event match our notion of the world or not ? [Was Attack Success] For instance, for hostile events, how likely is it that the attack succeeded in damaging our network?

Returns:

Relative measure of likelihood that this event succeeded

setRelevance

```
public void setRelevance(int relevance)
```

Sets the relative measure of likelihood that this event succeeded. The relative measure of likelihood that this event succeeded, on a scale of 0 to 10.

Parameters:

relevance - Relative measure of likelihood that this event succeeded

getAssetCriticality

```
public int getAssetCriticality()
```

Returns the relative measure of the importance of the targeted device, on a scale of 0 to 10.

Returns:

The relative measure of the importance of the targeted device

setAssetCriticality

```
public void setAssetCriticality(int assetCriticality)
```

Sets the relative measure of the importance of the targeted device, on a scale of 0 to 10.

Parameters:

assetCriticality - The relative measure of the importance of the targeted device

getPriority

```
public int getPriority()
```

Returns the relative measure of importance of investigating this event on a scale of 0 to 10. This field incorporates Model Confidence.

Returns:

importance of investigating this event

setPriority

```
public void setPriority(int priority)
```

Sets the relative measure of importance of investigating this event on a scale of 0 to 10.

Parameters:

priority - Importance of investigating this event

getAgentSeverity

```
public int getAgentSeverity()
```

Returns agent severity assigned to the event. Agent Severity is the translation of the device severity into ESM-normalized values.

Returns:

setAgentSeverity

```
public void setAgentSeverity(int agentSeverity)
```

Sets agent severity assigned to the event. Agent Severity is the translation of the device severity into ESM-normalized values.

Parameters:

agentSeverity - agent severity assigned to the event.

getAgentReceiptTime

```
public long getAgentReceiptTime()
```

Returns the time at which information about the event was received by the agent.

Returns:

Time when the data was received by the agent

setAgentReceiptTime

```
public void setAgentReceiptTime(long agentReceiptTime)
```

Sets the time at which information about the event was received by the agent.

Parameters:

agentReceiptTime - Time when the data was received by the agent

getDeviceEventCategory

```
public String getDeviceEventCategory()
```

Returns the category provided by the original event. For example the classification that snort supplies.

Returns:

The category provided by the original event

setDeviceEventCategory

```
public void setDeviceEventCategory(String deviceEventCategory)
```

Sets the category provided by the original event.

Parameters:

deviceEventCategory - the category provided by the original event

getDeviceSeverity

```
public String getDeviceSeverity()
```

Returns the device-specific assessment of event severity. For example "High" or "Low".

Returns:

The device-specific assessment of event severity

setDeviceSeverity

```
public void setDeviceSeverity(String deviceSeverity)
```

Sets the device-specific assessment of event severity.

Parameters:

deviceSeverity - The device-specific assessment of event severity

getDeviceAction

```
public String getDeviceAction()
```

Returns the device-specific description of some activity associated with the event (i.e. blocked packet).

Returns:

Device-specific description of activity associated with the event

setDeviceAction

```
public void setDeviceAction(String deviceAction)
```

Sets the device-specific description of some activity associated with the event (i.e. blocked packet).

Parameters:

deviceAction - Device-specific description of activity associated with the event

getDeviceReceiptTime

```
public long getDeviceReceiptTime()
```

Returns the time when the event was created by device (defaults to Start Time).

Returns:

The time when the event was created by device

setDeviceReceiptTime

```
public void setDeviceReceiptTime(long deviceReceiptTime)
```

Sets the time when the event was created by device (defaults to Start Time).

Parameters:

deviceReceiptTime - The time when the event was created by device

getDeviceEventClassId

```
public String getDeviceEventClassId()
```

Returns the device-specific identifier associated with this type of event. When used in conjunction with the vendor and product name for the primary reporting device, this uniquely identifies a class of events. For Snort this would be the SID, for IDSes it's generally the signatureID.

Returns:

The device-specific identifier associated with this type of event

setDeviceEventClassId

```
public void setDeviceEventClassId(String deviceEventClassId)
```

Sets the device-specific identifier associated with this type of event.

Parameters:

deviceEventClassId - The device-specific identifier associated with this type of event

getDevicePayloadId

```
public String getDevicePayloadId()
```

Returns the internal identifier associated with a payload object linked to this event. Unique ID that can be used to fetch the payload for that particular event. If there is definitely no such payload, then this field will have no value. If it has a value, then there may be a payload.

Returns:

the internal identifier associated with a payload object linked to this event

setDevicePayloadId

```
public void setDevicePayloadId(String devicePayloadId)
```

Sets the internal identifier associated with a payload object linked to this event.

Parameters:

devicePayloadId - The internal identifier associated with a payload object linked to this event

getReason

```
public String getReason()
```

Returns the cause of the event when applicable. For example, Invalid Password.

Returns:

The cause of the event

setReason

```
public void setReason(String reason)
```

Sets the cause of the event when applicable. For example, Invalid Password.

Parameters:

reason - The cause of the event

getEventOutcome

```
public String getEventOutcome()
```

Returns the outcome of the event as reported by the device (when applicable). For example, Windows reports an event as `audit_success` or `audit_failure`.

Returns:

the eventOutcome The outcome of the event

setEventOutcome

```
public void setEventOutcome(String eventOutcome)
```

Sets the outcome of the event as reported by the device (when applicable). For example, Windows reports an event as `audit_success` or `audit_failure`.

Parameters:

eventOutcome - The outcome of the event

getDeviceProcessId

```
public int getDeviceProcessId()
```

Returns the ID of the sensor device process that reported the event.

Returns:

the deviceProcessId The ID of the sensor device process that reported the event

setDeviceProcessId

```
public void setDeviceProcessId(int deviceProcessId)
```

Sets the ID of the sensor device process that reported the event.

Parameters:

deviceProcessId - The ID of the sensor device process that reported the event

getDomain

```
public ResourceReference getDomain()
```

Returns a reference to the specific domain containing the sensor device associated with the event.

Returns:

The reference to the domain

setDomain

```
public void setDomain(ResourceReference domain)
```

Sets the reference to the specific domain containing the sensor device associated with the event.

Parameters:

domain - The reference to the domain

getDeviceDomain

```
public String getDeviceDomain()
```

Returns the specific domain containing the sensor device associated with the event. Devices that divide the sensory target to domains and name those domains. These values will be very device specific.

Returns:

The domain containing the sensor device associated with the event

setDeviceDomain

```
public void setDeviceDomain(String deviceDomain)
```

Sets the specific domain containing the sensor device associated with the event.

Parameters:

deviceDomain - The domain containing the sensor device associated with the event

getDeviceDirection

```
public int getDeviceDirection()
```

Returns whether the traffic was inbound (0) or outbound (1).

Returns:

integer indicating traffic direction

setDeviceDirection

```
public void setDeviceDirection(int deviceDirection)
```

Sets traffic direction to either inbound (0) or outbound (1).

Parameters:

deviceDirection - integer indicating traffic direction

getOriginator

```
public SecurityEvent.Originator getOriginator()
```

Returns the Originator of the event whether it was Source or Destination. This determines whether source and destination should be translated to attacker and target or they should be inverted.

Returns:

Indication of event originator

setOriginator

```
public void setOriginator(SecurityEvent.Originator originator)
```

Sets the Originator of the event whether it was Source or Destination.

Parameters:

originator - Indication of event originator

getSource

public [EndPointDescriptor](#) getSource()

Returns a reference to Source Resource. The network traffic is flowing from this end point. Every event that describes a network transaction will have a source and destination. The values in the source and destination fields characterize the flow of traffic on your network.

Returns:

The description of event Source endpoint

setSource

public void **setSource**([EndPointDescriptor](#) source)

Sets the reference to Source Resource. The network traffic is flowing from this end point.

Parameters:

source - The description of event Source endpoint

getDestination

public [EndPointDescriptor](#) getDestination()

Returns a reference to Destination Resource. The network traffic is flowing to this end point. Every event that describes a network transaction will have a source and destination. The values in the source and destination fields characterize the flow of traffic on your network.

Returns:

The description of event Destination endpoint

setDestination

public void **setDestination**([EndPointDescriptor](#) destination)

Sets the reference to Destination Resource. The network traffic is flowing from this end point.

Parameters:

destination - The description of event Destination endpoint

getDummyField

public String getDummyField()

Returns a dummy field. Is a dummy field. Used mainly to define the list of fields mapped to session list fields when some of the fields are not mapped

Returns:

name of dummy field

getFile

public [FileDescriptor](#) getFile()

Returns a reference to a File Resource associated with the event. File refers to the current state of an operating system file or an ESM resource that has been modified.

Returns:

Reference to a File Resource

setFile

```
public void setFile(FileDescriptor file)
```

Sets a reference to a File Resource. File refers to the current state of an operating system file or an ESM resource that has been modified.

Parameters:

file - Reference to a File Resource

getOldFile

```
public FileDescriptor getOldFile()
```

Returns a reference to a OldFile Resource associated with the event. Old File refers to the previous state of an operating system file or ESM resource that has been modified.

Returns:

Reference to a OldFile Resource

setOldFile

```
public void setOldFile(FileDescriptor oldFile)
```

Sets a reference to a OldFile Resource. Old File refers to the previous state of an operating system file or ESM resource that has been modified.

Parameters:

oldFile - Reference to a File Resource

getRequest

```
public RequestDescriptor getRequest()
```

Returns a reference to Request. Request describes the attributes of a request for some action to take place (such as an HTTP GET or a database query).

Returns:

A reference to Request

setRequest

```
public void setRequest(RequestDescriptor request)
```

Sets a reference to Request. Request describes the attributes of a request for some action to take place (such as an HTTP GET or a database query).

Parameters:

request - A reference to Request

getBaseEventCount

```
public int getBaseEventCount()
```

Returns the number of events on which this event is based. type == BASE|ACTION|AGGREGATED , baseEventCount = 1. type == CORRELATED, the number of events in the rulechain.

Returns:

Number of events on which this event is based

setBaseEventCount

```
public void setBaseEventCount(int baseEventCount)
```

Sets the number of events on which this event is based.

Parameters:

baseEventCount

getAggregatedEventCount

```
public int getAggregatedEventCount()
```

Returns the number of events in an aggregated event. type == BASE | ACTION | CORRELATION, aggregatedEventCount = 1 type == AGGREGATED, the number of events aggregated into the base event count field

Returns:

The number of events in an aggregated event or 1

setAggregatedEventCount

```
public void setAggregatedEventCount(int count)
```

Sets the number of events in the aggregated event. It also change the type of the event to [SecurityEvent.TypeEnumeration.AGGREGATED](#)

Parameters:

count - The number of events in the aggregated event

getCorrelatedEventCount

```
public int getCorrelatedEventCount()
```

Sets the number of events in the correlated event. type == BASE | ACTION | CORRELATION, aggregatedEventCount = 1 type == AGGREGATED, the number of events aggregated into the base event count field

Returns:

The number of events in an correlated event or 0

setCorrelatedEventCount

```
public void setCorrelatedEventCount(int count)
```


Sets the number of events in the correlated event. It also change the type of the event to [SecurityEvent.TypeEnumeration.CORRELATION](#)

Parameters:

count - The number of events in the correlated event

getBaseEventIds

```
public Long[] getBaseEventIds()
```

Returns the array of event IDs which contributed the generation of this correlated event. It's populated only in the correlated events.

Returns:

The array of event IDs

setBaseEventIds

```
public void setBaseEventIds(Long[] baseEventIds)
```

Sets the array of event IDs which contributed the generation of this correlated event. It also change the type of the event to [SecurityEvent.TypeEnumeration.CORRELATION](#).

Parameters:

baseEventIds - The array of event IDs

getRuleThreadId

```
public String getRuleThreadId()
```

Returns optional thread id associated with event. When the rule starts firing it can create many correlated events, with this id they are all put together.

Returns:

The optional thread id associated with event

setRuleThreadId

```
public void setRuleThreadId(String ruleThreadId)
```

Sets the optional thread id associated with event.

Parameters:

ruleThreadId - The optional thread id associated with event

getDeviceCustomString1

```
public String getDeviceCustomString1()
```

Returns the first customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The first customString

setDeviceCustomString1

```
public void setDeviceCustomString1(String deviceCustomString1)
```

Sets the first device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString1 - The first device customString

getDeviceCustomString2

```
public String getDeviceCustomString2()
```

Returns the second customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The second customString

setDeviceCustomString2

```
public void setDeviceCustomString2(String deviceCustomString2)
```

Sets the second device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString2 - The second device customString

getDeviceCustomString3

```
public String getDeviceCustomString3()
```

Returns the third customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The third customString

setDeviceCustomString3

```
public void setDeviceCustomString3(String deviceCustomString3)
```

Sets the third device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString3 - The third device customString

getDeviceCustomString4

```
public String getDeviceCustomString4()
```

Returns the fourth customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The fourth customString

setDeviceCustomString4

```
public void setDeviceCustomString4(String deviceCustomString4)
```

Sets the fourth device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString2 - The fourth device customString

getDeviceCustomString5

```
public String getDeviceCustomString5()
```

Returns the fifth customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The fifth customString

setDeviceCustomString5

```
public void setDeviceCustomString5(String deviceCustomString5)
```

Sets the fifth device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString5 - The fifth device customString

getDeviceCustomString6

```
public String getDeviceCustomString6()
```

Returns the sixth customString. There are six strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Returns:

The sixth customString

setDeviceCustomString6

```
public void setDeviceCustomString6(String deviceCustomString6)
```

Sets the sixth device custom string. There are six custom strings available which can be used to map fields which do not fit into any other field of this dictionary. If possible, these fields should not be used, but a more specific field from the dictionary.

Parameters:

deviceCustomString6 - The sixth device customString

getFlexString1

```
public String getFlexString1()
```

Returns the first flexString. There are two flex strings available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The first flexString

setFlexString1

```
public void setFlexString1(String flexString1)
```

Sets the first flex string. There are two flex strings available which can be used to map fields which do not fit into any other field of this dictionary.

Parameters:

flexString1 - The first flexString

getFlexString2

```
public String getFlexString2()
```

Returns the second flexString. There are two flex strings available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The second flexString

setFlexString2

```
public void setFlexString2(String flexString2)
```

Sets the second flex string. There are two flex strings available which can be used to map fields which do not fit into any other field of this dictionary.

Parameters:

flexString2 - The second flexString

getDeviceCustomNumber1

```
public long getDeviceCustomNumber1()
```

Returns the first device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

setDeviceCustomNumber1

```
public void setDeviceCustomNumber1(long deviceCustomNumber1)
```

Sets the first device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Parameters:

deviceCustomNumber1 - The first device custom number

getDeviceCustomNumber2

```
public long getDeviceCustomNumber2()
```

Returns the second device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The second device custom number

setDeviceCustomNumber2

```
public void setDeviceCustomNumber2(long deviceCustomNumber2)
```

Sets the second device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Parameters:

deviceCustomNumber2 - The second device custom number

getDeviceCustomNumber3

```
public long getDeviceCustomNumber3()
```

Returns the third device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The third device custom number

setDeviceCustomNumber3

```
public void setDeviceCustomNumber3(long deviceCustomNumber3)
```

Sets the third device custom number. There are three device custom numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Parameters:

deviceCustomNumber3 - The third device custom number

getDomainNumber1

```
public long getDomainNumber1()
```

Returns the first domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The first domain number

setDomainNumber1

```
public void setDomainNumber1(long domainNumber1)
```

Sets the first domain number.

Parameters:

domainNumber1 - The first domain number.

getDomainNumber2

```
public long getDomainNumber2()
```

Returns the second domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The second domain number

setDomainNumber2

```
public void setDomainNumber2(long domainNumber2)
```

Sets the second domain number.

Parameters:

domainNumber2 - The second domain number.

getDomainNumber3

```
public long getDomainNumber3()
```

Returns the third domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The third domain number

setDomainNumber3

```
public void setDomainNumber3(long domainNumber3)
```

Sets the third domain number.

Parameters:

domainNumber3 - The third domain number.

getDomainNumber4

```
public long getDomainNumber4()
```

Returns the fourth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The fourth domain number

setDomainNumber4

```
public void setDomainNumber4(long domainNumber4)
```

Sets the fourth domain number.

Parameters:

domainNumber4 - The fourth domain number.

getDomainNumber5

```
public long getDomainNumber5()
```

Returns the fifth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The fifth domain number

setDomainNumber5

```
public void setDomainNumber5(long domainNumber5)
```

Sets the fifth domain number.

Parameters:

domainNumber5 - The fifth domain number.

getDomainNumber6

```
public long getDomainNumber6()
```

Returns the sixth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The sixth domain number

setDomainNumber6

```
public void setDomainNumber6(long domainNumber6)
```

Sets the sixth domain number.

Parameters:

domainNumber6 - The sixth domain number.

getDomainNumber7

```
public long getDomainNumber7()
```

Returns the seventh domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The seventh domain number

setDomainNumber7

```
public void setDomainNumber7(long domainNumber7)
```

Sets the seventh domain number.

Parameters:

domainNumber7 - The seventh domain number.

getDomainNumber8

```
public long getDomainNumber8()
```

Returns the eighth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The eighth domain number

setDomainNumber8

```
public void setDomainNumber8(long domainNumber8)
```

Sets the eighth domain number.

Parameters:

domainNumber8 - The eighth domain number.

getDomainNumber9

```
public long getDomainNumber9()
```

Returns the ninth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The ninth domain number

setDomainNumber9

```
public void setDomainNumber9(long domainNumber9)
```

Sets the ninth domain number.

Parameters:

domainNumber9 - The ninth domain number.

getDomainNumber10

```
public long getDomainNumber10()
```

Returns the tenth domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The tenth domain number

setDomainNumber10

```
public void setDomainNumber10(long domainNumber10)
```

Sets the tenth domain number.

Parameters:

domainNumber10 - The tenth domain number.

getDomainNumber11

```
public long getDomainNumber11()
```

Returns the eleventh domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The eleventh domain number

setDomainNumber11

```
public void setDomainNumber11(long domainNumber11)
```

Sets the eleventh domain number.

Parameters:

domainNumber11 - The eleventh domain number.

getDomainNumber12

```
public long getDomainNumber12()
```

Returns the twelve domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The twelve domain number

setDomainNumber12

```
public void setDomainNumber12(long domainNumber12)
```

Sets the twelve domain number.

Parameters:

domainNumber12 - The twelve domain number.

getDomainNumber13

```
public long getDomainNumber13()
```

Returns the thirteen domain number. There are thirteen domain numbers available which can be used to map fields which do not fit into any other field of this dictionary.

Returns:

The thirteen domain number

setDomainNumber13

```
public void setDomainNumber13(long domainNumber13)
```

Sets the thirteen domain number.

Parameters:

domainNumber13 - The thirteen domain number.

getFlexNumber1

```
public long getFlexNumber1()
```

First flexNumber

setFlexNumber1

```
public void setFlexNumber1(long flexNumber1)
```

getFlexNumber2

```
public long getFlexNumber2()
```

Second flexNumber

setFlexNumber2

```
public void setFlexNumber2(long flexNumber2)
```

getDeviceCustomDate1

```
public long getDeviceCustomDate1()
```

First customDate

setDeviceCustomDate1

```
public void setDeviceCustomDate1(long deviceCustomDate1)
```

getDeviceCustomDate2

```
public long getDeviceCustomDate2()
```

Second customDate

setDeviceCustomDate2

```
public void setDeviceCustomDate2(long deviceCustomDate2)
```

getDomainDate1

```
public long getDomainDate1()
```

setDomainDate1

```
public void setDomainDate1(long domainDate1)
```

getDomainDate2

```
public long getDomainDate2()
```

setDomainDate2

```
public void setDomainDate2(long domainDate2)
```

getDomainDate3

```
public long getDomainDate3()
```

setDomainDate3

public void **setDomainDate3**(long domainDate3)

getDomainDate4

public long **getDomainDate4**()

setDomainDate4

public void **setDomainDate4**(long domainDate4)

getDomainDate5

public long **getDomainDate5**()

setDomainDate5

public void **setDomainDate5**(long domainDate5)

getDomainDate6

public long **getDomainDate6**()

setDomainDate6

public void **setDomainDate6**(long domainDate6)

getFlexDate1

public long **getFlexDate1**()

First flexDate

setFlexDate1

public void **setFlexDate1**(long flexDate1)

getDeviceCustomFloatingPoint1

public double **getDeviceCustomFloatingPoint1**()

setDeviceCustomFloatingPoint1

public void **setDeviceCustomFloatingPoint1**(double deviceCustomFloatingPoint1)

getDeviceCustomFloatingPoint2

public double **getDeviceCustomFloatingPoint2**()

setDeviceCustomFloatingPoint2

public void **setDeviceCustomFloatingPoint2**(double deviceCustomFloatingPoint2)

getDeviceCustomFloatingPoint3

public double **getDeviceCustomFloatingPoint3**()

setDeviceCustomFloatingPoint3

public void **setDeviceCustomFloatingPoint3**(double deviceCustomFloatingPoint3)

getDeviceCustomFloatingPoint4

public double **getDeviceCustomFloatingPoint4**()

setDeviceCustomFloatingPoint4

public void **setDeviceCustomFloatingPoint4**(double deviceCustomFloatingPoint4)

getDomainFp1

public double **getDomainFp1**()

setDomainFp1

public void **setDomainFp1**(double domainFp1)

getDomainFp2

public double **getDomainFp2**()

setDomainFp2

public void **setDomainFp2**(double domainFp2)

getDomainFp3

public double **getDomainFp3**()

setDomainFp3

public void **setDomainFp3**(double domainFp3)

getDomainFp4

public double **getDomainFp4**()

setDomainFp4

public void **setDomainFp4**(double domainFp4)

getDomainFp5

public double **getDomainFp5**()

setDomainFp5

public void **setDomainFp5**(double domainFp5)

getDomainFp6

public double **getDomainFp6**()

setDomainFp6

public void **setDomainFp6**(double domainFp6)

getDomainFp7

public double **getDomainFp7**()

setDomainFp7

public void **setDomainFp7**(double domainFp7)

getDomainFp8

public double **getDomainFp8**()

setDomainFp8

public void **setDomainFp8**(double domainFp8)

getDomainIpv4addr1

public long **getDomainIpv4addr1**()

Returns:

the domainIpv4addr1

setDomainIpv4addr1

public void **setDomainIpv4addr1**(long domainIpv4addr1)

getDomainIpv4addr2

```
public long getDomainIpv4addr2()
```

Returns:

the domainIpv4addr2

setDomainIpv4addr2

```
public void setDomainIpv4addr2(long domainIpv4addr2)
```

getDomainIpv4addr3

```
public long getDomainIpv4addr3()
```

Returns:

the domainIpv4addr3

setDomainIpv4addr3

```
public void setDomainIpv4addr3(long domainIpv4addr3)
```

getDomainIpv4addr4

```
public long getDomainIpv4addr4()
```

Returns:

the domainIpv4addr4

setDomainIpv4addr4

```
public void setDomainIpv4addr4(long domainIpv4addr4)
```

getDeviceCustomIPv6Address1

```
public byte[] getDeviceCustomIPv6Address1()
```

First customIPv6

setDeviceCustomIPv6Address1

```
public void setDeviceCustomIPv6Address1(byte[] deviceCustomIPv6Address1)
```

getDeviceCustomIPv6Address2

```
public byte[] getDeviceCustomIPv6Address2()
```

Second customIPv6

setDeviceCustomIPv6Address2

```
public void setDeviceCustomIPv6Address2(byte[] deviceCustomIPv6Address2)
```

getDeviceCustomIPv6Address3

```
public byte[] getDeviceCustomIPv6Address3()
```

Third customIPv6

setDeviceCustomIPv6Address3

```
public void setDeviceCustomIPv6Address3(byte[] deviceCustomIPv6Address3)
```

getDeviceCustomIPv6Address4

```
public byte[] getDeviceCustomIPv6Address4()
```

Fourth customIPv6

setDeviceCustomIPv6Address4

```
public void setDeviceCustomIPv6Address4(byte[] deviceCustomIPv6Address4)
```

getDomainIPv6addr1

```
public byte[] getDomainIPv6addr1()
```

Returns:

the domainIPv6addr1

setDomainIPv6addr1

```
public void setDomainIPv6addr1(byte[] domainIPv6addr1)
```

getDomainIpv6addr2

```
public byte[] getDomainIpv6addr2()
```

Returns:

the domainIpv6addr2

setDomainIpv6addr2

```
public void setDomainIpv6addr2(byte[] domainIpv6addr2)
```

getDomainIpv6addr3

```
public byte[] getDomainIpv6addr3()
```

Returns:

the domainIpv6addr3

setDomainIpv6addr3

```
public void setDomainIpv6addr3(byte[] domainIpv6addr3)
```

getDomainIpv6addr4

```
public byte[] getDomainIpv6addr4()
```

Returns:

the domainIpv6addr4

setDomainIpv6addr4

```
public void setDomainIpv6addr4(byte[] domainIpv6addr4)
```

getDomainResourceRef1

```
public ResourceReference getDomainResourceRef1()
```

Resource Reference to DomainResourceReference.

setDomainResourceRef1

```
public void setDomainResourceRef1(ResourceReference domainResourceRef1)
```

getDomainResourceRef2

```
public ResourceReference getDomainResourceRef2()
```

Resource Reference to DomainResourceReference.

setDomainResourceRef2

```
public void setDomainResourceRef2(ResourceReference domainResourceRef2)
```

getDomainResourceRef3

```
public ResourceReference getDomainResourceRef3()
```

Resource Reference to DomainResourceReference.

setDomainResourceRef3

```
public void setDomainResourceRef3(ResourceReference domainResourceRef3)
```

getDomainResourceRef4

```
public ResourceReference getDomainResourceRef4()
```

Resource Reference to DomainResourceReference.

setDomainResourceRef4

```
public void setDomainResourceRef4(ResourceReference domainResourceRef4)
```

getDomainBlob1

```
public byte[] getDomainBlob1()
```

First domain blob

setDomainBlob1

```
public void setDomainBlob1(byte[] domainBlob1)
```

getDomainBlob2

```
public byte[] getDomainBlob2()
```

Second domain blob

setDomainBlob2

```
public void setDomainBlob2(byte[] domainBlob2)
```

getDomainBlob3

```
public byte[] getDomainBlob3()
```

Third domain blob

setDomainBlob3

```
public void setDomainBlob3(byte[] domainBlob3)
```

getDomainBlob4

```
public byte[] getDomainBlob4()
```

Fourth domain blob

setDomainBlob4

```
public void setDomainBlob4(byte[] domainBlob4)
```

getDomainClob1

```
public char[] getDomainClob1()
```

First domain Clob

setDomainClob1

```
public void setDomainClob1(char[] domainClob1)
```

Parameters:

domainClob1 - the domainClob1 to set

getDomainClob2

```
public char[] getDomainClob2()
```

Returns:

the domainClob2

setDomainClob2

```
public void setDomainClob2(char[] domainClob2)
```

Parameters:

domainClob2 - the domainClob2 to set

getDomainClob3

```
public char[] getDomainClob3()
```

Returns:

the domainClob3

setDomainClob3

```
public void setDomainClob3(char[] domainClob3)
```

Parameters:

domainClob3 - the domainClob3 to set

getDomainClob4

```
public char[] getDomainClob4()
```

Returns:

the domainClob4

setDomainClob4

```
public void setDomainClob4(char[] domainClob4)
```

Parameters:

domainClob4 - the domainClob4 to set

getLocality

```
public int getLocality()
```

One of Local, Forwarded, or Remote - events forwarded to a Manager from most Agents are considered Local; events forwarded to a Manager by a Super Agent (aka Manager Agent) are considered Forwarded; events fetched from a remote Manager (to display a Rule chain, for instance) are considered Remote. Or one of ESMPassThrough - event is processed by ESM or DirectPassToLogger - event is not processed by ESM and passed to logger or any other product.

Returns:

locality of the event

setLocality

```
public void setLocality(int locality)
```

getPersistence

```
public int getPersistence()
```

One of Persisted or Transient; events default to being Transient and are marked as Persisted as soon as they reach the Batch Alert Persistor or when they are loaded by the Alert Broker.

setPersistence

```
public void setPersistence(int persistence)
```

getDeviceCustom

```
public LabelsDescriptor getDeviceCustom()
```

Resource Reference to deviceCustom. Device specific fields can be added to deviceCustom fields.

setDeviceCustom

```
public void setDeviceCustom(LabelsDescriptor deviceCustom)
```

getFlexDate1Label

```
public String getFlexDate1Label()
```

Label of first flexDate

setFlexDate1Label

```
public void setFlexDate1Label(String flexDate1Label)
```

getDomainString1

public String **getDomainString1()**

getDomainString2

public String **getDomainString2()**

getDomainString3

public String **getDomainString3()**

getDomainString4

public String **getDomainString4()**

getDomainString5

public String **getDomainString5()**

getDomainString6

public String **getDomainString6()**

getDomainString7

public String **getDomainString7()**

getDomainString8

public String **getDomainString8()**

getDomainString9

public String **getDomainString9()**

getDomainString10

public String **getDomainString10**()

getDomainString11

public String **getDomainString11**()

getDomainString12

public String **getDomainString12**()

getDomainString13

public String **getDomainString13**()

getDomainString14

public String **getDomainString14**()

getDomainString15

public String **getDomainString15**()

getDomainString16

public String **getDomainString16**()

getDomainString17

public String **getDomainString17**()

getDomainString18

public String **getDomainString18**()

getDomainString19

public String **getDomainString19**()

getDomainString20

public String **getDomainString20**()

getDomainString21

public String **getDomainString21**()

getDomainString22

public String **getDomainString22**()

getDomainString23

public String **getDomainString23**()

getDomainString24

public String **getDomainString24**()

getDomainString25

public String **getDomainString25**()

getDomainString26

public String **getDomainString26**()

getDomainString27

public String **getDomainString27**()

getDomainString28

public String **getDomainString28**()

getDomainString29

public String **getDomainString29**()

getDomainString30

public String **getDomainString30**()

getDomainString31

public String **getDomainString31**()

getDomainString32

public String **getDomainString32**()

getDomainString33

public String **getDomainString33**()

getDomainString34

public String **getDomainString34**()

setDomainString1

public void **setDomainString1**(String domainString1)

setDomainString2

public void **setDomainString2**(String domainString2)

setDomainString3

public void **setDomainString3**(String domainString3)

setDomainString4

public void **setDomainString4**(String domainString4)

setDomainString5

public void **setDomainString5**(String domainString5)

setDomainString6

public void **setDomainString6**(String domainString6)

setDomainString7

public void **setDomainString7**(String domainString7)

setDomainString8

public void **setDomainString8**(String domainString8)

setDomainString9

public void **setDomainString9**(String domainString9)

setDomainString10

public void **setDomainString10**(String domainString10)

setDomainString11

public void **setDomainString11**(String domainString11)

setDomainString12

public void **setDomainString12**(String domainString12)

setDomainString13

public void **setDomainString13**(String domainString13)

setDomainString14

public void **setDomainString14**(String domainString14)

setDomainString15

public void **setDomainString15**(String domainString15)

setDomainString16

public void **setDomainString16**(String domainString16)

setDomainString17

public void **setDomainString17**(String domainString17)

setDomainString18

public void **setDomainString18**(String domainString18)

setDomainString19

public void **setDomainString19**(String domainString19)

setDomainString20

public void **setDomainString20**(String domainString20)

setDomainString21

public void **setDomainString21**(String domainString21)

setDomainString22

public void **setDomainString22**(String domainString22)

setDomainString23

public void **setDomainString23**(String domainString23)

setDomainString24

public void **setDomainString24**(String domainString24)

setDomainString25

public void **setDomainString25**(String domainString25)

setDomainString26

public void **setDomainString26**(String domainString26)

setDomainString27

public void **setDomainString27**(String domainString27)

setDomainString28

public void **setDomainString28**(String domainString28)

setDomainString29

public void **setDomainString29**(String domainString29)

setDomainString30

public void **setDomainString30**(String domainString30)

setDomainString31

public void **setDomainString31**(String domainString31)

setDomainString32

public void **setDomainString32**(String domainString32)

setDomainString33

public void **setDomainString33**(String domainString33)

setDomainString34

public void **setDomainString34**(String domainString34)

getFlexString1Label

public String **getFlexString1Label**()

Label of the first FlexString.

setFlexString1Label

public void **setFlexString1Label**(String flexString1Label)

getFlexNumber2Label

public String **getFlexNumber2Label**()

Label of the second FlexNumber.

setFlexNumber2Label

public void **setFlexNumber2Label**(String flexNumber2Label)

getFlexString2Label

```
public String getFlexString2Label()
```

Label of the second FlexString.

setFlexString2Label

```
public void setFlexString2Label(String flexString2Label)
```

getFlexNumber1Label

```
public String getFlexNumber1Label()
```

Label of the first FlexNumber.

setFlexNumber1Label

```
public void setFlexNumber1Label(String flexNumber1Label)
```

getTtl

```
public int getTtl()
```

TBD Internal field defining the time to live for an event.

setTtl

```
public void setTtl(int ttl)
```

getUuid

```
public String getUuid()
```

Deprecated. *The field will be removed in the next releases*

This field is used by the agents to support old managers. Note: This field can be removed in future, so don't use this in any other place.

setUuid

```
public void setUuid(String uuid)
```

Deprecated. *The field will be removed in the next releases*

It sets UUID to support old managers.

Parameters:

getObjectTypeName

```
public String getObjectTypeName()
```

Returns the object target id type for this object. This is based upon the constants in this class and the ResourceTypes class.

See Also:

[ResourceTypes](#)

getAgent

```
public AgentDescriptor getAgent()
```

Reference to an Agent. Externally this information is exposed as the individual Agent Descriptor fields described below. Note that this is always the original reporting Agent.

setAgent

```
public void setAgent(AgentDescriptor agent)
```

appendConcentratorAgent

```
public void appendConcentratorAgent(AgentDescriptor agent)
```

addes an agent to the list of agent descriptors... also makes the current agent as the last element of the descriptor.

Parameters:

agent

getOriginalAgent

```
public AgentDescriptor getOriginalAgent()
```

The agent which received the first event from the device. The current event could have been passed on by different agents and finally getting here, so this field lets you access that information. for the agents... index 0 == the original agent. index n-1 == the "as is" agent.

setOriginalAgent

```
public void setOriginalAgent(AgentDescriptor agent)
```

getDevice

```
public DeviceDescriptor getDevice()
```

Resource Reference to Device. This is the reporting sensor entity.

setDevice

```
public void setDevice(DeviceDescriptor device)
```

getFinalDevice

```
public DeviceDescriptor getFinalDevice()
```

The device which sent the event to arcsight. the event could have passed through many devices before getting into the arcsight device. index 0 == as is device index n-1 == final device.

setFinalDevice

```
public void setFinalDevice(DeviceDescriptor device)
```

appendConcentratorDevice

```
public void appendConcentratorDevice(DeviceDescriptor device)
```

addes a device to the list of device descriptors... also makes the current agent as the last element of the descriptor.

Parameters:
device

getAdditionalData

```
public AdditionalData\[\] getAdditionalData()
```

Reference to additional data.

setAdditionalData

```
public void setAdditionalData(AdditionalData\[\] additionalData)
```

getEventAnnotation

```
public EventAnnotation getEventAnnotation()
```

Resource Reference to EventAnnotation. Annotations are used to annotate events.

setEventAnnotation

```
public void setEventAnnotation(EventAnnotation eventAnnotation)
```

com.arcsight.product.manager.resource.service.v1.model.event

Class SecurityEvent.Originator

java.lang.Object

└- java.lang.Enum

└-

com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.Originator

All Implemented Interfaces:

Serializable, Comparable

public static final class **SecurityEvent.Originator**
extends Enum

Field Summary

public static final	DESTINATION Denotes the destination of action described in the Event
public static final	SOURCE Denotes Source of the action described in the Event

Method Summary

static SecurityEvent.Originator	forValue (int value)
int	getValue ()
static SecurityEvent.Originator	valueOf (String name)
static SecurityEvent.Originator[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

SOURCE

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.Originator  
SOURCE
```

Denotes Source of the action described in the Event

DESTINATION

```
public static final  
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.Originator  
DESTINATION
```

Denotes the destination of action described in the Event

Methods

values

```
public static SecurityEvent.Originator\[\] values()
```

valueOf

```
public static SecurityEvent.Originator valueOf(String name)
```

getValue

```
public int getValue()
```

forValue

```
public static SecurityEvent.Originator forValue(int value)
```

com.arcsight.product.manager.resource.service.v1.model.event Class SecurityEvent.TypeEnumeration

java.lang.Object

└ java.lang.Enum

└

com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration

All Implemented Interfaces:

Serializable, Comparable

```
public static final class SecurityEvent.TypeEnumeration
extends Enum
```

Field Summary

public static final	ACTION Events created when a correlation rule's action is triggered.
public static final	AGGREGATED Denotes aggregated events when some number of events are merged into one event.
public static final	BASE Denotes events of Base type.
public static final	CORRELATION Events created by ESM correlation engine when some Rules' Conditions are met.
public static final	UNKOWN Unknown type

Method Summary

static SecurityEvent.TypeEnumeration	forValue (int value) Returns an item that has associated value value.
int	getValue () Returns the integer associated with the item.
static SecurityEvent.TypeEnumeration	valueOf (String name)
static SecurityEvent.TypeEnumeration[]	values ()

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable

compareTo

Fields

BASE

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration BASE
```

Denotes events of Base type. The most common case of events received from ArcSight Connectors

AGGREGATED

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration AGGREGATED
```

Denotes aggregated events when some number of events are merged into one event.

CORRELATION

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration CORRELATION
```

Events created by ESM correlation engine when some Rules' Conditions are met.

ACTION

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration ACTION
```

Events created when a correlation rule's action is triggered.

UNKNOWN

```
public static final
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEvent.TypeEnumeration UNKNOWN
```

Unknown type

Methods

values

```
public static SecurityEvent.TypeEnumeration\[\] values()
```

valueOf

```
public static SecurityEvent.TypeEnumeration valueOf(String name)
```

getValue

```
public int getValue()
```

Returns the integer associated with the item.

Returns:

Integer associated with the item

forValue

```
public static SecurityEvent.TypeEnumeration forValue(int value)
```

Returns an item that has associated value value.

Parameters:

value - The value of the item in question

Returns:

Items with the specified value

com.arcsight.product.manager.resource.service.v1.model.event

Class SecurityEventDomainDataBag

java.lang.Object



com.arcsight.product.manager.resource.service.v1.model.event.SecurityEventDomainDataBag

All Implemented Interfaces:
Serializable

```
public class SecurityEventDomainDataBag
extends Object
implements Serializable
```

The holder of security event domain custom data. The purpose of this class is to serve as a placeholder for custom Domain references. The benefit of this is that systems that do not make use of the Domain fields will not have to pay the memory costs associated with them.

JSON prototype

Constructor Summary

public	SecurityEventDomainDataBag() Default constructor to create an object with default values.

Method Summary

long	_getDomainIpv4addr(int index)
void	_setDomainIpv4addr(int index, long domainIpv4addr)
byte[]	getDomainBlob1() Returns the first BLOB field.
byte[]	getDomainBlob2() Returns the second BLOB field.
byte[]	getDomainBlob3() Returns the third BLOB field.
byte[]	getDomainBlob4() Returns the fourth BLOB field.
char[]	getDomainClob1() Returns the first CLOB field.
char[]	getDomainClob2() Returns the second CLOB field.

char[]	<u>getDomainClob3()</u> Returns the third CLOB field.
char[]	<u>getDomainClob4()</u> Returns the fourth CLOB field.
long	<u>getDomainDate1()</u> Returns the first domain date field.
long	<u>getDomainDate2()</u> Returns the second domain date field.
long	<u>getDomainDate3()</u> Returns the third domain date field.
long	<u>getDomainDate4()</u> Returns the fourth domain date field.
long	<u>getDomainDate5()</u> Returns the fifth domain date field.
long	<u>getDomainDate6()</u> Returns the sixth domain date field.
double	<u>getDomainFp1()</u> Returns the first domain floating point field.
double	<u>getDomainFp2()</u> Returns the second domain floating point field.
double	<u>getDomainFp3()</u> Returns the third domain floating point field.
double	<u>getDomainFp4()</u> Returns the fourth domain floating point field.
double	<u>getDomainFp5()</u> Returns the fifth domain floating point field.
double	<u>getDomainFp6()</u> Returns the sixth domain floating point field.
double	<u>getDomainFp7()</u> Returns the seventh domain floating point field.
double	<u>getDomainFp8()</u> Returns the eighth domain floating point field.
long	<u>getDomainIpv4addr1()</u> Returns the first domain IPv4 address field.
long	<u>getDomainIpv4addr2()</u> Returns the second domain IPv4 address field.

long	<u>getDomainIpv4addr3()</u> Returns the third domain IPv4 address field.
long	<u>getDomainIpv4addr4()</u> Returns the fourth domain IPv4 address field.
byte[]	<u>getDomainIpv6addr1()</u> Returns the first domain IPv6 address field.
byte[]	<u>getDomainIpv6addr2()</u> Returns the second domain IPv6 address field.
byte[]	<u>getDomainIpv6addr3()</u> Returns the third domain IPv6 address field.
byte[]	<u>getDomainIpv6addr4()</u> Returns the fourth domain IPv6 address field.
long	<u>getDomainNumber1()</u> Returns the first domain number field.
long	<u>getDomainNumber10()</u> Returns the tenth domain number field.
long	<u>getDomainNumber11()</u> Returns the eleventh domain number field.
long	<u>getDomainNumber12()</u> Returns the twelve domain number field.
long	<u>getDomainNumber13()</u> Returns the thirteen domain number field.
long	<u>getDomainNumber2()</u> Returns the second domain number field.
long	<u>getDomainNumber3()</u> Returns the third domain number field.
long	<u>getDomainNumber4()</u> Returns the fourth domain number field.
long	<u>getDomainNumber5()</u> Returns the fifth domain number field.
long	<u>getDomainNumber6()</u> Returns the sixth domain number field.
long	<u>getDomainNumber7()</u> Returns the seventh domain number field.
long	<u>getDomainNumber8()</u> Returns the eighth domain number field.

long	getDomainNumber9() Returns the ninth domain number field.
ResourceReference	getDomainResourceRef1() Returns the first domain reference field.
ResourceReference	getDomainResourceRef2() Returns the second domain reference field.
ResourceReference	getDomainResourceRef3() Returns the third domain reference field.
ResourceReference	getDomainResourceRef4() Returns the fourth domain reference field.
String	getDomainString1() Returns the first domain string field.
String	getDomainString10() Returns the tenth domain string field.
String	getDomainString11() Returns the eleventh domain string field.
String	getDomainString12() Returns the twelve domain string field.
String	getDomainString13() Returns the thirteen domain string field.
String	getDomainString14() Returns the fourteen domain string field.
String	getDomainString15() Returns the fifteen domain string field.
String	getDomainString16() Returns the sixteenth domain string field.
String	getDomainString17() Returns the seventeenth domain string field.
String	getDomainString18() Returns the eighteen domain string field.
String	getDomainString19() Returns the nineteenth domain string field.
String	getDomainString2() Returns the second domain string field.
String	getDomainString20() Returns the twentieth domain string field.

String	<u>getDomainString21()</u> Returns the twenty first domain string field.
String	<u>getDomainString22()</u> Returns the twenty second domain string field.
String	<u>getDomainString23()</u> Returns the twenty third domain string field.
String	<u>getDomainString24()</u> Returns the twenty fourth domain string field.
String	<u>getDomainString25()</u> Returns the twenty fifth domain string field.
String	<u>getDomainString26()</u> Returns the twenty sixth domain string field.
String	<u>getDomainString27()</u> Returns the twenty seventh domain string field.
String	<u>getDomainString28()</u> Returns the twenty eighth domain string field.
String	<u>getDomainString29()</u> Returns the twenty ninth domain string field.
String	<u>getDomainString3()</u> Returns the third domain string field.
String	<u>getDomainString30()</u> Returns the thirtieth domain string field.
String	<u>getDomainString31()</u> Returns the thirty first domain string field.
String	<u>getDomainString32()</u> Returns the thirty second domain string field.
String	<u>getDomainString33()</u> Returns the thirty third domain string field.
String	<u>getDomainString34()</u> Returns the thirty fourth domain string field.
String	<u>getDomainString4()</u> Returns the fourth domain string field.
String	<u>getDomainString5()</u> Returns the fifth domain string field.
String	<u>getDomainString6()</u> Returns the sixth domain string field.

String	<u>getDomainString7()</u> Returns the seventh domain string field.
String	<u>getDomainString8()</u> Returns the eighth domain string field.
String	<u>getDomainString9()</u> Returns the ninth domain string field.
void	<u>setDomainBlob1()</u> (byte[] domainBlob1) Sets the first BLOB field.
void	<u>setDomainBlob2()</u> (byte[] domainBlob2) Sets the second BLOB field.
void	<u>setDomainBlob3()</u> (byte[] domainBlob3) Sets the third BLOB field.
void	<u>setDomainBlob4()</u> (byte[] domainBlob4) Sets the fourth BLOB field.
void	<u>setDomainClob1()</u> (char[] domainClob) Sets the first CLOB (Character Large Object) field.
void	<u>setDomainClob2()</u> (char[] domainClob) Sets the second CLOB (Character Large Object) field.
void	<u>setDomainClob3()</u> (char[] domainClob) Sets the third CLOB (Character Large Object) field.
void	<u>setDomainClob4()</u> (char[] domainClob) Sets the fourth CLOB (Character Large Object) field.
void	<u>setDomainDate1()</u> (long domainDate1) Sets the first domain Date field
void	<u>setDomainDate2()</u> (long domainDate2) Sets the second domain Date field
void	<u>setDomainDate3()</u> (long domainDate3) Sets the third domain Date field
void	<u>setDomainDate4()</u> (long domainDate4) Sets the fourth domain Date field
void	<u>setDomainDate5()</u> (long domainDate5) Sets the fifth domain Date field
void	<u>setDomainDate6()</u> (long domainDate6) Sets the sixth domain Date field
void	<u>setDomainFp1()</u> (double domainFp1) Sets the first domain floating point field

void	<u>setDomainFp2</u> (double domainFp2) Sets the second domain floating point field
void	<u>setDomainFp3</u> (double domainFp3) Sets the third domain floating point field
void	<u>setDomainFp4</u> (double domainFp4) Sets the fourth domain floating point field
void	<u>setDomainFp5</u> (double domainFp5) Sets the fifth domain floating point field
void	<u>setDomainFp6</u> (double domainFp6) Sets the sixth domain floating point field
void	<u>setDomainFp7</u> (double domainFp7) Sets the seventh domain floating point field
void	<u>setDomainFp8</u> (double domainFp8) Sets the eighth domain floating point field
void	<u>setDomainIpv4addr1</u> (long domainIpv4addr1) Sets the first IPv4 address field.
void	<u>setDomainIpv4addr2</u> (long domainIpv4addr2) Sets the second IPv4 address field.
void	<u>setDomainIpv4addr3</u> (long domainIpv4addr3) Sets the third IPv4 address field.
void	<u>setDomainIpv4addr4</u> (long domainIpv4addr4) Sets the fourth IPv4 address field.
void	<u>setDomainIpv6addr1</u> (byte[] domainIpv6addr1) Sets the first IPv6 address field.
void	<u>setDomainIpv6addr2</u> (byte[] domainIpv6addr2) Sets the second IPv6 address field.
void	<u>setDomainIpv6addr3</u> (byte[] domainIpv6addr3) Sets the third IPv6 address field.
void	<u>setDomainIpv6addr4</u> (byte[] domainIpv6addr4) Sets the fourth IPv6 address field.
void	<u>setDomainNumber1</u> (long domainNumber1) Sets the first domain number field.
void	<u>setDomainNumber10</u> (long domainNumber10) Sets the tenth domain number field.
void	<u>setDomainNumber11</u> (long domainNumber11) Sets the eleventh domain number field.

void	<u>setDomainNumber12</u> (long domainNumber12) Sets the twelve domain number field.
void	<u>setDomainNumber13</u> (long domainNumber13) Sets the thirteen domain number field.
void	<u>setDomainNumber2</u> (long domainNumber2) Sets the second domain number field.
void	<u>setDomainNumber3</u> (long domainNumber3) Sets the third domain number field.
void	<u>setDomainNumber4</u> (long domainNumber4) Sets the fourth domain number field.
void	<u>setDomainNumber5</u> (long domainNumber5) Sets the fifth domain number field.
void	<u>setDomainNumber6</u> (long domainNumber6) Sets the sixth domain number field.
void	<u>setDomainNumber7</u> (long domainNumber7) Sets the seventh domain number field.
void	<u>setDomainNumber8</u> (long domainNumber8) Sets the eight domain number field.
void	<u>setDomainNumber9</u> (long domainNumber9) Sets the ninth domain number field.
void	<u>setDomainResourceRef1</u> (<u>ResourceReference</u> domainResourceRef1) Sets the first domain reference field.
void	<u>setDomainResourceRef2</u> (<u>ResourceReference</u> domainResourceRef2) Sets the second domain reference field.
void	<u>setDomainResourceRef3</u> (<u>ResourceReference</u> domainResourceRef3) Sets the third domain reference field.
void	<u>setDomainResourceRef4</u> (<u>ResourceReference</u> domainResourceRef4) Sets the fourth domain reference field.
void	<u>setDomainString1</u> (String domainString1) Sets the first domain string field.
void	<u>setDomainString10</u> (String domainString10) Sets the tenth domain string field.
void	<u>setDomainString11</u> (String domainString11) Sets the eleventh domain string field.
void	<u>setDomainString12</u> (String domainString12) Sets the twelve domain string field.

void	<u>setDomainString13</u> (String domainString13) Sets the thirteen domain string field.
void	<u>setDomainString14</u> (String domainString14) Sets the fourteen domain string field.
void	<u>setDomainString15</u> (String domainString15) Sets the fifteen domain string field.
void	<u>setDomainString16</u> (String domainString16) Sets the sixteenth domain string field.
void	<u>setDomainString17</u> (String domainString17) Sets the seventeenth domain string field.
void	<u>setDomainString18</u> (String domainString18) Sets the eighteenth domain string field.
void	<u>setDomainString19</u> (String domainString19) Sets the nineteenth domain string field.
void	<u>setDomainString2</u> (String domainString2) Sets the second domain string field.
void	<u>setDomainString20</u> (String domainString20) Sets the twentieth domain string field.
void	<u>setDomainString21</u> (String domainString21) Sets the twenty first domain string field.
void	<u>setDomainString22</u> (String domainString22) Sets the twenty second domain string field.
void	<u>setDomainString23</u> (String domainString23) Sets the twenty third domain string field.
void	<u>setDomainString24</u> (String domainString24) Sets the twenty fourth domain string field.
void	<u>setDomainString25</u> (String domainString25) Sets the twenty fifth domain string field.
void	<u>setDomainString26</u> (String domainString26) Sets the twenty sixth domain string field.
void	<u>setDomainString27</u> (String domainString27) Sets the twenty seventh domain string field.
void	<u>setDomainString28</u> (String domainString28) Sets the twenty eighth domain string field.
void	<u>setDomainString29</u> (String domainString29) Sets the twenty ninth domain string field.

void	<code>setDomainString3</code> (String domainString3) Sets the third domain string field.
void	<code>setDomainString30</code> (String domainString30) Sets the thirtieth domain string field.
void	<code>setDomainString31</code> (String domainString31) Sets the thirty first domain string field.
void	<code>setDomainString32</code> (String domainString32) Sets the thirty second domain string field.
void	<code>setDomainString33</code> (String domainString33) Sets the thirty third domain string field.
void	<code>setDomainString34</code> (String domainString34) Sets the thirty fourth domain string field.
void	<code>setDomainString4</code> (String domainString4) Sets the fourth domain string field.
void	<code>setDomainString5</code> (String domainString5) Sets the fifth domain string field.
void	<code>setDomainString6</code> (String domainString6) Sets the sixth domain string field.
void	<code>setDomainString7</code> (String domainString7) Sets the seventh domain string field.
void	<code>setDomainString8</code> (String domainString8) Sets the eighth domain string field.
void	<code>setDomainString9</code> (String domainString9) Sets the ninth domain string field.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

SecurityEventDomainDataBag

```
public SecurityEventDomainDataBag()
```

Default constructor to create an object with default values.

Methods

getDomainBlob1

```
public byte[] getDomainBlob1()
```

Returns the first BLOB field. BLOB (Binary large object) fields are typically used images, audio or other multimedia.

Returns:

The first BLOB field.

setDomainBlob1

```
public void setDomainBlob1(byte[] domainBlob1)
```

Sets the first BLOB field.

Parameters:

domainBlob1 - Binary large object field

getDomainBlob2

```
public byte[] getDomainBlob2()
```

Returns the second BLOB field. BLOB (Binary large object) fields are typically used images, audio or other multimedia.

Returns:

The second BLOB field.

setDomainBlob2

```
public void setDomainBlob2(byte[] domainBlob2)
```

Sets the second BLOB field.

Parameters:

domainBlob2 - Binary large object field

getDomainBlob3

```
public byte[] getDomainBlob3()
```

Returns the third BLOB field. BLOB (Binary large object) fields are typically used images, audio or other multimedia.

Returns:

The third BLOB field.

setDomainBlob3

```
public void setDomainBlob3(byte[] domainBlob3)
```

Sets the third BLOB field.

Parameters:

domainBlob3 - Binary large object field

getDomainBlob4

```
public byte[] getDomainBlob4()
```

Returns the fourth BLOB field. BLOB (Binary large object) fields are typically used images, audio or other multimedia.

Returns:

The fourth BLOB field.

setDomainBlob4

```
public void setDomainBlob4(byte[] domainBlob4)
```

Sets the fourth BLOB field.

Parameters:

domainBlob4 - Binary large object field

getDomainClob1

```
public char[] getDomainClob1()
```

Returns the first CLOB field. CLOB (Character Large Object) fields are collections of character data.

Returns:

The first CLOB field.

setDomainClob1

```
public void setDomainClob1(char[] domainClob)
```

Sets the first CLOB (Character Large Object) field.

Parameters:

domainClob1 - Character Large Object field

getDomainClob2

```
public char[] getDomainClob2()
```

Returns the second CLOB field. CLOB (Character Large Object) fields are collections of character data.

Returns:

The second CLOB field.

setDomainClob2

```
public void setDomainClob2(char[] domainClob)
```

Sets the second CLOB (Character Large Object) field.

Parameters:

domainClob2 - Character Large Object field

getDomainClob3

```
public char[] getDomainClob3()
```

Returns the third CLOB field. CLOB (Character Large Object) fields are collections of character data.

Returns:

The third CLOB field.

setDomainClob3

```
public void setDomainClob3(char[] domainClob)
```

Sets the third CLOB (Character Large Object) field.

Parameters:

domainClob3 - Character Large Object field

getDomainClob4

```
public char[] getDomainClob4()
```

Returns the fourth CLOB field. CLOB (Character Large Object) fields are collections of character data.

Returns:

The fourth CLOB field.

setDomainClob4

```
public void setDomainClob4(char[] domainClob)
```

Sets the fourth CLOB (Character Large Object) field.

Parameters:

domainClob4 - Character Large Object field

getDomainDate1

```
public long getDomainDate1()
```

Returns the first domain date field.

Returns:

The date field

setDomainDate1

```
public void setDomainDate1(long domainDate1)
```

Sets the first domain Date field

Parameters:

domainDate1 - The date field

getDomainDate2

public long **getDomainDate2**()

Returns the second domain date field.

Returns:

The date field

setDomainDate2

public void **setDomainDate2**(long domainDate2)

Sets the second domain Date field

Parameters:

domainDate2 - The date field

getDomainDate3

public long **getDomainDate3**()

Returns the third domain date field.

Returns:

The date field

setDomainDate3

public void **setDomainDate3**(long domainDate3)

Sets the third domain Date field

Parameters:

domainDate3 - The date field

getDomainDate4

public long **getDomainDate4**()

Returns the fourth domain date field.

Returns:

The date field

setDomainDate4

public void **setDomainDate4**(long domainDate4)

Sets the fourth domain Date field

Parameters:

domainDate4 - The date field

getDomainDate5

public long **getDomainDate5**()

Returns the fifth domain date field.

Returns:

The date field

setDomainDate5

public void **setDomainDate5**(long domainDate5)

Sets the fifth domain Date field

Parameters:

domainDate5 - The date field

getDomainDate6

public long **getDomainDate6**()

Returns the sixth domain date field.

Returns:

The date field

setDomainDate6

public void **setDomainDate6**(long domainDate6)

Sets the sixth domain Date field

Parameters:

domainDate6 - The date field

getDomainFp1

public double **getDomainFp1**()

Returns the first domain floating point field.

Returns:

The floating point field

setDomainFp1

public void **setDomainFp1**(double domainFp1)

Sets the first domain floating point field

Parameters:

domainFp1 - The floating point field

getDomainFp2

public double **getDomainFp2**()

Returns the second domain floating point field.

Returns:

The floating point field

setDomainFp2

public void **setDomainFp2**(double domainFp2)

Sets the second domain floating point field

Parameters:

domainFp2 - The floating point field

getDomainFp3

public double **getDomainFp3**()

Returns the third domain floating point field.

Returns:

The floating point field

setDomainFp3

public void **setDomainFp3**(double domainFp3)

Sets the third domain floating point field

Parameters:

domainFp3 - The floating point field

getDomainFp4

public double **getDomainFp4**()

Returns the fourth domain floating point field.

Returns:

The floating point field

setDomainFp4

public void **setDomainFp4**(double domainFp4)

Sets the fourth domain floating point field

Parameters:

domainFp4 - The floating point field

getDomainFp5

public double **getDomainFp5**()

Returns the fifth domain floating point field.

Returns:

The floating point field

setDomainFp5

public void **setDomainFp5**(double domainFp5)

Sets the fifth domain floating point field

Parameters:

domainFp5 - The floating point field

getDomainFp6

public double **getDomainFp6**()

Returns the sixth domain floating point field.

Returns:

The floating point field

setDomainFp6

public void **setDomainFp6**(double domainFp6)

Sets the sixth domain floating point field

Parameters:

domainFp6 - The floating point field

getDomainFp7

public double **getDomainFp7**()

Returns the seventh domain floating point field.

Returns:

The floating point field

setDomainFp7

public void **setDomainFp7**(double domainFp7)

Sets the seventh domain floating point field

Parameters:

domainFp7 - The floating point field

getDomainFp8

public double **getDomainFp8**()

Returns the eighth domain floating point field.

Returns:

The floating point field

setDomainFp8

public void **setDomainFp8**(double domainFp8)

Sets the eighth domain floating point field

Parameters:

domainFp8 - The floating point field

_getDomainIpv4addr

public long **_getDomainIpv4addr**(int index)

_setDomainIpv4addr

public void **_setDomainIpv4addr**(int index,
long domainIpv4addr)

getDomainIpv4addr1

public long **getDomainIpv4addr1**()

Returns the first domain IPv4 address field.

Returns:

The IPv4 address field

setDomainIpv4addr1

public void **setDomainIpv4addr1**(long domainIpv4addr1)

Sets the first IPv4 address field.

Parameters:

domainIpv4addr1 - IPv4 address field

getDomainIpv4addr2

public long **getDomainIpv4addr2**()

Returns the second domain IPv4 address field.

Returns:

The IPv4 address field

setDomainIpv4addr2

```
public void setDomainIpv4addr2(long domainIpv4addr2)
```

Sets the second IPv4 address field.

Parameters:

domainIpv4addr2 - IPv4 address field

getDomainIpv4addr3

```
public long getDomainIpv4addr3()
```

Returns the third domain IPv4 address field.

Returns:

The IPv4 address field

setDomainIpv4addr3

```
public void setDomainIpv4addr3(long domainIpv4addr3)
```

Sets the third IPv4 address field.

Parameters:

domainIpv4addr3 - IPv4 address field

getDomainIpv4addr4

```
public long getDomainIpv4addr4()
```

Returns the fourth domain IPv4 address field.

Returns:

The IPv4 address field

setDomainIpv4addr4

```
public void setDomainIpv4addr4(long domainIpv4addr4)
```

Sets the fourth IPv4 address field.

Parameters:

domainIpv4addr4 - IPv4 address field

getDomainIpv6addr1

```
public byte[] getDomainIpv6addr1()
```

Returns the first domain IPv6 address field.

Returns:

The IPv6 address field

setDomainIpv6addr1

```
public void setDomainIpv6addr1(byte[] domainIpv6addr1)
```

Sets the first IPv6 address field.

Parameters:

domainIpv6addr1 - IPv6 address field

getDomainIpv6addr2

```
public byte[] getDomainIpv6addr2()
```

Returns the second domain IPv6 address field.

Returns:

The IPv6 address field

setDomainIpv6addr2

```
public void setDomainIpv6addr2(byte[] domainIpv6addr2)
```

Sets the second IPv6 address field.

Parameters:

domainIpv6addr2 - IPv6 address field

getDomainIpv6addr3

```
public byte[] getDomainIpv6addr3()
```

Returns the third domain IPv6 address field.

Returns:

The IPv6 address field

setDomainIpv6addr3

```
public void setDomainIpv6addr3(byte[] domainIpv6addr3)
```

Sets the third IPv6 address field.

Parameters:

domainIpv6addr3 - IPv6 address field

getDomainIpv6addr4

```
public byte[] getDomainIpv6addr4()
```

Returns the fourth domain IPv6 address field.

Returns:

The IPv6 address field

setDomainIpv6addr4

```
public void setDomainIpv6addr4(byte[] domainIpv6addr4)
```

Sets the fourth IPv6 address field.

Parameters:

domainIpv6addr4 - IPv6 address field

getDomainNumber1

```
public long getDomainNumber1()
```

Returns the first domain number field.

Returns:

The long field.

setDomainNumber1

```
public void setDomainNumber1(long domainNumber1)
```

Sets the first domain number field.

Parameters:

domainNumber1 - Domain number field

getDomainNumber10

```
public long getDomainNumber10()
```

Returns the tenth domain number field.

Returns:

The long field.

setDomainNumber10

```
public void setDomainNumber10(long domainNumber10)
```

Sets the tenth domain number field.

Parameters:

domainNumber10 - Domain number field

getDomainNumber11

```
public long getDomainNumber11()
```

Returns the eleventh domain number field.

Returns:

The long field.

setDomainNumber11

```
public void setDomainNumber11(long domainNumber11)
```

Sets the eleventh domain number field.

Parameters:

domainNumber11 - Domain number field

getDomainNumber12

```
public long getDomainNumber12()
```

Returns the twelve domain number field.

Returns:

The long field.

setDomainNumber12

```
public void setDomainNumber12(long domainNumber12)
```

Sets the twelve domain number field.

Parameters:

domainNumber12 - Domain number field

getDomainNumber13

```
public long getDomainNumber13()
```

Returns the thirteen domain number field.

Returns:

The long field.

setDomainNumber13

```
public void setDomainNumber13(long domainNumber13)
```

Sets the thirteen domain number field.

Parameters:

domainNumber13 - Domain number field

getDomainNumber2

```
public long getDomainNumber2()
```

Returns the second domain number field.

Returns:

The long field.

setDomainNumber2

```
public void setDomainNumber2(long domainNumber2)
```

Sets the second domain number field.

Parameters:

domainNumber2 - Domain number field

getDomainNumber3

```
public long getDomainNumber3()
```

Returns the third domain number field.

Returns:

The long field.

setDomainNumber3

```
public void setDomainNumber3(long domainNumber3)
```

Sets the third domain number field.

Parameters:

domainNumber3 - Domain number field

getDomainNumber4

```
public long getDomainNumber4()
```

Returns the fourth domain number field.

Returns:

The long field.

setDomainNumber4

```
public void setDomainNumber4(long domainNumber4)
```

Sets the fourth domain number field.

Parameters:

domainNumber4 - Domain number field

getDomainNumber5

```
public long getDomainNumber5()
```

Returns the fifth domain number field.

Returns:

The long field.

setDomainNumber5

```
public void setDomainNumber5(long domainNumber5)
```

Sets the fifth domain number field.

Parameters:

domainNumber5 - Domain number field

getDomainNumber6

```
public long getDomainNumber6()
```

Returns the sixth domain number field.

Returns:

The long field.

setDomainNumber6

```
public void setDomainNumber6(long domainNumber6)
```

Sets the sixth domain number field.

Parameters:

domainNumber6 - Domain number field

getDomainNumber7

```
public long getDomainNumber7()
```

Returns the seventh domain number field.

Returns:

The long field.

setDomainNumber7

```
public void setDomainNumber7(long domainNumber7)
```

Sets the seventh domain number field.

Parameters:

domainNumber7 - Domain number field

getDomainNumber8

```
public long getDomainNumber8()
```

Returns the eighth domain number field.

Returns:

The long field.

setDomainNumber8

```
public void setDomainNumber8(long domainNumber8)
```

Sets the eight domain number field.

Parameters:

domainNumber8 - Domain number field

getDomainNumber9

```
public long getDomainNumber9()
```

Returns the ninth domain number field.

Returns:

The long field.

setDomainNumber9

```
public void setDomainNumber9(long domainNumber9)
```

Sets the ninth domain number field.

Parameters:

domainNumber9 - Domain number field

getDomainResourceRef1

```
public ResourceReference getDomainResourceRef1()
```

Returns the first domain reference field.

Returns:

The reference to another resource

setDomainResourceRef1

```
public void setDomainResourceRef1(ResourceReference domainResourceRef1)
```

Sets the first domain reference field.

Parameters:

domainResourceRef1 - The reference to another resource

getDomainResourceRef2

```
public ResourceReference getDomainResourceRef2()
```

Returns the second domain reference field.

Returns:

The reference to another resource.

setDomainResourceRef2

```
public void setDomainResourceRef2(ResourceReference domainResourceRef2)
```

Sets the second domain reference field.

Parameters:

domainResourceRef2 - The reference to another resource

getDomainResourceRef3

```
public ResourceReference getDomainResourceRef3()
```

Returns the third domain reference field.

Returns:

The reference to another resource.

setDomainResourceRef3

```
public void setDomainResourceRef3(ResourceReference domainResourceRef3)
```

Sets the third domain reference field.

Parameters:

domainResourceRef3 - The reference to another resource

getDomainResourceRef4

```
public ResourceReference getDomainResourceRef4()
```

Returns the fourth domain reference field.

Returns:

The reference to another resource.

setDomainResourceRef4

```
public void setDomainResourceRef4(ResourceReference domainResourceRef4)
```

Sets the fourth domain reference field.

Parameters:

domainResourceRef1 - The reference to another resource

getDomainString1

```
public String getDomainString1()
```


Returns the first domain string field.

Returns:

The string field.

setDomainString1

```
public void setDomainString1(String domainString1)
```

Sets the first domain string field.

Parameters:

domainString1 - Domain string field

getDomainString10

```
public String getDomainString10()
```

Returns the tenth domain string field.

Returns:

The string field.

setDomainString10

```
public void setDomainString10(String domainString10)
```

Sets the tenth domain string field.

Parameters:

domainString10 - Domain string field

getDomainString11

```
public String getDomainString11()
```

Returns the eleventh domain string field.

Returns:

The string field.

setDomainString11

```
public void setDomainString11(String domainString11)
```

Sets the eleventh domain string field.

Parameters:

domainString11 - Domain string field

getDomainString12

```
public String getDomainString12()
```

Returns the twelve domain string field.

Returns:

The string field.

setDomainString12

```
public void setDomainString12(String domainString12)
```

Sets the twelve domain string field.

Parameters:

domainString12 - Domain string field

getDomainString13

```
public String getDomainString13()
```

Returns the thirteen domain string field.

Returns:

The string field.

setDomainString13

```
public void setDomainString13(String domainString13)
```

Sets the thirteen domain string field.

Parameters:

domainString13 - Domain string field

getDomainString14

```
public String getDomainString14()
```

Returns the fourteen domain string field.

Returns:

The string field.

setDomainString14

```
public void setDomainString14(String domainString14)
```

Sets the fourteen domain string field.

Parameters:

domainString14 - Domain string field

getDomainString15

```
public String getDomainString15()
```

Returns the fifteen domain string field.

Returns:

The string field.

setDomainString15

```
public void setDomainString15(String domainString15)
```

Sets the fifteen domain string field.

Parameters:

domainString15 - Domain string field

getDomainString16

```
public String getDomainString16()
```

Returns the sixteenth domain string field.

Returns:

The string field.

setDomainString16

```
public void setDomainString16(String domainString16)
```

Sets the sixteenth domain string field.

Parameters:

domainString16 - Domain string field

getDomainString17

```
public String getDomainString17()
```

Returns the seventeenth domain string field.

Returns:

The string field.

setDomainString17

```
public void setDomainString17(String domainString17)
```

Sets the seventeenth domain string field.

Parameters:

domainString1 - Domain string field

getDomainString18

```
public String getDomainString18()
```

Returns the eighteen domain string field.

Returns:

The string field.

setDomainString18

```
public void setDomainString18(String domainString18)
```

Sets the eighteenth domain string field.

Parameters:

domainString18 - Domain string field

getDomainString19

```
public String getDomainString19()
```

Returns the nineteenth domain string field.

Returns:

The string field.

setDomainString19

```
public void setDomainString19(String domainString19)
```

Sets the nineteenth domain string field.

Parameters:

domainString19 - Domain string field

getDomainString2

```
public String getDomainString2()
```

Returns the second domain string field.

Returns:

The string field.

setDomainString2

```
public void setDomainString2(String domainString2)
```

Sets the second domain string field.

Parameters:

domainString2 - Domain string field

getDomainString20

```
public String getDomainString20()
```

Returns the twentieth domain string field.

Returns:

The string field.

setDomainString20

```
public void setDomainString20(String domainString20)
```

Sets the twentieth domain string field.

Parameters:

domainString20 - Domain string field

getDomainString21

```
public String getDomainString21()
```

Returns the twenty first domain string field.

Returns:

The string field.

setDomainString21

```
public void setDomainString21(String domainString21)
```

Sets the twenty first domain string field.

Parameters:

domainString21 - Domain string field

getDomainString22

```
public String getDomainString22()
```

Returns the twenty second domain string field.

Returns:

The string field.

setDomainString22

```
public void setDomainString22(String domainString22)
```

Sets the twenty second domain string field.

Parameters:

domainString22 - Domain string field

getDomainString23

```
public String getDomainString23()
```

Returns the twenty third domain string field.

Returns:

The string field.

setDomainString23

```
public void setDomainString23(String domainString23)
```

Sets the twenty third domain string field.

Parameters:

domainString23 - Domain string field

getDomainString24

```
public String getDomainString24()
```

Returns the twenty fourth domain string field.

Returns:

The string field.

setDomainString24

```
public void setDomainString24(String domainString24)
```

Sets the twenty fourth domain string field.

Parameters:

domainString24 - Domain string field

getDomainString25

```
public String getDomainString25()
```

Returns the twenty fifth domain string field.

Returns:

The string field.

setDomainString25

```
public void setDomainString25(String domainString25)
```

Sets the twenty fifth domain string field.

Parameters:

domainString25 - Domain string field

getDomainString26

```
public String getDomainString26()
```

Returns the twenty sixth domain string field.

Returns:

The string field.

setDomainString26

```
public void setDomainString26(String domainString26)
```

Sets the twenty sixth domain string field.

Parameters:

domainString26 - Domain string field

getDomainString27

```
public String getDomainString27()
```

Returns the twenty seventh domain string field.

Returns:

The string field.

setDomainString27

```
public void setDomainString27(String domainString27)
```

Sets the twenty seventh domain string field.

Parameters:

domainString27 - Domain string field

getDomainString28

```
public String getDomainString28()
```

Returns the twenty eighth domain string field.

Returns:

The string field.

setDomainString28

```
public void setDomainString28(String domainString28)
```

Sets the twenty eighth domain string field.

Parameters:

domainString28 - Domain string field

getDomainString29

```
public String getDomainString29()
```

Returns the twenty ninth domain string field.

Returns:

The string field.

setDomainString29

```
public void setDomainString29(String domainString29)
```

Sets the twenty ninth domain string field.

Parameters:

domainString29 - Domain string field

getDomainString3

```
public String getDomainString3()
```

Returns the third domain string field.

Returns:

The string field.

setDomainString3

```
public void setDomainString3(String domainString3)
```

Sets the third domain string field.

Parameters:

domainString3 - Domain string field

getDomainString30

```
public String getDomainString30()
```

Returns the thirtieth domain string field.

Returns:

The string field.

setDomainString30

```
public void setDomainString30(String domainString30)
```

Sets the thirtieth domain string field.

Parameters:

domainString30 - Domain string field

getDomainString31

```
public String getDomainString31()
```


Returns the thirty first domain string field.

Returns:

The string field.

setDomainString31

```
public void setDomainString31(String domainString31)
```

Sets the thirty first domain string field.

Parameters:

domainString31 - Domain string field

getDomainString32

```
public String getDomainString32()
```

Returns the thirty second domain string field.

Returns:

The string field.

setDomainString32

```
public void setDomainString32(String domainString32)
```

Sets the thirty second domain string field.

Parameters:

domainString32 - Domain string field

getDomainString33

```
public String getDomainString33()
```

Returns the thirty third domain string field.

Returns:

The string field.

setDomainString33

```
public void setDomainString33(String domainString33)
```

Sets the thirty third domain string field.

Parameters:

domainString33 - Domain string field

getDomainString34

```
public String getDomainString34()
```

Returns the thirty fourth domain string field.

Returns:

The string field.

setDomainString34

```
public void setDomainString34(String domainString34)
```

Sets the thirty fourth domain string field.

Parameters:

domainString34 - Domain string field

getDomainString4

```
public String getDomainString4()
```

Returns the fourth domain string field.

Returns:

The string field.

setDomainString4

```
public void setDomainString4(String domainString4)
```

Sets the fourth domain string field.

Parameters:

domainString4 - Domain string field

getDomainString5

```
public String getDomainString5()
```

Returns the fifth domain string field.

Returns:

The string field.

setDomainString5

```
public void setDomainString5(String domainString5)
```

Sets the fifth domain string field.

Parameters:

domainString5 - Domain string field

getDomainString6

```
public String getDomainString6()
```

Returns the sixth domain string field.

Returns:

The string field.

setDomainString6

```
public void setDomainString6(String domainString6)
```

Sets the sixth domain string field.

Parameters:

domainString6 - Domain string field

getDomainString7

```
public String getDomainString7()
```

Returns the seventh domain string field.

Returns:

The string field.

setDomainString7

```
public void setDomainString7(String domainString7)
```

Sets the seventh domain string field.

Parameters:

domainString7 - Domain string field

getDomainString8

```
public String getDomainString8()
```

Returns the eighth domain string field.

Returns:

The string field.

setDomainString8

```
public void setDomainString8(String domainString8)
```

Sets the eighth domain string field.

Parameters:

domainString8 - Domain string field

getDomainString9

```
public String getDomainString9()
```

Returns the ninth domain string field.

Returns:

The string field.

setDomainString9

```
public void setDomainString9(String domainString9)
```

Sets the ninth domain string field.

Parameters:

domainString9 - Domain string field

com.arcsight.product.manager.resource.service.v1.model.event

Class SecurityEventFieldProfile

java.lang.Object
└─
com.arcsight.product.manager.resource.service.v1.model.event.SecurityEventFieldProfile

All Implemented Interfaces:
Serializable

public class **SecurityEventFieldProfile**
extends Object
implements Serializable

Describes what fields in the event are to be populated in SecurityEvent.

JSON prototype

Constructor Summary

public	SecurityEventFieldProfile()

Method Summary

byte[]	getProfile() Returns the array of indexes of ArcFields that need to be populated.
void	setProfile (byte[] profile) Sets the array of indexes of ArcFields that need to be populated.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

SecurityEventFieldProfile

public **SecurityEventFieldProfile()**

Methods

getProfile

```
public byte[] getProfile()
```

Returns the array of indexes of ArcFields that need to be populated.

Returns:

array of ArcField indexes

setProfile

```
public void setProfile(byte[] profile)
```


Sets the array of indexes of ArcFields that need to be populated.

Parameters:

`profile` - array of ArcField indexes

com.arcsight.product.manager.resource.service.v1.model.event

Class SensorRelatedDescriptorBase



```
public class SensorRelatedDescriptorBase
extends AddressableDescriptorBase
implements Serializable, Comparable, Serializable, Serializable
```

The base part of descriptors for various types of sensors and devices.

JSON prototype

Constructor Summary	
public	SensorRelatedDescriptorBase()

Method Summary	
boolean	equals (SensorRelatedDescriptorBase descriptor) Returns whether this object is equal to the another object descriptor.
Long	getDescriptorId () Returns the Id of this descriptor.
String	getTimeZone () Returns the time zone where this device locates in.
String	getVersion () Returns the version of this device or agent.
int	hashCode ()
void	setDescriptorId (Long descriptorId) Sets the unique Id of this descriptor.

void	<u>setTimeZone</u> (String timeZone) Sets the time zone where this device locates in.
void	<u>setVersion</u> (String version) Sets the version of this device or agent.

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.AddressableDescriptorBase](#)

[compareTo](#), [equalsDescriptorBase](#), [getAddress](#), [getAddressAsBytes](#), [getAssetId](#), [getAssetLocalId](#), [getAssetName](#), [getDnsDomain](#), [getHostName](#), [getMacAddress](#), [getNtDomain](#), [getTranslatedAddress](#), [getTranslatedAddressAsBytes](#), [getTranslatedZone](#), [getZone](#), [hashCode](#), [setAddress](#), [setAddressAsBytes](#), [setAssetId](#), [setAssetLocalId](#), [setAssetName](#), [setDnsDomain](#), [setHostName](#), [setMacAddress](#), [setNtDomain](#), [setTranslatedAddress](#), [setTranslatedAddressAsBytes](#), [setTranslatedZone](#), [setZone](#)

Methods inherited from class

[com.arcsight.product.manager.resource.service.v1.model.event.MutableBase](#)

[isMutable](#), [setMutable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface java.lang.Comparable

[compareTo](#)

Constructors

SensorRelatedDescriptorBase

```
public SensorRelatedDescriptorBase()
```

Methods

getDescriptorId

```
public Long getDescriptorId()
```

Returns the Id of this descriptor.

Returns:

Id of the descriptor

setDescriptorId

```
public void setDescriptorId(Long descriptorId)
```


Sets the unique Id of this descriptor.

Parameters:

descriptorId - Id of the descriptor

getVersion

```
public String getVersion()
```

Returns the version of this device or agent.

Returns:

The version

setVersion

```
public void setVersion(String version)
```

Sets the version of this device or agent.

Parameters:

version - The version

getTimeZone

```
public String getTimeZone()
```

Returns the time zone where this device locates in.

Returns:

The time zone

setTimeZone

```
public void setTimeZone(String timeZone)
```

Sets the time zone where this device locates in.

Parameters:

timeZone - The time zone

equals

```
public boolean equals(SensorRelatedDescriptorBase descriptor)
```

Returns whether this object is equal to the another object descriptor.

Parameters:

descriptor - another object to compare with

hashCode


```
public int hashCode()
```


Package

com.arcsight.product.manager.resource.service.v1.model.jaxb

com.arcsight.product.manager.resource.service.v1.model.jaxb

Class HashMapOfDeviceDetailsListResponse



```
public class HashMapOfDeviceDetailsListResponse
extends com.arcsight.coma.util.HashMapOfListsResponse
```

Class to be used with JAXB for return types like HashMap>.
See Also:
com.arcsight.product.manager.resource.service.v1.impl.ConnectorServiceImpl


Constructor Summary	
public	HashMapOfDeviceDetailsListResponse()
Methods inherited from class com.arcsight.coma.util.HashMapOfListsResponse	
getReturn, setReturn	
Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Constructors

```
HashMapOfDeviceDetailsListResponse
public HashMapOfDeviceDetailsListResponse()
```

com.arcsight.product.manager.resource.service.v1.model.jaxb

Class HashMapOfStringListResponse



```
public class HashMapOfStringListResponse
extends com.arcsight.coma.util.HashMapOfListsResponse
```

Class to be used with JAXB for return types like HashMap>.
See Also:
com.arcsight.product.manager.resource.service.v1.impl.ResourceDaoBase

Constructor Summary

public	HashMapOfStringListResponse()

Methods inherited from class com.arcsight.coma.util.HashMapOfListsResponse

getReturn, setReturn

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

HashMapOfStringListResponse

```
public HashMapOfStringListResponse()
```

com.arcsight.product.manager.resource.service.v1.model.jaxb

Class ObjectFactory

java.lang.Object
└-com.arcsight.product.manager.resource.service.v1.model.jaxb.ObjectFactory

public final class **ObjectFactory**
extends Object

Constructor Summary	
public	ObjectFactory()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ObjectFactory
public **ObjectFactory**()

Package

com.arcsight.product.manager.resource.service.v1.rest

com.arcsight.product.manager.resource.service.v1.rest Class CaseServiceImpl

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.rest.CaseServiceImpl

public class **CaseServiceImpl**
extends Object

A service that allows users to work with Cases.

Constructor Summary

public	CaseServiceImpl()

Method Summary

Void	addCaseEvents (CaseServiceAddCaseEvents value) Adds these events to the case specified with the given case ID.
CaseServiceAddRelationshipResponse	addRelationship (CaseServiceAddRelationship value) Adds the relationship of the type relationshipType between specified target and source resources.
CaseServiceAddRelationshipResponse	addRelationship (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
CaseServiceAddRelationshipResponse	addRelationshipPost (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
CaseServiceCaseClosureStatsResponse	caseClosureStats (CaseServiceCaseClosureStats value) Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.
CaseServiceCaseClosureStatsResponse	caseClosureStats (String authToken, String startTime, String endTime, String groupIds, String numGroupResults, String numUserResults, String metricType, String sla, javax.ws.rs.core.HttpHeaders hh) Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.
CaseServiceCaseClosureStatsResponse	caseClosureStatsPost (String authToken, String startTime, String endTime, String groupIds, String numGroupResults, String numUserResults, String metricType, String sla, javax.ws.rs.core.HttpHeaders hh) Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.

<u>CaseServiceCaseClosureVelocityResponse</u>	<u>caseClosureVelocity</u> (<u>CaseServiceCaseClosureVelocity</u> value) Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend
<u>CaseServiceCaseClosureVelocityResponse</u>	<u>caseClosureVelocity</u> (String authToken, String startTime, String endTime, javax.ws.rs.core.HttpHeaders hh) Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend
<u>CaseServiceCaseClosureVelocityResponse</u>	<u>caseClosureVelocityPost</u> (String authToken, String startTime, String endTime, javax.ws.rs.core.HttpHeaders hh) Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend
<u>CaseServiceContainsDirectMemberByNameOrAliasResponse</u>	<u>containsDirectMemberByNameOrAlias</u> (<u>CaseServiceContainsDirectMemberByNameOrAlias</u> value) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
<u>CaseServiceContainsDirectMemberByNameOrAliasResponse</u>	<u>containsDirectMemberByNameOrAlias</u> (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
<u>CaseServiceContainsDirectMemberByNameOrAliasResponse</u>	<u>containsDirectMemberByNameOrAliasPost</u> (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
<u>CaseServiceCopyResourceIntoGroupResponse</u>	<u>copyResourceIntoGroup</u> (<u>CaseServiceCopyResourceIntoGroup</u> value) Creates a copy of the given resource of type S and inserts that resource into the given target group.
<u>CaseServiceCopyResourceIntoGroupResponse</u>	<u>copyResourceIntoGroup</u> (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
<u>CaseServiceCopyResourceIntoGroupResponse</u>	<u>copyResourceIntoGroupPost</u> (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
<u>CaseServiceCountResponse</u>	<u>count</u> (<u>CaseServiceCount</u> value) Returns the case count after applying various filters and aggregated by aggBy.
<u>CaseServiceCountResponse</u>	<u>count</u> (String authToken, long startTime, long endTime, String aggGranularity, String timeZone, String stage, String state, String severity, String assignee, String aggBy, javax.ws.rs.core.HttpHeaders hh) Returns the case count after applying various filters and aggregated by aggBy.
<u>CaseServiceCountResponse</u>	<u>countPost</u> (String authToken, long startTime, long endTime, String aggGranularity, String timeZone, String stage, String state, String severity, String assignee, String aggBy, javax.ws.rs.core.HttpHeaders hh) Returns the case count after applying various filters and aggregated by aggBy.

Void	<u>delete</u> (<u>CaseServiceDelete</u> value) Deletes the resource of the type S from the database.
Void	<u>deleteAllCaseEvents</u> (<u>CaseServiceDeleteAllCaseEvents</u> value) Delete all events whose links are referred to the case specified by the given case ID.
Void	<u>deleteAllCaseEvents</u> (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Delete all events whose links are referred to the case specified by the given case ID.
Void	<u>deleteAllCaseEventsPost</u> (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Delete all events whose links are referred to the case specified by the given case ID.
Void	<u>deleteByLocalId</u> (<u>CaseServiceDeleteByLocalId</u> value) Deletes the resource identified by the local ID.
Void	<u>deleteByLocalId</u> (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	<u>deleteByLocalIdPost</u> (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	<u>deleteByUUID</u> (<u>CaseServiceDeleteByUUID</u> value) Deletes the resource identified by the ID.
Void	<u>deleteByUUID</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	<u>deleteByUUIDPost</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	<u>deleteCaseEvents</u> (<u>CaseServiceDeleteCaseEvents</u> value) Deletes the mapping data which links the events specified by their event IDs to the case specified by the given case ID.
Void	<u>deleteResource</u> (<u>CaseServiceDeleteResource</u> value) Deletes the resource of the type S from the database.
Void	<u>deleteResources</u> (<u>CaseServiceDeleteResources</u> value) Deletes the resources of the type S from the database.
<u>CaseServiceFindAllIdsResponse</u>	<u>findAllIds</u> (<u>CaseServiceFindAllIds</u> value) Finds and returns the list of IDs of all the resources of type S.
<u>CaseServiceFindAllIdsResponse</u>	<u>findAllIds</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
<u>CaseServiceFindAllIdsResponse</u>	<u>findAllIdsPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
<u>CaseServiceFindByIdResponse</u>	<u>findById</u> (<u>CaseServiceFindById</u> value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

<u>CaseServiceFindByIdResponse</u>	<u>findById</u> (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>CaseServiceFindByIdResponse</u>	<u>findByIdPost</u> (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>CaseServiceFindByUUIDResponse</u>	<u>findByUUID</u> (<u>CaseServiceFindByUUID</u> value) Returns the resource of the type S identified by its ID.
<u>CaseServiceFindByUUIDResponse</u>	<u>findByUUID</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
<u>CaseServiceFindByUUIDResponse</u>	<u>findByUUIDPost</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
<u>CaseServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDs</u> (<u>CaseServiceGetAllAttachmentOnlyResourceIDs</u> value) Returns a list of the IDs of all attachments of the type S.
<u>CaseServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDs</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
<u>CaseServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDsPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
<u>CaseServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypes</u> (<u>CaseServiceGetAllowedUserTypes</u> value) Returns the array of user types that are allowed to access the service.
<u>CaseServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypes</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
<u>CaseServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypesPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
<u>CaseServiceGetAllPathsToRootResponse</u>	<u>getAllPathsToRoot</u> (<u>CaseServiceGetAllPathsToRoot</u> value) Returns a list of all the paths to root relevant to the service for the given resource.
<u>CaseServiceGetAllPathsToRootResponse</u>	<u>getAllPathsToRoot</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
<u>CaseServiceGetAllPathsToRootAsStringsResponse</u>	<u>getAllPathsToRootAsStrings</u> (<u>CaseServiceGetAllPathsToRootAsStrings</u> value) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
<u>CaseServiceGetAllPathsToRootAsStringsResponse</u>	<u>getAllPathsToRootAsStrings</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.

CaseServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStringsPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
CaseServiceGetAllPathsToRootResponse	getAllPathsToRootPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
CaseServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (CaseServiceGetAllUnassignedResourceIDs value) Returns a list of the IDs of all unassigned resources of the type S.
CaseServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
CaseServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
CaseServiceGetCaseEventIDsResponse	getCaseEventIDs (CaseServiceGetCaseEventIDs value) Gets all the event IDs that are added in the specified case.
CaseServiceGetCaseEventIDsResponse	getCaseEventIDs (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Gets all the event IDs that are added in the specified case.
CaseServiceGetCaseEventIDsResponse	getCaseEventIDsPost (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Gets all the event IDs that are added in the specified case.
CaseServiceGetCaseEventsTimeSpanResponse	getCaseEventsTimeSpan (CaseServiceGetCaseEventsTimeSpan value) Gets min and max receipt times of all the events in the case specified by the given case ID.
CaseServiceGetCaseEventsTimeSpanResponse	getCaseEventsTimeSpan (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Gets min and max receipt times of all the events in the case specified by the given case ID.
CaseServiceGetCaseEventsTimeSpanResponse	getCaseEventsTimeSpanPost (String authToken, String caseId, javax.ws.rs.core.HttpHeaders hh) Gets min and max receipt times of all the events in the case specified by the given case ID.
CaseServiceGetCasesGroupIDResponse	getCasesGroupID (CaseServiceGetCasesGroupID value) Returns the ID of the "Cases" group which is the child of the meta group.
CaseServiceGetCasesGroupIDResponse	getCasesGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the ID of the "Cases" group which is the child of the meta group.
CaseServiceGetCasesGroupIDResponse	getCasesGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the ID of the "Cases" group which is the child of the meta group.
CaseServiceGetChildNamesAndAliasesResponse	getChildNamesAndAliases (CaseServiceGetChildNamesAndAliases value) Deprecated. This method is left for backward compatibility only. Please rather use method getNamesAndAliases(List)
CaseServiceGetCorruptedResourcesResponse	getCorruptedResources (CaseServiceGetCorruptedResources value) Returns the list of descriptors for all the corrupted resources of the corresponding type.

CaseServiceGetCorruptedResourcesResponse	getCorruptedResources (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
CaseServiceGetCorruptedResourcesResponse	getCorruptedResourcesPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
CaseServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (CaseServiceGetDependentResourceIDsForResourceId value) Returns the list of the IDs of dependent resources for the specified resource of the type S.
CaseServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
CaseServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceIdPost (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
CaseServiceGetEnabledResourceIDsResponse	getEnabledResourceIDs (CaseServiceGetEnabledResourceIDs value) Checks the specified resources and returns the list of IDs of the resources that are enabled.
CaseServiceGetESMVersionResponse	getESMVersion (CaseServiceGetESMVersion value) Returns the version of ESM manager.
CaseServiceGetESMVersionResponse	getESMVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
CaseServiceGetESMVersionResponse	getESMVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
CaseServiceGetEventExportStatusResponse	getEventExportStatus (CaseServiceGetEventExportStatus value) Returns the export status of the event(s).
CaseServiceGetExclusivelyDependentResourcesResponse	getExclusivelyDependentResources (CaseServiceGetExclusivelyDependentResources value) Returns a list of resources depending on the given resource of the type S.
CaseServiceGetMetaGroupIDResponse	getMetaGroupID (CaseServiceGetMetaGroupID value) Returns the string value of ID of the meta group for the resources of type S.
CaseServiceGetMetaGroupIDResponse	getMetaGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
CaseServiceGetMetaGroupIDResponse	getMetaGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
CaseServiceGetNamesAndAliasesResponse	getNamesAndAliases (CaseServiceGetNamesAndAliases value) Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds.
CaseServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (CaseServiceGetPersonalAndSharedResourceRoots value) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.

CaseServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
CaseServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRootsPost (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
CaseServiceGetPersonalGroupResponse	getPersonalGroup (CaseServiceGetPersonalGroup value) Returns the string value of ID of the user's personal group for the resources of type S.
CaseServiceGetPersonalGroupResponse	getPersonalGroup (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the user's personal group for the resources of type S.
CaseServiceGetPersonalGroupResponse	getPersonalGroupPost (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the user's personal group for the resources of type S.
CaseServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (CaseServiceGetPersonalResourceRoots value) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
CaseServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
CaseServiceGetPersonalResourceRootsResponse	getPersonalResourceRootsPost (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
CaseServiceGetReferencePagesResponse	getReferencePages (CaseServiceGetReferencePages value) Returns the list of reference pages for the resource identified by the ID.
CaseServiceGetReferencePagesResponse	getReferencePages (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
CaseServiceGetReferencePagesResponse	getReferencePagesPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
CaseServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (CaseServiceGetRelationshipsOfParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
CaseServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
CaseServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.

CaseServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (CaseServiceGetRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
CaseServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
CaseServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
CaseServiceGetResourceByIdResponse	getResourceById (CaseServiceGetResourceById value) Returns the resource of the type S specified by resource ID.
CaseServiceGetResourceByIdResponse	getResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
CaseServiceGetResourceByIdResponse	getResourceByIdPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
CaseServiceGetResourceByNameResponse	getResourceByName (CaseServiceGetResourceByName value) Returns one of the resources of the type S with the specified name.
CaseServiceGetResourceByNameResponse	getResourceByName (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
CaseServiceGetResourceByNameResponse	getResourceByNamePost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
CaseServiceGetResourceIfModifiedResponse	getResourceIfModified (CaseServiceGetResourceIfModified value) Returns the resource if it is newer than the signature specifies; otherwise returns null .
CaseServiceGetResourcesByIdsResponse	getResourcesByIds (CaseServiceGetResourcesByIds value) Returns the resources of the type S identified by the specified resource IDs.
CaseServiceGetResourcesByNamesResponse	getResourcesByNames (CaseServiceGetResourcesByNames value) Returns all the resources of the type S with the specified names.
CaseServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (CaseServiceGetResourcesByNameSafely value) Returns all the resources of the type S with the specified name.
CaseServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
CaseServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafelyPost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.

CaseServiceGetResourcesReferencePagesResponse	getResourcesReferencePages (CaseServiceGetResourcesReferencePages value) Returns the list of reference pages for the resources identified by the IDs.
CaseServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsers (CaseServiceGetResourcesWithVisibilityToUsers value) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsers (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsersPost (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (CaseServiceGetResourceTypesVisibleToUsers value) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsersPost (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
CaseServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (CaseServiceGetReverseRelationshipsOfParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
CaseServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
CaseServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
CaseServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (CaseServiceGetReverseRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
CaseServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

CaseServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
CaseServiceGetServiceMajorVersionResponse	getServiceMajorVersion (CaseServiceGetServiceMajorVersion value) The major version of this service.
CaseServiceGetServiceMajorVersionResponse	getServiceMajorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
CaseServiceGetServiceMajorVersionResponse	getServiceMajorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
CaseServiceGetServiceMinorVersionResponse	getServiceMinorVersion (CaseServiceGetServiceMinorVersion value) The minor version of this service.
CaseServiceGetServiceMinorVersionResponse	getServiceMinorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
CaseServiceGetServiceMinorVersionResponse	getServiceMinorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (CaseServiceGetSourcesWithThisTargetByACLRelationship value) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationshipPost (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByRelationshipResponse	getSourcesWithThisTargetByRelationship (CaseServiceGetSourcesWithThisTargetByRelationship value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse	getSourcesWithThisTargetByRelationshipCount (CaseServiceGetSourcesWithThisTargetByRelationshipCount value) Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (CaseServiceGetSourceURIWithThisTargetByRelationship value) Deprecated. <i>This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationship(S, int).</i>
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Deprecated. <i>This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int).</i>
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. <i>This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int).</i>
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. <i>This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int).</i>
CaseServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (CaseServiceGetSourceURIWithThisTargetByRelationship value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
CaseServiceGetSystemCasesGroupIDResponse	getSystemCasesGroupID (CaseServiceGetSystemCasesGroupID value) Returns the ID of the "System Cases" group which is the child of the meta group.

CaseServiceGetSystemCasesGroupIDResponse	getSystemCasesGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the ID of the "System Cases" group which is the child of the meta group.
CaseServiceGetSystemCasesGroupIDResponse	getSystemCasesGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the ID of the "System Cases" group which is the child of the meta group.
CaseServiceGetTargetsAsURIByRelationshipResponse	getTargetsAsURIByRelationship (CaseServiceGetTargetsAsURIByRelationship value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.
CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (CaseServiceGetTargetsAsURIByRelationshipForSourceId value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
CaseServiceGetTargetsByRelationshipResponse	getTargetsByRelationship (CaseServiceGetTargetsByRelationship value) Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.
CaseServiceGetTargetsByRelationshipCountResponse	getTargetsByRelationshipCount (CaseServiceGetTargetsByRelationshipCount value) Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.
CaseServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (CaseServiceGetTargetsByRelationshipForSourceId value) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
CaseServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
CaseServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
CaseServiceGetTargetsWithRelationshipTypeForResourceResponse	getTargetsWithRelationshipTypeForResource (CaseServiceGetTargetsWithRelationshipTypeForResource value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.

<u>CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceById</u> (<u>CaseServiceGetTargetsWithRelationshipTypeForResourceById</u> value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceById</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceByIdPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>CaseServiceHasReadPermissionResponse</u>	<u>hasReadPermission</u> (<u>CaseServiceHasReadPermission</u> value) Returns true if the source resource has Read permission on the target resource.
<u>CaseServiceHasReadPermissionResponse</u>	<u>hasReadPermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
<u>CaseServiceHasReadPermissionResponse</u>	<u>hasReadPermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
<u>CaseServiceHasReverseRelationshipResponse</u>	<u>hasReverseRelationship</u> (<u>CaseServiceHasReverseRelationship</u> value) Returns true if the relationship of the given target and source exists.
<u>CaseServiceHasWritePermissionResponse</u>	<u>hasWritePermission</u> (<u>CaseServiceHasWritePermission</u> value) Returns true if the source resource has Write permission on the target resource.
<u>CaseServiceHasWritePermissionResponse</u>	<u>hasWritePermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
<u>CaseServiceHasWritePermissionResponse</u>	<u>hasWritePermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
<u>CaseServiceHasXPermissionResponse</u>	<u>hasXPermission</u> (<u>CaseServiceHasXPermission</u> value) Returns true if the source resource has Execute (X) permission on the target resource.
<u>CaseServiceHasXPermissionResponse</u>	<u>hasXPermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
<u>CaseServiceHasXPermissionResponse</u>	<u>hasXPermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
<u>CaseServiceInsertResponse</u>	<u>insert</u> (<u>CaseServiceInsert</u> value) Inserts the resource of the type S.
<u>CaseServiceInsertResourceResponse</u>	<u>insertResource</u> (<u>CaseServiceInsertResource</u> value) Inserts the resource of the type S into the specified group.

<u>CaseServiceIsDisabledResponse</u>	<u>isDisabled</u> (<u>CaseServiceIsDisabled</u> value) Returns true if the resource is disabled.
<u>CaseServiceIsDisabledResponse</u>	<u>isDisabled</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
<u>CaseServiceIsDisabledResponse</u>	<u>isDisabledPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
<u>CaseServiceIsValidResourceIDResponse</u>	<u>isValidResourceID</u> (<u>CaseServiceIsValidResourceID</u> value) Returns true if the resource with the given ID does exist in the database.
<u>CaseServiceIsValidResourceIDResponse</u>	<u>isValidResourceID</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
<u>CaseServiceIsValidResourceIDResponse</u>	<u>isValidResourceIDPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
Void	<u>loadAdditional</u> (<u>CaseServiceLoadAdditional</u> value) Loads fields into the given resource that had not previously been loaded.
Void	<u>loadAdditional</u> (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	<u>loadAdditionalPost</u> (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
<u>CaseServiceOpenCasesResponse</u>	<u>openCases</u> (<u>CaseServiceOpenCases</u> value) Returns the list of case details of all the open cases for the requested userId
<u>CaseServiceOpenCasesResponse</u>	<u>openCases</u> (String authToken, String userIds, javax.ws.rs.core.HttpHeaders hh) Returns the list of case details of all the open cases for the requested userId
<u>CaseServiceOpenCasesResponse</u>	<u>openCasesPost</u> (String authToken, String userIds, javax.ws.rs.core.HttpHeaders hh) Returns the list of case details of all the open cases for the requested userId
Void	<u>resetState</u> (<u>CaseServiceResetState</u> value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	<u>resetState</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	<u>resetStatePost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>CaseServiceResolveRelationshipResponse</u>	<u>resolveRelationship</u> (<u>CaseServiceResolveRelationship</u> value) Returns true if the specified relationship exists between the source and the target resources.

CaseServiceResolveRelationshipResponse	resolveRelationship (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
CaseServiceResolveRelationshipResponse	resolveRelationshipPost (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
CaseServiceSeveritiesResponse	severities (CaseServiceSeverities value) Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english
CaseServiceSeveritiesResponse	severities (String authToken, String locale, javax.ws.rs.core.HttpHeaders hh) Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english
CaseServiceSeveritiesResponse	severitiesPost (String authToken, String locale, javax.ws.rs.core.HttpHeaders hh) Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english
CaseServiceStageTransitionsResponse	stageTransitions (CaseServiceStageTransitions value) Returns the duration of stage transition of those cases that matches with the given filters.
CaseServiceStageTransitionsResponse	stageTransitions (String authToken, String startTime, String endTime, String severity, String assignee, javax.ws.rs.core.HttpHeaders hh) Returns the duration of stage transition of those cases that matches with the given filters.
CaseServiceStageTransitionsResponse	stageTransitionsPost (String authToken, String startTime, String endTime, String severity, String assignee, javax.ws.rs.core.HttpHeaders hh) Returns the duration of stage transition of those cases that matches with the given filters.
Void	unloadAdditional (CaseServiceUnloadAdditional value) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
CaseServiceUpdateResponse	update (CaseServiceUpdate value) Updates the resource of the type S in the store.
Void	updateACLForResourceById (CaseServiceUpdateACLForResourceById value) Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder.
CaseServiceUpdateResourcesResponse	updateResources (CaseServiceUpdateResources value) Updates the resources of the type S in the database.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

CaseServiceImpl

```
public CaseServiceImpl()
```

Methods

addCaseEvents

```
public Void addCaseEvents(CaseServiceAddCaseEvents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds these events to the case specified with the given case ID.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteCaseEvents

```
public Void deleteCaseEvents(CaseServiceDeleteCaseEvents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the mapping data which links the events specified by their event IDs to the case specified by the given case ID. If the events in the list are not added to any other case, these preserved events will also be deleted from database. Also, the case will be updated with the new value for the field "estimated_starttime". Note that the preserved event is the event which is related to a case.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteAllCaseEvents

```
public Void deleteAllCaseEvents(String authToken,  
    String caseId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Delete all events whose links are referred to the case specified by the given case ID. If these preserved events are not added to any other case, all of them will also be deleted from database. Note that the preserved event is the event which is attached to a case.

Parameters:

caseId - The ID of case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteAllCaseEventsPost

```
public Void deleteAllCaseEventsPost(String authToken,  
    String caseId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Delete all events whose links are referred to the case specified by the given case ID. If these preserved events are not added to any other case, all of them will also be deleted from database. Note that the preserved event is the event which is attached to a case.

Parameters:

caseId - The ID of case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteAllCaseEvents

```
public Void deleteAllCaseEvents(CaseServiceDeleteAllCaseEvents value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Delete all events whose links are referred to the case specified by the given case ID. If these preserved events are not added to any other case, all of them will also be deleted from database. Note that the preserved event is the event which is attached to a case.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCaseEventIDs

```
public CaseServiceGetCaseEventIDsResponse getCaseEventIDs(String authToken,  
    String caseId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Gets all the event IDs that are added in the specified case.

Parameters:

caseId - The ID of the case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of Long values of the event IDs added in the specified case.

Throws:

[ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCaseEventIDsPost

```
public CaseServiceGetCaseEventIDsResponse getCaseEventIDsPost(String authToken,  
    String caseId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Gets all the event IDs that are added in the specified case.

Parameters:

caseId - The ID of the case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of Long values of the event IDs added in the specified case.

Throws:

[ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCaseEventIDs

```
public CaseServiceGetCaseEventIDsResponse getCaseEventIDs(CaseServiceGetCaseEventIDs  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Gets all the event IDs that are added in the specified case.

Parameters:

value - Model object containing request body

Returns:

The list of Long values of the event IDs added in the specified case.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCaseEventsTimeSpan

```
public CaseServiceGetCaseEventsTimeSpanResponse getCaseEventsTimeSpan(String authToken,  
    String caseId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Gets min and max receipt times of all the events in the case specified by the given case ID.

Parameters:

caseId - The ID of the case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the long values of the min and max receipt times of all the events in the case specified by the given case ID.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCaseEventsTimeSpanPost

```
public CaseServiceGetCaseEventsTimeSpanResponse getCaseEventsTimeSpanPost(String authToken,
    String caseId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Gets min and max receipt times of all the events in the case specified by the given case ID.

Parameters:

caseId - The ID of the case.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the long values of the min and max receipt times of all the events in the case specified by the given case ID.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCaseEventsTimeSpan

```
public CaseServiceGetCaseEventsTimeSpanResponse
getCaseEventsTimeSpan(CaseServiceGetCaseEventsTimeSpan value)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Gets min and max receipt times of all the events in the case specified by the given case ID.

Parameters:

value - Model object containing request body

Returns:

List of the long values of the min and max receipt times of all the events in the case specified by the given case ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSystemCasesGroupID

```
public CaseServiceGetSystemCasesGroupIDResponse getSystemCasesGroupID(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the ID of the "System Cases" group which is the child of the meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of resource ID for the system cases group.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSystemCasesGroupIDPost

```
public CaseServiceGetSystemCasesGroupIDResponse getSystemCasesGroupIDPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the ID of the "System Cases" group which is the child of the meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of resource ID for the system cases group.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSystemCasesGroupID

```
public CaseServiceGetSystemCasesGroupIDResponse
getSystemCasesGroupID(CaseServiceGetSystemCasesGroupID value)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the ID of the "System Cases" group which is the child of the meta group.

Parameters:

value - Model object containing request body

Returns:

The string value of resource ID for the system cases group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCasesGroupID

```
public CaseServiceGetCasesGroupIDResponse getCasesGroupID(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the ID of the "Cases" group which is the child of the meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of ID for the cases group.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCasesGroupIDPost

```
public CaseServiceGetCasesGroupIDResponse getCasesGroupIDPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the ID of the "Cases" group which is the child of the meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of ID for the cases group.

Throws:

[ServiceException](#) - If there was an error during authentication.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCasesGroupID

```
public CaseServiceGetCasesGroupIDResponse getCasesGroupID(CaseServiceGetCasesGroupID  
value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the ID of the "Cases" group which is the child of the meta group.

Parameters:

value - Model object containing request body

Returns:

The string value of ID for the cases group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getEventExportStatus

```
public CaseServiceGetEventExportStatusResponse  
getEventExportStatus(CaseServiceGetEventExportStatus value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the export status of the event(s). It checks whether provided event(s) is/are added to case(s) having external ID assigned.

Parameters:

value - Model object containing request body

Returns:

Returns true if provided event(s) is/are added to case(s) having external ID assigned, otherwise returns false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

severities

```
public CaseServiceSeveritiesResponse severities(String authToken,  
        String locale,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english

Parameters:

locale
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

severitiesPost

```
public CaseServiceSeveritiesResponse severitiesPost(String authToken,  
    String locale,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english

Parameters:

locale

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:**Throws:**

[ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

severities

```
public CaseServiceSeveritiesResponse severities(CaseServiceSeverities value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the allowed values of the consequence of severity for the cases for the specified locale if the locale is not provided, it will return the values for english

Parameters:

value - Model object containing request body

Returns:**Throws:**

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

caseClosureVelocity

```
public CaseServiceCaseClosureVelocityResponse caseClosureVelocity(String authToken,  
    String startTime,  
    String endTime,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend

Parameters:

startTime -- start of time window in epoch milli seconds.
endTime -- start of time window in epoch milli seconds.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

- case closure statistics across SOC.

Throws:

[ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

caseClosureVelocityPost

```
public CaseServiceCaseClosureVelocityResponse caseClosureVelocityPost(String authToken,  
    String startTime,  
    String endTime,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend

Parameters:

startTime -- start of time window in epoch milli seconds.
endTime -- start of time window in epoch milli seconds.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

- case closure statistics across SOC.

Throws:

[ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

caseClosureVelocity

```
public CaseServiceCaseClosureVelocityResponse  
caseClosureVelocity(CaseServiceCaseClosureVelocity value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the case closure statistics across SOC Average Time Taken to Close Case After Creation in milli seconds Average Time Taken to Close Case After Last Event Annotation in milli seconds Closed Cases Trend

Parameters:

value - Model object containing request body

Returns:

- case closure statistics across SOC.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

openCases

```
public CaseServiceOpenCasesResponse openCases(String authToken,  
        String userIds,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of case details of all the open cases for the requested userId

Parameters:

userIds - comma-separated list of user id's
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

- list of open cases details for the requested assignees

Throws:

[ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

openCasesPost

```
public CaseServiceOpenCasesResponse openCasesPost(String authToken,  
        String userIds,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of case details of all the open cases for the requested userId

Parameters:

userIds -- comma-separated list of user id's
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

- list of open cases details for the requested assignees

Throws:

ServiceException
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

openCases

```
public CaseServiceOpenCasesResponse openCases(CaseServiceOpenCases value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the list of case details of all the open cases for the requested userId

Parameters:

value - Model object containing request body

Returns:

- list of open cases details for the requested assignees

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

count

```
public CaseServiceCountResponse count(String authToken,
    long startTime,
    long endTime,
    String aggGranularity,
    String timeZone,
    String stage,
    String state,
    String severity,
    String assignee,
    String aggBy,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the case count after applying various filters and aggregated by aggBy.

Parameters:

startTime -- start time of the create time window the cases are to be counted.
endTime -- end time of the create time window the cases are to be counted.

aggGranularity -- granularity of case counts. Ex: daily, weekly, etc.
timeZone -- client timezone.
stage -- case stage filter
state -- case state filter
severity -- case severity filter.
assignee -- case assignee filter.
aggBy -- case aggregations fields.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

ServiceException -- when the passed in parameters contain some invalid values.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

for details of validation.

countPost

```
public CaseServiceCountResponse countPost(String authToken,  
    long startTime,  
    long endTime,  
    String aggGranularity,  
    String timeZone,  
    String stage,  
    String state,  
    String severity,  
    String assignee,  
    String aggBy,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case count after applying various filters and aggregated by aggBy.

Parameters:

startTime -- start time of the create time window the cases are to be counted.
endTime -- end time of the create time window the cases are to be counted.
aggGranularity -- granularity of case counts. Ex: daily, weekly, etc.
timeZone -- client timezone.
stage -- case stage filter
state -- case state filter
severity -- case severity filter.
assignee -- case assignee filter.
aggBy -- case aggregations fields.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

`ServiceException` -- when the passed in parameters contain some invalid values.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

for details of validation.

count

```
public CaseServiceCountResponse count(CaseServiceCount value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the case count after applying various filters and aggregated by aggBy.

Parameters:

value - Model object containing request body

Returns:**Throws:**

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

for details of validation.

stageTransitions

```
public CaseServiceStageTransitionsResponse stageTransitions(String authToken,
    String startTime,
    String endTime,
    String severity,
    String assignee,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the duration of stage transition of those cases that matches with the given filters.

Parameters:

startTime -- start time of the time window the case stage transitions are to be taken.

endTime -- start time of the time window the case stage transitions are to be taken..

severity -- case severity filter.

assignee -- case assignee filter.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

Throws:

`ServiceException` -- when the passed in parameters contain some invalid values.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

stageTransitionsPost

```
public CaseServiceStageTransitionsResponse stageTransitionsPost(String authToken,  
    String startTime,  
    String endTime,  
    String severity,  
    String assignee,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the duration of stage transition of those cases that matches with the given filters.

Parameters:

`startTime` -- start time of the time window the case stage transitions are to be taken.

`endTime` -- start time of the time window the case stage transitions are to be taken..

`severity` -- case severity filter.

`assignee` -- case assignee filter.

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:**Throws:**

`ServiceException` -- when the passed in parameters contain some invalid values.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

stageTransitions

```
public CaseServiceStageTransitionsResponse stageTransitions(CaseServiceStageTransitions  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the duration of stage transition of those cases that matches with the given filters.

Parameters:

`value` - Model object containing request body

Returns:**Throws:**

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

caseClosureStats

```
public CaseServiceCaseClosureStatsResponse caseClosureStats(String authToken,  
    String startTime,  
    String endTime,  
    String groupIds,  
    String numGroupResults,  
    String numUserResults,  
    String metricType,  
    String sla,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.

Parameters:

startTime -- start of time window for case closure.
endTime -- end of the time window for case closure
groupIds -- a comma-separated list of groupIds the closure metrics are needed for. If no groupId is specified, all groups will be considered.
numGroupResults -- the max number of top-performing groups whose stats will be returned. If no value is passed and no groupIds are passed then a maximum of 5 results will be returned. If no value is passed and groupIds are passed, the results for all specified groupIds are returned.
numUserResults -- the max number of top-performing users whose stats will be returned. If no value is passed a maximum of 5 user results per group will be passed. If 0 is passed, no user results will be returned for each group.
metricType -- a comma-separated string that the user can request to calculate additional metrics for the returned case stats. The list of supported values is specified in
sla -- service level agreements for calculating potential delay metric.SLA values need to be specified as a comma-separated string with each comma-separated element consisting of a severityLevel and the corresponding SLA in millis separated by a hyphen. E.g. "0-3600000,1-4800000"
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[ServiceException](#) -- when input parameters do not pass validation.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[com.arcsight.common.casehistory.service.CaseMetricType](#)

caseClosureStatsPost

```
public CaseServiceCaseClosureStatsResponse caseClosureStatsPost(String authToken,  
    String startTime,  
    String endTime,  
    String groupIds,  
    String numGroupResults,  
    String numUserResults,  
    String metricType,  
    String sla,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.

Parameters:

startTime -- start of time window for case closure.
endTime -- end of the time window for case closure
groupIds -- a comma-separated list of groupIds the closure metrics are needed for. If no groupId is specified, all groups will be considered.
numGroupResults -- the max number of top-performing groups whose stats will be returned. If no value is passed and no groupIds are passed then a maximum of 5 results will be returned. If no value is passed and groupIds are passed, the results for all specified groupIds are returned.
numUserResults -- the max number of top-performing users whose stats will be returned. If no value is passed a maximum of 5 user results per group will be passed. If 0 is passed, no user results will be returned for each group.
metricType -- a comma-separated string that the user can request to calculate additional metrics for the returned case stats. The list of supported values is specified in
sla -- service level agreements for calculating potential delay metric.SLA values need to be specified as a comma-separated string with each comma-separated element consisting of a severityLevel and the corresponding SLA in millis separated by a hyphen. E.g. "0-3600000,1-4800000"
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[ServiceException](#) -- when input parameters do not pass validation.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[com.arcsight.common.casehistory.service.CaseMetricType](#)

caseClosureStats

```
public CaseServiceCaseClosureStatsResponse caseClosureStats(CaseServiceCaseClosureStats  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the case closure statistics for user groups (owner groups) and the respective users (owners) belonging to the the group sorted by best performance.

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[com.arcsight.common.casehistory.service.CaseMetricType](#)

insert

```
public CaseServiceInsertResponse insert(CaseServiceInsert value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Inserts the resource of the type S. The system adds such required fields as resource ID if needed. The resource will be added to Unassigned group, and it's required that the current user has write permission to a Meta Group of the type S. So only a limited number of users can add and later access such new resources. Use another method, [insertResource\(resource, parentId\)](#) to create a new resource and add it to the group with the specified ID.

Parameters:

value - Model object containing request body

Returns:

The resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insertResource

```
public CaseServiceInsertResourceResponse insertResource(CaseServiceInsertResource value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Inserts the resource of the type S into the specified group.

Parameters:

value - Model object containing request body

Returns:

The inserted resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

delete

```
public Void delete(CaseServiceDelete value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource of the type S from the database.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findById

```
public CaseServiceFindByIdResponse findById(String authToken,
    long localId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByIdPost

```
public CaseServiceFindByIdResponse findByIdPost(String authToken,
    long localId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findById

```
public CaseServiceFindByIdResponse findById(CaseServiceFindById value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUID

```
public CaseServiceFindByUUIDResponse findByUUID(String authToken,
    String id,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDv0vLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUIDPost

```
public CaseServiceFindByUUIDResponse findByUUIDPost(String authToken,
    String id,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findByUUID

```
public CaseServiceFindByUUIDResponse findByUUID(CaseServiceFindByUUID value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

value - Model object containing request body

Returns:

The resource identified by the ID

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

update

```
public CaseServiceUpdateResponse update(CaseServiceUpdate value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Updates the resource of the type S in the store.

Parameters:

value - Model object containing request body

Returns:

The updated resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsDirectMemberByNameOrAlias

```
public CaseServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAlias(String authToken,  
    String groupId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAliasPost

```
public CaseServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAliasPost(String authToken,  
    String groupId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsDirectMemberByNameOrAlias

```
public CaseServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAlias(CaseServiceContainsDirectMemberByNameOrAlias value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

value - Model object containing request body

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroup

```
public CaseServiceCopyResourceIntoGroupResponse copyResourceIntoGroup(String authToken,  
    String newName,  
    String resourceId,  
    String oldParentId,  
    String newParentId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroupPost

```
public CaseServiceCopyResourceIntoGroupResponse copyResourceIntoGroupPost(String
authToken,
    String newName,
    String resourceId,
    String oldParentId,
    String newParentId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group. If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

copyResourceIntoGroup

```
public CaseServiceCopyResourceIntoGroupResponse
copyResourceIntoGroup(CaseServiceCopyResourceIntoGroup value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.
If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

value - Model object containing request body

Returns:

The inserted resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResource

```
public Void deleteResource(CaseServiceDeleteResource value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Deletes the resource of the type S from the database. Method allows to specify whether to abort the transaction during conflicts in the validation.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalId

```
public Void deleteByLocalId(String authToken,  
                             long id,  
                             javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalIdPost

```
public Void deleteByLocalIdPost(String authToken,  
    long id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByLocalId

```
public Void deleteByLocalId(CaseServiceDeleteByLocalId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUID

```
public Void deleteByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUIDPost

```
public Void deleteByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByUUID

```
public Void deleteByUUID(CaseServiceDeleteByUUID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResources

```
public Void deleteResources(CaseServiceDeleteResources value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resources of the type S from the database. Note that **nulls** in the list are not allowed

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIds

```
public CaseServiceFindAllIdsResponse findAllIds(String authToken,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resourcefindAllIds IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIdsPost

```
public CaseServiceFindAllIdsResponse findAllIdsPost(String authToken,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resourcefindAllIds IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findAllIds

```
public CaseServiceFindAllIdsResponse findAllIds(CaseServiceFindAllIds value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllAttachmentOnlyResourceIDs

```
public CaseServiceGetAllAttachmentOnlyResourceIDsResponse
getAllAttachmentOnlyResourceIDs(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDsPost

```
public CaseServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDs

```
public CaseServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(CaseServiceGetAllAttachmentOnlyResourceIDs value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

value - Model object containing request body

Returns:

The list of the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllowedUserTypes

```
public CaseServiceGetAllowedUserTypesResponse getAllowedUserTypes(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllowedUserTypesPost

```
public CaseServiceGetAllowedUserTypesResponse getAllowedUserTypesPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllowedUserTypes

```
public CaseServiceGetAllowedUserTypesResponse  
getAllowedUserTypes(CaseServiceGetAllowedUserTypes value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

value - Model object containing request body

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRoot

```
public CaseServiceGetAllPathsToRootResponse getAllPathsToRoot(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/O5CxZ+EUBABCA5fiIDvOvLA==/ObdhibUYBABCAR4Qqlpgzcw=="

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootPost

```
public CaseServiceGetAllPathsToRootResponse getAllPathsToRootPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/O5CxZ+EUBABCA5fiIDvOvLA==/ObdhibUYBABCAR4Qqlpgzcw=="

Parameters:

resourceId - The ID of the resource

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRoot

```
public CaseServiceGetAllPathsToRootResponse  
getAllPathsToRoot(CaseServiceGetAllPathsToRoot value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFqIR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/ObdhibUYBABCAR4Qqlpgzcw=="

Parameters:

value - Model object containing request body

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStrings

```
public CaseServiceGetAllPathsToRootAsStringsResponse getAllPathsToRootAsStrings(String  
authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID resourceId to the root. Since resource could belong to different groups, there could be more than one path. A path could look like "/All Cases/All Cases/Personal Cases/admin's Cases".

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStringsPost

```
public CaseServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStringsPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRootAsStrings

```
public CaseServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStrings(CaseServiceGetAllPathsToRootAsStrings value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`value` - Model object containing request body

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllUnassignedResourceIDs

```
public CaseServiceGetAllUnassignedResourceIDsResponse getAllUnassignedResourceIDs(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDsPost

```
public CaseServiceGetAllUnassignedResourceIDsResponse getAllUnassignedResourceIDsPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDs

```
public CaseServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDs(CaseServiceGetAllUnassignedResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getChildNamesAndAliases

```
public CaseServiceGetChildNamesAndAliasesResponse  
getChildNamesAndAliases(CaseServiceGetChildNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. This method is left for backward compatibility only. Please rather use method [getNamesAndAliases\(List\)](#)

Returns the names and aliases of all of the resources with ID specified in childIds. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources.

The size of the returned list will always be $2 * n$ where n is the size of the childIds list. It is possible for some of the names to be missing, in which case **null** values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getNamesAndAliases

```
public CaseServiceGetNamesAndAliasesResponse  
getNamesAndAliases(CaseServiceGetNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources. The size of the returned list will always be 2 * n where n is the number of specified resource ID. It is possible for some of the names to be missing, in which case null values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResources

```
public CaseServiceGetCorruptedResourcesResponse getCorruptedResources(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, null is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResourcesPost

```
public CaseServiceGetCorruptedResourcesResponse getCorruptedResourcesPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCorruptedResources

```
public CaseServiceGetCorruptedResourcesResponse  
getCorruptedResources(CaseServiceGetCorruptedResources value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

value - Model object containing request body

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceId

```
public CaseServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceIdPost

```
public CaseServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceIdPost(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getDependentResourceIdsForResourceId

```
public CaseServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(CaseServiceGetDependentResourceIdsForResourceId  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getRelationshipsOfThisAndParents

```
public CaseServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getRelationshipsOfParents(String, int)`
`getReverseRelationshipsOfThisAndParents(String, int)`
`getReverseRelationshipsOfParents(String, int)`

getRelationshipsOfThisAndParentsPost

```
public CaseServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`getRelationshipsOfParents(String, int)`

```
getReverseRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfParents(String, int)
```

getRelationshipsOfThisAndParents

```
public CaseServiceGetRelationshipsOfThisAndParentsResponse
getRelationshipsOfThisAndParents(CaseServiceGetRelationshipsOfThisAndParents value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`value` - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getRelationshipsOfParents(String, int)`
`getReverseRelationshipsOfThisAndParents(String, int)`
`getReverseRelationshipsOfParents(String, int)`

getRelationshipsOfParents

```
public CaseServiceGetRelationshipsOfParentsResponse getRelationshipsOfParents(String
authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParentsPost

```
public CaseServiceGetRelationshipsOfParentsResponse getRelationshipsOfParentsPost(String authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParents

```
public CaseServiceGetRelationshipsOfParentsResponse
getRelationshipsOfParents(CaseServiceGetRelationshipsOfParents value)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public CaseServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParentsPost

```
public CaseServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public CaseServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(CaseServiceGetReverseRelationshipsOfThisAndParent  
    S value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public CaseServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParentsPost

```
public CaseServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public CaseServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(CaseServiceGetReverseRelationshipsOfParents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

value - Model object containing request body

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getEnabledResourceIDs

```
public CaseServiceGetEnabledResourceIDsResponse  
getEnabledResourceIDs(CaseServiceGetEnabledResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Checks the specified resources and returns the list of IDs of the resources that are enabled. The returned list is a subset of resourceIds. If all the specified resources are disabled then the method returns an empty list.

Parameters:

value - Model object containing request body

Returns:

The IDs of enabled resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getExclusivelyDependentResources

```
public CaseServiceGetExclusivelyDependentResourcesResponse  
getExclusivelyDependentResources(CaseServiceGetExclusivelyDependentResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resources depending on the given resource of the type S. This means that the given resource is the only path to root for those resources.

Parameters:

value - Model object containing request body

Returns:

List of resources that depend on the specified resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupID

```
public CaseServiceGetMetaGroupIDResponse getMetaGroupID(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupIDPost

```
public CaseServiceGetMetaGroupIDResponse getMetaGroupIDPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getMetaGroupID

```
public CaseServiceGetMetaGroupIDResponse getMetaGroupID(CaseServiceGetMetaGroupID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRoots

```
public CaseServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRootsPost

```
public CaseServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRootsPost(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalAndSharedResourceRoots

```
public CaseServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(CaseServiceGetPersonalAndSharedResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

value - Model object containing request body

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroup

```
public CaseServiceGetPersonalGroupResponse getPersonalGroup(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

userId - The resource ID of the user
throwOnMissing - Whether or not an exception must be thrown if such a group is not found
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroupPost

```
public CaseServiceGetPersonalGroupResponse getPersonalGroupPost(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

`userId` - The resource ID of the user
`throwOnMissing` - Whether or not an exception must be thrown if such a group is not found
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalGroup

```
public CaseServiceGetPersonalGroupResponse getPersonalGroup(CaseServiceGetPersonalGroup  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

`value` - Model object containing request body

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRoots

```
public CaseServiceGetPersonalResourceRootsResponse getPersonalResourceRoots(String
authToken,
    String resourceId,
    int relationshipType,
    int resourceType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#)
Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

resourceId - The ID of the resource used as source in relations
relationshipType - The relationship type of the targets to the given resource
resourceType - NOT USED. The parameter is left for backward compatibility
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRootsPost

```
public CaseServiceGetPersonalResourceRootsResponse getPersonalResourceRootsPost(String
authToken,
    String resourceId,
    int relationshipType,
    int resourceType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

resourceId - The ID of the resource used as source in relations
relationshipType - The relationship type of the targets to the given resource
resourceType - NOT USED. The parameter is left for backward compatibility
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalResourceRoots

```
public CaseServiceGetPersonalResourceRootsResponse  
getPersonalResourceRoots(CaseServiceGetPersonalResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

value - Model object containing request body

Returns:

The list of target resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesReferencePages

```
public CaseServiceGetResourcesReferencePagesResponse  
getResourcesReferencePages(CaseServiceGetResourcesReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resources identified by the IDs.

Parameters:

value - Model object containing request body

Returns:

A list of reference pages for the resources identified by the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePages

```
public CaseServiceGetReferencePagesResponse getReferencePages(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePagesPost

```
public CaseServiceGetReferencePagesResponse getReferencePagesPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getReferencePages

```
public CaseServiceGetReferencePagesResponse  
getReferencePages(CaseServiceGetReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

value - Model object containing request body

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByName

```
public CaseServiceGetResourceByNameResponse getResourceByName(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByNamePost

```
public CaseServiceGetResourceByNameResponse getResourceByNamePost(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceByName

```
public CaseServiceGetResourceByNameResponse  
getResourceByName(CaseServiceGetResourceByName value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

value - Model object containing request body

Returns:

The resource identified by the name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNames

```
public CaseServiceGetResourcesByNamesResponse  
getResourcesByNames(CaseServiceGetResourcesByNames value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified names. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.
If parameter names contains only one name, then the returned collection would contain all resources which have that name.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of names

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByIds

```
public CaseServiceGetResourcesByIdsResponse  
getResourcesByIds(CaseServiceGetResourcesByIds value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resources of the type S identified by the specified resource IDs. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafely

```
public CaseServiceGetResourcesByNameSafelyResponse getResourcesByNameSafely(String  
    authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```


Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafelyPost

```
public CaseServiceGetResourcesByNameSafelyResponse getResourcesByNameSafelyPost(String  
authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourcesByNameSafely

```
public CaseServiceGetResourcesByNameSafelyResponse  
getResourcesByNameSafely(CaseServiceGetResourcesByNameSafely value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

value - Model object containing request body

Returns:

The resources with the specified name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermission

```
public CaseServiceHasReadPermissionResponse hasReadPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermissionPost

```
public CaseServiceHasReadPermissionResponse hasReadPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.

targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasReadPermission

```
public CaseServiceHasReadPermissionResponse  
hasReadPermission(CaseServiceHasReadPermission value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermission

```
public CaseServiceHasWritePermissionResponse hasWritePermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermissionPost

```
public CaseServiceHasWritePermissionResponse hasWritePermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasWritePermission

```
public CaseServiceHasWritePermissionResponse  
hasWritePermission(CaseServiceHasWritePermission value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermission

```
public CaseServiceHasXPermissionResponse hasXPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermissionPost

```
public CaseServiceHasXPermissionResponse hasXPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasXPermission

```
public CaseServiceHasXPermissionResponse hasXPermission(CaseServiceHasXPermission value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabled

```
public CaseServiceIsDisabledResponse isDisabled(String authToken,
        String resourceId,
        javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabledPost

```
public CaseServiceIsDisabledResponse isDisabledPost(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isDisabled

```
public CaseServiceIsDisabledResponse isDisabled(CaseServiceIsDisabled value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceID

```
public CaseServiceIsValidResourceIDResponse isValidResourceID(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceIDPost

```
public CaseServiceIsValidResourceIDResponse isValidResourceIDPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isValidResourceID

```
public CaseServiceIsValidResourceIDResponse  
isValidResourceID(CaseServiceIsValidResourceID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

value - Model object containing request body

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

loadAdditional

```
public Void loadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

loadAdditionalPost

```
public Void loadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[unloadAdditional\(String\)](#)

loadAdditional

```
public Void loadAdditional(CaseServiceLoadAdditional value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

resetState

```
public Void resetState(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resetStatePost

```
public Void resetStatePost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

resetState

```
public Void resetState(CaseServiceResetState value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resolveRelationship

```
public CaseServiceResolveRelationshipResponse resolveRelationship(String authToken,
    String sourceId,
    String targetId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource

targetId - The ID of the target resource

relationshipType - The relationship type

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

resolveRelationshipPost

```
public CaseServiceResolveRelationshipResponse resolveRelationshipPost(String authToken,  
    String sourceId,  
    String targetId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

resolveRelationship

```
public CaseServiceResolveRelationshipResponse  
resolveRelationship(CaseServiceResolveRelationship value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

unloadAdditional

```
public Void unloadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

unloadAdditionalPost

```
public Void unloadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`loadAdditional(String)`

unloadAdditional

```
public Void unloadAdditional(CaseServiceUnloadAdditional value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

updateResources

```
public CaseServiceUpdateResourcesResponse updateResources(CaseServiceUpdateResources
value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Updates the resources of the type S in the database. Resources are updated in different transactions. Method tries to update as many resources as possible. For all resources that failed to be updated error messages are logged on the server. Failed resources are not included in the returned collection. If the response does not include some of the submitted resources, then check server log-messages to find out why the update failed for them.

Parameters:

value - Model object containing request body

Returns:

The list of successfully updated resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceIfModified

```
public CaseServiceGetResourceIfModifiedResponse
getResourceIfModified(CaseServiceGetResourceIfModified value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource if it is newer than the signature specifies; otherwise returns **null**.

Parameters:

value - Model object containing request body

Returns:

The resource with the specified ID if its modification count is bigger than the one in the signature; **null** otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceSignature](#)

getTargetsByRelationshipCount

```
public CaseServiceGetTargetsByRelationshipCountResponse  
getTargetsByRelationshipCount(CaseServiceGetTargetsByRelationshipCount value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationship

```
public CaseServiceGetTargetsByRelationshipResponse  
getTargetsByRelationship(CaseServiceGetTargetsByRelationship value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

hasReverseRelationship

```
public CaseServiceHasReverseRelationshipResponse  
hasReverseRelationship(CaseServiceHasReverseRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the relationship of the given target and source exists.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the given target and source exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipCount

```
public CaseServiceGetSourcesWithThisTargetByRelationshipCountResponse  
getSourcesWithThisTargetByRelationshipCount(CaseServiceGetSourcesWithThisTargetByRelation  
shipCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationship

```
public CaseServiceGetSourcesWithThisTargetByRelationshipResponse  
getSourcesWithThisTargetByRelationship(CaseServiceGetSourcesWithThisTargetByRelationship  
value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationship

```
public CaseServiceGetTargetsAsURIByRelationshipResponse  
getTargetsAsURIByRelationship(CaseServiceGetTargetsAsURIByRelationship value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnship

```
public CaseServiceGetSourceURIWithThisTargetByRelatiobnshipResponse  
getSourceURIWithThisTargetByRelatiobnship(CaseServiceGetSourceURIWithThisTargetByRelatiobnship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationship(S, int)`.*

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationship

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipResponse  
getSourceURIWithThisTargetByRelationship(CaseServiceGetSourceURIWithThisTargetByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource URIs for all enabled resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public CaseServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceIdPost

```
public CaseServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public CaseServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(CaseServiceGetTargetsByRelationshipForSourceId value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceIdPost

```
public CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceIdPost(String authToken,  
        String sourceResourceId,  
        int relationshipType,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public CaseServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(CaseServiceGetTargetsAsURIByRelationshipForSourceId  
value)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceIdPost

```
public CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public CaseServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(CaseServiceGetSourcesWithThisTargetByRelationshipForResourceId value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelatiobnshipForResourceIdPost

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourceURIWithThisTargetByRelatiobnshipForResourceId

```
public CaseServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceId(CaseServiceGetSourceURIWithThisTar  
getByRelatiobnshipForResourceId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationshipForResourceId

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

getSourceURIWithThisTargetByRelationshipForResourceIdPost

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public CaseServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(CaseServiceGetSourceURIWithThisTarg  
etByRelationshipForResourceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByACLRelationship

```
public CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(String authToken,  
    String sourceResourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourcesWithThisTargetByACLRelationshipPost

```
public CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationshipPost(String authToken,  
    String sourceResourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourcesWithThisTargetByACLRelationship

```
public CaseServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(CaseServiceGetSourcesWithThisTargetByACLRelationship  
value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResource

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceResponse  
getTargetsWithRelationshipTypeForResource(CaseServiceGetTargetsWithRelationshipTypeForResource  
value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceById

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(String authToken,  
String resourceId,  
java.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceByIdPost

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceByIdPost(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getTargetsWithRelationshipTypeForResourceById

```
public CaseServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(CaseServiceGetTargetsWithRelationshipTypeFo  
rResourceById value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateACLForResourceById

```
public Void updateACLForResourceById(CaseServiceUpdateACLForResourceById value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder. For every element from data, the method adds, removes, or updates the relationship between the resource and another resource with ID specified in ACLDataHolder.id. Every ACLDataHolder element also specifies whether it's for source or for target relationship ("forSourceRelationship"), identifier of the resource ("id"), and update type ("updateType"). The request is performed in a single transaction. If any of relations cannot be changed, then the entire transaction fails.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesWithVisibilityToUsers

```
public CaseServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsersPost

```
public CaseServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsers

```
public CaseServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(CaseServiceGetResourcesWithVisibilityToUsers value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public CaseServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsersPost

```
public CaseServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public CaseServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(CaseServiceGetResourceTypesVisibleToUsers value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceById

```
public CaseServiceGetResourceByIdResponse getResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByIdPost

```
public CaseServiceGetResourceByIdResponse getResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceById

```
public CaseServiceGetResourceByIdResponse getResourceById(CaseServiceGetResourceById  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

value - Model object containing request body

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addRelationship

```
public CaseServiceAddRelationshipResponse addRelationship(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type relationshipType between specified target and source resources. There are no additional requirements on the types of the resources identified by sourceResourceId and targetResourceId.

Parameters:

sourceResourceId - The ID of the source resource
targetResourceId - The ID of the target resource
relationshipType - The type of the relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

addRelationshipPost

```
public CaseServiceAddRelationshipResponse addRelationshipPost(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type relationshipType between specified target and source resources. There are no additional requirements on the types of the resources identified by sourceResourceId and targetResourceId.

Parameters:

sourceResourceId - The ID of the source resource
targetResourceId - The ID of the target resource
relationshipType - The type of the relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

addRelationship

```
public CaseServiceAddRelationshipResponse addRelationship(CaseServiceAddRelationship  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`value` - Model object containing request body

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getESMVersion

```
public CaseServiceGetESMVersionResponse getESMVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getESMVersionPost

```
public CaseServiceGetESMVersionResponse getESMVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getESMVersion

```
public CaseServiceGetESMVersionResponse getESMVersion(CaseServiceGetESMVersion value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

value - Model object containing request body

Returns:

Version of ESM

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersion

```
public CaseServiceGetServiceMajorVersionResponse getServiceMajorVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersionPost

```
public CaseServiceGetServiceMajorVersionResponse getServiceMajorVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMajorVersion

```
public CaseServiceGetServiceMajorVersionResponse  
getServiceMajorVersion(CaseServiceGetServiceMajorVersion value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The major version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersion

```
public CaseServiceGetServiceMinorVersionResponse getServiceMinorVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersionPost

```
public CaseServiceGetServiceMinorVersionResponse getServiceMinorVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMinorVersion

```
public CaseServiceGetServiceMinorVersionResponse  
getServiceMinorVersion(CaseServiceGetServiceMinorVersion value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The minor version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

com.arcsight.product.manager.resource.service.v1.rest Class GroupServiceImpl

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.rest.GroupServiceImpl

public class **GroupServiceImpl**
extends Object

Implementation of GroupService to access Group resources.

Constructor Summary

public	GroupServiceImpl()

Method Summary

Void	addChild (GroupServiceAddChild value) Adds a child to the group specified by groupId.
Void	addChild (String authToken, String groupId, String childId, javax.ws.rs.core.HttpHeaders hh) Adds a child to the group specified by groupId.
Void	addChildPost (String authToken, String groupId, String childId, javax.ws.rs.core.HttpHeaders hh) Adds a child to the group specified by groupId.
Void	addChildren (GroupServiceAddChildren value) Adds a list of children to the group specified by groupId.
GroupServiceAddRelationshipResponse	addRelationship (GroupServiceAddRelationship value) Adds the relationship of the type relationshipType between specified target and source resources.
GroupServiceAddRelationshipResponse	addRelationship (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
GroupServiceAddRelationshipResponse	addRelationshipPost (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
Void	childAttributesChanged (GroupServiceChildAttributesChanged value) Notifies the specified group that the name (or alias) of the given resource child may have changed.

GroupServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (GroupServiceContainsDirectMemberByNameOrAlias value) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
GroupServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
GroupServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAliasPost (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
GroupServiceContainsResourcesRecursivelyResponse	containsResourcesRecursively (GroupServiceContainsResourcesRecursively value) Checks whether this group or any of its subgroups contains any resource of the given type.
GroupServiceContainsResourcesRecursivelyResponse	containsResourcesRecursively (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Checks whether this group or any of its subgroups contains any resource of the given type.
GroupServiceContainsResourcesRecursivelyResponse	containsResourcesRecursivelyPost (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Checks whether this group or any of its subgroups contains any resource of the given type.
GroupServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (GroupServiceCopyResourceIntoGroup value) Creates a copy of the given resource of type S and inserts that resource into the given target group.
GroupServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
GroupServiceCopyResourceIntoGroupResponse	copyResourceIntoGroupPost (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
Void	delete (GroupServiceDelete value) Deletes the resource of the type S from the database.
Void	deleteByLocalId (GroupServiceDeleteByLocalId value) Deletes the resource identified by the local ID.
Void	deleteByLocalId (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByLocalIdPost (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByUUID (GroupServiceDeleteByUUID value) Deletes the resource identified by the ID.

Void	<u>deleteByUUID</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	<u>deleteByUUIDPost</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	<u>deleteResource</u> (<u>GroupServiceDeleteResource</u> value) Deletes the resource of the type S from the database.
Void	<u>deleteResources</u> (<u>GroupServiceDeleteResources</u> value) Deletes the resources of the type S from the database.
<u>GroupServiceFindAllIdsResponse</u>	<u>findAllIds</u> (<u>GroupServiceFindAllIds</u> value) Finds and returns the list of IDs of all the resources of type S.
<u>GroupServiceFindAllIdsResponse</u>	<u>findAllIds</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
<u>GroupServiceFindAllIdsResponse</u>	<u>findAllIdsPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
<u>GroupServiceFindByIdResponse</u>	<u>findById</u> (<u>GroupServiceFindById</u> value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>GroupServiceFindByIdResponse</u>	<u>findById</u> (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>GroupServiceFindByIdResponse</u>	<u>findByIdPost</u> (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
<u>GroupServiceFindByUUIDResponse</u>	<u>findByIdUUID</u> (<u>GroupServiceFindByUUID</u> value) Returns the resource of the type S identified by its ID.
<u>GroupServiceFindByUUIDResponse</u>	<u>findByIdUUID</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
<u>GroupServiceFindByUUIDResponse</u>	<u>findByIdUUIDPost</u> (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
<u>GroupServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDs</u> (<u>GroupServiceGetAllAttachmentOnlyResourceIDs</u> value) Returns a list of the IDs of all attachments of the type S.
<u>GroupServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDs</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
<u>GroupServiceGetAllAttachmentOnlyResourceIDsResponse</u>	<u>getAllAttachmentOnlyResourceIDsPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
<u>GroupServiceGetAllChildIDCountResponse</u>	<u>getAllChildIDCount</u> (<u>GroupServiceGetAllChildIDCount</u> value) Returns the number of all children for this specified group.

<u>GroupServiceGetAllChildIDCountResponse</u>	<u>getAllChildIDCount</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the number of all children for this specified group.
<u>GroupServiceGetAllChildIDCountResponse</u>	<u>getAllChildIDCountPost</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the number of all children for this specified group.
<u>GroupServiceGetAllChildIDsResponse</u>	<u>getAllChildIDs</u> (<u>GroupServiceGetAllChildIDs</u> value) Returns a list of the IDs of all children for the specified group.
<u>GroupServiceGetAllChildIDsResponse</u>	<u>getAllChildIDs</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all children for the specified group.
<u>GroupServiceGetAllChildIDsResponse</u>	<u>getAllChildIDsPost</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all children for the specified group.
<u>GroupServiceGetAllChildrenResponse</u>	<u>getAllChildren</u> (<u>GroupServiceGetAllChildren</u> value) Returns a list of all of the resource children of this specified group.
<u>GroupServiceGetAllChildrenResponse</u>	<u>getAllChildren</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all of the resource children of this specified group.
<u>GroupServiceGetAllChildrenResponse</u>	<u>getAllChildrenPost</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all of the resource children of this specified group.
<u>GroupServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypes</u> (<u>GroupServiceGetAllowedUserTypes</u> value) Returns the array of user types that are allowed to access the service.
<u>GroupServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypes</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
<u>GroupServiceGetAllowedUserTypesResponse</u>	<u>getAllowedUserTypesPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
<u>GroupServiceGetAllPathsToRootResponse</u>	<u>getAllPathsToRoot</u> (<u>GroupServiceGetAllPathsToRoot</u> value) Returns a list of all the paths to root relevant to the service for the given resource.
<u>GroupServiceGetAllPathsToRootResponse</u>	<u>getAllPathsToRoot</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
<u>GroupServiceGetAllPathsToRootAsStringsResponse</u>	<u>getAllPathsToRootAsStrings</u> (<u>GroupServiceGetAllPathsToRootAsStrings</u> value) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
<u>GroupServiceGetAllPathsToRootAsStringsResponse</u>	<u>getAllPathsToRootAsStrings</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.

GroupServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStringsPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
GroupServiceGetAllPathsToRootResponse	getAllPathsToRootPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
GroupServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (GroupServiceGetAllUnassignedResourceIDs value) Returns a list of the IDs of all unassigned resources of the type S.
GroupServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
GroupServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
GroupServiceGetChildIDByChildNameOrAliasResponse	getChildIDByChildNameOrAlias (GroupServiceGetChildIDByChildNameOrAlias value) Returns the resource ID of the child in this group with the given name or alias.
GroupServiceGetChildIDByChildNameOrAliasResponse	getChildIDByChildNameOrAlias (String authToken, String groupId, String alias, String name, javax.ws.rs.core.HttpHeaders hh) Returns the resource ID of the child in this group with the given name or alias.
GroupServiceGetChildIDByChildNameOrAliasResponse	getChildIDByChildNameOrAliasPost (String authToken, String groupId, String alias, String name, javax.ws.rs.core.HttpHeaders hh) Returns the resource ID of the child in this group with the given name or alias.
GroupServiceGetChildNamesAndAliasesResponse	getChildNamesAndAliases (GroupServiceGetChildNamesAndAliases value) Deprecated. <i>This method is left for backward compatibility only. Please rather use method getNamesAndAliases(List)</i>
GroupServiceGetChildrenByTypeResponse	getChildrenByType (GroupServiceGetChildrenByType value) Returns a list of IDs of all children of the specified type.
GroupServiceGetChildrenByTypeResponse	getChildrenByType (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all children of the specified type.
GroupServiceGetChildrenByTypeResponse	getChildrenByTypePost (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all children of the specified type.
GroupServiceGetChildResourcesByTypeResponse	getChildResourcesByType (GroupServiceGetChildResourcesByType value) Return a list of resources based on the type of child required.
GroupServiceGetChildResourcesByTypeResponse	getChildResourcesByType (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Return a list of resources based on the type of child required.
GroupServiceGetChildResourcesByTypeResponse	getChildResourcesByTypePost (String authToken, String groupId, int resourceType, javax.ws.rs.core.HttpHeaders hh) Return a list of resources based on the type of child required.

<u>GroupServiceGetCorruptedResourcesResponse</u>	<u>getCorruptedResources</u> (<u>GroupServiceGetCorruptedResources</u> value) Returns the list of descriptors for all the corrupted resources of the corresponding type.
<u>GroupServiceGetCorruptedResourcesResponse</u>	<u>getCorruptedResources</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
<u>GroupServiceGetCorruptedResourcesResponse</u>	<u>getCorruptedResourcesPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
<u>GroupServiceGetDependentResourceIDsForResourceIdResponse</u>	<u>getDependentResourceIDsForResourceId</u> (<u>GroupServiceGetDependentResourceIDsForResourceId</u> value) Returns the list of the IDs of dependent resources for the specified resource of the type S.
<u>GroupServiceGetDependentResourceIDsForResourceIdResponse</u>	<u>getDependentResourceIDsForResourceId</u> (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
<u>GroupServiceGetDependentResourceIDsForResourceIdResponse</u>	<u>getDependentResourceIDsForResourceIdPost</u> (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
<u>GroupServiceGetEnabledResourceIDsResponse</u>	<u>getEnabledResourceIDs</u> (<u>GroupServiceGetEnabledResourceIDs</u> value) Checks the specified resources and returns the list of IDs of the resources that are enabled.
<u>GroupServiceGetESMVersionResponse</u>	<u>getESMVersion</u> (<u>GroupServiceGetESMVersion</u> value) Returns the version of ESM manager.
<u>GroupServiceGetESMVersionResponse</u>	<u>getESMVersion</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
<u>GroupServiceGetESMVersionResponse</u>	<u>getESMVersionPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
<u>GroupServiceGetExclusivelyDependentResourcesResponse</u>	<u>getExclusivelyDependentResources</u> (<u>GroupServiceGetExclusivelyDependentResources</u> value) Returns a list of resources depending on the given resource of the type S.
<u>GroupServiceGetGroupByIDResponse</u>	<u>getGroupByID</u> (<u>GroupServiceGetGroupByID</u> value) Returns the group specified by the groupId.
<u>GroupServiceGetGroupByIDResponse</u>	<u>getGroupByID</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the group specified by the groupId.
<u>GroupServiceGetGroupByIDResponse</u>	<u>getGroupByIDPost</u> (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the group specified by the groupId.
<u>GroupServiceGetGroupByURIResponse</u>	<u>getGroupByURI</u> (<u>GroupServiceGetGroupByURI</u> value) Returns the group specified by the URI.
<u>GroupServiceGetGroupByURIResponse</u>	<u>getGroupByURI</u> (String authToken, String uri, javax.ws.rs.core.HttpHeaders hh) Returns the group specified by the URI.

GroupServiceGetGroupByURIResponse	getGroupByURIPost (String authToken, String uri, javax.ws.rs.core.HttpHeaders hh) Returns the group specified by the URI.
GroupServiceGetGroupChildCountResponse	getGroupChildCount (GroupServiceGetGroupChildCount value) Returns the number of displayable children for the given group.
GroupServiceGetGroupChildCountResponse	getGroupChildCount (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the number of displayable children for the given group.
GroupServiceGetGroupChildCountResponse	getGroupChildCountPost (String authToken, String groupId, javax.ws.rs.core.HttpHeaders hh) Returns the number of displayable children for the given group.
GroupServiceGetMetaGroupResponse	getMetaGroup (GroupServiceGetMetaGroup value) Get the meta group of this resource type.
GroupServiceGetMetaGroupResponse	getMetaGroup (String authToken, int resourceType, javax.ws.rs.core.HttpHeaders hh) Get the meta group of this resource type.
GroupServiceGetMetaGroupIDResponse	getMetaGroupID (GroupServiceGetMetaGroupID value) Returns the string value of ID of the meta group for the resources of type S.
GroupServiceGetMetaGroupIDResponse	getMetaGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
GroupServiceGetMetaGroupIDResponse	getMetaGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
GroupServiceGetMetaGroupResponse	getMetaGroupPost (String authToken, int resourceType, javax.ws.rs.core.HttpHeaders hh) Get the meta group of this resource type.
GroupServiceGetNamesAndAliasesResponse	getNamesAndAliases (GroupServiceGetNamesAndAliases value) Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds.
GroupServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (GroupServiceGetPersonalAndSharedResourceRoots value) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
GroupServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
GroupServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRootsPost (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
GroupServiceGetPersonalGroupResponse	getPersonalGroup (GroupServiceGetPersonalGroup value) Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.

GroupServiceGetPersonalGroupResponse	getPersonalGroup (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.
GroupServiceGetPersonalGroupResponse	getPersonalGroupPost (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.
GroupServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (GroupServiceGetPersonalResourceRoots value) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
GroupServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
GroupServiceGetPersonalResourceRootsResponse	getPersonalResourceRootsPost (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
GroupServiceGetReferencePagesResponse	getReferencePages (GroupServiceGetReferencePages value) Returns the list of reference pages for the resource identified by the ID.
GroupServiceGetReferencePagesResponse	getReferencePages (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
GroupServiceGetReferencePagesResponse	getReferencePagesPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
GroupServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (GroupServiceGetRelationshipsOfParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
GroupServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
GroupServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
GroupServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (GroupServiceGetRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
GroupServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.

GroupServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
GroupServiceGetResourceByIdResponse	getResourceById (GroupServiceGetResourceById value) Returns the resource of the type S specified by resource ID.
GroupServiceGetResourceByIdResponse	getResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
GroupServiceGetResourceByIdResponse	getResourceByIdPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
GroupServiceGetResourceByNameResponse	getResourceByName (GroupServiceGetResourceByName value) Returns one of the resources of the type S with the specified name.
GroupServiceGetResourceByNameResponse	getResourceByName (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
GroupServiceGetResourceByNameResponse	getResourceByNamePost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
GroupServiceGetResourceIfModifiedResponse	getResourceIfModified (GroupServiceGetResourceIfModified value) Returns the resource if it is newer than the signature specifies; otherwise returns null .
GroupServiceGetResourcesByIdsResponse	getResourcesByIds (GroupServiceGetResourcesByIds value) Returns the resources of the type S identified by the specified resource IDs.
GroupServiceGetResourcesByNamesResponse	getResourcesByNames (GroupServiceGetResourcesByNames value) Returns all the resources of the type S with the specified names.
GroupServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (GroupServiceGetResourcesByNameSafely value) Returns all the resources of the type S with the specified name.
GroupServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
GroupServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafelyPost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
GroupServiceGetResourcesReferencePagesResponse	getResourcesReferencePages (GroupServiceGetResourcesReferencePages value) Returns the list of reference pages for the resources identified by the IDs.
GroupServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsers (GroupServiceGetResourcesWithVisibilityToUsers value) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).

<u>GroupServiceGetResourcesWithVisibilityToUsersResponse</u>	<u>getResourcesWithVisibilityToUsers</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>GroupServiceGetResourcesWithVisibilityToUsersResponse</u>	<u>getResourcesWithVisibilityToUsersPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>GroupServiceGetResourceTypesVisibleToUsersResponse</u>	<u>getResourceTypesVisibleToUsers</u> (<u>GroupServiceGetResourceTypesVisibleToUsers</u> value) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>GroupServiceGetResourceTypesVisibleToUsersResponse</u>	<u>getResourceTypesVisibleToUsers</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>GroupServiceGetResourceTypesVisibleToUsersResponse</u>	<u>getResourceTypesVisibleToUsersPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>GroupServiceGetReverseRelationshipsOfParentsResponse</u>	<u>getReverseRelationshipsOfParents</u> (<u>GroupServiceGetReverseRelationshipsOfParents</u> value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
<u>GroupServiceGetReverseRelationshipsOfParentsResponse</u>	<u>getReverseRelationshipsOfParents</u> (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
<u>GroupServiceGetReverseRelationshipsOfParentsResponse</u>	<u>getReverseRelationshipsOfParentsPost</u> (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
<u>GroupServiceGetReverseRelationshipsOfThisAndParentsResponse</u>	<u>getReverseRelationshipsOfThisAndParents</u> (<u>GroupServiceGetReverseRelationshipsOfThisAndParents</u> value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
<u>GroupServiceGetReverseRelationshipsOfThisAndParentsResponse</u>	<u>getReverseRelationshipsOfThisAndParents</u> (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
<u>GroupServiceGetReverseRelationshipsOfThisAndParentsResponse</u>	<u>getReverseRelationshipsOfThisAndParentsPost</u> (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
<u>GroupServiceGetServiceMajorVersionResponse</u>	<u>getServiceMajorVersion</u> (<u>GroupServiceGetServiceMajorVersion</u> value) The major version of this service.

GroupServiceGetServiceMajorVersionResponse	getServiceMajorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
GroupServiceGetServiceMajorVersionResponse	getServiceMajorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
GroupServiceGetServiceMinorVersionResponse	getServiceMinorVersion (GroupServiceGetServiceMinorVersion value) The minor version of this service.
GroupServiceGetServiceMinorVersionResponse	getServiceMinorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
GroupServiceGetServiceMinorVersionResponse	getServiceMinorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
GroupServiceGetSourceWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (GroupServiceGetSourcesWithThisTargetByACLRelationship value) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationshipPost (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByRelationshipResponse	getSourcesWithThisTargetByRelationship (GroupServiceGetSourcesWithThisTargetByRelationship value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByRelationshipCountResponse	getSourcesWithThisTargetByRelationshipCount (GroupServiceGetSourcesWithThisTargetByRelationshipCount value) Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (GroupServiceGetSourceWithThisTargetByRelationshipForResourceId value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

GroupServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship(GroupServiceGetSourceURIWithThisTargetByRelationship value) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationship(S, int)</code> .
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId(GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId(String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .
GroupServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship(GroupServiceGetSourceURIWithThisTargetByRelationship value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId(GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId(String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
GroupServiceGetTargetAsURIByRelationshipResponse	getTargetsAsURIByRelationship(GroupServiceGetTargetsAsURIByRelationship value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.
GroupServiceGetTargetAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId(GroupServiceGetTargetsAsURIByRelationshipForSourceId value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
GroupServiceGetTargetAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId(String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.

<u>GroupServiceGetTargetAsURIByRelationshipForSourceIdResponse</u>	<u>getTargetsAsURIByRelationshipForSourceIdPost</u> (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
<u>GroupServiceGetTargetSByRelationshipResponse</u>	<u>getTargetsByRelationship</u> (<u>GroupServiceGetTargetsByRelationship</u> value) Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.
<u>GroupServiceGetTargetSByRelationshipCountResponse</u>	<u>getTargetsByRelationshipCount</u> (<u>GroupServiceGetTargetsByRelationshipCount</u> value) Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.
<u>GroupServiceGetTargetSByRelationshipForSourceIdResponse</u>	<u>getTargetsByRelationshipForSourceId</u> (<u>GroupServiceGetTargetsByRelationshipForSourceId</u> value) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
<u>GroupServiceGetTargetSByRelationshipForSourceIdResponse</u>	<u>getTargetsByRelationshipForSourceId</u> (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
<u>GroupServiceGetTargetSByRelationshipForSourceIdResponse</u>	<u>getTargetsByRelationshipForSourceIdPost</u> (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
<u>GroupServiceGetTargetSWithRelationshipTypeForResourceResponse</u>	<u>getTargetsWithRelationshipTypeForResource</u> (<u>GroupServiceGetTargetsWithRelationshipTypeForResource</u> value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.
<u>GroupServiceGetTargetSWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceById</u> (<u>GroupServiceGetTargetsWithRelationshipTypeForResourceById</u> value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>GroupServiceGetTargetSWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceById</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>GroupServiceGetTargetSWithRelationshipTypeForResourceByIdResponse</u>	<u>getTargetsWithRelationshipTypeForResourceByIdPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
<u>GroupServiceHasChildWith NameOrAliasResponse</u>	<u>hasChildWithNameOrAlias</u> (<u>GroupServiceHasChildWithNameOrAlias</u> value) Returns whether this group contains a child with the given name or alias.
<u>GroupServiceHasChildWith NameOrAliasResponse</u>	<u>hasChildWithNameOrAlias</u> (String authToken, String groupId, String alias, String name, javax.ws.rs.core.HttpHeaders hh) Returns whether this group contains a child with the given name or alias.
<u>GroupServiceHasChildWith NameOrAliasResponse</u>	<u>hasChildWithNameOrAliasPost</u> (String authToken, String groupId, String alias, String name, javax.ws.rs.core.HttpHeaders hh) Returns whether this group contains a child with the given name or alias.

<u>GroupServiceHasReadPermissionResponse</u>	<u>hasReadPermission</u> (<u>GroupServiceHasReadPermission</u> value) Returns true if the source resource has Read permission on the target resource.
<u>GroupServiceHasReadPermissionResponse</u>	<u>hasReadPermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
<u>GroupServiceHasReadPermissionResponse</u>	<u>hasReadPermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
<u>GroupServiceHasReverseRelationshipResponse</u>	<u>hasReverseRelationship</u> (<u>GroupServiceHasReverseRelationship</u> value) Returns true if the relationship of the given target and source exists.
<u>GroupServiceHasWritePermissionResponse</u>	<u>hasWritePermission</u> (<u>GroupServiceHasWritePermission</u> value) Returns true if the source resource has Write permission on the target resource.
<u>GroupServiceHasWritePermissionResponse</u>	<u>hasWritePermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
<u>GroupServiceHasWritePermissionResponse</u>	<u>hasWritePermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
<u>GroupServiceHasXPermissionResponse</u>	<u>hasXPermission</u> (<u>GroupServiceHasXPermission</u> value) Returns true if the source resource has Execute (X) permission on the target resource.
<u>GroupServiceHasXPermissionResponse</u>	<u>hasXPermission</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
<u>GroupServiceHasXPermissionResponse</u>	<u>hasXPermissionPost</u> (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
<u>GroupServiceInsertResponse</u>	<u>insert</u> (<u>GroupServiceInsert</u> value) Inserts the resource of the type S.
<u>GroupServiceInsertGroupResponse</u>	<u>insertGroup</u> (<u>GroupServiceInsertGroup</u> value) Inserts the group to the resource specified by parentId; and adds the list of children to the group.
<u>GroupServiceInsertResourceResponse</u>	<u>insertResource</u> (<u>GroupServiceInsertResource</u> value) Inserts the resource of the type S into the specified group.
<u>GroupServiceIsDisabledResponse</u>	<u>isDisabled</u> (<u>GroupServiceIsDisabled</u> value) Returns true if the resource is disabled.
<u>GroupServiceIsDisabledResponse</u>	<u>isDisabled</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
<u>GroupServiceIsDisabledResponse</u>	<u>isDisabledPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.

GroupServiceIsGroupResponse	isGroup (GroupServiceIsGroup value) Returns whether or not this resource is a group
GroupServiceIsGroupResponse	isGroup (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns whether or not this resource is a group
GroupServiceIsGroupResponse	isGroupPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns whether or not this resource is a group
GroupServiceIsParentOfResponse	isParentOf (GroupServiceIsParentOf value) Returns whether this group is a parent of the specified resource.
GroupServiceIsValidResourceIDResponse	isValidResourceID (GroupServiceIsValidResourceID value) Returns true if the resource with the given ID does exist in the database.
GroupServiceIsValidResourceIDResponse	isValidResourceID (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
GroupServiceIsValidResourceIDResponse	isValidResourceIDPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
Void	loadAdditional (GroupServiceLoadAdditional value) Loads fields into the given resource that had not previously been loaded.
Void	loadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	loadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	removeChild (GroupServiceRemoveChild value) Removes a child from the group specified by groupId.
Void	removeChild (String authToken, String groupId, String childId, javax.ws.rs.core.HttpHeaders hh) Removes a child from the group specified by groupId.
Void	removeChildPost (String authToken, String groupId, String childId, javax.ws.rs.core.HttpHeaders hh) Removes a child from the group specified by groupId.
Void	removeChildren (GroupServiceRemoveChildren value) Removes a list of children from the group specified by groupId.
Void	resetState (GroupServiceResetState value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	resetState (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Void	resetStatePost (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
GroupServiceResolveRelationshipResponse	resolveRelationship (GroupServiceResolveRelationship value) Returns true if the specified relationship exists between the source and the target resources.
GroupServiceResolveRelationshipResponse	resolveRelationship (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
GroupServiceResolveRelationshipResponse	resolveRelationshipPost (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
Void	unloadAdditional (GroupServiceUnloadAdditional value) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
GroupServiceUpdateResponse	update (GroupServiceUpdate value) Updates the resource of the type S in the store.
Void	updateACLForResourceById (GroupServiceUpdateACLForResourceById value) Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder.
GroupServiceUpdateGroupResponse	updateGroup (GroupServiceUpdateGroup value) Updates the group itself and its children list with the specified will-be-added children list and will-be-removed children list.
GroupServiceUpdateResourcesResponse	updateResources (GroupServiceUpdateResources value) Updates the resources of the type S in the database.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupServiceImpl

```
public GroupServiceImpl()
```

Methods

getPersonalGroup

```
public GroupServiceGetPersonalGroupResponse getPersonalGroup(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroupPost

```
public GroupServiceGetPersonalGroupResponse getPersonalGroupPost(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalGroup

```
public GroupServiceGetPersonalGroupResponse getPersonalGroup(GroupServiceGetPersonalGroup  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. GroupService doesn't support personal Groups - there is no such concept in ESM Resource Framework.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isGroup

```
public GroupServiceIsGroupResponse isGroup(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns whether or not this resource is a group

Parameters:

resourceId - The resource id.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if this resource is a group; otherwise, false.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isGroupPost

```
public GroupServiceIsGroupResponse isGroupPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns whether or not this resource is a group

Parameters:

resourceId - The resource id.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if this resource is a group; otherwise, false.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

isGroup

```
public GroupServiceIsGroupResponse isGroup(GroupServiceIsGroup value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns whether or not this resource is a group

Parameters:

value - Model object containing request body

Returns:

True if this resource is a group; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupByID

```
public GroupServiceGetGroupByIDResponse getGroupByID(String authToken,
    String groupId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the group specified by the groupId.

Parameters:

groupId - The resource ID of the group to return.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The group specified by the resource ID.

Throws:

[ServiceException](#) - If there was an error returning the group.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupByIDPost

```
public GroupServiceGetGroupByIDResponse getGroupByIDPost(String authToken,
    String groupId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the group specified by the groupId.

Parameters:

groupId - The resource ID of the group to return.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The group specified by the resource ID.

Throws:

ServiceException - If there was an error returning the group.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getGroupByID

```
public GroupServiceGetGroupByIDResponse getGroupByID(GroupServiceGetGroupByID value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the group specified by the groupId.

Parameters:

value - Model object containing request body

Returns:

The group specified by the resource ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupByURI

```
public GroupServiceGetGroupByURIResponse getGroupByURI(String authToken,  
String uri,  
java.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the group specified by the URI.

Parameters:

uri - The URI of the group to return.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The group specified by the URI.

Throws:

[ServiceException](#) - If there was an error returning the group.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupByURIPost

```
public GroupServiceGetGroupByURIResponse getGroupByURIPost(String authToken,  
    String uri,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the group specified by the URI.

Parameters:

uri - The URI of the group to return.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The group specified by the URI.

Throws:

[ServiceException](#) - If there was an error returning the group.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getGroupByURI

```
public GroupServiceGetGroupByURIResponse getGroupByURI(GroupServiceGetGroupByURI value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the group specified by the URI.

Parameters:

value - Model object containing request body

Returns:

The group specified by the URI.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupChildCount

```
public GroupServiceGetGroupChildCountResponse getGroupChildCount(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the number of displayable children for the given group. This only takes into account hidden resources and any cases that are already handled.

Parameters:

groupId - The ID of the specified group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The number of displayable children for the group specified by groupId.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getGroupChildCountPost

```
public GroupServiceGetGroupChildCountResponse getGroupChildCountPost(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the number of displayable children for the given group. This only takes into account hidden resources and any cases that are already handled.

Parameters:

groupId - The ID of the specified group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The number of displayable children for the group specified by groupId.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getGroupChildCount

```
public GroupServiceGetGroupChildCountResponse  
getGroupChildCount(GroupServiceGetGroupChildCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of displayable children for the given group. This only takes into account hidden resources and any cases that are already handled.

Parameters:

value - Model object containing request body

Returns:

The number of displayable children for the group specified by groupId.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addChild

```
public Void addChild(String authToken,  
                     String groupId,  
                     String childId,  
                     javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds a child to the group specified by groupId.

Parameters:

groupId - The resource id of the group.
childId - The resource id of the child.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addChildPost

```
public Void addChildPost(String authToken,  
                          String groupId,  
                          String childId,  
                          javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds a child to the group specified by groupId.

Parameters:

groupId - The resource id of the group.
childId - The resource id of the child.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

ServiceException - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

addChild

```
public Void addChild(GroupServiceAddChild value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds a child to the group specified by groupId.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addChildren

```
public Void addChildren(GroupServiceAddChildren value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds a list of children to the group specified by groupId. If any of the children couldn't be added, then the entire transaction is rolled back.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

removeChild

```
public Void removeChild(String authToken,  
    String groupId,  
    String childId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Removes a child from the group specified by groupId. There is a limitation for this functionality. Resource cannot be removed from the last group that the resource belongs to. An attempt to do it would fail with AccessDeniedException.

Parameters:

groupId - The ID of the group.
childId - The ID of the child to remove from the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[ServiceException](#) - If there was an error during processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

removeChildPost

```
public Void removeChildPost(String authToken,  
    String groupId,  
    String childId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Removes a child from the group specified by groupId. There is a limitation for this functionality. Resource cannot be removed from the last group that the resource belongs to. An attempt to do it would fail with AccessDeniedException.

Parameters:

groupId - The ID of the group.
childId - The ID of the child to remove from the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[ServiceException](#) - If there was an error during processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

removeChild

```
public Void removeChild(GroupServiceRemoveChild value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```


Removes a child from the group specified by groupId. There is a limitation for this functionality. Resource cannot be removed from the last group that the resource belongs to. An attempt to do it would fail with AccessDeniedException.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

removeChildren

```
public Void removeChildren(GroupServiceRemoveChildren value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Removes a list of children from the group specified by groupId. There is a limitation for this functionality. Resources cannot be removed from the last group that they belong to. An attempt to do it would fail with AccessDeniedException.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateGroup

```
public GroupServiceUpdateGroupResponse updateGroup(GroupServiceUpdateGroup value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Updates the group itself and its children list with the specified will-be-added children list and will-be-removed children list. There is a limitation for this functionality. Resources cannot be removed from the last group that they belong to. An attempt to do it would fail with AccessDeniedException.

Parameters:

value - Model object containing request body

Returns:

The updated group object.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insertGroup

```
public GroupServiceInsertGroupResponse insertGroup(GroupServiceInsertGroup value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Inserts the group to the resource specified by parentId; and adds the list of children to the group.

Parameters:

value - Model object containing request body

Returns:

The group object.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildrenByType

```
public GroupServiceGetChildrenByTypeResponse getChildrenByType(String authToken,
    String groupId,
    int resourceType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all children of the specified type.

Parameters:

groupId - The resource ID of the group

resourceType - The resource type of the children to return.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

A list of IDs of all children of the specified type

Throws:

[ServiceException](#) - If there was an error during returning.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildrenByTypePost

```
public GroupServiceGetChildrenByTypeResponse getChildrenByTypePost(String authToken,  
    String groupId,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all children of the specified type.

Parameters:

groupId - The resource ID of the group
resourceType - The resource type of the children to return.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of IDs of all children of the specified type

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getChildrenByType

```
public GroupServiceGetChildrenByTypeResponse  
getChildrenByType(GroupServiceGetChildrenByType value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all children of the specified type.

Parameters:

value - Model object containing request body

Returns:

A list of IDs of all children of the specified type

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildIDs

```
public GroupServiceGetAllChildIDsResponse getAllChildIDs(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all children for the specified group.

Parameters:

groupId - The resource ID of the group
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of the IDs of all children for the specified group.

Throws:

ServiceException - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildIDsPost

```
public GroupServiceGetAllChildIDsResponse getAllChildIDsPost(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all children for the specified group.

Parameters:

groupId - The resource ID of the group
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of the IDs of all children for the specified group.

Throws:

ServiceException - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllChildIDs

```
public GroupServiceGetAllChildIDsResponse getAllChildIDs(GroupServiceGetAllChildIDs  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all children for the specified group.

Parameters:

value - Model object containing request body

Returns:

A list of the IDs of all children for the specified group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildIDCount

```
public GroupServiceGetAllChildIDCountResponse getAllChildIDCount(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the number of all children for this specified group.

Parameters:

groupId - The resource ID of the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The number of all children for this specified group.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildIDCountPost

```
public GroupServiceGetAllChildIDCountResponse getAllChildIDCountPost(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the number of all children for this specified group.

Parameters:

groupId - The resource ID of the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The number of all children for this specified group.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllChildIDCount

```
public GroupServiceGetAllChildIDCountResponse  
getAllChildIDCount(GroupServiceGetAllChildIDCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of all children for this specified group.

Parameters:

value - Model object containing request body

Returns:

The number of all children for this specified group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasChildWithNameOrAlias

```
public GroupServiceHasChildWithNameOrAliasResponse hasChildWithNameOrAlias(String  
    authToken,  
        String groupId,  
        String alias,  
        String name,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns whether this group contains a child with the given name or alias.

Parameters:

groupId - The resource ID of the group.
alias - The alias of the resource.
name - The name of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the specified group has the child with the given name or alias; otherwise, false.

Throws:

[ServiceException](#) - At least one of the children of this group could not be loaded from the persistent store.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasChildWithNameOrAliasPost

```
public GroupServiceHasChildWithNameOrAliasResponse hasChildWithNameOrAliasPost(String
authToken,
    String groupId,
    String alias,
    String name,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns whether this group contains a child with the given name or alias.

Parameters:

groupId - The resource ID of the group.
alias - The alias of the resource.
name - The name of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the specified group has the child with the given name or alias; otherwise, false.

Throws:

[ServiceException](#) - At least one of the children of this group could not be loaded from the persistent store.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasChildWithNameOrAlias

```
public GroupServiceHasChildWithNameOrAliasResponse
hasChildWithNameOrAlias(GroupServiceHasChildWithNameOrAlias value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns whether this group contains a child with the given name or alias.

Parameters:

value - Model object containing request body

Returns:

True if the specified group has the child with the given name or alias; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

childAttributesChanged

```
public Void childAttributesChanged(GroupServiceChildAttributesChanged value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Notifies the specified group that the name (or alias) of the given resource child may have changed.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildren

```
public GroupServiceGetAllChildrenResponse getAllChildren(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all of the resource children of this specified group.

Parameters:

groupId - The ID of the group.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

A list of all children of the specified group.

Throws:

[ServiceException](#) - If there was an error during returning.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllChildrenPost

```
public GroupServiceGetAllChildrenResponse getAllChildrenPost(String authToken,  
    String groupId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all of the resource children of this specified group.

Parameters:

groupId - The ID of the group.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

A list of all children of the specified group.

Throws:

[ServiceException](#) - If there was an error during returning.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllChildren

```
public GroupServiceGetAllChildrenResponse getAllChildren(GroupServiceGetAllChildren  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of all of the resource children of this specified group.

Parameters:

value - Model object containing request body

Returns:

A list of all children of the specified group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsResourcesRecursively

```
public GroupServiceContainsResourcesRecursivelyResponse  
containsResourcesRecursively(String authToken,  
    String groupId,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Checks whether this group or any of its subgroups contains any resource of the given type.

Parameters:

groupId - The resource ID of the group.

resourceType - The resource type of the resource to look for.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

True if the group or its subgroup contains entries of this resource type; otherwise, false.

Throws:

[ServiceException](#) - If there was an error during returning.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsResourcesRecursivelyPost

```
public GroupServiceContainsResourcesRecursivelyResponse  
containsResourcesRecursivelyPost(String authToken,  
    String groupId,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Checks whether this group or any of its subgroups contains any resource of the given type.

Parameters:

groupId - The resource ID of the group.
resourceType - The resource type of the resource to look for.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group or its subgroup contains entries of this resource type; otherwise, false.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsResourcesRecursively

```
public GroupServiceContainsResourcesRecursivelyResponse  
containsResourcesRecursively(GroupServiceContainsResourcesRecursively value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Checks whether this group or any of its subgroups contains any resource of the given type.

Parameters:

value - Model object containing request body

Returns:

True if the group or its subgroup contains entries of this resource type; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildIDByChildNameOrAlias

```
public GroupServiceGetChildIDByChildNameOrAliasResponse  
getChildIDByChildNameOrAlias(String authToken,  
    String groupId,  
    String alias,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource ID of the child in this group with the given name or alias.

Parameters:

groupId - The resource ID of the group.
alias - The alias of the resource.
name - The name of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of resource ID of the child in this group with the given name or alias; null if there is not a resource with the given name.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildIDByChildNameOrAliasPost

```
public GroupServiceGetChildIDByChildNameOrAliasResponse  
getChildIDByChildNameOrAliasPost(String authToken,  
    String groupId,  
    String alias,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource ID of the child in this group with the given name or alias.

Parameters:

groupId - The resource ID of the group.
alias - The alias of the resource.
name - The name of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The string value of resource ID of the child in this group with the given name or alias; null if there is not a resource with the given name.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

getChildIDByChildNameOrAlias

```
public GroupServiceGetChildIDByChildNameOrAliasResponse  
getChildIDByChildNameOrAlias(GroupServiceGetChildIDByChildNameOrAlias value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource ID of the child in this group with the given name or alias.

Parameters:

value - Model object containing request body

Returns:

The string value of resource ID of the child in this group with the given name or alias; null if there is not a resource with the given name.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isParentOf

```
public GroupServiceIsParentOfResponse isParentOf(GroupServiceIsParentOf value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns whether this group is a parent of the specified resource.

Parameters:

value - Model object containing request body

Returns:

True if this resource is a parent of the specified resource; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroup

```
public GroupServiceGetMetaGroupResponse getMetaGroup(String authToken,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Get the meta group of this resource type. The meta group is the top level of the specified categorical group.

Parameters:

resourceType - The resource type of the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The meta group of the specified resource type.

Throws:

ServiceException - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupPost

```
public GroupServiceGetMetaGroupResponse getMetaGroupPost(String authToken,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Get the meta group of this resource type. The meta group is the top level of the specified categorical group.

Parameters:

resourceType - The resource type of the group.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The meta group of the specified resource type.

Throws:

ServiceException - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getMetaGroup

```
public GroupServiceGetMetaGroupResponse getMetaGroup(GroupServiceGetMetaGroup value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Get the meta group of this resource type. The meta group is the top level of the specified categorical group.

Parameters:

value - Model object containing request body

Returns:

The meta group of the specified resource type.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildResourcesByType

```
public GroupServiceGetChildResourcesByTypeResponse getChildResourcesByType(String  
authToken,  
    String groupId,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Return a list of resources based on the type of child required.

Parameters:

groupId - The resource ID of the group.
resourceType - The resource Type of children.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resources based on the type of child required.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildResourcesByTypePost

```
public GroupServiceGetChildResourcesByTypeResponse getChildResourcesByTypePost(String  
authToken,  
    String groupId,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Return a list of resources based on the type of child required.

Parameters:

groupId - The resource ID of the group.
resourceType - The resource Type of children.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resources based on the type of child required.

Throws:

[ServiceException](#) - If there was an error during returning.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

getChildResourcesByType

```
public GroupServiceGetChildResourcesByTypeResponse  
getChildResourcesByType(GroupServiceGetChildResourcesByType value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Return a list of resources based on the type of child required.

Parameters:

value - Model object containing request body

Returns:

A list of resources based on the type of child required.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insert

```
public GroupServiceInsertResponse insert(GroupServiceInsert value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Inserts the resource of the type S. The system adds such required fields as resource ID if needed. The resource will be added to Unassigned group, and it's required that the current user has write permission to a Meta Group of the type S. So only a limited number of users can add and later access such new resources. Use another method, `insertResource(resource, parentId)` to create a new resource and add it to the group with the specified ID.

Parameters:

value - Model object containing request body

Returns:

The resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insertResource

```
public GroupServiceInsertResourceResponse insertResource(GroupServiceInsertResource  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Inserts the resource of the type S into the specified group.

Parameters:

value - Model object containing request body

Returns:

The inserted resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

delete

```
public Void delete(GroupServiceDelete value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource of the type S from the database.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findById

```
public GroupServiceFindByIdResponse findById(String authToken,
    long localId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByIdPost

```
public GroupServiceFindByIdResponse findByIdPost(String authToken,  
        long localId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findById

```
public GroupServiceFindByIdResponse findById(GroupServiceFindById value)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByIdUUID

```
public GroupServiceFindByUUIDResponse findByIdUUID(String authToken,  
        String id,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUIDPost

```
public GroupServiceFindByUUIDResponse findByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findByUUID

```
public GroupServiceFindByUUIDResponse findByUUID(GroupServiceFindByUUID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

value - Model object containing request body

Returns:

The resource identified by the ID

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

update

```
public GroupServiceUpdateResponse update(GroupServiceUpdate value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Updates the resource of the type S in the store.

Parameters:

value - Model object containing request body

Returns:

The updated resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAlias

```
public GroupServiceContainsDirectMemberByNameOrAliasResponse
containsDirectMemberByNameOrAlias(String authToken,
    String groupId,
    String targetId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAliasPost

```
public GroupServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAliasPost(String authToken,  
    String groupId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsDirectMemberByNameOrAlias

```
public GroupServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAlias(GroupServiceContainsDirectMemberByNameOrAlias value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

value - Model object containing request body

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroup

```
public GroupServiceCopyResourceIntoGroupResponse copyResourceIntoGroup(String authToken,  
    String newName,  
    String resourceId,  
    String oldParentId,  
    String newParentId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.
If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroupPost

```
public GroupServiceCopyResourceIntoGroupResponse copyResourceIntoGroupPost(String  
authToken,  
    String newName,  
    String resourceId,  
    String oldParentId,  
    String newParentId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.
If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource

resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

copyResourceIntoGroup

```
public GroupServiceCopyResourceIntoGroupResponse  
copyResourceIntoGroup(GroupServiceCopyResourceIntoGroup value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

value - Model object containing request body

Returns:

The inserted resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResource

```
public Void deleteResource(GroupServiceDeleteResource value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource of the type S from the database. Method allows to specify whether to abort the transaction during conflicts in the validation.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalId

```
public Void deleteByLocalId(String authToken,  
    long id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalIdPost

```
public Void deleteByLocalIdPost(String authToken,  
    long id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByLocalId

```
public Void deleteByLocalId(GroupServiceDeleteByLocalId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUID

```
public Void deleteByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUIDPost

```
public Void deleteByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByUUID

```
public Void deleteByUUID(GroupServiceDeleteByUUID value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResources

```
public Void deleteResources(GroupServiceDeleteResources value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resources of the type S from the database. Note that **nulls** in the list are not allowed

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIds

```
public GroupServiceFindAllIdsResponse findAllIds(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resourcefindAllIds IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIdsPost

```
public GroupServiceFindAllIdsResponse findAllIdsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findAllIds

```
public GroupServiceFindAllIdsResponse findAllIds(GroupServiceFindAllIds value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllAttachmentOnlyResourceIDs

```
public GroupServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDsPost

```
public GroupServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDs

```
public GroupServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(GroupServiceGetAllAttachmentOnlyResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

value - Model object containing request body

Returns:

The list of the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllowedUserTypes

```
public GroupServiceGetAllowedUserTypesResponse getAllowedUserTypes(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllowedUserTypesPost

```
public GroupServiceGetAllowedUserTypesResponse getAllowedUserTypesPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User .UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllowedUserTypes

```
public GroupServiceGetAllowedUserTypesResponse  
getAllowedUserTypes(GroupServiceGetAllowedUserTypes value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

value - Model object containing request body

Returns:

The array of user types; see [User .UserTypeEnum](#).

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRoot

```
public GroupServiceGetAllPathsToRootResponse getAllPathsToRoot(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"0AFPLmPsAABCAHBFqR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/0bdhibUYBABCAR4QQ!pgzcw=="

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootPost

```
public GroupServiceGetAllPathsToRootResponse getAllPathsToRootPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/0bdhibUYBABCAR4QQ!pgzcg=="

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRoot

```
public GroupServiceGetAllPathsToRootResponse  
getAllPathsToRoot(GroupServiceGetAllPathsToRoot value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID resourceId to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/0bdhibUYBABCAR4QQ!pgzcg=="

Parameters:

value - Model object containing request body

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStrings

```
public GroupServiceGetAllPathsToRootAsStringsResponse getAllPathsToRootAsStrings(String authToken,
    String resourceId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStringsPost

```
public GroupServiceGetAllPathsToRootAsStringsResponse getAllPathsToRootAsStringsPost(String authToken,
    String resourceId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRootAsStrings

```
public GroupServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStrings(GroupServiceGetAllPathsToRootAsStrings value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

value - Model object containing request body

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllUnassignedResourceIDs

```
public GroupServiceGetAllUnassignedResourceIDsResponse getAllUnassignedResourceIDs(String  
    authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDsPost

```
public GroupServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDs

```
public GroupServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDs(GroupServiceGetAllUnassignedResourceIDs value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getAllAttachmentOnlyResourceIDs()`

getChildNamesAndAliases

```
public GroupServiceGetChildNamesAndAliasesResponse  
getChildNamesAndAliases(GroupServiceGetChildNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. This method is left for backward compatibility only. Please rather use method `getNamesAndAliases(List)`

Returns the names and aliases of all of the resources with ID specified in `childIds`. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources.

The size of the returned list will always be $2 * n$ where n is the size of the `childIds` list. It is possible for some of the names to be missing, in which case `null` values will be in the list (including the first half where the names are located)

Parameters:

`value` - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getNamesAndAliases

```
public GroupServiceGetNamesAndAliasesResponse  
getNamesAndAliases(GroupServiceGetNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the names and aliases of all of the resources of the type `S` with ID specified in `resourceIds`. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources.

The size of the returned list will always be $2 * n$ where n is the number of specified resource ID. It is possible for some of the names to be missing, in which case `null` values will be in the list (including the first half where the names are located)

Parameters:

`value` - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResources

```
public GroupServiceGetCorruptedResourcesResponse getCorruptedResources(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResourcesPost

```
public GroupServiceGetCorruptedResourcesResponse getCorruptedResourcesPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCorruptedResources

```
public GroupServiceGetCorruptedResourcesResponse  
getCorruptedResources(GroupServiceGetCorruptedResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

value - Model object containing request body

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceId

```
public GroupServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If `excludeAttachmentOnlyResources` is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource

excludeHiddenResources - If true, excludes the hidden resources

excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceIdPost

```
public GroupServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceIdPost(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If `excludeAttachmentOnlyResources` is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

`resourceId` - The ID of the resource

`excludeHiddenResources` - If true, excludes the hidden resources

`excludeAttachmentOnlyResources` - Whether to exclude the dependent resources which are attachment resources only

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getDependentResourceIdsForResourceId

```
public GroupServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(GroupServiceGetDependentResourceIdsForResourceId  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If `excludeAttachmentOnlyResources` is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getRelationshipsOfThisAndParents

```
public GroupServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID sourceId and goes recursively through all its parents to collect resources that play role target for the relationship relationshipType. See [RelationshipTypes](#)

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

```
getRelationshipsOfParents(String, int)  
getReverseRelationshipsOfThisAndParents(String, int)  
getReverseRelationshipsOfParents(String, int)
```

getRelationshipsOfThisAndParentsPost

```
public GroupServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID sourceId and goes recursively through all its parents to collect resources that play role target for the relationship relationshipType. See [RelationshipTypes](#)

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getRelationshipsOfParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)

getRelationshipsOfThisAndParents

```
public GroupServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParents(GroupServiceGetRelationshipsOfThisAndParents value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID sourceId and goes recursively through all its parents to collect resources that play role target for the relationship relationshipType. See [RelationshipTypes](#)

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

```
getRelationshipsOfParents(String, int)
getReverseRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfParents(String, int)
```

getRelationshipsOfParents

```
public GroupServiceGetRelationshipsOfParentsResponse getRelationshipsOfParents(String
authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

```
getRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfParents(String, int)
RelationshipTypes
```

getRelationshipsOfParentsPost

```
public GroupServiceGetRelationshipsOfParentsResponse getRelationshipsOfParentsPost(String
authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParents

```
public GroupServiceGetRelationshipsOfParentsResponse  
getRelationshipsOfParents(GroupServiceGetRelationshipsOfParents value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public GroupServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParentsPost

```
public GroupServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public GroupServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(GroupServiceGetReverseRelationshipsOfThisAndParents  
ts value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public GroupServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParentsPost

```
public GroupServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)

getReverseRelationshipsOfParents

```
public GroupServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(GroupServiceGetReverseRelationshipsOfParents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

value - Model object containing request body

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getEnabledResourceIDs

```
public GroupServiceGetEnabledResourceIDsResponse  
getEnabledResourceIDs(GroupServiceGetEnabledResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Checks the specified resources and returns the list of IDs of the resources that are enabled. The returned list is a subset of resourceIds. If all the specified resources are disabled then the method returns an empty list.

Parameters:

value - Model object containing request body

Returns:

The IDs of enabled resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getExclusivelyDependentResources

```
public GroupServiceGetExclusivelyDependentResourcesResponse  
getExclusivelyDependentResources(GroupServiceGetExclusivelyDependentResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resources depending on the given resource of the type S. This means that the given resource is the only path to root for those resources.

Parameters:

value - Model object containing request body

Returns:

List of resources that depend on the specified resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupID

```
public GroupServiceGetMetaGroupIDResponse getMetaGroupID(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupIDPost

```
public GroupServiceGetMetaGroupIDResponse getMetaGroupIDPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getMetaGroupID

```
public GroupServiceGetMetaGroupIDResponse getMetaGroupID(GroupServiceGetMetaGroupID  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRoots

```
public GroupServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRootsPost

```
public GroupServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRootsPost(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalAndSharedResourceRoots

```
public GroupServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(GroupServiceGetPersonalAndSharedResourceRoots value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```


Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type `relationshipType`. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, `CaseService` would return roots of the type `Case`. Regardless of service type, typically the method is called for a user with relationship types `READ_PERMISSION` or `WRITE_PERMISSION`. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship. See the list of available relationship types here [RelationshipTypes](#)

Parameters:

`value` - Model object containing request body

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRoots

```
public GroupServiceGetPersonalResourceRootsResponse getPersonalResourceRoots(String
authToken,
    String resourceId,
    int relationshipType,
    int resourceType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with `relationshipType` relations. The returned list contains only resources whose type match the selected service (e.g. `CaseService`, `UserResourceService`).

For example calling this method from `GroupService` for a `Case` resource would return Personal Groups associated with that `Case` as targets in relations of the type `relationshipType`. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

`resourceId` - The ID of the resource used as source in relations

`relationshipType` - The relationship type of the targets to the given resource

`resourceType` - NOT USED. The parameter is left for backward compatibility

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRootsPost

```
public GroupServiceGetPersonalResourceRootsResponse getPersonalResourceRootsPost(String
authToken,
    String resourceId,
    int relationshipType,
    int resourceType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#) Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

resourceId - The ID of the resource used as source in relations
relationshipType - The relationship type of the targets to the given resource
resourceType - NOT USED. The parameter is left for backward compatibility
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalResourceRoots

```
public GroupServiceGetPersonalResourceRootsResponse
getPersonalResourceRoots(GroupServiceGetPersonalResourceRoots value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#) Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

value - Model object containing request body

Returns:

The list of target resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesReferencePages

```
public GroupServiceGetResourcesReferencePagesResponse  
getResourcesReferencePages(GroupServiceGetResourcesReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resources identified by the IDs.

Parameters:

value - Model object containing request body

Returns:

A list of reference pages for the resources identified by the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePages

```
public GroupServiceGetReferencePagesResponse getReferencePages(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePagesPost

```
public GroupServiceGetReferencePagesResponse getReferencePagesPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getReferencePages

```
public GroupServiceGetReferencePagesResponse  
getReferencePages(GroupServiceGetReferencePages value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

value - Model object containing request body

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByName

```
public GroupServiceGetResourceByNameResponse getResourceByName(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByNamePost

```
public GroupServiceGetResourceByNameResponse getResourceByNamePost(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceByName

```
public GroupServiceGetResourceByNameResponse  
getResourceByName(GroupServiceGetResourceByName value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

value - Model object containing request body

Returns:

The resource identified by the name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNames

```
public GroupServiceGetResourcesByNamesResponse  
getResourcesByNames(GroupServiceGetResourcesByNames value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified names. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.
If parameter names contains only one name, then the returned collection would contain all resources which have that name.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of names

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByIds

```
public GroupServiceGetResourcesByIdsResponse  
getResourcesByIds(GroupServiceGetResourcesByIds value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resources of the type S identified by the specified resource IDs. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafely

```
public GroupServiceGetResourcesByNameSafelyResponse getResourcesByNameSafely(String
authToken,
    String name,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafelyPost

```
public GroupServiceGetResourcesByNameSafelyResponse getResourcesByNameSafelyPost(String
authToken,
    String name,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourcesByNameSafely

```
public GroupServiceGetResourcesByNameSafelyResponse  
getResourcesByNameSafely(GroupServiceGetResourcesByNameSafely value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

value - Model object containing request body

Returns:

The resources with the specified name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermission

```
public GroupServiceHasReadPermissionResponse hasReadPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermissionPost

```
public GroupServiceHasReadPermissionResponse hasReadPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasReadPermission

```
public GroupServiceHasReadPermissionResponse  
hasReadPermission(GroupServiceHasReadPermission value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermission

```
public GroupServiceHasWritePermissionResponse hasWritePermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermissionPost

```
public GroupServiceHasWritePermissionResponse hasWritePermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasWritePermission

```
public GroupServiceHasWritePermissionResponse  
hasWritePermission(GroupServiceHasWritePermission value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermission

```
public GroupServiceHasXPermissionResponse hasXPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermissionPost

```
public GroupServiceHasXPermissionResponse hasXPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasXPermission

```
public GroupServiceHasXPermissionResponse hasXPermission(GroupServiceHasXPermission  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabled

```
public GroupServiceIsDisabledResponse isDisabled(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabledPost

```
public GroupServiceIsDisabledResponse isDisabledPost(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isDisabled

```
public GroupServiceIsDisabledResponse isDisabled(GroupServiceIsDisabled value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceID

```
public GroupServiceIsValidResourceIDResponse isValidResourceID(String authToken,
    String resourceId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceIDPost

```
public GroupServiceIsValidResourceIDResponse isValidResourceIDPost(String authToken,
    String resourceId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isValidResourceID

```
public GroupServiceIsValidResourceIDResponse  
isValidResourceID(GroupServiceIsValidResourceID value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

value - Model object containing request body

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

loadAdditional

```
public void loadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`unloadAdditional(String)`

loadAdditionalPost

```
public Void loadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

`sourceId` - The ID of the resource.
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`unloadAdditional(String)`

loadAdditional

```
public Void loadAdditional(GroupServiceLoadAdditional value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

`value` - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`unloadAdditional(String)`

resetState

```
public Void resetState(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resetStatePost

```
public Void resetStatePost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

resetState

```
public Void resetState(GroupServiceResetState value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resolveRelationship

```
public GroupServiceResolveRelationshipResponse resolveRelationship(String authToken,  
    String sourceId,  
    String targetId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

resolveRelationshipPost

```
public GroupServiceResolveRelationshipResponse resolveRelationshipPost(String authToken,  
    String sourceId,  
    String targetId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

resolveRelationship

```
public GroupServiceResolveRelationshipResponse  
resolveRelationship(GroupServiceResolveRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

unloadAdditional

```
public Void unloadAdditional(String authToken,  
                             String sourceId,  
                             javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[loadAdditional\(String\)](#)

unloadAdditionalPost

```
public Void unloadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[loadAdditional\(String\)](#)

unloadAdditional

```
public Void unloadAdditional(GroupServiceUnloadAdditional value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[loadAdditional\(String\)](#)

updateResources

```
public GroupServiceUpdateResourcesResponse updateResources(GroupServiceUpdateResources
value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Updates the resources of the type S in the database. Resources are updated in different transactions. Method tries to update as many resources as possible. For all resources that failed to be updated error messages are logged on the server. Failed resources are not included in the returned collection. If the response does not include some of the submitted resources, then check server log-messages to find out why the update failed for them.

Parameters:

value - Model object containing request body

Returns:

The list of successfully updated resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceIfModified

```
public GroupServiceGetResourceIfModifiedResponse
getResourceIfModified(GroupServiceGetResourceIfModified value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource if it is newer than the signature specifies; otherwise returns **null**.

Parameters:

value - Model object containing request body

Returns:

The resource with the specified ID if its modification count is bigger than the one in the signature; **null** otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceSignature](#)

getTargetsByRelationshipCount

```
public GroupServiceGetTargetsByRelationshipCountResponse
getTargetsByRelationshipCount(GroupServiceGetTargetsByRelationshipCount value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationship

```
public GroupServiceGetTargetsByRelationshipResponse  
getTargetsByRelationship(GroupServiceGetTargetsByRelationship value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

hasReverseRelationship

```
public GroupServiceHasReverseRelationshipResponse  
hasReverseRelationship(GroupServiceHasReverseRelationship value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns true if the relationship of the given target and source exists.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the given target and source exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipCount

```
public GroupServiceGetSourcesWithThisTargetByRelationshipCountResponse  
getSourcesWithThisTargetByRelationshipCount(GroupServiceGetSourcesWithThisTargetByRelatio  
nshipCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationship

```
public GroupServiceGetSourcesWithThisTargetByRelationshipResponse  
getSourcesWithThisTargetByRelationship(GroupServiceGetSourcesWithThisTargetByRelationship  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationship

```
public GroupServiceGetTargetsAsURIByRelationshipResponse  
getTargetsAsURIByRelationship(GroupServiceGetTargetsAsURIByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnship

```
public GroupServiceGetSourceURIWithThisTargetByRelatiobnshipResponse  
getSourceURIWithThisTargetByRelatiobnship(GroupServiceGetSourceURIWithThisTargetByRelatio  
bnship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationship(S, int)`.

Parameters:

value - Model object containing request body

Returns:**Throws:**

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationship

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipResponse  
getSourceURIWithThisTargetByRelationship(GroupServiceGetSourceURIWithThisTargetByRelationship  
    value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource URIs for all enabled resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public GroupServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceIdPost

```
public GroupServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public GroupServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(GroupServiceGetTargetsByRelationshipForSourceId  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceIdPost

```
public GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public GroupServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(GroupServiceGetTargetsAsURIByRelationshipForSourceId  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceIdPost

```
public GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(GroupServiceGetSourcesWithThisTargetByRelationshipForResourceId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationshipForResourceIdPost

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourceURIWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(GroupServiceGetSourceURIWithThisTa  
rgetByRelationshipForResourceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceIdPost

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public GroupServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(GroupServiceGetSourceURIWithThisTar  
getByRelationshipForResourceId value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByACLRelationship

```
public GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(String authToken,  
      String sourceResourceId,  
      javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourcesWithThisTargetByACLRelationshipPost

```
public GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationshipPost(String authToken,  
        String sourceResourceId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourcesWithThisTargetByACLRelationship

```
public GroupServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(GroupServiceGetSourcesWithThisTargetByACLRelationship  
onship value)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResource

```
public GroupServiceGetTargetsWithRelationshipTypeForResourceResponse  
getTargetsWithRelationshipTypeForResource(GroupServiceGetTargetsWithRelationshipTypeForResource  
source value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceById

```
public GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceByIdPost

```
public GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getTargetsWithRelationshipTypeForResourceById

```
public GroupServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(GroupServiceGetTargetsWithRelationshipTypeF  
orResourceById value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateACLForResourceById

```
public Void updateACLForResourceById(GroupServiceUpdateACLForResourceById value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Modifies relationships of the resource specified by `resourceId` with other resources specified in the list of `ACLDataHolder`. For every element from data, the method adds, removes, or updates the relationship between the resource and another resource with ID specified in `ACLDataHolder.id`. Every `ACLDataHolder` element also specifies whether it's for source or for target relationship ("forSourceRelationship"), identifier of the resource ("id"), and update type ("updateType").

The request is performed in a single transaction. If any of relations cannot be changed, then the entire transaction fails.

Parameters:

`value` - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesWithVisibilityToUsers

```
public GroupServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsersPost

```
public GroupServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsers

```
public GroupServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(GroupServiceGetResourcesWithVisibilityToUsers value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public GroupServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsersPost

```
public GroupServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public GroupServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(GroupServiceGetResourceTypesVisibleToUsers value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceById

```
public GroupServiceGetResourceByIdResponse getResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByIdPost

```
public GroupServiceGetResourceByIdResponse getResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceById

```
public GroupServiceGetResourceByIdResponse getResourceById(GroupServiceGetResourceById  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

value - Model object containing request body

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addRelationship

```
public GroupServiceAddRelationshipResponse addRelationship(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource
`relationshipType` - The type of the relationship
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

addRelationshipPost

```
public GroupServiceAddRelationshipResponse addRelationshipPost(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource
`relationshipType` - The type of the relationship
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

addRelationship

```
public GroupServiceAddRelationshipResponse addRelationship(GroupServiceAddRelationship  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds the relationship of the type relationshipType between specified target and source resources. There are no additional requirements on the types of the resources identified by sourceResourceId and targetResourceId.

Parameters:

value - Model object containing request body

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getESMVersion

```
public GroupServiceGetESMVersionResponse getESMVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getESMVersionPost

```
public GroupServiceGetESMVersionResponse getESMVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getESMVersion

```
public GroupServiceGetESMVersionResponse getESMVersion(GroupServiceGetESMVersion value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

value - Model object containing request body

Returns:

Version of ESM

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersion

```
public GroupServiceGetServiceMajorVersionResponse getServiceMajorVersion(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersionPost

```
public GroupServiceGetServiceMajorVersionResponse getServiceMajorVersionPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMajorVersion

```
public GroupServiceGetServiceMajorVersionResponse  
getServiceMajorVersion(GroupServiceGetServiceMajorVersion value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The major version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersion

```
public GroupServiceGetServiceMinorVersionResponse getServiceMinorVersion(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersionPost

```
public GroupServiceGetServiceMinorVersionResponse getServiceMinorVersionPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMinorVersion

```
public GroupServiceGetServiceMinorVersionResponse  
getServiceMinorVersion(GroupServiceGetServiceMinorVersion value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

com.arcsight.product.manager.resource.service.v1.rest Class ReportServiceImpl

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.rest.ReportServiceImpl

public class **ReportServiceImpl**
extends Object

An implementation of the ReportService that allows a user to access reports resources.

Constructor Summary

public	ReportServiceImpl()

Method Summary

ReportServiceAddRelationshipResponse	addRelationship (ReportServiceAddRelationship value) Adds the relationship of the type relationshipType between specified target and source resources.
ReportServiceAddRelationshipResponse	addRelationship (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
ReportServiceAddRelationshipResponse	addRelationshipPost (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
ReportServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (ReportServiceContainsDirectMemberByNameOrAlias value) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ReportServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ReportServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAliasPost (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ReportServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (ReportServiceCopyResourceIntoGroup value) Creates a copy of the given resource of type S and inserts that resource into the given target group.

ReportServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
ReportServiceCopyResourceIntoGroupResponse	copyResourceIntoGroupPost (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
Void	delete (ReportServiceDelete value) Deletes the resource of the type S from the database.
Void	deleteByLocalId (ReportServiceDeleteByLocalId value) Deletes the resource identified by the local ID.
Void	deleteByLocalId (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByLocalIdPost (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByUUID (ReportServiceDeleteByUUID value) Deletes the resource identified by the ID.
Void	deleteByUUID (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	deleteByUUIDPost (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	deleteResource (ReportServiceDeleteResource value) Deletes the resource of the type S from the database.
Void	deleteResources (ReportServiceDeleteResources value) Deletes the resources of the type S from the database.
ReportServiceFindAllIdsResponse	findAllIds (ReportServiceFindAllIds value) Finds and returns the list of IDs of all the resources of type S.
ReportServiceFindAllIdsResponse	findAllIds (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
ReportServiceFindAllIdsResponse	findAllIdsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Finds and returns the list of IDs of all the resources of type S.
ReportServiceFindByIdResponse	findById (ReportServiceFindById value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ReportServiceFindByIdResponse	findById (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

ReportServiceFindByIdResponse	findByIdPost (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ReportServiceFindByUUIDResponse	findByIdUUID (ReportServiceFindByUUID value) Returns the resource of the type S identified by its ID.
ReportServiceFindByUUIDResponse	findByIdUUID (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
ReportServiceFindByUUIDResponse	findByIdUUIDPost (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
ReportServiceGetAllAttachmentOnlyResourceIDsResponse	getAllAttachmentOnlyResourceIDs (ReportServiceGetAllAttachmentOnlyResourceIDs value) Returns a list of the IDs of all attachments of the type S.
ReportServiceGetAllAttachmentOnlyResourceIDsResponse	getAllAttachmentOnlyResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
ReportServiceGetAllAttachmentOnlyResourceIDsResponse	getAllAttachmentOnlyResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all attachments of the type S.
ReportServiceGetAllowedUserTypesResponse	getAllowedUserTypes (ReportServiceGetAllowedUserTypes value) Returns the array of user types that are allowed to access the service.
ReportServiceGetAllowedUserTypesResponse	getAllowedUserTypes (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
ReportServiceGetAllowedUserTypesResponse	getAllowedUserTypesPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
ReportServiceGetAllPathsToRootResponse	getAllPathsToRoot (ReportServiceGetAllPathsToRoot value) Returns a list of all the paths to root relevant to the service for the given resource.
ReportServiceGetAllPathsToRootResponse	getAllPathsToRoot (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
ReportServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStrings (ReportServiceGetAllPathsToRootAsStrings value) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
ReportServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStrings (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
ReportServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStringsPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.

ReportServiceGetAllPathsToRootResponse	getAllPathsToRootPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
ReportServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (ReportServiceGetAllUnassignedResourceIDs value) Returns a list of the IDs of all unassigned resources of the type S.
ReportServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
ReportServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns a list of the IDs of all unassigned resources of the type S.
ReportServiceGetChildNamesAndAliasesResponse	getChildNamesAndAliases (ReportServiceGetChildNamesAndAliases value) Deprecated. This method is left for backward compatibility only. Please rather use method getNamesAndAliases (List)
ReportServiceGetCorruptedResourcesResponse	getCorruptedResources (ReportServiceGetCorruptedResources value) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ReportServiceGetCorruptedResourcesResponse	getCorruptedResources (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ReportServiceGetCorruptedResourcesResponse	getCorruptedResourcesPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ReportServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (ReportServiceGetDependentResourceIDsForResourceId value) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ReportServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ReportServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceIdPost (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ReportServiceGetEnabledResourceIDsResponse	getEnabledResourceIDs (ReportServiceGetEnabledResourceIDs value) Checks the specified resources and returns the list of IDs of the resources that are enabled.
ReportServiceGetESMVersionResponse	getESMVersion (ReportServiceGetESMVersion value) Returns the version of ESM manager.
ReportServiceGetESMVersionResponse	getESMVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
ReportServiceGetESMVersionResponse	getESMVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.

ReportServiceGetExclusivelyDependentResourcesResponse	getExclusivelyDependentResources (ReportServiceGetExclusivelyDependentResources value) Returns a list of resources depending on the given resource of the type S.
ReportServiceGetMetaGroupIDResponse	getMetaGroupID (ReportServiceGetMetaGroupID value) Returns the string value of ID of the meta group for the resources of type S.
ReportServiceGetMetaGroupIDResponse	getMetaGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
ReportServiceGetMetaGroupIDResponse	getMetaGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the meta group for the resources of type S.
ReportServiceGetNamesAndAliasesResponse	getNamesAndAliases (ReportServiceGetNamesAndAliases value) Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds.
ReportServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (ReportServiceGetPersonalAndSharedResourceRoots value) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
ReportServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
ReportServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRootsPost (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType.
ReportServiceGetPersonalGroupResponse	getPersonalGroup (ReportServiceGetPersonalGroup value) Returns the string value of ID of the user's personal group for the resources of type S.
ReportServiceGetPersonalGroupResponse	getPersonalGroup (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the user's personal group for the resources of type S.
ReportServiceGetPersonalGroupResponse	getPersonalGroupPost (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Returns the string value of ID of the user's personal group for the resources of type S.
ReportServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (ReportServiceGetPersonalResourceRoots value) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
ReportServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.
ReportServiceGetPersonalResourceRootsResponse	getPersonalResourceRootsPost (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations.

ReportServiceGetReferencePagesResponse	getReferencePages (ReportServiceGetReferencePages value) Returns the list of reference pages for the resource identified by the ID.
ReportServiceGetReferencePagesResponse	getReferencePages (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
ReportServiceGetReferencePagesResponse	getReferencePagesPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
ReportServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (ReportServiceGetRelationshipsOfParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ReportServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ReportServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ReportServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (ReportServiceGetRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ReportServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ReportServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ReportServiceGetResourceByIdResponse	getResourceById (ReportServiceGetResourceById value) Returns the resource of the type S specified by resource ID.
ReportServiceGetResourceByIdResponse	getResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
ReportServiceGetResourceByIdResponse	getResourceByIdPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
ReportServiceGetResourceByNameResponse	getResourceByName (ReportServiceGetResourceByName value) Returns one of the resources of the type S with the specified name.
ReportServiceGetResourceByNameResponse	getResourceByName (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.

ReportServiceGetResourceByNameResponse	getResourceByNamePost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
ReportServiceGetResourceIfModifiedResponse	getResourceIfModified (ReportServiceGetResourceIfModified value) Returns the resource if it is newer than the signature specifies; otherwise returns null .
ReportServiceGetResourcesByIdsResponse	getResourcesByIds (ReportServiceGetResourcesByIds value) Returns the resources of the type S identified by the specified resource IDs.
ReportServiceGetResourcesByNamesResponse	getResourcesByNames (ReportServiceGetResourcesByNames value) Returns all the resources of the type S with the specified names.
ReportServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (ReportServiceGetResourcesByNameSafely value) Returns all the resources of the type S with the specified name.
ReportServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafely (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
ReportServiceGetResourcesByNameSafelyResponse	getResourcesByNameSafelyPost (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
ReportServiceGetResourcesReferencePagesResponse	getResourcesReferencePages (ReportServiceGetResourcesReferencePages value) Returns the list of reference pages for the resources identified by the IDs.
ReportServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsers (ReportServiceGetResourcesWithVisibilityToUsers value) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ReportServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsers (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ReportServiceGetResourcesWithVisibilityToUsersResponse	getResourcesWithVisibilityToUsersPost (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ReportServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (ReportServiceGetResourceTypesVisibleToUsers value) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ReportServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ReportServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsersPost (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).

ReportServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (ReportServiceGetReverseRelationshipsOfParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ReportServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ReportServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ReportServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (ReportServiceGetReverseRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ReportServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ReportServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ReportServiceGetServiceMajorVersionResponse	getServiceMajorVersion (ReportServiceGetServiceMajorVersion value) The major version of this service.
ReportServiceGetServiceMajorVersionResponse	getServiceMajorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
ReportServiceGetServiceMajorVersionResponse	getServiceMajorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
ReportServiceGetServiceMinorVersionResponse	getServiceMinorVersion (ReportServiceGetServiceMinorVersion value) The minor version of this service.
ReportServiceGetServiceMinorVersionResponse	getServiceMinorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
ReportServiceGetServiceMinorVersionResponse	getServiceMinorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (ReportServiceGetSourcesWithThisTargetByACLRelationship value) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.

ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationshipPost (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByRelationshipResponse	getSourcesWithThisTargetByRelationship (ReportServiceGetSourcesWithThisTargetByRelationship value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse	getSourcesWithThisTargetByRelationshipCount (ReportServiceGetSourcesWithThisTargetByRelationshipCount value) Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (ReportServiceGetSourceURIWithThisTargetByRelationship value) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationship(S, int)</code> .
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use <code>getSourceURIWithThisTargetByRelationshipForResourceId(String, int)</code> .

ReportServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (ReportServiceGetSourceURIWithThisTargetByRelationship value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ReportServiceGetTargetsAsURIByRelationshipResponse	getTargetsAsURIByRelationship (ReportServiceGetTargetsAsURIByRelationship value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.
ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (ReportServiceGetTargetsAsURIByRelationshipForSourceId value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ReportServiceGetTargetsByRelationshipResponse	getTargetsByRelationship (ReportServiceGetTargetsByRelationship value) Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.
ReportServiceGetTargetsByRelationshipCountResponse	getTargetsByRelationshipCount (ReportServiceGetTargetsByRelationshipCount value) Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.
ReportServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (ReportServiceGetTargetsByRelationshipForSourceId value) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
ReportServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.

ReportServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
ReportServiceGetTargetsWithRelationshipTypeForResourceResponse	getTargetsWithRelationshipTypeForResource (ReportServiceGetTargetsWithRelationshipTypeForResource value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.
ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceById (ReportServiceGetTargetsWithRelationshipTypeForResourceById value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceByIdPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ReportServiceHasReadPermissionResponse	hasReadPermission (ReportServiceHasReadPermission value) Returns true if the source resource has Read permission on the target resource.
ReportServiceHasReadPermissionResponse	hasReadPermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
ReportServiceHasReadPermissionResponse	hasReadPermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
ReportServiceHasReverseRelationshipResponse	hasReverseRelationship (ReportServiceHasReverseRelationship value) Returns true if the relationship of the given target and source exists.
ReportServiceHasWritePermissionResponse	hasWritePermission (ReportServiceHasWritePermission value) Returns true if the source resource has Write permission on the target resource.
ReportServiceHasWritePermissionResponse	hasWritePermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
ReportServiceHasWritePermissionResponse	hasWritePermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
ReportServiceHasXPermissionResponse	hasXPermission (ReportServiceHasXPermission value) Returns true if the source resource has Execute (X) permission on the target resource.
ReportServiceHasXPermissionResponse	hasXPermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.

ReportServiceHasXPermissionResponse	hasXPermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
ReportServiceInsertResponse	insert (ReportServiceInsert value) Inserts the resource of the type S.
ReportServiceInsertResourceResponse	insertResource (ReportServiceInsertResource value) Inserts the resource of the type S into the specified group.
ReportServiceIsDisabledResponse	isDisabled (ReportServiceIsDisabled value) Returns true if the resource is disabled.
ReportServiceIsDisabledResponse	isDisabled (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
ReportServiceIsDisabledResponse	isDisabledPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
ReportServiceIsValidResourceIDResponse	isValidResourceID (ReportServiceIsValidResourceID value) Returns true if the resource with the given ID does exist in the database.
ReportServiceIsValidResourceIDResponse	isValidResourceID (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
ReportServiceIsValidResourceIDResponse	isValidResourceIDPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
Void	loadAdditional (ReportServiceLoadAdditional value) Loads fields into the given resource that had not previously been loaded.
Void	loadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	loadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	resetState (ReportServiceResetState value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	resetState (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	resetStatePost (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ReportServiceResolveRelationshipResponse	resolveRelationship (ReportServiceResolveRelationship value) Returns true if the specified relationship exists between the source and the target resources.

ReportServiceResolveRelationshipResponse	resolveRelationship (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
ReportServiceResolveRelationshipResponse	resolveRelationshipPost (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
Void	unloadAdditional (ReportServiceUnloadAdditional value) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
ReportServiceUpdateResponse	update (ReportServiceUpdate value) Updates the resource of the type S in the store.
Void	updateACLForResourceById (ReportServiceUpdateACLForResourceById value) Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder.
ReportServiceUpdateResourcesResponse	updateResources (ReportServiceUpdateResources value) Updates the resources of the type S in the database.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ReportServiceImpl

public **ReportServiceImpl**()

Methods

insert

public [ReportServiceInsertResponse](#) **insert**([ReportServiceInsert](#) value)
throws [ServiceException](#),
[AuthorizationException](#),
[AuthenticationException](#)

Inserts the resource of the type S. The system adds such required fields as resource ID if needed. The resource will be added to Unassigned group, and it's required that the current user has write permission to a Meta Group of the type S. So only a limited number of users can add and later access such new resources. Use another method, `insertResource(resource, parentId)` to create a new resource and add it to the group with the specified ID.

Parameters:

value - Model object containing request body

Returns:

The resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insertResource

```
public ReportServiceInsertResourceResponse insertResource(ReportServiceInsertResource  
value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Inserts the resource of the type S into the specified group.

Parameters:

value - Model object containing request body

Returns:

The inserted resource with the ID assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

delete

```
public Void delete(ReportServiceDelete value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Deletes the resource of the type S from the database.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findById

```
public ReportServiceFindByIdResponse findById(String authToken,  
        long localId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByIdPost

```
public ReportServiceFindByIdResponse findByIdPost(String authToken,  
        long localId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findById

```
public ReportServiceFindByIdResponse findById(ReportServiceFindById value)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUID

```
public ReportServiceFindByUUIDResponse findByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDv0vLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUIDPost

```
public ReportServiceFindByUUIDResponse findByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDv0vLA=="

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findByUUID

```
public ReportServiceFindByUUIDResponse findByUUID(ReportServiceFindByUUID value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiIDv0vLA=="

Parameters:

value - Model object containing request body

Returns:

The resource identified by the ID

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

update

```
public ReportServiceUpdateResponse update(ReportServiceUpdate value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Updates the resource of the type S in the store.

Parameters:

value - Model object containing request body

Returns:

The updated resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAlias

```
public ReportServiceContainsDirectMemberByNameOrAliasResponse
containsDirectMemberByNameOrAlias(String authToken,
    String groupId,
    String targetId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAliasPost

```
public ReportServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAliasPost(String authToken,  
    String groupId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsDirectMemberByNameOrAlias

```
public ReportServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAlias(ReportServiceContainsDirectMemberByNameOrAlias value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

value - Model object containing request body

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroup

```
public ReportServiceCopyResourceIntoGroupResponse copyResourceIntoGroup(String authToken,  
    String newName,  
    String resourceId,  
    String oldParentId,  
    String newParentId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroupPost

```
public ReportServiceCopyResourceIntoGroupResponse copyResourceIntoGroupPost(String
authToken,
    String newName,
    String resourceId,
    String oldParentId,
    String newParentId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

copyResourceIntoGroup

```
public ReportServiceCopyResourceIntoGroupResponse
copyResourceIntoGroup(ReportServiceCopyResourceIntoGroup value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

value - Model object containing request body

Returns:

The inserted resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResource

```
public Void deleteResource(ReportServiceDeleteResource value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource of the type S from the database. Method allows to specify whether to abort the transaction during conflicts in the validation.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalId

```
public Void deleteByLocalId(String authToken,
    long id,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalIdPost

```
public Void deleteByLocalIdPost(String authToken,
    long id,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByLocalId

```
public Void deleteByLocalId(ReportServiceDeleteByLocalId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUID

```
public Void deleteByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUIDPost

```
public Void deleteByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByUUID

```
public Void deleteByUUID(ReportServiceDeleteByUUID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResources

```
public Void deleteResources(ReportServiceDeleteResources value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resources of the type S from the database. Note that **nulls** in the list are not allowed

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIds

```
public ReportServiceFindAllIdsResponse findAllIds(String authToken,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resourcefindAllIds IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIdsPost

```
public ReportServiceFindAllIdsResponse findAllIdsPost(String authToken,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resourcefindAllIds IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findAllIds

```
public ReportServiceFindAllIdsResponse findAllIds(ReportServiceFindAllIds value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Finds and returns the list of IDs of all the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The list of the string values of IDs of the resources of type S. An empty list is returned if there is no resources of type S

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllAttachmentOnlyResourceIDs

```
public ReportServiceGetAllAttachmentOnlyResourceIDsResponse
getAllAttachmentOnlyResourceIDs(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
        AuthorizationException,
        AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session
 hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDsPost

```
public ReportServiceGetAllAttachmentOnlyResourceIDsResponse
getAllAttachmentOnlyResourceIDsPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
        AuthorizationException,
        AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllAttachmentOnlyResourceIDs

```
public ReportServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(ReportServiceGetAllAttachmentOnlyResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of the IDs of all attachments of the type S. Attachments are the resources that are not assigned to any group, but are assigned to a separate resource via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#) with the exception of [RelationshipTypes.IS_PARENT_OF](#).

Parameters:

value - Model object containing request body

Returns:

The list of the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllUnassignedResourceIDs\(\)](#)

getAllowedUserTypes

```
public ReportServiceGetAllowedUserTypesResponse getAllowedUserTypes(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllowedUserTypesPost

```
public ReportServiceGetAllowedUserTypesResponse getAllowedUserTypesPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllowedUserTypes

```
public ReportServiceGetAllowedUserTypesResponse  
getAllowedUserTypes(ReportServiceGetAllowedUserTypes value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

value - Model object containing request body

Returns:

The array of user types; see [User.UserTypeEnum](#).

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRoot

```
public ReportServiceGetAllPathsToRootResponse getAllPathsToRoot(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/0bdhibUYBABCAR4Qqlpgzcw=="

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootPost

```
public ReportServiceGetAllPathsToRootResponse getAllPathsToRootPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqIR1uw==/05CxZ+EUBABCA5fiIDvOvLA==/0bdhibUYBABCAR4Qqlpgzcw=="

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRoot

```
public ReportServiceGetAllPathsToRootResponse  
getAllPathsToRoot(ReportServiceGetAllPathsToRoot value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqR1uw==/05CxZ+EUBABCA5fiIDv0vLA==/0bDhibUYBABCAR4Qqlpgzcw=="

Parameters:

value - Model object containing request body

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStrings

```
public ReportServiceGetAllPathsToRootAsStringsResponse getAllPathsToRootAsStrings(String  
authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like "/All Cases/All Cases/Personal Cases/admin's Cases".

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStringsPost

```
public ReportServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStringsPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRootAsStrings

```
public ReportServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStrings(ReportServiceGetAllPathsToRootAsStrings value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`value` - Model object containing request body

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllUnassignedResourceIDs

```
public ReportServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDs(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDsPost

```
public ReportServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getAllUnassignedResourceIDs

```
public ReportServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDs(ReportServiceGetAllUnassignedResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of the IDs of all unassigned resources of the type S. Unassigned resources are those that are not attachments and not assigned to any group via relationships listed in the [RelationshipTypes.PERMISSION_INHERITANCE_RELATIONSHIPS](#).

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs which are not assigned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getAllAttachmentOnlyResourceIDs\(\)](#)

getChildNamesAndAliases

```
public ReportServiceGetChildNamesAndAliasesResponse  
getChildNamesAndAliases(ReportServiceGetChildNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. *This method is left for backward compatibility only. Please rather use method [getNamesAndAliases\(List\)](#)*

Returns the names and aliases of all of the resources with ID specified in childIds. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources.

The size of the returned list will always be $2 * n$ where n is the size of the childIds list. It is possible for some of the names to be missing, in which case **null** values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getNamesAndAliases

```
public ReportServiceGetNamesAndAliasesResponse  
getNamesAndAliases(ReportServiceGetNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources. The size of the returned list will always be 2 * n where n is the number of specified resource ID. It is possible for some of the names to be missing, in which case null values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResources

```
public ReportServiceGetCorruptedResourcesResponse getCorruptedResources(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, null is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResourcesPost

```
public ReportServiceGetCorruptedResourcesResponse getCorruptedResourcesPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCorruptedResources

```
public ReportServiceGetCorruptedResourcesResponse  
getCorruptedResources(ReportServiceGetCorruptedResources value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

value - Model object containing request body

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceId

```
public ReportServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceIdPost

```
public ReportServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceIdPost(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getDependentResourceIdsForResourceId

```
public ReportServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(ReportServiceGetDependentResourceIdsForResourceId  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getRelationshipsOfThisAndParents

```
public ReportServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getRelationshipsOfParents(String, int)`
`getReverseRelationshipsOfThisAndParents(String, int)`
`getReverseRelationshipsOfParents(String, int)`

getRelationshipsOfThisAndParentsPost

```
public ReportServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`getRelationshipsOfParents(String, int)`

```
getReverseRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfParents(String, int)
```

getRelationshipsOfThisAndParents

```
public ReportServiceGetRelationshipsOfThisAndParentsResponse
getRelationshipsOfThisAndParents(ReportServiceGetRelationshipsOfThisAndParents value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`value` - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getRelationshipsOfParents(String, int)`
`getReverseRelationshipsOfThisAndParents(String, int)`
`getReverseRelationshipsOfParents(String, int)`

getRelationshipsOfParents

```
public ReportServiceGetRelationshipsOfParentsResponse getRelationshipsOfParents(String
authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParentsPost

```
public ReportServiceGetRelationshipsOfParentsResponse  
getRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParents

```
public ReportServiceGetRelationshipsOfParentsResponse  
getRelationshipsOfParents(ReportServiceGetRelationshipsOfParents value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public ReportServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParentsPost

```
public ReportServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public ReportServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(ReportServiceGetReverseRelationshipsOfThisAndParents  
    value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public ReportServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParentsPost

```
public ReportServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public ReportServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(ReportServiceGetReverseRelationshipsOfParents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

value - Model object containing request body

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getEnabledResourceIDs

```
public ReportServiceGetEnabledResourceIDsResponse  
getEnabledResourceIDs(ReportServiceGetEnabledResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Checks the specified resources and returns the list of IDs of the resources that are enabled. The returned list is a subset of resourceIds. If all the specified resources are disabled then the method returns an empty list.

Parameters:

value - Model object containing request body

Returns:

The IDs of enabled resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getExclusivelyDependentResources

```
public ReportServiceGetExclusivelyDependentResourcesResponse  
getExclusivelyDependentResources(ReportServiceGetExclusivelyDependentResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resources depending on the given resource of the type S. This means that the given resource is the only path to root for those resources.

Parameters:

value - Model object containing request body

Returns:

List of resources that depend on the specified resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupID

```
public ReportServiceGetMetaGroupIDResponse getMetaGroupID(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupIDPost

```
public ReportServiceGetMetaGroupIDResponse getMetaGroupIDPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getMetaGroupID

```
public ReportServiceGetMetaGroupIDResponse getMetaGroupID(ReportServiceGetMetaGroupID  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the meta group for the resources of type S.

Parameters:

value - Model object containing request body

Returns:

The ID of the meta group. **Null** is returned if there is no meta group.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRoots

```
public ReportServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRootsPost

```
public ReportServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRootsPost(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

userId - The ID of the user for which we want to find personal and shared roots
relationshipType - Type of relationship to follow
authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalAndSharedResourceRoots

```
public ReportServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(ReportServiceGetPersonalAndSharedResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of personal and shared resource roots linked as targets to the specified user via the relations of the type relationshipType. Returned list contains only roots that directly linked to this resource (i.e. not inherited from groups) and the returned roots are of the type that matches the current service. For example, CaseService would return roots of the type Case. Regardless of service type, typically the method is called for a user with relationship types READ_PERMISSION or WRITE_PERMISSION. Personal roots are tree root resources that a user has direct links with via a relationship. Shared groups - These are the groups that a user has permission to read, but it is not a direct relationship See the list of available relationship types here [RelationshipTypes](#)

Parameters:

value - Model object containing request body

Returns:

The list of IDs of the root resources. An empty list, if there are no such roots.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroup

```
public ReportServiceGetPersonalGroupResponse getPersonalGroup(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

userId - The resource ID of the user
throwOnMissing - Whether or not an exception must be thrown if such a group is not found
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroupPost

```
public ReportServiceGetPersonalGroupResponse getPersonalGroupPost(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

`userId` - The resource ID of the user
`throwOnMissing` - Whether or not an exception must be thrown if such a group is not found
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the user is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalGroup

```
public ReportServiceGetPersonalGroupResponse  
getPersonalGroup(ReportServiceGetPersonalGroup value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the string value of ID of the user's personal group for the resources of type S. Personal groups are those groups that a user has direct Read/Write permissions to.

Parameters:

`value` - Model object containing request body

Returns:

The ID of the user's personal group for the resources of type S. If such a group is not found, `ServiceException` is thrown if `throwOnMissing` is set to true; otherwise, `null` is returned.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRoots

```
public ReportServiceGetPersonalResourceRootsResponse getPersonalResourceRoots(String  
authToken,  
    String resourceId,  
    int relationshipType,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

resourceId - The ID of the resource used as source in relations
relationshipType - The relationship type of the targets to the given resource
resourceType - NOT USED. The parameter is left for backward compatibility
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRootsPost

```
public ReportServiceGetPersonalResourceRootsResponse getPersonalResourceRootsPost(String  
authToken,  
    String resourceId,  
    int relationshipType,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

resourceId - The ID of the resource used as source in relations
relationshipType - The relationship type of the targets to the given resource
resourceType - NOT USED. The parameter is left for backward compatibility
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of target resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalResourceRoots

```
public ReportServiceGetPersonalResourceRootsResponse  
getPersonalResourceRoots(ReportServiceGetPersonalResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

For the specified resource, returns the list of personal resource roots linked to the resource as targets with relationshipType relations. The returned list contains only resources whose type match the selected service (e.g. CaseService, UserResourceService).

For example calling this method from GroupService for a Case resource would return Personal Groups associated with that Case as targets in relations of the type relationshipType. For available relationship types see [RelationshipTypes](#). Personal roots are tree root resources that this resource has direct links with via a relationship.

Parameters:

value - Model object containing request body

Returns:

The list of target resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesReferencePages

```
public ReportServiceGetResourcesReferencePagesResponse  
getResourcesReferencePages(ReportServiceGetResourcesReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resources identified by the IDs.

Parameters:

value - Model object containing request body

Returns:

A list of reference pages for the resources identified by the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePages

```
public ReportServiceGetReferencePagesResponse getReferencePages(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePagesPost

```
public ReportServiceGetReferencePagesResponse getReferencePagesPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getReferencePages

```
public ReportServiceGetReferencePagesResponse  
getReferencePages(ReportServiceGetReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

value - Model object containing request body

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByName

```
public ReportServiceGetResourceByNameResponse getResourceByName(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByNamePost

```
public ReportServiceGetResourceByNameResponse getResourceByNamePost(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceByName

```
public ReportServiceGetResourceByNameResponse  
getResourceByName(ReportServiceGetResourceByName value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

value - Model object containing request body

Returns:

The resource identified by the name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNames

```
public ReportServiceGetResourcesByNamesResponse  
getResourcesByNames(ReportServiceGetResourcesByNames value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified names. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.
If parameter names contains only one name, then the returned collection would contain all resources which have that name.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of names

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByIds

```
public ReportServiceGetResourcesByIdsResponse  
getResourcesByIds(ReportServiceGetResourcesByIds value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resources of the type S identified by the specified resource IDs. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafely

```
public ReportServiceGetResourcesByNameSafelyResponse getResourcesByNameSafely(String  
    authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafelyPost

```
public ReportServiceGetResourcesByNameSafelyResponse getResourcesByNameSafelyPost(String  
authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourcesByNameSafely

```
public ReportServiceGetResourcesByNameSafelyResponse  
getResourcesByNameSafely(ReportServiceGetResourcesByNameSafely value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

value - Model object containing request body

Returns:

The resources with the specified name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermission

```
public ReportServiceHasReadPermissionResponse hasReadPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermissionPost

```
public ReportServiceHasReadPermissionResponse hasReadPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.

targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasReadPermission

```
public ReportServiceHasReadPermissionResponse  
hasReadPermission(ReportServiceHasReadPermission value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermission

```
public ReportServiceHasWritePermissionResponse hasWritePermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermissionPost

```
public ReportServiceHasWritePermissionResponse hasWritePermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasWritePermission

```
public ReportServiceHasWritePermissionResponse  
hasWritePermission(ReportServiceHasWritePermission value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermission

```
public ReportServiceHasXPermissionResponse hasXPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermissionPost

```
public ReportServiceHasXPermissionResponse hasXPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasXPermission

```
public ReportServiceHasXPermissionResponse hasXPermission(ReportServiceHasXPermission  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabled

```
public ReportServiceIsDisabledResponse isDisabled(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabledPost

```
public ReportServiceIsDisabledResponse isDisabledPost(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isDisabled

```
public ReportServiceIsDisabledResponse isDisabled(ReportServiceIsDisabled value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceID

```
public ReportServiceIsValidResourceIDResponse isValidResourceID(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceIDPost

```
public ReportServiceIsValidResourceIDResponse isValidResourceIDPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isValidResourceID

```
public ReportServiceIsValidResourceIDResponse  
isValidResourceID(ReportServiceIsValidResourceID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

value - Model object containing request body

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

loadAdditional

```
public Void loadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

loadAdditionalPost

```
public Void loadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[unloadAdditional\(String\)](#)

loadAdditional

```
public Void loadAdditional(ReportServiceLoadAdditional value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

resetState

```
public Void resetState(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resetStatePost

```
public Void resetStatePost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

resetState

```
public Void resetState(ReportServiceResetState value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resolveRelationship

```
public ReportServiceResolveRelationshipResponse resolveRelationship(String authToken,
    String sourceId,
    String targetId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

resolveRelationshipPost

```
public ReportServiceResolveRelationshipResponse resolveRelationshipPost(String authToken,  
    String sourceId,  
    String targetId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

resolveRelationship

```
public ReportServiceResolveRelationshipResponse  
resolveRelationship(ReportServiceResolveRelationship value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

unloadAdditional

```
public Void unloadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

unloadAdditionalPost

```
public Void unloadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`loadAdditional(String)`

unloadAdditional

```
public Void unloadAdditional(ReportServiceUnloadAdditional value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

updateResources

```
public ReportServiceUpdateResourcesResponse updateResources(ReportServiceUpdateResources  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Updates the resources of the type S in the database. Resources are updated in different transactions. Method tries to update as many resources as possible. For all resources that failed to be updated error messages are logged on the server. Failed resources are not included in the returned collection. If the response does not include some of the submitted resources, then check server log-messages to find out why the update failed for them.

Parameters:

value - Model object containing request body

Returns:

The list of successfully updated resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceIfModified

```
public ReportServiceGetResourceIfModifiedResponse  
getResourceIfModified(ReportServiceGetResourceIfModified value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource if it is newer than the signature specifies; otherwise returns **null**.

Parameters:

value - Model object containing request body

Returns:

The resource with the specified ID if its modification count is bigger than the one in the signature; **null** otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceSignature](#)

getTargetsByRelationshipCount

```
public ReportServiceGetTargetsByRelationshipCountResponse  
getTargetsByRelationshipCount(ReportServiceGetTargetsByRelationshipCount value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationship

```
public ReportServiceGetTargetsByRelationshipResponse  
getTargetsByRelationship(ReportServiceGetTargetsByRelationship value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

hasReverseRelationship

```
public ReportServiceHasReverseRelationshipResponse  
hasReverseRelationship(ReportServiceHasReverseRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the relationship of the given target and source exists.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the given target and source exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipCount

```
public ReportServiceGetSourcesWithThisTargetByRelationshipCountResponse  
getSourcesWithThisTargetByRelationshipCount(ReportServiceGetSourcesWithThisTargetByRelationshipCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationship

```
public ReportServiceGetSourcesWithThisTargetByRelationshipResponse  
getSourcesWithThisTargetByRelationship(ReportServiceGetSourcesWithThisTargetByRelationship  
value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationship

```
public ReportServiceGetTargetsAsURIByRelationshipResponse  
getTargetsAsURIByRelationship(ReportServiceGetTargetsAsURIByRelationship value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnship

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipResponse  
getSourceURIWithThisTargetByRelatiobnship(ReportServiceGetSourceURIWithThisTargetByRelatiobnship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationship(S, int)`.

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationship

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipResponse  
getSourceURIWithThisTargetByRelationship(ReportServiceGetSourceURIWithThisTargetByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource URIs for all enabled resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public ReportServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceIdPost

```
public ReportServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public ReportServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(ReportServiceGetTargetsByRelationshipForSourceId  
value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(String authToken,  
String sourceResourceId,  
int relationshipType,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceIdPost

```
public ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public ReportServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(ReportServiceGetTargetsAsURIByRelationshipForSou  
rceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceIdPost

```
public ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public ReportServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(ReportServiceGetSourcesWithThisTargetByRelationshipForResourceId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnshipForResourceId

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelatiobnshipForResourceIdPost

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourceURIWithThisTargetByRelatiobnshipForResourceId

```
public ReportServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceId(ReportServiceGetSourceURIWithThisT  
argetByRelatiobnshipForResourceId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use*
getSourceURIWithThisTargetByRelationshipForResourceId(String, int).

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationshipForResourceId

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source

relationshipType - The id of the relationship type

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceIdPost

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public ReportServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(ReportServiceGetSourceURIWithThisTa  
rgetByRelationshipForResourceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByACLRelationship

```
public ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(String authToken,  
    String sourceResourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourcesWithThisTargetByACLRelationshipPost

```
public ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationshipPost(String authToken,  
    String sourceResourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourcesWithThisTargetByACLRelationship

```
public ReportServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(ReportServiceGetSourcesWithThisTargetByACLRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResource

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceResponse  
getTargetsWithRelationshipTypeForResource(ReportServiceGetTargetsWithRelationshipTypeForResource value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceById

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceByIdPost

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getTargetsWithRelationshipTypeForResourceById

```
public ReportServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(ReportServiceGetTargetsWithRelationshipTypeForResourceById value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateACLForResourceById

```
public Void updateACLForResourceById(ReportServiceUpdateACLForResourceById value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder. For every element from data, the method adds, removes, or updates the relationship between the resource and another resource with ID specified in ACLDataHolder.id. Every ACLDataHolder element also specifies whether it's for source or for target relationship ("forSourceRelationship"), identifier of the resource ("id"), and update type ("updateType").

The request is performed in a single transaction. If any of relations cannot be changed, then the entire transaction fails.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesWithVisibilityToUsers

```
public ReportServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsersPost

```
public ReportServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsers

```
public ReportServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(ReportServiceGetResourcesWithVisibilityToUsers value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public ReportServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsersPost

```
public ReportServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public ReportServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(ReportServiceGetResourceTypesVisibleToUsers value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceById

```
public ReportServiceGetResourceByIdResponse getResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByIdPost

```
public ReportServiceGetResourceByIdResponse getResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceById

```
public ReportServiceGetResourceByIdResponse getResourceById(ReportServiceGetResourceById  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

value - Model object containing request body

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addRelationship

```
public ReportServiceAddRelationshipResponse addRelationship(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource
`relationshipType` - The type of the relationship
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

addRelationshipPost

```
public ReportServiceAddRelationshipResponse addRelationshipPost(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource

relationshipType - The type of the relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

addRelationship

```
public ReportServiceAddRelationshipResponse addRelationship(ReportServiceAddRelationship  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds the relationship of the type relationshipType between specified target and source resources. There are no additional requirements on the types of the resources identified by sourceResourceId and targetResourceId.

Parameters:

value - Model object containing request body

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getESMVersion

```
public ReportServiceGetESMVersionResponse getESMVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getESMVersionPost

```
public ReportServiceGetESMVersionResponse getESMVersionPost(String authToken,  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getESMVersion

```
public ReportServiceGetESMVersionResponse getESMVersion(ReportServiceGetESMVersion value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

value - Model object containing request body

Returns:

Version of ESM

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersion

```
public ReportServiceGetServiceMajorVersionResponse getServiceMajorVersion(String
authToken,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersionPost

```
public ReportServiceGetServiceMajorVersionResponse getServiceMajorVersionPost(String
authToken,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMajorVersion

```
public ReportServiceGetServiceMajorVersionResponse
getServiceMajorVersion(ReportServiceGetServiceMajorVersion value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

The major version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersion

```
public ReportServiceGetServiceMinorVersionResponse getServiceMinorVersion(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersionPost

```
public ReportServiceGetServiceMinorVersionResponse getServiceMinorVersionPost(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMinorVersion

```
public ReportServiceGetServiceMinorVersionResponse  
getServiceMinorVersion(ReportServiceGetServiceMinorVersion value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

com.arcsight.product.manager.resource.service.v1.rest Class ResourceServiceImpl

java.lang.Object

└-com.arcsight.product.manager.resource.service.v1.rest.ResourceServiceImpl

public class **ResourceServiceImpl**
extends Object

An implementation of the DAO service that provides a user with an access to the ESM resources.

Constructor Summary

public	ResourceServiceImpl()

Method Summary

ResourceServiceAddRelationshipResponse	addRelationship (ResourceServiceAddRelationship value) Adds the relationship of the type relationshipType between specified target and source resources.
ResourceServiceAddRelationshipResponse	addRelationship (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
ResourceServiceAddRelationshipResponse	addRelationshipPost (String authToken, String sourceResourceId, String targetResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Adds the relationship of the type relationshipType between specified target and source resources.
ResourceServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (ResourceServiceContainsDirectMemberByNameOrAlias value) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ResourceServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAlias (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ResourceServiceContainsDirectMemberByNameOrAliasResponse	containsDirectMemberByNameOrAliasPost (String authToken, String groupId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource.
ResourceServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (ResourceServiceCopyResourceIntoGroup value) Creates a copy of the given resource of type S and inserts that resource into the given target group.

ResourceServiceCopyResourceIntoGroupResponse	copyResourceIntoGroup (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
ResourceServiceCopyResourceIntoGroupResponse	copyResourceIntoGroupPost (String authToken, String newName, String resourceId, String oldParentId, String newParentId, javax.ws.rs.core.HttpHeaders hh) Creates a copy of the given resource of type S and inserts that resource into the given target group.
Void	delete (ResourceServiceDelete value) Deletes the resource of the type S from the database.
Void	deleteByLocalId (ResourceServiceDeleteByLocalId value) Deletes the resource identified by the local ID.
Void	deleteByLocalId (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByLocalIdPost (String authToken, long id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the local ID.
Void	deleteByUUID (ResourceServiceDeleteByUUID value) Deletes the resource identified by the ID.
Void	deleteByUUID (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	deleteByUUIDPost (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Deletes the resource identified by the ID.
Void	deleteResource (ResourceServiceDeleteResource value) Deletes the resource of the type S from the database.
Void	deleteResources (ResourceServiceDeleteResources value) Deletes the resources of the type S from the database.
ResourceServiceFindAllIdsResponse	findAllIds (ResourceServiceFindAllIds value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceFindAllIdsResponse	findAllIds (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceFindAllIdsResponse	findAllIdsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceFindByIdResponse	findById (ResourceServiceFindById value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

ResourceServiceFindBy IdResponse	findById (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ResourceServiceFindBy IdResponse	findByIdPost (String authToken, long localId, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ResourceServiceFindBy UUIDResponse	findByIdUUID (ResourceServiceFindByUUID value) Returns the resource of the type S identified by its ID.
ResourceServiceFindBy UUIDResponse	findByIdUUID (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
ResourceServiceFindBy UUIDResponse	findByIdUUIDPost (String authToken, String id, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S identified by its ID.
ResourceServiceGetAll AttachmentOnlyResourc eIDsResponse	getAllAttachmentOnlyResourceIDs (ResourceServiceGetAllAttachmentOnlyResour ceIDs value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetAll AttachmentOnlyResourc eIDsResponse	getAllAttachmentOnlyResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetAll AttachmentOnlyResourc eIDsResponse	getAllAttachmentOnlyResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetAll owedUserTypesResponse	getAllowedUserTypes (ResourceServiceGetAllowedUserTypes value) Returns the array of user types that are allowed to access the service.
ResourceServiceGetAll owedUserTypesResponse	getAllowedUserTypes (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
ResourceServiceGetAll owedUserTypesResponse	getAllowedUserTypesPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the array of user types that are allowed to access the service.
ResourceServiceGetAll PathsToRootResponse	getAllPathsToRoot (ResourceServiceGetAllPathsToRoot value) Returns a list of all the paths to root relevant to the service for the given resource.
ResourceServiceGetAll PathsToRootResponse	getAllPathsToRoot (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
ResourceServiceGetAll PathsToRootAsStringsR esponse	getAllPathsToRootAsStrings (ResourceServiceGetAllPathsToRootAsStrings value) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
ResourceServiceGetAll PathsToRootAsStringsR esponse	getAllPathsToRootAsStrings (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.

ResourceServiceGetAllPathsToRootAsStringsResponse	getAllPathsToRootAsStringsPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of all paths (URIs) from the specified resource to the root relevant to the service.
ResourceServiceGetAllPathsToRootResponse	getAllPathsToRootPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of all the paths to root relevant to the service for the given resource.
ResourceServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (ResourceServiceGetAllUnassignedResourceIDs value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDs (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetAllUnassignedResourceIDsResponse	getAllUnassignedResourceIDsPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetChildNamesAndAliasesResponse	getChildNamesAndAliases (ResourceServiceGetChildNamesAndAliases value) Deprecated. This method is left for backward compatibility only. Please rather use method getNamesAndAliases (List)
ResourceServiceGetCorruptedResourcesResponse	getCorruptedResources (ResourceServiceGetCorruptedResources value) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ResourceServiceGetCorruptedResourcesResponse	getCorruptedResources (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ResourceServiceGetCorruptedResourcesResponse	getCorruptedResourcesPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the list of descriptors for all the corrupted resources of the corresponding type.
ResourceServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (ResourceServiceGetDependentResourceIDsForResourceId value) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ResourceServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceId (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ResourceServiceGetDependentResourceIDsForResourceIdResponse	getDependentResourceIDsForResourceIdPost (String authToken, String resourceId, boolean excludeHiddenResources, boolean excludeAttachmentOnlyResources, javax.ws.rs.core.HttpHeaders hh) Returns the list of the IDs of dependent resources for the specified resource of the type S.
ResourceServiceGetEnabledResourceIDsResponse	getEnabledResourceIDs (ResourceServiceGetEnabledResourceIDs value) Checks the specified resources and returns the list of IDs of the resources that are enabled.
ResourceServiceGetESMVersionResponse	getESMVersion (ResourceServiceGetESMVersion value) Returns the version of ESM manager.

ResourceServiceGetESMVersionResponse	getESMVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
ResourceServiceGetESMVersionResponse	getESMVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Returns the version of ESM manager.
ResourceServiceGetExclusivelyDependentResourcesResponse	getExclusivelyDependentResources (ResourceServiceGetExclusivelyDependentResources value) Returns a list of resources depending on the given resource of the type S.
ResourceServiceGetMetaGroupIDResponse	getMetaGroupID (ResourceServiceGetMetaGroupID value) Not supported by this service. Generic resource types do not have a meta group.
ResourceServiceGetMetaGroupIDResponse	getMetaGroupID (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Generic resource types do not have a meta group.
ResourceServiceGetMetaGroupIDResponse	getMetaGroupIDPost (String authToken, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Generic resource types do not have a meta group.
ResourceServiceGetNamesAndAliasesResponse	getNamesAndAliases (ResourceServiceGetNamesAndAliases value) Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds.
ResourceServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (ResourceServiceGetPersonalAndSharedResourceRoots value) Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user.
ResourceServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRoots (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user.
ResourceServiceGetPersonalAndSharedResourceRootsResponse	getPersonalAndSharedResourceRootsPost (String authToken, String userId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user.
ResourceServiceGetPersonalGroupResponse	getPersonalGroup (ResourceServiceGetPersonalGroup value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetPersonalGroupResponse	getPersonalGroup (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetPersonalGroupResponse	getPersonalGroupPost (String authToken, String userId, boolean throwOnMissing, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (ResourceServiceGetPersonalResourceRoots value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.

ResourceServiceGetPersonalResourceRootsResponse	getPersonalResourceRoots (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetPersonalResourceRootsResponse	getPersonalResourceRootsPost (String authToken, String resourceId, int relationshipType, int resourceType, javax.ws.rs.core.HttpHeaders hh) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceGetReferencePagesResponse	getReferencePages (ResourceServiceGetReferencePages value) Returns the list of reference pages for the resource identified by the ID.
ResourceServiceGetReferencePagesResponse	getReferencePages (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
ResourceServiceGetReferencePagesResponse	getReferencePagesPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the list of reference pages for the resource identified by the ID.
ResourceServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (ResourceServiceGetRelationshipsOfParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ResourceServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ResourceServiceGetRelationshipsOfParentsResponse	getRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource.
ResourceServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (ResourceServiceGetRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ResourceServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ResourceServiceGetRelationshipsOfThisAndParentsResponse	getRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents.
ResourceServiceGetResourceByIdResponse	getResourceById (ResourceServiceGetResourceById value) Returns the resource of the type S specified by resource ID.
ResourceServiceGetResourceByIdResponse	getResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.

<u>ResourceServiceGetResourceByIdResponse</u>	<u>getResourceByIdPost</u> (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns the resource of the type S specified by resource ID.
<u>ResourceServiceGetResourceByNameResponse</u>	<u>getResourceByName</u> (<u>ResourceServiceGetResourceByName</u> value) Returns one of the resources of the type S with the specified name.
<u>ResourceServiceGetResourceByNameResponse</u>	<u>getResourceByName</u> (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
<u>ResourceServiceGetResourceByNameResponse</u>	<u>getResourceByNamePost</u> (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns one of the resources of the type S with the specified name.
<u>ResourceServiceGetResourceIfModifiedResponse</u>	<u>getResourceIfModified</u> (<u>ResourceServiceGetResourceIfModified</u> value) Returns the resource if it is newer than the signature specifies; otherwise returns null .
<u>ResourceServiceGetResourcesByIdsResponse</u>	<u>getResourcesByIds</u> (<u>ResourceServiceGetResourcesByIds</u> value) Returns the resources of the type S identified by the specified resource IDs.
<u>ResourceServiceGetResourcesByNamesResponse</u>	<u>getResourcesByNames</u> (<u>ResourceServiceGetResourcesByNames</u> value) Returns all the resources of the type S with the specified names.
<u>ResourceServiceGetResourcesByNameSafelyResponse</u>	<u>getResourcesByNameSafely</u> (<u>ResourceServiceGetResourcesByNameSafely</u> value) Returns all the resources of the type S with the specified name.
<u>ResourceServiceGetResourcesByNameSafelyResponse</u>	<u>getResourcesByNameSafely</u> (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
<u>ResourceServiceGetResourcesByNameSafelyResponse</u>	<u>getResourcesByNameSafelyPost</u> (String authToken, String name, javax.ws.rs.core.HttpHeaders hh) Returns all the resources of the type S with the specified name.
<u>ResourceServiceGetResourcesReferencePagesResponse</u>	<u>getResourcesReferencePages</u> (<u>ResourceServiceGetResourcesReferencePages</u> value) Returns the list of reference pages for the resources identified by the IDs.
<u>ResourceServiceGetResourcesWithVisibilityToUsersResponse</u>	<u>getResourcesWithVisibilityToUsers</u> (<u>ResourceServiceGetResourcesWithVisibilityToUsers</u> value) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>ResourceServiceGetResourcesWithVisibilityToUsersResponse</u>	<u>getResourcesWithVisibilityToUsers</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
<u>ResourceServiceGetResourcesWithVisibilityToUsersResponse</u>	<u>getResourcesWithVisibilityToUsersPost</u> (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).

ResourceServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (ResourceServiceGetResourceTypesVisibleToUsers value) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ResourceServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsers (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ResourceServiceGetResourceTypesVisibleToUsersResponse	getResourceTypesVisibleToUsersPost (String authToken, javax.ws.rs.core.HttpHeaders hh) It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator).
ResourceServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (ResourceServiceGetReverseRelationshipsOfParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ResourceServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ResourceServiceGetReverseRelationshipsOfParentsResponse	getReverseRelationshipsOfParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.
ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (ResourceServiceGetReverseRelationshipsOfThisAndParents value) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParents (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse	getReverseRelationshipsOfThisAndParentsPost (String authToken, String sourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.
ResourceServiceGetServiceMajorVersionResponse	getServiceMajorVersion (ResourceServiceGetServiceMajorVersion value) The major version of this service.
ResourceServiceGetServiceMajorVersionResponse	getServiceMajorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
ResourceServiceGetServiceMajorVersionResponse	getServiceMajorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
ResourceServiceGetServiceMinorVersionResponse	getServiceMinorVersion (ResourceServiceGetServiceMinorVersion value) The minor version of this service.

ResourceServiceGetServiceMinorVersionResponse	getServiceMinorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
ResourceServiceGetServiceMinorVersionResponse	getServiceMinorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (ResourceServiceGetSourcesWithThisTargetByACLRelationship value) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationship (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse	getSourcesWithThisTargetByACLRelationshipPost (String authToken, String sourceResourceId, javax.ws.rs.core.HttpHeaders hh) It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByRelationshipResponse	getSourcesWithThisTargetByRelationship (ResourceServiceGetSourcesWithThisTargetByRelationship value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse	getSourcesWithThisTargetByRelationshipCount (ResourceServiceGetSourcesWithThisTargetByRelationshipCount value) Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId value) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse	getSourcesWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (ResourceServiceGetSourceURIWithThisTargetByRelationship value) Deprecated. This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationship(S, int) .
ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Deprecated. This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int) .

ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int) .
ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdPostResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Deprecated. This method will be removed as misspelled. Please use getSourceURIWithThisTargetByRelationshipForResourceId(String, int) .
ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse	getSourceURIWithThisTargetByRelationship (ResourceServiceGetSourceURIWithThisTargetByRelationship value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId value) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse	getSourceURIWithThisTargetByRelationshipForResourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdPostResponse	getSourceURIWithThisTargetByRelationshipForResourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.
ResourceServiceGetTargetsAsURIByRelationshipResponse	getTargetsAsURIByRelationship (ResourceServiceGetTargetsAsURIByRelationship value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.
ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (ResourceServiceGetTargetsAsURIByRelationshipForSourceId value) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse	getTargetsAsURIByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ResourceServiceGetTargetsAsURIByRelationshipForSourceIdPostResponse	getTargetsAsURIByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId.
ResourceServiceGetTargetsByRelationshipResponse	getTargetsByRelationship (ResourceServiceGetTargetsByRelationship value) Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.

ResourceServiceGetTargetsByRelationshipCountResponse	getTargetsByRelationshipCount (ResourceServiceGetTargetsByRelationshipCount value) Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource sourceResource.
ResourceServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (ResourceServiceGetTargetsByRelationshipForSourceId value) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
ResourceServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceId (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
ResourceServiceGetTargetsByRelationshipForSourceIdResponse	getTargetsByRelationshipForSourceIdPost (String authToken, String sourceResourceId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId.
ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse	getTargetsWithRelationshipTypeForResource (ResourceServiceGetTargetsWithRelationshipTypeForResource value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.
ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceById (ResourceServiceGetTargetsWithRelationshipTypeForResourceById value) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceById (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse	getTargetsWithRelationshipTypeForResourceByIdPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.
ResourceServiceHasReadPermissionResponse	hasReadPermission (ResourceServiceHasReadPermission value) Returns true if the source resource has Read permission on the target resource.
ResourceServiceHasReadPermissionResponse	hasReadPermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
ResourceServiceHasReadPermissionResponse	hasReadPermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Read permission on the target resource.
ResourceServiceHasReverseRelationshipResponse	hasReverseRelationship (ResourceServiceHasReverseRelationship value) Returns true if the relationship of the given target and source exists.
ResourceServiceHasWritePermissionResponse	hasWritePermission (ResourceServiceHasWritePermission value) Returns true if the source resource has Write permission on the target resource.

ResourceServiceHasWritePermissionResponse	hasWritePermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
ResourceServiceHasWritePermissionResponse	hasWritePermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Write permission on the target resource.
ResourceServiceHasXPermissionResponse	hasXPermission (ResourceServiceHasXPermission value) Returns true if the source resource has Execute (X) permission on the target resource.
ResourceServiceHasXPermissionResponse	hasXPermission (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
ResourceServiceHasXPermissionResponse	hasXPermissionPost (String authToken, String sourceId, String targetId, javax.ws.rs.core.HttpHeaders hh) Returns true if the source resource has Execute (X) permission on the target resource.
ResourceServiceInsertResponse	insert (ResourceServiceInsert value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceInsertResourceResponse	insertResource (ResourceServiceInsertResource value) Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type.
ResourceServiceIsDisabledResponse	isDisabled (ResourceServiceIsDisabled value) Returns true if the resource is disabled.
ResourceServiceIsDisabledResponse	isDisabled (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
ResourceServiceIsDisabledResponse	isDisabledPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource is disabled.
ResourceServiceIsValidResourceIDResponse	isValidResourceID (ResourceServiceIsValidResourceID value) Returns true if the resource with the given ID does exist in the database.
ResourceServiceIsValidResourceIDResponse	isValidResourceID (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
ResourceServiceIsValidResourceIDResponse	isValidResourceIDPost (String authToken, String resourceId, javax.ws.rs.core.HttpHeaders hh) Returns true if the resource with the given ID does exist in the database.
Void	loadAdditional (ResourceServiceLoadAdditional value) Loads fields into the given resource that had not previously been loaded.
Void	loadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.

Void	loadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Loads fields into the given resource that had not previously been loaded.
Void	resetState (ResourceServiceResetState value) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	resetState (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
Void	resetStatePost (String authToken, javax.ws.rs.core.HttpHeaders hh) TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!
ResourceServiceResolveRelationshipResponse	resolveRelationship (ResourceServiceResolveRelationship value) Returns true if the specified relationship exists between the source and the target resources.
ResourceServiceResolveRelationshipResponse	resolveRelationship (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
ResourceServiceResolveRelationshipResponse	resolveRelationshipPost (String authToken, String sourceId, String targetId, int relationshipType, javax.ws.rs.core.HttpHeaders hh) Returns true if the specified relationship exists between the source and the target resources.
Void	unloadAdditional (ResourceServiceUnloadAdditional value) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditional (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
Void	unloadAdditionalPost (String authToken, String sourceId, javax.ws.rs.core.HttpHeaders hh) Unloads any unnecessary fields of the resource that may have been loaded by a call to the loadAdditional(String) method.
ResourceServiceUpdateResponse	update (ResourceServiceUpdate value) Not supported by this service. Generic resource types do not support update of a given resource.
Void	updateACLForResourceById (ResourceServiceUpdateACLForResourceById value) Modifies relationships of the resource specified by resourceId with other resources specified in the list of ACLDataHolder.
ResourceServiceUpdateResourcesResponse	updateResources (ResourceServiceUpdateResources value) Not supported by this service. Generic resource types do not support updates of resources.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceServiceImpl

```
public ResourceServiceImpl()
```

Methods

getPersonalAndSharedResourceRoots

```
public ResourceServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user. Please use a service that matches the type of your Resource.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalAndSharedResourceRootsPost

```
public ResourceServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRootsPost(String authToken,  
    String userId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user. Please use a service that matches the type of your Resource.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalAndSharedResourceRoots

```
public ResourceServiceGetPersonalAndSharedResourceRootsResponse  
getPersonalAndSharedResourceRoots(ResourceServiceGetPersonalAndSharedResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Generic resource types do not support personal and shared resource roots for a given user. Please use a service that matches the type of your Resource.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

update

```
public ResourceServiceUpdateResponse update(ResourceServiceUpdate value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Generic resource types do not support update of a given resource. Please use a service that matches the type of your Resource.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateResources

```
public ResourceServiceUpdateResourcesResponse  
updateResources(ResourceServiceUpdateResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Generic resource types do not support updates of resources. Please use a service that matches the type of your Resource.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupID

```
public ResourceServiceGetMetaGroupIDResponse getMetaGroupID(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Generic resource types do not have a meta group. Please use a service that matches the type of your Resources For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getMetaGroupIDPost

```
public ResourceServiceGetMetaGroupIDResponse getMetaGroupIDPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Generic resource types do not have a meta group. Please use a service that matches the type of your Resources For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getMetaGroupID

```
public ResourceServiceGetMetaGroupIDResponse getMetaGroupID(ResourceServiceGetMetaGroupID  
value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Generic resource types do not have a meta group. Please use a service that matches the type of your Resources For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insert

```
public ResourceServiceInsertResponse insert(ResourceServiceInsert value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method insert is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

insertResource

```
public ResourceServiceInsertResourceResponse insertResource(ResourceServiceInsertResource
value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method insertResource is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllUnassignedResourceIDs

```
public ResourceServiceGetAllUnassignedResourceIDsResponse
getAllUnassignedResourceIDs(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllUnassignedResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllUnassignedResourceIDsPost

```
public ResourceServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllUnassignedResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllUnassignedResourceIDs

```
public ResourceServiceGetAllUnassignedResourceIDsResponse  
getAllUnassignedResourceIDs(ResourceServiceGetAllUnassignedResourceIDs value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllUnassignedResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIds

```
public ResourceServiceFindAllIdsResponse findAllIds(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method findAllIds is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findAllIdsPost

```
public ResourceServiceFindAllIdsResponse findAllIdsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method findAllIds is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findAllIds

```
public ResourceServiceFindAllIdsResponse findAllIds(ResourceServiceFindAllIds value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method findAllIds is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllAttachmentOnlyResourceIDs

```
public ResourceServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllAttachmentOnlyResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllAttachmentOnlyResourceIDsPost

```
public ResourceServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDsPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllAttachmentOnlyResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllAttachmentOnlyResourceIDs

```
public ResourceServiceGetAllAttachmentOnlyResourceIDsResponse  
getAllAttachmentOnlyResourceIDs(ResourceServiceGetAllAttachmentOnlyResourceIDs value)  
    throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```


Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getAllAttachmentOnlyResourceIDs is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroup

```
public ResourceServiceGetPersonalGroupResponse getPersonalGroup(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalGroup is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalGroupPost

```
public ResourceServiceGetPersonalGroupResponse getPersonalGroupPost(String authToken,  
    String userId,  
    boolean throwOnMissing,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalGroup is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalGroup

```
public ResourceServiceGetPersonalGroupResponse  
getPersonalGroup(ResourceServiceGetPersonalGroup value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalGroup is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRoots

```
public ResourceServiceGetPersonalResourceRootsResponse getPersonalResourceRoots(String  
authToken,  
    String resourceId,  
    int relationshipType,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalResourceRoots is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getPersonalResourceRootsPost

```
public ResourceServiceGetPersonalResourceRootsResponse  
getPersonalResourceRootsPost(String authToken,  
    String resourceId,  
    int relationshipType,  
    int resourceType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalResourceRoots is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getPersonalResourceRoots

```
public ResourceServiceGetPersonalResourceRootsResponse  
getPersonalResourceRoots(ResourceServiceGetPersonalResourceRoots value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Not supported by this service. Some actions cannot be performed by generic ResourceService, they need to use a specific resource type. Method getPersonalResourceRoots is one of them. Please use a service that matches the type of your Resources. For example, CaseService for getting Case meta group.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

delete

```
public Void delete(ResourceServiceDelete value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource of the type S from the database.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findById

```
public ResourceServiceFindByIdResponse findById(String authToken,  
        long localId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByIdPost

```
public ResourceServiceFindByIdResponse findByIdPost(String authToken,  
        long localId,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findById

```
public ResourceServiceFindByIdResponse findById(ResourceServiceFindById value)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUID

```
public ResourceServiceFindByUUIDResponse findByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here `id` is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

`id` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

findByUUIDPost

```
public ResourceServiceFindByUUIDResponse findByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S identified by its ID. Here `id` is the standard resource ID like "05CxZ+EUBABCA5fiIDvOvLA=="

Parameters:

`id` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The resource identified by the ID

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource (e.g. wrong resource type)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

findByUUID

```
public ResourceServiceFindByUUIDResponse findByUUID(ResourceServiceFindByUUID value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource of the type S identified by its ID. Here id is the standard resource ID like "05CxZ+EUBABCA5fiDvOvLA=="

Parameters:

value - Model object containing request body

Returns:

The resource identified by the ID

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAlias

```
public ResourceServiceContainsDirectMemberByNameOrAliasResponse
containsDirectMemberByNameOrAlias(String authToken,
    String groupId,
    String targetId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

containsDirectMemberByNameOrAliasPost

```
public ResourceServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAliasPost(String authToken,  
    String groupId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

groupId - The ID of the group
targetId - The ID of the target resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the group is not found, the target resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

containsDirectMemberByNameOrAlias

```
public ResourceServiceContainsDirectMemberByNameOrAliasResponse  
containsDirectMemberByNameOrAlias(ResourceServiceContainsDirectMemberByNameOrAlias value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the given group directly contains a member with the same name or the same alias (but a different ID) as the target resource. Otherwise, returns false.

Parameters:

value - Model object containing request body

Returns:

True if the group contains a resource with the same name or the same alias and this resource is not the target; otherwise, returns false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroup

```
public ResourceServiceCopyResourceIntoGroupResponse copyResourceIntoGroup(String
authToken,
    String newName,
    String resourceId,
    String oldParentId,
    String newParentId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

copyResourceIntoGroupPost

```
public ResourceServiceCopyResourceIntoGroupResponse copyResourceIntoGroupPost(String
authToken,
    String newName,
    String resourceId,
    String oldParentId,
    String newParentId,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

newName - The new name to give the resource
resourceId - The resource being copied
oldParentId - The parent group of the resource being copied
newParentId - The target parent group where the new resource will be stored
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The inserted resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the groups is not found, the original resource is not found, a naming conflict occurs or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

copyResourceIntoGroup

```
public ResourceServiceCopyResourceIntoGroupResponse  
copyResourceIntoGroup(ResourceServiceCopyResourceIntoGroup value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Creates a copy of the given resource of type S and inserts that resource into the given target group.

If value for newName is **null**, then the original name of the resource is attempted and transformed based upon whether there is already another resource in one of the parent groups with the same name. If the source and target groups are equal, then 'Copy of <Resource Name>' will be used. A zero-length string will be treated as a null string.

If the name is not **null**, then an exception is thrown upon any name conflicts.

Parameters:

value - Model object containing request body

Returns:

The inserted resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResource

```
public Void deleteResource(ResourceServiceDeleteResource value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource of the type S from the database. Method allows to specify whether to abort the transaction during conflicts in the validation.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalId

```
public Void deleteByLocalId(String authToken,  
    long id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByLocalIdPost

```
public Void deleteByLocalIdPost(String authToken,  
    long id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

resourceId - The local ID of the resource to delete
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByLocalId

```
public Void deleteByLocalId(ResourceServiceDeleteByLocalId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the local ID. Local IDs are internal ESM numbers used for optimization.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUID

```
public Void deleteByUUID(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteByUUIDPost

```
public Void deleteByUUIDPost(String authToken,  
    String id,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

id - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the deleting of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

deleteByUUID

```
public Void deleteByUUID(ResourceServiceDeleteByUUID value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resource identified by the ID.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

deleteResources

```
public Void deleteResources(ResourceServiceDeleteResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deletes the resources of the type S from the database. Note that **nulls** in the list are not allowed

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllowedUserTypes

```
public ResourceServiceGetAllowedUserTypesResponse getAllowedUserTypes(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User .UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllowedUserTypesPost

```
public ResourceServiceGetAllowedUserTypesResponse getAllowedUserTypesPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
        AuthorizationException,
        AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The array of user types; see [User .UserTypeEnum](#).

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the service call.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllowedUserTypes

```
public ResourceServiceGetAllowedUserTypesResponse getAllowedUserTypes(ResourceServiceGetAllowedUserTypes value)
    throws ServiceException,
        AuthorizationException,
        AuthenticationException
```

Returns the array of user types that are allowed to access the service.

Parameters:

value - Model object containing request body

Returns:

The array of user types; see [User .UserTypeEnum](#).

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRoot

```
public ResourceServiceGetAllPathsToRootResponse getAllPathsToRoot(String authToken,
    String resourceId,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
        AuthorizationException,
        AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqR1uw==/05CxZ+EUBABCA5filDvOvLA==/0bdhibUYBABCAR4Qqlpgzcw=="

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootPost

```
public ResourceServiceGetAllPathsToRootResponse getAllPathsToRootPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqR1uw==/05CxZ+EUBABCA5filDvOvLA==/0bdhibUYBABCAR4Qqlpgzcw=="

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource ID
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRoot

```
public ResourceServiceGetAllPathsToRootResponse  
getAllPathsToRoot(ResourceServiceGetAllPathsToRoot value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of all the paths to root relevant to the service for the given resource. Each element is a path from the resource with ID `resourceId` to the root and elements of the path are resource IDs on the nodes. Since resource could belong to different groups, there could be more than one path. For example:

"OAFPLmPsAABCAHBFLqR1uw==/05CxZ+EUBABCA5filDvOvLA==/0bdkhibUYBABCAR4Qqlpgzcw=="

Parameters:

`value` - Model object containing request body

Returns:

A list of all the paths to root for the given resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStrings

```
public ResourceServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStrings(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like "/All Cases/All Cases/Personal Cases/admin's Cases".

Parameters:

`resourceId` - The ID of the resource

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getAllPathsToRootAsStringsPost

```
public ResourceServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStringsPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`resourceId` - The ID of the resource
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the loading of the resource IDs
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getAllPathsToRootAsStrings

```
public ResourceServiceGetAllPathsToRootAsStringsResponse  
getAllPathsToRootAsStrings(ResourceServiceGetAllPathsToRootAsStrings value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the list of all paths (URIs) from the specified resource to the root relevant to the service. Each element is a path from the resource with ID `resourceId` to the root. Since resource could belong to different groups, there could be more than one path. A path could look like `"/All Cases/All Cases/Personal Cases/admin's Cases"`.

Parameters:

`value` - Model object containing request body

Returns:

The list of all paths to the root. An empty list if the root is not accessible from the specified resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getChildNamesAndAliases

```
public ResourceServiceGetChildNamesAndAliasesResponse  
getChildNamesAndAliases(ResourceServiceGetChildNamesAndAliases value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Deprecated. *This method is left for backward compatibility only. Please rather use method `getNamesAndAliases(List)`*

Returns the names and aliases of all of the resources with ID specified in `childIds`. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources.

The size of the returned list will always be $2 * n$ where n is the size of the `childIds` list. It is possible for some of the names to be missing, in which case `null` values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getNamesAndAliases

```
public ResourceServiceGetNamesAndAliasesResponse  
getNamesAndAliases(ResourceServiceGetNamesAndAliases value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the names and aliases of all of the resources of the type S with ID specified in resourceIds. If the resources are not already cached, then a query will be made to retrieve the names without loading the actual resources. The size of the returned list will always be 2 * n where n is the number of specified resource ID. It is possible for some of the names to be missing, in which case null values will be in the list (including the first half where the names are located)

Parameters:

value - Model object containing request body

Returns:

A list of the names followed by the aliases

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResources

```
public ResourceServiceGetCorruptedResourcesResponse getCorruptedResources(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, null is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getCorruptedResourcesPost

```
public ResourceServiceGetCorruptedResourcesResponse getCorruptedResourcesPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - if an exception occurred during the loading of the resources
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getCorruptedResources

```
public ResourceServiceGetCorruptedResourcesResponse
getCorruptedResources(ResourceServiceGetCorruptedResources value)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

Returns the list of descriptors for all the corrupted resources of the corresponding type.

Parameters:

value - Model object containing request body

Returns:

A list of CorruptedResource descriptors if there are any or empty list corrupted resources for this type; otherwise, **null** is returned

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceId

```
public ResourceServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getDependentResourceIdsForResourceIdPost

```
public ResourceServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceIdPost(String authToken,  
    String resourceId,  
    boolean excludeHiddenResources,  
    boolean excludeAttachmentOnlyResources,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

resourceId - The ID of the resource
excludeHiddenResources - If true, excludes the hidden resources
excludeAttachmentOnlyResources - Whether to exclude the dependent resources which are attachment resources only
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getDependentResourceIdsForResourceId

```
public ResourceServiceGetDependentResourceIdsForResourceIdResponse  
getDependentResourceIdsForResourceId(ResourceServiceGetDependentResourceIdsForResourceId  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of the IDs of dependent resources for the specified resource of the type S. This is different from just using the DEPENDS_ON relationship, because the method determines this by looking at various types of relationships such as IS_PARENT_OF, USES_RULE_FOR_REPLAY, HAS_VULNERABILITY and others. See more on available relationships here [RelationshipTypes](#).

If excludeAttachmentOnlyResources is true, excludes all of the dependent resources that are attachments that can only be reached through one of the requested resources.

There is a limit defined by the property "persist.resource.dependentids.fetch.max" with default value 2000. If the number of dependent resources is greater than the limit, then the returned collection will contain only part of such resources.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of dependent resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getRelationshipsOfThisAndParents

```
public ResourceServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`getRelationshipsOfParents(String, int)`
`getReverseRelationshipsOfThisAndParents(String, int)`
`getReverseRelationshipsOfParents(String, int)`

getRelationshipsOfThisAndParentsPost

```
public ResourceServiceGetRelationshipsOfThisAndParentsResponse  
getRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID `sourceId` and goes recursively through all its parents to collect resources that play role target for the relationship `relationshipType`. See [RelationshipTypes](#)

Parameters:

`sourceId` - The ID of the resource to start with
`relationshipType` - The relationship type to follow
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`getRelationshipsOfParents(String, int)`

```
getReverseRelationshipsOfThisAndParents(String, int)
getReverseRelationshipsOfParents(String, int)
```

getRelationshipsOfThisAndParents

```
public ResourceServiceGetRelationshipsOfThisAndParentsResponse
getRelationshipsOfThisAndParents(ResourceServiceGetRelationshipsOfThisAndParents value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is either the specified resource or any of its parents. Method starts with the resource with ID sourceId and goes recursively through all its parents to collect resources that play role target for the relationship relationshipType. See [RelationshipTypes](#)

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)

getRelationshipsOfParents

```
public ResourceServiceGetRelationshipsOfParentsResponse getRelationshipsOfParents(String
authToken,
    String sourceId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParentsPost

```
public ResourceServiceGetRelationshipsOfParentsResponse  
getRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getRelationshipsOfParents

```
public ResourceServiceGetRelationshipsOfParentsResponse  
getRelationshipsOfParents(ResourceServiceGetRelationshipsOfParents value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets for the specified relationship where the source is any of the parents of the specified resource. Please note that the method doesn't retrieve the targets of the resource itself, only of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the resource IDs. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getReverseRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParentsPost

```
public ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfThisAndParents

```
public ResourceServiceGetReverseRelationshipsOfThisAndParentsResponse  
getReverseRelationshipsOfThisAndParents(ResourceServiceGetReverseRelationshipsOfThisAndPa  
rents value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is either the specified resource or any of its parents.

Parameters:

value - Model object containing request body

Returns:

The list of the IDs of source resources. An empty list if there are no such resources.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public ResourceServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParentsPost

```
public ResourceServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParentsPost(String authToken,  
    String sourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

sourceId - The ID of the resource to start with
relationshipType - The relationship type to follow
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the source resource is not found or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getReverseRelationshipsOfParents

```
public ResourceServiceGetReverseRelationshipsOfParentsResponse  
getReverseRelationshipsOfParents(ResourceServiceGetReverseRelationshipsOfParents value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are sources for the specified relationship where the target is any of the parents of the specified resource.

Parameters:

value - Model object containing request body

Returns:

The list of string values of the IDs related to all the ancestors of the source resource. An empty list if there are no such resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[getReverseRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfThisAndParents\(String, int\)](#)
[getRelationshipsOfParents\(String, int\)](#)
[RelationshipTypes](#)

getEnabledResourceIDs

```
public ResourceServiceGetEnabledResourceIDsResponse  
getEnabledResourceIDs(ResourceServiceGetEnabledResourceIDs value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Checks the specified resources and returns the list of IDs of the resources that are enabled. The returned list is a subset of resourceIds. If all the specified resources are disabled then the method returns an empty list.

Parameters:

value - Model object containing request body

Returns:

The IDs of enabled resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getExclusivelyDependentResources

```
public ResourceServiceGetExclusivelyDependentResourcesResponse  
getExclusivelyDependentResources(ResourceServiceGetExclusivelyDependentResources value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resources depending on the given resource of the type S. This means that the given resource is the only path to root for those resources.

Parameters:

value - Model object containing request body

Returns:

List of resources that depend on the specified resources

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesReferencePages

```
public ResourceServiceGetResourcesReferencePagesResponse  
getResourcesReferencePages(ResourceServiceGetResourcesReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resources identified by the IDs.

Parameters:

value - Model object containing request body

Returns:

A list of reference pages for the resources identified by the IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePages

```
public ResourceServiceGetReferencePagesResponse getReferencePages(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getReferencePagesPost

```
public ResourceServiceGetReferencePagesResponse getReferencePagesPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If no resource with the specified ID is found or an exception occurred during the loading of the reference pages
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getReferencePages

```
public ResourceServiceGetReferencePagesResponse  
getReferencePages(ResourceServiceGetReferencePages value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the list of reference pages for the resource identified by the ID.

Parameters:

value - Model object containing request body

Returns:

The list of ReferencePage objects; an empty list if none were found

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByName

```
public ResourceServiceGetResourceByNameResponse getResourceByName(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByNamePost

```
public ResourceServiceGetResourceByNameResponse getResourceByNamePost(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource identified by the name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found or an exception occurred during the loading of the resource
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceByName

```
public ResourceServiceGetResourceByNameResponse  
getResourceByName(ResourceServiceGetResourceByName value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns one of the resources of the type S with the specified name. There could be more than one resource with the same name. This method returns one of such resources and each time it could be a different resource.

Parameters:

value - Model object containing request body

Returns:

The resource identified by the name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNames

```
public ResourceServiceGetResourcesByNamesResponse  
getResourcesByNames(ResourceServiceGetResourcesByNames value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified names. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.
If parameter names contains only one name, then the returned collection would contain all resources which have that name.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of names

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByIds

```
public ResourceServiceGetResourcesByIdsResponse  
getResourcesByIds(ResourceServiceGetResourcesByIds value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resources of the type S identified by the specified resource IDs. The whole request fails if there are problems to retrieve even one of the resources. Troubled resources could be identified by returned exception.

Parameters:

value - Model object containing request body

Returns:

The list of the resources identified by the specified list of IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafely

```
public ResourceServiceGetResourcesByNameSafelyResponse getResourcesByNameSafely(String  
    authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesByNameSafelyPost

```
public ResourceServiceGetResourcesByNameSafelyResponse  
getResourcesByNameSafelyPost(String authToken,  
    String name,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

name - The name of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resources with the specified name

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during accessing database
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourcesByNameSafely

```
public ResourceServiceGetResourcesByNameSafelyResponse  
getResourcesByNameSafely(ResourceServiceGetResourcesByNameSafely value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns all the resources of the type S with the specified name. Method guarantees that there won't be an exception thrown if there are no requested resources. The returned collection contains only resources that were successfully retrieved by ESM and converted without problems into service-layer objects.

Parameters:

value - Model object containing request body

Returns:

The resources with the specified name

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermission

```
public ResourceServiceHasReadPermissionResponse hasReadPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasReadPermissionPost

```
public ResourceServiceHasReadPermissionResponse hasReadPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasReadPermission

```
public ResourceServiceHasReadPermissionResponse  
hasReadPermission(ResourceServiceHasReadPermission value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Read permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can read the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermission

```
public ResourceServiceHasWritePermissionResponse hasWritePermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasWritePermissionPost

```
public ResourceServiceHasWritePermissionResponse hasWritePermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasWritePermission

```
public ResourceServiceHasWritePermissionResponse  
hasWritePermission(ResourceServiceHasWritePermission value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Write permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can update the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermission

```
public ResourceServiceHasXPermissionResponse hasXPermission(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

hasXPermissionPost

```
public ResourceServiceHasXPermissionResponse hasXPermissionPost(String authToken,  
    String sourceId,  
    String targetId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceId - The ID of the source resource.
targetId - The ID of the target resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

hasXPermission

```
public ResourceServiceHasXPermissionResponse hasXPermission(ResourceServiceHasXPermission  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the source resource has Execute (X) permission on the target resource. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the source can execute the target; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabled

```
public ResourceServiceIsDisabledResponse isDisabled(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isDisabledPost

```
public ResourceServiceIsDisabledResponse isDisabledPost(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The ID of the resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isDisabled

```
public ResourceServiceIsDisabledResponse isDisabled(ResourceServiceIsDisabled value)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource is disabled. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

True if the resource is disabled; false otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceID

```
public ResourceServiceIsValidResourceIDResponse isValidResourceID(String authToken,  
String resourceId,  
javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
AuthorizationException,  
AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

isValidResourceIDPost

```
public ResourceServiceIsValidResourceIDResponse isValidResourceIDPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

resourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

isValidResourceID

```
public ResourceServiceIsValidResourceIDResponse  
isValidResourceID(ResourceServiceIsValidResourceID value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns true if the resource with the given ID does exist in the database.

Parameters:

value - Model object containing request body

Returns:

True if the resource exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

loadAdditional

```
public Void loadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

loadAdditionalPost

```
public Void loadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

sourceId - The ID of the resource.
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[unloadAdditional\(String\)](#)

loadAdditional

```
public Void loadAdditional(ResourceServiceLoadAdditional value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Loads fields into the given resource that had not previously been loaded. This is for fields that are not loaded into resources by default.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[unloadAdditional\(String\)](#)

resetState

```
public Void resetState(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resetStatePost

```
public Void resetStatePost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

resetState

```
public Void resetState(ResourceServiceResetState value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

TODO: DOCUMENT THIS METHOD in the correspondent interface or class !!!

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

resolveRelationship

```
public ResourceServiceResolveRelationshipResponse resolveRelationship(String authToken,
    String sourceId,
    String targetId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

resolveRelationshipPost

```
public ResourceServiceResolveRelationshipResponse resolveRelationshipPost(String
authToken,
    String sourceId,
    String targetId,
    int relationshipType,
    javax.ws.rs.core.HttpHeaders hh)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

sourceId - The ID of the source resource
targetId - The ID of the target resource
relationshipType - The relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any of the resources is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

resolveRelationship

```
public ResourceServiceResolveRelationshipResponse
resolveRelationship(ResourceServiceResolveRelationship value)
throws ServiceException,
AuthorizationException,
AuthenticationException
```

Returns true if the specified relationship exists between the source and the target resources.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the specified type exists; otherwise, false

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

unloadAdditional

```
public Void unloadAdditional(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

`sourceId` - The ID of the resource.
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

unloadAdditionalPost

```
public Void unloadAdditionalPost(String authToken,  
    String sourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

`sourceId` - The ID of the resource.
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

`loadAdditional(String)`

unloadAdditional

```
public Void unloadAdditional(ResourceServiceUnloadAdditional value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Unloads any unnecessary fields of the resource that may have been loaded by a call to the `loadAdditional(String)` method.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

`loadAdditional(String)`

getResourceIfModified

```
public ResourceServiceGetResourceIfModifiedResponse
getResourceIfModified(ResourceServiceGetResourceIfModified value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the resource if it is newer than the signature specifies; otherwise returns **null**.

Parameters:

value - Model object containing request body

Returns:

The resource with the specified ID if its modification count is bigger than the one in the signature; **null** otherwise

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceSignature](#)

getTargetsByRelationshipCount

```
public ResourceServiceGetTargetsByRelationshipCountResponse
getTargetsByRelationshipCount(ResourceServiceGetTargetsByRelationshipCount value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the number of all enabled resources that are targets in the relationships of the specified type for the resource `sourceResource`.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationship

```
public ResourceServiceGetTargetsByRelationshipResponse  
getTargetsByRelationship(ResourceServiceGetTargetsByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationships of the specified type for the resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

hasReverseRelationship

```
public ResourceServiceHasReverseRelationshipResponse  
hasReverseRelationship(ResourceServiceHasReverseRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns true if the relationship of the given target and source exists.

Parameters:

value - Model object containing request body

Returns:

True if the relationship of the given target and source exists; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipCount

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipCountResponse  
getSourcesWithThisTargetByRelationshipCount(ResourceServiceGetSourcesWithThisTargetByRelationshipCount value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the number of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

The number of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationship

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipResponse  
getSourcesWithThisTargetByRelationship(ResourceServiceGetSourcesWithThisTargetByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationship

```
public ResourceServiceGetTargetsAsURIByRelationshipResponse  
getTargetsAsURIByRelationship(ResourceServiceGetTargetsAsURIByRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource sourceResource.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnship

```
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipResponse  
getSourceURIWithThisTargetByRelatiobnship(ResourceServiceGetSourceURIWithThisTargetByRelatiobnship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationship(S, int)`.

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationship

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipResponse  
getSourceURIWithThisTargetByRelationship(ResourceServiceGetSourceURIWithThisTargetByRelationship  
    value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target.

Parameters:

value - Model object containing request body

Returns:

A list of resource URIs for all enabled resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public ResourceServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceIdPost

```
public ResourceServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - The type of relationship
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsByRelationshipForSourceId

```
public ResourceServiceGetTargetsByRelationshipForSourceIdResponse  
getTargetsByRelationshipForSourceId(ResourceServiceGetTargetsByRelationshipForSourceId  
value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of IDs of all resources that are targets in the relationship of the specified type for the resource with the ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceIdPost

```
public ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
relationshipType - Type of relationship that must exist between specified source and expected targets

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of Resource URIs

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getTargetsAsURIByRelationshipForSourceId

```
public ResourceServiceGetTargetsAsURIByRelationshipForSourceIdResponse  
getTargetsAsURIByRelationshipForSourceId(ResourceServiceGetTargetsAsURIByRelationshipForS  
ourceId value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of Resource URIs for all resources that are targets in the relationship of the specified type relationshipType with the source resource with ID sourceResourceId. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of Resource URIs

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceIdPost

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByRelationshipForResourceId

```
public ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceIdResponse  
getSourcesWithThisTargetByRelationshipForResourceId(ResourceServiceGetSourcesWithThisTargetByRelationshipForResourceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource IDs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

A list of resource IDs for all resources that are sources for the specified type of relationship with this resource as a target.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelatiobnshipForResourceId

```
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. *This method will be removed as misspelled. Please use `getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.*

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelatiobnshipForResourceIdPost

```
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use
`getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.

Parameters:

sourceResourceId
relationshipType
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourceURIWithThisTargetByRelatiobnshipForResourceId

```
public ResourceServiceGetSourceURIWithThisTargetByRelatiobnshipForResourceIdResponse  
getSourceURIWithThisTargetByRelatiobnshipForResourceId(ResourceServiceGetSourceURIWithThi  
sTargetByRelatiobnshipForResourceId value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Deprecated. This method will be removed as misspelled. Please use
`getSourceURIWithThisTargetByRelationshipForResourceId(String, int)`.

Parameters:

value - Model object containing request body

Returns:

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourceURIWithThisTargetByRelationshipForResourceId

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceIdPost

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceIdPost(String authToken,  
    String sourceResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The resource ID of the source
relationshipType - The id of the relationship type
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

getSourceURIWithThisTargetByRelationshipForResourceId

```
public ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceIdResponse  
getSourceURIWithThisTargetByRelationshipForResourceId(ResourceServiceGetSourceURIWithThisTargetByRelationshipForResourceId value)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

Returns a list of resource URIs for all resources that are sources of the specified relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource URIs' for all resources that are sources of the specified relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getSourcesWithThisTargetByACLRelationship

```
public ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(String authToken,  
      String sourceResourceId,  
      javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
       AuthorizationException,  
       AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSourcesWithThisTargetByACLRelationshipPost

```
public ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationshipPost(String authToken,  
        String sourceResourceId,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

sourceResourceId - The ID of source resource
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getSourcesWithThisTargetByACLRelationship

```
public ResourceServiceGetSourcesWithThisTargetByACLRelationshipResponse  
getSourcesWithThisTargetByACLRelationship(ResourceServiceGetSourcesWithThisTargetByACLRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns a list of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are sources of the ACL relationship with this resource as a target

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResource

```
public ResourceServiceGetTargetsWithRelationshipTypeForResourceResponse  
getTargetsWithRelationshipTypeForResource(ResourceServiceGetTargetsWithRelationshipTypeFo  
rResource value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceById

```
public ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(String authToken,  
        String resourceId,  
        javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getTargetsWithRelationshipTypeForResourceByIdPost

```
public ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

resourceId - The resource ID of source
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getTargetsWithRelationshipTypeForResourceById

```
public ResourceServiceGetTargetsWithRelationshipTypeForResourceByIdResponse  
getTargetsWithRelationshipTypeForResourceById(ResourceServiceGetTargetsWithRelationshipTy  
peForResourceById value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns a list of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID. The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of resource ACLDataHolders for all resources that are targets of the ACL relationship with this resource specified by resource ID.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

updateACLForResourceById

```
public Void updateACLForResourceById(ResourceServiceUpdateACLForResourceById value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Modifies relationships of the resource specified by `resourceId` with other resources specified in the list of `ACLDataHolder`. For every element from data, the method adds, removes, or updates the relationship between the resource and another resource with ID specified in `ACLDataHolder.id`. Every `ACLDataHolder` element also specifies whether it's for source or for target relationship ("forSourceRelationship"), identifier of the resource ("id"), and update type ("updateType").

The request is performed in a single transaction. If any of relations cannot be changed, then the entire transaction fails.

Parameters:

`value` - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourcesWithVisibilityToUsers

```
public ResourceServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

`authToken` - Authentication token created for the current session

`hh` - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsersPost

```
public ResourceServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If an exception occurred during the resource processing
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourcesWithVisibilityToUsers

```
public ResourceServiceGetResourcesWithVisibilityToUsersResponse  
getResourcesWithVisibilityToUsers(ResourceServiceGetResourcesWithVisibilityToUsers value)  
    throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource type names, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type names which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public ResourceServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsersPost

```
public ResourceServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsersPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.tools.coma.service.ServiceException](#)
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[ResourceTypes](#)

getResourceTypesVisibleToUsers

```
public ResourceServiceGetResourceTypesVisibleToUsersResponse  
getResourceTypesVisibleToUsers(ResourceServiceGetResourceTypesVisibleToUsers value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

It returns the list of the resource types, which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator). The result doesn't depend on the service type, this method returns the same data for all services.

Parameters:

value - Model object containing request body

Returns:

List of the resource type IDs which are the first class and visible to the browsing interfaces (such as the ArcSight Console Navigator)

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[ResourceTypes](#)

getResourceById

```
public ResourceServiceGetResourceByIdResponse getResourceById(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getResourceByIdPost

```
public ResourceServiceGetResourceByIdResponse getResourceByIdPost(String authToken,  
    String resourceId,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

resourceId - The resource ID
authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getResourceById

```
public ResourceServiceGetResourceByIdResponse  
getResourceById(ResourceServiceGetResourceById value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Returns the resource of the type S specified by resource ID.

Parameters:

value - Model object containing request body

Returns:

The resource specified by resourceId

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

addRelationship

```
public ResourceServiceAddRelationshipResponse addRelationship(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource
`relationshipType` - The type of the relationship
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

addRelationshipPost

```
public ResourceServiceAddRelationshipResponse addRelationshipPost(String authToken,  
    String sourceResourceId,  
    String targetResourceId,  
    int relationshipType,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

`sourceResourceId` - The ID of the source resource
`targetResourceId` - The ID of the target resource
`relationshipType` - The type of the relationship
`authToken` - Authentication token created for the current session
`hh` - HTTP headers from http request

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If the resource is not found, or an exception occurred during the resource processing.
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

See Also:

[RelationshipTypes](#)

addRelationship

```
public ResourceServiceAddRelationshipResponse  
addRelationship(ResourceServiceAddRelationship value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Adds the relationship of the type `relationshipType` between specified target and source resources. There are no additional requirements on the types of the resources identified by `sourceResourceId` and `targetResourceId`.

Parameters:

value - Model object containing request body

Returns:

True if the relationship is added successfully; otherwise, false.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

[RelationshipTypes](#)

getESMVersion

```
public ResourceServiceGetESMVersionResponse getESMVersion(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getESMVersionPost

```
public ResourceServiceGetESMVersionResponse getESMVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Returns:

Version of ESM

Throws:

[com.arcsight.tools.coma.service.ServiceException](#) - If any exception happened during execution of this call
[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getESMVersion

```
public ResourceServiceGetESMVersionResponse getESMVersion(ResourceServiceGetESMVersion  
value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the version of ESM manager. For example 6.8.0.24151.0

Parameters:

value - Model object containing request body

Returns:

Version of ESM

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersion

```
public ResourceServiceGetServiceMajorVersionResponse getServiceMajorVersion(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersionPost

```
public ResourceServiceGetServiceMajorVersionResponse getServiceMajorVersionPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMajorVersion

```
public ResourceServiceGetServiceMajorVersionResponse
getServiceMajorVersion(ResourceServiceGetServiceMajorVersion value)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

The major version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersion

```
public ResourceServiceGetServiceMinorVersionResponse getServiceMinorVersion(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
    AuthorizationException,
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersionPost

```
public ResourceServiceGetServiceMinorVersionResponse getServiceMinorVersionPost(String authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMinorVersion

```
public ResourceServiceGetServiceMinorVersionResponse  
getServiceMinorVersion(ResourceServiceGetServiceMinorVersion value)  
throws ServiceException,  
    AuthorizationException,  
    AuthenticationException
```

The minor version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

com.arcsight.product.manager.resource.service.v1.rest

Class SecurityEventServiceImpl

java.lang.Object

↳ com.arcsight.product.manager.resource.service.v1.rest.SecurityEventServiceImpl

public class **SecurityEventServiceImpl**
extends Object

The implementation of SecurityEventService.

Constructor Summary

public	SecurityEventServiceImpl()

Method Summary

SecurityEventServiceCountResponse	count (SecurityEventServiceCount value) Returns the number of events and correlation events within the specified time limit
SecurityEventServiceCountResponse	count (String authToken, long startTime, long endTime, javax.ws.rs.core.HttpHeaders hh) Returns the number of events and correlation events within the specified time limit
SecurityEventServiceCountResponse	countPost (String authToken, long startTime, long endTime, javax.ws.rs.core.HttpHeaders hh) Returns the number of events and correlation events within the specified time limit
SecurityEventServiceGetSecurityEventsResponse	getSecurityEvents (SecurityEventServiceGetSecurityEvents value) Returns the events specified by the IDs and within specified time limits.
SecurityEventServiceGetSecurityEventsByProfileResponse	getSecurityEventsByProfile (SecurityEventServiceGetSecurityEventsByProfile value) Returns the events specified by the IDs and within specified time limits.
SecurityEventServiceGetSecurityEventsWithTimeoutResponse	getSecurityEventsWithTimeout (SecurityEventServiceGetSecurityEventsWithTimeout value) Returns the events specified by the IDs and within specified time limits.
SecurityEventServiceGetServiceMajorVersionResponse	getServiceMajorVersion (SecurityEventServiceGetServiceMajorVersion value) The major version of this service.
SecurityEventServiceGetServiceMajorVersionResponse	getServiceMajorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.
SecurityEventServiceGetServiceMajorVersionResponse	getServiceMajorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The major version of this service.

SecurityEventServiceGetServiceMinorVersionResponse	getServiceMinorVersion (SecurityEventServiceGetServiceMinorVersion value) The minor version of this service.
SecurityEventServiceGetServiceMinorVersionResponse	getServiceMinorVersion (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
SecurityEventServiceGetServiceMinorVersionResponse	getServiceMinorVersionPost (String authToken, javax.ws.rs.core.HttpHeaders hh) The minor version of this service.
Void	setAnnotationStage (SecurityEventServiceSetAnnotationStage value) Changes the current stage of event's annotation (e.g.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

SecurityEventServiceImpl

```
public SecurityEventServiceImpl()
```

Methods

getSecurityEvents

```
public SecurityEventServiceGetSecurityEventsResponse
getSecurityEvents(SecurityEventServiceGetSecurityEvents value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the events specified by the IDs and within specified time limits. To specify time restriction you would need to provide the range by entering the milliseconds for `startMillis` and `endMillis` and choose time field (for example `FIELD_START_TIME` (`fieldIndex=5`), `FIELD_END_TIME` (`fieldIndex=6`)) for which the restrictions will be applied. If `timeField` is not specified, then the limits will be applied to `FIELD_END_TIME`

Parameters:

`value` - Model object containing request body

Returns:

The events specified by the IDs.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

See Also:

The method returns only events for which the current User has permissions, which is enforced by event filters.

getSecurityEventsByProfile

```
public SecurityEventServiceGetSecurityEventsByProfileResponse  
getSecurityEventsByProfile(SecurityEventServiceGetSecurityEventsByProfile value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the events specified by the IDs and within specified time limits. The method returns only events for which the current User has permissions, which is enforced by event filters.

Parameters:

value - Model object containing request body

Returns:

The events specified by the IDs.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getSecurityEventsWithTimeout

```
public SecurityEventServiceGetSecurityEventsWithTimeoutResponse  
getSecurityEventsWithTimeout(SecurityEventServiceGetSecurityEventsWithTimeout value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Returns the events specified by the IDs and within specified time limits. The method returns only events for which the current User has permissions, which is enforced by event filters.

Parameters:

value - Model object containing request body

Returns:

the events specified by the IDs.

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

setAnnotationStage

```
public Void setAnnotationStage(SecurityEventServiceSetAnnotationStage value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

Changes the current stage of event's annotation (e.g. from Monitoring to Follow-Up, or to Final). Note that the new stage should be compliant with stage transition rules that define allowed transitions between stages.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

count

```
public SecurityEventServiceCountResponse count(String authToken,  
        long startTime,  
        long endTime,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the number of events and correlation events within the specified time limit

Parameters:

startTime -- The beginning of time range in epoch millis

endTime -- The end of time range in epoch millis

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

Number of events and correlation events within the specified time limit

Throws:

[ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

countPost

```
public SecurityEventServiceCountResponse countPost(String authToken,  
        long startTime,  
        long endTime,  
        javax.ws.rs.core.HttpHeaders hh)  
throws ServiceException,  
        AuthorizationException,  
        AuthenticationException
```

Returns the number of events and correlation events within the specified time limit

Parameters:

startTime -- The beginning of time range in epoch millis

endTime -- The end of time range in epoch millis

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Returns:

Number of events and correlation events within the specified time limit

Throws:

[ServiceException](#)

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

count

```
public SecurityEventServiceCountResponse count(SecurityEventServiceCount value)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

Returns the number of events and correlation events within the specified time limit

Parameters:

value - Model object containing request body

Returns:

Number of events and correlation events within the specified time limit

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersion

```
public SecurityEventServiceGetServiceMajorVersionResponse getServiceMajorVersion(String
authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session

hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation

[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMajorVersionPost

```
public SecurityEventServiceGetServiceMajorVersionResponse
getServiceMajorVersionPost(String authToken,
    javax.ws.rs.core.HttpHeaders hh)
    throws ServiceException,
           AuthorizationException,
           AuthenticationException
```

The major version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMajorVersion

```
public SecurityEventServiceGetServiceMajorVersionResponse  
getServiceMajorVersion(SecurityEventServiceGetServiceMajorVersion value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

The major version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersion

```
public SecurityEventServiceGetServiceMinorVersionResponse getServiceMinorVersion(String  
authToken,  
    javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

getServiceMinorVersionPost

```
public SecurityEventServiceGetServiceMinorVersionResponse  
getServiceMinorVersionPost(String authToken,  
                             javax.ws.rs.core.HttpHeaders hh)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

The minor version of this service.

Parameters:

authToken - Authentication token created for the current session
hh - HTTP headers from http request

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated

getServiceMinorVersion

```
public SecurityEventServiceGetServiceMinorVersionResponse  
getServiceMinorVersion(SecurityEventServiceGetServiceMinorVersion value)  
    throws ServiceException,  
           AuthorizationException,  
           AuthenticationException
```

The minor version of this service.

Parameters:

value - Model object containing request body

Throws:

[com.arcsight.coma.bridge.AuthorizationException](#) - If the user is not authorized to perform this operation
[com.arcsight.coma.bridge.AuthenticationException](#) - If the user is not authenticated
[com.arcsight.tools.coma.service.ServiceException](#) - For any errors happened during execution of this operation

Package

**com.arcsight.product.manager.service.v1.a
xis2.jaxws**

com.arcsight.product.manager.service.v1.axis2.jaxws

Class AuthenticationExceptionBean

java.lang.Object

└-com.arcsight.product.manager.service.v1.axis2.jaxws.AuthenticationExceptionBean

```
public class AuthenticationExceptionBean
extends Object
```

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary

public	AuthenticationExceptionBean()

Method Summary

String	getMessage()
void	setMessage(String message)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AuthenticationExceptionBean

```
public AuthenticationExceptionBean()
```

Methods

getMessage

```
public String getMessage()
```

Returns:

returns String

setMessage

```
public void setMessage(String message)
```

Parameters:

message - the value for the message property

com.arcsight.product.manager.service.v1.axis2.jaxws

Class AuthorizationExceptionBean

java.lang.Object

└-com.arcsight.product.manager.service.v1.axis2.jaxws.AuthorizationExceptionBean

```
public class AuthorizationExceptionBean
extends Object
```

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary

public	AuthorizationExceptionBean()

Method Summary

String	getMessage()
void	setMessage(String message)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AuthorizationExceptionBean

```
public AuthorizationExceptionBean()
```

Methods

getMessage

```
public String getMessage()
```

Returns:

returns String

setMessage

```
public void setMessage(String message)
```

Parameters:

message - the value for the message property

com.arcsight.product.manager.service.v1.axis2.jaxws

Class ModelLoader

java.lang.Object
└-com.arcsight.product.manager.service.v1.axis2.jaxws.ModelLoader

public final class **ModelLoader**
extends Object

Constructor Summary	
public	ModelLoader()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ModelLoader
public **ModelLoader()**

com.arcsight.product.manager.service.v1.axis2.jaxws

Class ObjectFactory

java.lang.Object
└-com.arcsight.product.manager.service.v1.axis2.jaxws.ObjectFactory

public final class **ObjectFactory**
extends Object

Constructor Summary	
public	ObjectFactory()

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ObjectFactory
public **ObjectFactory**()

com.arcsight.product.manager.service.v1.axis2.jaxws

Class ServiceExceptionBean

java.lang.Object
└-com.arcsight.product.manager.service.v1.axis2.jaxws.ServiceExceptionBean

public class ServiceExceptionBean
extends Object

This class was generated by the JAX-WS RI. JAX-WS RI 2.3.0 Generated source version: 2.3.0

Constructor Summary	
public	ServiceExceptionBean()

Method Summary	
int	getErrorCode()
String	getMessage()
void	setErrorCode(int errorCode)
void	setMessage(String message)

Methods inherited from class java.lang.Object
<code>equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait</code>

Constructors

ServiceExceptionBean
public ServiceExceptionBean()

Methods

getErrorCode
public int getErrorCode()

Returns:
returns int

setErrorCode

public void **setErrorCode**(int errorCode)

Parameters:
errorCode - the value for the errorCode property

getMessage

public String **getMessage**()

Returns:
returns String

setMessage

public void **setMessage**(String message)

Parameters:
message - the value for the message property

Package

**com.arcsight.product.manager.service.v1.
model**

com.arcsight.product.manager.service.v1.model

Class ResourceSearchHit

java.lang.Object

└-com.arcsight.product.manager.service.v1.model.ResourceSearchHit

```
public class ResourceSearchHit
extends Object
```

This class represents the information about a resource found as a result of search request.

Constructor Summary

public	ResourceSearchHit()

Method Summary

String	getDescription() Returns the description of the resource.
String	getName() Returns the resource name.
float	getScore() Returns the Lucene score of the resource.
String	getUri() Returns the resource URI.
String	getUuid() Returns the resource UUID.
void	setDescription(String description) Sets the description of the resource.
void	setName(String name) Sets the resource name.
void	setScore(float score) Sets the score of the resource.
void	setUri(String uri) Sets the resource URI.
void	setUuid(String uuid) Sets the resource UUID.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceSearchHit

```
public ResourceSearchHit()
```

Methods

getUuid

```
public String getUuid()
```

Returns the resource UUID.

Returns:
the UUID of the resource.

setUuid

```
public void setUuid(String uuid)
```

Sets the resource UUID.

Parameters:
uuid - the UUID of the resource.

getName

```
public String getName()
```

Returns the resource name.

Returns:
the name of the resource.

setName

```
public void setName(String name)
```

Sets the resource name.

Parameters:
name - the name of the resource.

getUri

```
public String getUri()
```

Returns the resource URI.

Returns:
the URI of the resource.

setUri

```
public void setUri(String uri)
```

Sets the resource URI.

Parameters:
uri - the URI of the resource.

getDescription

```
public String getDescription()
```

Returns the description of the resource.

Returns:
the description of the resource.

setDescription

```
public void setDescription(String description)
```

Sets the description of the resource.

Parameters:
description - the description of the resource.

getScore

```
public float getScore()
```

Returns the Lucene score of the resource.

Returns:
the Lucene score of the resource in the range from 0 to 1.

setScore

```
public void setScore(float score)
```

Sets the score of the resource.

Parameters:
score - the score of the resource in the range from 0 to 1.

com.arcsight.product.manager.service.v1.model

Class ResourceSearchHits

java.lang.Object

↳ com.arcsight.product.manager.service.v1.model.ResourceSearchHits

```
public class ResourceSearchHits
extends Object
```

Represents the resource search results.

Constructor Summary

public	ResourceSearchHits()

Method Summary

long	getElapsed() Returns the elapsed time of the search.
int	getHitCount() Returns the number of resources found.
String	getQueryStr() Returns the original query string from the search request.
List	getQueryTerms() Returns a list of the query terms.
String	getRewrittenQueryString() Returns the query rewritten into a primitive query.
List	getSearchHits() Returns a list of the search hits.
String	getStatusString() Returns the index status string.
void	setElapsed(long elapsed) Sets the elapsed time of the search.
void	setHitCount(int hitCount) Sets the number of the resources found.
void	setQueryStr(String queryStr) Sets the original query string from the search request.
void	setQueryTerms(List queryTerms) Sets the list of the query terms.

void	<code>setRewrittenQueryString</code> (String rewrittenQueryString) Sets the rewritten query.
void	<code>setSearchHits</code> (List searchHits) Sets the list of the search hits.
void	<code>setStatusString</code> (String statusString) Sets the index status string.

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ResourceSearchHits

`public ResourceSearchHits()`

Methods

getQueryStr

`public String getQueryStr()`

Returns the original query string from the search request.

Returns:

the original query string.

setQueryStr

`public void setQueryStr(String queryStr)`

Sets the original query string from the search request.

Parameters:

`queryStr` - the original query string.

getHitCount

`public int getHitCount()`

Returns the number of resources found.

Returns:

the number of resources found.

setHitCount

```
public void setHitCount(int hitCount)
```

Sets the number of the resources found.

Parameters:

hitCount - the number of resources found.

getSearchHits

```
public List getSearchHits()
```

Returns a list of the search hits. Every hit object contains information about a single found resource.

Returns:

a list of the search hits.

setSearchHits

```
public void setSearchHits(List searchHits)
```

Sets the list of the search hits. Every hit object contains information about a single found resource.

Parameters:

searchHits - the list of the search hits

getElapsed

```
public long getElapsed()
```

Returns the elapsed time of the search.

Returns:

the elapsed time of the search in milliseconds.

setElapsed

```
public void setElapsed(long elapsed)
```

Sets the elapsed time of the search.

Parameters:

elapsed - the elapsed time of the search in milliseconds.

getRewrittenQueryString

```
public String getRewrittenQueryString()
```

Returns the query rewritten into a primitive query.

Returns:

the query rewritten into a primitive query.

setRewrittenQueryString

public void **setRewrittenQueryString**(String rewrittenQueryString)

Sets the rewritten query.

Parameters:

rewrittenQueryString - the rewritten query.

getQueryTerms

public List **getQueryTerms**()

Returns a list of the query terms.

Returns:

a list of the query terms.

setQueryTerms

public void **setQueryTerms**(List queryTerms)

Sets the list of the query terms.

Parameters:

queryTerms - the list of the query terms.

getStatusString

public String **getStatusString**()

Returns the index status string.

Returns:

the index status string.

setStatusString

public void **setStatusString**(String statusString)

Sets the index status string.

Parameters:

statusString - the index status string.

Package

**com.arcsight.product.manager.service.v1.
model.parameter**

com.arcsight.product.manager.service.v1.model.parameter

Class BooleanParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- [com.arcsight.product.manager.service.v1.model.parameter.BooleanParameter](#)

All Implemented Interfaces:

Serializable

public class **BooleanParameter**

extends [ParameterBase](#)

Constructor Summary

public	BooleanParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)


Constructors

BooleanParameter

public **BooleanParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class BooleanStringParameter



All Implemented Interfaces:
Serializable

public class **BooleanStringParameter**
extends [ParameterBase](#)

Constructor Summary

public	BooleanStringParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

BooleanStringParameter

public **BooleanStringParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class ColorHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.ColorHolder

All Implemented Interfaces:
Serializable

public class **ColorHolder**
extends Object
implements Serializable

Constructor Summary

public	ColorHolder()

Method Summary

int	getBlue()
int	getGreen()
int	getRed()
void	setBlue(int blue)
void	setGreen(int green)
void	setRed(int red)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ColorHolder
public **ColorHolder()**

Methods

getRed

```
public int getRed()
```

Returns:

the red

setRed

```
public void setRed(int red)
```

Parameters:

red - the red to set

getGreen

```
public int getGreen()
```

Returns:

the green

setGreen

```
public void setGreen(int green)
```

Parameters:

green - the green to set

getBlue

```
public int getBlue()
```

Returns:

the blue

setBlue

```
public void setBlue(int blue)
```


Parameters:

blue - the blue to set

com.arcsight.product.manager.service.v1.model.parameter

Class ColorParameter

java.lang.Object



All Implemented Interfaces:
Serializable

```
public class ColorParameter
extends ParameterBase
```

Constructor Summary

public	ColorParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ColorParameter

```
public ColorParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class DoubleParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- [com.arcsight.product.manager.service.v1.model.parameter.DoubleParameter](#)

All Implemented Interfaces:

Serializable

```
public class DoubleParameter
extends ParameterBase
```

Constructor Summary

public	DoubleParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

DoubleParameter

```
public DoubleParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class DrilldownData

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.DrilldownData

All Implemented Interfaces:
Serializable

public class **DrilldownData**
extends Object
implements Serializable

Constructor Summary

public	DrilldownData()

Method Summary

FieldMapping[]	getFieldMappings()
ResourceReference	getResourceReference()
void	setFieldMappings(FieldMapping[] fieldMappings)
void	setResourceReference(ResourceReference resourceReference)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

DrilldownData
public **DrilldownData()**

Methods

getResourceReference

```
public ResourceReference getResourceReference()
```

setResourceReference

```
public void setResourceReference(ResourceReference resourceReference)
```

getFieldMappings

```
public FieldMapping\[\] getFieldMappings()
```

setFieldMappings

```
public void setFieldMappings(FieldMapping\[\] fieldMappings)
```

com.arcsight.product.manager.service.v1.model.parameter

Class FieldMapping

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.FieldMapping

All Implemented Interfaces:
Serializable

public class **FieldMapping**
extends Object
implements Serializable

Constructor Summary

public	FieldMapping()

Method Summary

String	getSourceResourceField()
String	getTargetResourceField()
void	setSourceResourceField(String sourceResourceField)
void	setTargetResourceField(String targetResourceField)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

FieldMapping
public **FieldMapping()**

Methods

getSourceResourceField

```
public String getSourceResourceField()
```

setSourceResourceField

```
public void setSourceResourceField(String sourceResourceField)
```

getTargetResourceField

```
public String getTargetResourceField()
```

setTargetResourceField

```
public void setTargetResourceField(String targetResourceField)
```

com.arcsight.product.manager.service.v1.model.parameter

Class FilteredResourceHolder

java.lang.Object
└─com.arcsight.product.manager.service.v1.model.parameter.FilteredResourceHolder

All Implemented Interfaces:
Serializable

public class **FilteredResourceHolder**
extends Object
implements Serializable

Constructor Summary

public	FilteredResourceHolder()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait


Constructors

FilteredResourceHolder
public **FilteredResourceHolder()**

com.arcsight.product.manager.service.v1.model.parameter

Class FilteredResourceParameter

java.lang.Object



All Implemented Interfaces:
Serializable

public class **FilteredResourceParameter**
extends [ParameterBase](#)

Constructor Summary

public	FilteredResourceParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

FilteredResourceParameter

public **FilteredResourceParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class FontHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.FontHolder

All Implemented Interfaces:
Serializable

public class **FontHolder**
extends Object
implements Serializable

Constructor Summary

public	FontHolder()

Method Summary

String	getName()
int	getSize()
int	getStyle()
void	setName(String name)
void	setSize(int size)
void	setStyle(int style)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

FontHolder
public **FontHolder()**

Methods

getName

```
public String getName()
```

setName

```
public void setName(String name)
```

getStyle

```
public int getStyle()
```

setStyle

```
public void setStyle(int style)
```

getSize

```
public int getSize()
```


setSize

```
public void setSize(int size)
```

com.arcsight.product.manager.service.v1.model.parameter

Class FontParameter

java.lang.Object



All Implemented Interfaces:
Serializable

```
public class FontParameter
extends ParameterBase
```

Constructor Summary

public	FontParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

FontParameter

```
public FontParameter()
```


com.arcsight.product.manager.service.v1.model.parameter

Class GroupAttributeEntry

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.GroupAttributeEntry

All Implemented Interfaces:
Serializable

public class **GroupAttributeEntry**
extends Object
implements Serializable

Constructor Summary

public	GroupAttributeEntry()

Method Summary

String	getFieldName()
String	getFunctionName()
String	getLabel()
void	setFieldName() (String fieldName)
void	setFunctionName() (String functionName)
void	setLabel() (String label)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

GroupAttributeEntry
public **GroupAttributeEntry()**

Methods

getFieldName

```
public String getFieldName()
```

setFieldName

```
public void setFieldName(String fieldName)
```

getFunctionName

```
public String getFunctionName()
```

setFunctionName

```
public void setFunctionName(String functionName)
```

getLabel


```
public String getLabel()
```

setLabel

```
public void setLabel(String label)
```

com.arcsight.product.manager.service.v1.model.parameter

Class GroupAttributesParameter



All Implemented Interfaces:
Serializable, Serializable

public class **GroupAttributesParameter**
extends [ParameterBase](#)
implements Serializable, Serializable

Constructor Summary

public	GroupAttributesParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)


Constructors

GroupAttributesParameter
public **GroupAttributesParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class HierarchyMapGroupByHolder

java.lang.Object



All Implemented Interfaces:
Serializable, Serializable

public class **HierarchyMapGroupByHolder**
extends [IntrospectableFieldListHolder](#)
implements Serializable, Serializable

Field Summary

public static final	DELIMITERS Value: Delimiters
public static final	MAX_DEPTH Value: Max Depth

Constructor Summary

public	HierarchyMapGroupByHolder()

Method Summary

HashMap[]	getSelectedFieldsExtraSettings() Returns the maps for the extra settings for the selected fields.
void	setSelectedFieldsExtraSettings (HashMap[] selectedFieldsExtraSettings) Sets the extra settings for the selected fields.

Methods inherited from class

[com.arcsight.product.manager.service.v1.model.parameter.IntrospectableFieldListHolder](#)

[getFieldFilterClassName](#), [getIntrospectableClassName](#), [getMaxSelectableFields](#),
[getMinSelectableFields](#), [getSelectedFieldNames](#), [getSelectedFields](#),
[setFieldFilterClassName](#), [setIntrospectableClassName](#), [setMaxSelectableFields](#),
[setMinSelectableFields](#), [setSelectedFieldNames](#), [setSelectedFields](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Fields

DELIMITERS

```
public static final java.lang.String DELIMITERS
```

Constant value: **Delimiters**

MAX_DEPTH

```
public static final java.lang.String MAX_DEPTH
```

Constant value: **Max Depth**

Constructors

HierarchyMapGroupByHolder

```
public HierarchyMapGroupByHolder()
```

Methods

getSelectedFieldsExtraSettings

```
public HashMap[] getSelectedFieldsExtraSettings()
```

Returns the maps for the extra settings for the selected fields. Each map contains values for DELIMITERS and MAX_DEPTH.

Returns:

- The maps with extra settings.

setSelectedFieldsExtraSettings

```
public void setSelectedFieldsExtraSettings(HashMap[] selectedFieldsExtraSettings)
```


Sets the extra settings for the selected fields. Each map contains values for DELIMITERS and MAX_DEPTH.

Parameters:

selectedFieldsExtraSettings

com.arcsight.product.manager.service.v1.model.parameter

Class HierarchyMapGroupByParameter



```
public class HierarchyMapGroupByParameter
extends ParameterBase
implements Serializable, Serializable
```

Constructor Summary

public	HierarchyMapGroupByParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#), [getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#), [getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#), [setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#), [setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object


[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

```
HierarchyMapGroupByParameter
public HierarchyMapGroupByParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class IntParameter



All Implemented Interfaces:
Serializable

```
public class IntParameter
extends ParameterBase
```

Constructor Summary

public	IntParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

IntParameter

```
public IntParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class IntrospectableFieldListHolder

java.lang.Object

↳ com.arcsight.product.manager.service.v1.model.parameter.IntrospectableFieldListHolder

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

[HierarchyMapGroupByHolder](#)

```
public class IntrospectableFieldListHolder
```

```
extends Object
```

```
implements Serializable
```

Constructor Summary

public	IntrospectableFieldListHolder()

Method Summary

String	getFieldFilterClassName()

String	getIntrospectableClassName()

int	getMaxSelectableFields()

int	getMinSelectableFields()

String[]	getSelectedFieldNames()

List	getSelectedFields()

void	setFieldFilterClassName(String className)

void	setIntrospectableClassName(String className)

void	setMaxSelectableFields(int max)

void	setMinSelectableFields(int min)

void	setSelectedFieldNames(String[] fieldNames)

void	<u>setSelectedFields</u> (List selectedFields)

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

IntrospectableFieldListHolder

```
public IntrospectableFieldListHolder()
```

Methods

getIntrospectableClassName

```
public String getIntrospectableClassName()
```

setIntrospectableClassName

```
public void setIntrospectableClassName(String className)
```

getFieldFilterClassName

```
public String getFieldFilterClassName()
```

setFieldFilterClassName

```
public void setFieldFilterClassName(String className)
```

getMinSelectableFields

```
public int getMinSelectableFields()
```

setMinSelectableFields

```
public void setMinSelectableFields(int min)
```

getMaxSelectableFields

```
public int getMaxSelectableFields()
```

setMaxSelectableFields

```
public void setMaxSelectableFields(int max)
```

getSelectedFieldNames

```
public String[] getSelectedFieldNames()
```

setSelectedFieldNames

```
public void setSelectedFieldNames(String[] fieldNames)
```

getSelectedFields


```
public List getSelectedFields()
```

setSelectedFields

```
public void setSelectedFields(List selectedFields)
```

com.arcsight.product.manager.service.v1.model.parameter

Class IntrospectableFieldListParameter



```
public class IntrospectableFieldListParameter
extends ParameterBase
implements Serializable, Serializable
```

Constructor Summary

public	IntrospectableFieldListParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

IntrospectableFieldListParameter

```
public IntrospectableFieldListParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class ListParameter

java.lang.Object



All Implemented Interfaces:
Serializable

public class **ListParameter**
extends [ParameterBase](#)

Constructor Summary

public	ListParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ListParameter

public **ListParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class ParameterBase

java.lang.Object

└-com.arcsight.product.manager.service.v1.model.parameter.ParameterBase

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

[StringSelectParameter](#), [StringParameter](#), [StringListParameter](#), [StatusMappingParameter](#), [ResourceReferenceParameter](#), [ResourceParameter](#), [ResourceGroupParameter](#), [ParameterizedReportParameter](#), [ListParameter](#), [IntrospectableFieldListParameter](#), [IntParameter](#), [HierarchyMapGroupByParameter](#), [GroupAttributesParameter](#), [FontParameter](#), [FilteredResourceParameter](#), [DoubleParameter](#), [ColorParameter](#), [BooleanStringParameter](#), [BooleanParameter](#)

public class **ParameterBase**

extends Object

implements Serializable

Constructor Summary

public	ParameterBase() Creates a new instance.
public	ParameterBase (String displayName, String description, boolean isWritable)

Method Summary

String	getBusinessModelType()
String	getServiceType()
String	getTranslatedDescription() Returns the description of the parameter.
String	getTranslatedDisplayName() Returns the display, or: friendly name of the parameter.
String	getUntranslatedDescription() Returns the untranslated description.
String	getUntranslatedDisplayName() Returns the untranslated display name.
Object	getValue()

boolean	<u>isWritable()</u> Returns whether or not the parameter is writable.
void	<u>setBusinessModelType</u> (String _type)
void	<u>setServiceType</u> (String type)
void	<u>setTranslatedDescription</u> (String td)
void	<u>setTranslatedDisplayName</u> (String tranDisplay)
void	<u>setUntranslatedDescription</u> (String description) Sets the description.
void	<u>setUntranslatedDisplayName</u> (String displayName)
void	<u>setValue</u> (Object value)
void	<u>setWritable</u> (boolean isWritable)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ParameterBase

```
public ParameterBase()
```

Creates a new instance.

ParameterBase

```
public ParameterBase(String displayName,  
                     String description,  
                     boolean isWritable)
```

Methods

setUntranslatedDisplayName

```
public void setUntranslatedDisplayName(String displayName)
```

getTranslatedDisplayName

```
public String getTranslatedDisplayName()
```

Returns the display, or: friendly name of the parameter.

Returns:

The display name of the parameter.

setTranslatedDisplayName

```
public void setTranslatedDisplayName(String tranDisplay)
```

setUntranslatedDescription

```
public void setUntranslatedDescription(String description)
```

Sets the description.

Parameters:

description - The description.

getTranslatedDescription

```
public String getTranslatedDescription()
```

Returns the description of the parameter.

Returns:

The description of the parameter.

setTranslatedDescription

```
public void setTranslatedDescription(String td)
```

setWritable

```
public void setWritable(boolean isWritable)
```

isWritable

```
public boolean isWritable()
```

Returns whether or not the parameter is writable. If it's not writable, ie. false is returned, the parameter is assumed to be read-only.

Returns:

Whether or not the parameter is writable.

getUntranslatedDisplayName

```
public String getUntranslatedDisplayName()
```

Returns the untranslated display name. (example, display name with "res:" will be returned as it is.

Returns:

- The untranslated display name.

getUntranslatedDescription

```
public String getUntranslatedDescription()
```

Returns the untranslated description. (example, description with "res:" will be returned as it is.

Returns:

- The untranslated description.

getValue

```
public Object getValue()
```

Returns:

the _instanceString

setValue

```
public void setValue(Object value)
```

Parameters:

value - the _instanceString to set

getBusinessModelType

```
public String getBusinessModelType()
```

Returns:

the _type

setBusinessModelType

```
public void setBusinessModelType(String _type)
```

Parameters:

_type - the _type to set

getServiceType

public String **getServiceType**()

Returns:

the _serviceType

setServiceType


public void **setServiceType**(String type)

Parameters:

type - the _serviceType to set

com.arcsight.product.manager.service.v1.model.parameter

Class ParameterizedReportParameter



```
public class ParameterizedReportParameter
extends ParameterBase
implements Serializable, Serializable
```

Constructor Summary

public	ParameterizedReportParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

```
ParameterizedReportParameter
public ParameterizedReportParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class ResourceGroupHolder



All Implemented Interfaces:
Serializable, Serializable

public class **ResourceGroupHolder**
extends [ResourceHolder](#)
implements Serializable, Serializable

Constructor Summary

public	ResourceGroupHolder()

Method Summary

String	getRootGroupID()
void	setRootGroupID (String rootGroupID)

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ResourceHolder](#)

[getResourceType](#), [getResourceTypeName](#), [getResourceUUID](#), [setResourceType](#), [setResourceTypeName](#), [setResourceUUID](#)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceGroupHolder

public **ResourceGroupHolder**()

Methods

getRootGroupID

```
public String getRootGroupID()
```

Returns:

the rootGroupID

setRootGroupID

```
public void setRootGroupID(String rootGroupID)
```

Parameters:

rootGroupID - the rootGroupID to set

com.arcsight.product.manager.service.v1.model.parameter

Class ResourceGroupParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- com.arcsight.product.manager.service.v1.model.parameter.ResourceGroupParameter

All Implemented Interfaces:

Serializable, Serializable

public class **ResourceGroupParameter**

extends [ParameterBase](#)

implements Serializable, Serializable

Constructor Summary

public	ResourceGroupParameter ()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ResourceGroupParameter

public **ResourceGroupParameter**()

com.arcsight.product.manager.service.v1.model.parameter

Class ResourceHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.ResourceHolder

All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[ResourceGroupHolder](#)

public class **ResourceHolder**
extends Object
implements Serializable

Hold the resource id and type

Constructor Summary	
public	ResourceHolder()

Method Summary	
int	getResourceType()
String	getResourceTypeName()
String	getResourceUUID()
void	setResourceType(int resourceType)
void	setResourceTypeName(String resourceTypeName)
void	setResourceUUID(String resourceUUID)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResourceHolder

```
public ResourceHolder()
```

Methods

getResourceUUID

```
public String getResourceUUID()
```

Returns:

the resourceUUID

setResourceUUID

```
public void setResourceUUID(String resourceUUID)
```

Parameters:

resourceUUID - the resourceUUID to set

getResourceType

```
public int getResourceType()
```

Returns:

the resourceType

setResourceType

```
public void setResourceType(int resourceType)
```

Parameters:

resourceType - the resourceType to set

getResourceTypeName

```
public String getResourceTypeName()
```

Returns:

the resourceTypeName

setResourceTypeName

```
public void setResourceTypeName(String resourceTypeName)
```


Parameters:

resourceTypeName - the resourceTypeName to set

com.arcsight.product.manager.service.v1.model.parameter

Class ResourceParameter

java.lang.Object



All Implemented Interfaces:
Serializable, Serializable

public class **ResourceParameter**
extends [ParameterBase](#)
implements Serializable, Serializable

Constructor Summary

public	ResourceParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ResourceParameter

public **ResourceParameter()**

com.arcsight.product.manager.service.v1.model.parameter

Class ResourceReferenceParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- [com.arcsight.product.manager.service.v1.model.parameter.ResourceReferenceParameter](#)

All Implemented Interfaces:

Serializable

```
public class ResourceReferenceParameter
extends ParameterBase
```

Constructor Summary

public	ResourceReferenceParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ResourceReferenceParameter

```
public ResourceReferenceParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class StatusMappingHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.StatusMappingHolder

All Implemented Interfaces:
Serializable

public class **StatusMappingHolder**
extends Object
implements Serializable

Constructor Summary	
public	StatusMappingHolder()

Method Summary	
String[][]	getMapping() Returns the mapping.
String[][]	getStatuses() Returns the statuses.
String[]	getValueFieldNames() Returns the value field names.
void	setMapping (String[][] mapping) Sets the mapping.
void	setStatuses (String[][] statuses) Sets the statuses.
void	setValueFieldNames (String[] valueFieldNames) Sets the value field names.

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

StatusMappingHolder

```
public StatusMappingHolder()
```

Methods

getValueFieldNames

```
public String[] getValueFieldNames()
```

Returns the value field names.

Returns:

The value field names.

setValueFieldNames

```
public void setValueFieldNames(String[] valueFieldNames)
```

Sets the value field names.

Parameters:

valueFieldNames - The value field names.

getStatuses

```
public String[][] getStatuses()
```

Returns the statuses.

Returns:

The statuses.

setStatuses

```
public void setStatuses(String[][] statuses)
```

Sets the statuses.

Parameters:

statuses - The statuses.

getMapping

```
public String[][] getMapping()
```

Returns the mapping.

Returns:

The mapping.

setMapping

public void **setMapping**(String[][] mapping)

Sets the mapping.

Parameters:

mapping - The mapping.

com.arcsight.product.manager.service.v1.model.parameter

Class StatusMappingParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- [com.arcsight.product.manager.service.v1.model.parameter.StatusMappingParameter](#)

All Implemented Interfaces:

Serializable, Serializable

public class **StatusMappingParameter**

extends [ParameterBase](#)

implements Serializable, Serializable

Constructor Summary

public	StatusMappingParameter ()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

StatusMappingParameter

public **StatusMappingParameter**()

com.arcsight.product.manager.service.v1.model.parameter

Class StringListHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.StringListHolder

All Implemented Interfaces:
Serializable

public class **StringListHolder**
extends Object
implements Serializable

Constructor Summary

public	StringListHolder()

Method Summary

StringParameter[]	getOptions()
int[]	getSelectedOptionsIndices()
void	setOptions(StringParameter[] in)
void	setSelectedOptionsIndices(int[] indices)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

StringListHolder
public **StringListHolder()**

Methods

setOptions

```
public void setOptions(StringParameter\[\] in)
```

getOptions

```
public StringParameter\[\] getOptions()
```

setSelectedOptionsIndices

```
public void setSelectedOptionsIndices(int[] indices)
```

getSelectedOptionsIndices

```
public int[] getSelectedOptionsIndices()
```


com.arcsight.product.manager.service.v1.model.parameter

Class StringListParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- com.arcsight.product.manager.service.v1.model.parameter.StringListParameter

All Implemented Interfaces:

Serializable

```
public class StringListParameter
extends ParameterBase
```

Constructor Summary

public	StringListParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

StringListParameter

```
public StringListParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class StringParameter

java.lang.Object

└- [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

└- [com.arcsight.product.manager.service.v1.model.parameter.StringParameter](#)

All Implemented Interfaces:

Serializable

```
public class StringParameter
extends ParameterBase
```

Constructor Summary

public	StringParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

StringParameter

```
public StringParameter()
```

com.arcsight.product.manager.service.v1.model.parameter

Class StringSelectHolder

java.lang.Object
└-com.arcsight.product.manager.service.v1.model.parameter.StringSelectHolder

All Implemented Interfaces:
Serializable

public class **StringSelectHolder**
extends Object
implements Serializable

Constructor Summary

public	StringSelectHolder()

Method Summary

StringParameter[]	getOptions()
int	getSelectedOptionsIndex()
void	setOptions(StringParameter[] in)
void	setSelectedOptionsIndex(int index)

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

StringSelectHolder
public **StringSelectHolder()**

Methods

setOptions

public void **setOptions**([StringParameter\[\]](#) in)

getOptions

public [StringParameter\[\]](#) **getOptions**()

setSelectedOptionsIndex

public void **setSelectedOptionsIndex**(int index)


getSelectedOptionsIndex

public int **getSelectedOptionsIndex**()

com.arcsight.product.manager.service.v1.model.parameter

Class StringSelectParameter

java.lang.Object



All Implemented Interfaces:
Serializable, Serializable

public class **StringSelectParameter**
extends [ParameterBase](#)
implements Serializable, Serializable

Constructor Summary

public	StringSelectParameter()

Methods inherited from class [com.arcsight.product.manager.service.v1.model.parameter.ParameterBase](#)

[getBusinessModelType](#), [getServiceType](#), [getTranslatedDescription](#),
[getTranslatedDisplayName](#), [getUntranslatedDescription](#), [getUntranslatedDisplayName](#),
[getValue](#), [isWritable](#), [setBusinessModelType](#), [setServiceType](#), [setTranslatedDescription](#),
[setTranslatedDisplayName](#), [setUntranslatedDescription](#), [setUntranslatedDisplayName](#),
[setValue](#), [setWritable](#)

Methods inherited from class java.lang.Object

[equals](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

StringSelectParameter

public **StringSelectParameter()**

Package

com.arcsight.product.manager.service.v1.rest.config

com.arcsight.product.manager.service.v1.rest.config

Class ApplicationConfig

```
java.lang.Object
├--javax.ws.rs.core.Application
│   └--org.glassfish.jersey.server.ResourceConfig
│       └--com.arcsight.product.manager.service.v1.rest.config.ApplicationConfig
```

All Implemented Interfaces:

org.glassfish.jersey.server.ServerConfig, javax.ws.rs.core.Configurable

```
public class ApplicationConfig
extends org.glassfish.jersey.server.ResourceConfig
```

Nested Class Summary	
class	ApplicationConfig.AuthenticationExceptionMapper ApplicationConfig.AuthenticationExceptionMapper
class	ApplicationConfig.AuthorizationExceptionMapper ApplicationConfig.AuthorizationExceptionMapper
class	ApplicationConfig.JettisonJsonJaxbMessagingFeature ApplicationConfig.JettisonJsonJaxbMessagingFeature
class	ApplicationConfig.ServiceExceptionMapper ApplicationConfig.ServiceExceptionMapper
Constructor Summary	
public	ApplicationConfig()
Methods inherited from class org.glassfish.jersey.server.ResourceConfig	
addProperties, files, files, forApplication, forApplicationClass, forApplicationClass, getApplication, getApplicationName, getClasses, getClassLoader, getConfiguration, getContracts, getInstances, getProperties, getProperty, getPropertyNames, getResources, getRuntimeType, getSingletons, isEnabled, isEnabled, isProperty, isRegistered, isRegistered, packages, packages, packages, property, register, register, register, register, register, register, register, register, registerClasses, registerClasses, registerFinder, registerInstances, registerInstances, registerResources, registerResources, setApplicationName, setClassLoader, setProperties	
Methods inherited from class javax.ws.rs.core.Application	
getClasses, getProperties, getSingletons	

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `javax.ws.rs.core.Configurable`

`getConfiguration`, `property`, `register`, `register`, `register`, `register`, `register`, `register`, `register`, `register`

Methods inherited from interface `org.glassfish.jersey.server.ServerConfig`

`getResources`

Methods inherited from interface `org.glassfish.jersey.ExtendedConfig`

`isProperty`

Methods inherited from interface `javax.ws.rs.core.Configuration`

`getClasses`, `getContracts`, `getInstances`, `getProperties`, `getProperty`, `getPropertyNames`, `getRuntimeType`, `isEnabled`, `isEnabled`, `isRegistered`, `isRegistered`


Constructors

ApplicationConfig

```
public ApplicationConfig()
```


com.arcsight.product.manager.service.v1.rest.config

Class ApplicationConfig.JettisonJsonJaxbMessagingFeature



All Implemented Interfaces:

javax.ws.rs.core.Feature

public static class ApplicationConfig.JettisonJsonJaxbMessagingFeature

extends org.glassfish.jersey.jettison.JettisonFeature

Constructor Summary

public	JettisonJsonJaxbMessagingFeature()

Method Summary

boolean	configure (javax.ws.rs.core.FeatureContext context)

Methods inherited from class org.glassfish.jersey.jettison.JettisonFeature

configure

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface javax.ws.rs.core.Feature

configure

Constructors

JettisonJsonJaxbMessagingFeature

public JettisonJsonJaxbMessagingFeature()

Methods

configure

```
public boolean configure(javax.ws.rs.core.FeatureContext context)
```

com.arcsight.product.manager.service.v1.rest.config
Class ApplicationConfig.AuthenticationExceptionMapper

java.lang.Object
└─
com.arcsight.product.manager.service.v1.rest.config.ApplicationConfig.AuthenticationExceptionMapper
All Implemented Interfaces:
 javax.ws.rs.ext.ExceptionMapper

public static class ApplicationConfig.AuthenticationExceptionMapper
extends Object
implements javax.ws.rs.ext.ExceptionMapper

Constructor Summary

public	AuthenticationExceptionMapper()

Method Summary

javax.ws.rs.core.Response	toResponse(AuthenticationException e)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface javax.ws.rs.ext.ExceptionMapper

toResponse

Constructors

AuthenticationExceptionMapper
public AuthenticationExceptionMapper()

Methods

toResponse
public javax.ws.rs.core.Response toResponse([AuthenticationException](#) e)

com.arcsight.product.manager.service.v1.rest.config Class ApplicationConfig.AuthorizationExceptionMapper

java.lang.Object
└─
com.arcsight.product.manager.service.v1.rest.config.ApplicationConfig.AuthorizationExceptionMapper

All Implemented Interfaces:
javax.ws.rs.ext.ExceptionMapper

public static class ApplicationConfig.AuthorizationExceptionMapper
extends Object
implements javax.ws.rs.ext.ExceptionMapper

Constructor Summary

public	AuthorizationExceptionMapper()

Method Summary

javax.ws.rs.core.Response	toResponse(AuthorizationException e)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface javax.ws.rs.ext.ExceptionMapper

toResponse

Constructors

AuthorizationExceptionMapper
public AuthorizationExceptionMapper()

Methods

toResponse
public javax.ws.rs.core.Response toResponse([AuthorizationException](#) e)

com.arcsight.product.manager.service.v1.rest.config Class ApplicationConfig.ServiceExceptionMapper

java.lang.Object

↓

com.arcsight.product.manager.service.v1.rest.config.ApplicationConfig.ServiceExceptionMapper

All Implemented Interfaces:

javax.ws.rs.ext.ExceptionMapper

public static class **ApplicationConfig.ServiceExceptionMapper**
extends Object
implements javax.ws.rs.ext.ExceptionMapper

Constructor Summary	
public	ServiceExceptionMapper()

Method Summary	
javax.ws.rs.core.Response	toResponse (ServiceException e)

Methods inherited from class java.lang.Object	
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	
Methods inherited from interface javax.ws.rs.ext.ExceptionMapper	
toResponse	

Constructors

ServiceExceptionMapper
public **ServiceExceptionMapper**()


Methods

toResponse
public javax.ws.rs.core.Response **toResponse**([ServiceException](#) e)

Package

com.arcsight.tools.coma.service

com.arcsight.tools.coma.service Class RuntimeCodedException



All Implemented Interfaces:
Serializable

Direct Known Subclasses:
[RuntimeLoginException](#)

```
public class RuntimeCodedException
extends RuntimeException
```

Base class for various internal runtime exceptions that may happen while communicating from service layer with internal ESM classes.

Constructor Summary	
public	RuntimeCodedException() Constructs a new runtime exception with null as its detail message.
public	RuntimeCodedException(String message) Constructs a new runtime exception with the specified detail message.
public	RuntimeCodedException(Throwable cause) Constructs a new runtime exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).
public	RuntimeCodedException(String message, Throwable cause) Constructs a new runtime exception with the specified detail message and cause.
public	RuntimeCodedException(int errorCode) Constructs a new exception with the specified error code

Method Summary	
int	getErrorCode() Returns the error code associated with this exception.
void	setErrorCode(int errorCode) Associates the error code with the exception.

Methods inherited from class java.lang.Throwable

```
addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage,
getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace,
printStackTrace, setStackTrace, toString
```

Methods inherited from class `java.lang.Object`

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructors

RuntimeCodedException

```
public RuntimeCodedException()
```

Constructs a new runtime exception with `null` as its detail message.

RuntimeCodedException

```
public RuntimeCodedException(String message)
```

Constructs a new runtime exception with the specified detail message.

Parameters:

`message` - the detail message.

RuntimeCodedException

```
public RuntimeCodedException(Throwable cause)
```

Constructs a new runtime exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of cause). This constructor is useful for runtime exceptions that are little more than wrappers for other throwables.

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

RuntimeCodedException

```
public RuntimeCodedException(String message,
                             Throwable cause)
```

Constructs a new runtime exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this runtime exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).
`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

RuntimeCodedException

```
public RuntimeCodedException(int errorCode)
```

Constructs a new exception with the specified error code

Parameters:

errorCode - error code identifying the exceptional case

Methods

getErrorCode

```
public int getErrorCode()
```

Returns the error code associated with this exception. The error code is set when the exception thrown and it indicates the failure or irregular situation.

Returns:

the errorCode

setErrorCode

```
public void setErrorCode(int errorCode)
```

Associates the error code with the exception.

Parameters:

errorCode - The errorCode to set

com.arcsight.tools.coma.service

Class RuntimeException

```
java.lang.Object
├─ java.lang.Throwable
│   └─ java.lang.Exception
│       └─ java.lang.RuntimeException
│           └─ com.arcsight.tools.coma.service.RuntimeCodedException
│               └─ com.arcsight.tools.coma.service.RuntimeLoginException
```

All Implemented Interfaces:
Serializable

```
public class RuntimeException
extends RuntimeCodedException
```

Exception thrown for authentication issues. It doesn't necessarily means failure. The exception could indicate a request for additional information (challenge).
This is internal exception not returned by API calls. To report related exceptional cases to the clients API converts this exception to [ServiceLoginException](#)

Field Summary	
public static final	LOGIN_CHALLENGE Indicates additional challenge requested by the server. Value: -4
public static final	LOGIN_ERROR_FAILURE Indicates login failure. Value: 0
public static final	LOGIN_ERROR_LICENSE_EXPIRED Indicates an expired license. Value: -1
public static final	LOGIN_ERROR_PASSWORD_EXPIRED Indicates expired password. Value: -3
public static final	LOGIN_ERROR_USER_DISABLED Indicates the fact that user account was disabled. Value: -2
public static final	LOGIN_ERROR_USER_NOT_ALLOWED Indicates that the user doesn't have permission to access the component. Value: -5

Constructor Summary

public	RuntimeLoginException () Constructs a new runtime exception with null as its detail message.
public	RuntimeLoginException (String message) Constructs a new runtime exception with the specified detail message.
public	RuntimeLoginException (Throwable cause) Constructs a new runtime exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).
public	RuntimeLoginException (String message, Throwable cause) Constructs a new runtime exception with the specified detail message and cause.
public	RuntimeLoginException (int errorCode)

Methods inherited from class [com.arcsight.tools.coma.service.RuntimeCodedException](#)

[getErrorCode](#), [setErrorCode](#)

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

LOGIN_ERROR_FAILURE

```
public static final int LOGIN_ERROR_FAILURE
```

Indicates login failure.
Constant value: **0**

LOGIN_ERROR_LICENSE_EXPIRED

```
public static final int LOGIN_ERROR_LICENSE_EXPIRED
```

Indicates an expired license.
Constant value: **-1**

LOGIN_ERROR_USER_DISABLED

```
public static final int LOGIN_ERROR_USER_DISABLED
```

Indicates the fact that user account was disabled.
Constant value: -2

LOGIN_ERROR_PASSWORD_EXPIRED

```
public static final int LOGIN_ERROR_PASSWORD_EXPIRED
```

Indicates expired password.
Constant value: -3

LOGIN_CHALLENGE

```
public static final int LOGIN_CHALLENGE
```

Indicates additional challenge requested by the server. Login cannot be completed until the user to meet the challenge.
Constant value: -4

LOGIN_ERROR_USER_NOT_ALLOWED

```
public static final int LOGIN_ERROR_USER_NOT_ALLOWED
```

Indicates that the user doesn't have permission to access the component.
Constant value: -5

Constructors

RuntimeLoginException

```
public RuntimeLoginException()
```

Constructs a new runtime exception with `null` as its detail message.

RuntimeLoginException

```
public RuntimeLoginException(String message)
```

Constructs a new runtime exception with the specified detail message.

Parameters:

message - the detail message.

RuntimeLoginException

```
public RuntimeLoginException(Throwable cause)
```

Constructs a new runtime exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of cause). This constructor is useful for runtime exceptions that are little more than wrappers for other throwables.

Parameters:

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

RuntimeLoginException

```
public RuntimeLoginException(String message,  
                             Throwable cause)
```

Constructs a new runtime exception with the specified detail message and cause.

Note that the detail message associated with cause is *not* automatically incorporated in this runtime exception's detail message.

Parameters:

message - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).
cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

RuntimeLoginException

```
public RuntimeLoginException(int errorCode)
```


com.arcsight.tools.coma.service Interface Service

All Known Implementing Classes:
[ServiceBase](#)

public interface **Service**
extends

Copyright (c) 2001-2018 Micro Focus or one of its affiliates. Confidential commercial computer software. Valid license required.
Base interface for services.

Method Summary

abstract int	getServiceMajorVersion() The major version of this service.
abstract int	getServiceMinorVersion() The minor version of this service.

Methods

getServiceMajorVersion

public abstract int **getServiceMajorVersion()**

The major version of this service.

Returns:

The major version of this service.

getServiceMinorVersion

public abstract int **getServiceMinorVersion()**

The minor version of this service.

Returns:

The minor version of this service.

com.arcsight.tools.coma.service Class ServiceBase

java.lang.Object

↓
-com.arcsight.tools.coma.service.ServiceBase

All Implemented Interfaces:

[Service](#)

public abstract class **ServiceBase**
extends **Object**
implements [Service](#)

Copyright (c) 2001-2018 Micro Focus or one of its affiliates. Confidential commercial computer software. Valid license required.
Base service implementation.

Constructor Summary

public	ServiceBase()

Method Summary

int	getServiceMajorVersion()

int	getServiceMinorVersion()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.arcsight.tools.coma.service.Service](#)

[getServiceMajorVersion](#), [getServiceMinorVersion](#)

Constructors

ServiceBase

public **ServiceBase()**

Methods

getServiceMajorVersion

```
public int getServiceMajorVersion()
```

getServiceMinorVersion

```
public int getServiceMinorVersion()
```

com.arcsight.tools.coma.service Class ServiceException

```
java.lang.Object
├─ java.lang.Throwable
│   └─ java.lang.Exception
│       └─ com.arcsight.tools.coma.service.ServiceException
```

All Implemented Interfaces:
Serializable, Serializable

Direct Known Subclasses:
[ValidationException](#), [ServiceLoginException](#)

```
public class ServiceException
extends Exception
implements Serializable, Serializable
```

This is exception for kahuna/coma service. There are several reasons to have special exception impl: 1. Make it serializable so all service binding can marshal it 2. Due to the known GWT marshaling issue, parent message can not be marshaled we have to duplicated parent instance variables in this class.

Field Summary	
public static final	ERROR_UNKNOWN Value: -54188

Constructor Summary	
public	ServiceException () Constructs a new exception with null as its detail message.
public	ServiceException (String message) Constructs a new exception with the specified detail message.
public	ServiceException (Throwable cause) Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).
public	ServiceException (String message, Throwable cause) Constructs a new exception with the specified detail message and cause.

Method Summary	
static String	buildExceptionStackTraceString (Throwable e) It builds a string for stack trace of an exception.

<code>static</code> <code>ServiceException</code>	<code>createServiceException</code> (Throwable e) It creates an exception which is serializable.
<code>int</code>	<code>getErrorCode</code> () Returns the error code associated with this exception.
<code>void</code>	<code>setErrorCode</code> (int errorCode) Associates the error code with the exception.

Methods inherited from class `java.lang.Throwable`

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

ERROR_UNKNOWN

```
public static final int ERROR_UNKNOWN
```

Constant value: **-54188**

Constructors

ServiceException

```
public ServiceException()
```

Constructs a new exception with null as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

ServiceException

```
public ServiceException(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

`message` - the detail message. The detail message is saved for later retrieval by the `Throwable.getMessage()` method.

ServiceException

```
public ServiceException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `java.security.PrivilegedActionException`).

Parameters:

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

ServiceException

```
public ServiceException(String message,  
                        Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with cause is *not* automatically incorporated in this exception's detail message.

Parameters:

message - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

Methods

buildExceptionStackTraceString

```
public static String buildExceptionStackTraceString(Throwable e)
```

It builds a string for stack trace of an exception. It is used for debugging log.

Parameters:

e

Returns:

createServiceException

```
public static ServiceException createServiceException(Throwable e)
```

It creates an exception which is serializable. Some of the throwables, such as `NullPointerException`, are not serializable. They will cause serialization error when they are wrapped in service exception. This approach wraps all stack traces as string in service exception.

Parameters:

e

Returns:

getErrorCode

```
public int getErrorCode()
```

Returns the error code associated with this exception. The error code is set when the exception thrown and it indicates the failure or irregular situation.

Returns:
the errorCode

setErrorCode

```
public void setErrorCode(int errorCode)
```

Associates the error code with the exception.

Parameters:
errorCode - The errorCode to set

com.arcsight.tools.coma.service

Class ServiceLoginException

```
java.lang.Object
├-- java.lang.Throwable
│   └-- java.lang.Exception
│       └-- com.arcsight.tools.coma.service.ServiceException
│           └-- com.arcsight.tools.coma.service.ServiceLoginException
```

All Implemented Interfaces:
Serializable, Serializable

```
public class ServiceLoginException
extends ServiceException
```

Exception thrown for authentication issues. It doesn't necessarily means failure. The exception could indicate a request for additional information (challenge).

Field Summary	
public static final	LOGIN_ERROR_FAILURE Indicates login failure. Value: 0
public static final	LOGIN_ERROR_LICENSE_EXPIRED Indicates an expired license. Value: -1
public static final	LOGIN_ERROR_USER_DISABLED Indicates the fact that user account was disabled. Value: -2
public static final	LOGIN_ERROR_USER_NOT_ALLOWED Indicates that the user doesn't have permission to access the component. Value: -5
Fields inherited from class com.arcsight.tools.coma.service.ServiceException	
ERROR_UNKNOWN	

Constructor Summary	
public	ServiceLoginException() Constructs a new exception with null as its detail message.
public	ServiceLoginException(String message) Constructs a new exception with the specified detail message.

public	ServiceLoginException (Throwable cause) Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).
public	ServiceLoginException (String message, Throwable cause) Constructs a new exception with the specified detail message and cause.
public	ServiceLoginException (int errorCode) Constructs a new exception with the specified error code

Methods inherited from class [com.arcsight.tools.coma.service.ServiceException](#)

[buildExceptionStackTraceString](#), [createServiceException](#), [getErrorCode](#), [setErrorCode](#)

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

LOGIN_ERROR_FAILURE

public static final int **LOGIN_ERROR_FAILURE**

Indicates login failure.
Constant value: 0

LOGIN_ERROR_LICENSE_EXPIRED

public static final int **LOGIN_ERROR_LICENSE_EXPIRED**

Indicates an expired license.
Constant value: -1

LOGIN_ERROR_USER_DISABLED

public static final int **LOGIN_ERROR_USER_DISABLED**

Indicates the fact that user account was disabled.
Constant value: -2

LOGIN_ERROR_USER_NOT_ALLOWED

public static final int **LOGIN_ERROR_USER_NOT_ALLOWED**

Indicates that the user doesn't have permission to access the component.

Constructors

ServiceLoginException

```
public ServiceLoginException()
```

Constructs a new exception with null as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

ServiceLoginException

```
public ServiceLoginException(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

message - the detail message. The detail message is saved for later retrieval by the `Throwable.getMessage()` method.

ServiceLoginException

```
public ServiceLoginException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of cause). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `java.security.PrivilegedActionException`).

Parameters:

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

ServiceLoginException

```
public ServiceLoginException(String message,  
                             Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with cause is *not* automatically incorporated in this exception's detail message.

Parameters:

message - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).
cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)

ServiceLoginException


```
public ServiceLoginException(int errorCode)
```

Constructs a new exception with the specified error code

Parameters:

errorCode - error code identifying the exceptional case

com.arcsight.tools.coma.service Class ValidationException



All Implemented Interfaces:
Serializable, Serializable

public class **ValidationException**
extends [ServiceException](#)

Base class for various validation exceptions to indicate failures to validate different types of data (e.g. password).

Fields inherited from class com.arcsight.tools.coma.service.ServiceException
ERROR_UNKNOWN

Constructor Summary	
public	ValidationException() Constructs a new exception with null as its detail message.
public	ValidationException(String message) Constructs a new exception with the specified detail message.
public	ValidationException(String message, Map validationErrors) Constructs a new exception with the specified detail message and a map containing error descriptions.

Method Summary	
String	getLocalizedMessage()
String	getMessage()
Map	getValidationErrors() Returns validationErrors, which is a map of errors found for different items.
void	setValidationErrors(Map validationErrors) Sets the validationErrors.
String	toString()

Methods inherited from class [com.arcsight.tools.coma.service.ServiceException](#)

[buildExceptionStackTraceString](#), [createServiceException](#), [getErrorCode](#), [setErrorCode](#)

Methods inherited from class `java.lang.Throwable`

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class `java.lang.Object`

`equals`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ValidationException

```
public ValidationException()
```

Constructs a new exception with null as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

ValidationException

```
public ValidationException(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

`message` - the detail message. The detail message is saved for later retrieval by the [getMessage\(\)](#) method.

ValidationException

```
public ValidationException(String message,  
                           Map validationErrors)
```

Constructs a new exception with the specified detail message and a map containing error descriptions. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

`message` - the detail message. The detail message is saved for later retrieval by the [getMessage\(\)](#) method.

`validationErrors` - Map containing errors found for different items

Methods

getValidationErrors

```
public Map getValidationErrors()
```

Returns `validationErrors`, which is a map of errors found for different items.

Returns:

the validationErrors errors associated with different properties

setValidationErrors

```
public void setValidationErrors(Map validationErrors)
```

Sets the validationErrors.

Parameters:

validationErrors - the validationErrors to set

getMessage

```
public String getMessage()
```

getLocalizedMessage

```
public String getLocalizedMessage()
```

toString

```
public String toString()
```
