opentext[™]

OpenText Core Data Discovery & Risk Insights

Application Version 25.2.0

Processing Agent Version 25.2.101

Support Matrix

Legal notices

Copyright 2019-2025 Open Text

The only warranties for products and services of Open Text and its affiliates and licensors ("Open Text") are as may be set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Open Text shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Except as specifically indicated otherwise, this document contains confidential information and a valid license is required for possession, use or copying. If this work is provided to the U.S. Government, consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

OpenText Core Data Discovery & Risk Insights Support Matrix

Application version:25.2.0

Processing Agent version:25.2.101

Publication date: April 2025

About OpenText Core Data Discovery & Risk Insights

OpenText Core Data Discovery & Risk Insights lets you find, protect, and secure sensitive and high-value data within on-premises and cloud data platforms across your enterprise. Identify, collect, and organize content to ensure discovery of sensitive data. Configure how structured and unstructured sources and datasets are processed and categorized with Connect. Analyze your data under management with Analyze. Organize, review, and take action on documents and unstructured data items with Manage.

Support matrix

The following hardware, software, and application requirements are supported with this version of OpenText Core Data Discovery & Risk Insights.

Web browsers and plug-ins

OpenText Core Data Discovery & Risk Insights is supported on the following browsers.

- · Google Chrome 135 or later
- · Firefox 137 or later
- · Microsoft Edge 135 or later

OpenText Core Data Discovery & Risk Insights is best viewed at the following screen resolution:

• 1366 x 768 or greater resolution.

Data Resources

The following resources are supported for data processing by the on-premises agent.

OpenText Content Manager 23.4.x

IMPORTANT: Only Microsoft SQL Server Unicode RDB datasets are supported at this time.

- File system CIFS/ SMBv2 shares
 - Must comply with SMBv2 protocol for share name restrictions.
- Microsoft Exchange Server 2016 fully updated and patched, 2019 fully updated and patched, and Office 365
- SharePoint 2016, fully updated and patched, and Office 365
 - For SharePoint 2016, Site Collections, Web Applications, and OneDrive are supported.
 - For Office 365 SharePoint, Site Collections and OneDrive are supported.
- Google Workspace's Drive (personal Google Drives are not supported)
- Documentum 24.4.x or later
- Extended ECM 24.3.x or later
- · Structured data platforms
 - Platforms supported by the built-in structured data processor
 - Oracle
 - Oracle 19c, Oracle 21c

- IBM Db2
 - Db2 11.5.x
- SQL Server
 - SQL Server 2019, SQL Server 2022
- PostgreSQL
 - PostgreSQL 12.x, PostgreSQL 13.x, PostgreSQL 14.x, PostgreSQL 15.x, PostgreSQL 16.x
- MySQL
 - MySQL 8.x
- Sybase
 - Sybase 16.0
- o Platforms supported by connection to Structured Data Manager

NOTE: For supported versions, see the *Structured Data Manager Certification Matrix*.

- Oracle
- IBM Db2
- SQL Server
- PostgreSQL
- MySQL
- JDBC
- Sybase

CAUTION: OpenText Core Data Discovery & Risk Insights does not support scanning and processing of the following.

- · virtual hard drives
- Operating System container files such as ISO files

Processing agent host

Review the agent host requirements.

CAUTION: Install the processing agent on a dedicated VM machine with connectivity to your data resources. Do not install the processing agent on a machine that you will be processing data from.

On-premises agent host requirements

The server that will host the on-premises processing agent must meet the following requirements.

Resources

The host server for the agent requires the following resources. The agent should be installed on a dedicated drive. If you will be processing large container files, start with the recommended values and consider defining a separate drive for processing.

Resource	Minimum (AWS c5.xlarge equivalent)	Recommended (AWS c5.2xlarge equivalent)
CPUs	4	8
RAM	8GB	16GB
Free space	85GB	200GB

• If more than 4 CPUs are available, increase the number of threads available to the Connector Framework Server service.

To increase the threads available to the Connector Framework Server service

- Open <agentInstallDir>\CFS\cfs.cfg. By default, the agent install directory is C:\Program Files\OpenText\Core Data Discovery & Risk Insights\Agent\.
- 2. Under the [ImportService] section, locate the ThreadCount setting.
- 3. Change the default setting value of 3 to be roughly two-thirds the number of the cores available.
 - For example, if you have 8 cores, set the ThreadCount value to 6.
- 4. Save the cfs.cfg file.
- 5. Restart the Connector Framework Server service.
- If you are processing large container files, you may consider defining a separate, dedicated
 large capacity drive (such as 500GB) on the agent host to handle the data processing. Files are
 processed concurrently and processing large container files may use an excess amount of disk
 space. If disk space runs out or runs low, all other processing may pause.

To define a separate drive on the agent host for data processing

1. On the agent host server that will be processing very large files, log on to the agent administration UI.

From the Start menu, click OpenText Core Data Discovery & Risk Insights Agent > Agent Admin.

2. In the navigation panel, click Advanced Settings.

The Advanced Settings page opens.

3. In the Category list, select Common.

The settings for the common configurations display.

- 4. Make the following selections.
 - a. In the **Documents Path** field, type the path to the desired directory on the local dedicated drive..
 - b. In the **Mail Spool Directory** field, type the path to the desired directory on the local dedicated drive.

CAUTION: This cannot be the same directory as the **Documents Path**.

c. In the **Maintain Free Space MB** field, update the value as necessary.

TIP: Start with doubling the existing value and then increase if necessary.

d. In the Min Free Space MB field, update the value as necessary.

TIP: Start with doubling the existing value and then increase if necessary.

- 5. Click Save.
- 6. Repeat for each agent server that will be processing very large files.

Operating System

Ensure that you are running a supported operating system with all currently "critical" and "important" updates installed from update.microsoft.com.

- Windows Server 2016 from English Installation Media (Standard, Datacenter)
 - The "Server with Desktop Experience" installation option is required. Additional language packs may be added after OS installation.
- Windows Server 2019 from English Installation Media (Standard, Datacenter)
 - The "Server with Desktop Experience" installation option is required. Additional language packs may be added after OS installation.
- Windows Server 2022 from English Installation Media (Standard, Datacenter)
 - The "Server with Desktop Experience" installation option is required. Additional language packs may be added after OS installation.

Agent host ports in use

The processing agent uses the following ports on the agent host server for intra-process communications.

IMPORTANT: The processing agent interacts with the back office and requires connectivity to the 9000-9999 port range as indicated in the General requirements section.

Adapter binding	Listening ports	Owning process	Usage/Notes
0.0.0.0, [::]	4200	agent-ui.exe	Local agent admin ui application, accepts connections from loopback only.
127.0.0.1, [::1]	7432	postgres.exe	Local relational database to manage local configuration and workflow processing.
0.0.0.0, [::]	7500, 7502	cfs.exe	Local process that handles content extraction, accepts actions/commands from loopback only.
127.0.0.1, [::1]	7957	AgentApi.exe	Local process that coordinates with other local processes and communicates (outbound) with the back office.

General

The following requirements must be met for the server hosting the processing agent. Applications listed must exist on the host server prior to installing the agent.

- If processing file system documents from a host machine that has long paths enabled, long paths must also be enabled on the agent host.
- Ensure the public certificate presented by the external proxy is trustable by agent hosts.
 Depending on the certificate presented, this may include importing a private certificate authority (CA) certificate to the local Windows certificate store.

IMPORTANT: If a private CA is used, ensure the private CA's certificate is removed if the agent is uninstalled.

• Ensure the Windows server is permitted to communicate through TLS 1.2 or 1.3, using a current "safe" cipher suite to ports 9000-9999. The OpenText Core Data Discovery & Risk Insights back office components (commonly in the cloud) implement and require an Intermediate TLS security level (see the "Security/Server Side TLS" article on the Mozilla wiki).

IMPORTANT: By default, most supported Windows server operating systems are preconfigured to allow communication with the back office and to dataset targets enforcing TLS

1.2 communication using a reduced safe set of ciphers (EX2019, O365, SPO). Ensure this connectivity is communicating with functional targets by using a web browser that utilizes Windows Schannel (Internet Explorer) or via the Invoke-WebRequest PowerShell cmdlet.

It is possible to harden encryption in Windows server to restrict the native Schannel encryption component, used by the processing agent services, to specific operating modes and particular cipher suites (see the "Transport Layer Security (TLS) registry settings" article on Microsoft Learn). The following are the minimum required values.

- ∘ TLS 1.2 (Client): Enabled
- Windows 2016/2019/2022 required cipher suites
 - TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
 - TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
 - TLS_DHE_RSA_WITH_AES_256_GCM_SHA384
 - TLS_DHE_RSA_WITH_AES_128_GCM_SHA256
- Ensure earlier versions of SSL and TLS in Windows Schannel are disabled and that .NET applications (particularly 4.x) use the system's Windows Schannel configuration. For more information, see the "Enable strong cryptography in .NET Framework 4.5 or higher" article on Microsoft Learn.
- Ensure that the user you run the installation as has administrative rights on each server. You cannot perform the installation unless you have administrative rights to perform the required tasks.
- If the agent will connect using a proxy, ensure the user you are logged in as has internet access on the host machine. Details for connecting using a proxy are detailed in the appropriate procedures for installing and configuring the agent.
- If using Media Server for optical character recognition (OCR), OpenText Core Data Discovery & Risk Insights processing agents and any Media Server host machines they interact with must be within the same network and can not have a proxy between them.
- If you will be sending copies of masked data items to a target location, ensure the most recent version of a 64-bit Chromium-based browser (such as Microsoft Edge, Google Chrome, or Chromium) is installed on the agent host machine.
- Microsoft Outlook 2019 x64 to process PST files located on file systems.

IMPORTANT: The default installation for Outlook 2019 is x32. Ensure you have the x64 version installed.

- SMTP (currently optional)
- Visual C++ 2019 runtime, updated to the most current version
- If processing structured data from Db2 databases, ensure the following are in place.

- Visual C++ 2013 Redistributable, updated to the most current version
- Additional drivers to support processing from Db2 databases are needed on the agent host machine.
 - 1. Download the driver package for your operating system from your Db2 web console.
 - 2. Unpack the driver package.
 - 3. Copy IBM.data.Db2.dl1 and the entire \clidriver directory from the unpacked driver package and place in the \Agent\StructuredDataProcessor directory of the OpenText Core Data Discovery & Risk Insights application installation path. By default, the application installation path is C:\Program Files\OpenText\Core Data Discovery & Risk Insights\Agent\StructuredDataProcessor.

Integrated resources

The following third-party applications are supported by OpenText Core Data Discovery & Risk Insights.

Microsoft Purview Information Protection (MPIP) for file protection in Connect and Manage.

IMPORTANT: OpenText Core Data Discovery & Risk Insights supports the version of MPIP available at the time of this release.

In OpenText Core Data Discovery & Risk Insights, this file protection type is referred to as "Microsoft data protection".

OpenText Media Server 24.4.x for optical character recognition (OCR).

OpenText Core Data Discovery & Risk Insights processing agents and any Media Server host machines they interact with must be within the same network and can not have a proxy between them.

The following third-party applications are required for specific OpenText Core Data Discovery & Risk Insights features.

 Microsoft Excel on the local machine where OpenText Core Data Discovery & Risk Insights is being accessed with a browser. This is required to support uploading term lists using a CSV file.