



**Hewlett Packard**  
Enterprise

# **HPE Web Connector**

Software Version: 11.4

## **Administration Guide**

Document Release Date: June 2017

Software Release Date: June 2017

## Legal notices

### Warranty

The only warranties for Hewlett Packard Enterprise Development LP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HPE shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

### Restricted rights legend

Confidential computer software. Valid license from HPE required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

### Copyright notice

© Copyright 2017 Hewlett Packard Enterprise Development LP

### Trademark notices

Adobe™ is a trademark of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

This product includes an interface of the 'zlib' general purpose compression library, which is Copyright © 1995-2002 Jean-loup Gailly and Mark Adler.

## Documentation updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To check for recent software updates, go to <https://downloads.autonomy.com/productDownloads.jsp>.

To verify that you are using the most recent edition of a document, go to <https://softwaresupport.hpe.com/group/softwaresupport/search-result?doctype=online help>.

This site requires that you register for an HPE Passport and sign in. To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HPE sales representative for details.

## Support

Visit the HPE Software Support Online web site at <https://softwaresupport.hpe.com>.

This web site provides contact information and details about the products, services, and support that HPE Software offers.

HPE Software online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support web site to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Access product documentation
- Manage support contracts
- Look up HPE support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HPE Passport user and sign in. Many also require a support contract.

To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

To find more information about access levels, go to <https://softwaresupport.hpe.com/web/softwaresupport/access-levels>.

To check for recent software updates, go to <https://downloads.autonomy.com/productDownloads.jsp>.

## About this PDF version of online Help

This document is a PDF version of the online Help.

This PDF file is provided so you can easily print multiple topics or read the online Help.

Because this content was originally created to be viewed as online help in a web browser, some topics may not be formatted properly. Some interactive topics may not be present in this PDF version. Those topics can be successfully printed from within the online Help.

# Contents

Chapter 1: Introduction .....	13
HPE Web Connector .....	13
Features and Capabilities .....	13
Supported Actions .....	14
Connector Framework Server .....	14
HPE's IDOL Platform .....	16
System Architecture .....	17
Display Online Help .....	18
Related Documentation .....	19
 Chapter 2: Install HPE Web Connector .....	 20
System Requirements .....	20
Install HPE Web Connector .....	20
Configure the License Server Host and Port .....	20
 Chapter 3: Configure HPE Web Connector .....	 21
HPE Web Connector Configuration File .....	21
Modify Configuration Parameter Values .....	23
Include an External Configuration File .....	24
Include the Whole External Configuration File .....	25
Include Sections of an External Configuration File .....	25
Include a Parameter from an External Configuration File .....	26
Merge a Section from an External Configuration File .....	26
Encrypt Passwords .....	27
Create a Key File .....	27
Encrypt a Password .....	27
Decrypt a Password .....	28
Configure Client Authorization .....	29
Register with a Distributed Connector .....	30
Set Up Secure Communication .....	31
Configure Outgoing SSL Connections .....	31
Configure Incoming SSL Connections .....	32
Backup and Restore the Connector's State .....	33
Backup a Connector's State .....	33
Restore a Connector's State .....	34

Validate the Configuration File .....	34
Example Configuration File .....	34
<b>Chapter 4: Start and Stop the Connector .....</b>	<b>38</b>
Start the Connector .....	38
Verify that HPE Web Connector is Running .....	39
GetStatus .....	39
GetLicenseInfo .....	39
Stop the Connector .....	39
<b>Chapter 5: Send Actions to HPE Web Connector .....</b>	<b>41</b>
Send Actions to HPE Web Connector .....	41
Asynchronous Actions .....	41
Check the Status of an Asynchronous Action .....	42
Cancel an Asynchronous Action that is Queued .....	42
Stop an Asynchronous Action that is Running .....	42
Store Action Queues in an External Database .....	43
Prerequisites .....	43
Configure HPE Web Connector .....	44
Store Action Queues in Memory .....	45
Use XSL Templates to Transform Action Responses .....	46
Example XSL Templates .....	47
<b>Chapter 6: Use the Connector .....</b>	<b>48</b>
Retrieve Information by Crawling the Web .....	48
Choose the Content to Index .....	50
Retrieve Information using a Sitemap .....	51
Retrieve Information through a Proxy Server .....	53
Retrieve Information over SSL .....	54
Incremental Synchronization .....	54
Clip Pages .....	55
Clip Pages Automatically .....	55
Clip Pages using CSS Selectors .....	55
Find Selectors using the CSS Selector Builder Tool .....	56
Choose How Long to Wait for Scripts .....	58
Log On to a Web Site .....	58
Authenticate using Cookies .....	61
Limit the Download Rate .....	61

Retrieve Recently Updated Content .....	62
Render an Image, Thumbnail, or PDF for Ingested Pages .....	64
Split Web Pages into Multiple Documents .....	65
Process XML Feeds .....	68
Run Custom JavaScript on Web Pages .....	69
Schedule Fetch Tasks .....	70
Troubleshoot the Connector .....	71
<b>Chapter 7: Manipulate Documents .....</b>	<b>73</b>
Introduction .....	73
Add a Field to Documents using an Ingest Action .....	73
Customize Document Processing .....	74
Standardize Field Names .....	75
Configure Field Standardization .....	75
Customize Field Standardization .....	76
Run Lua Scripts .....	80
Write a Lua Script .....	80
Run a Lua Script using an Ingest Action .....	82
Example Lua Scripts .....	82
Add a Field to a Document .....	83
Merge Document Fields .....	83
<b>Chapter 8: Ingestion .....</b>	<b>85</b>
Introduction .....	85
Send Data to Connector Framework Server .....	86
Send Data to Haven OnDemand .....	87
Prepare Haven OnDemand .....	87
Send Data to Haven OnDemand .....	87
Send Data to Another Repository .....	89
Index Documents Directly into IDOL Server .....	89
Index Documents into Vertica .....	91
Prepare the Vertica Database .....	92
Send Data to Vertica .....	93
Send Data to a MetaStore .....	93
Run a Lua Script after Ingestion .....	94
<b>Chapter 9: Monitor the Connector .....</b>	<b>96</b>
IDOL Admin .....	96

Prerequisites .....	96
Supported Browsers .....	96
Install IDOL Admin .....	96
Access IDOL Admin .....	97
Use the Connector Logs .....	98
Customize Logging .....	98
Set Up Event Handlers .....	99
Event Handlers .....	100
Configure an Event Handler .....	100
Set Up Performance Monitoring .....	101
Configure the Connector to Pause .....	102
Determine if an Action is Paused .....	103
Set Up Document Tracking .....	103
Chapter 10: Lua Functions and Methods Reference .....	106
General Functions .....	106
abs_path .....	109
base64_decode .....	109
base64_encode .....	109
convert_date_time .....	110
convert_encoding .....	112
copy_file .....	113
create_path .....	113
create_uuid .....	113
delete_file .....	114
delete_path .....	114
doc_tracking .....	115
encrypt .....	116
encrypt_security_field .....	116
extract_date .....	116
file_setdates .....	119
get_config .....	119
get_log .....	120
get_log .....	121
get_log_service .....	121
get_task_config .....	123
get_task_name .....	123
getcwd .....	123
gobble_whitespace .....	124
hash_file .....	124
hash_string .....	124
is_dir .....	125
log .....	125
move_file .....	126

parse_csv .....	126
parse_document_csv .....	127
parse_document_idx .....	129
parse_document_idx .....	129
parse_document_xml .....	130
parse_document_xml .....	132
parse_json .....	133
parse_json_array .....	134
parse_json_object .....	135
parse_xml .....	136
regex_match .....	136
regex_replace_all .....	137
regex_search .....	138
script_path .....	138
send_aci_action .....	139
send_aci_command .....	140
send_and_wait_for_async_aci_action .....	141
send_http_request .....	141
sleep .....	143
unzip_file .....	143
url_escape .....	144
url_unescape .....	144
xml_encode .....	145
zip_file .....	145
LuaConfig Methods .....	146
getEncryptedValue .....	146
getValue .....	147
getValues .....	147
LuaConfig:new .....	148
LuaDocument Methods .....	148
addField .....	150
addSection .....	150
appendContent .....	151
copyField .....	151
copyFieldNoOverwrite .....	152
countField .....	152
deleteField .....	153
getContent .....	153
getField .....	154
getFieldNames .....	155
getFields .....	155
getFieldValue .....	156
getFieldValues .....	156
getNextSection .....	157
getReference .....	157
getSection .....	158

getSectionCount	158
getValueByPath	159
getValuesByPath	159
hasField	160
insertJson	160
insertXml	161
insertXmlWithoutRoot	162
LuaDocument:new	162
removeSection	163
renameField	164
setContent	164
setFieldValue	165
setReference	165
to_idx	166
to_json	166
to_xml	166
writeStubIdx	166
writeStubXml	167
LuaField Methods	167
addField	169
copyField	169
copyFieldNoOverwrite	169
countField	170
deleteAttribute	170
deleteField	171
getAttributeValue	171
getField	172
getFieldNames	172
getFields	172
getFieldValues	173
getValueByPath	174
getValuesByPath	174
hasAttribute	175
hasField	176
insertJson	176
insertXml	177
insertXmlWithoutRoot	177
name	178
renameField	178
setAttributeValue	178
setValue	179
value	179
LuaHttpRequest Methods	179
LuaHttpRequest:new	180
send	181
set_body	181

set_config .....	182
set_header .....	182
set_headers .....	183
set_method .....	183
set_url .....	184
LuaHttpResponse Methods .....	184
get_body .....	185
get_header .....	185
get_headers .....	185
get_http_code .....	186
LuaJSONArray Methods .....	186
LuaJSONArray:new .....	187
append .....	188
clear .....	188
copy .....	188
empty .....	189
exists .....	189
existsByPath .....	190
ipairs .....	191
lookup .....	192
lookupByPath .....	193
size .....	194
string .....	194
LuaJsonObject Methods .....	195
LuaJsonObject:new .....	195
assign .....	196
assign .....	197
clear .....	198
copy .....	198
empty .....	198
erase .....	199
exists .....	199
existsByPath .....	200
lookup .....	202
lookupByPath .....	203
pairs .....	204
size .....	204
string .....	205
LuaJsonValue Methods .....	205
LuaJsonValue:new .....	206
array .....	207
copy .....	207
exists .....	208
existsByPath .....	209
is_array .....	210

is_boolean	210
is_float	211
is_integer	211
is_null	211
is_number	211
is_object	212
is_simple_value	212
is_string	212
lookup	213
lookupByPath	214
object	215
string	215
value	216
LuaLog Methods	217
write_line	217
LuaLogService Methods	218
LuaLogService:new	218
get_log	219
LuaRegexMatch Methods	220
length	220
next	221
position	221
size	222
str	222
LuaXmlDocument Methods	222
root	223
XPathExecute	223
XPathRegisterNs	224
XPathValue	224
XPathValues	224
LuaXmlNodeSet Methods	225
at	225
size	226
LuaXmlNode Methods	226
attr	227
content	227
firstChild	227
lastChild	228
name	228
next	228
nodePath	229
parent	229
prev	229
type	230

LuaXmlAttribute Methods .....	230
name .....	230
next .....	231
prev .....	231
value .....	231
Appendix A: Document Fields .....	233
Glossary .....	234
Send documentation feedback .....	237

# Chapter 1: Introduction

This section provides an overview of the HPE Web Connector.

• <a href="#">HPE Web Connector</a> .....	13
• <a href="#">Connector Framework Server</a> .....	14
• <a href="#">HPE's IDOL Platform</a> .....	16
• <a href="#">System Architecture</a> .....	17
• <a href="#">Display Online Help</a> .....	18
• <a href="#">Related Documentation</a> .....	19

## HPE Web Connector

The Web Connector is an IDOL connector that retrieves information from the World Wide Web. The connector can crawl the Web by following the links that exist on each page, or retrieve the resources listed in a site map.

The Web Connector uses an embedded browser to process Web pages and therefore provides several advantages over the HTTP Connector:

- The HPE Web Connector supports Javascript and dynamic pages. If Javascript is used on a page, the script runs before the connector crawls the page for links and ingests the page. As a result the connector can crawl links generated by the script and the page that is ingested is the final source after any scripts have run.
- The HPE Web Connector can interpret the structure of a page, as defined by the HTML markup, in addition to reading the content. As a result, when configuring the connector to extract links or submit forms, you can identify page elements using CSS selectors rather than regular expressions.

## Features and Capabilities

- The HPE Web Connector retrieves information from Web sites over HTTP.
- The connector can crawl a Web site starting from a page that you specify, or retrieve the pages listed in a site map. When crawling a web site, the connector can follow links that exist in the HTML source of the page or in Adobe Flash content.
- The connector can extract information contained in data URIs. For example, images might be base-64 encoded and included in the source of an HTML page:

```

```

- The connector can log on to Web sites to retrieve content. The connector supports:
  - Basic authentication
  - HTTP Digest authentication.
  - NTLMv2 authentication.

- You can configure the connector to populate and submit HTML forms. This feature is useful when the connector must log on to a Web site.
- The connector uses canonical links in web pages and response headers to de-duplicate content retrieved from the web.

## Supported Actions

The HPE Web Connector supports the following actions:

Action	Supported
Synchronize	✓
Synchronize (identifiers)	✗
Synchronize Groups	✗
Collect	✓
Identifiers	✓
Insert	✗
Delete/Remove	✗
Hold/ReleaseHold	✗
Update	✗
Stub	✗
GetURI	✓
View	✓

## Connector Framework Server

Connector Framework Server (CFS) processes the information that is retrieved by connectors, and then indexes the information into IDOL.

A single CFS can process information from any number of connectors. For example, a CFS might process files retrieved by a File System Connector, web pages retrieved by a Web Connector, and e-mail messages retrieved by an Exchange Connector.

To use the HPE Web Connector to index documents into IDOL Server, you must have a CFS. When you install the HPE Web Connector, you can choose to install a CFS or point the connector to an existing CFS.

For information about how to configure and use Connector Framework Server, refer to the *Connector Framework Server Administration Guide*.

## Filter Documents and Extract Subfiles

The documents that are sent by connectors to CFS contain only metadata extracted from the repository, such as the location of a file or record that the connector has retrieved. CFS uses KeyView to extract the file content and file specific metadata from over 1000 different file types, and adds this information to the documents. This allows IDOL to extract meaning from the information contained in the repository, without needing to process the information in its native format.

CFS also uses KeyView to extract and process sub-files. Sub-files are files that are contained within other files. For example, an e-mail message might contain attachments that you want to index, or a Microsoft Word document might contain embedded objects.

## Manipulate and Enrich Documents

CFS provides features to manipulate and enrich documents before they are indexed into IDOL. For example, you can:

- add additional fields to a document.
- divide long documents into multiple sections.
- run tasks including Education, Optical Character Recognition, or Face Recognition, and add the information that is obtained to the document.
- run a custom Lua script to modify a document.


## Index Documents

After CFS finishes processing documents, it automatically indexes them into one or more indexes. CFS can index documents into:

- **IDOL Server** (or send them to a *Distributed Index Handler*, so that they can be distributed across multiple IDOL servers).
- **Haven OnDemand**.
- **Vertica**.

## Import Process

This section describes the import process for new files that are added to IDOL through CFS.



1. Connectors aggregate documents from repositories and send the files to CFS. A single CFS can process documents from multiple connectors. For example, CFS might receive HTML files from HTTP Connectors, e-mail messages from Exchange Connector, and database records from ODBC Connector.
2. CFS runs pre-import tasks. Pre-Import tasks occur before document content and file-specific metadata is extracted by KeyView.
3. KeyView filters the document content, and extracts sub-files.
4. CFS runs post-import tasks. Post-Import tasks occur after KeyView has extracted document content and file-specific metadata.
5. The data is indexed into IDOL.

## HPE's IDOL Platform

At the core of HPE Web Connector is HPE's *Intelligent Data Operating Layer (IDOL)*.

IDOL gathers and processes unstructured, semi-structured, and structured information in any format from multiple repositories using IDOL connectors and a global relational index. It can automatically form a contextual understanding of the information in real time, linking disparate data sources together based on the concepts contained within them. For example, IDOL can automatically link concepts contained in an email message to a recorded phone conversation, that can be associated with a stock trade. This information is then imported into a format that is easily searchable, adding advanced retrieval, collaboration, and personalization to an application that integrates the technology.


For more information on IDOL, see the *IDOL Getting Started Guide*.

## System Architecture


An IDOL infrastructure can include the following components:

- **Connectors.** Connectors aggregate data from repositories and send the data to CFS.
- **Connector Framework Server (CFS).** Connector Framework Server (CFS) processes and enriches the information that is retrieved by connectors.
- **IDOL Server.** IDOL stores and processes the information that is indexed into it by CFS.
- **Distributed Index Handler (DIH).** The Distributed Index Handler distributes data across multiple IDOL servers. Using multiple IDOL servers can increase the availability and scalability of the system.
- **License Server.** The License server licenses multiple products.

These components can be installed in many different configurations. The simplest installation consists of a single connector, a single CFS, and a single IDOL Server.



A more complex configuration might include more than one connector, or use a Distributed Index Handler (DIH) to index content across multiple IDOL Servers.



## Display Online Help

You can display the HPE Web Connector Reference by sending an action from your web browser. The HPE Web Connector Reference describes the actions and configuration parameters that you can use with HPE Web Connector.

For HPE Web Connector to display help, the help data file (`help.dat`) must be available in the installation folder.

## To display help for HPE Web Connector

1. Start HPE Web Connector.
2. Send the following action from your web browser:

`http://host:port/action=Help`

where:

`host` is the IP address or name of the machine on which HPE Web Connector is installed.

`port` is the ACI port by which you send actions to HPE Web Connector (set by the `Port` parameter in the `[Server]` section of the configuration file).

For example:

`http://12.3.4.56:9000/action=help`

## Related Documentation

The following documents provide further information related to HPE Web Connector.

- *HPE Web Connector Reference*  
The *HPE Web Connector Reference* describes the configuration parameters and actions that you can use with the HPE Web Connector.
- *Connector Framework Server Administration Guide*  
Connector Framework Server (CFS) processes documents that are retrieved by connectors. CFS then indexes the documents into IDOL Server, Haven OnDemand, or Vertica. The *Connector Framework Server Administration Guide* describes how to configure and use CFS.
- *IDOL Getting Started Guide*  
The *IDOL Getting Started Guide* provides an introduction to IDOL. It describes the system architecture, how to install IDOL components, and introduces indexing and security.
- *IDOL Server Administration Guide*  
The *IDOL Server Administration Guide* describes the operations that IDOL server can perform with detailed descriptions of how to set them up.
- *IDOL Document Security Administration Guide*  
The *IDOL Document Security Administration Guide* describes how to protect the information that you index into IDOL Server.
- *License Server Administration Guide*  
This guide describes how to use a License Server to license multiple services.

# Chapter 2: Install HPE Web Connector

This section describes how to install the HPE Web Connector.

- [System Requirements](#) .....20
- [Install HPE Web Connector](#) .....20
- [Configure the License Server Host and Port](#) .....20

## System Requirements

HPE Web Connector can be installed as part of a larger system that includes an IDOL Server and an interface for the information stored in IDOL Server. To maximize performance, HPE recommends that you install IDOL Server and the connector on different machines.

For information about the minimum system requirements required to run IDOL components, including HPE Web Connector, refer to the *IDOL Getting Started Guide*.

## Install HPE Web Connector

The HPE Web Connector can be installed using the IDOL Server installer.

For information about installing the HPE Web Connector using this installer, refer to the *IDOL Getting Started Guide*.

## Configure the License Server Host and Port

HPE Web Connector is licensed through HPE License Server. In the HPE Web Connector configuration file, specify the information required to connect to the License Server.

### To specify the license server host and port

1. Open your configuration file in a text editor.
2. In the [License] section, modify the following parameters to point to your License Server.

LicenseServerHost      The host name or IP address of your License Server.

LicenseServerACIPort    The ACI port of your License Server.

For example:

```
[License]
LicenseServerHost=licenses
LicenseServerACIPort=20000
```

3. Save and close the configuration file.

# Chapter 3: Configure HPE Web Connector

This section describes how to configure the HPE Web Connector.

- [HPE Web Connector Configuration File](#) .....21
- [Modify Configuration Parameter Values](#) .....23
- [Include an External Configuration File](#) .....24
- [Encrypt Passwords](#) .....27
- [Configure Client Authorization](#) .....29
- [Register with a Distributed Connector](#) .....30
- [Set Up Secure Communication](#) .....31
- [Backup and Restore the Connector's State](#) .....33
- [Validate the Configuration File](#) .....34
- [Example Configuration File](#) .....34

## HPE Web Connector Configuration File

You can configure the HPE Web Connector by editing the configuration file. The configuration file is located in the connector's installation folder. You can modify the file with a text editor.

The parameters in the configuration file are divided into sections that represent connector functionality.

Some parameters can be set in more than one section of the configuration file. If a parameter is set in more than one section, the value of the parameter located in the most specific section overrides the value of the parameter defined in the other sections. For example, if a parameter can be set in "TaskName or FetchTasks or Default", the value in the TaskName section overrides the value in the FetchTasks section, which in turn overrides the value in the Default section. This means that you can set a default value for a parameter, and then override that value for specific tasks.

For information about the parameters that you can use to configure the HPE Web Connector, refer to the *HPE Web Connector Reference*.

### Server Section

The [Server] section specifies the ACI port of the connector. It can also contain parameters that control the way the connector handles ACI requests.

### Service Section

The [Service] section specifies the service port of the connector.

## Actions Section

The [Actions] section contains configuration parameters that specify how the connector processes actions that are sent to the ACI port. For example, you can configure event handlers that run when an action starts, finishes, or encounters an error.

## Logging Section

The [Logging] section contains configuration parameters that determine how messages are logged. You can use *log streams* to send different types of message to separate log files. The configuration file also contains a section to configure each of the log streams.

## Connector Section

The [Connector] section contains parameters that control general connector behavior. For example, you can specify a schedule for the fetch tasks that you configure.

## Default Section

The [Default] section is used to define default settings for configuration parameters. For example, you can specify default settings for the tasks in the [FetchTasks] section.

## FetchTasks Section

The [FetchTasks] section lists the fetch tasks that you want to run. A *fetch task* is a task that retrieves data from a repository. Fetch tasks are usually run automatically by the connector, but you can also run a fetch task by sending an action to the connector's ACI port.

In this section, enter the total number of fetch tasks in the `Number` parameter and then list the tasks in consecutive order starting from 0 (zero). For example:

```
[FetchTasks]
Number=2
0=MyTask0
1=MyTask1
```

## [TaskName] Section

The [TaskName] section contains configuration parameters that apply to a specific task. There must be a [TaskName] section for every task listed in the [FetchTasks] section.

## Ingestion Section

The [Ingestion] section specifies where to send the data that is extracted by the connector.

You can send data to a Connector Framework Server, Haven OnDemand, or another connector. For more information about ingestion, see [Ingestion, on page 85](#).

## DistributedConnector Section

The [DistributedConnector] section configures the connector to operate with the Distributed Connector. The Distributed Connector is an ACI server that distributes actions (synchronize, collect and so on) between multiple connectors.

For more information about the Distributed Connector, refer to the *Distributed Connector Administration Guide*.

## ViewServer Section

The [ViewServer] section contains parameters that allow the connector's *view* action to use a View Server. If necessary, the View Server converts files to HTML so that they can be viewed in a web browser.

## License Section

The [License] section contains details about the License server (the server on which your license file is located).

## Document Tracking Section

The [DocumentTracking] section contains parameters that enable the tracking of documents through import and indexing processes.

### **Related Topics**

- [Modify Configuration Parameter Values, below](#)
- [Customize Logging, on page 98](#)

## Modify Configuration Parameter Values

You modify HPE Web Connector configuration parameters by directly editing the parameters in the configuration file. When you set configuration parameter values, you must use UTF-8.

**CAUTION:**

You must stop and restart HPE Web Connector for new configuration settings to take effect.

This section describes how to enter parameter values in the configuration file.

## Enter Boolean Values

The following settings for Boolean parameters are interchangeable:

TRUE = true = ON = on = Y = y = 1

FALSE = false = OFF = off = N = n = 0

## Enter String Values

To enter a comma-separated list of strings when one of the strings contains a comma, you can indicate the start and the end of the string with quotation marks, for example:

```
ParameterName=cat,dog,bird,"wing,beak",turtle
```

Alternatively, you can escape the comma with a backslash:

```
ParameterName=cat,dog,bird,wing\,beak,turtle
```

If any string in a comma-separated list contains quotation marks, you must put this string into quotation marks and escape each quotation mark in the string by inserting a backslash before it. For example:

```
ParameterName="<font face=\"arial\" size=\"+1\"><b>\", \"<p>
```

Here, quotation marks indicate the beginning and end of the string. All quotation marks that are contained in the string are escaped.

## Include an External Configuration File

You can share configuration sections or parameters between ACI server configuration files. The following sections describe different ways to include content from an external configuration file.

You can include a configuration file in its entirety, specified configuration sections, or a single parameter.

When you include content from an external configuration file, the `GetConfig` and `ValidateConfig` actions operate on the combined configuration, after any external content is merged in.

In the procedures in the following sections, you can specify external configuration file locations by using absolute paths, relative paths, and network locations. For example:

```
../sharedconfig.cfg  
K:\sharedconfig\sharedsettings.cfg  
\\example.com\shared\idol.cfg  
file://example.com/shared/idol.cfg
```

Relative paths are relative to the primary configuration file.

**NOTE:**

You can use nested inclusions, for example, you can refer to a shared configuration file that references a third file. However, the external configuration files must not refer back to your original configuration file. These circular references result in an error, and HPE Web Connector does not start.

Similarly, you cannot use any of these methods to refer to a different section in your primary configuration file.

## Include the Whole External Configuration File

This method allows you to import the whole external configuration file at a specified point in your configuration file.

### To include the whole external configuration file

1. Open your configuration file in a text editor.
2. Find the place in the configuration file where you want to add the external configuration file.
3. On a new line, type a left angle bracket (<), followed by the path to and name of the external configuration file, in quotation marks (""). You can use relative paths and network locations. For example:

```
< "K:\sharedconfig\sharedsettings.cfg"
```

4. Save and close the configuration file.

## Include Sections of an External Configuration File

This method allows you to import one or more configuration sections from an external configuration file at a specified point in your configuration file. You can include a whole configuration section in this way, but the configuration section name in the external file must exactly match what you want to use in your file. If you want to use a configuration section from the external file with a different name, see [Merge a Section from an External Configuration File, on the next page](#).

### To include sections of an external configuration file

1. Open your configuration file in a text editor.
2. Find the place in the configuration file where you want to add the external configuration file section.
3. On a new line, type a left angle bracket (<), followed by the path to and name of the external configuration file, in quotation marks (""). You can use relative paths and network locations. After the configuration file name, add the configuration section name that you want to include. For example:

```
< "K:\sharedconfig\extrasettings.cfg" [License]
```

**NOTE:**

You cannot include a section that already exists in your configuration file.

4. Save and close the configuration file.

## Include a Parameter from an External Configuration File

This method allows you to import a parameter from an external configuration file at a specified point in your configuration file. You can include a section or a single parameter in this way, but the value in the external file must exactly match what you want to use in your file.

### To include a parameter from an external configuration file

1. Open your configuration file in a text editor.
2. Find the place in the configuration file where you want to add the parameter from the external configuration file.
3. On a new line, type a left angle bracket (<), followed by the path to and name of the external configuration file, in quotation marks (""). You can use relative paths and network locations. After the configuration file name, add the name of the configuration section name that contains the parameter, followed by the parameter name. For example:

```
< "license.cfg" [License] LicenseServerHost
```

To specify a default value for the parameter, in case it does not exist in the external configuration file, specify the configuration section, parameter name, and then an equals sign (=) followed by the default value. For example:

```
< "license.cfg" [License] LicenseServerHost=localhost
```

4. Save and close the configuration file.

## Merge a Section from an External Configuration File

This method allows you to include a configuration section from an external configuration file as part of your HPE Web Connector configuration file. For example, you might want to specify a standard SSL configuration section in an external file and share it between several servers. You can use this method if the configuration section that you want to import has a different name to the one you want to use.

### To merge a configuration section from an external configuration file

1. Open your configuration file in a text editor.
2. Find or create the configuration section that you want to include from an external file. For example:

```
[SSLOptions1]
```

3. After the configuration section name, type a left angle bracket (<), followed by the path to and name of the external configuration file, in quotation marks (""). You can use relative paths and network locations. For example:

```
[SSLOptions1] < "../sharedconfig/ssloptions.cfg"
```

If the configuration section name in the external configuration file does not match the name that you want to use in your configuration file, specify the section to import after the configuration file name. For example:

```
[SSLOptions1] < "../sharedconfig/ssloptions.cfg" [SharedSSLOptions]
```

In this example, HPE Web Connector uses the values in the [SharedSSLOptions] section of the external configuration file as the values in the [SSLOptions1] section of the HPE Web Connector configuration file.

**NOTE:**

You can include additional configuration parameters in the section in your file. If these parameters also exist in the imported external configuration file, HPE Web Connector uses the values in the local configuration file. For example:

```
[SSLOptions1] < "ssloptions.cfg" [SharedSSLOptions]  
SSLCACertificatesPath=C:\IDOL\HTTPConnector\CACERTS\
```

4. Save and close the configuration file.

## Encrypt Passwords

HPE recommends that you encrypt all passwords that you enter into a configuration file.

## Create a Key File

A key file is required to use AES encryption.

### *To create a new key file*

1. Open a command-line window and change directory to the HPE Web Connector installation folder.
2. At the command line, type:

```
outpassword -x -tAES -oKeyFile=./MyKeyFile.ky
```

A new key file is created with the name MyKeyFile.ky

**CAUTION:**

To keep your passwords secure, you must protect the key file. Set the permissions on the key file so that only authorized users and processes can read it. HPE Web Connector must be able to read the key file to decrypt passwords, so do not move or rename it.

## Encrypt a Password

The following procedure describes how to encrypt a password.

### *To encrypt a password*

1. Open a command-line window and change directory to the HPE Web Connector installation folder.
2. At the command line, type:

```
autpassword -e -tEncryptionType [-oKeyFile] [-cFILE -sSECTION -pPARAMETER] PasswordString
```

where:

Option	Description
-t <i>EncryptionType</i>	The type of encryption to use: <ul style="list-style-type: none"> <li>• Basic</li> <li>• AES</li> </ul> For example: -tAES <b>NOTE:</b> AES is more secure than basic encryption.
-oKeyFile	AES encryption requires a key file. This option specifies the path and file name of a key file. The key file must contain 64 hexadecimal characters. For example: -oKeyFile=./key.ky
-cFILE -sSECTION -pPARAMETER	(Optional) You can use these options to write the password directly into a configuration file. You must specify all three options. <ul style="list-style-type: none"> <li>• -c. The configuration file in which to write the encrypted password.</li> <li>• -s. The name of the section in the configuration file in which to write the password.</li> <li>• -p. The name of the parameter in which to write the encrypted password.</li> </ul> For example: -c./Config.cfg -sMyTask -pPassword
<i>PasswordString</i>	The password to encrypt.

For example:

```
autpassword -e -tBASIC MyPassword
```

```
autpassword -e -tAES -oKeyFile=./key.ky MyPassword
```

```
autpassword -e -tAES -oKeyFile=./key.ky -c./Config.cfg -sDefault -pPassword MyPassword
```

The password is returned, or written to the configuration file.

## Decrypt a Password

The following procedure describes how to decrypt a password.

### To decrypt a password

1. Open a command-line window and change directory to the HPE Web Connector installation folder.

2. At the command line, type:

```
outpassword -d -tEncryptionType [-oKeyFile] PasswordString
```

where:

Option	Description
-t <i>EncryptionType</i>	The type of encryption: <ul style="list-style-type: none"><li>• Basic</li><li>• AES</li></ul> For example: -tAES
-oKeyFile	AES encryption and decryption requires a key file. This option specifies the path and file name of the key file used to decrypt the password. For example: -oKeyFile=./key.ky
<i>PasswordString</i>	The password to decrypt.

For example:

```
outpassword -d -tBASIC 9t3M3t7awt/J8A
```

```
outpassword -d -tAES -oKeyFile=./key.ky 9t3M3t7awt/J8A
```

The password is returned in plain text.

## Configure Client Authorization

You can configure HPE Web Connector to authorize different operations for different connections.

Authorization roles define a set of operations for a set of users. You define the operations by using the `StandardRoles` configuration parameter, or by explicitly defining a list of allowed actions in the `Actions` and `ServiceActions` parameters. You define the authorized users by using a client IP address, SSL identities, and GSS principals, depending on your security and system configuration.

For more information about the available parameters, see the *HPE Web Connector Reference*.

### To configure authorization roles

1. Open your configuration file in a text editor.
2. Find the `[AuthorizationRoles]` section, or create one if it does not exist.
3. In the `[AuthorizationRoles]` section, list the user authorization roles that you want to create.  
For example:

```
[AuthorizationRoles]  
0=AdminRole  
1=UserRole
```

4. Create a section for each authorization role that you listed. The section name must match the name that you set in the `[AuthorizationRoles]` list. For example:

```
[AdminRole]
```

5. In the section for each role, define the operations that you want the role to be able to perform. You can set `StandardRoles` to a list of appropriate values, or specify an explicit list of allowed actions by using `Actions` and `ServiceActions`. For example:

```
[AdminRole]
```

```
StandardRoles=Admin,Index,ServiceControl,ServiceStatus
```

```
[UserRole]
```

```
Actions=GetVersion
```

```
ServiceActions=GetStatus
```

**NOTE:**

The standard roles do not overlap. If you want a particular role to be able to perform all actions, you must include all the standard roles, or ensure that the clients, SSL identities, and so on, are assigned to all relevant roles.

6. In the section for each role, define the access permissions for the role, by setting `Clients`, `SSLIdentities`, and `GSSPrincipals`, as appropriate. If an incoming connection matches one of the allowed clients, principals, or SSL identities, the user has permission to perform the operations allowed by the role. For example:

```
[AdminRole]
```

```
StandardRoles=Admin,Index,ServiceControl,ServiceStatus
```

```
Clients=localhost
```

```
SSLIdentities=admin.example.com
```

7. Save and close the configuration file.
8. Restart HPE Web Connector for your changes to take effect.

## Register with a Distributed Connector

To receive actions from a Distributed Connector, a connector must register with the Distributed Connector and join a *connector group*. A connector group is a group of similar connectors. The connectors in a group must be of the same type (for example, all HTTP Connectors), and must be able to access the same repository.

To configure a connector to register with a Distributed Connector, follow these steps. For more information about the Distributed Connector, refer to the *Distributed Connector Administration Guide*.

### To register with a Distributed Connector

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the `[DistributedConnector]` section, set the following parameters:

`RegisterConnector` (Required) To register with a Distributed Connector, set this parameter to `true`.

HostN	(Required) The host name or IP address of the Distributed Connector.
PortN	(Required) The ACI port of the Distributed Connector.
DataPortN	(Optional) The data port of the Distributed Connector.
ConnectorGroup	(Required) The name of the connector group to join. The value of this parameter is passed to the Distributed Connector.
ConnectorPriority	(Optional) The Distributed Connector can distribute actions to connectors based on a priority value. The lower the value assigned to ConnectorPriority, the higher the probability that an action is assigned to this connector, rather than other connectors in the same connector group.
SharedPath	(Optional) The location of a shared folder that is accessible to all of the connectors in the ConnectorGroup. This folder is used to store the connectors' datastore files, so that whichever connector in the group receives an action, it can access the information required to complete it. If you set the DataPortN parameter, the datastore file is streamed directly to the Distributed Connector, and this parameter is ignored.

4. Save and close the configuration file.
5. Start the connector.

The connector registers with the Distributed Connector. When actions are sent to the Distributed Connector for the connector group that you configured, they are forwarded to this connector or to another connector in the group.

## Set Up Secure Communication

You can configure Secure Socket Layer (SSL) connections between the connector and other ACI servers.

## Configure Outgoing SSL Connections

To configure the connector to send data to other components (for example Connector Framework Server) over SSL, follow these steps.

### To configure outgoing SSL connections

1. Open the HPE Web Connector configuration file in a text editor.
2. Specify the name of a section in the configuration file where the SSL settings are provided:
  - To send data to an ingestion server over SSL, set the `IngestSSLConfig` parameter in the `[Ingestion]` section. To send data from a single fetch task to an ingestion server over SSL, set `IngestSSLConfig` in a `[TaskName]` section.
  - To send data to a Distributed Connector over SSL, set the `SSLConfig` parameter in the `[DistributedConnector]` section.

- To send data to a View Server over SSL, set the `SSLConfig` parameter in the `[ViewServer]` section.

You can use the same settings for each connection. For example:

```
[Ingestion]
IngestSSLConfig=SSLOptions
```

```
[DistributedConnector]
SSLConfig=SSLOptions
```

3. Create a new section in the configuration file. The name of the section must match the name you specified in the `IngestSSLConfig` or `SSLConfig` parameter. Then specify the SSL settings to use.

`SSLMethod`            The SSL protocol to use.

`SSLCertificate`    (Optional) The SSL certificate to use (in PEM format).

`SSLPrivateKey`    (Optional) The private key for the SSL certificate (in PEM format).

For example:

```
[SSLOptions]
SSLMethod=TLSV1.2
SSLCertificate=host1.crt
SSLPrivateKey=host1.key
```

4. Save and close the configuration file.
5. Restart the connector.

#### **Related Topics**

- [Start and Stop the Connector, on page 38](#)

## **Configure Incoming SSL Connections**

To configure a connector to accept data sent to its ACI port over SSL, follow these steps.

### **To configure an incoming SSL Connection**

1. Stop the connector.
2. Open the configuration file in a text editor.
3. In the `[Server]` section set the `SSLConfig` parameter to specify the name of a section in the configuration file for the SSL settings. For example:

```
[Server]
SSLConfig=SSLOptions
```

4. Create a new section in the configuration file (the name must match the name you used in the `SSLConfig` parameter). Then, use the SSL configuration parameters to specify the details for the connection. You must set the following parameters:

`SSLMethod`            The SSL protocol to use.

`SSLCertificate` The SSL certificate to use (in PEM format).

`SSLPrivateKey` The private key for the SSL certificate (in PEM format).

For example:

```
[SSLOptions]
SSLMethod=TLSV1.2
SSLCertificate=host1.crt
SSLPrivateKey=host1.key
```

5. Save and close the configuration file.
6. Restart the connector.

### **Related Topics**

- [Start and Stop the Connector, on page 38](#)

## **Backup and Restore the Connector's State**

After configuring a connector, and while the connector is running, you can create a backup of the connector's state. In the event of a failure, you can restore the connector's state from the backup.

To create a backup, use the `backupServer` action. The `backupServer` action saves a ZIP file to a path that you specify. The backup includes:

- a copy of the `actions` folder, which stores information about actions that have been queued, are running, and have finished.
- a copy of the configuration file.
- a copy of the connector's datastore files, which contain information about the files, records, or other data that the connector has retrieved from a repository.

## **Backup a Connector's State**

### **To create a backup of the connectors state**

- In the address bar of your Web browser, type the following action and press **ENTER**:

```
http://host:port/action=backupServer&path=path
```

where,

*host* The host name or IP address of the machine where the connector is running.

*port* The connector's ACI port.

*path* The folder where you want to save the backup.

For example:

```
http://localhost:1234/action=backupServer&path=./backups
```

## Restore a Connector's State

### To restore a connector's state

- In the address bar of your Web browser, type the following action and press **ENTER**:

```
http://host:port/action=restoreServer&filename=filename
```

where,

*host*            The host name or IP address of the machine where the connector is running.

*port*            The connector's ACI port.

*filename*        The path of the backup that you created.

For example:

```
http://localhost:1234/action=restoreServer&filename=./backups/filename.zip
```

## Validate the Configuration File

You can use the `ValidateConfig` service action to check for errors in the configuration file.

### NOTE:

For the `ValidateConfig` action to validate a configuration section, HPE Web Connector must have previously read that configuration. In some cases, the configuration might be read when a task is run, rather than when the component starts up. In these cases, `ValidateConfig` reports any unread sections of the configuration file as unused.

### To validate the configuration file

- Send the following action to HPE Web Connector:

```
http://Host:ServicePort/action=ValidateConfig
```

where:

*Host*            is the host name or IP address of the machine where HPE Web Connector is installed.

*ServicePort*    is the service port, as specified in the `[Service]` section of the configuration file.

## Example Configuration File

```
[License]  
LicenseServerHost=licenses  
LicenseServerACIPort=20000
```

```
[Service]
ServicePort=17006

[Server]
Port=7006
XSLTemplates=TRUE

[AuthorizationRoles]
0=AdminRole
1=QueryRole

[AdminRole]
StandardRoles=admin,servicecontrol,query,servicestatus
Clients=:1,127.0.0.1

[QueryRole]
StandardRoles=query,servicestatus
Clients=*

[Logging]
LogLevel=FULL
LogEcho=TRUE
0=ApplicationLogStream
1=ActionLogStream
2=SynchronizeLogStream

[ApplicationLogStream]
LogFile=application.log
LogTypeCSVs=application

[ActionLogStream]
LogFile=action.log
LogTypeCSVs=action

[SynchronizeLogStream]
LogFile=synchronize.log
LogTypeCSVs=synchronize

[Connector]
TempDirectory=temp
EnableScheduledTasks=TRUE
ScheduleRepeatSecs=86400
ScheduleCycles=-1

[Ingestion]
IngesterType=CFS
IngestHost=localhost
IngestPort=7000
IndexDatabase=WebConnector
```

```
[FetchTasks]
SSLMethod=SSLV23
Number=1
0=MyTask0

[MyTask0]
//The url from which to start the crawl
Url=http://www.mywebsite.com

//Regexes to restrict pages that are crawled for links
SpiderUrlMustHaveRegex=
SpiderUrlCantHaveRegex=

//Regexes to restrict pages that are indexed.
UrlMustHaveRegex=
UrlCantHaveRegex=
PageMustHaveRegex=
PageCantHaveRegex=

//The delay between processing pages, per sync thread
PageDelay=5s

//Stay on the same site as the starting url
StayOnSite=true

//Maximum amount of time to spend crawling, 0 indicating unlimited
SiteDuration=0s

//Maximum number of pages to ingest per synchronize run, 0 indicating unlimited
MaxPages=0

//Minimum size that a page must be for it to be ingested
MinPageSize=0

//Maximum size that a page must be for it to be ingested, 0 indicating unlimited
MaxPageSize=0

//Maximum number of links a page can have before it is not ingested, 0 indicating
unlimited
MaxLinksPerPage=0

//Follow robots.txt and ROBOTS meta tag commands
FollowRobotProtocol=true

//The UserAgent sent in the request headers
SpiderAs=Autn-WK00P

//Maximum depth to spider to, -1 indicating unlimited.
```

```
Depth=-1
```

```
//Follow links found in flash content  
FollowFlash=false
```

```
//Proxy details  
ProxyHost=  
ProxyPort=  
ProxyUser=  
ProxyPassword=
```

```
//Authentication details sent if 401 is returned by the server.  
//Supports Basic, NTLM V2 and Digest-MD5.  
AuthUser=  
AuthPassword=
```

# Chapter 4: Start and Stop the Connector

This section describes how to start and stop the HPE Web Connector.

- [Start the Connector](#) ..... 38
- [Verify that HPE Web Connector is Running](#) ..... 39
- [Stop the Connector](#) ..... 39

## NOTE:

You must start and stop the Connector Framework Server separately from the HPE Web Connector.

## Start the Connector

After you have installed and configured a connector, you are ready to run it. Start the connector using one of the following methods.

### Start the Connector on Windows

#### To start the connector using Windows Services

1. Open the Windows Services dialog box.
2. Select the connector service, and click **Start**.
3. Close the Windows Services dialog box.

#### To start the connector by running the executable

- In the connector installation directory, double-click the connector executable file.

### Start the Connector on UNIX

To start the connector on a UNIX operating system, follow these steps.

#### To start the connector using the UNIX start script

1. Change to the installation directory.
2. Enter the following command:  

```
./startconnector.sh
```
3. If you want to check the HPE Web Connector service is running, enter the following command:

```
ps -aef | grep ConnectorInstallName
```

This command returns the HPE Web Connector service process ID number if the service is running.

## Verify that HPE Web Connector is Running

After starting HPE Web Connector, you can run the following actions to verify that HPE Web Connector is running.

- [GetStatus](#)
- [GetLicenseInfo](#)

### GetStatus

You can use the `GetStatus` service action to verify the HPE Web Connector is running. For example:

```
http://Host:ServicePort/action=GetStatus
```

**NOTE:**

You can send the `GetStatus` action to the ACI port instead of the service port. The `GetStatus` ACI action returns information about the HPE Web Connector setup.

### GetLicenseInfo

You can send a `GetLicenseInfo` action to HPE Web Connector to return information about your license. This action checks whether your license is valid and returns the operations that your license includes.

Send the `GetLicenseInfo` action to the HPE Web Connector ACI port. For example:

```
http://Host:ACIport/action=GetLicenseInfo
```

The following result indicates that your license is valid.

```
<autn:license>  
  <autn:validlicense>true</autn:validlicense>  
</autn:license>
```

As an alternative to submitting the `GetLicenseInfo` action, you can view information about your license, and about licensed and unlicensed actions, on the **License** tab in the Status section of IDOL Admin.

## Stop the Connector

You must stop the connector before making any changes to the configuration file.

### To stop the connector using Windows Services

1. Open the Windows Services dialog box.
2. Select the *ConnectorInstalLName* service, and click **Stop**.

3. Close the Windows Services dialog box.

**To stop the connector by sending an action to the service port**

- Type the following command in the address bar of your Web browser, and press ENTER:

`http://host:ServicePort/action=stop`

*host*            The IP address or host name of the machine where the connector is running.

*ServicePort*   The connector's service port (specified in the [Service] section of the connector's configuration file).

# Chapter 5: Send Actions to HPE Web Connector

This section describes how to send actions to HPE Web Connector.

- [Send Actions to HPE Web Connector](#) .....41
- [Asynchronous Actions](#) .....41
- [Store Action Queues in an External Database](#) .....43
- [Store Action Queues in Memory](#) .....45
- [Use XSL Templates to Transform Action Responses](#) .....46

## Send Actions to HPE Web Connector

HPE Web Connector actions are HTTP requests, which you can send, for example, from your web browser. The general syntax of these actions is:

```
http://host:port/action=action&parameters
```

where:

- host* is the IP address or name of the machine where HPE Web Connector is installed.
- port* is the HPE Web Connector ACI port. The ACI port is specified by the `Port` parameter in the [Server] section of the HPE Web Connector configuration file. For more information about the `Port` parameter, see the *HPE Web Connector Reference*.
- action* is the name of the action you want to run.
- parameters* are the required and optional parameters for the action.

**NOTE:**  
Separate individual parameters with an ampersand (&). Separate parameter names from values with an equals sign (=). You must percent-encode all parameter values.

For more information about actions, see the *HPE Web Connector Reference*.

## Asynchronous Actions

When you send an asynchronous action to HPE Web Connector, the connector adds the task to a queue and returns a token. HPE Web Connector performs the task when a thread becomes available. You can use the token with the `QueueInfo` action to check the status of the action and retrieve the results of the action.

Most of the features provided by the connector are available through `action=fetch`, so when you use the `QueueInfo` action, query the `fetch` action queue, for example:

```
/action=QueueInfo&QueueName=Fetch&QueueAction=GetStatus
```

## Check the Status of an Asynchronous Action

To check the status of an asynchronous action, use the token that was returned by HPE Web Connector with the `QueueInfo` action. For more information about the `QueueInfo` action, refer to the *HPE Web Connector Reference*.

### To check the status of an asynchronous action

- Send the `QueueInfo` action to HPE Web Connector with the following parameters.

<code>QueueName</code>	The name of the action queue that you want to check.
<code>QueueAction</code>	The action to perform. Set this parameter to <code>GetStatus</code> .
<code>Token</code>	(Optional) The token that the asynchronous action returned. If you do not specify a token, HPE Web Connector returns the status of every action in the queue.

For example:

```
/action=QueueInfo&QueueName=fetch&QueueAction=getstatus&Token=...
```

## Cancel an Asynchronous Action that is Queued

To cancel an asynchronous action that is waiting in a queue, use the following procedure.

### To cancel an asynchronous action that is queued

- Send the `QueueInfo` action to HPE Web Connector with the following parameters.

<code>QueueName</code>	The name of the action queue that contains the action to cancel.
<code>QueueAction</code>	The action to perform . Set this parameter to <code>Cancel</code> .
<code>Token</code>	The token that the asynchronous action returned.

For example:

```
/action=QueueInfo&QueueName=fetch&QueueAction=Cancel&Token=...
```

## Stop an Asynchronous Action that is Running

You can stop an asynchronous action at any point.

### To stop an asynchronous action that is running

- Send the QueueInfo action to HPE Web Connector with the following parameters.

QueueName	The name of the action queue that contains the action to stop.
QueueAction	The action to perform. Set this parameter to <b>Stop</b> .
Token	The token that the asynchronous action returned.

For example:

```
/action=QueueInfo&QueueName=fetch&QueueAction=Stop&Token=...
```

## Store Action Queues in an External Database

HPE Web Connector provides asynchronous actions. Each asynchronous action has a queue to store requests until threads become available to process them. You can configure HPE Web Connector to store these queues either in an internal database file, or in an external database hosted on a database server.

The default configuration stores queues in an internal database. Using this type of database does not require any additional configuration.

You might want to store the action queues in an external database so that several servers can share the same queues. In this configuration, sending a request to any of the servers adds the request to the shared queue. Whenever a server is ready to start processing a new request, it takes the next request from the shared queue, runs the action, and adds the results of the action back to the shared database so that they can be retrieved by any of the servers. You can therefore distribute requests between components without configuring a Distributed Action Handler (DAH).

#### **NOTE:**

You cannot use multiple servers to process a single request. Each request is processed by one server.

#### **NOTE:**

Although you can configure several connectors to share the same action queues, the connectors do not share fetch task data. If you share action queues between several connectors and distribute synchronize actions, the connector that processes a synchronize action cannot determine which items the other connectors have retrieved. This might result in some documents being ingested several times.

## Prerequisites

- Supported databases:
  - PostgreSQL 9.0 or later.
  - MySQL 5.0 or later.
- If you use PostgreSQL, you must set the PostgreSQL ODBC driver setting MaxVarChar to 0 (zero).

If you use a DSN, you can configure this parameter when you create the DSN. Otherwise, you can set the `MaxVarcharSize` parameter in the connection string.

## Configure HPE Web Connector

To configure HPE Web Connector to use a shared action queue, follow these steps.

### To store action queues in an external database

1. Stop HPE Web Connector, if it is running.
2. Open the HPE Web Connector configuration file.
3. Find the relevant section in the configuration file:
  - To store queues for all asynchronous actions in the external database, find the `[Actions]` section.
  - To store the queue for a single asynchronous action in the external database, find the section that configures that action.
4. Set the following configuration parameters.

`AsyncStoreLibraryDirectory` The path of the directory that contains the library to use to connect to the database. Specify either an absolute path, or a path relative to the server executable file.

`AsyncStoreLibraryName` The name of the library to use to connect to the database. You can omit the file extension. The following libraries are available:

- `postgresAsyncStoreLibrary` - for connecting to a PostgreSQL database.
- `mysqlAsyncStoreLibrary` - for connecting to a MySQL database.

`ConnectionString` The connection string to use to connect to the database. The user that you specify must have permission to create tables in the database. For example:

```
ConnectionString=DSN=my_ASYNC_QUEUE
```

or

```
ConnectionString=Driver={PostgreSQL};  
Server=10.0.0.1; Port=9876;  
Database=SharedActions; Uid=user; Pwd=password;  
MaxVarcharSize=0;
```

For example:

```
[Actions]  
AsyncStoreLibraryDirectory=acidlls  
AsyncStoreLibraryName=postgresAsyncStoreLibrary  
ConnectionString=DSN=ActionStore
```

5. If you are using the same database to store action queues for more than one type of component,

set the following parameter in the [Actions] section of the configuration file.

**DatastoreSharingGroupName** The group of components to share actions with. You can set this parameter to any string, but the value must be the same for each server in the group. For example, to configure several HPE Web Connectors to share their action queues, set this parameter to the same value in every HPE Web Connector configuration. HPE recommends setting this parameter to the name of the component.

**CAUTION:**

Do not configure different components (for example, two different types of connector) to share the same action queues. This will result in unexpected behavior.

For example:

```
[Actions]
...
DatastoreSharingGroupName=ComponentType
```

6. Save and close the configuration file.

When you start HPE Web Connector it connects to the shared database.

## Store Action Queues in Memory

HPE Web Connector provides asynchronous actions. Each asynchronous action has a queue to store requests until threads become available to process them. These queues are usually stored in a datastore file or in a database hosted on a database server, but in some cases you can increase performance by storing these queues in memory.

**NOTE:**

Storing action queues in memory improves performance only when the server receives large numbers of actions that complete quickly. Before storing queues in memory, you should also consider the following:

- The queues (including queued actions and the results of finished actions) are lost if HPE Web Connector stops unexpectedly, for example due to a power failure or the component being forcibly stopped. This could result in some requests being lost, and if the queues are restored to a previous state some actions could run more than once.
- Storing action queues in memory prevents multiple instances of a component being able to share the same queues.
- Storing action queues in memory increases memory use, so please ensure that the server has sufficient memory to complete actions and store the action queues.

If you stop HPE Web Connector cleanly, HPE Web Connector writes the action queues from memory to disk so that it can resume processing when it is next started.

To configure HPE Web Connector to store asynchronous action queues in memory, follow these steps.

### To store action queues in memory

1. Stop HPE Web Connector, if it is running.
2. Open the HPE Web Connector configuration file and find the [Actions] section.
3. If you have set any of the following parameters, remove them:
  - AsyncStoreLibraryDirectory
  - AsyncStoreLibraryName
  - ConnectionString
  - UseStringentDatastore
4. Set the following configuration parameters.

UseInMemoryDatastore

A Boolean value that specifies whether to keep the queues for asynchronous actions in memory. Set this parameter to TRUE.

InMemoryDatastoreBackupIntervalMins

(Optional) The time interval (in minutes) at which the action queues are written to disk. Writing the queues to disk can reduce the number of queued actions that would be lost if HPE Web Connector stops unexpectedly, but configuring a frequent backup will increase the load on the datastore and might reduce performance.

For example:

```
[Actions]
UseInMemoryDatastore=TRUE
InMemoryDatastoreBackupIntervalMins=30
```

5. Save and close the configuration file.

When you start HPE Web Connector, it stores action queues in memory.

## Use XSL Templates to Transform Action Responses

You can transform the action responses returned by HPE Web Connector using XSL templates. You must write your own XSL templates and save them with either an .xsl or .tmpl file extension.

After creating the templates, you must configure HPE Web Connector to use them, and then apply them to the relevant actions.

### To enable XSL transformations

1. Ensure that the autnxs1t library is located in the same directory as your configuration file. If the library is not included in your installation, you can obtain it from HPE Support.
2. Open the HPE Web Connector configuration file in a text editor.
3. In the [Server] section, ensure that the XSLTemplates parameter is set to true.

**CAUTION:**

If `XSLTemplates` is set to `true` and the `autnxs1t` library is not present in the same directory as the configuration file, the server will not start.

4. (Optional) In the `[Paths]` section, set the `TemplateDirectory` parameter to the path to the directory that contains your XSL templates. The default directory is `acitemplates`.
5. Save and close the configuration file.
6. Restart HPE Web Connector for your changes to take effect.

**To apply a template to action output**

- Add the following parameters to the action:

<code>Template</code>	The name of the template to use to transform the action output. Exclude the folder path and file extension.
<code>ForceTemplateRefresh</code>	(Optional) If you modified the template after the server started, set this parameter to <code>true</code> to force the ACI server to reload the template from disk rather than from the cache.

For example:

```
action=QueueInfo&QueueName=Fetch
      &QueueAction=GetStatus
      &Token=...
      &Template=myTemplate
```

In this example, HPE Web Connector applies the XSL template `myTemplate` to the response from a `QueueInfo` action.

**NOTE:**

If the action returns an error response, HPE Web Connector does not apply the XSL template.

## Example XSL Templates

HPE Web Connector includes the following sample XSL templates, in the `acitemplates` folder:

XSL Template	Description
<code>FetchIdentifiers</code>	Transforms the output from the <code>Identifiers</code> fetch action, to show what is in the repository.
<code>LuaDebug</code>	Transforms the output from the <code>LuaDebug</code> action, to assist with debugging Lua scripts.

# Chapter 6: Use the Connector

This section describes how to use the connector.

• Retrieve Information by Crawling the Web .....	48
• Retrieve Information using a Sitemap .....	51
• Retrieve Information through a Proxy Server .....	53
• Retrieve Information over SSL .....	54
• Incremental Synchronization .....	54
• Clip Pages .....	55
• Choose How Long to Wait for Scripts .....	58
• Log On to a Web Site .....	58
• Authenticate using Cookies .....	61
• Limit the Download Rate .....	61
• Retrieve Recently Updated Content .....	62
• Render an Image, Thumbnail, or PDF for Ingested Pages .....	64
• Split Web Pages into Multiple Documents .....	65
• Process XML Feeds .....	68
• Run Custom JavaScript on Web Pages .....	69
• Schedule Fetch Tasks .....	70
• Troubleshoot the Connector .....	71

## Retrieve Information by Crawling the Web

This section describes how to retrieve content from a Web site by crawling a site (following links from one page to another).

**TIP:**

*IDOL Expert* includes a full step-by-step guide that demonstrates how to ingest information from a website. The *IDOL Expert* guide discusses strategies for selecting the content to crawl and ingest, and includes an example configuration that you can run.

### To create a new Fetch Task

1. Stop the connector.
2. Open the configuration file in a text editor.
3. In the [FetchTasks] section of the configuration file, specify the number of fetch tasks using the `Number` parameter. If you are configuring the first fetch task, type `Number=1`. If one or more fetch tasks have already been configured, increase the value of the `Number` parameter by one (1). Below the `Number` parameter, specify the names of the fetch tasks, starting from zero (0). For example:

```
[FetchTasks]
```

```
Number=1
```

```
0=MyTask
```

4. Below the [FetchTasks] section, create a new *TaskName* section. The name of the section must match the name of the new fetch task. For example:

```
[FetchTasks]
```

```
Number=1
```

```
0=MyTask
```

```
[MyTask]
```

5. In the new section, set the following parameters.

Url	The URL of the page to start crawling from. You can specify multiple URLs to start crawling from by setting a comma-separated list of values or using a numbered list of parameters (Url0=, Url1=, and so on).
Depth	(Optional) The maximum depth to which the connector follows links when crawling. For example, to index all pages that can be reached from the Url by following no more than three links, set Depth=3. The default value of this parameter (Depth=-1) specifies no limit.
StayOnSite	(Optional) A Boolean value that specifies whether the connector stays on the Web site identified by the Url parameter. To allow the connector to follow links to other Web sites, set this parameter to false.
SpiderUrlCantHaveRegex	(Optional) A regular expression to restrict the pages that are crawled by the connector. If the full URL of a page matches the regular expression, the page is not downloaded, crawled, or ingested.
SpiderUrlMustHaveRegex	(Optional) A regular expression to restrict the pages that are crawled by the connector. The full URL of a page must match the regular expression, otherwise it is not downloaded, crawled, or ingested.

For example:

```
[MyTask]
```

```
Url=http://www.example.com/
```

```
StayOnSite=true
```

```
SpiderUrlCantHaveRegex=.*subdomain\.example\.com.*
```

6. (Optional) If you want to index specific pages, you can use the following configuration parameters:

PageCantHaveRegex	A regular expression to restrict the content retrieved by the connector. If the content of a page matches the regular expression, the page is not ingested. This
-------------------	--

	parameter applies to all file types.
PageMustHaveRegex	A regular expression to restrict the content retrieved by the connector. The content of a page must match the regular expression, otherwise the page is not ingested. This parameter applies to all file types.
UrlCantHaveRegex	A regular expression to restrict the content retrieved by the connector. If the full URL of a page matches the regular expression, the page is not ingested. This parameter applies to all file types, for example HTML pages, images, text documents, and so on.
UrlMustHaveRegex	A regular expression to restrict the content retrieved by the connector. The full URL of a page must match the regular expression, otherwise the page is not ingested. This parameter applies to all file types, for example HTML pages, images, text documents, and so on.

7. (Optional) If the connector is installed on a machine that is behind a proxy server, see [Retrieve Information through a Proxy Server, on page 53](#).
8. Save and close the configuration file.

#### **Related Topics**

- [Retrieve Information using a Sitemap, on the next page](#)
- [Schedule Fetch Tasks, on page 70](#)
- [Choose the Content to Index, below](#)

## **Choose the Content to Index**

When you configure a fetch task to retrieve information from the Web, you can exclude pages from being downloaded and crawled, and exclude pages from being ingested.

- The configuration parameters `SpiderUrlMustHaveRegex` and `SpiderUrlCantHaveRegex` exclude pages from being downloaded and crawled for links.
- The configuration parameters `UrlMustHaveRegex` and `UrlCantHaveRegex` exclude pages from being ingested.

There is an important difference between these two pairs of parameters. Pages can be crawled (the links on the page are followed by the connector) but not ingested.

For example, consider the following site structure:

```
index.html
|- products/software.html
|   |- products/software/product1.html
|   |- products/software/product2.html
|   |- products/software/product3.html
|
|- products/hardware.html
```

```
| - products/hardware/hardware1.html  
| - products/hardware/hardware2.html  
| - products/hardware/hardware3.html
```

If you set `SpiderUrlCantHaveRegex=.*software\.html`, the connector does not download or crawl the page `products/software.html`, so the links to the pages `product1.html`, `product2.html`, and `product3.html` are not followed. The pages highlighted below are therefore not ingested:

```
index.html  
| - products/software.html  
|   | - products/software/product1.html  
|   | - products/software/product2.html  
|   | - products/software/product3.html  
|  
| - products/hardware.html  
|   | - products/hardware/hardware1.html  
|   | - products/hardware/hardware2.html  
|   | - products/hardware/hardware3.html
```

**TIP:**

Site structures are usually more complex than the example shown here. If the page `hardware1.html` contained a link to `product1.html`, `product1.html` would still be crawled and ingested.

Alternatively, if you set `UrlCantHaveRegex=.*software\.html`, the connector does not ingest the page `products/software.html`, but the page is still crawled for links. The pages `product1.html`, `product2.html` and `product3.html` do not match the regular expression and so they are still ingested. Only the single page highlighted below is excluded from being ingested:

```
index.html  
| - products/software.html  
|   | - products/software/product1.html  
|   | - products/software/product2.html  
|   | - products/software/product3.html  
|  
| - products/hardware.html  
|   | - products/hardware/hardware1.html  
|   | - products/hardware/hardware2.html  
|   | - products/hardware/hardware3.html
```

## Retrieve Information using a Sitemap

This section describes how to retrieve content from a Web site by retrieving URLs contained in a sitemap. If you configure the connector to use a sitemap, the connector does not follow links between pages.

### To create a new Fetch Task

1. Stop the connector.
2. Open the configuration file in a text editor.

3. In the [FetchTasks] section of the configuration file, specify the number of fetch tasks using the `Number` parameter. If you are configuring the first fetch task, type `Number=1`. If one or more fetch tasks have already been configured, increase the value of the `Number` parameter by one (1). Below the `Number` parameter, specify the names of the fetch tasks, starting from zero (0). For example:

```
[FetchTasks]
Number=1
0=MyTask
```

4. Below the [FetchTasks] section, create a new `TaskName` section. The name of the section must match the name of the new fetch task. For example:

```
[FetchTasks]
Number=1
0=MyTask
```

```
[MyTask]
```

5. Choose whether to provide the URL of the sitemap, or configure the connector to automatically find the sitemap by reading the `robots.txt` file.
  - Specify the URL of the sitemap:

<code>SitemapUrl</code>	The URL of a sitemap that lists the pages to ingest. If you set this parameter, only the pages on the sitemap are ingested. The connector does not crawl the site by following links.
-------------------------	---

- Configure the connector to find the sitemap(s) from `robots.txt`:

<code>UseSitemapFromRobots</code>	To configure the connector to look in <code>robots.txt</code> for the URL of the sitemap, set this parameter to <code>TRUE</code> . If the connector cannot find the location of the sitemap in <code>robots.txt</code> , it falls back to crawling the site from the specified URL.
-----------------------------------	--

<code>Url</code>	The URL of the site. You must specify only one URL.
------------------	---

For example:

```
[MyTask]
UseSitemapFromRobots=TRUE
Url=https://www.hpe.com/
```

6. (Optional) If you want to index specific pages, you can use the following configuration parameters:

<code>PageCantHaveRegex</code>	A regular expression to restrict the content retrieved by the connector. If the content of a page matches the regular expression, the page is not ingested. This parameter applies to all file types.
--------------------------------	---

<code>PageMustHaveRegex</code>	A regular expression to restrict the content retrieved by the connector. The content of a page must match the regular expression, otherwise the page is not ingested.
--------------------------------	---

	This parameter applies to all file types.
Ur1CantHaveRegex	A regular expression to restrict the content retrieved by the connector. If the full URL of a page matches the regular expression, the page is not ingested. This parameter applies to all file types, for example HTML pages, images, text documents, and so on.
Ur1MustHaveRegex	A regular expression to restrict the content retrieved by the connector. The full URL of a page must match the regular expression, otherwise the page is not ingested. This parameter applies to all file types, for example HTML pages, images, text documents, and so on.

7. (Optional) If the connector is installed on a machine that is behind a proxy server, see [Retrieve Information through a Proxy Server, below](#).
8. Save and close the configuration file.

#### **Related Topics**

- [Retrieve Information by Crawling the Web, on page 48](#)
- [Schedule Fetch Tasks, on page 70](#)

## **Retrieve Information through a Proxy Server**

If the connector is installed on a machine that is behind a proxy server, use one of the following procedures to configure the connector so that it can reach the Web.

#### **To configure the proxy server to use by host name and port**

1. In the configuration file, add the following parameters to your fetch task:

ProxyHost	The host name or IP address of the proxy server to use.
ProxyPort	The port of the proxy server to use.
ProxyUsername	The user name to use to authenticate with the proxy server.
ProxyPassword	The password to use to authenticate with the proxy server.

For example:

```
[MyTask]
...
ProxyHost=10.0.0.1
ProxyPort=80
ProxyUsername=username
ProxyPassword=password
```

2. Save and close the configuration file.

### To configure the proxy server to use with a proxy automatic configuration script

1. In the configuration file, add one of the following parameters to your fetch task (if you set both, the connector uses `ProxyAutoConfigurationUrl` and ignores `ProxyAutoConfigurationFile`):

<code>ProxyAutoConfigurationUrl</code>	The URL of a proxy automatic configuration script, accessible from the connector machine, that specifies the proxy settings to use for accessing the Web.
<code>ProxyAutoConfigurationFile</code>	The path to a proxy automatic configuration script, located on the connector machine, that specifies the proxy settings to use for accessing the Web. Specify an absolute path or a path relative to the connector.

For example:

```
ProxyAutoConfigurationUrl=http://proxy.domain.com/proxy.pac
```

or

```
ProxyAutoConfigurationFile=proxy.pac
```

2. Save and close the configuration file.

## Retrieve Information over SSL

The connector can retrieve pages from web sites accessed over HTTPS. You can include the following configuration parameters in your fetch task to customize SSL/TLS settings:

- To choose the SSL method that is used, set `SSLMethod`. If you do not specify an SSL method, the connector uses the most secure SSL method that is supported by the server.
- To specify trusted Certificate Authorities (CAs), and check that the site returns a valid certificate issued by one of the authorities, set `SSLCACertificate` or `SSLCACertificatesPath`, and then set `SSLCheckCertificate=TRUE`. By default the connector does not check certificates.
- To check the common name provided by a certificate, set `SSLCheckCommonName=TRUE`. The connector checks whether the host name listed in the site's certificate (that is, the `CommonName` or "CN" attribute) resolves to the same IP address as the site URL itself.
- To specify a client-side certificate set `SSLCertificate`. Specify the private key for the certificate with `SSLPrivateKey`. If a password is required for the private key file, set `SSLPrivateKeyPassword`.

## Incremental Synchronization

The HPE Web Connector supports incremental synchronization. The first time the connector synchronizes with a web site, it ingests all of the content that is requested by the task configuration. Subsequently, the connector only ingests information that is new or has changed.

The connector stores the date and time when it requests a page. The next time it requests the page, it uses this information to set the `If-Modified-Since` header in the request sent to the web server. If the web server supports the `If-Modified-Since` header and does not consider the page to have been

modified, it returns an HTTP 304 response code, which tells the connector that the page has not changed. Otherwise, it returns the page.

If a page is returned, the connector performs a check to determine whether the page content has changed. Only if the connector determines that the page has changed does it ingest the page. This check occurs after **clipping** (if you have configured clipping) so that changes to parts of the page that are clipped do not cause the page to be re-ingested.

**TIP:**

Many web pages have dynamic content, and can appear to change every time they are requested.

## Clip Pages

The content on most web pages includes headers, footers, navigation bars, and advertisements. Unless these are removed from pages, the text from these items could reduce the quality of the documents indexed into IDOL Server and reduce the effectiveness of operations such as categorization.

You can configure HPE Web Connector to remove irrelevant content from pages before they are ingested.

## Clip Pages Automatically

HPE Web Connector can clip pages automatically, using an algorithm to decide which parts of the page to keep and which to discard. To clip pages automatically, add `Clipped=TRUE` to your task configuration.

## Clip Pages using CSS Selectors

The automatic clipping algorithm has been designed to work with many different pages, but this means that automatic clipping might not give the best results for every page. For this reason, you can use CSS selectors to choose which parts of the page to keep and which to discard. To clip pages with CSS selectors, add `Clipped=TRUE` to your task configuration, and then set the parameters `ClipPageUsingCssSelect` and `ClipPageUsingCssUnselect`.

- |                                       |   |
|---------------------------------------|---|
| <code>ClipPageUsingCssSelect</code>   | A comma-separated list of CSS2 selectors that specify parts of the page to keep. The connector also keeps all descendents of these elements.  |
| <code>ClipPageUsingCssUnselect</code> | A comma-separated list of CSS2 selectors that specify parts of the page to remove. The connector also removes all descendents of these elements. The <code>ClipPageUsingCssSelect</code> parameter is applied before <code>ClipPageUsingCssUnselect</code> , so you can use this parameter to remove unwanted descendants of elements identified by <code>ClipPageUsingCssSelect</code> . |

The HPE Web Connector supports standard CSS2 selectors. To construct the selectors, view the source HTML of the pages that you need to clip. CSS allows you to select elements based on the structure of the page. For example, you can select elements of a certain type that are descendents of another element. Also, the designer of the page might have added classes to the relevant elements in order to style them, and you can use these same classes to clip the page.

The following example shows a simple page:

```
<html>
<head>
</head>
<body>
  <nav>
    <!-- navigation and links -->
  </nav>
  <div class="maincontent">
    <p>Some content</p>
  </div>
  <div class="footer">
    <!-- footer -->
  </div>
</body>
</html>
```

To select the main content but exclude the navigation element and the footer, you could use the following configuration:

```
[MyTask]
...
Clipped=TRUE
ClipPageUsingCssSelect=div.maincontent
ClipPageUsingCssUnselect=nav,div.footer
```

**TIP:**

HPE Web Connector includes an example tool that can help you find the CSS selectors you need to clip web pages. For more information about this utility, see [Find Selectors using the CSS Selector Builder Tool](#), below.

## Find Selectors using the CSS Selector Builder Tool

The HPE CSS Selector Builder Tool is an example tool, provided with HPE Web Connector, that can help you find CSS selectors for parts of a web page. The tool is a plug-in for the Chrome web browser.

**NOTE:**

HPE does not support the CSS Selector Builder Tool, it is provided only as an example of a tool that you could build.

### To install the HPE CSS Selector Builder Tool

1. Open the Chrome web browser.
2. In the address bar, type `chrome://extensions` and press ENTER.  
The Extensions page opens.
3. Open a file manager (such as Windows Explorer on Windows).
4. Drag the file `HPE CSS Selector Builder Tool.crx` from the HPE Web Connector installation onto the Extensions page in the browser.  
A box opens, asking for your permission to install the tool.
5. Click **Add Extension**.  
The tool is installed.

### To find CSS Selectors

1. In Chrome, navigate to the web site that you want to index.
2. On the toolbar, click the **HPE CSS Selector Builder Tool**  button.  
The tool opens at the bottom of the browser window (but you can move it to the top of the window if you prefer, by clicking **Move to top**).



3. Move the mouse pointer over the page. Elements on the page are highlighted in blue as you hover over them, and the selector for the current element is displayed in the **Current** field.
4. Choose the page elements to keep and discard:
  - Right-click on each element that you want to keep when the page is clipped. The page elements to keep are highlighted in green and selectors are added to the **Select** box.
  - Right-click twice on each element that you want to discard when the page is clipped. The page elements to discard are highlighted in red and selectors are added to the **Unselect** box.
  - You can type one or more selectors in the **Select** and **Unselect** boxes and press **Refresh**. The tool will then show which parts of the page are clipped based on the selectors you have entered.
  - To clear all selectors, click **Clear Selectors**.
5. (Optional) Click on any hyperlink to navigate around the site. The tool highlights the selected and unselected elements on the current page, so that you can see whether the selectors you have chosen clip multiple pages as desired.
6. When you have optimized your selections, use the value in the **Select** box to set the parameter `ClipPageUsingCssSelect` in the connector's configuration file, and the value in the **Unselect** box to set the parameter `ClipPageUsingCssUnselect`.
7. Click **Close**.

## Choose How Long to Wait for Scripts

The HPE Web Connector allows time for scripts to complete before processing a page. However, some web pages run scripts that never finish. For example, a page might contain a script that performs an AJAX request and then schedules itself to run again five seconds later. During the five-second interval between the script completing and running again, the script is inactive. The connector can determine that scripts are inactive, but it is impossible for the connector to determine whether the page has completely loaded or whether the script might add more content.

When the HPE Web Connector detects that scripts have been inactive for a certain period of time, by default half a second, it considers a page to have finished loading. You can configure the duration of inactivity required by setting the parameter `ScriptActivityTimeout`. For example, if you set `ScriptActivityTimeout=1s`, all scripts must be inactive for a second before the connector processes the page.

### NOTE:

HPE recommends setting a short duration for this parameter, because the connector must wait for at least the specified amount of time for every page that contains scripts. Increasing the duration of `ScriptInactivityTimeout` could significantly increase the amount of time required to complete a synchronize cycle.

If scripts do not become inactive or remain inactive for long enough, the connector eventually terminates the scripts. You can configure the maximum amount of time to wait for scripts by setting the configuration parameter `MaxWaitForScripts`. For example, to wait no longer than 10 seconds, set `MaxWaitForScripts=10s`. This time limit does not affect custom scripts specified by the `CustomJSScriptPath` configuration parameter.

As described above, some web pages run scripts that never finish, so by default the HPE Web Connector does not consider having to terminate scripts as an error. The connector continues to process the page as if the scripts had completed successfully. In some cases, scripts are used to generate content and add links, so terminating a script could result in content being unreachable. You can therefore configure the connector to report an error and attempt to process the page again on the next synchronize cycle. To do this, set the configuration parameter `FailOnScriptTimeout=TRUE`.

## Log On to a Web Site

Some Web sites require that you log on before you can access content. To retrieve content from these Web sites, configure the connector to log on to the site.

## Basic, HTTP Digest, and NTLMv2 Authentication

To log on to a Web site that uses Basic, HTTP Digest, or NTLM version 2 authentication, specify a user name and password by setting the configuration parameters `AuthUser` and `AuthPassword`. For example:

```
[MyTask]
Url=http://www.example.com/
AuthUser=user
AuthPassword=pass
```

Alternatively, you can set the `AuthSection` parameter and set the `AuthUser` and `AuthPassword` parameters in a different section of the configuration file. This means you can use the same user name and password for several tasks:

```
[MyTask]
Url=http://www.example.com/
AuthSection=MyAuthSection
```

```
[AnotherTask]
Url=http://www.another-example.com/
AuthSection=MyAuthSection
```

```
[MyAuthSection]
AuthUser=user
AuthPassword=pass
```

If you create a fetch task to crawl more than one site, or you need to specify more than one set of credentials for a site, you can use multiple sections containing authentication details. The `AuthSection` parameter accepts multiple values. Set the `AuthUrlRegex` parameter in each section to specify the URLs that the authentication details can be used against. For example:

```
[MyTask]
Url=http://www.example.com/
AuthSection0=LogOnAuthExample
AuthSection1=LogOnAuthExampleSubDomain
```

```
[LogOnAuthExample]
AuthUrlRegex=.*www\.example\.com/. *
AuthUser=MyUsername
AuthPassword=MyP4ssw0rd
```

```
[LogOnAuthExampleSubDomain]
AuthUrlRegex=.*subsite\.example\.com/. *
AuthUser=MySubsiteUsername
AuthPassword=MySubsiteP4ssw0rd
```

## Submit a Form

If the Web site does not use Basic, HTTP Digest or NTLMv2 authentication, the connector might be able to log on by submitting a form.

Configure the connector to submit a form by setting the following configuration parameters:

<b>FormUrlRegex</b>	A regular expression to identify the page that contains the log-on form. The connector does not attempt to submit form data unless the URL of a page matches the regular expression.
<b>InputSelector</b>	A list of CSS2 selectors to identify the form fields to populate. Specify the selectors in a comma-separated list or by using numbered parameters.
<b>InputValue</b>	The values to use for the form fields specified by the <b>InputSelector</b> parameter. Specify the values in a comma-separated list or by using numbered parameters.
<b>SubmitSelector</b>	A CSS2 selector that identifies the form element to use to submit the form.
<b>ValidateFormData</b>	A Boolean value that specifies whether the connector attempts to validate the data supplied to complete a form. The connector can validate the data based on the types of the input elements.

You can set these parameters in the `[TaskName]` section of the configuration file, for example:

```
[MyTask]
Url=http://www.example.com/
FormUrlRegex=.*login\.php
InputSelector0=input[name=username]
InputSelector1=input[name=password]
InputValue0=MyUsername
InputValue1=MyP4ssw0rd!
SubmitSelector=input[name=login]
```

To specify the information in a separate section of the configuration file, set the `FormsSection` parameter:

```
[MyTask]
Url=http://www.example.com/
FormsSection=LogOnForm

[LogOnForm]
FormUrlRegex=.*login\.php
InputSelector0=input[name=username]
InputSelector1=input[name=password]
InputValue0=MyUsername
InputValue1=MyP4ssw0rd!
SubmitSelector=input[name=login]
```

To submit different forms during a single task, you can create multiple sections containing form settings. The `FormsSection` parameter accepts multiple values. In each section, use the `FormUrlRegex` parameter to identify the page that contains the form:

```
[MyTask]
Url=http://www.example.com/
FormsSection0=LogOnFormExample
FormsSection1=LogOnFormExampleSubDomain

[LogOnFormExample]
FormUrlRegex=.*www\.example\.com/.*/.*login\.php
InputSelector0=input[name=username]
InputSelector1=input[name=password]
InputValue0=MyUsername
InputValue1=MyP4ssw0rd!
SubmitSelector=input[name=login]

[LogOnFormExampleSubDomain]
FormUrlRegex=.*subsite\.example\.com/.*/.*login\.php
InputSelector0=input[name=username]
InputSelector1=input[name=password]
InputValue0=MySubsiteUsername
InputValue1=MySubsiteP4ssw0rd!
SubmitSelector=input[name=login]
```

## Authenticate using Cookies

To authenticate with a site that uses cookies, use the configuration parameters `CustomHeaderName` and `CustomHeaderValue` to send the cookie data to the web server with each request. For example:

```
[MyTask]
Url=https://my-site/index.htm
CustomHeaderName0=Cookie
CustomHeaderValue0=session=abc123;userID=12345
```

## Limit the Download Rate

To reduce the load on the Web site you are indexing, you can limit the maximum rate at which the connector downloads content, using the configuration parameter `MaxKBytesPerSec`. This parameter does not limit the download rate for any individual page, it limits the maximum download rate by pausing between pages.

A Web server might be configured to deny requests that arrive from the same host with little or no time between them. The connector requests information from a Web site much faster than a human visitor, so you might find that the connector's requests are denied. To prevent a server from denying requests from the connector, you can specify a time interval that a synchronize thread must wait between requests. To do this, set the configuration parameter `PageDelay`. If you set a delay of one second, each

synchronize thread must wait at least one second between requests. By default, the connector uses five synchronize threads so might request up to five pages per second.

You can also limit the maximum number of pages that are ingested in a single synchronize cycle, by setting the configuration parameter `MaxPages`. If the limit is reached, the remaining pages are ingested in future synchronize cycles.

**TIP:**

For more information about these configuration parameters, refer to the *HPE Web Connector Reference*.

## Retrieve Recently Updated Content

In some cases you might want to retrieve information from the Web only when it has been recently updated. For example, if you are crawling a news site, you might want to restrict the synchronize task to retrieve pages that were updated in the last 30 days.

To retrieve Web pages based on the date, the HPE Web Connector must be able to extract a date for each page. The connector checks the following sources (in order) and uses the first valid date that it finds:

- The URL of the page (but only if `DateInUrl` is set to `TRUE`).
- The page content (but only if you set `PageDateSelector`).
- The HTTP headers returned with the page. The connector attempts to extract a date from the headers named by the parameter `PageDateHeader`.

### To retrieve pages based on the date

1. Stop the connector and open the configuration file.
2. Modify your fetch task by adding the relevant parameters from the following list, so that the connector can extract the date associated with a page:

<code>DateInUrl</code>	A Boolean value that specifies whether the date associated with a Web page can be extracted from the page URL. When you set this parameter to <code>TRUE</code> , the connector attempts to extract the date from the URL.
<code>PageDateSelector</code>	A list of CSS2 selectors to identify elements in the page content that might contain the date associated with a Web page. <ul style="list-style-type: none"><li>• If the date is contained in the element's content, setting this parameter is sufficient to extract the date.</li><li>• If the date is contained in one of the element's attributes, set this parameter and then set <code>PageDateAttribute</code> to identify the attribute.</li></ul>
<code>PageDateAttribute</code>	A list of attributes (on elements listed by <code>PageDateSelector</code> ) that contain the date associated with the Web page.
<code>PageDateHeader</code>	A list of headers to retrieve the date from. The headers are checked in the order that you specify and the first valid date that the connector finds is associated with the page. The connector only attempts to extract a date

from HTTP headers if no date is found in the page URL (or `DateInUrl=FALSE`) and no date is found in the page content (or `PageDateSelector` is not set).

`DateFormats` A comma-separated list of date formats to use when searching for a date.

3. Choose which pages to retrieve:

- To configure a rolling limit, for example to retrieve pages that are not more than 30 days old when the synchronize task starts, set the following parameters:

`MaxPageAge` The maximum age that a page can reach and still be ingested.

`MinPageAge` The minimum age that a page must reach before it is ingested.

- To configure a fixed limit, for example to retrieve pages that were updated after 01 July 2015, set the following parameters:

`MinPageDate` Filters the pages that are ingested by date. The connector only ingests pages that are newer than the specified date.

`MaxPageDate` Filters the pages that are ingested by date. The connector only ingests pages that are older than the specified date.

4. (Optional) By default the connector ingests pages where it cannot determine a date. To prevent the connector from ingesting these pages, set the parameter `IngestPagesWithNoDate` to `False`.
5. (Optional) By default the connector does crawl pages that are outside your specified date range, even though they are not ingested. To prevent the connector following links from these pages, set the parameter `SpiderDateFilteredPages` to `False`.
6. Save and close the configuration file.

## Example

The following example configuration retrieves pages that are less than 30 days old, based on a date contained in the URL or in the page content:

```
[MyTask]
Url=http://www.example.com/
...
DateInUrl=true
PageDateSelector=p[id=date]
MaxPageAge=30 days
IngestPagesWithNoDate=False
SpiderDateFilteredPages=False
```

## Render an Image, Thumbnail, or PDF for Ingested Pages

The HPE Web Connector can render an image, thumbnail image, or PDF of each Web page that it ingests.

By default, when you configure the connector to create one or more of these files they are each indexed as the document content of a separate document, alongside the indexed Web page. Alternatively, you can configure the connector to write the files to a folder.

If you write rendered images, PDF files, and thumbnails to a folder the connector adds metadata fields to each document that contain the paths of associated files. The fields are named:

- RENDITION\_FILE\_IMAGE
- RENDITION\_FILE\_PDF
- RENDITION\_FILE\_THUMBNAIL

When the connector sends ingest-removes for deleted documents, the connector deletes any rendered images, PDF files and thumbnails associated with those documents.

### To render an image, thumbnail, or PDF for each ingested page

1. Stop the connector and open the configuration file.
2. Modify your fetch task by adding the following parameters:

CreateImageRendition	To render an image for each ingested page, set this parameter to <b>true</b> .
CreateThumbnailRendition	To render a thumbnail image for each ingested page, set this parameter to <b>true</b> .
CreatePDFRendition	To render a PDF copy of each ingested page, set this parameter to <b>true</b> .
RenditionsFilePath	The path of the folder to write rendered images, PDF files, and thumbnails to. The folder must already exist, and the user running the connector must have permission to write files to the folder. If you don't set this parameter, the connector indexes each file as the content of a separate document.
FullPageRender	Specifies whether images and thumbnail images show the full page ( <b>true</b> ), or only the top part of the page ( <b>false</b> ), that you would see when viewing the page in a web browser.
RenditionImageFormat	The image format for images and thumbnail images.
RenditionImageQuality	The image quality for JPEG and PNG images and thumbnail images. Specify an integer value from 0 to 100, where lower values represent higher compression (usually resulting in a

smaller file size), and higher values represent higher quality.

`ThumbnailRenditionWidth` The maximum width for thumbnail images, in pixels.

`ThumbnailRenditionHeight` The maximum height for thumbnail images, in pixels.

3. Save and close the configuration file.

## Example

The following example renders a thumbnail for each page, as a PNG image that has a maximum width of 350 pixels:

```
[MyTask]
Url=http://www.example.com/
...
CreateThumbnailRendition=true
RenditionImageFormat=png
ThumbnailRenditionWidth=350
FullPageRender=FALSE
```

## Split Web Pages into Multiple Documents

You might want to split Web pages into multiple documents. For example, if you ingest pages from a discussion board you might want to ingest one document for each message on the page.

The HPE Web Connector can create documents for sections of a Web page identified using CSS selectors. For each Web page, the connector creates a parent document and an associated file that contains the full page source. It then creates a child document for each section of the page. Each child document has an associated file that contains the `<head>` element from the original page, and a `<body>` element containing the content identified by your CSS selector. The parent document includes metadata fields (named `CHILD_DOCUMENT`) that refer to the child documents, and each child document has a metadata field (`PAGE_REFERENCE`) that refers back to the parent document.

### To split Web pages into multiple documents

1. Stop the connector and open the configuration file.
2. Modify your fetch task by adding the following parameters:

`ChildDocumentSection` (Optional) A comma-separated list of sections in the HPE Web Connector configuration file that contain settings for creating child documents. If you do not set this parameter, the connector uses the settings in the *TaskName* section.

`ChildDocumentUrlRegex` (Optional) A Perl-compatible regular expression to identify the pages to generate child documents from. The connector does not attempt to generate child documents from a page unless the full URL of a page matches the regular expression.

ChildDocumentSelector	A CSS2 selector that identifies the root element of each child document in the page source.
ChildReferenceSelector	(Optional) An element in the child document that contains a value to use as the document reference. The value you extract should be unique for each child document, because it is used as part of the DRREFERENCE field in the child document. If you do not set this parameter, the connector uses a GUID. Specify the element using a CSS2 selector, relative to the element identified by ChildDocumentSelector.
ChildMetadataFieldName	(Optional) The names to use for document fields (in child documents) that contain information extracted using the parameter ChildMetadataSelector. This parameter must have the same number of values as ChildMetadataSelector.
ChildMetadataSelector	(Optional) A list of elements in the child document that contain metadata. The metadata in these elements are extracted and added to the metadata fields of child documents. To specify the name(s) of the document field(s) to contain the extracted information, set the configuration parameter ChildMetadataFieldName. Both parameters must have the same number of values. Specify the elements as a list of CSS2 selectors, relative to the element identified by ChildDocumentSelector.

3. Save and close the configuration file.

## Example

Consider the following example page which represents messages on a page of a discussion board:

```
<html>
  <head>
    <title>Example Page</title>
    <meta charset="utf-8">
  </head>
  <body>
    <div>
      <h1>Example Page</h1>
      <div class="content">
        <p>content</p>
      </div>
      <div class="message">
        <h1>Message 1</h1>
        <p class="meta">some metadata</p>
        <p>some content</p>
      </div>
      <div class="message">
        <h1>Message 2</h1>
```

```
        <p class="meta">some metadata</p>
        <p>some content</p>
    </div>
    ...
</div>
</body>
</html>
```

To create separate documents for the messages contained on this page, you could use the following configuration:

```
[MyTask]
...
ChildDocumentSelector=div.message
ChildReferenceSelector=h1
ChildMetadataFieldName0=my_metadata
ChildMetadataSelector0=p.meta
```

This example would produce the following child document:

```
#DREREFERENCE [child][Message 1]http://www.hp.com/example.htm
#DREFIELD my_metadata="some metadata"
#DREFIELD PAGE_REFERENCE="http://www.hp.com/example.htm"
```

The PAGE\_REFERENCE field is added automatically by HPE Web Connector and contains the reference of the parent document.

The following file is associated with the child document. The HPE Web Connector includes the <head> element from the Web page and adds the content identified by ChildDocumentSelector to the <body> element. If you send your documents to CFS, this file is filtered by KeyView and the information it contains is used as the document content.

```
<html>
  <head>
    <title>Example Page</title>
    <meta charset="utf-8">
  </head>
  <body>
    <div class="message">
      <h1>Message 1</h1>
      <p class="meta">some metadata</p>
      <p>some content</p>
    </div>
  </body>
</html>
```

A similar document and file would be ingested for the second message.

The parent document contains the full page content. The HPE Web Connector automatically adds fields named CHILD\_DOCUMENT, containing the references of associated child documents:

```
#DREREFERENCE http://www.hp.com/example.htm
...
#DREFIELD CHILD_DOCUMENT="[child][Message 1]http://www.hp.com/example.htm"
```

```
#DREFIELD CHILD_DOCUMENT="[child][Message 2]http://www.hp.com/example.htm"  
...
```

## Process XML Feeds

Web sites might have pages, such as RSS feeds, that contain XML rather than HTML. This section describes how you can use HPE Web Connector to process XML pages.

HPE Web Connector identifies XML pages by the MIME type returned in the Content-Type header of the response from the web server.

XML pages can include processing instructions that instruct a web browser to apply an XSL transformation to the page, and sometimes the XML is transformed into HTML. The processing instruction looks similar to this:

```
<?xml-stylesheet type="text/xsl" href="transform_to_html.xsl"?>
```

If the Content-Type header indicates that the page contains XML but no XSL transformation is provided, the connector ingests the page as an XML document.

If the header indicates that page contains XML and an XSL transformation is provided, the connector applies the transformation and processes the page as if it were HTML. This means that the connector can:

- extract links from the page, and follow those links to retrieve more content.
- [split the page into multiple documents](#).
- [clip the page](#).
- [render an image, thumbnail image, or a PDF of the page](#).

As a result, you can use the HPE Web Connector to process an RSS feed that is transformed into HTML. The Web Connector, like the RSS Connector, retrieves the content contained in the feed, such as page titles and summaries. In addition, the Web Connector can follow the links contained in the feed and ingest the content on the associated pages.

In the Web Connector task configuration, specify the URL of the feed using the `Url` parameter and set `Depth=1`. Setting `Depth=1` ensures that the connector follows the links from the RSS feed, but does not follow any links that are extracted from the associated web pages:

```
[FetchTasks]  
Number=1  
0=RssFeed  
  
[RssFeed]  
Url=http://www.example-news-website.com/feed/rss.xml  
Depth=1
```

When the HPE Web Connector applies an XSL transformation to an XML document and logging is configured with `LogLevel=Full`, you will see the following messages in the synchronize log:

```
WK00P:Applying XSL transform  
WK00P:XSL Transform applied to XML document
```

## Run Custom JavaScript on Web Pages

The connector can run custom JavaScript on web pages before it crawls and ingests them. This allows you to manipulate pages or interact with them before they are processed. For example, if a page has a button to load more content you can configure the connector to run a script that clicks the button. The ingested page will then include the additional content.

**TIP:**

Running custom JavaScript on pages is usually only necessary in advanced cases, such as processing unconventional sites.

You must write the custom script and save it to a file that can be accessed by the connector.

HPE recommends that you enclose your script in a `try...catch` block to prevent exceptions being thrown out of the script. For example:

```
try
{
  // custom javascript
  true;
}
catch(e)
{
  console.log("Javascript Error: " + e.message) false;
}
```

Any messages that you write to the JavaScript console are written to the connector's synchronize log, but only when you set the parameter `LogLevel` to `FULL` and `EnableJavascriptConsoleLogging` to `TRUE`. To troubleshoot your script, set these parameters and include a reasonable amount of logging in your script. The connector also logs the return value of the script.

### To run custom JavaScript on web pages

1. Stop the connector and open the configuration file.
2. Modify your fetch task by adding the parameter `CustomJSSections`. This parameter specifies the names of the sections in the connector's configuration file that contain settings for running custom JavaScript on pages. For example:

```
[MyTask0]
...
CustomJSSections=MyCustomJS
```

3. Create a new section in the configuration file to contain the settings for running the script:

```
[MyCustomJS]
```

4. In the new section, set the following parameters:

<code>CustomJSUrlRegex</code>	A Perl-compatible regular expression to match the full URLs of the pages on which you want to run custom JavaScript.
-------------------------------	--

CustomJSScriptPath	The path of the file that contains the custom JavaScript to run. The path must be absolute, or relative to the HPE Web Connector executable file.
CustomJSElementSelector	(Optional) The page elements on which to run the custom JavaScript. Specify the elements using CSS2 selectors.
CustomJSAIAllSelected	(Optional) A Boolean value that specifies whether to run the custom JavaScript on all elements that match the selector specified by CustomJSElementSelector (the default value, false, means that the connector runs the JavaScript only on the first matching element).

For example:

```
[MyCustomJS]
CustomJSUrlRegex=http://www\.hpe\.com/. *
CustomJSScriptPath=javascript/my_script.js
CustomJSElementSelector=div#maincontent
```

5. Save and close the configuration file.

## Schedule Fetch Tasks

The connector automatically runs the fetch tasks that you have configured, based on the schedule in the configuration file. To modify the schedule, follow these steps.

### To schedule fetch tasks

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. Find the [Connector] section.
4. The EnableScheduleTasks parameter specifies whether the connector should automatically run the fetch tasks that have been configured in the [FetchTasks] section. To run the tasks, set this parameter to true. For example:

```
[Connector]
EnableScheduledTasks=True
```

5. In the [Connector] section, set the following parameters:

**ScheduleStartTime** The start time for the fetch task, the first time it runs after you start the connector. The connector runs subsequent synchronize cycles after the interval specified by ScheduleRepeatSecs.

Specify the start time in the format H[H]:MM[:SS]. To start running tasks as soon as the connector starts, do not set this parameter or use the value now.

**ScheduleRepeatSecs** The interval (in seconds) from the start of one scheduled synchronize

cycle to the start of the next. If a previous synchronize cycle is still running when the interval elapses, the connector queues a maximum of one action.

`ScheduleCycles` The number of times that each fetch task is run. To run the tasks continuously until the connector is stopped, set this parameter to `-1`. To run each task only one time, set this parameter to `1`.

For example:

```
[Connector]
EnableScheduledTasks=True
ScheduleStartTime=15:00:00
ScheduleRepeatSecs=3600
ScheduleCycles=-1
```

6. (Optional) To run a specific fetch task on a different schedule, you can override these parameters in a *TaskName* section of the configuration file. For example:

```
[Connector]
EnableScheduledTasks=TRUE
ScheduleStartTime=15:00:00
ScheduleRepeatSecs=3600
ScheduleCycles=-1
```

...

```
[FetchTasks]
Number=2
0=MyTask0
1=MyTask1
...
```

```
[MyTask1]
ScheduleStartTime=16:00:00
ScheduleRepeatSecs=60
ScheduleCycles=-1
```

In this example, `MyTask0` follows the schedule defined in the `[Connector]` section, and `MyTask1` follows the scheduled defined in the `[MyTask1]` *TaskName* section.

7. Save and close the configuration file. You can now start the connector.

#### **Related Topics**

- [Start and Stop the Connector, on page 38](#)

## **Troubleshoot the Connector**

This section describes how to troubleshoot common problems that might occur when you set up the HPE Web Connector.

***The synchronize log shows the error "Address already in use"***

You might see this error if the system has allocated all available TCP ports.

Operating systems typically allocate a limited number of ports to applications that need to make outbound connections. Also, when a connection is closed, the operating system waits before a port is released and can be reused.

If you encounter this issue on a Windows system, you can set the Windows registry parameter `MaxUserPort`, so that more ports are available for use. You could also shorten the amount of time that the operating system waits before releasing a port by setting the registry parameter `TcpTimedWaitDelay`. These are both set in:

`HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Tcpip\Parameters`

# Chapter 7: Manipulate Documents

This section describes how to manipulate documents that are created by the connector and sent for ingestion.

- [Introduction](#) ..... 73
- [Add a Field to Documents using an Ingest Action](#) ..... 73
- [Customize Document Processing](#) ..... 74
- [Standardize Field Names](#) ..... 75
- [Run Lua Scripts](#) ..... 80
- [Example Lua Scripts](#) ..... 82

## Introduction

IDOL Connectors retrieve data from repositories and create documents that are sent to Connector Framework Server, another connector, or Haven OnDemand. You might want to manipulate the documents that are created. For example, you can:

- Add or modify document fields, to change the information that is indexed into IDOL Server or Haven OnDemand.
- Add fields to a document to customize the way the document is processed by CFS.
- Convert information into another format so that it can be inserted into another repository by a connector that supports the `Insert` action.

When a connector sends documents to CFS, the documents only contain metadata extracted from the repository by the connector (for example, the location of the original files). To modify data extracted by KeyView, you must modify the documents using CFS. For information about how to manipulate documents with CFS, refer to the *Connector Framework Server Administration Guide*.

## Add a Field to Documents using an Ingest Action

To add a field to all documents retrieved by a fetch task, or all documents sent for ingestion, you can use an Ingest Action.

**NOTE:**

To add a field only to selected documents, use a Lua script (see [Run Lua Scripts, on page 80](#)). For an example Lua script that demonstrates how to add a field to a document, see [Add a Field to a Document, on page 83](#).

### To add a field to documents using an Ingest Action

1. Open the connector's configuration file.
2. Find one of the following sections in the configuration file:

- To add the field to all documents retrieved by a specific fetch task, find the [TaskName] section.
- To add a field to all documents that are sent for ingestion, find the [Ingestion] section.

**NOTE:**

If you set the `IngestActions` parameter in a [TaskName] section, the connector does not run any `IngestActions` set in the [Ingestion] section for documents retrieved by that task.

3. Use the `IngestActions` parameter to specify the name of the field to add, and the field value. For example, to add a field named `AUTN_NO_EXTRACT`, with the value `SET`, type:

```
IngestActions0=META:AUTN_NO_EXTRACT=SET
```

4. Save and close the configuration file.

## Customize Document Processing

You can add the following fields to a document to control how the document is processed by CFS. Unless stated otherwise, you can add the fields with any value.

### **AUTN\_FILTER\_META\_ONLY**

Prevents KeyView extracting file content from a file. KeyView only extracts metadata and adds this information to the document.

### **AUTN\_NO\_FILTER**

Prevents KeyView extracting file content and metadata from a file. You can use this field if you do not want to extract text from certain file types.

### **AUTN\_NO\_EXTRACT**

Prevents KeyView extracting subfiles. You can use this field to prevent KeyView extracting the contents of ZIP archives and other container files.

### **AUTN\_NEEDS\_MEDIA\_SERVER\_ANALYSIS**

Identifies media files (images, video, and documents such as PDF files that contain embedded images) that you want to send to Media Server for analysis, using a `MediaServerAnalysis` import task. You do not need to add this field if you are using a Lua script to run media analysis. For more information about running analysis on media, refer to the *Connector Framework Server Administration Guide*.

### **AUTN\_NEEDS\_TRANSCRIPTION**

Identifies audio and video assets that you want to send to an IDOL Speech Server for speech-to-text processing, using an `IdolSpeech` import task. You do not need to add this field if you are using a Lua script to run speech-to-text. For more information about running speech-to-text on documents, refer to the *Connector Framework Server Administration Guide*.

### **AUTN\_FORMAT\_CORRECT\_FOR\_TRANSCRIPTION**

To bypass the transcoding step of an `IdolSpeech` import task, add the field `AUTN_FORMAT_CORRECT_FOR_TRANSCRIPTION`. Documents that have this field are not sent to a Transcode Server. For more

information about the `Ido1Speech` task, refer to the *Connector Framework Server Administration Guide*.

### **AUTN\_AUDIO\_LANGUAGE**

To bypass the language identification step of an `Ido1Speech` import task add the field `AUTN_AUDIO_LANGUAGE`. The value of the field must be the name of the IDOL Speech Server language pack to use for extracting speech. Documents that have this field are not sent to the IDOL Speech Server for language identification. For more information about the `Ido1Speech` task, refer to the *Connector Framework Server Administration Guide*.

## **Standardize Field Names**

Field standardization modifies documents so that they have a consistent structure and consistent field names. You can use field standardization so that documents indexed into IDOL through different connectors use the same fields to store the same type of information.

For example, documents created by the File System Connector can have a field named `FILEOWNER`. Documents created by the Documentum Connector can have a field named `owner_name`. Both of these fields store the name of the person who owns a file. Field standardization renames the fields so that they have the same name.

Field standardization only modifies fields that are specified in a dictionary, which is defined in XML format. A standard dictionary, named `dictionary.xml`, is supplied in the installation folder of every connector. If a connector does not have any entries in the dictionary, field standardization has no effect.

## **Configure Field Standardization**

IDOL Connectors have several configuration parameters that control field standardization. All of these are set in the `[Connector]` section of the configuration file:

- `EnableFieldNameStandardization` specifies whether to run field standardization.
- `FieldNameDictionaryPath` specifies the path of the dictionary file to use.
- `FieldNameDictionaryNode` specifies the rules to use. The default value for this parameter matches the name of the connector, and HPE recommends that you do not change it. This prevents one connector running field standardization rules that are intended for another.

To configure field standardization, use the following procedure.

### **NOTE:**

You can also configure CFS to run field standardization. To standardize all field names, you must run field standardization from both the connector and CFS.

### **To enable field standardization**

1. Stop the connector.
2. Open the connector's configuration file.
3. In the `[Connector]` section, set the following parameters:

<code>EnableFieldNameStandardization</code>	A Boolean value that specifies whether to enable field standardization. Set this parameter to <code>true</code> .
<code>FieldNameDictionaryPath</code>	The path to the dictionary file that contains the rules to use to standardize documents. A standard dictionary is included with the connector and is named <code>dictionary.xml</code> .

For example:

```
[Connector]
EnableFieldNameStandardization=true
FieldNameDictionaryPath=dictionary.xml
```

4. Save the configuration file and restart the connector.

## Customize Field Standardization

Field standardization modifies documents so that they have a consistent structure and consistent field names. You can use field standardization so that documents indexed into IDOL through different connectors use the same fields to store the same type of information. Field standardization only modifies fields that are specified in a dictionary, which is defined in XML format. A standard dictionary, named `dictionary.xml`, is supplied in the installation folder of every connector.

In most cases you should not need to modify the standard dictionary, but you can modify it to suit your requirements or create dictionaries for different purposes. By modifying the dictionary, you can configure the connector to apply rules that modify documents before they are ingested. For example, you can move fields, delete fields, or change the format of field values.

The following examples demonstrate how to perform some operations with field standardization.

The following rule renames the field `Author` to `DOCUMENT_METADATA_AUTHOR_STRING`. This rule applies to all components that run field standardization and applies to all documents.

```
<FieldStandardization>
  <Field name="Author">
    <Move name="DOCUMENT_METADATA_AUTHOR_STRING"/>
  </Field>
</FieldStandardization>
```

The following rule demonstrates how to use the `Delete` operation. This rule instructs CFS to remove the field `KeyviewVersion` from all documents (the `Product` element with the attribute `key="ConnectorFrameWork"` ensures that this rule is run only by CFS).

```
<FieldStandardization>
  <Product key="ConnectorFrameWork">
    <Field name="KeyviewVersion">
      <Delete/>
    </Field>
  </Product>
</FieldStandardization>
```

There are several ways to select fields to process using the `Field` element.

Field element attribute	Description	Example
name	Select a field where the field name matches a fixed value.	Select the field MyField: <pre>&lt;Field name="MyField"&gt;   ... &lt;/Field&gt;</pre> Select the field Subfield, which is a subfield of MyField: <pre>&lt;Field name="MyField"&gt;   &lt;Field name="Subfield"&gt;     ...   &lt;/Field&gt; &lt;/Field&gt;</pre>
path	Select a field where its path matches a fixed value.	Select the field Subfield, which is a subfield of MyField. <pre>&lt;Field path="MyField/Subfield"&gt;   ... &lt;/Field&gt;</pre>
nameRegex	Select all fields at the current depth where the field name matches a regular expression.	In this case the field name must begin with the word File: <pre>&lt;Field nameRegex="File.*"&gt;   ... &lt;/Field&gt;</pre>
pathRegex	Select all fields where the path of the field matches a regular expression.  This operation can be inefficient because every metadata field must be checked. If possible, select the fields to process another way.	This example selects all subfields of MyField. <pre>&lt;Field pathRegex="MyField/[^/]*"&gt;   ... &lt;/Field&gt;</pre> This approach would be more efficient: <pre>&lt;Field name="MyField"&gt;   &lt;Field nameRegex=".*"&gt;     ...   &lt;/Field&gt; &lt;/Field&gt;</pre>

You can also limit the fields that are processed based on their value, by using one of the following:

Field element attribute	Description	Example
matches	Process a field if its value matches a fixed value.	Process a field named MyField, if its value matches abc.

		<pre>&lt;Field name="MyField" matches="abc"&gt;   ... &lt;/Field&gt;</pre>
matchesRegex	Process a field if its entire value matches a regular expression.	<p>Process a field named MyField, if its value matches one or more digits.</p> <pre>&lt;Field name="MyField" matchesRegex="\d+"&gt;   ... &lt;/Field&gt;</pre>
containsRegex	Process a field if its value contains a match to a regular expression.	<p>Process a field named MyField if its value contains three consecutive digits.</p> <pre>&lt;Field name="MyField" containsRegex="\d{3}"&gt;   ... &lt;/Field&gt;</pre>

The following rule deletes every field or subfield where the name of the field or subfield begins with temp.

```
<FieldStandardization>
  <Field pathRegex="(.*\/)?temp[^\/*]">
    <Delete/>
  </Field>
</FieldStandardization>
```

The following rule instructs CFS to rename the field Author to DOCUMENT\_METADATA\_AUTHOR\_STRING, but only when the document contains a field named DocumentType with the value 230 (the KeyView format code for a PDF file).

```
<FieldStandardization>
  <Product key="ConnectorFramework">
    <IfField name="DocumentType" matches="230"> <!-- PDF -->
      <Field name="Author">
        <Move name="DOCUMENT_METADATA_AUTHOR_STRING"/>
      </Field>
    </IfField>
  </Product>
</FieldStandardization>
```

**TIP:**

In this example, the IfField element is used to check the value of the DocumentType field. The IfField element does not change the current position in the document. If you used the Field element, field standardization would attempt to find an Author field that is a subfield of DocumentType, instead of finding the Author field at the root of the document.

The following rules demonstrate how to use the ValueFormat operation to change the format of dates. The only format that you can convert date values into is the IDOL AUTNDATE format. The first rule transforms the value of a field named CreatedDate. The second rule transforms the value of an attribute named Created, on a field named Date.

```
<FieldStandardization>
  <Field name="CreatedDate">
    <ValueFormat type="autndate" format="YYYY-SHORTMONTH-DD HH:NN:SS"/>
  </Field>
  <Field name="Date">
    <Attribute name="Created">
      <ValueFormat type="autndate" format="YYYY-SHORTMONTH-DD HH:NN:SS"/>
    </Attribute>
  </Field>
</FieldStandardization>
```

As demonstrated by this example, you can select field attributes to process in a similar way to selecting fields.

You must select attributes using either a fixed name or a regular expression:

Select a field attribute by name	<Attribute name="MyAttribute">
Select attributes that match a regular expression	<Attribute nameRegex=".*">

You can then add a restriction to limit the attributes that are processed:

Process an attribute only if its value matches a fixed value	<Attribute name="MyAttribute" matches="abc">
Process an attribute only if its value matches a regular expression	<Attribute name="MyAttribute" matchesRegex=".*">
Process an attribute only if its value contains a match to a regular expression	<Attribute name="MyAttribute" containsRegex="\w+">

The following rule moves all of the attributes of a field to sub fields, if the parent field has no value. The id attribute on the first Field element provides a name to a matching field so that it can be referred to by later operations. The GetName and GetValue operations save the name and value of a selected field or attribute (in this case an attribute) into variables (in this case '\$name' and '\$value') which can be used by later operations. The AddField operation uses the variables to add a new field at the selected location (the field identified by id="parent").

```
<FieldStandardization>
  <Field pathRegex=".*" matches="" id="parent">
    <Attribute nameRegex=".*">
      <GetName var="name"/>
      <GetValue var="value"/>
      <Field fieldId="parent">
        <AddField name="'$name'" value="'$value'"/>
      </Field>
    </Attribute>
  </Field>
</FieldStandardization>
```

```
        </Attribute>  
    </Field>  
</FieldStandardization>
```

The following rule demonstrates how to move all of the subfields of `UnwantedParentField` to the root of the document, and then delete the field `UnwantedParentField`.

```
<FieldStandardization id="root">  
  <Product key="MyConnector">  
    <Field name="UnwantedParentField">  
      <Field nameRegex=".*">  
        <Move destId="root"/>  
      </Field>  
    <Delete/>  
  </Field>  
</Product>  
</FieldStandardization>
```

## Run Lua Scripts

IDOL Connectors can run custom scripts written in Lua, an embedded scripting language. You can use Lua scripts to process documents that are created by a connector, before they are sent to CFS and indexed into IDOL Server. For example, you can:

- Add or modify document fields.
- Manipulate the information that is indexed into IDOL.
- Call out to an external service, for example to alert a user.

There might be occasions when you do not want to send documents to a CFS. For example, you might use the `Collect` action to retrieve documents from one repository and then insert them into another. You can use a Lua script to transform the documents from the source repository so that they can be accepted by the destination repository.

To run a Lua script from a connector, use one of the following methods:

- Set the `IngestActions` configuration parameter in the connector's configuration file. For information about how to do this, see [Run a Lua Script using an Ingest Action, on page 82](#). The connector runs ingest actions on documents before they are sent for ingestion.
- Set the `IngestActions` action parameter when using the `Synchronize` action.
- Set the `CollectActions` action parameter when using the `Collect` action.

## Write a Lua Script

A Lua script that is run from a connector must have the following structure:

```
function handler(config, document, params)  
    ...  
end
```

The `handler` function is called for each document and is passed the following arguments:

Argument	Description
config	A LuaConfig object that you can use to retrieve the values of configuration parameters from the connector's configuration file.
document	A LuaDocument object. The document object is an internal representation of the document being processed. Modifying this object changes the document.
params	<p>The params argument is a table that contains additional information provided by the connector:</p> <ul style="list-style-type: none"> <li>• <b>TYPE</b>. The type of task being performed. The possible values are ADD, UPDATE, DELETE, or COLLECT.</li> <li>• <b>SECTION</b>. The name of the section in the configuration file that contains configuration parameters for the task.</li> <li>• <b>FILENAME</b>. The document filename. The Lua script can modify this file, but must not delete it.</li> <li>• <b>OWNFILE</b>. Indicates whether the connector (and CFS) has ownership of the file. A value of true means that CFS deletes the file after it has been processed.</li> </ul>

The following script demonstrates how you can use the config and params arguments:

```
function handler(config, document, params)
  -- Write all of the additional information to a log file
  for k,v in pairs(params) do
    log("logfile.txt", k..": "..tostring(v))
  end

  -- The following lines set variables from the params argument
  type = params["TYPE"]
  section = params["SECTION"]
  filename = params["FILENAME"]

  -- Read a configuration parameter from the configuration file
  -- If the parameter is not set, "DefaultValue" is returned
  val = config:getValue(section, "Parameter", "DefaultValue")

  -- If the document is not being deleted, set the field FieldName
  -- to the value of the configuration parameter
  if type ~= "DELETE" then
    document:setFieldValue("FieldName", val)
  end

  -- If the document has a file (that is, not just metadata),
  -- copy the file to a new location and write a stub idx file
  -- containing the metadata.
  if filename ~= "" then
    copytofilename = "./out/"..create_uuid(filename)
    copy_file(filename, copytofilename)
    document:writeStubIdx(copytofilename..".idx")
  end
end
```

```
        end  
  
        return true  
    end
```

For the connector to continue processing the document, the `handler` function must return `true`. If the function returns `false`, the document is discarded.

**TIP:**

You can write a library of useful functions to share between multiple scripts. To include a library of functions in a script, add the code `dofile("library.lua")` to the top of the lua script, outside of the `handler` function.

## Run a Lua Script using an Ingest Action

To run a Lua script on documents that are sent for ingestion, use an Ingest Action.

### To run a Lua script using an Ingest Action

1. Open the connector's configuration file.
2. Find one of the following sections in the configuration file:
  - To run a Lua script on all documents retrieved by a specific task, find the `[TaskName]` section.
  - To run a Lua script on all documents that are sent for ingestion, find the `[Ingestion]` section.

**NOTE:**

If you set the `IngestActions` parameter in a `[TaskName]` section, the connector does not run any `IngestActions` set in the `[Ingestion]` section for that task.

3. Use the `IngestActions` parameter to specify the path to your Lua script. For example:

```
IngestActions=LUA:C:\Autonomy\myScript.lua
```

4. Save and close the configuration file.

### Related Topics

- [Write a Lua Script, on page 80](#)

## Example Lua Scripts

This section contains example Lua scripts.

- [Add a Field to a Document, on the next page](#)
- [Merge Document Fields, on the next page](#)

## Add a Field to a Document

The following script demonstrates how to add a field named “MyField” to a document, with a value of “MyValue”.

```
function handler(config, document, params)
    document:addField("MyField", "MyValue");
    return true;
end
```

The following script demonstrates how to add the field AUTN\_NEEDS\_MEDIA\_SERVER\_ANALYSIS to all JPEG, TIFF and BMP documents. This field indicates to CFS that the file should be sent to a Media Server for analysis (you must also define the MediaServerAnalysis task in the CFS configuration file).

The script finds the file type using the DREREFERENCE document field, so this field must contain the file extension for the script to work correctly.

```
function handler(config, document, params)
    local extensions_for_ocr = { jpg = 1 , tif = 1, bmp = 1 };
    local filename = document:getFieldValue("DREREFERENCE");
    local extension, extension_found = filename:gsub("^.*%.(%w+)$", "%1", 1);

    if extension_found > 0 then
        if extensions_for_ocr[extension:lower()] ~= nil then
            document:addField("AUTN_NEEDS_MEDIA_SERVER_ANALYSIS", "");
        end
    end

    return true;
end
```

## Merge Document Fields

This script demonstrates how to merge the values of document fields.

When you extract data from a repository, the connector can produce documents that have multiple values for a single field, for example:

```
#DREFIELD ATTACHMENT="attachment.txt"
#DREFIELD ATTACHMENT="image.jpg"
#DREFIELD ATTACHMENT="document.pdf"
```

This script shows how to merge the values of these fields, so that the values are contained in a single field, for example:

```
#DREFIELD ATTACHMENTS="attachment.txt, image.jpg, document.pdf"
```

## Example Script

```
function handler(config, document, params)
    onefield(document,"ATTACHMENT","ATTACHMENTS")
    return true;
end

function onefield(document,existingfield,newfield)
    if document:hasField(existingfield) then
        local values = { document:getFieldValues(existingfield) }

        local newfieldvalue=""
        for i,v in ipairs(values) do
            if i>1 then
                newfieldvalue = newfieldvalue ..", "
            end

            newfieldvalue = newfieldvalue..v
        end

        document:addField(newfield,newfieldvalue)
    end

    return true;
end
```

# Chapter 8: Ingestion


After a connector finds new documents in a repository, or documents that have been updated or deleted, it sends this information to another component called the *ingestion target*. This section describes where you can send the information retrieved by the HPE Web Connector, and how to configure the ingestion target.

- Introduction ..... 85
- Send Data to Connector Framework Server ..... 86
- Send Data to Haven OnDemand ..... 87
- Send Data to Another Repository ..... 89
- Index Documents Directly into IDOL Server ..... 89
- Index Documents into Vertica ..... 91
- Send Data to a MetaStore ..... 93
- Run a Lua Script after Ingestion ..... 94

## Introduction

A connector can send information to a single ingestion target, which could be:

- **Connector Framework Server.** To process information and then index it into IDOL, Haven OnDemand, or Vertica, send the information to a Connector Framework Server (CFS). Any files retrieved by the connector are *imported* using KeyView, which means the information contained in the files is converted into a form that can be indexed. If the files are containers that contain *subfiles*, these are extracted. You can manipulate and enrich documents using Lua scripts and automated tasks such as field standardization, image analysis, and speech-to-text processing. CFS can index your documents into one or more indexes. For more information about CFS, refer to the *Connector Framework Server Administration Guide*.



- **Haven OnDemand.** You can index documents directly into a Haven OnDemand text index. Haven OnDemand can extract text, metadata, and subfiles from over 1000 different file formats, so you might not need to send documents to CFS.
- **Another Connector.** Use another connector to keep another repository up-to-date. When a connector receives documents, it inserts, updates, or deletes the information in the repository. For example, you could use an Exchange Connector to extract information from Microsoft Exchange, and send the documents to a Notes Connector so that the information is inserted, updated, or deleted in the Notes repository.

**NOTE:**  
The destination connector can only insert, update, and delete documents if it supports the `insert`, `update`, and `delete` fetch actions.

In most cases HPE recommends ingesting documents through CFS, so that KeyView can extract content from any files retrieved by the connector and add this information to your documents. You can also use CFS to manipulate and enrich documents before they are indexed. However, if required you can configure the connector to index documents directly into:

- **IDOL Server.** You might index documents directly into IDOL Server when your connector produces metadata-only documents (documents that do not have associated files). In this case there is no need for the documents to be imported. Connectors that can produce metadata-only documents include ODBC Connector and Oracle Connector.
- **Vertica.** The metadata extracted by connectors is structured information held in structured fields, so you might use Vertica to analyze this information.
- **MetaStore.** You can index document metadata into a MetaStore for records management.

## Send Data to Connector Framework Server

This section describes how to configure ingestion into Connector Framework Server (CFS).

### To send data to a CFS

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

`EnableIngestion` To enable ingestion, set this parameter to `true`.

`IngesterType` To send data to CFS, set this parameter to `CFS`.

`IngestHost` The host name or IP address of the CFS.

`IngestPort` The ACI port of the CFS.

For example:

```
[Ingestion]
EnableIngestion=True
IngesterType=CFS
IngestHost=localhost
IngestPort=7000
```

4. (Optional) If you are sending documents to CFS for indexing into IDOL Server, set the `IndexDatabase` parameter. When documents are indexed, IDOL adds each document to the database specified in the document's `DREDBNAME` field. The connector sets this field for each document, using the value of `IndexDatabase`.

`IndexDatabase` The name of the IDOL database into which documents are indexed. Ensure that this database exists in the IDOL Server configuration file.

- To index all documents retrieved by the connector into the same IDOL database, set this parameter in the [Ingestion] section.
- To use a different database for documents retrieved by each task, set this parameter in the

*TaskName* section.

5. Save and close the configuration file.

## Send Data to Haven OnDemand

This section describes how to configure ingestion into Haven OnDemand. HPE Web Connector can index documents into a Haven OnDemand text index, or send the documents to a Haven OnDemand combination which can perform additional processing and then index the documents into a text index.

**NOTE:**

Haven OnDemand combinations do not accept binary files, so any documents that have associated binary files are indexed directly into a text index and cannot be sent to a combination.

## Prepare Haven OnDemand

Before you can send documents to Haven OnDemand, you must create a text index. For information about how to create text indexes, refer to the [Haven OnDemand documentation](#).

Before you can send documents to a Haven OnDemand combination endpoint, the combination must exist. HPE Web Connector requires your combination to accept the following input parameters, and produce the following output.

### Input Parameters

Name	Type	Description
json	any	A JSON object that contains a single attribute 'documents' that is an array of document objects.
index	string	The name of the text index that you want the combination to add documents to. HPE Web Connector uses the value of the parameter <code>HavenOnDemandIndexName</code> to set this value.
duplicate_mode	string	Specifies how to handle duplicates when adding documents to the text index. HPE Web Connector uses the value of the parameter <code>HavenOnDemandDuplicateMode</code> to set this value.

### Output

Name	Type	Description
result	any	The result of the call to <code>AddToTextIndex</code> made by the combination.

## Send Data to Haven OnDemand

This section describes how to send documents to Haven OnDemand.

### To send data to Haven OnDemand

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

EnableIngestion	To enable ingestion, set this parameter to <code>true</code> .
IngesterType	To send data to Haven OnDemand, set this parameter to <code>HavenOnDemand</code> .
HavenOnDemandApiKey	Your Haven OnDemand API key. You can obtain the key from your Haven OnDemand account.
HavenOnDemandIndexName	The name of the Haven OnDemand text index to index documents into.
IngestSSLConfig	The name of a section in the connector's configuration file that contains SSL settings. The connection to Haven OnDemand must be made over TLS. For more information about sending documents to the ingestion server over TLS, see <a href="#">Configure Outgoing SSL Connections, on page 31</a> .
HavenOnDemandCombinationName	(Optional) The name of the Haven OnDemand combination to send documents to. If you set this parameter, HPE Web Connector sends documents to the combination endpoint instead of indexing them directly into the text index.

**NOTE:**

Haven OnDemand combinations do not accept binary files. Therefore any document that has an associated binary file is indexed directly into the text index.

If you don't set this parameter, HPE Web Connector indexes all documents directly into the text index specified by `HavenOnDemandIndexName`.

For example:

```
[Ingestion]
EnableIngestion=True
IngesterType=HavenOnDemand
HavenOnDemandApiKey=[Your API Key]
HavenOnDemandIndexName=MyTextIndex
IngestSSLConfig=SSLOptions
HavenOnDemandCombinationName=MyCombination

[SSLOptions]
SSLMethod=TLSV1
```

4. Save and close the configuration file.

## Send Data to Another Repository

You can configure a connector to send the information it retrieves to another connector. When the destination connector receives the documents, it inserts them into another repository. When documents are updated or deleted in the source repository, the source connector sends this information to the destination connector so that the documents can be updated or deleted in the other repository.

**NOTE:**

The destination connector can only insert, update, and delete documents if it supports the insert, update, and delete fetch actions.

### To send data to another connector for ingestion into another repository

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

<code>EnableIngestion</code>	To enable ingestion, set this parameter to <code>true</code> .
<code>IngesterType</code>	To send data to another repository, set this parameter to <code>Connector</code> .
<code>IngestHost</code>	The host name or IP address of the machine hosting the destination connector.
<code>IngestPort</code>	The ACI port of the destination connector.
<code>IngestActions</code>	Set this parameter so that the source connector runs a Lua script to convert documents into form that can be used with the destination connector's insert action. For information about the required format, refer to the Administration Guide for the destination connector.

For example:

```
[Ingestion]
EnableIngestion=True
IngesterType=Connector
IngestHost=AnotherConnector
IngestPort=7010
IngestActions=Lua:transformation.lua
```

4. Save and close the configuration file.

## Index Documents Directly into IDOL Server

This section describes how to index documents from a connector directly into IDOL Server.

**TIP:**

In most cases, HPE recommends sending documents to a Connector Framework Server

(CFS). CFS extracts metadata and content from any files that the connector has retrieved, and can manipulate and enrich documents before they are indexed. CFS also has the capability to insert documents into more than one index, for example IDOL Server and a Vertica database. For information about sending documents to CFS, see [Send Data to Connector Framework Server, on page 86](#)

### To index documents directly into IDOL Server

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

EnableIngestion To enable ingestion, set this parameter to **true**.

IngesterType To send data to IDOL Server, set this parameter to **Indexer**.

IndexDatabase The name of the IDOL database to index documents into.

For example:

```
[Ingestion]
EnableIngestion=True
IngesterType=Indexer
IndexDatabase=News
```

4. In the [Indexing] section of the configuration file, set the following parameters:

IndexerType To send data to IDOL Server, set this parameter to **IDOL**.

Host The host name or IP address of the IDOL Server.

Port The IDOL Server ACI port.

SSLConfig (Optional) The name of a section in the connector's configuration file that contains SSL settings for connecting to IDOL.

For example:

```
[Indexing]
IndexerType=IDOL
Host=10.1.20.3
Port=9000
SSLConfig=SSLOptions
```

```
[SSLOptions]
SSLMethod=SSLV23
```

5. Save and close the configuration file.

## Index Documents into Vertica

HPE Web Connector can index documents into Vertica, so that you can run queries on structured fields (document metadata).

Depending on the metadata contained in your documents, you could investigate the average age of documents in a repository. You might want to answer questions such as: How much time has passed since the documents were last updated? How many files are regularly updated? Does this represent a small proportion of the total number of documents? Who are the most active users?

**TIP:**

In most cases, HPE recommends sending documents to a Connector Framework Server (CFS). CFS extracts metadata and content from any files that the connector has retrieved, and can manipulate and enrich documents before they are indexed. CFS also has the capability to insert documents into more than one index, for example IDOL Server and a Vertica database. For information about sending documents to CFS, see [Send Data to Connector Framework Server, on page 86](#)

## Prerequisites

- HPE Web Connector supports indexing into Vertica 7.1 and later.
- You must install the appropriate Vertica ODBC drivers (version 7.1 or later) on the machine that hosts HPE Web Connector. If you want to use an ODBC Data Source Name (DSN) in your connection string, you will also need to create the DSN. For more information about installing Vertica ODBC drivers and creating the DSN, refer to the [HPE Vertica documentation](#).

## New, Updated and Deleted Documents

When documents are indexed into Vertica, HPE Web Connector adds a timestamp that contains the time when the document was indexed. The field is named `VERTICA_INDEXER_TIMESTAMP` and the timestamp is in the format `YYYY-MM-DD HH:NN:SS`.

When a document in a data repository is modified, HPE Web Connector adds a new record to the database with a new timestamp. All of the fields are populated with the latest data. The record describing the older version of the document is not deleted. You can create a projection to make sure your queries only return the latest record for a document.

When HPE Web Connector detects that a document has been deleted from a repository, the connector inserts a new record into the database. The record contains only the `DREREFERENCE` and the field `VERTICA_INDEXER_DELETED` set to `TRUE`.

## Fields, Sub-Fields, and Field Attributes

Documents that are created by connectors can have multiple levels of fields, and field attributes. A database table has a flat structure, so this information is indexed into Vertica as follows:

- Document fields become columns in the flex table. An IDOL document field and the corresponding database column have the same name.
- Sub-fields become columns in the flex table. A document field named `my_field` with a sub-field named `subfield` results in two columns, `my_field` and `my_field.subfield`.
- Field attributes become columns in the flex table. A document field named `my_field`, with an attribute named `my_attribute` results in two columns, `my_field` holding the field value and `my_field.my_attribute` holding the attribute value.

## Prepare the Vertica Database

Indexing documents into a standard database is problematic, because documents do not have a fixed schema. A document that represents an image has different metadata fields to a document that represents an e-mail message. Vertica databases solve this problem with *flex tables*. You can create a flex table without any column definitions, and you can insert a record regardless of whether a referenced column exists.

You must create a flex table before you index data into Vertica.

When creating the table, consider the following:

- Flex tables store entire records in a single column named `__raw__`. The default maximum size of the `__raw__` column is 128K. You might need to increase the maximum size if you are indexing documents with large amounts of metadata.
- Documents are identified by their DREREFERENCE. HPE recommends that you do not restrict the size of any column that holds this value, because this could result in values being truncated. As a result, rows that represent different documents might appear to represent the same document. If you do restrict the size of the DREREFERENCE column, ensure that the length is sufficient to hold the longest DREREFERENCE that might be indexed.

To create a flex table without any column definitions, run the following query:

```
create flex table my_table();
```

To improve query performance, create real columns for the fields that you query frequently. For documents indexed by a connector, this is likely to include the DREREFERENCE:

```
create flex table my_table(DREREFERENCE varchar NOT NULL);
```

You can add new column definitions to a flex table at any time. Vertica automatically populates new columns with values for existing records. The values for existing records are extracted from the `__raw__` column.

For more information about creating and using flex tables, refer to the [HPE Vertica Documentation](#) or contact HPE Vertica technical support.

## Send Data to Vertica

To send documents to a Vertica database, follow these steps.

### To send data to Vertica

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

`EnableIngestion` To enable ingestion, set this parameter to `true`.

`IngesterType` To send data to a Vertica database, set this parameter to `Indexer`.

For example:

```
[Ingestion]
EnableIngestion=TRUE
IngesterType=Indexer
```

4. In the [Indexing] section, set the following parameters:

`IndexerType` To send data to a Vertica database, set this parameter to `Library`.

`LibraryDirectory` The directory that contains the library to use to index data.

`LibraryName` The name of the library to use to index data. You can omit the `.dll` or `.so` file extension. Set this parameter to `verticaIndexer`.

`ConnectionString` The connection string to use to connect to the Vertica database.

`TableName` The name of the table in the Vertica database to index the documents into. The table must be a flex table and must exist before you start indexing documents. For more information, see [Prepare the Vertica Database, on the previous page](#).

For example:

```
[Indexing]
IndexerType=Library
LibraryDirectory=indexerdlls
LibraryName=verticaIndexer
ConnectionString=DSN=VERTICA
TableName=my_flex_table
```

5. Save and close the configuration file.

## Send Data to a MetaStore

You can configure a connector to send documents to a MetaStore. When you send data to a Metastore, any files associated with documents are ignored.

**TIP:**

In most cases, HPE recommends sending documents to a Connector Framework Server (CFS). CFS extracts metadata and content from any files that the connector has retrieved, and can manipulate and enrich documents before they are indexed. CFS also has the capability to insert documents into more than one index, for example IDOL Server and a MetaStore. For information about sending documents to CFS, see [Send Data to Connector Framework Server, on page 86](#)

### To send data to a MetaStore

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. In the [Ingestion] section, set the following parameters:

`EnableIngestion` To enable ingestion, set this parameter to `true`.

`IngesterType` To send data to a MetaStore, set this parameter to `Indexer`.

For example:

```
[Ingestion]
EnableIngestion=True
IngesterType=Indexer
```

4. In the [Indexing] section, set the following parameters:

`IndexerType` To send data to a MetaStore, set this parameter to `MetaStore`.

`Host` The host name of the machine hosting the MetaStore.

`Port` The port of the MetaStore.

For example:

```
[Indexing]
IndexerType=Metastore
Host=MyMetaStore
Port=8000
```

5. Save and close the configuration file.

## Run a Lua Script after Ingestion

You can configure the connector to run a Lua script after batches of documents are successfully sent to the ingestion server. This can be useful if you need to log information about documents that were processed, for monitoring and reporting purposes.

To configure the file name of the Lua script to run, set the `IngestBatchActions` configuration parameter in the connector's configuration file.

- To run the script for all batches of documents that are ingested, set the parameter in the [Ingestion] section.
- To run the script for batches of documents retrieved by a specific task, set the parameter in the

[*TaskName*] section.

**NOTE:**

If you set the parameter in a [*TaskName*] section, the connector does not run any scripts specified in the [Ingestion] section for that task.

For example:

```
[Ingestion]
IngestBatchActions0=LUA:./scripts/myScript.lua
```

For more information about this parameter, refer to the *HPE Web Connector Reference*.

The Lua script must have the following structure:

```
function batchhandler(documents, ingesttype)
    ...
end
```

The `batchhandler` function is called after each batch of documents is sent to the ingestion server. The function is passed the following arguments:

Argument	Description
documents	A table of document objects, where each object represents a document that was sent to the ingestion server.  A document object is an internal representation of a document. You can modify the document object and this changes the document. However, as the script runs after the documents are sent to the ingestion server, any changes you make are not sent to CFS or IDOL.
ingesttype	A string that contains the ingest type for the documents. The <code>batchhandler</code> function is called multiple times if different document types are sent.

For example, the following script prints the ingest type (ADD, DELETE, or UPDATE) and the reference for all successfully processed documents to `stdout`:

```
function batchhandler(documents, ingesttype)
    for i,document in ipairs(documents) do
        local ref = document:getReference()
        print(ingesttype..": "..ref)
    end
end
```

# Chapter 9: Monitor the Connector

This section describes how to monitor the connector.

- [IDOL Admin](#) ..... 96
- [Use the Connector Logs](#) ..... 98
- [Set Up Event Handlers](#) ..... 99
- [Set Up Performance Monitoring](#) ..... 101
- [Set Up Document Tracking](#) ..... 103

## IDOL Admin

IDOL Admin is an administration interface for performing ACI server administration tasks, such as gathering status information, monitoring performance, and controlling the service. IDOL Admin provides an alternative to constructing actions and sending them from your web browser.

## Prerequisites

By default, the latest version of HPE Web Connector should include the `admin.dat` file that is required to run IDOL Admin. If you do not have this file, you must download it separately.

## Supported Browsers

IDOL Admin supports the following browsers:

- Internet Explorer 11 and later
- Edge
- Chrome (latest version)
- Firefox (latest version)

## Install IDOL Admin

You must install IDOL Admin on the same host that the ACI server or component is installed on. To set up a component to use IDOL Admin, you must configure the location of the `admin.dat` file and enable Cross Origin Resource Sharing.

### To install IDOL Admin

1. Stop the ACI server.
2. Save the `admin.dat` file to any directory on the host.
3. Using a text editor, open the ACI server or component configuration file. For the location of the

configuration file, see the ACI server documentation.

4. In the [Paths] section of the configuration file, set the AdminFile parameter to the location of the admin.dat file. If you do not set this parameter, the ACI server attempts to find the admin.dat file in its working directory when you call the IDOL Admin interface.
5. Enable Cross Origin Resource Sharing.
6. In the [Service] section, add the Access-Control-Allow-Origin parameter and set its value to the URLs that you want to use to access the interface.

Each URL must include:

- the http:// or https:// prefix

**NOTE:**

URLs can contain the https:// prefix if the ACI server or component has SSL enabled.

- The host that IDOL Admin is installed on
- The ACI port of the component that you are using IDOL Admin for

Separate multiple URLs with spaces.

For example, you could specify different URLs for the local host and remote hosts:

```
Access-Control-Allow-Origin=http://localhost:9010  
http://Computer1.Company.com:9010
```

Alternatively, you can set Access-Control-Allow-Origin=\*, which allows you to access IDOL Admin using any valid URL (for example, localhost, direct IP address, or the host name). The wildcard character (\*) is supported only if no other entries are specified.

If you do not set the Access-Control-Allow-Origin parameter, IDOL Admin can communicate only with the server's ACI port, and not the index or service ports.

7. Start the ACI server.

You can now access IDOL Admin (see [Access IDOL Admin, below](#)).

## Access IDOL Admin

You access IDOL Admin from a web browser. You can access the interface only through URLs that are set in the Access-Control-Allow-Origin parameter in the ACI server or component configuration file. For more information about configuring URL access, see [Install IDOL Admin, on the previous page](#).

### To access IDOL Admin from the host that it is installed on

- Type the following URL into the address bar of your web browser:

```
http://localhost:port/action=admin
```

where *port* is the ACI server or component ACI port.

### To access IDOL Admin from a different host

- Type the following URL into the address bar of your web browser:

```
http://host:port/action=admin
```

where:

*host* is the name or IP address of the host that IDOL Admin is installed on.

*port* is the ACI server or component ACI port of the IDOL Admin host.

## Use the Connector Logs

As the HPE Web Connector runs, it outputs messages to its logs. Most log messages occur due to normal operation, for example when the connector starts, receives actions, or sends documents for ingestion. If the connector encounters an error, the logs are the first place to look for information to help troubleshoot the problem.

The connector separates messages into the following message types, each of which relates to specific features:

Log Message Type	Description
Action	Logs actions that are received by the connector, and related messages.
Application	Logs application-related occurrences, such as when the connector starts.
Collect	Messages related to the <code>Collect</code> fetch action.
Identifiers	Messages related to the <code>Identifiers</code> fetch action.
Synchronize	Messages related to the <code>Synchronize</code> fetch action.
View	Messages related to the <code>View</code> action.

## Customize Logging

You can customize logging by setting up your own *log streams*. Each log stream creates a separate log file in which specific log message types (for example, action, index, application, or import) are logged.

### To set up log streams

1. Open the HPE Web Connector configuration file in a text editor.
2. Find the `[Logging]` section. If the configuration file does not contain a `[Logging]` section, add one.
3. In the `[Logging]` section, create a list of the log streams that you want to set up, in the format `N=LogStreamName`. List the log streams in consecutive order, starting from 0 (zero). For example:

```
[Logging]
LogLevel=FULL
LogDirectory=logs
0=ApplicationLogStream
1=ActionLogStream
```

You can also use the `[Logging]` section to configure any default values for logging configuration parameters, such as `LogLevel`. For more information, see the *HPE Web Connector Reference*.

4. Create a new section for each of the log streams. Each section must have the same name as the log stream. For example:

```
[ApplicationLogStream]
[ActionLogStream]
```

5. Specify the settings for each log stream in the appropriate section. You can specify the type of logging to perform (for example, full logging), whether to display log messages on the console, the maximum size of log files, and so on. For example:

```
[ApplicationLogStream]
LogTypeCSVs=application
LogFile=application.log
LogHistorySize=50
LogTime=True
LogEcho=False
LogMaxSizeKBs=1024

[ActionLogStream]
LogTypeCSVs=action
LogFile=logs/action.log
LogHistorySize=50
LogTime=True
LogEcho=False
LogMaxSizeKBs=1024
```

6. Save and close the configuration file. Restart the service for your changes to take effect.

## Set Up Event Handlers

The fetch actions sent to a connector are asynchronous. Asynchronous actions do not run immediately, but are added to a queue. This means that the person or application that sends the action does not receive an immediate response. However, you can configure the connector to call an event handler when an asynchronous action starts, finishes, or encounters an error.

You can use an event handler to:

- return data about an event back to the application that sent the action.
- write event data to a text file, to log any errors that occur.

The connector can call an event handler for the following events:

- OnStart** The `OnStart` event is called when the connector starts processing an asynchronous action.
- OnFinish** The `OnFinish` event is called when the connector successfully finishes processing an asynchronous action.
- OnError** The `OnError` event is called when an asynchronous action fails and cannot continue.

## Event Handlers

You can configure the connector to call an internal event handler, or write your own event handler. Connectors include the following internal event handlers.

### TextFileHandler

The TextFileHandler writes event data to a text file.

### HttpHandler

The HttpHandler sends event data to a URL.

### LuaHandler

The LuaHandler runs a Lua script. The event data is passed into the script. The script must have the following form:

```
function handler(request, xml)
    ...
end
```

- request is a table holding the request parameters.
- xml is a string holding the response to the request.

## Configure an Event Handler

To configure an event handler, follow these steps.

### To configure an event handler

1. Stop the connector.
2. Open the connector's configuration file in a text editor.
3. Use the `OnStart`, `OnFinish`, or `OnError` parameter to specify the name of a section in the configuration file that contains event handler settings for the corresponding event.
  - To run an event handler for all actions, set these parameters in the `[Actions]` section. For example:

```
[Actions]
OnStart=NormalEvents
OnFinish=NormalEvents
OnError=ErrorEvents
```
  - To run an event handler for specific actions, use the action name as a section in the configuration file. The following example runs an event handler when the *Fetch* action starts and finishes successfully:

```
[Fetch]
OnStart=NormalEvents
OnFinish=NormalEvents
```

4. Create a new section in the configuration file to contain the settings for your event handler. You must name the section using the name you specified with the `OnStart`, `OnFinish`, or `OnError` parameter.
5. In the new section, set the following parameters.

`LibraryName` (Required) The name of the library to use as the event handler. You can write your own event handler, or use one of the internal event handlers:

- To write event data to a text file, set this parameter to `TextFileHandler`, and then set the `FilePath` parameter to specify the path of the file.
- To send event data to a URL, set this parameter to `HttpHandler`, and then use the HTTP event handler parameters to specify the URL, proxy server settings, credentials and so on.
- To run a Lua script, set this parameter to `LuaHandler`, and then set the `LuaScript` parameter to specify the path to the Lua script.

For example:

```
[NormalEvents]
LibraryName=TextFileHandler
FilePath=./events.txt
```

```
[ErrorEvents]
LibraryName=LuaHandler
LuaScript=./error.lua
```

6. Save and close the configuration file.

## Set Up Performance Monitoring

You can configure a connector to pause tasks temporarily if performance indicators on the local machine or a remote machine breach certain limits. For example, if there is a high load on the CPU or memory of the repository from which you are retrieving information, you might want the connector to pause until the machine recovers.

**NOTE:**

Performance monitoring is available on Windows platforms only. To monitor a remote machine, both the connector machine and remote machine must be running Windows.

## Configure the Connector to Pause

### To configure the connector to pause

1. Open the configuration file in a text editor.
2. Find the [FetchTasks] section, or a [TaskName] section.
  - To pause all tasks, use the [FetchTasks] section.
  - To specify settings for a single task, find the [TaskName] section for the task.
3. Set the following configuration parameters:

PerfMonCounterNameN	The names of the performance counters that you want the connector to monitor. You can use any counter that is available in the Windows perfmon utility.
PerfMonCounterMinN	The minimum value permitted for the specified performance counter. If the counter falls below this value, the connector pauses until the counter meets the limits again.
PerfMonCounterMaxN	The maximum value permitted for the specified performance counter. If the counter exceeds this value, the connector pauses until the counter meets the limits again.
PerfMonAvgOverReadings	(Optional) The number of readings that the connector averages before checking a performance counter against the specified limits. For example, if you set this parameter to 5, the connector averages the last five readings and pauses only if the average breaches the limits. Increasing this value makes the connector less likely to pause if the limits are breached for a short time. Decreasing this value allows the connector to continue working faster following a pause.
PerfMonQueryFrequency	(Optional) The amount of time, in seconds, that the connector waits between taking readings from a performance counter.

For example:

```
[FetchTasks]
PerfMonCounterName0=\\machine-hostname\Memory\Available MBytes
PerfMonCounterMin0=1024
PerfMonCounterMax0=1024000
PerfMonCounterName1=\\machine-hostname\Processor(_Total)\% Processor Time
PerfMonCounterMin1=0
PerfMonCounterMax1=70
PerfMonAvgOverReadings=5
PerfMonQueryFrequency=10
```

**NOTE:**

You must set both a minimum and maximum value for each performance counter. You can

not set only a minimum or only a maximum.

4. Save and close the configuration file.

## Determine if an Action is Paused

To determine whether an action has been paused for performance reasons, use the QueueInfo action:

```
/action=queueInfo&queueAction=getStatus&queueName=fetch
```

You can also include the optional token parameter to return information about a single action:

```
/action=queueInfo&queueAction=getStatus&queueName=fetch&token=...
```

The connector returns the status, for example:

```
<autnresponse>  
  <action>QUEUEINFO</action>  
  <response>SUCCESS</response>  
  <responsedata>  
    <actions>  
      <action owner="2266112570">  
        <status>Processing</status>  
        <queued_time>2016-Jul-27 14:49:40</queued_time>  
        <time_in_queue>1</time_in_queue>  
        <process_start_time>2016-Jul-27 14:49:41</process_start_time>  
        <time_processing>219</time_processing>  
        <documentcounts>  
          <documentcount errors="0" task="MYTASK"/>  
        </documentcounts>  
        <fetchaction>SYNCHRONIZE</fetchaction>  
        <pausedforperformance>true</pausedforperformance>  
        <token>...</token>  
      </action>  
    </actions>  
  </responsedata>  
</autnresponse>
```

When the element `pausedforperformance` has a value of `true`, the connector has paused the task for performance reasons. If the `pausedforperformance` element is not present in the response, the connector has not paused the task.

## Set Up Document Tracking

Document tracking reports metadata about documents when they pass through various stages in the indexing process. For example, when a connector finds a new document and sends it for ingestion, a document tracking event is created that shows the document has been added. Document tracking can help you detect problems with the indexing process.

You can write document tracking events to a database, log file, or IDOL Server. For information about how to set up a database to store document tracking events, refer to the *IDOL Server Administration Guide*.

### To enable Document Tracking

1. Open the connector's configuration file.
2. Create a new section in the configuration file, named [DocumentTracking].
3. In the new section, specify where the document tracking events are sent.

- To send document tracking events to a database through ODBC, set the following parameters:

Backend	To send document tracking events to a database, set this parameter to <b>Library</b> .
LibraryPath	Specify the location of the ODBC document tracking library. This is included with IDOL Server.
ConnectionString	The ODBC connection string for the database.

For example:

```
[DocumentTracking]
Backend=Library
LibraryPath=C:\Autonomy\IDOLServer\IDOL\modules\dt_odbc.dll
ConnectionString=DSN=MyDatabase
```

- To send document tracking events to the connector's synchronize log, set the following parameters:

Backend	To send document tracking events to the connector's logs, set this parameter to <b>Log</b> .
DatabaseName	The name of the log stream to send the document tracking events to. Set this parameter to <b>synchronize</b> .

For example:

```
[DocumentTracking]
Backend=Log
DatabaseName=synchronize
```

- To send document tracking events to an IDOL Server, set the following parameters:

Backend	To send document tracking events to an IDOL Server, set this parameter to <b>IDOL</b> .
TargetHost	The host name or IP address of the IDOL Server.
TargetPort	The index port of the IDOL Server.

For example:

```
[DocumentTracking]
Backend=IDOL
```

```
TargetHost=idol  
TargetPort=9001
```

For more information about the parameters you can use to configure document tracking, refer to the *HPE Web Connector Reference*.

4. Save and close the configuration file.

# Chapter 10: Lua Functions and Methods Reference

This section describes the functions and methods that you can use in your Lua scripts.

- [General Functions](#) ..... 106
- [LuaConfig Methods](#) ..... 146
- [LuaDocument Methods](#) ..... 148
- [LuaField Methods](#) ..... 167
- [LuaHttpRequest Methods](#) ..... 179
- [LuaHttpResponse Methods](#) ..... 184
- [LuaJSONArray Methods](#) ..... 186
- [LuaJsonObject Methods](#) ..... 195
- [LuaJsonValue Methods](#) ..... 205
- [LuaLog Methods](#) ..... 217
- [LuaLogService Methods](#) ..... 218
- [LuaRegexMatch Methods](#) ..... 220
- [LuaXmlDocument Methods](#) ..... 222
- [LuaXmlNodeSet Methods](#) ..... 225
- [LuaXmlNode Methods](#) ..... 226
- [LuaXmlAttribute Methods](#) ..... 230

## General Functions

Function	Description
<a href="#">abs_path</a>	Returns the supplied path as an absolute path.
<a href="#">base64_decode</a>	Decodes a base64-encoded string.
<a href="#">base64_encode</a>	Base64-encodes a string.
<a href="#">convert_date_time</a>	Converts date and time formats using standard IDOL date formats.
<a href="#">convert_encoding</a>	Converts the encoding of a string from one character encoding to another.
<a href="#">copy_file</a>	Copies a file.
<a href="#">create_path</a>	Creates the specified directory tree.

Function	Description
<a href="#">create_uuid</a>	Creates a universally unique identifier.
<a href="#">delete_file</a>	Deletes a file.
<a href="#">delete_path</a>	Deletes a specified directory, but only if it is empty.
<a href="#">doc_tracking</a>	Raises a document tracking event for a document.
<a href="#">encrypt</a>	Encrypts a string.
<a href="#">encrypt_security_field</a>	Encrypts the ACL.
<a href="#">extract_date</a>	Searches a string for a date and returns the date.
<a href="#">file_setdates</a>	Modifies the properties of a file (for example created date, last modified date).
<a href="#">get_config</a>	Loads a configuration file.
<a href="#">get_log</a>	(Deprecated) Returns a LuaLog object that provides the capability to write log messages.
<a href="#">get_log</a>	Returns a LuaLog object that provides the capability to write log messages.
<a href="#">get_log_service</a>	Obtains a <a href="#">LuaLogService</a> object, from which you can obtain a <a href="#">LuaLog</a> object that you can use to write messages to a log file.
<a href="#">get_task_config</a>	Returns a LuaConfig object that contains the configuration of the fetch task that called the script.
<a href="#">get_task_name</a>	Returns the name of the fetch task that called the script.
<a href="#">getcwd</a>	Returns the current working directory of the application.
<a href="#">gobble_whitespace</a>	Reduces multiple adjacent white spaces.
<a href="#">hash_file</a>	Hashes a file using the SHA1 or MD5 algorithm.
<a href="#">hash_string</a>	Hashes a string.
<a href="#">is_dir</a>	Checks if the supplied path is a directory.
<a href="#">log</a>	Appends log messages to a file.
<a href="#">move_file</a>	Moves a file.
<a href="#">parse_csv</a>	Parse comma-separated values into individual strings.
<a href="#">parse_document_csv</a>	Parse a CSV file into documents and call a function on each document.
<a href="#">parse_document_idx</a>	Parse an IDX file into documents and call a function on each document.

Function	Description
<code>parse_document_idx</code>	Parse an IDX string or file and return a LuaDocument.
<code>parse_document_xml</code>	Parse an XML file into documents and call a function on each document.
<code>parse_document_xml</code>	Parse an XML string or file and return a LuaDocument.
<code>parse_json</code>	Parse a string of JSON data and return a LuaJsonValue.
<code>parse_json_array</code>	Parse a string of JSON data (that is a JSON array) and return a LuaJsonArray.
<code>parse_json_object</code>	Parse a string of JSON data (that is a JSON object) and return a LuaJsonObject.
<code>parse_xml</code>	Parse XML string to a LuaXmlDocument.
<code>regex_match</code>	Performs a regular expression match on a string.
<code>regex_replace_all</code>	Searches a string for matches to a regular expression, and replaces the matches.
<code>regex_search</code>	Performs a regular expression search on a string.
<code>script_path</code>	Returns the path and file name of the script that is running.
<code>send_aci_action</code>	Sends a query to an ACI server.
<code>send_aci_command</code>	Sends a query to an ACI server.
<code>send_and_wait_for_async_aci_action</code>	Sends a query to an ACI server and then waits for the action to finish. Use this method for sending asynchronous actions so that the action response is returned instead of a token.
<code>send_http_request</code>	Sends an HTTP request.
<code>sleep</code>	Pauses the running thread.
<code>unzip_file</code>	Extracts the contents of a zip file.
<code>url_escape</code>	Percent-encode a string.
<code>url_unescape</code>	Replaces URL escaped characters and returns a standard string.
<code>xml_encode</code>	Takes a string and encodes it using XML escaping.
<code>zip_file</code>	Zips the supplied path (file or directory).

## abs\_path

The `abs_path` method returns the supplied path as an absolute path.

### Syntax

```
abs_path( path )
```

### Arguments

Argument	Description
path	(string) A relative path.

### Returns

(String). A string containing the supplied path as an absolute path.

## base64\_decode

The `base64_decode` method decodes a base64-encoded string.

### Syntax

```
base64_decode( input )
```

### Arguments

Argument	Description
input	(string) The string to decode.

### Returns

(String). The decoded string.

If the input is not a valid base64-encoded string, the function returns `nil`.

## base64\_encode

The `base64_encode` method base64-encodes a string.

## Syntax

```
base64_encode( input )
```

## Arguments

Argument	Description
input	(string) The string to base64-encode.

## Returns

(String). A base64-encoded string.

## convert\_date\_time

The `convert_date_time` method converts date and time formats using standard IDOL formats. All date and time input is treated as local time unless it contains explicit time zone information.

The `InputFormatCSV` and `OutputFormat` arguments specify date and time formats, and accept the following values:

- `AUTNDATE`. The HPE date format (1 to a maximum of 10 digits). This format covers the epoch range (1 January 1970 to 19 January 2038) to a resolution of one second, and dates between 30 October 1093 BC and 26 October 3058 to a resolution of one minute.
- date formats that you specify using one or more of the following:

YY	Year (2 digits). For example, 99, 00, 01 and so on.
YYYY	Year (4 digits). For example, 1999, 2000, 2001 and so on.
#YY+	Year (2 or 4 digits). If you provide 2 digits, then it uses the YY format. If you provide 4 digits, it uses the YYYY format. For example, it interprets 07 as 2007 AD and 1007 as 1007 AD.
#Y	Year (1 to a maximum of 16 digits) and can be followed by AD or BC. An apostrophe ( ' ) immediately before the year denotes a truncated year. For example, 2008, '97 (interpreted as 1997), 97 (interpreted as 97 AD), '08 (interpreted as 2008), 2008 AD and 200 BC. A truncated year with a BC identifier is invalid ('08 BC).
#FULLYEAR	Year (1 to a maximum of 16 digits). For example 8, 98, 108, 2008, each of which is taken literally. The year is taken relative to the common EPOCH (0AD).
#ADBC	Time Period. For example, AD, CE, BC, BCE or any predefined list of EPOCH indicators. Typically, the year specified using the above Year formats is interpreted as un-truncated and relative to the EPOCH. For example, 84 AD is interpreted as 1984 AD and 84 BC is interpreted as 84 BC.

	The only exception to this is when you use both #YY+ and #ADBC. In this case, the format is interpreted as un-truncated even if the year was set to truncated by #YY+. For example, 99 AD is interpreted as the year 99 AD. HPE recommends you use only YY, YYYY or #FULLYEAR with #ADBC.
LONGMONTH	A long month, for example, January, February and so on.
SHORTMONTH	A short month, for example, Jan, Feb and so on.
MM	Month (2 digits). For example, 01, 10, 12 and so on.
M+	Month (1 or 2 digits). For example, 1,2,3,10 and so on.
DD	Day (2 digits). For example, 01, 02, 03, 12, 23 and so on.
D+	Day (1 or 2 digits). For example, 1, 2, 12, 13, 31 and so on.
LONGDAY	2 digits with a postfix. For example, 1st, 2nd and so on.
HH	Hour (2 digits). For example, 01, 12, 13 and so on.
H+	Hour (1 or 2 digits).
NN	Minute (2 digits).
N+	Minute (1 or 2 digits).
SS	Second (2 digits).
S+	Second (1 or 2 digits).
ZZZ	Time Zone, for example, GMT, EST, PST, and so on.
ZZZZZ	Time Difference (1 to 9 digits). For example, +04 denotes 4 hours ahead of UTC. Other examples include +4, +04, +0400, +0400 MSD (the string MSD is ignored). A further example is +030, in this case the time differences is interpreted as 30 minutes.
#PM	AM or PM indicator (2 characters). For example, 2001/09/09 02:46:40 pm
#S	A space

The following table shows some example date and time formats:

Date and time format string	Example date
DD/MM/YYYY	09/05/2013
D+ SHORTMONTH YYYY	2 Jan 2001
D+ LONGMONTH YYYY HH:NN:SS ZZZZZ	17 August 2003 10:41:07 -0400

## Syntax

```
convert_date_time( Input, InputFormatCSV, OutputFormat )
```

## Arguments

Argument	Description
Input	(string) The date and time to convert.
InputFormatCSV	(string) A comma-separated list of the possible date and time formats of the input.
OutputFormat	(string) The format of the date and time to output.

## Returns

(String). A string containing the date and time in the desired format.

## convert\_encoding

The `convert_encoding` method converts the encoding of a string from one character encoding to another.

## Syntax

```
convert_encoding( input, encodingTo, encodingTables [, encodingFrom])
```

## Arguments

Argument	Description
input	(string) The string to convert.
encodingTo	(string) The character encoding to convert <i>to</i> (same as IDOL encoding names).
encodingTables	(string) The path to the conversion tables.
encodingFrom	(string) The character encoding to convert <i>from</i> . The default is "UTF8".

## Returns

(String). A string, using the specified character encoding.

## copy\_file

The `copy_file` method copies a file.

### Syntax

```
copy_file( src, dest [, overwrite] )
```

### Arguments

Argument	Description
<code>src</code>	(string) The source file.
<code>dest</code>	(string) The destination path and file name.
<code>overwrite</code>	(boolean) A boolean that specifies whether to copy the file if the destination file already exists. If this argument is <code>false</code> and the file already exists, the copy operation fails. The default is <code>true</code> , which means that the existing file is overwritten.

### Returns

(Boolean). A Boolean, `true` to indicate success or `false` for failure.

## create\_path

The `create_path` method creates the specified directory tree.

### Syntax

```
create_path( path )
```

### Arguments

Argument	Description
<code>path</code>	(string) The path to create.

## create\_uuid

The `create_uuid` method creates a universally unique identifier.

## Syntax

```
create_uuid()
```

## Returns

(String). A string containing the universally unique identifier.

## delete\_file

The `delete_file` method deletes a file.

## Syntax

```
delete_file( path )
```

## Arguments

Argument	Description
path	(string) The path and filename of the file to delete.

## Returns

(Boolean). A boolean, `true` to indicate success or `false` for failure.

## delete\_path

The `delete_path` function deletes the specified directory, but only if it is empty.

## Syntax

```
delete_path( path )
```

## Arguments

Argument	Description
path	(string) The empty directory to delete.

## Returns

Nothing.

## Example

```
delete_path( "C:\MyFolder\AnotherFolder\" )
```

## doc\_tracking

The `doc_tracking` function raises a document tracking event for a document.

## Syntax

```
doc_tracking( document , eventName [, eventMetadata] [, reference] )
```

## Arguments

Argument	Description
document	(LuaDocument) The document to track.
eventName	(string) The event name. You can type a description of the event.
eventMetadata	(table) A table of key-value pairs that contain metadata for the document tracking event.
reference	(string) The document reference. You can set this parameter to override the document reference used.

## Returns

(Boolean). A Boolean that indicates whether the event was raised successfully.

## Example

```
local ref=document:getReference()  
  
doc_tracking(document, "The document has been processed",  
             {myfield="myvalue", anotherfield="anothervalue"}, ref )
```

## encrypt

The `encrypt` method encrypts a string and returns the encrypted string. It uses the same encryption method as ACL encryption.

### Syntax

```
encrypt( content )
```

### Arguments

Argument	Description
content	(string) The string to encrypt.

### Returns

(String). The encrypted string.

## encrypt\_security\_field

The `encrypt_security_field` method returns the encrypted form of the supplied field.

### Syntax

```
encrypt_security_field( field )
```

### Arguments

Argument	Description
field	(string) An Access Control List string.

### Returns

(String). An encrypted string.

## extract\_date

The `extract_date` function searches a string for a date and returns the date. This function uses standard IDOL date formats. All date and time input is treated as local time unless it contains explicit

time zone information.

The following table describes the standard IDOL date formats:

YY	Year (2 digits). For example, 99, 00, 01 and so on.
YYYY	Year (4 digits). For example, 1999, 2000, 2001 and so on.
#YY+	Year (2 or 4 digits). If you provide 2 digits, then it uses the YY format. If you provide 4 digits, it uses the YYYY format.  For example, it interprets 07 as 2007 AD and 1007 as 1007 AD.
#Y	Year (1 to a maximum of 16 digits) and can be followed by AD or BC. An apostrophe ( ' ) immediately before the year denotes a truncated year. For example, 2008, '97 (interpreted as 1997), 97 (interpreted as 97 AD), '08 (interpreted as 2008), 2008 AD and 200 BC. A truncated year with a BC identifier is invalid ('08 BC).
#FULLYEAR	Year (1 to a maximum of 16 digits). For example 8, 98, 108, 2008, each of which is taken literally. The year is taken relative to the common EPOCH (0AD).
#ADBC	Time Period. For example, AD, CE, BC, BCE or any predefined list of EPOCH indicators. Typically, the year specified using the above Year formats is interpreted as un-truncated and relative to the EPOCH. For example, 84 AD is interpreted as 1984 AD and 84 BC is interpreted as 84 BC.  The only exception to this is when you use both #YY+ and #ADBC. In this case, the format is interpreted as un-truncated even if the year was set to truncated by #YY+. For example, 99 AD is interpreted as the year 99 AD.  HPE recommends you use only YY, YYYY or #FULLYEAR with #ADBC.
LONGMONTH	A long month, for example, January, February and so on.
SHORTMONTH	A short month, for example, Jan, Feb and so on.
MM	Month (2 digits). For example, 01, 10, 12 and so on.
M+	Month (1 or 2 digits). For example, 1,2,3,10 and so on.
DD	Day (2 digits). For example, 01, 02, 03, 12, 23 and so on.
D+	Day (1 or 2 digits). For example, 1, 2, 12, 13, 31 and so on.
LONGDAY	2 digits with a postfix. For example, 1st, 2nd and so on.
HH	Hour (2 digits). For example, 01, 12, 13 and so on.
H+	Hour (1 or 2 digits).
NN	Minute (2 digits).
N+	Minute (1 or 2 digits).
SS	Second (2 digits).

S+	Second (1 or 2 digits).
ZZZ	Time Zone, for example, GMT, EST, PST, and so on.
ZZZZZ	Time Difference (1 to 9 digits). For example, +04 denotes 4 hours ahead of UTC. Other examples include +4, +04, +0400, +0400 MSD (the string MSD is ignored). A further example is +030, in this case the time differences is interpreted as 30 minutes.
#PM	AM or PM indicator (2 characters). For example, 2001/09/09 02:46:40 pm
#S	A space

The following table shows some example date and time formats:

Date and time format string	Example date
DD/MM/YYYY	09/05/2013
D+ SHORTMONTH YYYY	2 Jan 2001
D+ LONGMONTH YYYY HH:NN:SS ZZZZZ	17 August 2003 10:41:07 -0400

## Syntax

```
extract_date( input, formatCSV, outputFormat )
```

## Arguments

Argument	Description
input	(string) The string that you want to search for a date.
formatCSV	(string) A comma-separated list of the possible date and time formats for dates contained in the input.
outputFormat	(string) The format for the output.

## Returns

(String). A string containing the date and time in the desired format.

## Example

The following example would return the value "1989/01/14":

```
extract_date("This string contains a date 14/01/1989 somewhere",
"DD/YYYY/MM,DD/MM/YYYY", "YYYY/MM/DD")
```

## file\_setdates

The `file_setdates` method sets the metadata for the file specified by `path`. If the `format` argument is not specified, the dates must be specified in seconds since the epoch (1st January 1970).

### Syntax

```
file_setdates( path, created, modified, accessed [, format] )
```

### Arguments

Argument	Description
<code>path</code>	(string) The path or filename of the file.
<code>created</code>	(string) The date created (Windows only).
<code>modified</code>	(string) The date modified.
<code>accessed</code>	(string) The date last accessed.
<code>format</code>	(string) The format of the dates supplied. The format parameter uses the same values as other IDOL components. The default is "EPOCHSECONDS"

### Returns

(Boolean). A Boolean indicating whether the operation was successful.

## get\_config

The `get_config` function loads a configuration file.

Configuration files are cached after the first call to `get_config`, to avoid unnecessary disk I/O in the likely event that the same configuration is accessed frequently by subsequent invocations of the Lua script. One cache is maintained per Lua state, so the maximum number of reads for a configuration file is equal to the number of threads that run Lua scripts.

If you do not specify a path, the function returns the configuration file with the same name as the ACI server executable file.

### Syntax

```
get_config( [path] )
```

## Arguments

Argument	Description
path	(string) The path of the configuration file to load.

## Returns

(LuaConfig). A LuaConfig object.

## get\_log

### DEPRECATED:

This version of the `get_log` function is deprecated in HPE Web Connector 11.4.0 and later.

This version of the function is still available for existing implementations, but it might be incompatible with new functionality. This version of the function might be removed in future.

HPE recommends that you use the function `get_log( log_type )` instead.

The `get_log` function reads a configuration file and returns a [LuaLog](#) object that provides the capability to use the specified log stream.

## Syntax

```
get_log( config, logstream )
```

## Arguments

Argument	Description
config	(LuaConfig) A LuaConfig object that represents the configuration file which contains the log stream. You can obtain a LuaConfig object using the function <a href="#">get_config</a> .
logstream	(string) The name of the section in the configuration file that contains the settings for the log stream.

## Returns

(LuaLog). A [LuaLog](#) object that provides the capability to use the log stream.

## Example

```
local config = get_config("connector.cfg")  
local log = get_log(config, "SynchronizeLogStream")
```

## get\_log

The `get_log` method returns a [LuaLog](#) object that provides the capability to write messages to a specified log type.

## Syntax

```
get_log( log_type )
```

## Arguments

Argument	Description
log_type	(string) The log type name.

## Returns

(LuaLog). A [LuaLog](#) object.

## Example

```
local log = get_log("application")  
log:write_line(log_level_normal(), "doing something...")
```

## get\_log\_service

The `get_log_service` function obtains a [LuaLogService](#) object, from which you can obtain a [LuaLog](#) object that you can use to write messages to a log file.

### IMPORTANT:

To obtain a [LuaLog](#) object for writing to a standard log stream, call the function without any arguments or use the function [get\\_log](#) instead. Set the `config` argument only when you want to write to a custom log file that is not controlled by the ACI Server.

## Syntax

```
get_log_service( [config] )
```

## Arguments

Argument	Description
config	(LuaConfig) A LuaConfig object that represents the configuration file which contains the logging settings. You can obtain a LuaConfig object using the function <a href="#">get_config</a> .

## Returns

(LuaLogService). A [LuaLogService](#) object.

## Example

The following example shows how to use the `get_log_service` function to obtain a `LuaLogService` object. From this you can obtain a `LuaLog` object. The `LuaLog` object has a method, `write_line`, that writes messages to the log file.

```
local logService = get_log_service()
-- import is a standard log stream for CFS
local log = logService:get_log("import")
log:write_line( log_level_error() , "The log message")
```

The `get_log` function provides an easier way to accomplish the same task:

```
local log = get_log("import")
-- import is a standard log stream for CFS
log:write_line( log_level_error() , "The log message")
```

The following example demonstrates how to write messages to a custom log file. Declare the log service globally to avoid a `LuaLogService` object being created every time the script runs. For example, if you are writing a Lua script to use with a connector or CFS, call the `get_log_service` function outside the handler function.

```
local luaConfigString = [===[
[Logging]
LogLevel=FULL
Ø=LuaLogStream

[LuaLogStream]
LogTypeCSVs=lua
LogFile=lua.log
]===]

local config = LuaConfig:new(luaConfigString)

-- global log service instance for Lua log stream
luaLogService = get_log_service(config)
```

```
local luaLog = luaLogService:get_log("lua")  
luaLog:write_line(log_level_normal(), "running Lua script")
```

## get\_task\_config

The `get_task_config` function returns a `LuaConfig` object that contains the configuration of the fetch task that called the script.

For information about the methods you can use to read information from the `LuaConfig` object, see [LuaConfig Methods, on page 146](#).

### Syntax

```
get_task_config()
```

### Returns

(`LuaConfig`). A `LuaConfig` object.

## get\_task\_name

The `get_task_name` function returns a string that contains the name of the fetch task that called the script.

### Syntax

```
get_task_name()
```

### Returns

(`String`). A string that contains the task name.

## getcwd

The `getcwd` method returns the current working directory of the application.

### Syntax

```
getcwd()
```

### Returns

(`String`). Returns a string containing the absolute path of the current working directory.

## **gobble\_whitespace**

The `gobble_whitespace` method reduces multiple adjacent white spaces (tabs, carriage returns, spaces, and so on) in the specified string to a single space.

### **Syntax**

```
gobble_whitespace( input )
```

### **Arguments**

Argument	Description
input	(string) An input string.

### **Returns**

(String). A string without adjacent white spaces.

## **hash\_file**

The `hash_file` method hashes the contents of the specified file using the SHA1 or MD5 algorithm.

### **Syntax**

```
hash_file( FileName, Algorithm )
```

### **Arguments**

Argument	Description
FileName	(string) The name of the file.
Algorithm	(string) The type of algorithm to use. Must be either SHA1 or MD5.

### **Returns**

(String). A hash of the file contents.

## **hash\_string**

The `hash_string` method hashes the specified string using the SHA1 or MD5 algorithm.

## Syntax

```
hash_string( StringToHash, Algorithm )
```

## Arguments

Argument	Description
StringToHash	(string) The string to hash.
Algorithm	(string) The algorithm to use. Must be either SHA1 or MD5.

## Returns

(String). The hashed input string.

## is\_dir

The `is_dir` method checks if the supplied path is a directory.

## Syntax

```
is_dir( path )
```

## Arguments

Argument	Description
path	(string) The path to check.

## Returns

(Boolean). Returns `true` if the supplied path is a directory, `false` otherwise.

## log

The `log` method appends log messages to the specified file.

## Syntax

```
log( file, message )
```

## Arguments

Argument	Description
file	(string) The file to append log messages to.
message	(string) The message to print to the file.

## move\_file

The `move_file` method moves a file.

## Syntax

```
move_file( src, dest [, overwrite] )
```

## Arguments

Argument	Description
src	(string) The source file.
dest	(string) The destination file.
overwrite	(boolean) A boolean that specifies whether to move the file if the destination file already exists. If this argument is <code>false</code> , and the destination file already exists, the move operation fails. The default is <code>true</code> , which means that the destination file is overwritten.

## Returns

(Boolean). Returns `true` to indicate success, `false` otherwise.

## parse\_csv

The `parse_csv` method parses a string of comma-separated values into individual strings. The method understands quoted values (such that parsing 'foot, "leg, torso", elbow' produces three values) and ignores white space around delimiters.

## Syntax

```
parse_csv( input [, delimiter ] )
```

## Arguments

Argument	Description
input	(string) The string to parse.
delimiter	(string) The delimiter to use (the default delimiter is ",").

## Returns

(Strings). You can put them in a table like this:

```
local results = { parse_csv("cat,tree,house", ",") };
```

## parse\_document\_csv

The `parse_document_csv` function parses a CSV file into documents and calls a function on each document.

This function can handle CSV files with or without a header row, but if a header row is not present you must:

- set the named parameter `use_header_row` to `false`.
- specify the document field names to use by setting the named parameter `csv_field_names`.

## Syntax

```
parse_document_csv( filename, handler [, params ] )
```

## Arguments

Argument	Description
filename	(string) The path and file name of the CSV file to parse into documents.
handler	(document_handler_function) The function to call on each document that is parsed from the CSV file.
params	(table) A table of named parameters to configure parsing. The table maps parameter names (String) to parameter values. For information about the parameters that you can set, see the following table.

## Named Parameters

Named Parameter	Description
<code>content_field</code>	(string, default <code>DRECONTENT</code> ) The name of the field, in the CSV file, to use as the document content.
<code>csv_field_names</code>	(string list) A list of names for the fields that exist in the CSV file. This overrides any header row, if one is present.
<code>reference_field</code>	(string, default <code>DRREFERENCE</code> ) The name of the field, in the CSV file, to use as the document reference.
<code>use_header_row</code>	(boolean, default <code>TRUE</code> ) Specify whether the CSV file includes a header row (whether the first row is a list of field names and not values). If this parameter is <code>True</code> and you do not set <code>csv_field_names</code> , the field names in the header row are used as the names of the document fields.

## Example

The following example parses a CSV file named `data.csv`, and calls the function `documentHandler` on each document. The values in the field `item_id` become document references and the values in the field `body` become document content.

```
function documentHandler(document)
  -- do something, for example
  print(document:getReference())
end

...

parse_document_csv("./data.csv", documentHandler, {
  reference_field="item_id",
  content_field="body"
})
```

The following example shows how to provide field names when there is no header row in the CSV file:

```
parse_document_csv("./data_no_header.csv", documentHandler, {
  use_header_row=false,
  csv_field_names={"DRREFERENCE", "title", "modified", "DRECONTENT"}
})
```

## Returns

Nil.

## parse\_document\_idx

The `parse_document_idx` function parses an IDX file into documents and calls a function on each document.

### Syntax

```
parse_document_idx( filename, handler )
```

### Arguments

Argument	Description
filename	(string) The path and file name of the IDX file to parse into documents.
handler	(document_handler_function) The function to call on each document that is parsed from the IDX file. The function must accept a <code>LuaDocument</code> as the only argument.

### Example

The following example uses the `parse_document_idx` function to parse an IDX file, and calls the function `appendDocumentReference` on each document.

```
local references = {}

function appendDocumentReference(document)
    table.insert(references, document:getReference())
end

function read_idx_references(filename)
    parse_document_idx(filename, appendDocumentReference)
    return references
end
```

### Returns

Nil.

## parse\_document\_idx

The `parse_document_idx` function parses an IDX string or file, and returns a [LuaDocument](#).

**TIP:**

You can use this function if the string or file contains a single document. If you have an IDX file

that contains multiple documents you can use the function `parse_document_idx(filename, handler)` instead.

## Syntax

```
parse_document_idx( input, file )
```

## Arguments

Argument	Description
input	(string) The string or path to the file that contains the document in IDX format.
file	(boolean, default <code>false</code> ) Specifies whether the <code>input</code> argument is a path to a file.

## Example

If you have a string named `myIdxString` that contains a document in IDX format, you can obtain a `LuaDocument` object as follows:

```
local myDocument = parse_document_idx(myIdxString)
```

## Returns

(`LuaDocument`). A `LuaDocument` object that represents the document.

## parse\_document\_xml

The `parse_document_xml` function parses an XML file into documents and calls a function on each document.

## Syntax

```
parse_document_xml( filename, handler [, params ] )
```

## Arguments

Argument	Description
filename	(string) The path and file name of the XML file to parse into documents.
handler	( <code>document_handler_function</code> ) The function to call on each document that is parsed from the XML file. The function must accept a <code>LuaDocument</code> as the only argument.
params	(table) A table of named parameters to configure parsing. The table maps parameter

Argument	Description
	names (String) to parameter values. For information about the parameters that you can set, see the following table.

## Named Parameters

Named Parameter	Description
content_paths	(string list, default DRECONTENT) The paths in the XML to the elements that contain document content. You can specify a list of paths.
document_root_paths	(string list, default DOCUMENT) The paths in the XML to the elements that represent the root of a document. You can specify a list of paths.
include_root_path	(boolean, default false) Specifies whether to include the document_root_paths node in the document metadata. The default value includes only children of the root node.
reference_paths	(string list, default DREREFERENCE) The paths in the XML to elements that contain document references. Though you can specify a list of paths, there must be exactly one reference per document.

The default values of the content\_paths, document\_root\_path, and reference\_paths arguments are suitable for processing XML documents written out using the CFS XmlWriter.

## Example

The following example parses an XML file named data.xml, and calls the function printReference on each document. Two values have been set for the named parameter content\_paths. You might want to do this if there are multiple fields that contain content or you want to use the same script with XML files that have different schema.

```
local function printReference(document)
    print(document:getReference())
end

local xmlParams = {
    document_root_paths={"DOC"},
    reference_paths={"REF"},
    content_paths={"CONTENT", "MORE_CONTENT"}
}

parse_document_xml("./data.xml", printReference, xmlParams)
```

## Returns

Nothing.

## parse\_document\_xml

The `parse_document_xml` function parses an XML string or file into a document and returns a `LuaDocument`.

**TIP:**

You can use this function if the string or file contains a single document. If you have an XML file that contains multiple documents you can use the function `parse_document_xml(filename, handler [, params] )` instead.

### Syntax

```
parse_document_xml( input, file [, params ] )
```

### Arguments

Argument	Description
input	(string) The string or path to the file that contains the document in XML format.
file	(boolean) Specifies whether the <code>input</code> argument is a path to a file.
params	(table) A table of named parameters to configure parsing. The table maps parameter names (String) to parameter values. For information about the parameters that you can set, see the following table.

### Named Parameters

Named Parameter	Description
content_paths	(string list, default DRECONTENT) The paths in the XML to the elements that contain document content. You can specify a list of paths.
document_root_paths	(string list, default DOCUMENT) The paths in the XML to the elements that represent the root of a document. You can specify a list of paths.
include_root_path	(boolean, default false) Specifies whether to include the <code>document_root_paths</code> node in the document metadata. The default value includes only children of the root node.
reference_paths	(string list, default DREREFERENCE) The paths in the XML to elements that contain document references. Though you can specify a list of paths, there must be exactly one reference per document.

The default values of the `content_paths`, `document_root_path`, and `reference_paths` arguments are suitable for processing XML documents written out using the CFS `XmlWriter`.

## Example

If you have a string named `myXmlString` that contains a document in XML format, you can obtain a `LuaDocument` object as follows:

```
local xmlParams = {  
    document_root_paths={"DOC"},  
    reference_paths={"REF"},  
    content_paths={"CONTENT", "MORE_CONTENT"}  
}  
  
local myDocument = parse_document_xml(myXmlString, false, xmlParams)
```

## Returns

([LuaDocument](#)). A `LuaDocument` object that represents the document.

## parse\_json

The `parse_json` function parses a string of JSON and returns a JSON value.

## Syntax

```
parse_json( json )
```

## Arguments

Argument	Description
<code>json</code>	(string) The input string to parse.

## Returns

([LuaJsonValue](#)). A `LuaJsonValue` containing the JSON data.

## Example

```
local fh = io.open("example_json.json", "r")  
local file_content = fh:read("*all")  
fh:close()  
  
local myJsonValue = parse_json(file_content)  
  
if myJsonValue:is_object() then
```

```
document:insertJson( myJsonValue:object() , "MyJsonField" )  
elseif myJsonValue:is_array() then  
    document:insertJson( myJsonValue:array() , "MyJsonField" )  
end
```

If the file `example_json.json` contained the following JSON object:

```
{  
  "product": "IDOL",  
  "component": "CFS",  
  "version": { "major": 11, "minor": 3 },  
  "ports": [  
    { "type": "ACI", "number": 7000 },  
    { "type": "Service", "number": 17000 }  
  ]  
}
```

The resulting document might look like this:

```
<document>  
  <reference>ref1</reference>  
  <xmlmetadata>  
    <MyJsonField>  
      <component>CFS</component>  
      <ports>  
        <number>7000</number>  
        <type>ACI</type>  
      </ports>  
      <ports>  
        <number>17000</number>  
        <type>Service</type>  
      </ports>  
      <product>IDOL</product>  
      <version>  
        <major>11</major>  
        <minor>3</minor>  
      </version>  
    </MyJsonField>  
  </xmlmetadata>  
</document>
```

## See Also

If you know that the input data is a JSON object, you can also use the function [parse\\_json\\_object](#). If you know that the input data is a JSON array, you can also use the function [parse\\_json\\_array](#).

## parse\_json\_array

The `parse_json_array` function parses a string and returns a JSON array.

## Syntax

```
parse_json_array( json )
```

## Arguments

Argument	Description
json	(string) The input string to parse.

## Returns

([LuaJsonArray](#)). A [LuaJsonArray](#) containing the JSON data.

## See Also

If you can't be sure whether the input data is a JSON array, you can use the function [parse\\_json](#) to parse the JSON. The [parse\\_json](#) function returns a [LuaJsonValue](#), which can represent a JSON array or a JSON object.

## parse\_json\_object

The `parse_json_object` function parses a string and returns a JSON object.

## Syntax

```
parse_json_object( json )
```

## Arguments

Argument	Description
json	(string) The input string to parse.

## Returns

([LuaJsonObject](#)). A [LuaJsonObject](#) containing the JSON data.

## See Also

If you can't be sure whether the input data is a JSON object, you can use the function [parse\\_json](#) to parse the JSON. The [parse\\_json](#) function returns a [LuaJsonValue](#), which can represent a JSON array

or a JSON object.

## parse\_xml

The `parse_xml` method parses an XML string to a `LuaXmlDocument`.

### Syntax

```
parse_xml( xml )
```

### Arguments

Argument	Description
<code>xml</code>	(string) XML data as a string.

### Returns

(`LuaXmlDocument`). A `LuaXmlDocument` containing the parsed data, or `nil` if the string could not be parsed.

## regex\_match

The `regex_match` method performs a regular expression match on a string.

### Syntax

```
regex_match( input, regex [, case] )
```

### Arguments

Argument	Description
<code>input</code>	(string) The string to match.
<code>regex</code>	(string) The regular expression to match against.
<code>case</code>	(boolean) A boolean that specifies whether the match is case-sensitive. The match is case sensitive by default ( <code>true</code> ).

### Returns

One or more strings, or `nil`.

If the string matches the regular expression, and the regular expression has no sub-matches, the full string is returned.

If the string matches the regular expression, and the regular expression has sub-matches, then only the sub-matches are returned.

If the string does not match the regular expression, there are no return values (any results are `nil`).

You can assign multiple strings to a table. To assign the return values to a table, surround the function call with braces. For example:

```
matches = { regex_match( input, regex ) }
```

## Examples

```
local r1, r2, r3 = regex_match( "abracadabra", "(a.r)((?:a.)*ra)" )
```

Results: r1="abr", r2="acadabra", r3=nil

```
local r1, r2, r3 = regex_match( "abracadabra", "a.r(?:a.)*ra" )
```

Results: r1="abracadabra", r2=nil, r3=nil

## regex\_replace\_all

The `regex_replace_all` method searches a string for matches to a regular expression, and replaces the matches according to the value specified by the replacement argument.

## Syntax

```
regex_replace_all( input, regex, replacement )
```

## Arguments

Argument	Description
input	(string) The string in which you want to replace values.
regex	(string) The regular expression to use to find values to be replaced.
replacement	(string) A string that specifies how to replace the matches of the regular expression.

## Returns

(String). The modified string.

## Examples

```
regex_replace_all("ABC ABC ABC", "AB", "A")  
-- returns "AC AC AC"
```

```
regex_replace_all("One Two Three", "\\w{3}", "_")  
-- returns "_ _ _ee"
```

```
regex_replace_all("One Two Three", "(\\w+) (\\w+)", "\\2 \\1")  
-- returns "Two One Three"
```

## regex\_search

The `regex_search` method performs a regular expression search on a string. This method returns a `LuaRegexMatch` object, rather than strings.

## Syntax

```
regex_search ( input, regex [, case])
```

## Arguments

Argument	Description
input	(string) The string in which to search.
regex	(string) The regular expression with which to search.
case	(boolean) A boolean that specifies whether the match is case-sensitive. The match is case sensitive by default (true).

## Returns

(`LuaRegexMatch`).

## script\_path

The `script_path` function returns the path and file name of the script that is running.

## Syntax

```
script_path()
```

## Returns

(String, String) Returns the path of the folder that contains the script and the file name of the script, as separate strings.

## Example

```
local script_directory, script_filename = script_path()
```

You can use this function to load scripts using their location relative to the current script. In the following example only the first return value from `script_path()` - the directory - is concatenated with `"more_scripts/another_script.lua"`.

```
dofile(script_path().."more_scripts/another_script.lua")
```

## send\_aci\_action

The `send_aci_action` method sends a query to an ACI server. This method takes the action parameters as a table instead of the full action as a string, as with `send_aci_command`. This avoids issues with parameter values containing an ampersand (&).

## Syntax

```
send_aci_action( host, port, action [, parameters] [, timeout] [, retries] [,  
sslParameters] )
```

## Arguments

Argument	Description
host	(string) The ACI host to send the query to.
port	(number) The port to send the query to.
action	(string) The action to perform (for example, query).
parameters	(table) A Lua table containing the action parameters, for example, { param1="value1", param2="value2" }
timeout	(number) The number of milliseconds to wait before timing out. The default is 3000.
retries	(number) The number of times to retry if the request fails. The default is 3.
sslParameters	(table) A Lua table containing the SSL settings.

## Returns

(String). Returns the XML response as a string. If required, you can call `parse_xml` on the string to return a `LuaXMLDocument`. If the request fails, it returns `nil`.

## Example

```
send_aci_action( "localhost", 9000, "query" ,  
                {text = "*", print = "all"} );
```

## See Also

- [send\\_aci\\_command, below](#)

## send\_aci\_command

The `send_aci_command` method sends a query to an ACI server.

## Syntax

```
send_aci_command( host, port, query [, timeout] [, retries] [, sslParameters] )
```

## Arguments

Argument	Description
host	(string) The ACI host to send the query to.
port	(number) The port to send the query to.
query	(string) The query to send (for example, <code>action=getstatus</code> )
timeout	(number) The number of milliseconds to wait before timing out. The default is 3000.
retries	(number) The number of times to retry if the request fails. The default is 3.
sslParameters	(table) A Lua table containing the SSL settings.

## Returns

(String). Returns the XML response as a string. If required, you can call `parse_xml` on the string to return a `LuaXMLDocument`. If the request fails, it returns `nil`.

## See Also

- [send\\_aci\\_action](#), on page 139

## send\_and\_wait\_for\_async\_aci\_action

The `send_and_wait_for_async_aci_action` method sends a query to an ACI server. The method does not return until the action has completed.

You might use this method when you want to use an asynchronous action. The `send_aci_action` method returns as soon as it receives a response, which for an asynchronous action means that it returns a token. The method `send_and_wait_for_async_aci_action` sends an action and then waits. It polls the server until the action is complete and then returns the response.

Argument	Description
host	(string) The ACI host to send the query to.
port	(number) The ACI port to send the query to.
action	(string) The name of the action to perform.
parameters	(table) A Lua table containing the action parameters, for example, { param1="value1", param2="value2" }
timeout	(number) The number of milliseconds to wait before timing out. The default is 60000 (1 minute).
retries	(number) The number of times to retry if the connection fails. The default is 3.
sslParameters	(table) A Lua table containing the SSL settings.

## Returns

(String). Returns the XML response as a string. If required, you can call `parse_xml` on the string to return a `LuaXMLDocument`. If the request fails, it returns `nil`.

## See Also

- [send\\_aci\\_action](#), on page 139

## send\_http\_request

The `send_http_request` function sends a HTTP request.

## Syntax

```
send_http_request( params )
```

## Arguments

Argument	Description
params	(table) Named parameters that configure the HTTP request. The table maps parameter names (string) to parameter values. For information about the parameters that you can set, see the following table.

## Named Parameters

Named Parameter	Description
url	(string) The full URL for the HTTP request. If you provide a URL, the other parameters used to build the URL are not used.
method	(string) The HTTP method to use (GET, POST, or DELETE). The default is "GET".
headers	(table) A table of HTTP headers to send with the request. The table must map header names to values.
content	(string) For HTTP POST, the data to be sent with the post.
site	(string) The site to which the HTTP request is sent.
port	(integer) The port to which the HTTP request is sent. By default, the request is sent to port 80.
uri	(string) The URI to request.
params	(table) Additional parameters for the request. The table must map parameter names to parameter values.
section	(string) The name of a section in the configuration file that contains transport related parameters such as SSL or proxy settings.

## Returns

**String.** The HTTP response.

## Examples

```
local wikipedia_page = send_http_request(  
    {url = "http://en.wikipedia.org/wiki/Hypertext_Transfer_Protocol"} )  
  
local google_search = send_http_request(  
    {site = "www.google.co.uk", port = 80, uri = "/search",  
    params = {q = "http protocol", safe = "active"}} )  
  
local search = send_http_request(  
    {site = "www.site.com", port = 80, uri = "/query",  
    params = {text = "http headers", maxresults = "10"},  
    headers = { Cache-Control = "no-cache" }} )
```

## sleep

The sleep method pauses the thread.

## Syntax

```
sleep( milliseconds )
```

## Arguments

Argument	Description
milliseconds	(number) The number of milliseconds for which to pause the current thread.

## unzip\_file

The unzip\_file method extracts the contents of a zip file.

## Syntax

```
unzip_file( path, dest )
```

## Arguments

Argument	Description
path	(string) The path and filename of the file to unzip.
dest	(string) The destination path where files are extracted.

## Returns

(Boolean). Returns a Boolean indicating success or failure.

## url\_escape

The `url_escape` method percent-encodes a string.

## Syntax

```
url_escape( input )
```

## Arguments

Argument	Description
input	(string) The string to percent-encode.

## Returns

(String). The percent-encoded string.

## url\_unescape

The `url_unescape` method replaces URL escaped characters and returns a standard string.

## Syntax

```
url_unescape( input )
```

## Arguments

Argument	Description
input	(string) The string to process.

## Returns

(String). The modified string.

## xml\_encode

The `xml_encode` method takes a string and encodes it using XML escaping.

### Syntax

```
xml_encode ( content )
```

### Arguments

Argument	Description
<code>content</code>	(string) The string to encode.

### Returns

(String).

## zip\_file

The `zip_file` method zips the supplied path (file or directory). It overwrites the output file only if you set the optional `overwrite` argument to `true`.

### Syntax

```
zip_file( path [, overwrite] )
```

### Arguments

Argument	Description
<code>path</code>	(string) The path or filename of the file or folder to zip.
<code>overwrite</code>	(boolean) A boolean that specifies whether to force the creation of the zip file if an output file already exists. The default is <code>false</code> .

### Returns

(Boolean). Returns a Boolean indicating success or failure. On success writes a file called `path.zip`.

## LuaConfig Methods

A `LuaConfig` object provides access to configuration information. You can retrieve a `LuaConfig` for a given configuration file using the `get_config` function.

If you have a `LuaConfig` object called `config` you can call its methods using the `':'` operator. For example:

```
config:getValue(sectionName, parameterName)
```

Constructor	Description
<code>LuaConfig:new</code>	The constructor for a <code>LuaConfig</code> object (creates a new <code>LuaConfig</code> object).

Method	Description
<code>getEncryptedValue</code>	Returns the unencrypted value from the config of an encrypted value.
<code>getValue</code>	Returns the value of the configuration parameter key in a given section.
<code>getValues</code>	Returns all the values of a configuration parameter if you have multiple values for a key (for example, a comma-separated list or numbered list like <code>keyN</code> ).

## getEncryptedValue

The `getEncryptedValue` method returns the unencrypted value from the configuration file of an encrypted value.

### Syntax

```
getEncryptedValue( section, parameter )
```

### Arguments

Argument	Description
<code>section</code>	(string) The section in the configuration file.
<code>parameter</code>	(string) The parameter in the configuration file to get the value for.

### Returns

(String). The unencrypted value.

## getValue

The `getValue` method returns the value of the configuration parameter key in a given section. If the key does not exist in the section, then it returns the default value.

### Syntax

```
getValue( section, key [, default] )
```

### Arguments

Argument	Description
section	(string) The section name in the configuration file.
key	(string) The name of the key from which to read.
default	(string/boolean/number) The default value to use if no key is found.

### Returns

A string, boolean, or integer containing the value read from the configuration file.

## getValues

The `getValues` method returns multiple values for a parameter (for example, a comma-separated list or numbered list like keyN).

### Syntax

```
getValues( section, parameter )
```

### Arguments

Argument	Description
section	(string) The section in the configuration file.
parameter	(string) The parameter to find in the configuration file.

## Returns

(Strings). The strings can be assigned to a table. To map the return values to a table, surround the function call with braces. For example:

```
values = { config:getValues( section, parameter ) }
```

## LuaConfig:new

The constructor for a LuaConfig object (creates a new LuaConfig object).

## Syntax

```
LuaConfig:new( config_buffer )
```

## Arguments

Argument	Description
config_buffer	(string) The configuration to use to create the LuaConfig object.

## Returns

(LuaConfig). The new LuaConfig object.

## Example

```
local config_buffer = "[default]\nparameter=value"  
local config = LuaConfig:new(config_buffer)
```

## LuaDocument Methods

This section describes the methods provided by the LuaDocument object. A LuaDocument allows you to access and modify the reference, metadata and content of a document.

If you have a LuaDocument object called `document` you can call its methods using the ':' operator. For example:

```
document:addField(name, value)
```

Constructor	Description
<a href="#">LuaDocument:new</a>	The constructor for a LuaDocument object (creates a new LuaDocument object that only contains a reference).

Method	Description
<a href="#">addField</a>	Creates a new field.
<a href="#">addSection</a>	Add an empty section to the end of the document.
<a href="#">appendContent</a>	Appends content to the existing content of the document.
<a href="#">copyField</a>	Creates a new named field with the same value as an existing named field.
<a href="#">copyFieldNoOverwrite</a>	Copies a field to a certain name but does not overwrite the existing value.
<a href="#">countField</a>	Returns the number of fields with the name specified.
<a href="#">deleteField</a>	Removes a field from the document.
<a href="#">getContent</a>	Returns the document content.
<a href="#">getField</a>	Returns the first field with a specified name.
<a href="#">getFieldNames</a>	Returns all the field names for the document.
<a href="#">getFields</a>	Returns all fields with the specified name.
<a href="#">getFieldValue</a>	Gets a field value.
<a href="#">getFieldValues</a>	Gets all values of a multi-valued field.
<a href="#">getNextSection</a>	Gets the next section in a document, allowing you to perform find or add operations on every section.
<a href="#">getReference</a>	Returns the document reference.
<a href="#">getSection</a>	Returns a LuaDocument object with the specified section as the active section.
<a href="#">getSectionCount</a>	Returns the number of sections in the document.
<a href="#">getValueByPath</a>	Gets the value of the document field or sub field with the specified path.
<a href="#">getValuesByPath</a>	Gets all values of a multi-value document field or sub field, with the specified path.
<a href="#">hasField</a>	Checks whether the document has a named field.
<a href="#">insertJson</a>	Inserts metadata, from a JSON string, into a document.
<a href="#">insertXml</a>	Inserts XML metadata into a document.
<a href="#">insertXmlWithoutRoot</a>	Inserts XML metadata into a document.
<a href="#">removeSection</a>	Removes a section from a document.
<a href="#">renameField</a>	Renames a field.
<a href="#">setContent</a>	Sets the content for a document.

Method	Description
<a href="#">setFieldValue</a>	Sets a field value.
<a href="#">setReference</a>	Sets the document reference.
<a href="#">to_idx</a>	Returns a string containing the document in IDX format.
<a href="#">to_json</a>	Returns a string containing the document in JSON format.
<a href="#">to_xml</a>	Returns a string containing the document in XML format.
<a href="#">writeStubIdx</a>	Writes out a stub IDX document.
<a href="#">writeStubXml</a>	Writes out a stub XML document.

## addField

The `addField` method adds a new field to the document.

### Syntax

```
addField ( fieldname, fieldvalue )
```

### Arguments

Argument	Description
<code>fieldname</code>	(string) The name of the field to add.
<code>fieldvalue</code>	(string) The value to set for the field.

## addSection

The `addSection` method adds an empty section to the end of the document.

### Syntax

```
addSection()
```

### Returns

(LuaDocument). Returns a LuaDocument object representing the document, with the new section as the active section.

## Example

```
local newSection = document:addSection() -- Add a new section to the document
newSection:setContent("content")       -- Set content for the new section
```

## appendContent

The `appendContent` method appends content to the existing content (the `DRECONTENT` field) of a document or document section.

## Syntax

```
appendContent ( content [, number])
```

## Arguments

Argument	Description
content	(string) The content to append.
number	(number) The document section to modify. If you do not specify this argument, content is appended to the last section. If you specify a number greater than the number of existing sections, additional empty sections are created.

## Examples

```
-- Append content to the last section
document:appendContent("content")
```

```
-- Append content to section 7, empty sections are created before this section if
necessary
document:appendContent("content", 7)
```

## copyField

The `copyField` method copies a field value to a new field. If the target field already exists it is overwritten.

## Syntax

```
copyField ( sourcename, targetname [, case] )
```

## Arguments

Argument	Description
sourcename	(string) The name of the field to copy.
targetname	(string) The destination field name.
case	(boolean) A boolean that specifies whether <code>sourcename</code> is case-sensitive. The field name is case sensitive by default ( <code>true</code> ).

## copyFieldNoOverwrite

The `copyFieldNoOverwrite` method copies a field value to a new field but does not overwrite the existing value. After calling this function the target field will contain all values of the source field in addition to any values it already had.

### Syntax

```
copyFieldNoOverwrite( sourcename, targetname [, case])
```

## Arguments

Argument	Description
sourcename	(string) The name of the field to copy.
targetname	(string) The destination field name.
case	(boolean) A boolean that specifies whether <code>sourcename</code> is case-sensitive. The name is case sensitive by default ( <code>true</code> ).

## countField

The `countField` method returns the number of fields with the specified name.

### Syntax

```
countField( fieldname [, case] )
```

## Arguments

Argument	Description
fieldname	(string) The name of the field to count.
case	(boolean) A boolean that specifies whether <code>fieldname</code> is case sensitive. The field name is case sensitive by default ( <code>true</code> ).

## Returns

(Number) The number of fields with the specified name.

## deleteField

The `deleteField` method deletes a field from a document. If you specify the optional `value` argument, the field is deleted only if it has the specified value.

## Syntax

```
deleteField( fieldName [, case] )  
deleteField( fieldName, value [, case] )
```

## Arguments

Argument	Description
fieldname	(string) The name of the field to delete.
value	(string) The value of the field. If this is specified only fields with matching names and values are deleted. If this is not specified, all fields that match <code>fieldname</code> are deleted.
case	(boolean) A boolean that specifies whether <code>fieldname</code> is case sensitive. The field name is case sensitive by default ( <code>true</code> ).

## getContent

The `getContent` method gets the content (the value of the `DRECONTENT` field) for a document or document section.

## Syntax

```
getContent([number])
```

## Arguments

Argument	Description
number	(number) The document section for which you want to return the content. If you do not specify this argument, the method returns the content of the active section. For the document object passed to the script's <code>handler</code> function, the active section is the first section (section 0).

## Returns

(String). The document content as a string.

## Examples

```
local content7 = document:getContent(7)    -- Get content for section 7
local section = document:getSection(3)    -- Get document for section 3
local content3 = section:getContent()    -- Get content for section 3
local content0 = document:getContent()    -- Get content for section 0
```

## getField

The `getField` method returns a `LuaField` object representing the field with the specified name.

## Syntax

```
getField( name [, case]
```

## Arguments

Argument	Description
name	(string) The name of the field.
case	(boolean) A boolean that specifies whether the <code>name</code> argument is case-sensitive. The name is case sensitive by default ( <code>true</code> ).

## Returns

(`LuaField`). A `LuaField` object.

## getFieldNames

The `getFieldNames` method returns all of the field names for the document.

### Syntax

```
getFieldNames()
```

### Returns

(Strings) The names of the fields. To map the return values to a table, surround the function call with braces. For example:

```
names = { document:getFieldNames() }
```

## getFields

The `getFields` method returns `LuaField` objects where each object represents a field that matches the specified name.

### Syntax

```
getFields( name [, case]
```

### Arguments

Argument	Description
name	(string) The name of the field.
case	(boolean) A boolean that specifies whether the <code>name</code> argument is case-sensitive. The name is case sensitive by default ( <code>true</code> ).

### Returns

(`LuaFields`) One `LuaField` for each matching field. To map the return values to a table, surround the function call with braces. For example:

```
fields = { document:getFields( name ) }
```

## getFieldValue

The `getFieldValue` method gets the value of a field in a document. To return the values of a multi-value field, see [getFieldValues](#), below.

### Syntax

```
getFieldValue( fieldname [, case])
```

### Arguments

Argument	Description
fieldname	(string) The name of the field to be retrieved.
case	(boolean) A boolean that specifies whether <code>fieldname</code> is case-sensitive. The argument is case sensitive by default ( <code>true</code> ).

### Returns

(String). A string containing the value.

## getFieldValues

The `getFieldValues` method gets all values from all fields that have the same name.

### Syntax

```
getFieldValues( fieldname [, case])
```

### Arguments

Argument	Description
fieldname	(string) The name of the field.
case	(boolean) A boolean that specifies whether <code>fieldname</code> is case-sensitive. The argument is case sensitive by default ( <code>true</code> ).

## Returns

(Strings). Strings that contain the values. To map the return values to a table, surround the function call with braces. For example:

```
fieldvalues = { document:getFieldValues( fieldname ) }
```

## getNextSection

The `getNextSection` method returns the next section of a document (if the document has been divided into sections).

The document object passed to the script's handler function represents the first section of the document. This means that the methods described in this section read and modify only the first section.

Calling `getNextSection` on the `LuaDocument` passed to the handler function will always return the second section. To perform operations on every section, see the example below.

When a document is divided into sections, each section has the same fields. The only difference between each section is the document content (the value of the `DRECONTENT` field).

## Syntax

```
getNextSection()
```

## Returns

(`LuaDocument`) A `LuaDocument` object that contains the next DRE section.

## Example

To perform operations on every section, use the following script.

```
local section = document
while section do
    -- Manipulate section
    section = section:getNextSection()
end
```

## getReference

The `getReference` method returns a string containing the reference (the value of the `DREREFERENCE` document field).

## Syntax

```
getReference()
```

## Returns

(String). A string containing the reference.

## getSection

The `getSection` method returns a `LuaDocument` object with the specified section as the active section.

## Syntax

```
getSection(number)
```

## Arguments

Argument	Description
number	(number) The document section for which you want to return a <code>LuaDocument</code> object.

## Returns

(`LuaDocument`). A `LuaDocument` object with the specified section as the active section.

## Example

```
-- Get object for section 7 of document  
local section = document:getSection(7)  
  
-- Get the content from the section  
local content = section:getContent()
```

## getSectionCount

The `getSectionCount` method returns the number of sections in a document.

## Syntax

```
getSectionCount()
```

## Returns

(Number). The number of sections.

## Example

```
local sectionCount = document:getSectionCount()
```

## getValueByPath

The `getValueByPath` method gets the value of a document field. The field is specified by its path, which means that you can get the value of a sub field. If you pass this method the path of a multi-value field, only the first value is returned. To return all of the values from a multi-value field, see [getValuesByPath](#), below.

## Syntax

```
getValueByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the field.

## Returns

(String). A string containing the value.

## Example

```
local value = document:getValueByPath("myfield")  
local subfieldvalue = document:getValueByPath("myfield/subfield")
```

## getValuesByPath

The `getValuesByPath` method gets all values of a document field. The field is specified by its path, which means that you can get values from a sub field.

## Syntax

```
getValuesByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the field.

## Returns

(Strings). Strings that contain the values. To map the return values to a table, surround the function call with braces. For example:

```
fieldvalues = { document:getValuesByPath("myfield/subfield") }
```

## hasField

The `hasField` method checks to see if a field exists in the current document.

## Syntax

```
hasField ( fieldname [, case] )
```

## Arguments

Argument	Description
fieldname	(string) The name of the field.
case	(boolean) A boolean that specifies whether the <code>fieldname</code> is case-sensitive. The field name is case-sensitive by default.

## Returns

(Boolean). True if the field exists, false otherwise.

## insertJson

The `insertJson` method inserts metadata from a JSON string, `LuaJsonObject`, or `LuaJsonArray`, into a document.

## Syntax

```
insertJson ( json [, fieldName] )
```

## Arguments

Argument	Description
json	(string or <a href="#">LuaJsonArray</a> or <a href="#">LuaJsonObject</a> ) The JSON to insert into the document.
fieldName	(string) The name of the metadata field to add the JSON to. This field is created if it does not exist. If you do not specify a field the JSON is added at the root of the document.

## Example

The following example Lua script uses the `insertJson` method to add metadata to a document:

```
function handler(document)
  local jsonString = [[
    {"email":"example@domain.com",
      "name":"A N Example",
      "address":
        {"address1":"New street",
          "city":"Cambridge",
          "country":"Great Britain"},
      "id":15}
  ]]

  document:insertJson( jsonString , "MyField")
  return true
end
```

When written to an IDX file, the resulting document looks like this:

```
#DREREFERENCE c:\test.html
#DREFIELD DREFILENAME="c:\test.html"
...
#DREFIELD MyField/address/address1="New street"
#DREFIELD MyField/address/city="Cambridge"
#DREFIELD MyField/address/country="Great Britain"
#DREFIELD MyField/email="example@domain.com"
#DREFIELD MyField/id="15"
#DREFIELD MyField/name="A N Example"
#DRECONTENT
Some content

#DREENDDOC
```

## insertXml

The `insertXml` method inserts XML metadata into the document.

## Syntax

```
insertXml ( node )
```

## Arguments

Argument	Description
node	(LuaXmlNode) The node to insert.

## Returns

(LuaField). A LuaField object of the inserted data.

## insertXmlWithoutRoot

The `insertXmlWithoutRoot` method inserts XML metadata into the document.

This method does not insert the top level node. All of the child nodes are inserted into the document. `insertXmlWithoutRoot(node)` is therefore equivalent to calling `insertXml()` for each child node.

## Syntax

```
insertXmlWithoutRoot ( node )
```

## Arguments

Argument	Description
node	(LuaXmlNode) The node to insert.

## LuaDocument:new

The constructor for a `LuaDocument` object (creates a new `LuaDocument` object that only contains a reference).

## Syntax

```
LuaDocument:new( reference )
```

## Arguments

Argument	Description
reference	(string) The reference to assign to the new document.

## Returns

(LuaDocument). The new LuaDocument object.

## Example

```
local reference = "my_reference"  
local document = LuaDocument:new(reference)
```

## removeSection

The `removeSection` method removes a section from a document.

## Syntax

```
removeSection( sectionNumber )
```

## Arguments

Argument	Description
sectionNumber	(number) A zero-based index that specifies the section to remove. For example, to remove the second section, set this argument to 1.

## Returns

Nothing.

## Example

```
-- Example that removes the last section of a document  
if document:getSectionCount() > 0 then  
    local lastSection = document:getSectionCount() - 1  
    document:removeSection( lastSection )  
end
```

## renameField

The `renameField` method changes the name of a field.

### Syntax

```
renameField( currentname, newname [, case])
```

### Arguments

Argument	Description
<code>currentname</code>	(string) The name of the field to rename.
<code>newname</code>	(string) The new name of the field.
<code>case</code>	(boolean) A boolean that specifies whether the <code>currentname</code> argument is case-sensitive. The argument is case sensitive by default ( <code>true</code> ).

## setContent

The `setContent` method sets the content (the value of the `DRECONTENT` field) for a document or document section.

### Syntax

```
setContent( content [, number] )
```

### Arguments

Argument	Description
<code>content</code>	(string) The content to set for the document or document section.
<code>number</code>	(number) The document section to modify. If you do not specify a number, the method modifies the active section. For the document object passed to the script's <code>handler</code> function, the active section is the first section (section 0). If you specify a number greater than the number of existing sections, additional empty sections are created.

### Examples

```
-- Set content for section 0  
document:setContent("content0")
```

```
-- Get document for section 1
local section = document:getNextSection()

-- Set content for section 1
section:setContent("content1")

-- Set content for section 7, and assign sections 2-6 to
-- empty string if non-existent
document:setContent("content7", 7)
```

## setFieldValue

The `setFieldValue` method sets the value of a field in a document. If the field does not exist, it is created. If the field already exists, the existing value is overwritten.

### Syntax

```
setFieldValue( fieldname, newvalue )
```

### Arguments

Argument	Description
fieldname	(string) The name of the field to set.
newvalue	(string) The value to set for the field.

## setReference

The `setReference` method sets the reference (the value of the `DRREFERENCE` document field) to the string passed in.

### Syntax

```
setReference( reference )
```

### Arguments

Argument	Description
reference	(string) The reference to set.

## **to\_idx**

The `to_idx` method returns a string containing the document in IDX format.

### **Syntax**

```
to_idx()
```

### **Returns**

(String). Returns the document as a string.

## **to\_json**

The `to_json` method returns a string containing the document in JSON format.

### **Syntax**

```
to_json()
```

### **Returns**

(String). Returns the document as a string.

## **to\_xml**

The `to_xml` method returns a string containing the document in XML format.

### **Syntax**

```
to_xml()
```

### **Returns**

(String). Returns the document as a string.

## **writeStubIdx**

The `writeStubIdx` method writes out a stub IDX document (a metadata file used by IDOL applications). The file is created in the current folder, but you can specify a full path and file name if you want to create the file in another folder.

## Syntax

```
writeStubIdx( filename )
```

## Arguments

Argument	Description
filename	(string) The name of the file to create.

## Returns

(Boolean). True if written, false otherwise.

## writeStubXml

The `writeStubXml` method writes out an XML file containing the metadata for the document. The file is created in the current folder but you can specify a full path and file name if you want to create the file in another folder.

## Syntax

```
writeStubXml( filename )
```

## Arguments

Argument	Description
filename	(String) The name of the file to create.

## Returns

(Boolean) True if successful, false otherwise.

## LuaField Methods

This section describes the methods provided by `LuaField` objects. A `LuaField` represents a single field in a document. You can retrieve `LuaField` objects for a document using the `LuaDocument` `getField` and `getFields` methods. In its simplest form a field has just a name and a value, but it can also contain sub-fields.

If you have a LuaField object called `field` you can call its methods using the `'.'` operator. For example:

```
field.addField(name, value)
```

Method	Description
<a href="#">addField</a>	Adds a sub field with the specified name and value.
<a href="#">copyField</a>	Copies the sub field to another sub field.
<a href="#">copyFieldNoOverwrite</a>	Copies the sub field to another sub field but does not overwrite the destination.
<a href="#">countField</a>	Returns the number of sub fields that exist with the specified name.
<a href="#">deleteAttribute</a>	Deletes the attribute with the specified name.
<a href="#">deleteField</a>	Deletes the sub field with the specified name.
<a href="#">getAttributeValue</a>	Gets the value of an attribute.
<a href="#">getField</a>	Gets the sub field specified by the name.
<a href="#">getFieldNames</a>	Returns the names of all sub fields of this field.
<a href="#">getFields</a>	Gets all the sub fields specified by the name.
<a href="#">getFieldValues</a>	Returns all the values of the sub field with the specified name.
<a href="#">getValueByPath</a>	Returns the value of a sub field with the specified path.
<a href="#">getValuesByPath</a>	Returns all the values of the sub field with the specified path.
<a href="#">hasAttribute</a>	Returns a Boolean specifying if the field has the specified attribute passed in by name.
<a href="#">hasField</a>	Returns a Boolean specifying if the sub field exists or not.
<a href="#">insertJson</a>	Inserts metadata from a JSON string, LuaJsonObject, or LuaJsonArray into the field.
<a href="#">insertXml</a>	Inserts XML metadata into a document.
<a href="#">insertXmlWithoutRoot</a>	Inserts XML metadata into a document.
<a href="#">name</a>	Returns the name of the field object in a string.
<a href="#">renameField</a>	Renames a sub field.
<a href="#">setAttributeValue</a>	Sets the value for the specified attribute of the field.
<a href="#">setValue</a>	Sets the value of the field.
<a href="#">value</a>	Returns the value of the field object.

## addField

The `addField` method adds a sub field with the specified name and value.

### Syntax

```
addField( fieldname, fieldvalue )
```

### Arguments

Argument	Description
fieldname	(string) The name of the field.
fieldvalue	(string) The value of the field.

## copyField

The `copyField` method copies a sub field to another sub field. If the target sub field exists it is overwritten.

### Syntax

```
copyField ( from, to [, case])
```

### Arguments

Argument	Description
from	(string) The name of the field to copy.
to	(string) The name of the field to copy to.
case	(boolean) A boolean that specifies whether the <code>from</code> argument is case sensitive. The argument is case sensitive by default ( <code>true</code> ).

## copyFieldNoOverwrite

The `copyFieldNoOverwrite` method copies the sub field to another sub field but does not overwrite the destination. After this operation the destination field contains all the values of the source field as well as any values it already had.

## Syntax

```
copyFieldNoOverwrite( from, to [, case])
```

## Arguments

Argument	Description
from	(string) The name of the field to copy.
to	(string) The name of the field to copy to.
case	(boolean) A boolean that specifies whether the from argument is case sensitive. The argument is case sensitive by default (true).

## countField

The countField method returns the number of sub fields that exist with the specified name.

## Syntax

```
countField ( fieldname [, case])
```

## Arguments

Argument	Description
fieldname	(string) The name of the field.
case	(boolean) A boolean that specifies whether the fieldname argument is case sensitive. The argument is case sensitive by default (true).

## Returns

(Number). The number of sub fields that exist with the specified name.

## deleteAttribute

The deleteAttribute method deletes the specified field attribute.

## Syntax

```
deleteAttribute( name )
```

## Arguments

Argument	Description
name	(string) The name of the attribute to delete.

## deleteField

The `deleteField` method deletes the sub field with the specified name.

## Syntax

```
deleteField( name [, case] )
```

```
deleteField( name , value [, case] )
```

## Arguments

Argument	Description
name	(string) The name of the sub field to delete.
value	(string) The value of the sub field. If this is specified a field is deleted only if it has the specified name and value. If this is not specified, all fields with the specified name are deleted.
case	(boolean) A boolean that specifies whether the <code>name</code> argument is case sensitive. The argument is case sensitive by default ( <code>true</code> ).

## getAttributeValue

The `getAttributeValue` method gets the value of the specified attribute.

## Syntax

```
getAttributeValue( name )
```

## Arguments

Argument	Description
name	(string) The name of the attribute.

## Returns

(String). The attribute value.

## getField

The `getField` method returns the specified sub field.

## Syntax

```
getField ( name [, case])
```

## Arguments

Argument	Description
name	(string) The name of the field to return.
case	(boolean) A boolean that specifies whether the <code>name</code> argument is case sensitive. The argument is case sensitive by default ( <code>true</code> ).

## Returns

(LuaField) A `LuaField` object.

## getFieldNames

The `getFieldNames` method returns the names of the sub fields in the `LuaField` object.

## Syntax

```
getFieldNames()
```

## Returns

(Strings). The names of the sub fields. The strings can be assigned to a table. To map the return values to a table, surround the function call with braces. For example:

```
fieldnames = { field:getFieldNames() }
```

## getFields

The `getFields` method returns all of the sub fields specified by the `name` argument.

## Syntax

```
getFields( name [, case] )
```

## Arguments

Argument	Description
name	(string) The name of the fields.
case	(boolean) A boolean that specifies whether the name argument is case sensitive. The argument is case sensitive by default (true).

## Returns

(LuaFields) One LuaField per matching field. The objects can be assigned to a table. To map the return values to a table, surround the function call with braces. For example:

```
fields = { field:getFields( name [, case] ) }
```

## getFieldValues

The getFieldValues method returns the values of all of the sub fields with the specified name.

## Syntax

```
getFieldValues( fieldname [, case] )
```

## Arguments

Argument	Description
fieldname	(string) The name of the field.
case	(boolean) A boolean that specifies whether the fieldname argument is case sensitive. The argument is case sensitive by default (true).

## Returns

(Strings) One string for each value. The strings can be assigned to a table. To map the return values to a table, surround the function call with braces. For example:

```
fieldvalues = { field:getFieldValues( fieldname ) }
```

## getValueByPath

The `getValueByPath` method gets the value of a sub-field, specified by path. If you pass this method the path of a sub-field that has multiple values, only the first value is returned. To return all of the values from a multi-value sub-field, see [getValuesByPath](#), below.

### Syntax

```
getValueByPath( path )
```

### Arguments

Argument	Description
path	(string) The path of the sub-field.

### Returns

(String). A string containing the value.

### Example

Consider the following document:

```
<DOCUMENT>  
  ...  
  <A_FIELD>  
    <subfield>  
      <anotherSubfield>the value to return</anotherSubfield>  
    </subfield>  
  </A_FIELD>  
  ...  
</DOCUMENT>
```

The following example demonstrates how to retrieve the value "the value to return" from the sub-field `anotherSubfield`, using a `LuaField` object representing `A_FIELD`:

```
local field = document:getField("A_FIELD")  
local value = field:getValueByPath("subfield/anotherSubfield")
```

## getValuesByPath

The `getValuesByPath` method gets the values of a sub-field, specified by path.

## Syntax

```
getValuesByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the sub-field.

## Returns

(Strings). Strings that contain the values. To map the return values to a table, surround the function call with braces. For example:

```
fieldvalues = { myfield:getValuesByPath("subfield/anotherfield") }
```

## Example

Consider the following document:

```
<DOCUMENT>
...
<A_FIELD>
  <subfield>
    <anotherfield>one</anotherfield>
    <anotherfield>two</anotherfield>
    <anotherfield>three</anotherfield>
  </subfield>
</A_FIELD>
...
</DOCUMENT>
```

The following example demonstrates how to retrieve the values "one", "two", and "three" from the sub-field anotherfield, using a LuaField object representing A\_FIELD:

```
local field = document:getField("A_FIELD")
local values = { field:getValuesByPath("subfield/anotherfield") }
```

## hasAttribute

The hasAttribute method returns a Boolean indicating whether the field has the specified attribute.

## Syntax

```
hasAttribute( name )
```

## Arguments

Argument	Description
name	(string) The name of the attribute.

## Returns

(Boolean). A Boolean specifying if the field has the specified attribute.

## hasField

The `hasField` method returns a Boolean specifying if the sub field exists.

## Syntax

```
hasField( fieldname [, case])
```

## Arguments

Argument	Description
fieldname	(string) The name of the field.
case	(boolean) A boolean that specifies whether the <code>fieldname</code> argument is case sensitive. The argument is case sensitive by default ( <code>true</code> ).

## Returns

(Boolean). A Boolean specifying if the sub field exists or not.

## insertJson

The `insertJson` method inserts metadata from a JSON string, `LuaJsonObject`, or `LuaJsonArray`, into the field.

## Syntax

```
insertJson ( json [, fieldName] )
```

## Arguments

Argument	Description
json	(string or <a href="#">LuaJsonArray</a> or <a href="#">LuaJsonObject</a> ) The JSON to insert into the field.
fieldName	(string) The name of a sub-field to add the JSON to. If you set this argument, a sub-field is created. If you do not set this argument, the JSON is added to the field that the method was called on.

## See Also

- [LuaDocument:insertJson](#)

## insertXml

The `insertXml` method inserts XML metadata into the document. When called on a `LuaField`, the `insertXml` method inserts the fields as children of the `LuaField`.

## Syntax

```
insertXml ( node )
```

## Arguments

Argument	Description
node	( <a href="#">LuaXmlNode</a> ) The node to insert.

## Returns

(`LuaField`). A `LuaField` object of the inserted data.

## insertXmlWithoutRoot

The `insertXmlWithoutRoot` method inserts XML metadata into the document.

This method does not insert the top level node. All of the child nodes are inserted into the document. `insertXmlWithoutRoot(node)` is therefore equivalent to calling `insertXml()` for each child node.

## Syntax

```
insertXmlWithoutRoot ( node )
```

## Arguments

Argument	Description
node	(LuaXmlNode) The node to insert.

## name

The `name` method returns the name of the field object.

## Syntax

```
name()
```

## Returns

(String). The name of the field object.

## renameField

The `renameField` method renames a sub field.

## Syntax

```
renameField( oldname, newname [, case] )
```

## Arguments

Argument	Description
oldname	(string) The previous name of the field.
newname	(string) The new name of the field.
case	(boolean) A boolean that specifies whether the <code>oldname</code> argument is case sensitive. The argument is case sensitive by default ( <code>true</code> ).

## setAttributeValue

The `setAttributeValue` method sets the value for the specified attribute of the field.

## Syntax

```
setAttributeValue( attribute, value )
```

## Arguments

Argument	Description
attribute	(string) The name of the attribute to set.
value	(string) The value to set.

## setValue

The setValue method sets the value of the field.

## Syntax

```
setValue( value )
```

## Arguments

Argument	Description
value	(string) The value to set.

## value

The value method returns the value of the field object.

## Syntax

```
value()
```

## Returns

(String). The value of the field object.

## LuaHttpRequest Methods

This section describes the methods provided by LuaHttpRequest objects.

If you have a `LuaHttpRequest` object called `request` you can call its methods using the ':' operator. For example:

```
request:send()
```

Constructor	Description
<code>LuaHttpRequest:new</code>	The constructor for a <code>LuaHttpRequest</code> object (creates a new <code>LuaHttpRequest</code> ).

Method	Description
<code>send</code>	Sends the HTTP request.
<code>set_body</code>	Sets the body of the HTTP request.
<code>set_config</code>	Specifies settings to use for sending the HTTP request.
<code>set_header</code>	Adds a header to the HTTP request.
<code>set_headers</code>	Replaces all headers in the HTTP request with new headers.
<code>set_method</code>	Specifies the HTTP request method to use when sending the request, for example GET or POST.
<code>set_url</code>	Sets the URL that you want to send the HTTP request to.

## LuaHttpRequest:new

The constructor for a `LuaHttpRequest` object (creates a new `LuaHttpRequest`).

### Syntax

```
LuaHttpRequest:new( config, section )
```

### Arguments

Argument	Description
<code>config</code>	( <code>LuaConfig</code> ) The <code>LuaConfig</code> object that contains the settings for sending the HTTP request. To obtain a <code>LuaConfig</code> object, see the function <a href="#">get_config, on page 119</a> or <a href="#">LuaConfig:new, on page 148</a> .
<code>section</code>	(string) The name of the configuration section from which to read the settings.

### Returns

(`LuaHttpRequest`). The new `LuaHttpRequest` object.

## Example

The following example creates a new `LuaHttpRequest` object by reading configuration settings from a string that is defined in the script:

```
local config_string = [=[  
[HTTP]  
ProxyHost=proxy.domain.com  
ProxyPort=8080  
SSLMethod=NEGOTIATE  
]=]=]

local config = LuaConfig:new(config_string)
local request = LuaHttpRequest:new(config, "HTTP")
```

## send

The `send` method sends the HTTP request.

## Syntax

```
send()
```

## Returns

(`LuaHttpResponse`). A [LuaHttpResponse](#) object.

## set\_body

The `set_body` method sets the body of the HTTP request.

## Syntax

```
set_body( body )
```

## Arguments

Argument	Description
body	(string or nil) The body of the HTTP request.

## set\_config

The `set_config` method specifies settings to use for sending the HTTP request (in the form of a section from a configuration file). For example, you can specify the proxy server to use by setting the parameters `ProxyHost` and `ProxyPort`, or specify the SSL version to use by setting `SSLMethod`.

### Syntax

```
set_config( config, section )
```

### Arguments

Argument	Description
<code>config</code>	(LuaConfig) The LuaConfig object that contains the settings for sending the HTTP request. To obtain a LuaConfig object, see the function <a href="#">get_config, on page 119</a> or <a href="#">LuaConfig:new, on page 148</a> .
<code>section</code>	(string) The name of the configuration section from which to read the settings.

### Example

The following example creates a new `LuaConfig` object from a string. Usually you would read the configuration settings from the configuration file using the function [get\\_config, on page 119](#). It then uses the `LuaConfig` object to provide settings for a `LuaHttpRequest` named `request`.

```
local config_string = [=[  
[HTTP]  
ProxyHost=proxy.domain.com  
ProxyPort=8080  
SSLMethod=NEGOTIATE  
]=]=]

local config = LuaConfig:new(config_string)
request:set_config(config, "HTTP")
```

## set\_header

The `set_header` method adds a header to the HTTP request.

### Syntax

```
set_header( name, value )
```

## Arguments

Argument	Description
name	(string) The name of the HTTP header to add to the request.
value	(string or nil) The value of the HTTP header to add to the request.

## Example

```
request:set_header("X-EXAMPLE", "Example")
```

## set\_headers

The `set_headers` method replaces all headers in the HTTP request with new headers. To add a header without changing existing headers, use the method [set\\_header](#).

## Syntax

```
set_headers( headers )
```

## Arguments

Argument	Description
headers	(table) The new HTTP headers to add to the request. The table must map header names to values.

## Example

```
request:set_headers( {X-EXAMPLE="Example", X-ANOTHER="ANOTHER"} )
```

## set\_method

Specifies the HTTP request method to use when sending the request, for example GET or POST.

## Syntax

```
set_method( method )
```

## Arguments

Argument	Description
method	(string) The HTTP request method to use.

## Example

```
request:set_method("POST")
```

## set\_url

The `set_url` method sets the URL that you want to send the HTTP request to.

## Syntax

```
set_url( url )
```

## Arguments

Argument	Description
url	(string) The URL to send the request to.

## Example

```
request:set_url("https://www.example.com/")
```

## LuaHttpResponse Methods

This section describes the methods provided by `LuaHttpResponse` objects. A `LuaHttpResponse` object is provided when you send an HTTP request using the `send` method on a `LuaHttpRequest` object.

If you have a `LuaHttpResponse` object called `response` you can call its methods using the `'.'` operator. For example:

```
response:get_http_code()
```

Method	Description
<code>get_body</code>	Returns the body of the HTTP response.

Method	Description
<code>get_header</code>	Returns the value of the specified HTTP header.
<code>get_headers</code>	Returns the value of all HTTP headers in the response.
<code>get_http_code</code>	Returns the HTTP response code.

## get\_body

The `get_body` method returns the body of the HTTP response.

### Syntax

```
get_body()
```

### Returns

(String). The body of the HTTP response.

## get\_header

The `get_header` method returns the value of a specified HTTP header.

### Syntax

```
get_header( name )
```

### Arguments

Argument	Description
<code>name</code>	(string) The name of the HTTP header for which you want to get the value.

### Returns

(String). The value of the header.

## get\_headers

The `get_headers` method returns the names and values of all of the headers in the HTTP response.

## Syntax

```
get_headers()
```

## Returns

(table) A table that maps header names to values.

## Example

The following example sends an HTTP request and then prints the headers that are returned to the console:

```
local response = request:send()  
for k,v in pairs(response:get_headers()) do  
    print("HEADER:",k,v)  
end
```

## get\_http\_code

The `get_http_code` method returns the HTTP response code for the request.

## Syntax

```
get_http_code()
```

## Returns

(number). The response code, for example 200 for success, or 404 for not found.

## LuaJsonArray Methods

A `LuaJsonArray` object represents a JSON array.

If you have a `LuaJsonArray` object called `myJsonArray` you can call its methods using the `':'` operator. For example:

```
myJsonArray:size()
```

Constructor	Description
<a href="#">LuaJsonArray:new</a>	The constructor for a <code>LuaJsonArray</code> object (creates a new <code>LuaJsonArray</code> ).

Method	Description
<a href="#">append</a>	Appends a value to the array.
<a href="#">clear</a>	Clears the array, so that it contains no values.
<a href="#">copy</a>	Copies the array.
<a href="#">empty</a>	Checks whether the array is empty.
<a href="#">exists</a>	Checks whether a specified path exists in the array.
<a href="#">existsByPath</a>	Checks whether a specified path exists in the array.
<a href="#">ipairs</a>	Returns an iterator function that you can use to iterate over all of the values in the array.
<a href="#">lookup</a>	Returns the value at a specified path in the array.
<a href="#">lookupByPath</a>	Returns the value at a specified path in the array.
<a href="#">size</a>	Returns the size of the array.
<a href="#">string</a>	Returns the array as a string.

## LuaJsonArray:new

The constructor for a LuaJsonArray object (creates a new LuaJsonArray).

### Syntax

```
LuaJsonArray:new( values )
```

### Arguments

Argument	Description
values	(lua_json_type) The values to add to the array. Each value can be a Boolean, float, integer, string, <a href="#">LuaJsonArray</a> , <a href="#">LuaJsonObject</a> , <a href="#">LuaJsonValue</a> , or nil.

### Returns

(LuaJsonArray). The new LuaJsonArray object.

### Example

The following is a simple JSON array:

```
[4, "a string", true]
```

To create a `LuaJSONArray` object to represent this array:

```
local myJSONArray = LuaJSONArray:new(4,"a string",true)
```

## append

The `append` method appends a value to the JSON array.

### Syntax

```
append( value )
```

### Arguments

Argument	Description
value	(lua_json_type) The value to append to the array. This can be a Boolean, float, integer, string, <a href="#">LuaJSONArray</a> , <a href="#">LuaJsonObject</a> , <a href="#">LuaJsonValue</a> , or nil.

### Example

```
local myJSONArray = LuaJSONArray:new(4,"a string",true)
myJSONArray:append(6)
-- the array is now [4, "a string", true, 6]
```

## clear

The `clear` method clears the array, so that it contains no values.

### Syntax

```
clear()
```

### Example

```
local myJSONArray = LuaJSONArray:new(4,"a string",true)
myJSONArray:clear()
print (myJSONArray:string())
-- []
```

## copy

The `copy` method returns a copy of the array. Modifying the copy does not modify the original array.

## Syntax

```
copy()
```

## Returns

(LuaJsonArray). A copy of the array.

## Example

```
local myJsonArray = LuaJsonArray:new(4,"a string",true)
local anotherJsonArray = myJsonArray:copy()
print (anotherJsonArray:string())
-- [4, "a string", true]
```

## empty

The `empty` method checks whether the JSON array is empty.

## Syntax

```
empty()
```

## Returns

(Boolean). Returns `true` if the array is empty.

## Example

```
local myJsonArray = LuaJsonArray:new(4,"a string",true)

print ("Is the array empty? " , myJsonArray:empty() )
-- Is the array empty?  false

myJsonArray:clear()

print ("Is the array empty? " , myJsonArray:empty() )
-- Is the array empty?  true
```

## exists

The `exists` method checks whether a specified path exists in the JSON array.

## Syntax

```
exists( pathElements )
```

## Arguments

Argument	Description
pathElements	(json_path_string_or_integer) The path to check. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(Boolean) Returns true if the path exists, false otherwise.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )
local myJsonArray = LuaJsonArray:new("zero", 1, 2, myJsonObject)

print (myJsonArray:exists(0))
-- true (LuaJsonArrays are zero-indexed)

print (myJsonArray:exists(4))
-- false (LuaJsonArrays are zero-indexed, and there is no fifth value)

print (myJsonArray:exists(3, "product"))
-- true
```

## See Also

- [existsByPath](#), below

## existsByPath

The existsByPath method checks whether a specified path exists in the JSON array.

## Syntax

```
existsByPath( path )
```

## Arguments

Argument	Description
path	(string) The path to check. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(Boolean) Returns true if the path exists, false otherwise.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )
local myJsonArray = LuaJsonArray:new("zero",1,2,myJsonObject)

print (myJsonArray:existsByPath("3/product"))
-- true (LuaJsonArrays are zero-indexed)
```

## See Also

- [exists, on page 189](#)

## ipairs

The `ipairs` method returns a function that you can use with a for loop to iterate over all of the values in the array.

## Syntax

```
ipairs()
```

## Example

```
local myJsonArray = LuaJsonArray:new(4,"a string",true)

for i, v in myJsonArray:ipairs() do
  print (v:string())
end

-- prints the following...
```

```
-- 4  
-- a string  
-- true
```

## lookup

The lookup method returns the value at the specified path in the JSON array.

**NOTE:**

This method does not make a copy of the value, so modifying the returned value affects the original array.

## Syntax

```
lookup( pathElements )
```

## Arguments

Argument	Description
pathElements	(json_path_string_or_integer) The path of the value to return. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(LuaJsonValue) Returns the value that exists at the specified path, or nil if the specified path does not exist.

## Example

The following example demonstrates how to obtain a value:

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
local myJsonArray = LuaJsonArray:new(0, 1, 2, myJsonObject)  
local myValue = myJsonArray:lookup(3, "product")  
print (myValue:value())  
-- IDOL
```

The following example demonstrates how modifying a returned value affects the original array:

```
local myJsonObject = LuaJsonObject:new()  
myJsonObject:assign("name", LuaJsonArray:new("value1"))  
  
local myJsonArray = myJsonObject:lookup("name"):array()  
myJsonArray:append("value2")
```

```
print (myJsonObject:string())  
-- {"name":["value1","value2"]}
```

## See Also

- [lookupByPath](#), below

## lookupByPath

The `lookupByPath` method returns the value at the specified path in the JSON array.

### NOTE:

This method does not make a copy of the value, so modifying the returned value affects the original array.

## Syntax

```
lookupByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the value to return. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(LuaJsonValue) Returns the value that exists at the specified path, or `nil` if the specified path does not exist.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
local myJsonArray = LuaJsonArray:new("zero",1,2,myJsonObject)  
  
local myValue = myJsonArray:lookupByPath("3/product")  
print (myValue:value())  
-- IDOL
```

## See Also

- [lookup, on page 192](#)

## size

The `size` method returns the size of the JSON array.

## Syntax

```
size()
```

## Returns

(integer). The number of values in the array.

## Example

```
local myJsonArray = LuaJsonArray:new(4,"a string",true)
print ("Array size is " , myJsonArray:size() )
-- Array size is 3
```

## string

The `string` method returns the JSON array as a string.

## Syntax

```
string()
```

## Returns

(String). The array as a string.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )
local myJsonArray = LuaJsonArray:new("zero",1,2,myJsonObject)

print (myJsonArray:string())
-- ["zero",1,2,{"product":"IDOL","version":11}]
```

## LuaJsonObject Methods

A `LuaJsonObject` object represents a JSON object.

If you have a `LuaJsonObject` object called `object` you can call its methods using the `'.'` operator. For example:

```
object:size()
```

Constructor	Description
<code>LuaJsonObject:new</code>	The constructor for a <code>LuaJsonObject</code> object (creates a new <code>LuaJsonObject</code> ).
Method	Description
<code>assign</code>	Adds an attribute (a name/value pair) to the object.
<code>assign</code>	Adds a table of attributes (name/value pairs) to the object.
<code>clear</code>	Clears the object, so that it contains no attributes.
<code>copy</code>	Copies the object.
<code>empty</code>	Checks whether the object is empty.
<code>erase</code>	Removes a specified attribute (name/value pair) from the object.
<code>exists</code>	Checks whether a specified path exists in the object.
<code>existsByPath</code>	Checks whether a specified path exists in the object.
<code>lookup</code>	Returns the value at a specified path in the object.
<code>lookupByPath</code>	Returns the value at a specified path in the object.
<code>pairs</code>	Returns an iterator function that you can use to iterate over all of the attributes in the object.
<code>size</code>	Returns the number of attributes (name/value pairs) contained in the object.
<code>string</code>	Returns the object as a string.

### LuaJsonObject:new

The constructor for a `LuaJsonObject` object (creates a new `LuaJsonObject`).

If you do not specify any attributes to assign to the object (by omitting the `attributes` argument), an empty object is created.

## Syntax

```
LuaJsonObject:new( [attributes] )
```

## Arguments

Argument	Description
attributes	<p>(lua_json_object_type) A table of attributes (name/value pairs) to assign to the object. The keys in the table must be strings which specify the names of the attributes. Each value can be a Boolean, float, integer, string, <a href="#">LuaJsonObject</a>, <a href="#">LuaJsonArray</a>, <a href="#">LuaJsonValue</a>, or nil.</p> <p><b>TIP:</b> In Lua, keys in a table cannot be assigned the value of nil. If you want to have a null value (nil in Lua), you can do the following:</p> <pre>LuaJsonObject:new( { key=LuaJsonValue:new(nil) } ).</pre>

## Returns

(LuaJsonObject). The new LuaJsonObject object.

## Example

The following is a simple JSON object:

```
{"product":"IDOL","version":11}
```

To create a LuaJsonObject object to represent this JSON object:

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )
```

## assign

The assign method adds an attribute (a name/value pair) to the object.

## Syntax

```
assign (name, value)
```

## Arguments

Argument	Description
name	(string) The name of the attribute to add.
value	(lua_json_type) The value of the attribute to add. This can be a Boolean, float, integer, string, <a href="#">LuaJsonArray</a> , <a href="#">LuaJsonObject</a> , <a href="#">LuaJsonValue</a> , or nil.

## Example

```
local myJsonObject = LuaJsonObject:new( { name1="value1" , name2="value2" } )  
myJsonObject:assign("name3", "value3")  
myJsonObject:assign("name4", LuaJsonArray:new("value4a","value4b") )
```

## assign

The `assign` method adds a table of attributes (name/value pairs) to the object.

## Syntax

```
assign (attributes)
```

## Arguments

Argument	Description
attributes	(lua_json_object_type) The table of attributes to add. The keys in the table must be strings which specify the names of the attributes to add. Each value can be a Boolean, float, integer, string, <a href="#">LuaJsonArray</a> , <a href="#">LuaJsonObject</a> , <a href="#">LuaJsonValue</a> , or nil.  <b>TIP:</b> In Lua, keys in a table cannot be assigned the value of <code>nil</code> . If you want to have a null value ( <code>nil</code> in Lua), you can do the following:  <code>myJsonObject:assign( { key=LuaJsonValue:new(nil) } ).</code>

## Example

```
local myJsonObject = LuaJsonObject:new()  
myJsonObject:assign( {  
    attr1=LuaJsonObject:new( { n=42 } ),  
    attr2=LuaJsonArray:new( 1, 2, "three" ),  
    attr3=true
```

```
    } )  
print(myJsonObject:string())  
-- {"attr1":{"n":42},"attr2":[1,2,"three"],"attr3":true}
```

## clear

The `clear` method clears the object, so that it contains no attributes (name/value pairs).

## Syntax

```
clear()
```

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
myJsonObject:clear()  
print (myJsonObject:string())  
-- {}
```

## copy

The `copy` method returns a copy of the JSON object. Modifying the copy does not modify the original object.

## Syntax

```
copy()
```

## Returns

(LuaJsonObject). A copy of the object.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
local anotherJsonObject = myJsonObject:copy()  
  
print (anotherJsonObject:string())  
-- {"product":"IDOL","version":11}
```

## empty

The `empty` method determines whether the JSON object is empty.

## Syntax

```
empty()
```

## Returns

(Boolean). Returns true if the object has no attributes (name/value pairs).

## Example

```
local myJsonObject = LuaJsonObject:new()  
print(myJsonObject:empty())  
-- true
```

## erase

The erase method removes a specified attribute (name/value pair) from the JSON object.

## Syntax

```
erase( name )
```

## Arguments

Argument	Description
name	(string) The name of the attribute to erase.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
myJsonObject:erase("version")  
print (myJsonObject:string())  
-- {"product":"IDOL"}
```

## exists

The exists method checks whether a specified path exists in the JSON object.

## Syntax

```
exists( pathElements )
```

## Arguments

Argument	Description
pathElements	(json_path_string_or_integer) The path to check. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(Boolean) Returns `true` if the path exists, `false` otherwise.

## Example

Consider the following JSON:

```
{
  "product": "IDOL",
  "component": "CFS",
  "version": { "major": 11, "minor": 3 },
  "ports": [
    { "type": "ACI", "number": 7000 },
    { "type": "Service", "number": 17000 }
  ]
}
```

If this JSON is represented by an object named `myJsonObject`, you could use the `exists` method as follows:

```
print (myJsonObject:exists("ports",0,"type"))
-- true (LuaJsonArrays are zero-indexed)

print (myJsonObject:exists("ports",2,"type"))
-- false (LuaJsonArrays are zero-indexed, and there is no third value)

print (myJsonObject:exists("version", "major"))
-- true
```

## See Also

- [existsByPath](#), below

## existsByPath

The `existsByPath` method checks whether a specified path exists in the JSON object.

## Syntax

```
existsByPath( path )
```

## Arguments

Argument	Description
path	(string) The path to check. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(Boolean) Returns true if the path exists, false otherwise.

## Example

Consider the following JSON:

```
{  
  "product": "IDOL",  
  "component": "CFS",  
  "version": { "major": 11, "minor": 3 },  
  "ports": [  
    { "type": "ACI", "number": 7000 },  
    { "type": "Service", "number": 17000 }  
  ]  
}
```

If this JSON is represented by an object named `myJsonObject`, you could use the `existsByPath` method as follows:

```
print (myJsonObject:existsByPath("ports/0/type"))  
-- true (LuaJsonArrays are zero-indexed)  
  
print (myJsonObject:existsByPath("ports/2/type" ) )  
-- false (LuaJsonArrays are zero-indexed, and there is no third value)  
  
print (myJsonObject:existsByPath("version/major"))  
-- true
```

## See Also

- [exists, on page 199](#)

## lookup

The `lookup` method returns the value at the specified path in the JSON object.

**NOTE:**

This method does not make a copy of the value, so modifying the returned value affects the original object.

## Syntax

```
lookup( pathElements )
```

## Arguments

Argument	Description
<code>pathElements</code>	( <code>json_path_string_or_integer</code> ) The path of the value to return. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(`LuaJsonValue`) Returns the value that exists at the specified path, or `nil` if the specified path does not exist.

## Example

```
myJsonObject = LuaJsonObject:new()
myJsonObject:assign( {
    attr1=LuaJsonObject:new( { n=42, x=5 } ),
    attr2=LuaJsonArray:new( 1, 2, "three" ),
} )

print ( myJsonObject:lookup("attr2",2):value() )
-- three (LuaJsonArrays are zero-indexed)

-- Modifying the returned value changes the original object
local lookup_attr = myJsonObject:lookup("attr1"):object()
lookup_attr:assign("y",3)
print (myJsonObject:string())
-- {"attr1":{"n":42,"x":5,"y":3},"attr2":[1,2,"three"]}
```

## See Also

- [lookupByPath](#), below

## lookupByPath

The `lookupByPath` method returns the value at the specified path in the JSON object.

**NOTE:**

This method does not make a copy of the value, so modifying the returned value affects the original object.

## Syntax

```
lookupByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the value to return. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(LuaJsonValue) Returns the value that exists at the specified path, or `nil` if the specified path does not exist.

## Example

```
myJsonObject = LuaJsonObject:new()
myJsonObject:assign( {
    attr1=LuaJsonObject:new( { n=42, x=5 } ),
    attr2=LuaJsonArray:new( 1, 2, "three" ),
} )

print ( myJsonObject:lookupByPath("attr2/2"):value() )
-- three (LuaJsonArrays are zero-indexed)

-- Modifying the returned value changes the original object
local lookup_attr = myJsonObject:lookupByPath("attr1"):object()
lookup_attr:assign("y",3)
```

```
print (myJsonObject:string())  
-- {"attr1":{"n":42,"x":5,"y":3},"attr2":[1,2,"three"]}
```

## See Also

- [lookup, on page 202](#)

## pairs

The `pairs` method returns an iterator function that you can use with a `for` loop to iterate over all of the attributes contained in the JSON object.

## Syntax

```
pairs()
```

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
  
for i, v in myJsonObject:pairs() do  
  print (i .. '=' .. v:string())  
end  
  
-- prints the following...  
-- product=IDOL  
-- version=11
```

## size

The `size` method returns the number of attributes (name/value pairs) in the JSON object.

## Syntax

```
size()
```

## Returns

(Number). The number of attributes in the JSON object.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
print (myJsonObject:size())  
-- 2
```

## string

The `string` method returns the JSON object as a string.

## Syntax

```
string()
```

## Returns

(String). The JSON object as a string.

## Example

```
local myJsonObject = LuaJsonObject:new( { product="IDOL" , version=11 } )  
print (myJsonObject:string())  
-- {"product":"IDOL","version":11}
```

## LuaJsonValue Methods

A `LuaJsonValue` object represents a JSON value.

If you have a `LuaJsonValue` object called `myJsonValue` you can call its methods using the `':'` operator. For example:

```
myJsonValue:is_object()
```

Constructor	Description
<code>LuaJsonValue:new</code>	The constructor for a <code>LuaJsonValue</code> object (creates a new <code>LuaJsonValue</code> ).

Method	Description
<code>array</code>	Gets a <code>LuaJsonArray</code> that represents the JSON array, if the value is an array.
<code>copy</code>	Copies the value.

Method	Description
<code>exists</code>	Checks whether a specified path exists in the value (when the value is a JSON array or object).
<code>existsByPath</code>	Checks whether a specified path exists in the value (when the value is a JSON array or object).
<code>is_array</code>	Returns whether the value is a JSON array.
<code>is_boolean</code>	Returns whether the value is a Boolean value.
<code>is_float</code>	Returns whether the value is a floating point value.
<code>is_integer</code>	Returns whether the value is an integer value.
<code>is_null</code>	Returns whether the value is a null value.
<code>is_number</code>	Returns whether the value is a number.
<code>is_object</code>	Returns whether the value is a JSON object.
<code>is_simple_value</code>	Returns whether the value is a simple value (Boolean, float, integer, or string).
<code>is_string</code>	Returns whether the value is a string value.
<code>lookup</code>	Returns the value at a specified path (when the value is a JSON array or object).
<code>lookupByPath</code>	Returns the value at a specified path (when the value is a JSON array or object).
<code>object</code>	Gets a <code>LuaJsonObject</code> that represents the JSON object, if the value is an object.
<code>string</code>	Returns the value as a string.
<code>value</code>	Returns the value, if the JSON value is a simple type. If you specify a default value and the value cannot be converted to the same type as the default, the default value is returned.

## LuaJsonValue:new

The constructor for a `LuaJsonValue` object (creates a new `LuaJsonValue`).

### Syntax

```
LuaJsonValue:new( value )
```

## Arguments

Argument	Description
value	(lua_json_type) The initial value. This can be a Boolean, float, integer, string, <a href="#">LuaJSONArray</a> , <a href="#">LuaJsonObject</a> , <a href="#">LuaJsonValue</a> , or nil.

## Returns

(LuaJsonValue). The new [LuaJsonValue](#) object.

## array

The array method gets the array, if the value is a JSON array.

## Syntax

```
array()
```

## Returns

(LuaJSONArray). A [LuaJSONArray](#) object that represents the array.

## Example

```
local fh = io.open("example_array.json", "r")
local file_content = fh:read("*all")
fh:close()
```

```
local myJsonValue = parse_json(file_content)
```

```
if myJsonValue:is_array() then
    print "The value is a JSON array"
    local myJSONArray=myJsonValue:array()
    print (myJSONArray:string())
end
```

## copy

The copy method returns a copy of the value. Modifying the copy does not affect the original value.

## Syntax

```
copy()
```

## Returns

(LuaJsonValue). A copy of the value.

## exists

The `exists` method checks whether a specified path exists in the JSON value.

## Syntax

```
exists( pathElements )
```

## Arguments

Argument	Description
<code>pathElements</code>	( <code>json_path_string_or_integer</code> ) The path to check. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(Boolean) Returns `true` if the path exists, `false` otherwise.

## Example

Consider the following JSON:

```
{  
  "product": "IDOL",  
  "component": "CFS",  
  "version": { "major": 11, "minor": 3 },  
  "ports": [  
    { "type": "ACI", "number": 7000 },  
    { "type": "Service", "number": 17000 }  
  ]  
}
```

If this JSON is represented by a `LuaJsonValue` object named `myJsonValue`, you could use the `exists` method as follows:

```
print (myJsonValue:exists("ports",0,"type"))  
-- true (LuaJsonArrays are zero-indexed)  
  
print (myJsonValue:exists("ports",2,"type"))  
-- false (LuaJsonArrays are zero-indexed, and there is no third value)  
  
print (myJsonValue:exists("version", "major"))  
-- true
```

## See Also

- [existsByPath, below](#)

## existsByPath

The `existsByPath` method checks whether a specified path exists in the JSON value.

## Syntax

```
existsByPath( path )
```

## Arguments

Argument	Description
path	(string) The path to check. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(Boolean) Returns `true` if the path exists, `false` otherwise.

## Example

Consider the following JSON:

```
{  
  "product": "IDOL",  
  "component": "CFS",  
  "version": { "major": 11, "minor": 3 },  
  "ports": [  
    { "type": "ACI", "number": 7000 },  
    { "type": "Service", "number": 17000 }  
  ]  
}
```

```
    ]  
  }
```

If this JSON is represented by a `LuaJsonValue` object named `myJsonValue`, you could use the `existsByPath` method as follows:

```
print (myJsonValue:existsByPath("ports/0/type"))  
-- true (LuaJsonArrays are zero-indexed)  
  
print (myJsonValue:existsByPath("ports/2/type") )  
-- false (LuaJsonArrays are zero-indexed, and there is no third value)  
  
print (myJsonValue:existsByPath("version/major"))  
-- true
```

## See Also

- [exists, on page 208](#)

## is\_array

The `is_array` method whether the value is a JSON array.

### Syntax

```
is_array()
```

### Returns

(Boolean). Returns `true` if the value is an array value, `false` otherwise.

## is\_boolean

The `is_boolean` method returns whether the value is a Boolean value.

### Syntax

```
is_boolean()
```

### Returns

(Boolean). Returns `true` if the value is a Boolean value, `false` otherwise.

## **is\_float**

The `is_float` method returns whether the value is a floating point value.

### **Syntax**

```
is_float()
```

### **Returns**

(Boolean). Returns `true` if the value is a floating point value, `false` otherwise.

## **is\_integer**

The `is_integer` method returns whether the value is an integral value.

### **Syntax**

```
is_integer()
```

### **Returns**

(Boolean). Returns `true` if the value is an integer value, `false` otherwise.

## **is\_null**

The `is_null` method returns whether the value is a null value.

### **Syntax**

```
is_null()
```

### **Returns**

(Boolean). Returns `true` if the value is a null value, `false` otherwise.

## **is\_number**

The `is_number` method returns whether the value is a number.

## Syntax

```
is_number()
```

## Returns

(Boolean). Returns `true` if the value is a number, `false` otherwise.

## is\_object

The `is_object` method returns whether the value is a JSON object.

## Syntax

```
is_object()
```

## Returns

(Boolean). Returns `true` if the value is a JSON object, `false` otherwise.

## is\_simple\_value

The `is_simple_value` method returns whether the value is a simple value (Boolean, float, integer, or string).

## Syntax

```
is_simple_value()
```

## Returns

(Boolean). Returns `true` if the value is a simple value, `false` otherwise.

## is\_string

The `is_string` method returns whether the value is a string value.

## Syntax

```
is_string()
```

## Returns

(Boolean). Returns `true` if the value is a string value, `false` otherwise.

## lookup

The `lookup` method returns the value at the specified path in the JSON value.

### NOTE:

This method does not make a copy of the value, so modifying the returned value affects the original object.

## Syntax

```
lookup( pathElements )
```

## Arguments

Argument	Description
<code>pathElements</code>	( <code>json_path_string_or_integer</code> ) The path of the value to return. Specify one or more path elements, which might be object attribute names (strings) or array indexes (integers).

## Returns

(`LuaJsonValue`) Returns the value that exists at the specified path, or `nil` if the specified path does not exist.

## Example

```
local myJsonObject = LuaJsonObject:new()
myJsonObject:assign( {
    attr1=LuaJsonObject:new( { n=42, x=5 } ),
    attr2=LuaJsonArray:new( 1, 2, "three" ),
} )

local myJsonValue = LuaJsonValue:new( myJsonObject )

print ( myJsonValue:lookup("attr2",2):value() )
-- three (LuaJsonArrays are zero-indexed)

-- Modifying the returned value changes the original object
local lookup = myJsonValue:lookup("attr1"):object()
```

```
lookup:assign("y",3)
print (myJsonValue:string())
-- {"attr1":{"n":42,"x":5,"y":3},"attr2":[1,2,"three"]}
```

## See Also

- [lookupByPath](#), below

## lookupByPath

The `lookupByPath` method returns the value at the specified path in the JSON array.

### NOTE:

This method does not make a copy of the value, so modifying the returned value affects the original object.

## Syntax

```
lookupByPath( path )
```

## Arguments

Argument	Description
path	(string) The path of the value to return. Construct the path from array indexes and object attribute names, and use a slash (/) as the separator. If an object attribute name includes a slash, then escape the slash with a backslash, for example "one\\/two". Notice that you must also escape a backslash with another backslash.

## Returns

(LuaJsonValue) Returns the value that exists at the specified path, or `nil` if the specified path does not exist.

## Example

```
local myJsonObject = LuaJsonObject:new()
myJsonObject:assign( {
    attr1=LuaJsonObject:new( { n=42, x=5 } ),
    attr2=LuaJsonArray:new( 1, 2, "three" ),
} )

local myJsonValue = LuaJsonValue:new( myJsonObject )
```

```
print ( myJsonValue:lookupByPath("attr2/2"):value() )
-- three (LuaJsonArrays are zero-indexed)

-- Modifying the returned value changes the original object
local lookup = myJsonValue:lookupByPath("attr1"):object()
lookup:assign("y",3)
print (myJsonValue:string())
-- {"attr1":{"n":42,"x":5,"y":3},"attr2":[1,2,"three"]}
```

## See Also

- [lookup, on page 213](#)

## object

The object method gets the object, if the value is a JSON object.

## Syntax

```
object()
```

## Returns

(LuaJsonObject) A [LuaJsonObject](#) object that represents the JSON object.

## Example

```
local fh = io.open("example_json.json", "r")
local file_content = fh:read("*all")
fh:close()

local myJsonValue = parse_json(file_content)

if myJsonValue:is_object() then
    print "The value is a JSON object"
    local myJsonObject=myJsonValue:object()
    print (myJsonObject:string())
end
```

## string

The string method returns the JSON value as a string.

## Syntax

```
string()
```

## Returns

(String). The JSON value as a string.

## Example

```
local fh = io.open("example_json.json", "r")
local file_content = fh:read("*all")
fh:close()

local myJsonValue = parse_json(file_content)

print(myJsonValue:string())
```

## value

The `value` method gets the value, if the JSON value is a simple type (a Boolean, float, integer, or string). This method returns a default value if one is specified and the value cannot be converted to the same type as the default.

## Syntax

```
value( [default] )
```

## Arguments

Argument	Description
default	(lua_json_simple_type) The default value to return, if the value cannot be converted to the same type as the default. You can specify a Boolean, float, integer, string, or nil.

## Returns

(lua\_json\_simple\_type). A Boolean, float, integer, string, or nil.

## LuaLog Methods

A LuaLog object provides the capability to use a log stream. You can obtain a LuaLog object for a log stream by using the function [get\\_log](#).

If you have a LuaLog object called `log` you can call its methods using the ':' operator. For example:

```
log:write_line(level, message)
```

Method	Description
<a href="#">write_line</a>	Write a message to the log stream.

### write\_line

The `write_line` method writes a message to the log stream.

### Syntax

```
write_line( level, message )
```

### Arguments

Argument	Description
level	The log level for the message. The message only appears in the log if the log level specified here is the same as, or higher than, the log level set for the log stream. To obtain the correct value for the log level, use one of the following functions: <ul style="list-style-type: none"><li><code>log_level_always()</code></li><li><code>log_level_error()</code></li><li><code>log_level_warning()</code></li><li><code>log_level_normal()</code></li><li><code>log_level_full()</code></li></ul>
message	(string) The message to write to the log stream.

### Example

```
local config = get_config("connector.cfg")  
local log = get_log(config, "SynchronizeLogStream")  
log:write_line( log_level_error() , "This message is written to the synchronize  
log")
```

## LuaLogService Methods

A `LuaLogService` object provides the capability to write messages to a standard or custom log file.

If you have a `LuaLogService` object called `myLogService` you can call its methods using the `'.'` operator. For example:

```
myLogService:get_log("application")
```

Constructor	Description
<code>LuaLogService:new</code>	The constructor for a <code>LuaLogService</code> object (creates a new <code>LuaLogService</code> ).

Method	Description
<code>get_log</code>	Returns a <code>LuaLog</code> object that you can use to write log messages to a specified log type.

## LuaLogService:new

The constructor for a `LuaLogService` object (creates a new `LuaLogService`).

**IMPORTANT:**

Do not create a new log service to write messages to standard log types. Obtain a `LuaLog` object through the function `get_log` instead.

## Syntax

```
LuaLogService:new( config )
```

## Arguments

Argument	Description
<code>config</code>	( <code>LuaConfig</code> ) The configuration object to read the logging settings from. You can obtain a <code>LuaConfig</code> object through the function <code>get_config</code> .

## Returns

(`LuaLogService`). The new `LuaLogService` object.

## Example

The following example creates a `LuaLogService` object to write log messages to a custom log file named `lua.log`. Declare the log service globally to avoid a `LuaLogService` object being created every time the script runs. For example, if you are writing a Lua script to use with a connector or CFS, create the `LuaLogService` outside the handler function. Otherwise, the server creates a `LuaLogService` object for every document that is processed.

```
local luaConfigString = [=[  
[Logging]  
LogLevel=FULL  
Ø=LuaLogStream  
  
[LuaLogStream]  
LogTypeCSVs=lua  
LogFile=lua.log  
]=]=]  
  
local config = LuaConfig:new(luaConfigString)  
  
-- global log service instance for Lua log stream  
luaLogService = LuaLogService:new(config)  
  
local luaLog = luaLogService:get_log("lua")  
luaLog:write_line(log_level_normal(), "running Lua script")
```

## get\_log

The `get_log` method returns a `LuaLog` object that you can use to write log messages to a specified log type.

## Syntax

```
get_log( type )
```

## Arguments

Argument	Description
type	(string) The log type.

## Returns

(`LuaLog`). A `LuaLog` object.

## Example

```
local log = myLuaLogService:get_log("import")  
-- import is a standard log type for CFS
```

## LuaRegexMatch Methods

A `LuaRegexMatch` object provides information about the matches for a regular expression found in a string. For example, the `regex_search` function returns a `LuaRegexMatch` object.

If a match is found for a regular expression at multiple points in the string, you can use the `next()` method to get a `LuaRegexMatch` object for the next match.

If the regular expression contained sub-expressions (surrounded by parentheses) the methods of `LuaRegexMatch` objects can also be used to retrieve information about the sub-expression matches.

If you have a `LuaRegexMatch` object called `match` you can call its methods using the ":" operator. For example:

```
match:length()
```

Method	Description
<code>length</code>	Returns the length of the sub match.
<code>next</code>	Returns a <code>LuaRegexMatch</code> for the next match.
<code>position</code>	Returns the position of the sub match as an index from 1.
<code>size</code>	Returns the number of sub matches for the current match.
<code>str</code>	Returns the string for the sub match.

## length

The `length` method returns the length of the match. You can also retrieve the length of sub matches by specifying the `submatch` parameter.

## Syntax

```
length( [ submatch ] )
```

## Arguments

Argument	Description
<code>submatch</code>	(number) The sub match to return the length of, starting at 1 for the first sub match. With

Argument	Description
	the default value of 0 the length of the whole match is returned.

## Returns

(Number). The length of the sub match.

## next

The `next` method returns a `LuaRegexMatch` object for the next match.

## Syntax

```
next()
```

## Returns

(`LuaRegexMatch`). A `LuaRegexMatch` object for the next match, or `nil` if there are no matches following this one.

## position

The `position` method returns the position of the match in the string searched, where 1 refers to the first character in the string. You can also retrieve the position of sub matches by specifying the `submatch` parameter.

## Syntax

```
position( [ submatch ] )
```

## Arguments

Argument	Description
<code>submatch</code>	(number) The sub match to return the position of, starting at 1 for the first sub match. With the default value of 0 the position of the whole match is returned.

## Returns

(Number). The position of the submatch as an index from 1.

## size

The `size` method returns the total number of sub matches made for the current match, including the whole match (sub match 0).

### Syntax

```
size()
```

### Returns

(Number). The number of sub matches for the current match.

## str

The `str` method returns the value of the substring that matched the regular expression. You can also retrieve the values of sub matches by specifying the `submatch` parameter.

### Syntax

```
str( [ submatch ] )
```

### Arguments

Argument	Description
submatch	(number) The sub match to return the value of, starting at 1 for the first sub match. With the default value of 0 the value of the whole match is returned.

### Returns

(String). The value of the sub match.

## LuaXmlDocument Methods

This section describes the methods provided by `LuaXmlDocument` objects. A `LuaXmlDocument` object provides methods for accessing information stored in XML format. You can create a `LuaXmlDocument` from a string containing XML using the `parse_xml` function.

If you have a `LuaXmlDocument` object called `xml` you can call its methods using the `'.'` operator. For example:

```
xml:root()
```

Method	Description
<a href="#">root</a>	Returns a LuaXmlNode that is the root node of the XML document.
<a href="#">XPathExecute</a>	Returns a LuaXmlNodeSet that is the result of supplied XPath query.
<a href="#">XPathRegisterNs</a>	Register a namespace with the XML parser. Returns an integer detailing the error code.
<a href="#">XPathValue</a>	Returns the first occurrence of the value matching the XPath query.
<a href="#">XPathValues</a>	Returns the values according to the XPath query.

## root

The `root` method returns an `LuaXmlNode`, which is the root node of the XML document.

## Syntax

```
root()
```

## Returns

(`LuaXmlNode`). A `LuaXmlNode` object.

## XPathExecute

The `XPathExecute` method returns a `LuaXmlNodeSet`, which is the result of the supplied XPath query.

## Syntax

```
XPathExecute( xpathQuery )
```

## Arguments

Argument	Description
<code>xpathQuery</code>	(string) The xpath query to run.

## Returns

(`LuaXmlNodeSet`). A `LuaXmlNodeSet` object.

## XPathRegisterNs

The XPathRegisterNs method registers a namespace with the XML parser.

### Syntax

```
XPathRegisterNs( prefix, location )
```

### Arguments

Argument	Description
prefix	(string) The namespace prefix.
location	(string) The namespace location.

### Returns

(Boolean). True if successful, False in case of error.

## XPathValue

The XPathValue method returns the first occurrence of the value matching the XPath query.

### Syntax

```
XPathValue( query )
```

### Arguments

Argument	Description
query	(string) The XPath query to use.

### Returns

(String). A string of the value.

## XPathValues

The XPathValues method returns the values according to the XPath query.

## Syntax

```
XPathValues( query )
```

## Arguments

Argument	Description
query	(string) The XPath query to use.

## Returns

(Strings). The strings can be assigned to a table. To map the return values to a table, surround the function call with braces. For example:

```
values = { xml.XPathValues(query) }
```

## LuaXmlNodeSet Methods

A `LuaXmlNodeSet` object represents a set of XML nodes.

If you have a `LuaXmlNodeSet` object called `nodes` you can call its methods using the `'.'` operator. For example:

```
nodes:size()
```

Method	Description
<code>at</code>	Returns the <code>LuaXmlNode</code> at position <code>pos</code> in the set.
<code>size</code>	Returns size of node set.

### at

The `at` method returns the `LuaXmlNode` at position `position` in the set.

## Syntax

```
at( position )
```

## Arguments

Argument	Description
position	(number) The index of the item in the array to get.

## Returns

(LuaXmlNode).

## size

The `size` method returns the size of the node set.

## Syntax

```
size()
```

## Returns

(Number) An integer, the size of the node set.

## LuaXmlNode Methods

A `LuaXmlNode` object represents a single node in an XML document.

If you have a `LuaXmlNode` object called `node` you can call its methods using the `'.'` operator. For example:

```
node:name()
```

Method	Description
<code>attr</code>	Returns the first <code>LuaXmlAttribute</code> attribute object for this element.
<code>content</code>	Returns the content (text element) of the XML node.
<code>firstChild</code>	Returns a <code>LuaXmlNode</code> that is the first child of this node.
<code>lastChild</code>	Returns a <code>LuaXmlNode</code> that is the last child of this node.
<code>name</code>	Returns the name of the XML node.
<code>next</code>	Returns a <code>LuaXmlNode</code> that is the next sibling of this node.
<code>nodePath</code>	Returns the XML path to the node that can be used in another XPath query.

Method	Description
<code>parent</code>	Returns the parent <code>LuaXmlNode</code> of the node.
<code>prev</code>	Returns a <code>LuaXmlNode</code> that is the previous sibling of this node.
<code>type</code>	Returns the type of the node as a string.

## attr

The `attr` method returns the first `LuaXmlAttribute` attribute object for the `LuaXmlNode`. If the `name` argument is specified, the method returns the first `LuaXmlAttribute` object with the specified name.

## Syntax

```
attr( [name] )
```

## Arguments

Argument	Description
<code>name</code>	(string) The name of the <code>LuaXmlAttribute</code> object.

## Returns

(`LuaXmlAttribute`).

## content

The `content` method returns the content (text element) of the XML node.

## Syntax

```
content()
```

## Returns

(String). A string containing the content.

## firstChild

The `firstChild` method returns the `LuaXmlNode` that is the first child of this node.

## Syntax

```
firstChild()
```

## Returns

(LuaXmlNode).

## lastChild

The `lastChild` method returns the `LuaXmlNode` that is the last child of this node.

## Syntax

```
lastChild()
```

## Returns

(LuaXmlNode).

## name

The `name` method returns the name of the XML node.

## Syntax

```
name()
```

## Returns

(String). A string containing the name.

## next

The `next` method returns the `LuaXmlNode` that is the next sibling of this node.

## Syntax

```
next()
```

## Returns

(LuaXmlNode).

## nodePath

The `nodePath` method returns the XML path to the node, which can be used in another XPath query.

## Syntax

```
nodePath()
```

## Returns

(String). A string containing the path.

## parent

The `parent` method returns the parent `LuaXmlNode` of the node.

## Syntax

```
parent()
```

## Returns

(LuaXmlNode).

## prev

The `prev` method returns a `LuaXmlNode` that is the previous sibling of this node.

## Syntax

```
prev()
```

## Returns

(LuaXmlNode).

## type

The type method returns the type of the node as a string.

## Syntax

```
type()
```

## Returns

(String) A string containing the type. Possible values are:

```
element_node comment_node element_decl  
attribute_node document_node attribute_decl  
text_node document_type_node entity_decl  
cdata_section_node document_frag_node namespace_decl  
entity_ref_node notation_node xinclude_start  
entity_node html_document_node xinclude_end  
pi_node dtd_node docb_document_node
```

## LuaXmlAttribute Methods

A `LuaXmlAttribute` object represents an attribute on an XML element.

If you have a `LuaXmlAttribute` object called `attribute` you can call its methods using the `'.'` operator. For example:

```
attribute:name()
```

Method	Description
<code>name</code>	Returns the name of this attribute.
<code>next</code>	Returns a <code>LuaXmlAttribute</code> object for the next attribute in the parent element.
<code>prev</code>	Returns a <code>LuaXmlAttribute</code> object for the previous attribute in the parent element.
<code>value</code>	Returns the value of this attribute.

## name

The name method returns the name of this attribute.

## Syntax

`name()`

## Returns

(String). A string containing the name of the attribute.

## next

The `next` method returns a `LuaXmlAttribute` object for the next attribute in the parent element.

## Syntax

`next()`

## Returns

(`LuaXmlAttribute`).

## prev

The `prev` method returns a `LuaXmlAttribute` object for the previous attribute in the parent element.

## Syntax

`prev()`

## Returns

(`LuaXmlAttribute`).

## value

The `value` method returns the value of this attribute.

## Syntax

`value()`

## Returns

(String). A string containing the value of the attribute.

# Appendix A: Document Fields

The connector adds the following fields to each document that it ingests:

Field Name	Description
AUTN_IDENTIFIER	An identifier that allows a connector to extract the document from the repository again, for example during the collect or view actions.
DocTrackingId	An identifier used for document tracking functionality.
DRREFERENCE	A reference for the document. This is the standard IDOL reference field, which is used for deduplication.
source_connector_run_id	(Added only when <code>IngestSourceConnectorFields=TRUE</code> ). The asynchronous action token of the <code>fetch</code> action that ingested the document.
source_connector_server_id	(Added only when <code>IngestSourceConnectorFields=TRUE</code> ). A token that identifies the instance of the connector that retrieved the document (different installations of the same connector populate this field with different IDs). You can retrieve the UID of a connector through <code>action=GetVersion</code> .

# Glossary

## A

---

### **ACI (Autonomy Content Infrastructure)**

A technology layer that automates operations on unstructured information for cross-enterprise applications. ACI enables an automated and compatible business-to-business, peer-to-peer infrastructure. The ACI allows enterprise applications to understand and process content that exists in unstructured formats, such as email, Web pages, Microsoft Office documents, and IBM Notes.

### **ACI Server**

A server component that runs on the Autonomy Content Infrastructure (ACI).

### **ACL (access control list)**

An ACL is metadata associated with a document that defines which users and groups are permitted to access the document.

### **action**

A request sent to an ACI server.

### **active directory**

A domain controller for the Microsoft Windows operating system, which uses LDAP to authenticate users and computers on a network.

## C

---

### **Category component**

The IDOL Server component that manages categorization and clustering.

### **Community component**

The IDOL Server component that manages users and communities.

### **connector**

An IDOL component (for example File System Connector) that retrieves information from a local or remote repository (for example, a file system, database, or Web site).

### **Connector Framework Server (CFS)**

Connector Framework Server processes the information that is retrieved by connectors. Connector Framework Server uses KeyView to extract document content and metadata from over 1,000 different file types. When the information has been processed, it is sent to an IDOL Server or Distributed Index Handler (DIH).

### **Content component**

The IDOL Server component that manages the data index and performs most of the search and retrieval operations from the index.

### **CSS**

Cascading Style Sheets

## D

---

### **DAH (Distributed Action Handler)**

DAH distributes actions to multiple copies of IDOL Server or a component. It allows you to use failover, load balancing, or distributed content.

### **DIH (Distributed Index Handler)**

DIH allows you to efficiently split and index extremely large quantities of data into multiple copies of IDOL Server or the Content component. DIH allows you to create a scalable solution that delivers high performance and high availability. It provides a flexible way to batch, route, and categorize

the indexing of internal and external content into IDOL Server.

---

## I

### **IDOL**

The Intelligent Data Operating Layer (IDOL) Server, which integrates unstructured, semi-structured and structured information from multiple repositories through an understanding of the content. It delivers a real-time environment in which operations across applications and content are automated.

### **IDOL Proxy component**

An IDOL Server component that accepts incoming actions and distributes them to the appropriate subcomponent. IDOL Proxy also performs some maintenance operations to make sure that the subcomponents are running, and to start and stop them when necessary.

### **Intellectual Asset Protection System (IAS)**

An integrated security solution to protect your data. At the front end, authentication checks that users are allowed to access the system that contains the result data. At the back end, entitlement checking and authentication combine to ensure that query results contain only documents that the user is allowed to see, from repositories that the user has permission to access. For more information, refer to the IDOL Document Security Administration Guide.

---

## K

### **KeyView**

The IDOL component that extracts data, including text, metadata, and subfiles from over 1,000 different file types. KeyView can also convert documents to HTML format for viewing in a Web browser.

---

## L

### **LDAP**

Lightweight Directory Access Protocol. Applications can use LDAP to retrieve information from a server. LDAP is used for directory services (such as corporate email and telephone directories) and user authentication. See also: active directory, primary domain controller.

### **License Server**

License Server enables you to license and run multiple IDOL solutions. You must have a License Server on a machine with a known, static IP address.

---

## O

### **OmniGroupServer (OGS)**

A server that manages access permissions for your users. It communicates with your repositories and IDOL Server to apply access permissions to documents.

---

## P

### **primary domain controller**

A server computer in a Microsoft Windows domain that controls various computer resources. See also: active directory, LDAP.

---

## V

### **View**

An IDOL component that converts files in a repository to HTML formats for viewing in a Web browser.

## W

---

### **Wildcard**

A character that stands in for any character or group of characters in a query.

## X

---

### **XML**

Extensible Markup Language. XML is a language that defines the different attributes of document content in a format that can be read by humans and machines. In IDOL Server, you can index documents in XML format. IDOL Server also returns action responses in XML format.

# Send documentation feedback

If you have comments about this document, you can [contact the documentation team](#) by email. If an email client is configured on this system, click the link above and an email window opens with the following information in the subject line:

## **Feedback on Administration Guide (HPE Web Connector 11.4)**

Add your feedback to the email and click **Send**.

If no email client is available, copy the information above to a new message in a web mail client, and send your feedback to [AutonomyTPFeedback@hpe.com](mailto:AutonomyTPFeedback@hpe.com).

We appreciate your feedback!