



Dropbox Connector

Software Version: 11.6.0

Release Notes

Document Release Date: February 2018

Software Release Date: February 2018

Legal notices

Warranty

The only warranties for Seattle SpinCo, Inc. and its subsidiaries ("Seattle") products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Seattle shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Restricted rights legend

Confidential computer software. Except as specifically indicated, valid license from Seattle required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright notice

© Copyright 2017 EntIT Software LLC, a Micro Focus company

Trademark notices

Adobe™ is a trademark of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

Documentation updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To verify you are using the most recent edition of a document, go to

<https://softwaresupport.softwaregrp.com/group/softwaresupport/search-result?doctype=online help>.

This site requires you to sign in with a Software Passport. You can register for a Passport through a link on the site.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your Micro Focus sales representative for details.

Support

Visit the Micro Focus Software Support Online website at <https://softwaresupport.softwaregrp.com>.

This website provides contact information and details about the products, services, and support that Micro Focus offers.

Micro Focus online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support website to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Access the Software Licenses and Downloads portal
- Download software patches
- Access product documentation
- Manage support contracts

- Look up Micro Focus support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require you to register as a Passport user and sign in. Many also require a support contract.

You can register for a Software Passport through a link on the Software Support Online site.

To find more information about access levels, go to

<https://softwaresupport.softwaregrp.com/web/softwaresupport/access-levels>.

Contents

New in this Release 5

Resolved Issues 7

Supported Operating System Platforms 8

Notes 9

Documentation10

New in this Release

This section lists the enhancements to Dropbox Connector version 11.6.0.

- The connector supports progress reporting for the `collect`, `delete`, and `insert` fetch actions.
- The connector can log detailed information about HTTP requests for troubleshooting purposes. To enable this, set the new configuration parameter `EnableHTTPTrace` to `TRUE`.
- The `GetStatistics` service action can return statistics about the number and frequency of API calls made to the repository. To enable this, set the parameter `EnableDebugStatistics=TRUE`.
- The connector provides additional statistics about the work it has completed, for example the number and frequency of ingest-adds, ingest-updates, and ingest-deletes. You can view these statistics through the `GetStatistics` service action. The connector also includes an XSL template that you can use to transform the output of the `GetStatistics` action and visualize the statistics.
- The `LogTypeCSVs` configuration parameter supports additional options for customizing logging. You can now create a separate log file for a fetch task or fetch action.
- The connector generates events to alert you when an asynchronous action queue becomes full, becomes empty, and when the queue size passes certain thresholds. You can handle these events with any of the existing event handlers.
- The connector can assign a priority to documents retrieved by a fetch task so that when they are ingested they are processed before documents retrieved by other tasks or other connectors. To use this feature set the new configuration parameter `IngestPriority`.
- The connector supports the following Lua functions:
 - New functions and classes for parsing and manipulating JSON. The new functions are `parse_json`, `parse_json_array`, and `parse_json_object`. The new classes are `LuaJsonArray`, `LuaJsonObject`, and `LuaJsonValue`.
 - `deleteFieldByPath`, which you can call on a `LuaDocument` or `LuaField` object to delete fields or sub-fields that match a specified path.
 - `get_log_service`, and the new class `LuaLogService`. You can use these when you want to write log messages to a custom log file (instead of the standard ACI server log files).
 - `getFieldsByRegex`, which you can call on a `LuaDocument` or `LuaField` object to get fields or sub-fields where the name or path of the field or sub-field matches a regular expression.
 - `parse_document_csv`, `parse_document_idx`, and `parse_document_xml`. These functions parse CSV, IDX, or XML files into documents and call a function on each document. `parse_document_idx` and `parse_document_xml` can also parse a string or file that contains a single document and return a `LuaDocument` object.
- You can now call the Lua method `insertJson` on `LuaField` objects as well as `LuaDocument` objects. You can also pass it one of the new `LuaJsonArray` or `LuaJsonObject` objects instead of a string.
- You can now configure action authorization more flexibly. The `[AuthorizationRoles]` configuration section has been added. You can add subsections to create roles, which can use a combination of existing roles (equivalent to the existing `AdminClients`, `QueryClients`, and so on), or a specific set of actions. For each role, you can specify the client IPs and hosts, SSL identities, and

GSS principals to use to identify users that have particular permissions to run actions.

If you want to use only SSL and GSS authorization, you can disable the client settings by setting the appropriate client configuration parameters to `""`. For example, `AdminClients=""` disables client authorization for administrative actions, and ensures that users must meet the SSL or GSS requirements.

- You can now set `SSLCertificate` to be a chain certificate in PEM format (consisting of the end-entity certificate, any intermediate certificates, and ending with the root CA certificate). This option allows a complete certificate to be returned to the connected peer.
- You can now set `SSLCheckCertificate` to `False` even when `SSLCACertificate` or `SSLCACertificatePath` are set. This allows the component to fill in any chain required for the `SSLCertificate` by using the certificates that you specify in `SSLCACertificate` and `SSLCACertificatePath`, without requiring a certificate from the connected peer.
- The `GSSAPILibrary` configuration parameter has been added to the `[Paths]` section. You can set this parameter to the path to the GSSAPI shared library or DLL that the application uses. Depending on your system configuration, Dropbox Connector attempts to detect the appropriate library to use. However, if you use Kerberos or GSSAPI security in your setup, Micro Focus recommends that you set an explicit value for this parameter.
- All ACI server ports now support the `Expect: 100-continue` HTTP header. Previously, third-party client applications that used this header (for example, using the `cURL` utility with the `-F` option to POST form data) could experience increased latency when communicating with Dropbox Connector.
- You can now configure your authorization role `SSLIdentities` to identify clients by using an email address in the certificate `subjectAltName`. You can use an optional tag for each SSL identity to specify whether it is a **dns** or **email** type identity. If there is no tag, the server treats it as **dns** type. For example:

```
SSLIdentities=email:user@example.com,dns:admin.example.com,webapp.example.com
```

- When using GSS security, you can now configure the service to allow clients to authenticate to any service principal in the service's keytab, rather than requiring a single principal. You use this option by setting the `GSSServiceName` configuration parameter to an asterisk (*).

Resolved Issues

This section lists the resolved issues in Dropbox Connector version 11.6.0.

- The `GetVersion` action could incorrectly report the operating system on Microsoft Windows 10 and Microsoft Windows Server 2016.
- License related messages in the event log would appear from a different source to other messages.
- The `LogSysLog` logging configuration option did not output event logs.

Supported Operating System Platforms

The following operating system platforms are supported by Dropbox Connector 11.6.0.

- Windows x86 64
- Linux x86 64
- Solaris x86 64
- Solaris SPARC 64

The most fully tested versions of these platforms are:

Windows

- Windows Server 2012 x86 64
- Windows 7 SP1 x86 64
- Windows Server 2008 R2 x86 64
- Windows Server 2008 SP2 x86 64

Linux

For Linux, the minimum recommended versions of particular distributions are:

- Red Hat Enterprise Linux (RHEL) 6
- CentOS 6
- SuSE Linux Enterprise Server (SLES) 10
- Ubuntu 14.04
- Debian 7

Solaris

- Solaris 10
- Solaris 11

Notes

- The Lua function `get_log(config, logstream)` has been deprecated. Micro Focus recommends that you use the new function `get_log(log_type)` instead.
- The Lua function `string_uint_less` has been removed.
- The following configuration parameters, for action authorization by client IP address, have been deprecated:
 - [Server] AdminClients
 - [Server] QueryClients
 - [Service] ServiceControlClients
 - [Service] ServiceStatusClients

You can now use the [AuthorizationRoles] configuration section to set up authorization for your servers more flexibly. These configuration parameters are still available for existing implementations, but they might be incompatible with new functionality. The parameters might be deleted in future.

Documentation

The following documentation was updated for this release.

- *Dropbox Connector Administration Guide*
- *Dropbox Connector Reference*