

Volume Management

Developer Kit

January 6, 2016

Novell®



Legal Notices

For information about legal notices, trademarks, disclaimers, warranties, export and other use restrictions, U.S. Government rights, patent policy, and FIPS compliance, see <https://www.novell.com/company/legal/>.

Contents

About This Guide	5
1 Concepts	7
1.1 Volume Basics	7
1.2 Volume Information Functions	7
1.3 Volume Utilization and Restriction Functions	7
2 Tasks	9
2.1 Reading Volume Information	9
2.2 Managing Disk Space.	9
3 Functions	11
NWGetDirSpaceInfoExt	12
NWGetDirSpaceLimit	14
NWGetDiskUtilization	16
NWGetExtendedVolumeInfo.	18
NWGetExtendedVolumeInfoExt	20
NWGetObjDiskRestrictions.	22
NWGetObjDiskRestrictionsExt	24
NWGetVolumeDetailsByInfoMask	26
NWGetVolumeInfoWithHandle	28
NWGetVolumeInfoWithNumber	31
NWGetVolumeName	34
NWGetVolumeNumber	36
NWRemoveObjectDiskRestrictions.	38
NWScanVolDiskRestrictionsExt	40
NWScanVolDiskRestrictions2.	42
NWScanMountedVolumeList	44
NWSetDirSpaceLimitExt.	46
NWSetObjectVolSpaceLimit.	48
NWSetObjectVolSpaceLimitExt	50
4 Structures	53
NWOBJ_REST	54
NWVolExtendedInfo	55
NWVolMountNumWithName.	59
NWWOL_RESTRICTIONS	60
VOL_STATS	61
5 Server-Based Volume Management Functions	63
GetNumberOfVolumes	64
GetVolumeInformation	65
GetVolumeInfoWithNumber	68

GetVolumeName	70
GetVolumeNumber	72
GetVolumeStatistics	74
NWGetExtendedVolumeInfo	77

A Revision History 79

About This Guide

The volume management functions enable you to manage and obtain statistics about OES volumes. They allow you to perform the following tasks:

- ♦ Return information about a specified volume
- ♦ Access space restrictions for a specified object on a specified volume
- ♦ Access utilization statistics for a specified volume

This guide contains the following sections:

- ♦ [Chapter 1, “Concepts,” on page 7](#)
- ♦ [Chapter 2, “Tasks,” on page 9](#)
- ♦ [Chapter 3, “Functions,” on page 11](#)
- ♦ [Chapter 4, “Structures,” on page 53](#)
- ♦ [Chapter 5, “Server-Based Volume Management Functions,” on page 63](#)

Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comments feature at the bottom of each page of the online documentation.

Documentation Updates

For the most recent version of this guide, see [OES Cross-Platform Libraries \(XPlat\) for Windows](https://www.novell.com/developer/ndk/xplat-linux.html) (<https://www.novell.com/developer/ndk/xplat-linux.html>).

Additional Information

For help with XPlat problems or questions, visit the [OES Cross-Platform Libraries \(XPlat\) for Windows Developer Support Forums](https://forums.novell.com/forumdisplay.php/807-DEVELOPERS) (<https://forums.novell.com/forumdisplay.php/807-DEVELOPERS>).

Documentation Conventions

In this documentation, a greater-than symbol (>) is used to separate actions within a step and items within a cross-reference path.

A trademark symbol (®, ™, etc.) denotes a Novell trademark. An asterisk (*) denotes a third-party trademark.

1 Concepts

This documentation describes OES volumes, their functions, and features.

1.1 Volume Basics

An OES volume is the highest level in the OES directory structure (the network equivalent of a DOS root directory). Volumes are divided into blocks made up of sectors. Each sector is 512 bytes. The default block size is 4 KB. (The number of blocks per volume depends on the size of the volume.)

The OES server identifies volumes by name and number. Knowing either value allows you to find the other.

- ♦ [NWGetVolumeNumber](#) (page 36) uses the volume name to return the volume number.
- ♦ [NWGetVolumeName](#) (page 34) uses the volume number to find the volume name.

1.2 Volume Information Functions

These functions return information about a volume:

Function	Header File	Description
NWGetVolumeInfoWithHandle	nwvol.h	Returns information for the volume on which the specified directory is found.
NWGetVolumeInfoWithNumber	nwvol.h	Returns volume information for the specified volume.
NWGetVolumeName	nwvol.h	Returns the name of the volume associated with the specified volume number.
NWGetVolumeNumber	nwvol.h	Returns the volume number based on the OES server connection ID and volume name.
NWGetVolumeDetailsByInfoMask	nwfse.h	Returns the volume details based on the information structure provided in <code>ReturnInfoMask</code> .
NWGetExtendedVolumeInfo	nwvol.h	Returns extended information for the specified volume.
NWGetExtendedVolumeInfoExt	nwvol.h	Returns extended information for the specified volume.
NWGetDirSpaceInfoExt	nwdirect.h	Returns information on space usage for a volume.

1.3 Volume Utilization and Restriction Functions

These functions access space restrictions and utilization statistics for a volume.

Function	Header File	Description
NWGetDirSpaceLimit	nwdirect.h	Returns the actual space restrictions for a directory.
NWGetDiskUtilization	nwvol.h	Returns disk usage for a specified bindery object on a volume.
NWGetObjDiskRestrictions	nwvol.h	Returns the restriction on a volume for the specified bindery object.
NWGetObjDiskRestrictionsExt	nwvol.h	Returns the restriction on a volume for the specified bindery object.
NWRemoveObjectDiskRestrictions	nwvol.h	Removes all disk restrictions for the specified object on a volume.
NWScanVolDiskRestrictionsExt	nwvol.h	Returns a list of objects and their disk restrictions on a volume.
NWScanVolDiskRestrictions2	nwvol.h	Returns a list of objects and their disk restrictions on a volume.
NWSetDirSpaceLimitExt	nwdirect.h	Specifies a user disk space restrictions (in 4 KB blocks) on a particular subdirectory.
NWSetObjectVolSpaceLimit	nwvol.h	Adds a user disk space restriction to a volume.
NWSetObjectVolSpaceLimitExt	nwvol.h	Adds a user disk space restriction to a volume.

2 Tasks

This documentation describes common tasks associated with the volume functions.

2.1 Reading Volume Information

OES volume information indicates the amount of space available on a volume. It includes the block size (number of sectors per block) and the following totals:

- ♦ Total blocks available
- ♦ Total blocks in use
- ♦ Total directory entries available
- ♦ Total directory entries in use

It also indicates whether the volume is removable.

Two functions enable you to read volume information, one by means of volume number and the other by directory handle:

- ♦ [NWGetVolumeInfoWithNumber \(page 31\)](#) takes a volume number.
- ♦ [NWGetVolumeInfoWithHandle \(page 28\)](#) takes a directory handle.

Additional volume information is available at the directory level by calling [NWGetDirSpaceInfo](#) (Multiple and Inter-File Services), [NWGetDirSpaceInfoExt \(page 12\)](#), and [NWGetDirSpaceLimit \(page 14\)](#).

2.2 Managing Disk Space

With OES, you can control the total amount of space available to each object within a volume.

OES servers let you restrict the number of 4 KB blocks available to a specified object. Two functions set disk space restrictions and four functions read restrictions:

- ♦ [NWSetObjectVolSpaceLimit \(page 48\)](#) sets an object's disk space restriction in blocks. On OES servers, the restriction can range from 0 to 0x08000000.
- ♦ [NWSetObjectVolSpaceLimitExt \(page 50\)](#) sets an object's disk space restriction in blocks. On OES servers, the restriction can range from 0 to 0x7ffffffffffe.
- ♦ [NWGetObjDiskRestrictions \(page 22\)](#) and [NWGetObjDiskRestrictionsExt \(page 24\)](#) returns the restriction for a specified object.
- ♦ [NWScanVolDiskRestrictionsExt \(page 40\)](#) and [NWScanVolDiskRestrictions2 \(page 42\)](#) can be called iteratively to build a list of objects that are assigned disk space restrictions.

To remove restrictions for a specific object on a volume, call [NWRemoveObjectDiskRestrictions \(page 38\)](#).

- ♦ [NWGetDiskUtilization \(page 16\)](#) returns the number of files, directories, and blocks an object is using on a volume.

3 Functions

This documentation alphabetically lists the volume functions and describes their purpose, syntax, parameters, and return values.

- ♦ [“NWGetDirSpaceInfoExt” on page 12](#)
- ♦ [“NWGetDirSpaceLimit” on page 14](#)
- ♦ [“NWGetDiskUtilization” on page 16](#)
- ♦ [“NWGetExtendedVolumeInfo” on page 18](#)
- ♦ [“NWGetExtendedVolumeInfoExt” on page 20](#)
- ♦ [“NWGetObjDiskRestrictions” on page 22](#)
- ♦ [“NWGetObjDiskRestrictionsExt” on page 24](#)
- ♦ [“NWGetVolumeDetailsByInfoMask” on page 26](#)
- ♦ [“NWGetVolumeInfoWithHandle” on page 28](#)
- ♦ [“NWGetVolumeInfoWithNumber” on page 31](#)
- ♦ [“NWGetVolumeName” on page 34](#)
- ♦ [“NWGetVolumeNumber” on page 36](#)
- ♦ [“NWRemoveObjectDiskRestrictions” on page 38](#)
- ♦ [“NWScanVolDiskRestrictionsExt” on page 40](#)
- ♦ [“NWScanVolDiskRestrictions2” on page 42](#)
- ♦ [“NWScanMountedVolumeList” on page 44](#)
- ♦ [“NWSetDirSpaceLimitExt” on page 46](#)
- ♦ [“NWSetObjectVolSpaceLimit” on page 48](#)
- ♦ [“NWSetObjectVolSpaceLimitExt” on page 50](#)

NWGetDirSpaceInfoExt

Returns information on space usage for a volume or directory

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: File System

Syntax

```
#include <nwdirect.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetDirSpaceInfoExt(
    NWCONN_HANDLE    conn,
    NWDIR_HANDLE      dirHandle,
    nuint32           volNum,
    DIR_SPACE_INFO2   N_FAR * spaceInfo);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

dirHandle

(IN) Specifies the directory handle associated with the desired directory path (0 if volume information is to be returned).

volNum

(IN) Specifies the volume number to return space information for (0 if directory information is to be returned).

spaceInfo

(OUT) Points to the DIR_SPACE_INFO2 structure.

Return Values

These are common return values; see [Return Values](#) ([Return Values for C](#)) for more information.

0x0000	SUCCESSFUL
0x899B	BAD_DIRECTORY_HANDLE
0x8998	VOLUME_DOES_NOT_EXIST
0x89FD	BAD_STATION_NUMBER
0x89FF	FAILURE (Bad Info Type or Bad return info mask)

Remarks

If the `dirHandle` parameter is zero, `NWGetDirSpaceInfoExt` returns the volume information to the `DIR_SPACE_INFO2` structure. Pass the volume number in `volNum`, which is obtained from calling `NWGetVolumeNumber`.

`purgeableBlocks` and `nonYetPurgeableBlocks` are set to 0 if the `dirHandle` parameter contains a nonzero value.

The `availableBlocks` field is the only field that returns information when disk space restrictions are in effect. The rest of the structure fields contain volume-wide information. If disk space restrictions are not in effect, the `availableBlocks` field will contain the number of blocks available for use on the entire volume.

One block equals the size of the block size for the specified volume, which is obtained by multiplying `sectorsPerBlock` by 512 bytes.

You can call [NWGetExtendedVolumeInfoExt](#) (Volume Services) to return the block size (in bytes).

NCP Calls

0x2222 123 35 Get Volume Purge Information

0x2222 22 58 Get Dir Info

NWGetDirSpaceLimit

Returns the actual space limitations for a directory

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: File System

Syntax

```
#include <nwdirect.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetDirSpaceLimit(
    NWCONN_HANDLE    conn,
    NWDIR_HANDLE      dirHandle,
    NW_RESTRICTION_64 N_FAR * Restrictions);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

dirHandle

(IN) Specifies the directory handle pointing to the desired directory.

Restrictions

(OUT) Points to Restrictions.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8977	ERR_BUFFER_TOO_SMALL
0x8996	SERVER_OUT_OF_MEMORY
0x8997	ERR_TARGET_NOT_A_SUBDIRECTORY
0x8998	VOLUME_DOES_NOT_EXIST
0x899B	BAD_DIRECTORY_HANDLE
0x899C	INVALID_PATH
0x89A1	DIRECTORY_IO_ERROR
0x89BF	INVALID_NAME_SPACE
0x89FD	BAD_STATION_NUMBER
0x89FF	FAILURE (Invalid Request Parameter)

Remarks

To find the actual amount of space (MinSpaceLeft) available to a directory, scan the amount of disk space assigned to all directories between the current directory and root directory. The smallest of the SpaceLeft values for the current directory and ancestor directories in the path is calculated and returned. If the MinSpaceLeft is zero, there is no space in the directory.

All restrictions are returned in units of 4KB blocks.

The valid restriction values are as follows:

- ♦ If the restriction equals 0x7fffffffffff, the object has no restrictions.
- ♦ If the restriction equals 0, the object has full restrictions or no space allowed.
- ♦ If the restriction value is from 1 to 0x7ffffffffffe, the object has restrictions based on the corresponding value.

NOTE: If you use this function in a loop on an NSS volume, server utilization can rise to 100% which causes a denial of service to connections. You need to limit the number of quick calls to this function to under 200 and then let the server utilization drop before calling another set. Server utilization is not affected by numerous quick calls to this function on traditional volumes.

NCP Calls

0x2222 89 41 Get Directory Disk Space Restriction

NWGetDiskUtilization

Allows a client to determine how much physical space the specified object ID is using on the given volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetDiskUtilization (
    NWCONN_HANDLE conn,
    nuint32 objID,
    nuint8 volNum,
    pnuint16 usedDirectories,
    pnuint16 usedFiles,
    pnuint16 usedBlocks);
```

Pascal Syntax

```
uses calwin32

Function NWGetDiskUtilization
( conn : NWCONN_HANDLE;
  objID : nuint32;
  volNum : nuint8;
  usedDirectories : pnuint16;
  usedFiles : pnuint16;
  usedBlocks : pnuint16
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

objID

(IN) Specifies the object ID.

volNum

(IN) Specifies the volume number.

usedDirectories

(OUT) Points to the number of directories on the volume owned by **objID**.

usedFiles

(OUT) Points to the number of files on the volume owned by objID.

usedBlocks

(OUT) Points to the number of physical volume blocks occupied by files owned by objID.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8996	SERVER_OUT_OF_MEMORY
0x8998	VOLUME_DOES_NOT_EXIST
0x89A1	DIRECTORY_IO_ERROR
0x89F2	NO_OBJECT_READ_PRIVILEGE
0x89FC	NO_SUCH_OBJECT

Remarks

usedBlocks will return incorrect information for disks larger than 268 megabytes. Call NWGetObjDiskRestrictions to get the disk space being used by an object.

Clients who are SUPERVISOR equivalent can call NWGetDiskUtilization for any object. Clients not having SUPERVISOR rights can call NWGetDiskUtilization only for the object used when logging in.

Call either NWGetObjectID or NWDSMapNameToID to get the object ID.

NWGetDiskUtilization will not validate objID. If objID is invalid or does not exist on the server, NWGetDiskUtilization will return zero (0) for the disk utilization.

NCP Calls

- 0x2222 23 14 Get Disk Utilization
- 0x2222 23 54 Get Object Name

See Also

[NWDSMapNameToID](#) (*NDS Core Services*), [NWGetObjDiskRestrictions](#) (page 22), [NWGetObjectID](#) (*NDK: Bindery Management*)

NWGetExtendedVolumeInfo

Returns extended volume information

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetExtendedVolumeInfo (
    NWCONN_HANDLE conn,
    nuint16 volNum,
    NWVolExtendedInfo N_FAR *volInfo);
```

Pascal Syntax

```
uses calwin32

Function NWGetExtendedVolumeInfo
( conn : NWCONN_HANDLE;
  volNum : nuint16;
  Var volInfo : NWVolExtendedInfo
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number.

volInfo

(OUT) Points to NWVolExtendedInfo, which receives information.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8998	VOLUME_DOES_NOT_EXIST
0x897E	NCP_BOUNDARY_CHECK_FAILED
0x89FB	NO_SUCH_PROPERTY

Remarks

NWGetExtendedVolumeInfo returns information based on the volume block size (64 KB), which can be determined using the formula:

```
(sectorSize*sectorsPerCluster) / 1024
```

NWGetExtendedVolumeInfo must be called for a licensed connection or NO_SUCH_PROPERTY will be returned.

For sample code, see [Developer Q&A \(http://support.novell.com/techcenter/qna/dnq20030204.html\)](http://support.novell.com/techcenter/qna/dnq20030204.html).

NCP Calls

0x2222 22 51 Get Extended Volume Information

NWGetExtendedVolumeInfoExt

Returns extended volume information

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetExtendedVolumeInfoExt(
    NWCONN_HANDLE conn,
    nuint32 volNum,
    NWVolExtendedInfo2 N_FAR * volInfo);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number.

volInfo

(OUT) Points to NWVolExtendedInfo2, which receives information.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8998	VOLUME_DOES_NOT_EXIST
0x899B	BAD_DIRECTORY_HANDLE
0x89FD	BAD_STATION_NUMBER
0x89FB	FAILURE (Bad Info Type or Bad return info mask)

Remarks

NWGetExtendedVolumeInfoExt returns information based on the volume block size (64 KB), which can be determined using the formula:

$(\text{sectorSize} * \text{sectorsPerCluster}) / 1024$

NWGetExtendedVolumeInfoExt must be called for a licensed connection or FAILURE will be returned.

NCP Calls

0x2222 123 35 Get Extended Volume Information

NWGetObjDiskRestrictions

Returns the disk restrictions imposed on an object for the specified volume number

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetObjDiskRestrictions (
    NWCONN_HANDLE conn,
    nuint8 volNumber,
    nuint32 objectID,
    pnuint32 restriction,
    pnuint32 inUse);
```

Pascal Syntax

```
uses calwin32

Function NWGetObjDiskRestrictions
    (conn : NWCONN_HANDLE;
     volNumber : nuint8;
     objectID : nuint32;
     restriction : pnuint32;
     inUse : pnuint32
    ) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNumber

(IN) Specifies the volume number for which to return the restrictions.

objectID

(IN) Specifies the object ID.

restriction

(OUT) Points to the buffer containing the number of blocks the object can use.

inUse

(OUT) Points to the buffer containing the number of blocks the object is currently using.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

The restrictions are returned in units of 4KB blocks and ignore the block size of the volume.

NOTE: If the restriction equals 0x40000000, the object has no restrictions.

NCP Calls

0x2222 22 41 Get Object Disk Usage And Restrictions

See Also

[NWGetExtendedVolumeInfo](#) (page 18), [NWSetObjectVolSpaceLimit](#) (page 48)

NWGetObjDiskRestrictionsExt

Returns the disk restrictions imposed on an object for the specified volume number

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetObjDiskRestrictionsExt(
    NWCONN_HANDLE    conn,
    nuint32           volNumber,
    nuint32           objectID,
    pnuint64          restriction,
    pnuint64          inUse);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNumber

(IN) Specifies the volume number for which the restrictions has to be returned.

objectID

(IN) Specifies the object ID.

restriction

(OUT) Points to the buffer containing the number of blocks the object can use.

inUse

(OUT) Points to the buffer containing the number of blocks the object is currently using.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

The restrictions are returned in units of 4KB blocks and ignore the block size of the volume.

NOTE: The valid restriction values are as follows:

- ♦ If the restriction equals 0x7fffffffffff, the object has no restrictions.
 - ♦ If the restriction equals 0, the object has full restrictions or no space allowed.
 - ♦ If the restriction value is from 1 to 0x7ffffffffffe, the object has restrictions based on the corresponding value.
-

NCP Calls

0x2222 22 55 Get Object Disk Usage And Restrictions

See Also

[NWGetObjDiskRestrictions \(page 22\)](#)

NWGetVolumeDetailsByInfoMask

Returns information for the specified volume based on the information structure provided in `ReturnInfoMask`

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Server Environment

Syntax

```
#include <nwfse.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetVolumeDetailsByInfoMask(
    NWCONN_HANDLE    conn,
    nuint32           volNum,
    nuint32           dirhandle,
    nuint32           ReturnInfoMask,
    NWFSE_VOLUME_DETAILS_BY_INFOMASK N_FAR * fseVolumeDetails);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number to return space information for (0 if directory information is to be returned).

dirHandle

(IN) Specifies the directory handle associated with the desired directory path (0 if volume information is to be returned).

ReturnInfoMask

(IN) Specifies the `ReturnInfoMask` information to return (`VINFO_RIM_VOL_INFO64` or `VINFO_RIM_VOL_NAME` or `VINFO_RIM_VOL_INFO64|VINFO_RIM_VOL_NAME`).

fseVolumeDetails

(OUT) Points to `NWFSE_VOLUME_DETAILS_BY_INFOMASK`, which receives information.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8998	VOLUME_DOES_NOT_EXIST
0x899B	BAD_DIRECTORY_HANDLE
0x89FD	BAD_STATION_NUMBER
0x89FF	FAILURE (Bad Info Type or Bad return info mask)

Remarks

In reply data, only the information structure indicated in `ReturnInfoMask` will be returned in the reply length. That is, if the request comes with only `VINFO_RIM_VOL_NAME` for `ReturnInfoMask`, the reply contains only structure `VolumeNameDetails` along with filled data and starts at the offset without considering the size for `VolumeInfo_64`.

Similarly, if the request comes with `VINFO_RIM_VOL_INFO64` for `ReturnInfoMask`, the reply contains only structure `VolumeInfoDetails`. Also, if the request comes with `VINFO_RIM_VOL_INFO64 | VINFO_RIM_VOL_NAME` for `ReturnInfoMask`, the reply contains both the `VolumeInfoDetails` and `VolumeNameDetails`.

Order of the information filled by the server is in the order of its bit mask. That is, the info with bit mask `0x00000001` is filled first (if requested), followed by the information with bit mask `0x00000002` is filled next, followed by `0x00000003` and so on.

NCP Calls

0x2222 123 35 Get Volume Information By InfoMask

NWGetVolumeInfoWithHandle

Returns the physical information or data of a server's volumes

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY(NWCCODE) NWGetVolumeInfoWithHandle (
    NWCONN_HANDLE    conn,
    NWDIR_HANDLE      dirHandle,
    pnstr8             volName,
    pnuint16           totalBlocks,
    pnuint16           sectorsPerBlock,
    pnuint16           availableBlocks,
    pnuint16           totalDirEntries,
    pnuint16           availableDirEntries,
    pnuint16           volIsRemovableFlag);
```

Pascal Syntax

```
uses calwin32

Function NWGetVolumeInfoWithHandle(
    conn : NWCONN_HANDLE;
    dirHandle : NWDIR_HANDLE;
    volName : pnstr8;
    totalBlocks : pnuint16;
    sectorsPerBlock : pnuint16;
    availableBlocks : pnuint16;
    totalDirEntries : pnuint16;
    availableDirEntries : pnuint16;
    volIsRemovableFlag : pnuint16
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

dirHandle

(IN) Specifies the directory handle pointing to the directory on the volume whose information is to be reported.

volName

(OUT) Points to the volume name (optional 17 character buffer including the terminating NULL).

totalBlocks

(OUT) Points to the total number of blocks on the volume (optional).

sectorsPerBlock

(OUT) Points to the number of sectors per block (optional).

availableBlocks

(OUT) Points to the total number of unused blocks on the volume (optional).

totalDirEntries

(OUT) Points to the total number of physical directory entries (optional).

availableDirEntries

(OUT) Points to the number of unused directory entries (optional).

volIsRemovableFlag

(OUT) Set to NULL. The value in this field is never set.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8998	VOLUME_DOES_NOT_EXIST
0x899B	BAD_DIRECTORY_HANDLE
0x899C	INVALID_PATH
0x89FF	HARDWARE_FAILURE

Remarks

NWGetVolumeInfoWithHandle returns a 16-bit number in the `totalBlocks` parameter. If the volume size is greater than a 16-bit number (or 256 megabytes), NWGetDirSpaceInfo should be called.

`dirHandle` is an index number (1 through 255) pointing to a volume, directory, or subdirectory on the OES server. Directory handles are recorded in the Directory Handle Table maintained by the server for each logged-in workstation. When a workstation allocates a directory handle, the OES server enters the volume number and directory entry number for the specified directory into the Directory Handle Table. Applications running on the workstation can then refer to a directory using a directory handle, which is actually an index into the Directory Handle Table.

Since all of the output parameters are optional, substitute NULL for unwanted information. However, all parameter positions must be filled.

Volumes use logical sector sizes of 512 bytes. If the physical media uses a different sector size, the server performs appropriate mappings. Volume space is allocated in groups of sectors called blocks.

`sectorsPerBlock` indicates how many 512-byte sectors are contained in each block of the specified volume.

`totalDirEntries` indicates how many directory entries were allocated for the specified volume during installation. If this information is meaningless under a given server's implementation, it is 0xFFFF.

`volIsRemovableFlag` indicates whether a user can physically remove the volume from the OES server. It returns one of the following values:

0x0000 = not removable/fixed media
non-zero = removable/mountable

With OES 2015 and SFTIII, the volume sector size can be changed from the 512-byte default. If changed, `NWGetVolumeInfoWithHandle` may return adjusted data meeting DOS requirements. `totalBlocks`, `sectorsPerBlock` and `availableBlocks` may be affected. To see the actual field size, call `NWGetExtendedVolumeInfo`.

NOTE: Block size can be found by calling `NWGetExtendedVolumeInfo` and multiplying `sectorSize` and `sectorPerCluster`.

NCP Calls

0x2222 22 21 Get Volume Info With Handle

See Also

[NWGetDirSpaceInfo](#) (Multiple and Inter-File Services), [NWGetVolumeInfoWithNumber](#) (page 31)

NWGetVolumeInfoWithNumber

Returns information for the specified volume by passing a volume number, allowing a client to check the physical space available on a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetVolumeInfoWithNumber (
    NWCONN_HANDLE conn,
    uint16         volNum,
    pstr8          volName,
    puint16        totalBlocks,
    puint16        sectorsPerBlock,
    puint16        availableBlocks,
    puint16        totalDirEntries,
    puint16        availableDirEntries,
    puint16        volIsRemovableFlag);
```

Pascal Syntax

```
uses calwin32

Function NWGetVolumeInfoWithNumber
( conn : NWCONN_HANDLE;
  volNum : uint16;
  volName : pstr8;
  totalBlocks : puint16;
  sectorsPerBlock : puint16;
  availableBlocks : puint16;
  totalDirEntries : puint16;
  availableDirEntries : puint16;
  volIsRemovableFlag : puint16
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number of the volume for which information is being obtained.

volName

(OUT) Points to the volume name (optional 17 character buffer including the terminating NULL).

totalBlocks

(OUT) Points to the total number of blocks on the volume (optional).

sectorsPerBlock

(OUT) Points to the number of sectors per block (optional).

availableBlocks

(OUT) Points to the number of unused blocks on the volume (optional).

totalDirEntries

(OUT) Points to the total number of physical directory entries (optional).

availableDirEntries

(OUT) Points to the number of unused directory entries (optional).

volIsRemovableFlag

(OUT) Set to NULL. The value in this field is never set.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

NWGetVolumeInfoWithNumber returns a 16-bit number in the `totalBlocks` parameter. If the volume size is greater than a 16-bit number (or 256 megabytes), NWGetDirSpaceInfo should be called.

`volNum` identifies the volume name on the OES server's Volume Table.

Volumes use logical sector sizes of 512 bytes. If the physical media uses a different sector size, the server performs appropriate mappings. Volume space is allocated in groups of sectors called blocks.

`sectorsPerBlock` indicates the number of 512-byte sectors contained in each block of the specified volume.

`totalDirEntries` indicates how many directory entries were allocated for the specified volume during installation. If this information is meaningless under a given server's implementation, it is 0xFFFF.

Since all of the output parameters are optional, substitute a NULL for unwanted information. However, all parameter positions must be filled.

With OES 2015 and SFTIII, the volume sector size can be changed from the 512-byte default. If changed, NWGetVolumeInfoWithHandle may return adjusted data that meets DOS requirements. `totalBlocks`, `sectorsPerBlock`, and `availableBlocks` may be affected. To see the actual field size, call NWGetExtendedVolumeInfo.

NOTE: Block size can be found by calling `NWGetExtendedVolumeInfo` and multiplying `sectorSize` and `sectorPerCluster`.

NCP Calls

0x2222 18 Get Volume Info With Number

See Also

[NWGetDirSpaceInfo](#) (Multiple and Inter-File Services), [NWGetVolumeInfoWithHandle](#) (page 28)

NWGetVolumeName

Returns the name of the volume associated with the specified volume number and OES server

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWGetVolumeName (
    NWCONN_HANDLE conn,
    nuint16        volNum,
    pnstr8         volName);
```

Pascal Syntax

```
uses calwin32

Function NWGetVolumeName
( conn : NWCONN_HANDLE;
  volNum : nuint16;
  volName : pnstr8
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number of the volume for which information is being obtained.

volName

(OUT) Points to the volume name (17 characters including the terminating NULL).

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8996	SERVER_OUT_OF_MEMORY
0x8998	VOLUME_DOES_NOT_EXIST
0x89FF	HARDWARE_FAILURE

Remarks

`volNum` identifies the volume name on the OES server's Volume Table. `volNum` needs to be between 0 and the maximum allowable volumes on the server.

NWGetVolumeName can be called to determine all volume numbers and volume names currently mounted on the specified OES server:

- ♦ For regular volumes, start the scan with volume number 0 and scan upwards.
- ♦ For clustered volumes, start the scan with volume number 255 and scan downwards.

SUCCESSFUL will be returned for each allowable volume number whether or not that volume exists on the specified server. For example, OES supports 64 volumes on each server. Calling NWGetVolumeName on each of the 64 volumes will return SUCCESSFUL even though the volume is not mounted.

NCP Calls

0x2222 22 6 Get Volume Name

See Also

[NWGetVolumeNumber \(page 36\)](#)

NWGetVolumeNumber

Returns the volume number based on the OES server connection handle and the volume name

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY(NWCCODE) NWGetVolumeNumber (
    NWCONN_HANDLE      conn,
    const nstr8 N_FAR  *volName,
    pnuint16            volNum);
```

Pascal Syntax

```
uses calwin32

Function NWGetVolumeNumber
  (conn : NWCONN_HANDLE;
   const volName : pnstr8;
   volNum : pnuint16
  ) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volName

(IN) Points to the volume name (17 characters including the terminating NULL).

volNum

(OUT) Points to the volume number (identifies the volume on the OES server's Volume Table).

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8996	SERVER_OUT_OF_MEMORY
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

For sample code, see [Developer Q&A \(http://support.novell.com/techcenter/qna/dnq20030204.html\)](http://support.novell.com/techcenter/qna/dnq20030204.html).

NCP Calls

0x2222 22 5 Get Volume Number

See Also

[NWGetVolumeName \(page 34\)](#), [NWGetVolumeInfoWithNumber \(page 31\)](#)

NWRemoveObjectDiskRestrictions

Removes any disk restrictions for the specified object, for the specified volume, on the specified server

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWRemoveObjectDiskRestrictions (
    NWCONN_HANDLE conn,
    nuint8         volNum,
    nuint32        objID);
```

Pascal Syntax

```
uses calwin32

Function NWRemoveObjectDiskRestrictions
( conn : NWCONN_HANDLE;
  volNum : nuint8;
  objID : nuint32
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number for which to remove restrictions.

objID

(IN) Specifies the object ID for which to remove restrictions.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x898C	NO_MODIFY_PRIVILEGES
0x8998	VOLUME_DOES_NOT_EXIST
0x89FE	NetWare Error (object has no restrictions)

NCP Calls

0x2222 22 34 Remove User Disk Space Restriction

NWScanVolDiskRestrictionsExt

Returns a list of the disk restrictions for a volume

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWScanVolDiskRestrictionsExt(
    NWCONN_HANDLE    conn,
    nuint32           volNum,
    pnuint32          iterhandle,
    NWVOL_RESTRICTIONS_EXT N_FAR * volInfo);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number for which to return the restrictions.

iterhandle

(OUT) Points to the sequence number to use in the search (set to 0 initially).

volInfo

(OUT) Points to NWVOL_RESTRICTIONS_EXT.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8977	ERR_BUFFER_TOO_SMALL
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

NWScanVolDiskRestrictionsExt function uses a larger structure for the volume restrictions that allows up to 16 restrictions per volume.

The information returned in NWVOL_RESTRICTIONS_EXT contains the object restrictions that have been made for the volume. All restrictions are returned in 4KB blocks. The valid restriction values are as follows:

- ♦ If the restriction equals 0x7fffffffffff, the object has no restrictions.
- ♦ If the restriction equals 0, the object has full restrictions or no space allowed.
- ♦ If the restriction value is from 1 to 0x7ffffffffffe, the object has restrictions based on the corresponding value.

IMPORTANT: NWScanVolDiskRestrictionsExt is called iteratively to retrieve information on all disk space restrictions. The number of entries is returned in the `volInfo.numberOfEntries` field. If the `volInfo.numberOfEntries` field returns the value 16, then it is assumed that there are additional entries to be returned. In this case, the value of `volInfo.numberOfEntries` field must be added to the previous `iterhandle` to obtain the value for the next iterative call.

NCP Calls

0x2222 22 56 Scan Volume's User Disk Restrictions

NWScanVolDiskRestrictions2

Returns a list of the disk restrictions for a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWScanVolDiskRestrictions2 (
    NWCONN_HANDLE      conn,
    nuint8              volNum,
    pnuint32            iterHnd,
    NWVOL_RESTRICTIONS N_FAR *volInfo);
```

Pascal Syntax

```
uses calwin32

Function NWScanVolDiskRestrictions2
( conn : NWCONN_HANDLE;
  volNum : nuint8;
  iterhandle : pnuint32;
  Var volInfo : NWVOL_RESTRICTIONS
) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number for which to return the restrictions.

iterHnd

(OUT) Points to the sequence number to use in the search (set to 0 initially).

volInfo

(OUT) Points to NWVOL_RESTRICTIONS.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

NWScanVolDiskRestrictions2 replaces NWScanVolDiskRestrictions. The new function uses a larger structure for the volume restrictions that allows up to 16 restrictions per volume.

NOTE: Calling NWScanVolDiskRestrictions when you have more than 12 restrictions per volume causes random failures. For this reason, call NWScanVolDiskRestrictions2 exclusively.

The information returned in NWVOL_RESTRICTIONS contains the object restrictions that have been made for the volume. All restrictions are returned in 4KB blocks. If the restriction is greater than 0x80000000 on an OES server, the object has no restrictions.

IMPORTANT: NWScanVolDiskRestrictions2 is called iteratively to retrieve information on all disk space restrictions. The number of entries is returned in the `volInfo.numberOfEntries` field. This value must be added to the previous `iterHnd` to obtain the value for the next iterative call.

NCP Calls

0x2222 22 32 Scan Volume's User Disk Restrictions

NWScanMountedVolumeList

Returns a list of mounted volumes

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

NWCCODE NWScanMountedVolumeList (
    uint32          conn,
    uint32          volRequestFlags,
    uint32          nameSpace,
    puint32         iterHandle,
    uint32          numberItems,
    puint32         numberReturned,
    NWVolMountNumWithName N_FAR *volInfo);
```

Pascal Syntax

```
Function NWScanMountedVolumeList (
    conn : uint32;
    volRequestFlags : uint32;
    nameSpace : uint32;
    VAR iterHandle : uint32;
    numberItems : uint32;
    VAR numberReturned : uint32;
    volInfo : pNWVolMountNumWithName
) : NWCCODE; stdcall;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volRequestFlags

(IN) Specifies only the volume number or the volume number with the volume name.

nameSpace

(IN) Specifies the name space for which you want to get the mounted volume list.

iterHandle

(IN/OUT) Points to an uint32 containing the number of the next record to be scanned. (Set to 0 for the first call.)

numberItems
(IN) Specifies the size of the array passed into `volMountedArr`.

numberReturned
(OUT) Specifies how many volumes are actually in the array pointed to by `volMountedArr`.

volMountArr
(OUT) Points to an array of `NWVolMountNumWithName` structures containing a list of volumes returned from the current call.

Return Values

These are common return values; see [Return Values \(Return Values for C\)](#) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x8836	INVALID_PARAMETER

Remarks

`NWScanMountedVolumeList` allows you to pass in a pointer to a variably sized array of `NWVolMountNumWithName` structures. On return, that pointer points to a list of mounted volumes. Based on the size of the array and number of mounted volumes, `NWScanMountedVolumeList` might return the complete list in only one call or might take multiple calls.

To call `NWScanMountedVolumeList` iteratively, pass in zero for the `iterHandle` parameter on the first call. On return, check `iterHandle` to get the number of the next record to scan for mounted volumes. When `iterHandle` contains zero on return, there are no more records to scan.

The `volRequestFlags` parameter can take one of the following values:

NW_VOLUME_NUMBER_ONLY	0
NW_VOLUME_NUMBER_AND_NAME	1

The `nameSpace` parameter can use any of the constant values identified in [Naming Conventions \(Multiple and Inter-File Services\)](#).

`NWScanMountedVolumeList` is implemented through a call to NCP 0x2222 22 52. This NCP is supported on OES.

NCP Calls

0x2222 22 52 Get Mount Volume List

NWSetDirSpaceLimitExt

Specifies a space limit (in 4 KB blocks) on a particular subdirectory

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: File System

Syntax

```
#include <nwdirect.h>
or
#include <nwcalls.h>

NWSetDirSpaceLimitExt(
    NWCONN_HANDLE    conn,
    NWDIR_HANDLE      dirHandle,
    nuint64            spaceLimit);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

dirHandle

(IN) Specifies the OES directory handle pointing to the directory to scan.

spaceLimit

(IN) Specifies the directory space limit (in 4 KB sizes).

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8901	ERR_INSUFFICIENT_SPACE
0x898C	NO_MODIFY_PRIVILEGES
0x899B	BAD_DIRECTORY_HANDLE
0x899C	INVALID_PATH
0x89FD	BAD_STATION_NUMBER

Remarks

The valid restriction values are as follows:

- ♦ If the restriction equals 0x7fffffffffffff, the object has no restrictions.

- ♦ If the restriction equals 0, the object has full restrictions or no space allowed.
- ♦ If the restriction value is from 1 to 0x7ffffffffffe, the object has restrictions based on the corresponding value.

NOTE: All restrictions are set in units of 4KB blocks.

NSS volumes and traditional volumes have very different architectures, so this function behaves differently, depending upon the volume the directory resides on. For example, traditional volumes take a long time to mount because as the volume mounts, all entries are placed in memory and disk space usage information is calculated and kept current. NSS volumes mount quickly because the entire file system is not scanned and thus disk space usage information must be calculated when a request comes in. For a few disk space requests, you will not see a great deal of difference between an NSS volume and a traditional volume. However, if you send through 3000 requests at the same time to an NSS volume, utilization can spike to 100%, causing the server to drop connections.

NCP Calls

0x2222 22 57 Set Directory Disk Space Restrictions

NWSetObjectVolSpaceLimit

Sets an object's disk space limit on a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWSetObjectVolSpaceLimit (
    NWCONN_HANDLE conn,
    nuint16        volNum,
    nuint32        objID,
    nuint32        restriction);
```

Pascal Syntax

```
uses calwin32

Function NWSetObjectVolSpaceLimit
  (conn : NWCONN_HANDLE;
   volNum : nuint16;
   objID : nuint32;
   restriction : nuint32
  ) : NWCCODE;
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number for which to set the space limit.

objID

(IN) Specifies the object ID for which to limit the volume space.

restriction

(IN) Specifies the number of blocks (in 4KB sizes) to limit the volume space.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8801	INVALID_CONNECTION
0x890A	NLM_INVALID_CONNECTION
0x898C	NO_MODIFY_PRIVILEGES
0x8996	SERVER_OUT_OF_MEMORY
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

The restrictions are returned in units of 4KB blocks.

NOTE: If the restriction equals 0x40000000, the object has no restrictions.

NCP Calls

0x2222 22 33 Add User Disk Space Restriction

See Also

[NWGetExtendedVolumeInfo \(page 18\)](#), [NWGetObjDiskRestrictions \(page 22\)](#)

NWSetObjectVolSpaceLimitExt

Sets an object disk space limit on a volume

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Library: Cross-Platform Calls (CAL*.*)

Service: Volume

Syntax

```
#include <nwvol.h>
or
#include <nwcalls.h>

N_EXTERN_LIBRARY( NWCCODE ) NWSetObjectVolSpaceLimitExt (
    NWCONN_HANDLE   conn,
    nuint32          volNum,
    nuint32          objID,
    nuint64          restriction);
```

Parameters

conn

(IN) Specifies the OES server connection handle.

volNum

(IN) Specifies the volume number for which to set the space limit.

objID

(IN) Specifies the object ID for which to limit the volume space.

restriction

(IN) Specifies the number of blocks (in 4KB sizes) to limit the volume space.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x898C	NO_MODIFY_PRIVILEGES
0x8996	SERVER_OUT_OF_MEMORY
0x8998	VOLUME_DOES_NOT_EXIST

Remarks

The valid restriction values are as follows:

- ♦ If the restriction equals 0x7fffffffffff, the object has no restrictions.
- ♦ If the restriction equals 0, the object has full restrictions or no space allowed.
- ♦ If the restriction value is from 1 to 0x7ffffffffffe, the object has restrictions based on the corresponding value.

The restrictions are returned in units of 4KB blocks.

NCP Calls

0x2222 22 54 Add User Disk Space Restriction

See Also

[NWSetObjectVolSpaceLimit \(page 48\)](#)

4 Structures

This documentation alphabetically lists the volume structures and describes their purpose, syntax, and fields.

NWOBJ_REST

Contains an object ID with the restrictions placed on the object for a certain volume (to be used with NWVOL_RESTRICTIONS)

Service: Volume

Defined In: nwvol.h

Structure

```
typedef struct
{
    nuint32    objectID ;
    nuint32    restriction ;
} NWOBJ_REST;
```

Pascal Structure

```
uses calwin32

NWOBJ_REST = packed Record
    objectID : nuint32;
    restriction : nuint32;
End;
```

Fields

objectID

Specifies the NDS ID for an object.

restriction

Specifies by the number of blocks, the amount of restriction placed on the object.

NWVolExtendedInfo

Contains extended information for a volume

Service: Volume

Defined In: nwvol.h

Structure

```
typedef struct {
    nuint32    volType ;
    nuint32    statusFlag ;
    nuint32    sectorSize ;
    nuint32    sectorsPerCluster ;
    nuint32    volSizeInClusters ;
    nuint32    freeClusters ;
    nuint32    subAllocFreeableClusters ;
    nuint32    freeableLimboSectors ;
    nuint32    nonfreeableLimboSectors ;
    nuint32    availSubAllocSectors ;
    nuint32    nonuseableSubAllocSectors ;
    nuint32    subAllocClusters ;
    nuint32    numDataStreams ;
    nuint32    numLimboDataStreams ;
    nuint32    oldestDelFileAgeInTicks ;
    nuint32    numCompressedDataStreams ;
    nuint32    numCompressedLimboDataStreams ;
    nuint32    numNoncompressibleDataStreams ;
    nuint32    precompressedSectors ;
    nuint32    compressedSectors ;
    nuint32    numMigratedDataStreams ;
    nuint32    migratedSectors ;
    nuint32    clustersUsedByFAT ;
    nuint32    clustersUsedByDirs ;
    nuint32    clustersUsedByExtDirs ;
    nuint32    totalDirEntries ;
    nuint32    unusedDirEntries ;
    nuint32    totalExtDirExtants ;
    nuint32    unusedExtDirExtants ;
    nuint32    extAttrsDefined ;
    nuint32    extAttrExtantsUsed ;
    nuint32    DirectoryServicesObjectID ;
    nuint32    volLastModifiedDateAndTime ;
} NWVolExtendedInfo;
```

Pascal Structure

uses calwin32

```
NWVolExtendedInfo = packed Record
    volType : nuint32;
    statusFlag : nuint32;
    sectorSize : nuint32;
    sectorsPerCluster : nuint32;
    volSizeInClusters : nuint32;
    freeClusters : nuint32;
    subAllocFreeableClusters : nuint32;
    freeableLimboSectors : nuint32;
    nonfreeableLimboSectors : nuint32;
    availSubAllocSectors : nuint32;
    nonuseableSubAllocSectors : nuint32;
    subAllocClusters : nuint32;
    numDataStreams : nuint32;
    numLimboDataStreams : nuint32;
```

```

oldestDelFileAgeInTicks : nuint32;
numCompressedDataStreams : nuint32;
numCompressedLimboDataStreams : nuint32;
numNoncompressibleDataStreams : nuint32;
precompressedSectors : nuint32;
compressedSectors : nuint32;
numMigratedDataStreams : nuint32;
migratedSectors : nuint32;
clustersUsedByFAT : nuint32;
clustersUsedByDirs : nuint32;
clustersUsedByExtDirs : nuint32;
totalDirEntries : nuint32;
unusedDirEntries : nuint32;
totalExtDirExtants : nuint32;
unusedExtDirExtants : nuint32;
extAttrsDefined : nuint32;
extAttrExtantsUsed : nuint32;
DirectoryServicesObjectID : nuint32;
volLastModifiedDateAndTime : nuint32;
End;

```

Fields

volType

Specifies different volumes that may be supported in the future.

statusFlag

Specifies the options currently available in this volume:

C Value	Pascal Value	Value Name
0x01	\$01	NWSubAllocEnableBit
0x02	\$02	NWCompressionEnabledBit
0x04	\$04	NWMigrationEnableBit
0x08	\$08	NWAuditingEnabledBit
0x10	\$10	NWReadOnlyEnableBit
0x80000000	\$80000000	NWPSSSEnableBit—the volume is an NSS volume.

sectorSize

Specifies the sector size in bytes.

sectorsPerCluster

Specifies the number of sectors per cluster.

volSizeInClusters

Specifies the size, in clusters, of the volume.

freeClusters

Specifies the number of clusters currently free for allocation. This does not include space currently available from deleted (limbo) files, nor space that could be reclaimed from the suballocation file system.

subAllocFreeableClusters

Specifies the space that could be reclaimed from the suballocation file system.

freeableLimboSectors

Specifies the disk space, in sectors, that could be freed from deleted files.

nonfreeableLimboSectors

Specifies the disk space, in sectors, that are currently in deleted files and not aged enough to be classified as `FreeableLimboClusters`. These will be migrated to the status of `FreeableLimboCluster` after time.

availSubAllocSectors

Specifies the space available to the suballocation file system, but not freeable to return as sectors.

nonuseableSubAllocSectors

Specifies the disk space wasted by the suballocation file system. These sectors cannot be allocated by the suballocation system or used as regular sectors.

subAllocClusters

Specifies the disk space being used by the suballocation file system.

numDataStreams

Specifies the number of data streams for real files with data allocated to them.

numLimboDataStreams

Specifies the number of data streams for deleted files with data allocated to them.

oldestDelFileAgeInTicks

Specifies the current age of the oldest file in ticks.

numCompressedDataStreams

Specifies the number of data streams for compressed real files.

numCompressedLimboDataStreams

Specifies the count of data streams for compressed deleted files.

numNoncompressibleDataStreams

Specifies the data streams found not compressable (real and deleted).

precompressedSectors

Specifies the disk space allocated to all files before they were compressed (includes "hole" space).

compressedSectors

Specifies the disk space used by all compressed files.

numMigratedDataStreams

Specifies the number of migrated data streams.

migratedSectors

Specifies the migrated disk space (in sectors).

clustersUsedByFAT

Specifies the disk space (in clusters) that is used by the FAT table.

clustersUsedByDirs

Specifies the disk space (in clusters) that is used by directories.

clustersUsedByExtDirs

Specifies the disk space (in clusters) that is used by the extended directory space.

totalDirEntries

Specifies the total number of directories available on the volume.

unusedDirEntries

Specifies the total directory entries unused on volume.

totalExtDirExtants

Specifies the amount of extended directory space extants (128 bytes each) that are available on the volume.

unusedExtDirExtants

Specifies the amount of extended directory space extants (128 bytes each) that are unused on the volume.

extAttrsDefined

Specifies the number of extended attributes that are defined on the volume.

extAttrExtantsUsed

Specifies the number of extended directory extants that are used by the extended attributes.

DirectoryServicesObjectID

Specifies the NDS ID for volume.

volLastModifiedDateAndTime

Specifies the last time any file or subdirectory within the volume was modified (tracked by the OS).

Remarks

The `volType` parameter can have the following values:

0 VNetWare386

1 VNetWare286

2 VNetWare386v30

3 VNetWare386v31

NWVolMountNumWithName

Returns the volume information.

Service: Volume

Defined In: nwwol.h

Structure

```
typedef struct NWVolMountNumWithName_tag
{
    nuint32    volumeNumber;
    nstr8      volumeName[NW_MAX_VOLUME_NAME_LEN];
} NWVolMountNumWithName;
```

Pascal Syntax

```
TYPE
    NWVolMountNumWithName = packed RECORD
        volumeNumber : nuint32;
        volumeName : Array[1..NW_MAX_VOLUME_NAME_LEN]
            of nstr8;
        filler : Array[1..3] of nuint8;
    end;

pNWVolMountNumWithName = ^NWVolMountNumWithName;
```

Fields

volumeNumber

Specifies the number of the volume.

volumeName

Specifies the volume name.

NWVOL_RESTRICTIONS

Returns a list of objects with space restrictions on a volume

Service: Volume

Defined In: nwvol.h

Structure

```
typedef struct
{
    nuint8    numberOfEntries;
    struct
    {
        nuint32    objectID;
        nuint32    restriction;
    } resInfo[16];
} NWVOL_RESTRICTIONS;
```

Pascal Structure

```
uses calwin32

NWVOL_RESTRICTIONS = packed Record
    numberOfEntries : nuint8;
    resInfo : Array[0..15] Of RES_INFO;
End;

RES_INFO = Record
    objectID : nuint32;
    restriction : nuint32;
End;
```

Fields

numberOfEntries

Specifies the number of objects in the list (0-16 objects).

objectID

Specifies the ID of the NDS object (in Hi-Lo format). This value needs to be byte swapped when passed to [NWGetObjectName](#) or [NWDSMapIDToName](#).

restriction

Specifies the size in 4KB blocks, of the restriction placed on an object (Lo-Hi format).

VOL_STATS

Contains volume statistics

Service: Volume

Defined In: nwvol.h

Structure

```
typedef struct
{
    nint32    systemElapsedTime ;
    nuint8    volumeNumber ;
    nuint8    logicalDriveNumber ;
    nuint16   sectorsPerBlock ;
    nuint16   startingBlock ;
    nuint16   totalBlocks ;
    nuint16   availableBlocks ;
    nuint16   totalDirectorySlots ;
    nuint16   availableDirectorySlots ;
    nuint16   maxDirectorySlotsUsed ;
    nuint8    isHashing ;
    nuint8    isCaching ;
    nuint8    isRemovable ;
    nuint8    isMounted ;
    nstr8     volumeName [16];
} VOL_STATS;
```

Pascal Structure

```
uses calwin32

VOL_STATS = packed Record
    systemElapsedTime : nint32;
    volumeNumber : nuint8;
    logicalDriveNumber : nuint8;
    sectorsPerBlock : nuint16;
    startingBlock : nuint16;
    totalBlocks : nuint16;
    availableBlocks : nuint16;
    totalDirectorySlots : nuint16;
    availableDirectorySlots : nuint16;
    maxDirectorySlotsUsed : nuint16;
    isHashing : nuint8;
    isCaching : nuint8;
    isRemovable : nuint8;
    isMounted : nuint8;
    volumeName : Array[0..15] Of nstr8;
End;
```

Fields

systemElapsedTime

Specifies how long the server has been up. This value is returned in ticks (units of approximately 1/18 second) and is used to determine the amount of time elapsing between consecutive calls. After reaching a value of 0xFFFFFFFF, the value wraps back to zero.

volumeNumber

Specifies the number of a volume in a volume table on a server. SYS volume is always zero.

logicalDriveNumber

Specifies the logical drive number of the drive on which the volume exists.

sectorsPerBlock

Specifies the number of 512-byte sectors contained in each block of the specified volume.

startingBlock

Specifies the number of the first block of the volume.

totalBlocks

Specifies the number of blocks in the specified volume. All volumes mounted from the same file system will return the same value.

availableBlocks

Specifies the number of unused blocks in the specified volume. All volumes mounted from the same file system will return the same value.

totalDirectorySlots

Specifies the number of directory slots allocated for the specified volume.

availableDirectorySlots

Specifies the number of directories that can be created, based on the differences between the total allowable number of directories and the number of directories already created.

maxDirectorySlotsUsed

Specifies the greatest number of directory slots ever used at one time on the volume.

isHashing

Specifies whether the volume is hashing in server memory (0=not hashing).

isCaching

Specifies whether the volume is caching in server memory (0=volume not caching).

isRemovable

Specifies if a user can physically remove the volume from the server (0=cannot be removed).

isMounted

Specifies whether the volume is physically mounted in the server (0=volume is not mounted).

volumeName

Specifies the name given to the volume (1 to 16 characters long). It cannot contain asterisks (*), question marks (?), colons (:), slashes (/), or backslashes (\). If the name is less than 16 characters, the remaining characters must be null.

5 Server-Based Volume Management Functions

This documentation alphabetically lists the server-based volume management functions and describes their purpose, syntax, parameters, and return values.

GetNumberOfVolumes

Returns the number of volumes for the local server

Local Servers: blocking

Remote Servers: N/A

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

LONG GetNumberOfVolumes (void);
```

Return Values

This function returns the number of volumes for the local server.

Remarks

This returns the number of volumes currently mounted on the local server.

See Also

[GetVolumeInformation \(page 65\)](#)

Example

```
#include <stdlib.h>
#include <nwdir.h>

printf("Number of volumes on local server = %d\n",
    GetNumberOfVolumes() );
```


GetVolumeInformation

Returns information about a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

int GetVolumeInformation (
    WORD          fileServerID,
    BYTE          volumeNumber,
    int           structSize,
    VOLUME_STATS  *volumeStatistics);
```

Parameters

fileServerID

(IN) 0 = Local server.

volumeNumber

(IN) Specifies the volume number to return information on.

structSize

(IN) Specifies the size (in bytes) of the information to return in `volumeStatistics`.

volumeStatistics

(OUT) Receives information about the specified volume.

Return Values

Decimal	Hex	Constant
0	(0x00)	ESUCCESS
152	(0x98)	ERR_INVALID_VOLUME
NetWare Error	UNSUCCESSFUL	

Remarks

If `structSize` is less than the size of `VOLUME_STATS`, then only the first `structSize` bytes of `VOLUME_STATS` are returned.

The `VOLUME_STATS` structure, pointed to by the `volumeStatistics` parameter, has the following format:

```
long    systemElapsedTime;
BYTE    volumeNumber;
BYTE    logicalDriveNumber;
WORD    sectorsPerBlock;
long    startingBlock;
WORD    totalBlocks;
WORD    availableBlocks;
WORD    totalDirectorySlots;
WORD    availableDirectorySlots;
WORD    maxDirectorySlotsUsed;
BYTE    isHashing;
BYTE    isRemovable;
BYTE    isMounted;
char    volumeName[17];
LONG    purgableBlocks;
LONG    notYetPurgableBlocks;
```

IMPORTANT: With large volumes, the number of blocks to be returned in `totalBlocks` or `availableBlocks` may be greater than 64K, resulting in inaccurate field values because of limited field size. In such instances, use `GetVolumeStatistics` instead of this function.

The *isRemovable* field always returns true.

See Also

[GetVolumeInfoWithNumber](#) (page 68), [GetVolumeName](#) (page 70), [GetVolumeNumber](#) (page 72), [GetVolumeStatistics](#) (page 74)

Example

```
#include <stdlib.h>
#include <stdio.h>
#include <stddef.h>
#include <fcntl.h>
#include <nwshare.h>
#include <nwdir.h>
#include <nwbitops.h>
#include <nwtts.h>
#include <nwbindry.h>
#include <time.h>

main()
{
    int          rc;
    VOLUME_STATS vs;
    char         svn[10];
    int          vn;

    printf("volume number: ");
    gets(svn);
    vn = atoi(svn);
    rc = GetVolumeInformation(0,vn,sizeof (vs), &vs);
```

```

if(rc)
{
    printf("rc = %d\r\n",rc);
    printf("errno = %d\r\n",errno);
    printf("%s\r\n",strerror(errno));
}
else
{
    printf("systemElapsedTime = %d\r\n",vs.systemElapsedTime);
    printf("volumeNumber = %d\r\n",vs.volumeNumber);
    printf("logicalDriveNumber = %d\r\n",vs.logicalDriveNumber);
    printf("sectorsPerBlock = %d\r\n",vs.sectorsPerBlock);
    printf("startingBlock = %d\r\n",vs.startingBlock);
    printf("totalBlocks = %d\r\n",vs.totalBlocks);

    printf("availableBlocks = %d\r\n",vs.availableBlocks);

    printf("totalDirectorySlots = %d\r\n",
        vs.totalDirectorySlots);
    printf("availableDirectorySlots = %d\r\n",
        vs.availableDirectorySlots);

    printf("maxDirectorySlotsUsed = %d\r\n",
        vs.maxDirectorySlotsUsed);
    printf("isHashing = %d\r\n",vs.isHashing);

    printf("isRemovable = %d\r\n",vs.isRemovable);

    printf("isMounted = %d\r\n",vs.isMounted);
    printf("volumeName = %s\r\n",vs.volumeName);
}
}

```

GetVolumeInfoWithNumber

Returns information about a volume by volume number

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

int GetVolumeInfoWithNumber (
    BYTE    volumeNumber,
    char     *volumeName,
    WORD     *totalBlocks,
    WORD     *sectorsPerBlock,
    WORD     *availableBlocks,
    WORD     *totalDirectorySlots,
    WORD     *availableDirectorySlots,
    WORD     *volumeIsRemovable);
```

Parameters

volumeNumber

(IN) Specifies the number of the volume slot. Even though the Volume Mount Table is 256 slots in size (0-255), the system reserves 255 as an invalid volume ID.

volumeName

(OUT) Returns a string containing the volume name (maximum 16 characters, including the NULL terminator).

totalBlocks

(OUT) Returns the number of blocks on the volume.

sectorsPerBlock

(OUT) Returns the number of sectors in a block.

availableBlocks

(OUT) Returns the number of unused blocks on the volume.

totalDirectorySlots

(OUT) Returns the number of directory slots on the volume.

availableDirectorySlots

(OUT) Returns the number of unused directory slots on the volume.

volumeIsRemovable

(OUT) Set to NULL. Always returns TRUE.

Return Values

Decimal	Hex	Constant
0	(0x00)	ESUCCESS
NetWare Error	UNSUCCES SFUL	

Remarks

The `GetVolumeInfoWithNumber` function returns information about a volume by passing a volume number. The `volumeNumber` identifies the volume in the server's Volume Table. The Volume Table contains information about each volume on the server. A server running OES can accommodate up to 64 volumes.

The `volumeName` parameter must be 16 bytes long. A volume name can be from 2 to 15 characters long plus the NULL terminator and cannot include spaces or the following characters:

*	Asterisk
?	Question mark
:	Colon
/	Slash
\	Backslash

The `sectorsPerBlock` parameter shows the number of 512-byte sectors contained in each block of the specified volume.

The `totalDirectorySlots` parameter shows the number of total directory slots available in OES.

See Also

[GetVolumeInformation](#) (page 65), [GetVolumeName](#) (page 70), [GetVolumeNumber](#) (page 72), [GetVolumeStatistics](#) (page 74)

GetVolumeName

Returns a volume name for a volume

Local Servers: nonblocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

int GetVolumeName (
    int     volumeNumber,
    char    *volumeName);
```

Parameters

volumeNumber

(IN) Specifies the number of the volume slot. Even though the Volume Mount Table is 256 slots in size (0-255), the system reserves 255 as an invalid volume ID.

volumeName

(OUT) Points to the buffer in which to return the volume name (maximum 16 characters, including the NULL terminator).

Return Values

Decimal	Hex	Constant
0	(0x00)	ESUCCESS
152	(0x98)	ERR_VOLUME_DOES_NOT_EXIST

Remarks

The `volumeNumber` identifies the volume on the server's Volume Table, which contains information about each volume on the server.

If a volume *is* mounted in the referenced slot in the Volume Table, its name is returned in the `volumeName` parameter. If a volume is *not* mounted in that slot, the output parameter `volumeName` is NULL.

ESUCCESS is returned when the `volumeNumber` is valid, even if the volume is not mounted. In that case, you need to test for `volumeName` being valid.

An error is returned when an invalid `volumeNumber` is passed in.

See Also

[GetVolumeInformation](#) (page 65), [GetVolumeInfoWithNumber](#) (page 68), [GetVolumeNumber](#) (page 72), [GetVolumeStatistics](#) (page 74)

GetVolumeNumber

Returns the volume number for a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

int GetVolumeNumber (
    char    *volumeName,
    int     *volumeNumber);
```

Parameters

volumeName

(IN) Specifies the string containing the volume name (maximum 16 characters, including the NULL terminator).

volumeNumber

(OUT) Receives the volume number associated with the `volumeName`. Even though the Volume Mount Table is 256 slots in size (0-255), the system reserves 255 as an invalid volume ID.

Return Values

Decimal	Hex	Constant
0	(0x00)	ESUCCESS
152	(0x98)	ERR_VOLUME_DOES_NOT_EXIST

Remarks

The `GetVolumeNumber` function converts a volume name to a zero-based index. The `volumeName` parameter is 16 bytes long. A volume name can be from 2 to 16 characters long and cannot include spaces or the following characters:

*	Asterisk
?	Question Mark
:	Colon
/	Slash
\	Backslash

Wildcards are not allowed in the volume name.

The `volumeNumber` identifies the volume in the server's VolumeTable. The Volume Table contains information about each volume on the server. A server running OES can accommodate up to 64 volumes.

See Also

[GetVolumeInformation](#) (page 65), [GetVolumeInfoWithNumber](#) (page 68), [GetVolumeName](#) (page 70), [GetVolumeStatistics](#) (page 74)

GetVolumeStatistics

Returns information about a volume

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

SMP Aware: No

Service: Volume

Syntax

```
#include <nwdir.h>

int GetVolumeStatistics (
    WORD          fileServerID,
    BYTE          volumeNumber,
    int           structSize,
    VOLUME_INFO   *returnedVolumeStatistics);
```

Parameters

fileServerID

(IN) 0 = Local server.

volumeNumber

(IN) Specifies the volume number to return information on.

structSize

(IN) Specifies the size (in bytes) of the information to return in `volumeStatistics`.

returnedVolumeStatistics

(OUT) Receives information about the volume.

Return Values

Decimal	Hex	Constant
0	(0x00)	ESUCCESS
152	(0x98)	ERR_INVALID_VOLUME
NetWare Error	UNSUCCESS SFUL	

On remote calls, in the structure returned for `returnedVolumeStatistics`, `GetVolumeStatistics` returns -1 in the `systemElapsedTime` field and -1 in the `startingBlock` field working as designed.

Remarks

If `structSize` is less than the size of `VOLUME_INFO`, then only the first `structSize` bytes of `VOLUME_INFO` are returned.

The following equations explain how to calculate available disk space in bytes:

- ♦ Total usable blocks = `availableBlocks` + `purgableBlocks` .
- ♦ Block size in bytes = `sectorsPerBlock` * 512.
- ♦ TOTAL AVAILABLE DISK SPACE in bytes = total usable blocks * block size in bytes.

The `VOLUME_INFO` structure, pointed to by the `returnedVolumeStatistics` parameter, has the following format:

```
long    systemElapsedTime;
BYTE    volumeNumber;
BYTE    logicalDriveNumber;
WORD    sectorsPerBlock;
short   startingBlock;
LONG    totalBlocks;
LONG    availableBlocks;
LONG    totalDirectorySlots;
LONG    availableDirecotrySlots;
BYTE    isHashing;
BYTE    isRemovable;
BYTE    isMounted;
char    volumeName[17];
LONG    purgableBlocks;
LONG    notyetPurgableBlocks;
```

The *isRemovable* field always returns true.

See Also

[GetVolumeInformation](#) (page 65), [GetVolumeInfoWithNumber](#) (page 68), [GetVolumeName](#) (page 70), [GetVolumeNumber](#) (page 72)

Example

```
#include <stdlib.h>
#include <stdio.h>
#include <stddef.h>
#include <fcntl.h>
#include <nwshare.h>
#include <nwbitops.h>
#include <nwfile.h>
#include <nwdir.h>
#include <nwtts.h>
#include <nwbindry.h>
#include <time.h>

main()
{
    int          rc;
    VOLUME_INFO  vs;
    char         svn[10];
    int          vn;

    printf("volume number: ");
    gets(svn);
    vn = atoi(svn);
    rc = GetVolumeStatistics(0,vn,sizeof (vs),&vs);
    if(rc)
```

```

    {
        printf("rc = %d\r\n",rc);
        printf("errno = %d\r\n",errno);
        printf("%s\r\n",strerror(errno));
    }
    else
    {
        printf("systemElapsedTime = %d\r\n",vs.systemElapsedTime);

        printf("volumeNumber = %d\r\n",vs.volumeNumber);

        printf("logicalDriveNumber = %d\r\n",vs.logicalDriveNumber);

        printf("sectorsPerBlock = %d\r\n",vs.sectorsPerBlock);

        printf("startingBlock = %d\r\n",vs.startingBlock);

        printf("totalBlocks = %d\r\n",vs.totalBlocks);
        printf("availableBlocks = %d\r\n",vs.availableBlocks);
        printf("totalDirectorySlots = %d\r\n",
            vs.totalDirectorySlots);
        printf("availableDirectorySlots = %d\r\n",
            vs.availableDirectorySlots);
        printf("isHashing = %d\r\n",vs.isHashing);
        printf("isRemovable = %d\r\n",vs.isRemovable);
        printf("isMounted = %d\r\n",vs.isMounted);

        printf("volumeName = %s\r\n",vs.volumeName);
    }
}

```

NWGetExtendedVolumeInfo

Returns extended volume information

Local Servers: blocking

Remote Servers: blocking

OES Server: OES 2015.0

Platform: Windows 7 or later

Service: Volume

Syntax

```
#include <\nlm\nit\nwdir.h>

extern int NWGetExtendedVolumeInfo (
    int          connNumber,
    char         *volName,
    NWVolExtendedInfo *volInfo);
```

Parameters

volNumber

(IN) Specifies the volume number.

volName

(IN) Specifies the volume name.

volInfo

(OUT) Points to NWVolExtendedInfo, which receives information.

Return Values

These are common return values; see [Return Values](#) (*Return Values for C*) for more information.

0x0000	SUCCESSFUL
0x8998	VOLUME_DOES_NOT_EXIST
0x897E	NCP_BOUNDARY_CHECK_FAILED
0x89FB	NO_SUCH_PROPERTY

Remarks

For more information, see [NWVolExtendedInfo](#) (page 55).

A Revision History

The following table outlines all the changes that have been made to the Volume Management documentation (in reverse chronological order):

January 6, 2016	Added NWGetDirSpaceInfoExt (page 12) , NWGetDirSpaceLimit (page 14) , NWGetExtendedVolumeInfoExt (page 20) , NWGetObjDiskRestrictionsExt (page 24) , NWGetVolumeDetailsByInfoMask (page 26) , NWScanVolDiskRestrictionsExt (page 40) , NWSetDirSpaceLimitExt (page 46) , NWSetObjectVolSpaceLimitExt (page 50) to support volume functions greater than 16 TB.
March 1, 2006	Updated format.
October 5, 2005	Transitioned to revised Novell documentation standards.
March 2, 2005	Fixed the legal information.
October 6, 2004	Fixed the preface.
February 18, 2004	Added links to sample code for the NWGetVolumeNumber (page 36) and NWGetExtendedVolumeInfo (page 18) functions.
October 8, 2003	Modified NWVolExtendedInfo (page 55) to indicate that the <code>statusFlag</code> field indicates whether the volume is an NSS volume.
July 30, 2003	Modified NWGetVolumeInfoWithNumber (page 31) , NWGetVolumeInfoWithHandle (page 28) , GetVolumeInformation (page 65) , GetVolumeStatistics (page 74) , and GetVolumeInfoWithNumber (page 68) to indicate that they do not return information about whether a volume is removable.
October 2002	Updated the information for NWScanMountedVolumeList (page 44) , to clarify that this function is supported on OES.
September 2002	Updated the information for NWGetVolumeName (page 34) and the Pascal syntax for NWVolMountNumWithName (page 59) .
May 2002	Updated the field descriptions of NWVolExtendedInfo (page 55) .
February 2002	Updated links.
October 2001	Added Pascal syntax to NWScanMountedVolumeList (page 44) and NWVolMountNumWithName (page 59) .
September 2001	Added support for NetWare 6.x to documentation.
June 2001	Updated tables.

February 2001	<p>Added Chapter 5, "Server-Based Volume Management Functions," on page 63, including volume functions moved from Multiple and Inter-File Services, and the server-based version of NWGetExtendedVolumeInfo (page 77).</p> <p>Added number of volumes allowed for OES to NWGetVolumeInfoWithNumber (page 31), GetVolumeName (page 70), and GetVolumeNumber (page 72) along with an explanation.</p> <p>Replaced "bindery objects" references with "objects" since these references can also apply to NDS objects.</p>
July 2000	<p>Removed obsolete function NWGetVolumeStats from Chapter 3, "Functions," on page 11.</p>
May 2000	<p>Added volume block size information and formula to NWGetExtendedVolumeInfo (page 18).</p> <p>Added restriction information to NWSetObjectVolSpaceLimit (page 48).</p> <p>Added Hi-Lo and byte swapping information to the <code>objectID</code> field of NWWOL_RESTRICTIONS (page 60).</p> <p>Fixed typographical errors in Return Values sections.</p>
March 2000	<p>Changed block sizes to 4K blocks and range to 0x40000000 in Remarks section of NWSetObjectVolSpaceLimit (page 48).</p>
November 1999	<p>Changed the description of NWGetObjDiskRestrictions (page 22) and added if the restriction is equal to 0x40000000 that the object has no restrictions.</p>
June 1999	<p>Added NWWolMountNumWithName (page 59) structure.</p>
