opentext™

NetIQ Security Solutions for IBM i

TGAudit 26.4 (v4.2)

Report Reference Guide

Revised June 2026

Legal Notice

THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT ARE FURNISHED UNDER AND ARE SUBJECT TO THE TERMS OF A LICENSE AGREEMENT OR A NON-DISCLOSURE AGREEMENT. EXCEPT AS EXPRESSLY SET FORTH IN SUCH LICENSE AGREEMENT OR NON-DISCLOSURE AGREEMENT, NETIQ CORPORATION PROVIDES THIS DOCUMENT AND THE SOFTWARE DESCRIBED IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME STATES DO NOT ALLOW DISCLAIMERS OF EXPRESS OR IMPLIED WARRANTIES IN CERTAIN TRANSACTIONS; THEREFORE, THIS STATEMENT MAY NOT APPLY TO YOU.

For purposes of clarity, any module, adapter or other similar material ("Module") is licensed under the terms and conditions of the End User License Agreement for the applicable version of the NetIQ product or software to which it relates or interoperates with, and by accessing, copying or using a Module you agree to be bound by such terms. If you do not agree to the terms of the End User License Agreement you are not authorized to use, access or copy a Module and you must destroy all copies of the Module and contact NetIQ for further instructions.

This document and the software described in this document may not be lent, sold, or given away without the prior written permission of NetIQ Corporation, except as otherwise permitted by law. Except as expressly set forth in such license agreement or non-disclosure agreement, no part of this document or the software described in this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, or otherwise, without the prior written consent of NetIQ Corporation. Some companies, names, and data in this document are used for illustration purposes and may not represent real companies, individuals, or data.

This document could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These changes may be incorporated in new editions of this document. NetIQ Corporation may make improvements in or changes to the software described in this document at any time.

U.S. Government Restricted Rights: If the software and documentation are being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), in accordance with 48 C.F.R. 227.7202-4 (for Department of Defense (DOD) acquisitions) and 48 C.F.R. 2.101 and 12.212 (for non-DOD acquisitions), the government’s rights in the software and documentation, including its rights to use, modify, reproduce, release, perform, display or disclose the software or documentation, will be subject in all respects to the commercial license rights and restrictions provided in the license agreement.

For information about NetIQ trademarks, see https://www.netiq.com/company/legal/.

Copyright © 2026 Trinity Guard LLC. All rights reserved.

What's New . . . 10
TGAudit Report Reference Introduction . . . 11
Authority Collection Reports . . . 12
Authority Collection for Object IFS Report . . . 13
Authority Collection for Object Native Report . . . 14
Authority Collection for Users and IFS Report . . . 15
Authority Collection for Users and Native Object Report . . . 16
Authority Collection Report (*ALL) . . . 17
Configuration Management Reports . . . 18
Access Control List Changes . . . 21
Actions that Affect a Job are Audited . . . 22
Active Job Information . . . 24
Advanced Analysis Command Configuration . . . 25
Adopting Authority from a Program Owner is Audited . . . 26
All Deletions of External Objects on the System are Audited . . . 27
All Object Creations are Audited . . . 28
All Optical Functions are Audited . . . 30
All Security Functions are Audited . . . 32
Alternate Subsystem Configurations . . . 35
Attention Events are Audited . . . 36
Auditing End Action set to Power Down System . . . 37
Authority Changes to Restored Objects . . . 38
Authorization Failures are Audited . . . 39
Authorization List or Object Authority Changes . . . 40
Basic Product Information on the System . . . 41
Certificate Details . . . 42
Certificates Expired . . . 43
Certificates Expiring in 90 Days . . . 44
Change Request Descriptor Changes . . . 45
Columns with Field Procedures . . . 46
Cryptographic Configuration Changes . . . 47
Current Cumulative PTF Level . . . 48
Current Job's Reply List Entry Information . . . 49
Dependencies of Row Permissions and Column Masks . . . 50
Disk Information . . . 51
DRDA and DDM User Access . . . 52
EIM Attribute Changes . . . 53
Environment Variable Changes . . . 54
Exit Point Information . . . 55
Exit Program Information . . . 56
Function Usage Configuration Details . . . 57
Function Usage Identifiers . . . 58
Group PTFs Information . . . 59
IBM i Temporary Storage Pool Detail . . . 60
IPv4 and IPv6 Network Connection Details . . . 61

Installed Products . . . 62
Job and Database Activity . . . 63
Job Description Details . . . 64
Job Descriptions that Contain User Profile Names were Restored . . . 65
Job Descriptions - USER Parameter Changes . . . 66
Job Descriptions with Logging . . . 67
Job Descriptions with Request Data . . . 68
Job Descriptions with Specific Initial Library Lists . . . 69
Job Schedule Entry Information . . . 70
Journal and Remote Journal Information . . . 71
Key Ring File Changes . . . 72
Limit Device Sessions Not Enabled . . . 73
Line Description Details . . . 74
Media Library Status Details . . . 75
Memory Pool Details . . . 76
Message Queue Data by Date Range . . . 77
Message Queue Data for All Queues . . . 78
Message Queue Data QSYSOPR . . . 79
Message Queue Data Severity Greater than 30 . . . 80
Message Queue Details . . . 81
Networking and Communications Functions are Audited . . . 82
Object Auditing Attribute Changes . . . 84
Object Lock Information . . . 85
Object Management Tasks are Audited . . . 86
OfficeVision Tasks are Audited . . . 88
Operating System Product Info . . . 90
Output Queue Details . . . 91
Ownership Changes for Restored Objects . . . 92
Partition Information . . . 93
Permission or Column Mask Defined . . . 94
Primary Group Changes for Restored Objects . . . 95
Printing Functions are Audited . . . 96
Product Information on the System . . . 97
Product Registration ID Information . . . 99
Products License Information . . . 100
Products with Load Errors . . . 101
Program Changes to Adopt Owner Authority . . . 102
Program Failures are Audited . . . 103
Programs Restored that Adopt Owner Authority . . . 105
Programs that Adopt Authority were Executed . . . 106
PTF Status for all Products . . . 107
PTFs Applied to the Licensed Internal Code . . . 108
PTFs for WDS . . . 109
PTFs Requiring IPL . . . 110
PTFs that are Loaded but not Applied . . . 111

Record Lock Information . . . 112
Restrict Use of Use Adopted Authority . . . 113
QHST Message Information . . . 114
QHST Messages with Severity Greater Than 40 . . . 115
Save and Restore Information is Audited . . . 116
Security Auditing Level . . . 118
Security Configuration Information . . . 119
Security System Values . . . 120
Server Security Data is Retained . . . 123
Server Security User Information Actions . . . 124
Service Tasks are Audited . . . 125
Service Tools Actions . . . 126
Software Product Information . . . 127
Spooled File Functions are Audited . . . 128
Spooled File in Output Queue . . . 129
Storage Usage by User Profile . . . 130
Strong System Security Level . . . 131
Subsystem Autostart Details . . . 132
Subsystem Communication Details . . . 133
Subsystem Information Details . . . 134
Subsystem Job Queue Details . . . 135
Subsystem Pool Data Details . . . 136
Subsystem Prestart Job Details . . . 137
Subsystem Remote Entries . . . 138
Subsystem Routing Entries . . . 139
Subsystem Routing Entry Changes . . . 140
Subsystem Workstation Names . . . 141
Subsystem Workstation Types . . . 142
Superseded PTFs . . . 143
System, User, and Object Auditing Control Configuration . . . 144
System Management Tasks are Audited . . . 145
System Software Resources . . . 147
System Value Changes . . . 148
System Value Configuration Changes . . . 149
System Value Configuration Details . . . 151
System Value Default Changes . . . 152
System Value Defaults . . . 154
System Value Valid Value Changes . . . 156
System Value Valid Values . . . 158
Systems Management Changes . . . 160
Time Adjustment Software Installed . . . 162
User Profile Changes . . . 163
User Profile Information . . . 164
Databases Management Reports . . . 165
Cross Reference Physical File . . . 166

Data Area Changes . . . 167
Database Access . . . 168
Database Changes . . . 169
Database Content . . . 170
Database Operations . . . 171
Database Operations by Journal . . . 172
Field Level Authorities . . . 173
Row and Column Access Control . . . 174
Schedule Master File . . . 175
Sensitive Database Content . . . 176
Log Management Reports . . . 177
Job Activity Details . . . 178
Job Activity Summary . . . 179
Network Management Reports . . . 180
Actions to IP Rules . . . 182
APPN Endpoint Filter Violations . . . 184
Asynchronous Signals Processed . . . 185
Cluster Operations . . . 186
Connections Started, Ended, or Rejected . . . 187
Controller Description Details . . . 188
Controllers and Attached Devices . . . 189
Database Server Initialization Report . . . 190
Database Server Native DB Report . . . 191
Database Server Object Info Report . . . 192
Database Server SQL Requests Report . . . 193
Device Description Data . . . 194
Device Descriptions - *APPC . . . 195
DNS Configuration Details . . . 196
FTP Client Operations - Certificate data . . . 197
Integrated File System Exits Installed . . . 198
Internet Security Management Events . . . 199
Inter-process Communication Events . . . 200
Intrusion Monitor Events . . . 201
NetServer Configuration . . . 203
NetServer Shares . . . 204
Network Attribute Details . . . 205
Network Authentication Events . . . 206
Network Connection Details . . . 208
Network Interface Details IPv4 . . . 209
Network Interface Details IPv6 . . . 210
Network Route Details IPv4 . . . 211
Network Route Details IPv6 . . . 212
Network Server Descriptions . . . 213
Network Server Encryption Status . . . 214
Network Servers with Encryption Verified . . . 215

Network Servers with Failed or Unknown Encryption . . . 216
Object Management Changes . . . 217
OfficeVision Mail Services Actions . . . 218
Remote Power On and IPL . . . 219
Remote Service Attribute . . . 220
Remote Sign-on Control . . . 221
Secure Socket Connections . . . 222
Server Sessions Started or Ended . . . 224
Server Share Information . . . 225
Service Status Change Events . . . 226
Sockets-related Exit Points Not Secured . . . 228
SSL Cipher Control and Specification List . . . 229
TCP_IP IPv4 Stack Attributes . . . 230
TCP_IP IPv6 Stack Attributes . . . 231
TELNET Server Attributes . . . 232
Unsecured Remote Server Exit Points . . . 233
Profile Management Reports . . . 235
All User Profiles . . . 237
Authority Failures . . . 238
Authority Restored for User Profiles . . . 240
Block Password Change . . . 241
Changes to Service Tools Profiles . . . 242
Connection Verifications . . . 243
Directory Server Extensions . . . 244
Disable Profile After Maximum Failed Signon Attempts . . . 245
Duplicate Password Control . . . 246
Enabled IBM Profiles . . . 248
Exceeded Account Limit Events . . . 249
Group Profile Information . . . 251
Group Profiles with *ALLOBJ *SECADM or *SERVICE Special Authorities . . . 252
Group Profiles with Passwords . . . 253
Group Profiles with Special Authorities . . . 254
IBM Profile Details Report . . . 255
Identity Token Events . . . 256
Inactive Job Message Queue . . . 258
Inactive Job Time-out . . . 259
Invalid Sign-on Attempts . . . 260
Limit Adjacent Digits in Password . . . 261
Limit Characters in Password . . . 262
Limit Password Character Positions . . . 263
Limit Repeating Characters in Password . . . 264
Limit Security Officer Device Access . . . 265
Maximum Password Length . . . 266
Minimum Password Length . . . 267
Network Attribute Changes . . . 268

Network Log on and Logoff Events . . . 269
Network Password Errors . . . 271
Network Profile Changes . . . 272
Object Authorities of User Profiles . . . 273
Ownership Changes for Restored Objects0 . . . 274
Password Expiration Interval . . . 275
Password Expiration Warning . . . 277
Password Level . . . 278
Password Rules . . . 280
Password Validation Program . . . 281
Powerful User Profiles . . . 282
Profile Object Auditing Values . . . 284
Profile with Password Expiration Interval not *SYSVAL . . . 285
Profiles that are *DISABLED . . . 286
Profiles with Expired Passwords . . . 287
Profiles with Limit Capabilities = *NO . . . 288
Profiles with Multiple Groups . . . 289
Profiles with Pwd = *NONE or *DISABLED . . . 290
Publicly Accessible User Profiles . . . 291
Require Digit in Password . . . 292
Security Officer Profiles . . . 293
Service Tool Security Attributes . . . 294
Swap Profile Events . . . 295
System Service Tools Users . . . 297
User Profile = Password . . . 298
User Profiles Not Used in 90 Days . . . 299
Users with Job Control Special Authority . . . 300
Users with Save System Special Authority . . . 301
Users with Unlimited Device Sessions . . . 302
Resource Management Reports . . . 303
*PUBLIC User with *RWX Authorities -*PUBLIC with *ALL . . . 306
Actions on Validation Lists . . . 307
Allow Object Restore Option . . . 309
Allow User Domain Objects in Libraries . . . 310
ASCII Files Stored in the IFS . . . 311
Attributes for QSYS.LIB . . . 312
Authorization List Details . . . 313
Authorization Lists with Public Access . . . 314
Authorized Users via Authorization Lists . . . 315
Change Request Descriptors Restored . . . 316
Changed Data Files in Last 30 Days . . . 317
Close Operations on Server Files . . . 318
Commands Available in QSH . . . 319
Commands Executed . . . 320
Configuration Files . . . 322

Create Operations . . . 323
Damages Objects . . . 324
Data Queue Entries . . . 325
Database Files Larger than 100Mb . . . 326
Database Files with Over 1,000,000 Read Operations . . . 327
Database Files with Over 100,000 Delete Operations . . . 328
Database Files with Over 100,000 Insert Operations . . . 329
Database Files with 10000 Delete Records . . . 330
Database Monitoring . . . 331
Db2 Mirror Communication Services . . . 332
Db2 Mirror Product Services . . . 333
Db2 Mirror Replication Services . . . 334
Db2 Mirror Replication State . . . 335
Db2 Mirror Setup Tools . . . 336
Delete Operations . . . 337
Directory Link, Unlink, and Search Operations . . . 338
Directory Search Violations . . . 339
DLO Object Changes . . . 340
DLO Object Reads . . . 341
Dual Optical Object Accesses . . . 342
Exit Point Maintenance Operations . . . 344
File Statistics . . . 346
File Usage Information . . . 348
Files Checked Out Status . . . 349
Files Not Secured by Authorization Lists . . . 350
Files Not Used in the Last 30 Days . . . 351
Files with RWX Authorities . . . 352
HTTP Server and Web Files Status . . . 353
HTTP Server File Authorities . . . 354
IFS Directory Information . . . 355
IFS Files Being Journaled . . . 356
Integrated File System Content . . . 357
Integrated File System Security . . . 358
Job Changes . . . 359
Job Descriptions - USER Parameter Changes . . . 361
Journaled Files . . . 362
Journaled Objects . . . 363
Largest Files Report >100Mb . . . 364
LDAP Operations . . . 365
Library QGPL Database Files not Backed up in 30 Days . . . 367
Library Statistics . . . 368
Maximum sign-on attempts allowed is NOMAX . . . 370
Network Resource Accesses . . . 371
New Data Files in Last 30 Days . . . 373
New Library in Last 30 Days . . . 374

New Objects in the Last 30 Days . . . 375
Object Authority . . . 376
Object Changes . . . 377
Object Details . . . 378
Object Ownership Changes . . . 379
Object Reads . . . 380
Object Source . . . 381
Object Statistics . . . 382
Objects Changed in the Last 30 Days . . . 383
Objects Created in the Last 30 Days . . . 384
Objects Larger than 100MB . . . 385
Objects Owned by QSECOFR . . . 386
Objects Restored . . . 387
Objects Used in the Last 30 Days . . . 388
Optical Volume Accesses . . . 389
Primary Group Changes . . . 391
Printer Output Changes . . . 392
Program Reference Details . . . 393
Programs that Adopt Authority . . . 394
PTF Object Changes . . . 395
PTF Operations . . . 396
Public Access to Commands in QSYS . . . 397
Public Access to Devices . . . 398
Public Access to Journal Receivers in QGPL . . . 399
Public Access to Objects in QGPL . . . 400
Regular Files on the IFS . . . 401
Restored Objects in the Last 30 Days . . . 402
Root *PUBLIC User with *RWX Authorities . . . 403
Single Optical Object Accesses . . . 404
Socket Descriptor Details . . . 405
Source Changes in Last 30 Days . . . 406
Spooled File Actions . . . 407
System Directory Changes . . . 409
System Security Audit Journal Exists . . . 411
TGAudit Report Configuration . . . 412
TGCentral Agent Configuration . . . 414
Unsaved Objects in the Last 30 Days . . . 416
User-defined File Systems (UDFS's) . . . 417
Verify Object on Restore . . . 418
Appendices . . . 420
APPENDIX - TGAudit Report Reference Revisions . . . 421
Version 4.2 - TGAudit Report Reference . . . 422
Version 4.1 - TGAudit Report Reference . . . 423
Version 4.0 - TGAudit Report Reference . . . 424
Version 3.4 - TGAudit Report Reference . . . 425

Version 3.3 - TGAudit Report Reference . . . 426
Version 3.2 - TGAudit Report Reference . . . 427
Version 3.1 - TGAudit Report Reference . . . 428
Version 3.0 - TGAudit Report Reference . . . 429
Version 2.5 - TGAudit Report Reference . . . 430
Version 2.4 - TGAudit Report Reference . . . 431
Version 2.3 - TGAudit Report Reference . . . 432
Version 2.2 - TGAudit Report Reference . . . 433
Version 2.1 - TGAudit Report Reference . . . 435
APPENDIX - TGAudit Collectors . . . 437

What's New

There were no major updates to the TGAudit Report Reference for this release.

See also

APPENDIX - TGAudit Report Reference Revisions

TGAudit Report Reference Introduction

This reference guide provides information about the built-in reports provided in TGAudit. Use this reference guide to learn why a report passed or failed in a pre-defined TGAudit Report Card, as well as learn information about report topics and recommendations on how to address existing vulnerabilities.

Note: Refer to the TGAudit User Guide for detailed information and concepts on how to use TGAudit.

The TGAudit reports fall into the following categories:

- Authority Collection Reports
- Configuration Management Reports
- Database Management Reports
- Log Management Reports
- Network Management Reports
- Profile Management Reports
- Resource Management Reports

Authority Collection Reports

This section includes descriptions of the following **Authority Collection** reports:

- Authority Collection for Object IFS Report
- Authority Collection for Object Native Report
- Authority Collection for Users and IFS Report
- Authority Collection for Users and Native Object Report
- Authority Collection Report (*ALL)

Authority Collection for Object IFS Report

If a user is enrolled in Authority Collection through the STRAUTCOL command with DLO and file system objects selected for inclusion, then the Authority Collection data collected for IFS objects will be displayed in this report. Information about current and required authorities to applications is displayed for enrolled users.

Collector ID: AUTHORITY_COL_IFS

Report ID: AUTHORITY_COL_IFS

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **4** (Authority Collection).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **20** (Authority Collection Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **4** (Auth Collection For Objects IFS Report).

7) Press **Enter**.

9) Modify the run criteria as necessary.

10) Press **Enter**.

See also

Resource Management Reports

Authority Collection for Object Native Report

If a user is enrolled in Authority Collection through the STRAUTCOL command, then the Authority Collection data collected for native (QSYS.LIB) objects will be displayed in this report. Information about current and required authorities to applications is displayed for enrolled users.

Collector ID: AUTHORITY_COL_OBJECT

Report ID: AUTHORITY_COL_OBJECT

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **4** (Authority Collection).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **20** (Authority Collection Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **3** (Auth Collection For Objects Native Report).

7) Press **Enter**.

9) Modify the run criteria as necessary.

10) Press **Enter**.

See also

Resource Management Reports

Authority Collection for Users and IFS Report

If a user is enrolled in Authority Collection through the STRAUTCOL command, then the Authority Collection data collected for IFS objects will be displayed in this report and categorized by user. Information about current and required authorities to applications is displayed for enrolled users.

⚠ **Important**: This report is only available for OS 7.3 or higher.

Collector ID: AUTHORITY_COLLECTION

Report ID: AUTHORITY_IFS

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **4** (Authority Collection).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter **20** (Authority Collection Reports).

5) Press **Enter**.

6 At the **Selection or command** prompt, enter **2** (Auth Collection For Users and Native Object Report).

7) Press **Enter**.

8) Modify the run criteria as necessary.

⚠ **Note**: The criteria allow you to limit the data returned in the report. To see field descriptions of common report criteria, see Run Reports.

Tip: Place your cursor in a field and press **F1** (Help) to access a field description. Press **F4** (Prompt) for a list of valid field options.

9) Press **Enter**. The status of the report is displayed at the bottom of the screen.

See also

Resource Management Reports

Authority Collection for Users and Native Object Report

If a user is enrolled in Authority Collection through the STRAUTCOL command, then the Authority Collection data collected for native (QSYS.LIB) objects will be displayed in this report and categorized by user. Information about current and required authorities to applications is displayed for enrolled users.

Important: This report is only available for OS 7.3 or higher.

Collector ID: AUTHORITY_COLLECTION

Report ID: AUTHORITY_OBJECTS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **4** (Authority Collection).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (Authority Collection Reports).
5) Press **Enter**.
6 At the **Selection or command** prompt, enter **1** (Auth Collection For Users and Native Object Report).
7) Press **Enter**.
8) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report. To see field descriptions of common report criteria, see Run Reports.

Tip: Place your cursor in a field and press **F1** (Help) to access a field description. Press **F4** (Prompt) for a list of valid field options.

9) Press **Enter**. The status of the report is displayed at the bottom of the screen.

See also

Resource Management Reports

Authority Collection Report (*ALL)

If a user is enrolled in Authority Collection through the STRAUTCOL command with DLO and file system objects selected for inclusion, then the Authority Collection data collected for all objects will be displayed in this report. Information about current and required authorities to applications is displayed for enrolled users.

Important: This report is only available for OS 7.4 or higher.

Collector ID: AUTHORITY_COL_ALL

Report ID: AUTHORITY_COL_ALL

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **4** (Authority Collection).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **20** (Authority Collection Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Auth Collection Report *ALL).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Configuration Management Reports

This section includes descriptions of the following **Configuration Management** reports:

- Access Control List Changes
- Actions that Affect a Job are Audited
- Active Job Information
- Advanced Analysis Command Configuration
- Adopting Authority from a Program Owner is Audited
- All Deletions of External Objects on the System are Audited
- All Object Creations are Audited
- All Optical Functions are Audited
- All Security Functions are Audited
- Alternate Subsystem Configurations
- Attention Events are Audited
- Auditing End Action set to Power Down System
- Authority Changes to Restored Objects
- Authorization Failures are Audited
- Authorization List or Object Authority Changes
- Basic Product Information on the System
- Certificate Details
- Certificates Expired
- Certificates Expiring in 90 Days
- Change Request Descriptor Changes
- Columns with Field Procedures
- Cryptographic Configuration Changes
- Current Cumulative PTF Level
- Current Job's Reply List Entry Information
- Dependencies of Row Permissions and Column Masks
- Disk Information
- DRDA and DDM User Access
- EIM Attribute Changes
- Environment Variable Changes
- Exit Point Information
- Exit Program Information
- Function Usage Configuration Details
- Function Usage Identifiers
- Group PTFs Information
- IBM i Temporary Storage Pool Detail
- IPv4 and IPv6 Network Connection Details
- Installed Products
- Job and Database Activity
- Job Description Details
- Job Descriptions that Contain User Profile Names were Restored
- Job Descriptions - USER Parameter Changes
- Job Descriptions with Logging
- Job Descriptions with Request Data
- Job Descriptions with Specific Initial Library Lists
- Job Schedule Entry Information

- Journal and Remote Journal Information
- Key Ring File Changes
- Limit Device Sessions Not Enabled
- Line Description Details
- Media Library Status Details
- Memory Pool Details
- Message Queue Data by Date Range
- Message Queue Data for All Queues
- Message Queue Data QSYSOPR
- Message Queue Data Severity Greater than 30
- Message Queue Details
- Networking and Communications Functions are Audited
- Object Auditing Attribute Changes
- Object Lock Information
- Object Management Tasks are Audited
- OfficeVision Tasks are Audited
- Operating System Product Info
- Output Queue Details
- Ownership Changes for Restored Objects
- Partition Information
- Permission or Column Mask Defined
- Primary Group Changes for Restored Objects
- Printing Functions are Audited
- Product Information on the System
- Product Registration ID Information
- Products License Information
- Products with Load Errors
- Program Changes to Adopt Owner Authority
- Program Failures are Audited
- Programs Restored that Adopt Owner Authority
- Programs that Adopt Authority were Executed
- PTF Status for all Products
- PTFs Applied to the Licensed Internal Code
- PTFs for WDS
- PTFs Requiring IPL
- PTFs that are Loaded but not Applied
- Record Lock Information
- Restrict Use of Use Adopted Authority
- QHST Message Information
- QHST Messages with Severity Greater Than 40
- Save and Restore Information is Audited
- Security Auditing Level
- Security Configuration Information
- Security System Values
- Server Security Data is Retained
- Server Security User Information Actions
- Service Tasks are Audited
- Service Tools Actions
- Software Product Information
- Spooled File Functions are Audited

- Spooled File in Output Queue
- Storage Usage by User Profile
- Strong System Security Level
- Subsystem Autostart Details
- Subsystem Communication Details
- Subsystem Information Details
- Subsystem Job Queue Details
- Subsystem Pool Data Details
- Subsystem Prestart Job Details
- Subsystem Remote Entries
- Subsystem Routing Entries
- Subsystem Routing Entry Changes
- Subsystem Workstation Names
- Subsystem Workstation Types
- Superseded PTFs
- System, User, and Object Auditing Control Configuration
- System Management Tasks are Audited
- System Software Resources
- System Value Changes
- System Value Configuration Changes
- System Value Configuration Details
- System Value Default Changes
- System Value Defaults
- System Value Valid Value Changes
- System Value Valid Values
- Systems Management Changes
- Time Adjustment Software Installed
- User Profile Changes
- User Profile Information

See also

TGAudit Report Reference Introduction

Access Control List Changes

This report displays changes to Access Control Lists. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VA.

Collector ID: JOURNAL_VA

Report ID: *BASE

Tip: For VA journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = VA journal entries were not found in QAUDJRN.

FAIL = VA journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **21** (Access Control List Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Actions that Affect a Job are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *JOBDTA is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_JOBDTA

PASS = Value *JOBDTA is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * JOBDTA is not specified in QAUDLVL or QAUDLVL2 system value.

Actions that affect a job are audited. (*JOBDTA) The following are some examples:

- Job start and stop data
- Hold, release, stop, continue, change, disconnect, end, end abnormal, PSR-attached to prestart job entries
- Changing a thread's active user profile or group profiles

*JOBBAS

*JOBCHGUSR

When you have this value set, the following security audit journal entry types are generated:

JS – A change was made to job data

SG – Asynchronous signals

VC – Connection started or ended

VN – A logon or logoff operation on the network

VS – A server session started or ended

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Actions that Affect a Job are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Configuration Management Reports

Active Job Information

This report displays a list of active jobs.

Collector ID: QSYS2.ACTIVE_JOB_INFO

Report ID: QSYS2_ACTIVE_JOB_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.
8) Press **Enter**.

See also

Configuration Management Reports

Advanced Analysis Command Configuration

This report displays a list of modifications to the advanced analysis commands.

Collector ID: JOURNAL_C3

Report ID: *BASE

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Adopting Authority from a Program Owner is Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *PGMADP is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_PGMADP

PASS = Value *PGMADP is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *PGMADP is not specified in QAUDLVL or QAUDLVL2 system value.

Adopting authority from a program owner is audited. (*PGMADP)

When you have this value set, the following security audit journal entry types are generated:

AP – A change was made to program adopt

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Adopting Authority from a Program Owner is Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

All Deletions of External Objects on the System are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *DELETE is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_DELETE

PASS = Value *DELETE is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * DELETE is not specified in QAUDLVL or QAUDLVL2 system value.

When you have this value set, the following security audit journal entry types are generated:

DO – Object deleted. Pending delete committed. Pending create rolled back. Delete pending. Pending delete rolled back.

DI – Object deleted.

XD – Group names (associated with DI entry)

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **4** (All Deletions of External Objects on the System are Audited).

9) Press **Enter**.

10) Modify the run criteria as necessary.

11) Press **Enter**.

See also

Configuration Management Reports

All Object Creations are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *CREATE is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_CREATE

PASS = Value *CREATE is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *CREATE is not specified in QAUDLVL or QAUDLVL2 system value.

All object creations are audited. (*CREATE) Objects created in library QTEMP are not audited. The following are some examples:

- Newly-created objects
- Objects created to replace an existing object

When you have this value set, the following security audit journal entry types are generated:

CO - Creation of a new object, except creation of objects in QTEMP library.

DI - Object created.

XD - Group names (associated with DI entry)

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (All Object Creations are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

All Optical Functions are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *OPTICAL is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_OPTICAL

PASS = Value *OPTICAL is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * OPTICAL is not specified in QAUDLVL or QAUDLVL2 system value.

All optical functions are audited. (*OPTICAL) The following are some examples:

- Add or remove optical cartridge
- Change the authorization list used to secure an optical volume
- Open optical file or directory
- Create or delete optical directory
- Change or retrieve optical directory attributes
- Copy, move, or rename optical file
- Copy optical directory
- Back up optical volume
- Initialize or rename optical volume
- Convert backup optical volume to a primary volume
- Save or release held optical file
- Absolute read of an optical volume

When you have this value set, the following security audit journal entry types are generated:

O1 - Single optical object access

O2- Dual optical object access

O3- Optical volume access

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **6** (All Optical Functions are Audited).

9) Press **Enter**.

10) Modify the run criteria as necessary.

11) Press **Enter**.

See also

Configuration Management Reports

All Security Functions are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *SECURITY is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_SECURITY

PASS = Value *SECURITY is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *SECURITY is not specified in QAUDLVL or QAUDLVL2 system value.

Note: *SECURITY is composed of several values to allow you to better customize your auditing. If you specify all of the values, you will get the same auditing as if you specified *SECURITY. The following values make up *SECURITY.

- *SECCFG
- *SECDIRSRV
- *SECIPC
- *SECNAS
- *SECRUN
- *SECSCKD
- *SECVFY
- *SECVLDL

All security-related functions are audited (*SECURITY).

- Security configuration
- Changes or updates when doing directory service functions
- Changes to inter-process communications
- Network authentication service actions
- Security run time functions
- Socket descriptor
- Use of verification functions
- Changes to validation list objects

When you have this value set, the following security audit journal entry types are generated:

AD - A change was made to the auditing attribute

X1- Identity token

AU - Attribute change

CA - Changes to object authority (authorization list or object)

CP - Create, change, and restore user profiles

CV - Connection verification

CY - Cryptographic configuration

DI - Directory services

DS - DST security officer password reset

EV - Environment variable

GR - General purpose audit record

GS - A descriptor was given

IP - Inter-process communication event

JD - Changes to the USER parameter of a job description

KF - Key ring file name

NA - Changes to network attributes

OW - Changes to object ownership

PA - Changes to programs (CHGPGM) that will now adopt the owner's authority

PG - Changes to an object's primary group

PS - Profile swap

SE - Changes to subsystem routing

SO - A change was made by server security

SV - Changes to system values

VA - Changes to access control list

VO - Actions on validation lists

VU - A network profile was changed

X0 - Network authentication

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **7** (All Security Functions are Audited).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Alternate Subsystem Configurations

This report returns information about the users who have alternate subsystem configurations for some IBM i servers. When a user profile listed in this view attempts to use TCP/IP to form a connection to the server, an attempt is made to use the alternate subsystem instead of the default subsystem for that server.

Collector ID: QSYS2.SERVER_SBS_ROUTING

Report ID: QSYS2_SERVER_SBS_ROUTING

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.
8) Press **Enter**.

See also

Configuration Management Reports

Attention Events are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *ATNEVT is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_ATNEVT

PASS = Value *ATNEVT is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *ATNEVT is not specified in QAUDLVL or QAUDLVL2 system value.

Tip: Attention events are audited. (*ATNEVT) Attention events are conditions that require further evaluation to determine the condition's security significance.

The following is an example: Intrusion monitor events need to be examined to determine whether the condition is an intrusion or a false positive

When you have this value set, it generates security audit journal entries of type IM in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Attention Events are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Auditing End Action set to Power Down System

This report displays the value of the QAUDENDACN (Auditing End Action) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QAUDENDACN

PASS = System value QRETSVRSEC is set to *PWRDWNSYS

FAIL = System value QRETSVRSEC is set to *NOTIFY.

The Auditing End Action system value specifies the action that should be taken by the system when audit records cannot be sent to the auditing journal because of errors that occur when the journal entry is sent.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Authority Changes to Restored Objects

This report displays authority changes to restored objects. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is RA.

Collector ID: JOURNAL_RA

Report ID: *BASE

Tip: For RA journal entries to be generated, the QAUDLVL system value must contain *SAVRST. Also, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = RA journal entries were not found in QAUDJRN.

FAIL = RA journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Authority Changes to Restored Objects).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Authorization Failures are Audited

Authorization List or Object Authority Changes

This report displays changes to object authorities. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CA.

Collector ID: JOURNAL_CA

Report ID: *BASE

Tip: For CA journal entries to be generated, the QAUDLVL system value must contain *SECRUN and *SECURITY.

PASS = CA journal entries were not found in QAUDJRN.

FAIL = CA journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Authorization List or Object Authority Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Basic Product Information on the System

This report displays product information.

Collector ID: PRODUCT_INFO

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Basic Product Information on the System).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Certificate Details

This report displays the details of your security certificates.

Collector ID: KEYSTORE_DATA

Report ID: CERTIFICATE_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **10** (Keystore Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Certificate Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Certificates Expired

This report displays expired security certificates.

Collector ID: KEYSTORE_DATA

Report ID: CERTIFICATE_EXPIRED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **10** (Keystore Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Certificates Expired).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Certificates Expiring in 90 Days

This report displays security certificates that will expire in 90 days.

Collector ID: KEYSTORE_DATA

Report ID: CERTIFICATE_EXP90

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **10** (Keystore Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Certificates Expiring in 90 Days).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Change Request Descriptor Changes

This report displays changes made to Change Requestor Descriptors. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CQ.

Collector ID: JOURNAL_CQ

Report ID: *BASE

Tip: For CQ journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = CQ journal entries were not found in QAUDJRN.

FAIL = CQ journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Change Request Descriptor Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Columns with Field Procedures

This report displays the characteristics of columns and fields within a database table.

Collector ID: ACCESS_ESCAL_ACC_CONTROL

Report ID: SYSFIELDS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Cryptographic Configuration Changes

This report displays changes to cryptographic configuration. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CY.

Collector ID: JOURNAL_CY

Report ID: *BASE

PASS = CY journal entries were not found in QAUDJRN.

FAIL = CY journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Cryptographic Configuration Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Configuration Management Reports

Current Cumulative PTF Level

This report displays the current Cumulative PTF level for the operating system. Cumulative PTF ID's begin with "TC" and are followed by a numerical value. The highest numerical value represents the most recently installed Cumulative PTF.

Keeping current with Cumulative PTF packages is a very important part of maintaining your operating system and limiting exposure to vulnerabilities.

Collector ID: PTF_DATA

Report ID: PTF_TO_GET_CUMULATIVE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Current Cumulative PTF Level).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Current Job's Reply List Entry Information

This report displays the list of current jobs and the associated entry information.

Collector ID: QSYS2.REPLY_LIST_INFO

Report ID: QSYS2_REPLY_LIST_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Dependencies of Row Permissions and Column Masks

This report displays the dependencies of row permissions and column masks.

Collector ID: QSYS2.SYSCONTROLSDEP

Report ID: QSYS2_SYSCONTROLSDEP

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Disk Information

This report displays information about the disk.

Collector ID: QSYS2.SYSDISKSTAT

Report ID: QSYS2_SYSDISKSTAT

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

DRDA and DDM User Access

This report displays DRDA and DDM User access.

Collector ID: QSYS2.DRDA_AUTHENTICATION

Report ID: QSYS2_DRDA_AUTHENTICATION

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

EIM Attribute Changes

This report displays Enterprise Identity Mapping (EIM) configuration attribute changes. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is AU.

Collector ID: JOURNAL_AU

Report ID: *BASE

Tip: For AU journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = AU journal entries were not found in QAUDJRN.

FAIL = AU journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (EIM Attribute Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Environment Variable Changes

This report displays changes to Environment Variables. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is EV.

Collector ID: JOURNAL_EV

Report ID: *BASE

Tip: For EV journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = EV journal entries were not found in QAUDJRN.

FAIL = EV journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Environment Variable Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Exit Point Information

This report displays lists of registration information. The data returned can also be obtained by running the WRKREGINF CL command and by the Retrieve Exit Information (QUSRTVEI, QusRetrieveExitInformation) API.

Collector ID: QSYS2.EXIT_POINT_INFO

Report ID: EXIT_POINT_INFO

Note: See the IBM documentation for additional information: https://www.ibm.com/support/pages/ibm-i-74-tr3-enhancements

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Exit Program Information

This report displays the lists exit program details. The data returned can also be obtained by running the WRKREGINF CL command and by the Retrieve Exit Information (QUSRTVEI, QusRetrieveExitInformation) API.

Collector ID: QSYS2.EXIT_PROGRAM_INFO

Report ID: EXIT_PROGRAM_INFO

Note: See the IBM documentation for additional information: https://www.ibm.com/support/pages/ibm-i-74-tr3-enhancements

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Function Usage Configuration Details

This report displays function usage configuration details. The detail returned corresponds to the data returned by the Retrieve Function Usage Information (QSYRTFUI, QsyRetrieveFunctionUsageInfo) API.

Collector ID: QSYS2.FUNCTION_USAGE

Report ID: QSYS2_FUNCTION_USAGE

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Function Usage Identifiers

This report displays details about function usage identifiers.

Collector ID: QSYS2.FUNCTION_INFO

Report ID: QSYS2_FUNCTION_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Group PTFs Information

This report displays information about the group PTFs for the server.

Collector ID: QSYS2.GROUP_PTF_INFO

Report ID: QSYS2_GROUP_PTF_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

IBM i Temporary Storage Pool Detail

This report displays the IBM i temporary storage pool detail.

Collector ID: QSYS2.SYSTMPSTG

Report ID: QSYS2_GROUP_PTF_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

IPv4 and IPv6 Network Connection Details

This report displays IPv4 and IPv6 connection details.

Collector ID: QSYS2.NETSTAT_JOB_INFO

Report ID: QSYS2_NETSTAT_JOB_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Installed Products

This report displays information for all products currently installed on the system. All product options for each Product ID are included.

Collector ID: PRODUCT_INFO

Report ID: Installed_Products

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Installed Products).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Configuration Management Reports

Job and Database Activity

This report display job and database activities.

Connector ID: JOB_DATABASE_ACTIVITY

Report ID: JOB_DATABASE_ACTIVITY

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **4** (Job Activity Monitor).
3) Press **Enter**.
   The **Job Activity Monitor Menu** interface is displayed.
4) At the **Selection or command** prompt, enter **4** (Job and Database Activity).
5) Press **Enter**.
   The **TG - Run Report (TGRPT)** interface is displayed.
6) Modify the report run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report. To see field descriptions of common report criteria, see Run Reports.

> **Tip**: Place your cursor in a field and press **F1** (Help) to access a field description. Press **F4** (Prompt) for a list of valid field options.

7) Enter the desired output format in the **Report output type** field.
8) Press **Enter**.
   The status of the report is displayed at the bottom of the screen.

See also

Configuration Management Reports

Job Description Details

This report displays all job descriptions on the system, as well as configuration information about each.

Collector ID: JOB_DESCSRIPTIONS

Report ID: JOB_DESCRIPTION_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Job Description Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Job Description Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Job Descriptions that Contain User Profile Names were Restored

This report displays job descriptions restored that had a user profile name in the USER parameter. The data related to this report is retrieved from the system security audit journal (QAUDJRN. The journal entry type associated with this event is RJ.

Collector ID: JOURNAL_RJ

Report ID: *BASE

Tip: For RJ journal entries to be generated, the QAUDLVL system value must contain *SAVRST.

PASS = RJ journal entries were not found in QAUDJRN.

FAIL = RJ journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **11** (Job Descriptions that Contain User Profile Names were Restored).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Job Descriptions - USER Parameter Changes

This report displays changes to the USER parameter of Job Descriptions. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is JD.

Collector ID: JOURNAL_JD

Report ID: *BASE

Tip: For JD journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = JD journal entries were not found in QAUDJRN.

FAIL = JD journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Job Descriptions with Logging

This report displays information about job descriptions on the system that have logging defined as anything other than 0, 99, *NOLIST, *NO.

Collector ID: JOB_DESCSRIPTIONS

Report ID: JOB_DESCRIPTION_LOGGING

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Job Description Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Job Descriptions with Logging).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Job Descriptions with Request Data

This report displays information about job descriptions on the system that have Request Data values defined.

Collector ID: JOB_DESCSRIPTIONS

Report ID: JOB_DESCRIPTIONS_REQUEST_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Job Description Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Job Descriptions with Request Data).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Job Descriptions with Specific Initial Library Lists

This report displays information about job descriptions on the system that have initial library lists defined as anything other than *SYSVAL.

Collector ID: JOB_DESCSRIPTIONS

Report ID: JOB_DESCRIPTIONS_LIBL

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Job Description Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Job Descriptions with Specific Initial Library List).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Job Schedule Entry Information

This report displays information that can also be seen through the Work with Job Schedule Entries (WRKJOBSCDE) command interface. Each job schedule entry contains the information to automatically submit a batch job once or at regularly scheduled intervals.

Collector ID: QSYS2.SCHEDULED_JOB_INFO

Report ID: QSYS2_SCHEDULED_JOB_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Journal and Remote Journal Information

This report displays information about journals, including remote journals. The values returned for the columns in the view are closely related to the values returned by the QjoRetrieveJournalInformation() API. Refer to the API for more detailed information.

Collector ID: QSYS2.JOURNAL_INFO

Report ID: QSYS2_JOURNAL_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Key Ring File Changes

This report displays changes to Key Ring Files which store certificates. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is KF.

Collector ID: JOURNAL_KF

Report ID: *BASE

Tip: For KF journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *SECCFG, and *SECURITY.

PASS = KF journal entries were not found in QAUDJRN.

FAIL = KF journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Key Ring File Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Limit Device Sessions Not Enabled

This report displays the value of the QLMTDEVSSN (Limit Device Sessions) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QLMTDEVSSN

Tip: The Limit Device Sessions system value controls the number of device sessions a user can sign on. This does not prevent the user from using group jobs or making a system request (pressing the System Request key) at the same workstation.

PASS = System value QLMTDEVSSN is set to 1 - 9.

FAIL = System value QLMTDEVSSN is set to 0.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Line Description Details

This report displays configuration information about line descriptions available on the system. Line description configuration is crucial for ensuring system communications are available.

Collector ID: LINE_DESCRIPTION_DATA

Report ID: LINE_DESCRIPTION_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Line Description Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Media Library Status Details

This report displays information that can also be seen through the Work with Media Library Status (WRKMLBSTS) command interface.

Collector ID: QSYS2.MEDIA_LIBRARY_INFO

Report ID: QSYS2_MEDIA_LIBRARY_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Memory Pool Details

This report displays one row for every pool.

Collector ID: QSYS2.MEMORY_POOL

Report ID: QSYS2_MEMORY_POOL

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Message Queue Data by Date Range

This report shows messages for a date range.

Collector ID: QSYS2.MESSAGE_QUEUE_INFO

Report ID: MESSAGE_QUEUE_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Message Queue Data by Time Range).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Message Queue Data for All Queues

This report displays all messages in all message queues on the system. If you need message data for a particular user or a particular message ID or severity, this is a good report to copy and edit to suit the needs of your search.

Collector ID: MESSAGE_QUEUE_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Message Queue Data for All Queues).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

[Configuration Management Reports]

Message Queue Data QSYSOPR

This report shows all messages in the QSYSOPR system operator message queue. Important messages regarding the operations of the overall system are sent to this message queue and should monitored frequently to ensure system operations are not interrupted and important system functions are operating normally.

Collector ID: MESSAGE_QUEUE_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Message Queue Data QSYSOPR).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Message Queue Data Severity Greater than 30

This report shows messages that have a severity of 30 or higher. Messages with a severity of 30 or higher indicate errors that have occurred on the system and should be monitored to ensure significant issues do not exist and disrupt system operations.

Collector ID: MESSAGE_QUEUE_DATA

Report ID: MESSAGE_QUEUE_DATA_SEV_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Message Queue Data Severity Greater than 30).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Message Queue Details

This report contains general information about message queues defined on the system, such as the number of messages in each queue, the message delivery type, break handling programs, storage information, etc.

Collector ID: MESSAGE_QUEUE

Report ID: MESSAGE_QUEUE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Message Queue Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Networking and Communications Functions are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *NETCMN is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_NETCMN

PASS = Value *NETCMN is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * NETCMN is not specified in QAUDLVL or QAUDLVL2 system value.

Networking and communications functions are audited (*NETCMN). The following are some examples:

- Network base functions (See *NETBAS)
- Cluster or cluster resource group operations (See *NETCLU)
- Network failures (See *NETFAIL)
- Sockets functions (See *NETSCK)

When you have this value set, the following security audit journal entry types are generated:

CU - Creation of an object by the cluster control operation.

CV - Connection established. Connection ended normally.

IR - IP rules have been loaded from a file.

IS - Internet security management

ND - Directory search violations

NE - End point violations

SK - Secure sockets connection

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **12** (Networking and Communications Functions are Audited).

9) Press **Enter**.

10) Modify the run criteria as necessary.

11) Press **Enter**.

See also

Configuration Management Reports

Object Auditing Attribute Changes

This report displays changes made to auditing attributes of objects. The data on this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is AD.

Collector ID: JOURNAL_AD

Report ID: *BASE

Tip: For AD journal entries to be generated, the QAUDLVL system value must contain values *SECCFG and *SECURITY. Also, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = AD journal entries were not found in QAUDJRN.

FAIL = AD journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Object Auditing Attribute Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Object Lock Information

This report displays one row for every lock held for every object on the partition.

Collector ID: QSYS2.OBJECT_LOCK_INFO

Report ID: QSYS2_OBJECT_LOCK_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Object Management Tasks are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *OBJMGT is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_OBJMGT

PASS = Value *OBJMGT is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * OBJMGT is not specified in QAUDLVL or QAUDLVL2 system value.

Generic object tasks are audited (*OBJMGT). The following are some examples:

- Moves of objects
- Renames of objects

When you have this value set, the following security audit journal entry types are generated:

DI - Object rename

OM - An object was moved to a different library

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (Object Management Tasks are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

OfficeVision Tasks are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *OFCSRV is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_OFCSRV

PASS = Value *OFCSRV is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value * OFCSRV is not specified in QAUDLVL or QAUDLVL2 system value.

OfficeVision tasks are audited (*OFCSRV). The following are some examples:

- Changes to the system distribution directory
- Tasks involving electronic mail

When you have this value set, the following security audit journal entry types are generated:

ML - A mail log was opened.

SD - A change was made to the system distribution directory.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (OfficeVision Tasks are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Operating System Product Info

This report displays information related to the current version of the Operating System (OS) installed. Several product options are typically associated with the OS licensed product.

Collector ID: SOFTWARE_RESOURCES

Report ID: OS400_Product_Installed

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Operating System Product Info).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Output Queue Details

This report displays all output queues on the system, as well as configuration information about each.

Collector ID: OUTPUT_QUEUE

Report ID: OUTPUT_QUEUE_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Output Queue Details).
7) Press **Enter**.
8) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

9) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Ownership Changes for Restored Objects

This report displays ownership changes to objects during restore operations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is RO.

Collector ID: JOURNAL_RO

Report ID: *BASE

Tip: For RO journal entries to be generated, the QAUDLVL system value must contain *SAVRST. Also, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = RO journal entries were not found in QAUDJRN.

FAIL = RO journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **12** (Ownership Changes for Restored Objects).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Partition Information

This report displays a single row containing details about the current partition.

Collector ID: QSYS2.SYSTEM_STATUS_INFO

Report ID: QSYS2_SYSTEM_STATUS_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Permission or Column Mask Defined

This report displays one row for each row permission or column mask defined by the CREATE PERMISSION or CREATE MASK statements.

Collector ID: QSYS2.SYSCONTROLS

Report ID: QSYS2_SYSCONTROLS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Primary Group Changes for Restored Objects

This report displays changes to Primary Groups for objects during restore operations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is RZ.

Collector ID: JOURNAL_RZ

Report ID: *BASE

Tip: For RZ journal entries to be generated, the QAUDLVL system value must contain *SAVRST. Also, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = RZ journal entries were not found in QAUDJRN.

FAIL = RZ journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (Primary Group Changes for Restored Objects).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Printing Functions are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *PRTDTA is specified.

Collector ID: SYSTEM_VALUES

Report ID: QSYS2_SYSCONTROLS

PASS = Value *PRTDTA is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *PRTDTA is not specified in QAUDLVL or QAUDLVL2 system value.

Printing functions are audited (*PRTDTA). The following are some examples:

- Printing a spooled file
- Printing with parameter SPOOL(*NO)

When you have this value set, the following security audit journal entry types are generated:

PO - A change was made to printed output

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **14** (Printing Functions are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Product Information on the System

This report displays all the software license product information available on the system. Information is shown for products that are installed as well as for products that are not installed.

Collector ID: PRODUCT_INFO

Report ID: PRODUCT_INFORMATION

The list of products displayed can be in the following Load States:

- All installed products.
- All supported products.
- All defined products.
- A user-specified subset of all defined products.
- All products that are supported, installed, or both installed and supported.

Note: A product can be supported and unsupported by using the Work with Supported Products (WRKSPTPRD) command. This command is part of the System Manager for i5/OS® licensed program.

A defined product is one which is known to the system. This includes all installed products, but also includes products which are known to the system without the products being installed. For example, V5R4M0 of the System Manager for i5/OS licensed program (5722SM1) is known to the system once V5R4M0 of the operating system is installed. Therefore V5R4M0 of 5722SM1 is a defined product once V5R4M0 of the operating system is installed.

A product is also a defined product when a product definition (*PRDDFN) object exists for that product on the system.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Basic Product Information on the System).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Product Registration ID Information

This report displays Registration ID information for licensed products. A combination of the registration type and registration value makes up the Registration ID for a product.

Collector ID: PRODUCT_INFO

Report ID: PRODUCT_REGISTRATION

The registration type associated with the product could have the following values:

02	Registration type *PHONE was specified when the product load or product definition was created.
04	The registration value is the same as the registration value for i5/OS®.
08	Registration type *CUSTOMER was specified when the product load or product definition was created.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Product Registration ID Information).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Products License Information

This report displays information about all products or features that contain license information.

Collector ID: QSYS2.LICENSE_INFO

Report ID: QSYS2_LICENSE_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Products with Load Errors

This report displays products with Load Errors. Data on this report is determined by the Check Product Option (CHKPRDOPT) command.

A Load Error can be caused by a restore, delete, or save licensed program function that might be in progress or might not have completed. The product may need to be reloaded to rectify the issue.

Collector ID: PRODUCT_INFO

Report ID: PRODUCT_WITH_LOAD_ERRORS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Products with Load Errors).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Program Changes to Adopt Owner Authority

This report displays the program adopt details. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is PA.

Collector ID: JOURNAL_PA

Report ID: *BASE

Tip: For PA journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = PA journal entries were not found in QAUDJRN.

FAIL = PA journal entries were found in QAUDJRN.

Types of entries:

A - Change program to adopt owner's authority.

J - Java program adopts owner's authority.

M - Change object's SETUID, SETGID, or Restricted rename and unlink mode indicator.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (Program Changes to Adopt Owner Authority).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Report

Program Failures are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *PGMFAIL is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_PGMFAIL

PASS = Value *PGMFAIL is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *PGMFAIL is not specified in QAUDLVL or QAUDLVL2 system value.

Program failures are audited (*PGMFAIL). The following are some examples:

- Blocked instruction
- Validation value failure
- Domain violation

When you have this value set, the following security audit journal entry types are generated:

AF - All authority failures

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (Program Failures are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Programs that Adopt Authority were Executed

This report displays program executions where the programs inherited the authority of the program user or program owner. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is AP.

Collector ID: JOURNAL_AP

Report ID: *BASE

Tip: For AP journal entries to be generated, the QAUDLVL system value must contain *PGMADP.

PASS = AP journal entries were not found in QAUDJRN.

FAIL = AP journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Programs that Adopt Authority were Executed).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

PTF Status for all Products

This report displays the Program Temporary Fix (PTF) status and related information for all licensed products installed on the system.

Collector ID: PTF_DATA

Report ID: DISPLAY_PTF_STATUS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (PTF Status for all Products).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

PTFs Applied to the Licensed Internal Code

This report displays PTFs which have been applied to the Licensed Internal Code (LIC). The data displayed in this report is based on the Product ID ending with 999 and having a PTF status of permanently or temporarily applied.

The LIC Product ID changes based on OS version. For example, the LIC Product ID for V6R1 is 5761999 and, for V7R1, it is 5770999.

Collector ID: PTF_DATA

Report ID: LIC_PTFS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (PTFs Applied to the Licensed Internal Code).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

PTFs for WDS

This report displays PTFs that are installed on the system for WebSphere Development Studio (WDS).

Collector ID: PTF_DATA

Report ID: WEBSPHERE_DEV_S_PTF

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (PTFs for WDS).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

PTFs Requiring IPL

This report displays PTFs waiting for the next IPL in order to be applied. Fixes within these PTFs are not implemented until the next IPL is complete.

Collector ID: PTF_DATA

Report ID: PTF_WAITING_FOR_IPL

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (PTFs Requiring IPL).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

[Configuration Management Reports]

PTFs that are Loaded but not Applied

This report displays Program Temporary Fixes (PTFs) that are loaded on the system but have not been applied. The status of these PTFs is "Not Applied."

On the IBM i, to complete the installation of a PTF for a licensed product, two steps must be performed – loading the PTF, and applying the PTF. If the PTF remains in a load state and is never applied, then the fix contained in it is not installed and may result in potential vulnerabilities on the system.

Collector ID: PTF_DATA

Report ID: LOADED_PTFS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (PTFs that are Loaded but not Applied).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Record Lock Information

This report displays one row for every record lock for the partition.

Collector ID: QSYS2.RECORD_LOCK_INFO

Report ID: QSYS2_RECORD_LOCK_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

QHST Message Information

This report list the History Log details for a specified date range.

Collector ID: QHST_MSG_INFO

Report ID: QHST_MSG_INFO

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (QHST Message Information).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

QHST Messages with Severity Greater Than 40

This report lists the History Log details with Severity of 40 or higher for a specified date range.

Collector ID: QHST_MSG_INFO

Report ID: QHST_MSG_INFO_40

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Message Queue Report).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (QHST Messages with Severity Greater than 40).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Save and Restore Information is Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *SAVRST is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_SAVRST

PASS = Value *SAVRST is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *SAVRST is not specified in QAUDLVL or QAUDLVL2 system value.

Save and restore information is audited (*SAVRST). The following are some examples:

- When programs that adopt their owner's user profile are restored
- When job descriptions that contain user names are restored
- When ownership and authority information changes for objects that are restored
- When the authority for user profiles is restored
- When a system state program is restored
- When a system command is restored
- When an object is restored

When you have this value set, the following security audit journal entry types are generated:

OR - Object restored

RA - Restore of objects when authority changes

RJ - Restore of job descriptions that contain user profile names

RO - Restore of objects when ownership information changes

RP - Restore of programs that adopt their owner's authority

RQ - A change request descriptor was restored

RU - Restore of authority for user profiles

RZ - The primary group for an object was changed during a restore operation

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **17** (Save and Restore Information is Audited).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Security Configuration Information

This report displays a list of modifications to the security configuration.

Collector ID: QSYS2.SECURITY_CONFIG

Report ID: QSYS2.SECURITY_CONFIG

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Security System Values

This report displays the security-related system values and their contents.

Collector ID: SYSTEM_VALUES

Report ID: SECURITY_SYSTEM_VALUES

Note: There are no pass/fail criteria associated with this report since it is informational only.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

Report Column Description

System Value	Description
QALWOBJRST	Allow object restore option
QALWUSRDMN	Allow user domain objects in libraries
QAUDCTL	Auditing control
QAUDENDACN	Auditing end action
QAUDFRCLVL	Force auditing data
QAUDLVL	Security auditing level
QAUDLVL2	Security auditing level extension
QCRTAUT	Create default public authority
QCRTOBJAUD	Create object auditing
QDSPSGNINF	Sign-on display information control

QFRCCVNRST	Force conversion on restore
QINACTITV	Inactive job time-out
QINACTMSGQ	Inactive job message queue
QLMTDEVSSN	Limit device sessions
QLMTSECOFR	Limit security officer device access
QMAXSGNACN	Action to take for failed signon attempts
QMAXSIGN	Maximum sign-on attempts allowed
QPWDCHGBLK	Block password change
QPWDEXPITV	Password expiration interval
QPWDEXPWRN	Password expiration warning
QPWDLMTAJC	Limit adjacent digits in password
QPWDLMTCHR	Limit characters in password
QPWDLMTREP	Limit repeating characters in password
QPWDLVL	Password level
QPWDMAXLEN	Maximum password length
QPWDMINLEN	Minimum password length
QPWDPOSDIF	Limit password character positions
QPWDRQDDGT	Require digit in password
QPWDRQDDIF	Duplicate password control
QPWDRULES	Password rules
QPWDVLDPGM	Password validation program
QRETSVRSEC	Retain server security data
QRMTSIGN	Remote sign-on control
QSCANFS	Scan file systems
QSCANFSCTL	Scan file systems control
QSECURITY	System security level
QSHRMEMCTL	Shared memory control
QSSLCSL	Secure sockets layer cipher specification list
QSSLCSLCTL	Secure sockets layer cipher control

QSSLPCL	Secure sockets layer protocols
QUSEADPAUT	Use adopted authority
QVFYOBJRST	Verify object on restore

See also

Configuration Management Reports

Server Security Data is Retained

This report displays the value of the QRETSVRSEC (Retain Server Security Data) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QRETSVRSEC

PASS = System value QRETSVRSEC is set to 1.

FAIL = System value QRETSVRSEC is set to 0.

The Retain Server Security Data system value determines whether the security data needed by a server to authenticate a user on a target system through client-server interfaces can be retained on the host system.

It is recommended to retain server security data by setting this value to 1.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Server Security Data is Retained).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface..

See also

Configuration Management Reports

Server Security User Information Actions

This report displays actions to Server Security User Information. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SO.

Collector ID: JOURNAL_SO

Report ID: *BASE

Tip: For SO journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = SO journal entries were not found in QAUDJRN.

FAIL = SO journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (Server Security User Information Actions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Service Tools Actions

This report displays Service Tools actions performed. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is ST.

Collector ID: JOURNAL_ST

Report ID: *BASE

Tip: For ST journal entries to be generated, the QAUDLVL system value must contain *SERVICE.

PASS = ST journal entries were not found in QAUDJRN.

FAIL = ST journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (Server Security User Information Actions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Software Product Information

This report displays software product information. You can also obtain this information by running the Display Software Resources (DSPSFWRSC) command and the Retrieve Product Information (QSZRTVPR) API.

Collector ID: QSYS2.SOFTWARE_PRODUCT

Report ID: SOFTWARE_PRODUCT

Note: See the IBM documentation for additional information: https://www.ibm.com/support/pages/ibm-i-74-tr3-enhancements

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Spooled File in Output Queue

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *SPLFDTA is specified.

Collector ID: QSYS2.OUTPUT_QUEUE_ENTRIES

Report ID: QSYS2_OUTPUT_QUEUE_ENTRIES

PASS = Value *SPLFDTA is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *SPLFDTA is not specified in QAUDLVL or QAUDLVL2 system value.

Spooled file functions are audited. The following are some examples:

- Create, delete, display, copy, hold, and release a spooled file
- Get data from a spooled file (QSPGETSP)
- Change spooled file attributes (CHGSPLFA command)

When you have this value set, the following security audit journal entry types are generated:

SF - A change was made to a spooled output file

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Storage Usage by User Profile

This report displays details about storage by user profile.

Collector ID: QSYS2.USER_STORAGE

Report ID: QSYS2_USER_STORAGE

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Strong System Security Level

This report displays the value of the QSECURITY (System Security Level) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QSECURITY

PASS = System value QSECURITY is set to 40 or above.

FAIL = System value QSECURITY is less than 40.

The System Security Level system value specifies the level of security on the system.

This value should be set to at least 40.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **20** (Strong System Security Level).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Autostart Details

This report displays subsystem description information for autostart job entries.

Collector ID: SUBSYSTEM_AUTOSTART

Report ID: SUBSYSTEM_AUTOSTART_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Subsystem Autostart Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Communication Details

This report displays subsystem description information for communication entries.

Collector ID: SUBSYSTEM_COMMUNICATIONS

Report ID: SUBSYSTEM_COMMUNICATIONS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Subsystem Communication Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Information Details

This report displays general subsystem description information.

Collector ID: SUBSYSTEM_INFORMATION

Report ID: SUBSYSTEM_INFORMATION

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Subsystem Information Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Job Queue Details

This report displays subsystem description information for job queue entries.

Collector ID: SUBSYSTEM_JOB_QUEUE

Report ID: SUBSYSTEM_JOB_QUEUE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Subsystem Job Queue Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Pool Data Details

This report displays subsystem description information for pool definitions.

Collector ID: SUBSYSTEM_POOL_DATA

Report ID: SUBSYSTEM_POOL_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Subsystem Job Queue Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Prestart Job Details

This report displays subsystem description information for prestart job entries.

Collector ID: SUBSYSTEM_PRESTART

Report ID: SUBSYSTEM_PRESTART_JOBS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Subsystem PreStart Job Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Remote Entries

This report displays subsystem description information for remote location name entries.

Collector ID: SUBSYSTEM_REMOTE

Report ID: SUBSYSTEM_REMOTE_ENTRIES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Subsystem Remote Entries).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Routing Entry Changes

This report displays changes in subsystem routing entries. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SE.

Collector ID: JOURNAL_SE

Report ID: *BASE

Tip: For SE journal entries to be generated, the QAUDLVL system value must contain *SECURITY.

PASS = SE journal entries were not found in QAUDJRN.

FAIL = SE journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Subsystem Routing Entry Change).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Workstation Names

This report displays subsystem description information for workstation name entries.

Collector ID: SUBSYSTEM_WORKSTATION_NAMES

Report ID: SUBSYSTEM_WORKSTATION_NAMES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Subsystem Workstation Names).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Subsystem Workstation Types

This report displays subsystem description information for workstation type entries.

Collector ID: SUBSSTEM_WORKSTATION_TYPES

Report ID: SUBSYSTEM_WORKSTATION_TYPES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **6** (Subsystem Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Subsystem Workstation Types).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Superseded PTFs

This report displays PTFs on the system that have been superseded by more recent PTFs. Superseding PTFs include the fixes supplied in the superseded PTFs.

Collector ID: PTF_DATA

Report ID: SUSPERSEDED_PTFS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Superseded PTFs).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

System, User, and Object Auditing Control Configuration

System Management Tasks are Audited

This report displays the values of the QAUDLVL (Auditing level) or QAUDLVL2 (Auditing level extension) system value if *SYSMGT is specified.

Collector ID: SYSTEM_VALUES

Report ID: QAUDLVL_SYSMGT

PASS = Value *SYSMGT is specified in the QAUDLVL or QAUDLVL2 system value.

FAIL = Value *SYSMGT is not specified in QAUDLVL or QAUDLVL2 system value.

System management tasks are audited (*SYSMGT). The following are some examples:

- Hierarchical file system registration
- Changes for Operational Assistant functions
- Changes to the system reply list
- Changes to the DRDA relational database directory
- Network file operations

When you have this value set, the following security audit journal entry types are generated:

DI - Directory services

SM - A change was made by system management

VL - An account limit was exceeded

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Security Configuration System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **19** (System Management Tasks are Audited).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

System Software Resources

This report displays software resources installed on the system. Any licensed products installed through the IBM installation process will be displayed.

Collector ID: SOFTWARE_RESOURCES

Report ID: SOFTWARE_RESOURCES_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (Product Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (System Software Resources).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

System Value Changes

This report displays changes made to system values. The data relating to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SV.

Collector ID: JOURNAL_SE

Report ID: *BASE

Tip: For SV journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = SV journal entries were not found in QAUDJRN.

FAIL = SV journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **20** (System Values Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

System Value Configuration Changes

This report displays changes to the TGSecure System Value Management configuration values.

Collector ID: DATABASE_AUDITING

Report ID: SYS_VAL_CONFIG

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **3** (System Value Change Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **1** (System Value Configuration Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Description	
Type	Journal entry code for the type of operation: **DL** - Record delete **PT** - Record add **PX** - Record added by RRN (a relative record number) to a physical file member **UB** - Record edit (before-change) **UP** - Record edit (after-change)
Timestamp	Time at which the remote server attempted communication with the target server
Job Name	Name assigned to the job
User Name	Name of the user executing the job
Job Number	Numbered assigned to the job
Program Name	Name of the program used to perform encryption
Program Library	Name of the library in which the program resides

Object Name	Name of the object changed
Library Name	Name of the library in which the object resides
Member Name	Name of member
User Profile	Profile name of the user executing the change request
System Name	Name of system submitting the change request
Remote Address	IP address used to submit the change request
Audit Status	Flag indicating whether auditing is enabled **Y** - Auditing is enabled **N** - Auditing is disabled **Note:** Auditing must be enabled to capture data for reporting purposes
Audit Journal Name	Name of audit journal
Audit Journal Library	Library in which audit journal resides
Alert Status	Flag indicating whether alerting is enabled: **Y** - Alerting is enabled **N** - Alerting is disabled
Alert Message Queue	Queue in which to store triggered alerts
Alert Message Queue Library	Library in which the message queue resides
Journal Type	Code that identifies the type of journal

See also

System Value Change Reports

System Value Configuration Details

This report displays the TGSecure System Value Management configuration details.

Collector ID: SYS_VAL_CONFIG

Report ID: SYS_VAL_CONFIG

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **2** (System Value Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **1** (System Value Configuration).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Column	Description
System Value	Name assigned to the system value
Category	System value category
Description	Description of system value
OS Version	OS version installed
Field Type	Type of field value allowed (CHAR, DECIMAL)
Field Size	Max length of system value entry
Value	Value currently assigned to system value

See also

System Value Configuration Changes

System Value Default Changes

This report displays changes to the TGSecure System Value Management default values.

Collector ID: DATABASE_AUDITING

Report ID: SYS_VAL_DEFAULT

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **3** (System Value Change Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **2** (System Value Default Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Column	Description
Type	Journal entry code for the type of operation: **DL** - Record delete **PT** - Record add **PX** - Record added by RRN (a relative record number) to a physical file member **UB** - Record edit (before-change) **UP** - Record edit (after-change)
Timestamp	Time at which the remote server attempted communication with the target server
Job Name	Name assigned to the job
User Name	Name of the user executing the job
Job Number	Numbered assigned to the job
Program Name	Name of the program used to perform encryption
Program Library	Name of the library in which the program resides

Object Name	Name of the object changed
Library Name	Name of the library in which the object resides
Member Name	Name of member
User Profile	Profile name of the user executing the change request
System Name	Name of system submitting the change request
Remote Address	IP address used to submit the change request
Journal Name	Journal in which configuration changes are stored
Journal Library	Library in which the journal resides
Default Swap	Profile to be used in place of the user profile associated with the transactions
Time-out interval	Max amount of time allowed for the remote server to attempt to communicate with the target server
Command Execution Entry	Journal entry code for the type of transaction
Audit Configuration	Flag indicating whether auditing is enabled for configuration changes: Y - Auditing enabled (enable tracking and reporting) N - Auditing disabled (disable tracking and reporting)
Alert Message Queue	Queue in which alerts are stored
Alert Message Queue Library	Library in which the queue resides

See also

System Value Change Reports

System Value Defaults

This report displays the TGSecure System Value Management configuration default values.

Collector ID: SYS_VAL_DEFAULT

Report ID: SYS_VAL_DEFAULT

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **2** (System Value Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **2** (System Value Defaults).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Column	Description
Audit Journal Name	Name of the journal in which system value transactions are stored **Note**: The default journal is **TGJRN** in the library **TGDATA**.
Audit Journal Library	Library in which the journal resides
Audit Configuration	Flag indicating whether journaling is enabled: **Y** - Journaling is enabled **N** - Journaling is disabled
Alert Status	Flag indicating whether alerting is enabled: **Y** - Alerting is enabled **N** - Alerting is disabled
Alert Message Queue Name	Name of the message queue **Note**: The default alert queue is **TGMSGQ** in the library **TGDATA**.
Alert Message Queue Library	Library in which the alert queue resides

Enforcement (Enabled/Disabled)	Flag indicating whether system value rules enforcement is enabled: **Y** - Enable enforcement of system value rules **N** - Disable enforcement of system value rules

See also

System Value Configuration Changes

System Value Valid Value Changes

This report displays changes to the TGSecure System Value Management valid values.

Collector ID: DATABASE_AUDITING

Report ID: SYS_VAL_VALID

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **3** (System Value Change Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **3** (System Value Valid Value Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Report Column Description

Column	Description
Type	Journal entry code for the type of operation: **DL** - Record delete **PT** - Record add **PX** - Record added by RRN (a relative record number) to a physical file member **UB** - Record edit (before-change) **UP** - Record edit (after-change)
Timestamp	Time at which the remote server attempted communication with the target server
Job Name	Name assigned to the job
User Name	Name of the user executing the job
Job Number	Numbered assigned to the job
Program Name	Name of the program used to perform encryption

Program Library	Name of the library in which the program resides
Object Name	Name of the object changed
Library Name	Name of the library in which the object resides
Member Name	Name of member
User Profile	Profile name of the user executing the change request
System Name	Name of system submitting the change request
Remote Address	IP address used to submit the change request

See also

System Value Change Reports

System Value Valid Values

This report displays the TGSecure System Value Management configuration valid values (used for validation).

Collector ID: SYS_VAL_VALID

Report ID: SYS_VAL_VALID

To run this report

1) Access the TGSecure main menu.
2) At the **Selection or command** prompt, enter **7** (System Value Management).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter **20** (System Value Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter **2** (System Value Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter **1** (System Value Configuration).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report.

11) Press **Enter**.

Report Column Description

Column	Description
System Value	Name assigned to the system value
System Val Seq	Sequence order (position)
System Val Data	Parameter value
Data Type	Type of field value allowed (CHAR, DECIMAL)
Data Len	Max length of system value entry
Data Single (Y/N)	Does the system value consist of single or multiple values? **Y** - Single Value **N** - Multiple Value
Data Min Val	Minimum value allowed
Data Max Val	Maximum value allowed
Error Msg ID	Number assigned to the error produced when the validation criteria defined for the system value are not met

See also

System Value Configuration Changes

Systems Management Changes

This report displays Systems Management changes. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SM.

Collector ID: JOURNAL_SM

Report ID: *BASE

Tip: For SM journal entries to be generated, the QAUDLVL system value must contain *SYSMGT.

PASS = SM journal entries were not found in QAUDJRN.

FAIL = SM journal entries were found in QAUDJRN.

The following are the types of changes:

B - Backup list changed

C - Automatic cleanup options

D - DRDA

F - HFS file system

N - Network file operation

O - Backup options changed

P - Power on/off schedule

S - System reply list

T - Access path recovery times changed

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **17** (Systems Management Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Time Adjustment Software Installed

This report displays the value of the Time Adjustment (QTIMADJ) system value. This value will be set to *NONE if there is no software installed to automatically handle time changes for such events as daylight savings time.

Collector ID: SYSTEM_VALUES

Report ID: QTIMADJ

See also

Configuration Management Reports

User Profile Changes

This report displays changes to user profiles on the system. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CP.

Collector ID: JOURNAL_CP

Report ID: *BASE

Tip: For CP journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = CP Journal entries were not found in QAUDJRN.

FAIL = CP Journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (User Profile Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

User Profile Information

This report displays information about user profiles.

Collector ID: QSYS2.USER_INFO

Report ID: QSYS2_USER_INFO

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Databases Management Reports

This section includes descriptions of the following **Database Management** reports:

- Cross Reference Physical File
- Data Area Changes
- Database Access
- Database Changes
- Database Content
- Database Operations
- Database Operations by Journal
- Field Level Authorities
- Row and Column Access Control
- Schedule Master File
- Sensitive Database Content

See also

TGAudit Report Reference Introduction

Cross Reference Physical File

This report returns the list of database files (file definition).

Tip: If you enter ***ALL** in the Object field, the system returns a list of all database files (objects) in the specified library.

Collector ID: DATABASE_CONTENT

Report ID: DTABASE_CROSS_REF_FILE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **6** (Cross Reference Physical File).
5) Press **Enter**.
6) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Database Changes

This report returns database change details.

Collector ID: DATABASE_AUDITING

Collector Name: DATABASE_CHANGES

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Database Changes).
5) Press **Enter**.
6) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

See also

Databases Management Reports

Database Content

This report returns the content of a database file (columns and records).

Tip: The **Object** field defaults to ***All**. You will need to clear this parameter value and enter the specific (singular) database object for which you want details.

Collector ID: DATABASE_CONTENT

Report ID: DATABASE CONTENT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **5** (Database Content).
5) Press **Enter**.
6) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Database Operations

This report returns database operation details.

Collector ID: DATABASE_OPERATIONS

Collector Name: DATABASE_OPERATIONS

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **9** (Database Operations).
5) Press **Enter**.
6) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

See also

Databases Management Reports

Database Operations by Journal

This report returns database operation details grouped by journal.

Collector ID: DTBASE_OPERATIONS_JRN

Collector Name: DATABASE_OPERATIONS BY JOURNAL

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **10** (Database Operations by Journal).
5) Press **Enter**.
6) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

See also

Databases Management Reports

Field Level Authorities

This report returns database field level authority details.

Collector ID: FIELD_AUTHORITY

Collector Name: FIELD LEVEL AUTHORITIES

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Field Level Authorities).
5) Press **Enter**.
6) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

See also

Databases Management Reports

Row and Column Access Control

This report displays Row and Column Access Control (RCAC) events on the system. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is AX.

Collector ID: JOURNAL_AX

Report ID: *BASE

Tip: For AX journal entries to be generated, the QAUDLVL system value must contain *SECRUN.

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **4** (Row and Column Access Control).

5) Press **Enter**.

6) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Sensitive Database Content

This report identifies and lists database files on your IBM i server that contain sensitive data. By default, this report is configured to find credit card information, but you can expand the search to meet the needs of your organization.

Tip: If you desire customization of the Sensitive Database Content report, contact Trinity Guard customer support for assistance.

Collector ID: SENSTIIVE_DATABASE_CONTENT

Report ID: SENSITIVE_DATABASE CONTENT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **2** (Data Level Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **11** (Sensitive Database Content).
5) Press **Enter**.
6) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

7) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Configuration Management Reports

Log Management Reports

This section includes descriptions of the following **Log Management** reports:

- Job Activity Details
- Job Activity Summary

See also

TGAudit Report Reference Introduction

Job Activity Details

This report displays the activities identified for monitoring by the Job Activity Monitor.

Connector ID: JOB_ACTIVITY_DETAILS

Report ID: JOB_ACTIVITY_DETAILS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.
8) Press **Enter**.

See also

Log Management Reports

Job Activity Summary

This report displays a summary of the activities identified for monitoring by the Job Activity Monitor.

Connector ID: JOB_ACTIVITY_SUMMARY

Report ID: JOB_ACTIVITY_SUMMARY

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Log Management Reports

Network Management Reports

This section includes descriptions of the following **Network Management** reports:

- Actions to IP Rules
- APPN Endpoint Filter Violations
- Asynchronous Signals Processed
- Cluster Operations
- Connections Started, Ended, or Rejected
- Controller Description Details
- Controllers and Attached Devices
- Database Server Initialization Report
- Database Server Native DB Report
- Database Server Object Info Report
- Database Server SQL Requests Report
- Device Description Data
- Device Descriptions - *APPC
- DNS Configuration Details
- FTP Client Operations - Certificate data
- Integrated File System Exits Installed
- Internet Security Management Events
- Inter-process Communication Events
- Intrusion Monitor Events
- NetServer Configuration
- NetServer Shares
- Network Attribute Details
- Network Authentication Events
- Network Connection Details
- Network Interface Details IPv4
- Network Interface Details IPv6
- Network Route Details IPv4
- Network Route Details IPv6
- Network Server Descriptions
- Network Server Encryption Status
- Network Servers with Encryption Verified
- Network Servers with Failed or Unknown Encryption
- Object Management Changes
- OfficeVision Mail Services Actions
- Remote Power On and IPL
- Remote Service Attribute
- Remote Sign-on Control
- Secure Socket Connections
- Server Sessions Started or Ended
- Server Share Information
- Service Status Change Events
- Sockets-related Exit Points Not Secured
- SSL Cipher Control and Specification List
- TCP_IP IPv4 Stack Attributes
- TCP_IP IPv6 Stack Attributes

- TELNET Server Attributes
- Unsecured Remote Server Exit Points

See also

TGAudit Report Reference Introduction

Actions to IP Rules

This report displays actions to IP Rules. The data relating to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is IR.

Collector ID: JOURNAL_IR

Report ID: *BASE

Tip: For IR journal entries to be generated, the QAUDLVL system value must contain *NETBAS and *NETCMN.

PASS = IR journal entries were not found in QAUDJRN.

FAIL = IR journal entries were found in QAUDJRN.

Types of entries

L - IP rules have been loaded from a file.

N - IP rules have been unloaded for an IP Security connection.

P - IP rules have been loaded for an IP Security connection.

R - IP rules have been read and copied to a file.

U - IP rules have been unloaded (removed).

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Actions to IP Rules).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

APPN Endpoint Filter Violations

This report displays information about APPN Endpoint Filter Violations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is NE.

Collector ID: JOURNAL_NE

Report ID: *BASE

Tip: For NE journal entries to be generated, the QAUDLVL system value must contain *NETBAS and *NETCMN.

PASS = NE journal entries were not found in QAUDJRN.

FAIL = NE journal entries were found in QAUDJRN.

Types of entries

A - Change to network attribute

T - Change to TCP/IP attribute

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (APPN Endpoint Filter Violations).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Asynchronous Signals Processed

This report displays information about Asynchronous Signals Processed. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SG.

Collector ID: JOURNAL_SG

Report ID: *BASE

PASS = SG journal entries were not found in QAUDJRN.

FAIL = SG journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **14** (Asynchronous Signals Processed).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Network Management Reports

Cluster Operations

This report displays Cluster Operations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CU.

Collector ID: JOURNAL_CU

Report ID: *BASE

Tip: For CU journal entries to be generated, the QAUDLVL system value must contain *NETCLU and *NETCMN.

PASS = CU journal entries were not found in QAUDJRN.

FAIL = CU journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Cluster Operations).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Connections Started, Ended, or Rejected

This report displays information for connections that were started, ended, or rejected on the system. The data relating to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VC.

Collector ID: JOURNAL_VC

Report ID: *BASE

Tip: For VC journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL and *JOBDTA.

PASS = VC journal entries were not found in QAUDJRN.

FAIL = VC journal entries were found in QAUDJRN.

Types of entries

S - Start

E - End

R - Reject

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Connections Started, Ended, or Rejected).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Controller Description Details

This report displays information about controller descriptions available on the system.

Collector ID: CONTROLLER_DESCRIPTION_DATA

Report ID: CONTROLLER_DESCRIPTION_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (Controller Description Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Controllers and Attached Devices

This report displays information about controller descriptions on the system and the related devices attached to each controller description.

Collector ID: CONTROLLER_ATTACHED_DEVICES

Report ID: CONTROLLER_ATTACHED_DEVICES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **12** (Controllers and Attached Devices).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Database Server Initialization Report

This report displays DB server transactions of type DBINIT - Perform server initiation.

Collector IDs:

- NETWORK_TRANS_DATABASE
- NETWORK_TRANSACTIONS_DATABASE

Report ID: DATABASE_SERVER_INITLZ_REPORT

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Database Server Native DB Report

This report displays DB server transactions of type DBNDB - Perform native database requests.

Collector IDs:

- NETWORK_TRANS_DATABASE
- NETWORK_TRANSACTIONS_DATABASE

Report ID: DATABASE_SERVER_NATIVE_REPORT

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Database Server SQL Requests Report

This report displays DB server transactions of type DBSQL - Perform SQL requests

Collector IDs:

- NETWORK_TRANS_DATABASE
- NETWORK_TRANSACTIONS_DATABASE

Report ID: DATABASE_SERVER_SQL_REQUESTS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Device Description Data

This report displays information about device descriptions configured on the system.

Collector ID: DEVICE_DESCRIPTION_DATA

Report ID: DEVICE_DESCRIPTION_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **7** (Device Details Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Device Description Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Device Descriptions - *APPC

This report displays details about *APPC device descriptions configured on the system. *APPC devices are for advanced program-to-program communications.

Collector ID: DEVICE_DESCRIPTION_APPC

Report ID: DEVICE_DESCRIPTION_APPC

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **7** (Device Details Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Device Descriptions - *APPC).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

FTP Client Operations - Certificate data

This report displays a list of modifications to the FTP certification data.

Collector ID: JOURNAL_FT

Report ID: *BASE

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Integrated File System Exits Installed

This report displays information about exit programs installed on the QIBM_QP0L_SCAN_OPEN and QIBM_QP0L_SCAN_CLOSE exit points.

Collector ID: EXIT_POINTS

Report ID: INTEGRATED_FILE_EXITS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Internet Security Management Events

This report displays information about Internet Security Management Events. The data relating to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is IS.

Collector ID: JOURNAL_IS

Report ID: *BASE

PASS = IS journal entries were not found in QAUDJRN.

FAIL = IS journal entries were found in QAUDJRN.

Types of entries

A - Fail (starting in V7R1, this type is no longer used)

C - Normal (starting in V7R1, this type is no longer used)

U - Mobile User (starting in V7R1, this type is no longer used)

1 - IKE Phase 1 SA Negotiation

2 - IKE Phase 2 SA Negotiation

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Internet Security Management Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Network Management Reports

Inter-process Communication Events

This report displays details about Inter-process Communication Events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is IP.

Collector ID: JOURNAL_IP

Report ID: *BASE

Tip: For IP journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *SECIPC, and *SECURITY.

PASS = IP journal entries were not found in QAUDJRN.

FAIL = IP journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Inter-process Communication Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Intrusion Monitor Events

This report displays information about Intrusion Monitor Events. The data relating to this report is retrieved from the system security audit journal (QAUDJRN. The journal entry type associated with this event is IM.

Collector ID: JOURNAL_IM

Report ID: *BASE

Tip: For IM journal entries to be generated, the QAUDLVL system value must contain *ATNEVT.

PASS = IM journal entries were not found in QAUDJRN.

FAIL = IM journal entries were found in QAUDJRN.

The following are the types of intrusions monitored:

ACKSTORM - TCP ACK storm

ADRPOISN - Address poisoning

FLOOD - Flood event

FRAGGLE - Fraggle attack

ICMPRED - ICMP (Internet Control Message Protocol) redirect

IPFRAG - IP fragment

MALFPKT - Malformed packet

OUTRAW - Outbound Raw

PERPECH - Perpetual echo

PNGDEATH - Ping of death

RESTOPT - Restricted IP options

RESTPROT - Restricted IP protocol

SMURF - Smurf attack

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **3** (Network Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **7** (Intrusion Monitor Events).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

NetServer Configuration

This report displays the list of IBM® i NetServer configuration information.

Collector ID: NETSERVER_CONFIG

Report ID: NETSERVER_CONFIG

Note: See IBM documentation for additional information: https://www.ibm.com/docs/en/i/7.4?topic=ssw_ibm_i_74/apis/qzlslsti.htm

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (NetServer Configuration).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Attribute Details

This report displays all network attributes available on the system similar to what is displayed using the Display Network Attribute (DSPNETA) command. If there are attributes that are not configured correctly, you can update them using the Change Network Attribute (CHGNETA) command.

Collector ID: NETWORK_ATTRIBUTES

Report ID: NETWORK_ATTRIBUTES_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Network Attribute Detail).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Authentication Events

This report displays information about Network Authentication Events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is X0.

Collector ID: JOURNAL_X0

Provider ID: *BASE

Tip: For X0 journal entries to be generated, the QAUDLVL system value must contain *SECNAS and *SECURITY.

PASS = X0 journal entries were not found in QAUDJRN.

FAIL = X0 Journal entries were found in QAUDJRN.

Types of entries:

1 - Service ticket valid

2 - Service principals do not match

3 - Client principals do not match

4 - Ticket IP address mismatch

5 - Decryption of the ticket failed

6 - Decryption of authenticator failed

7 - Realm is not within client local realms

8 - Ticket is a replay attempt

9 - Ticket not yet valid

A - Decrypt of KRB_AP_PRIV or KRB_AP_SAFE checksum error

B - Remote IP address mismatch

C - Local IP address mismatch

D - KRB_AP_PRIV or KRB_AP_SAFE timestamp error

E - KRB_AP_PRIV or KRB_AP_SAFE replay error

F - KRB_AP_PRIV or KRB_AP_SAFE sequence order error

K - GSS accept — expired credential

L - GSS accept — checksum error

M - GSS accept — channel bindings

N - GSS unwrap or GSS verify expired context

O - GSS unwrap or GSS verify decrypt/decode

P - GSS unwrap or GSS verify checksum error

Q - GSS unwrap or GSS verify sequence error

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **3** (Network Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **19** (Network Authentication Events).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Connection Details

This report displays information about network connections to the system. The data is similar to network data, showing details such as local and remote IP addresses, port numbers, server information, SSL enabled status, TCP state, and connection type information.

Collector ID: NETWORK_CONNECTIONS

Report ID: NETWORK_CONNECTION_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Network Connection Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Interface Details IPv4

This report displays IPv4 network interface information for the system.

Collector ID: NETWORK_INTERFACE_IPV4

Report ID: NETWORK_INTERFACE_IPv4

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Network Interface Details IPv4).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Interface Details IPv6

This report displays IPv6 network interface information for the system.

Collector ID: NETWORK_INTERFACE_IPV6

Report ID: NETWORK_INTERFACE_IPV6

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Network Interface Details IPv6).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Route Details IPv4

This report displays IPv4 routing information on the system.

Collector ID: NETWORK_ROUTE_IPV4

Report ID: NETWORK_ROUTE_DETAILS_IPV4

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Network Route Details IPv4).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Route Details IPv6

This report displays IPv6 routing information on the system.

Collector ID: NETWORK_ROUTE_IPV6

Report ID: NETWORK_ROUTE_DETAILS_IPV6

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Network Route Details IPv6).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Server Descriptions

This report displays information about network server descriptions defined on the system.

Collector ID: NETWORK_SERVER_DESCRIPTIONS

Report ID: NETWORK_SERVER_DESCRIPTIONS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (Network Server Descriptions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Server Encryption Status

This report displays information about remote servers and whether or not communication to those servers is encrypted.

Collector ID: NETWORK_SVR_ENCRYPT_STATUS

Report ID: NETWORK_SVR_ENCRYPT_STATUS

See also

Network Management Reports

Network Servers with Encryption Verified

This report displays remote servers on the system that are able to complete a successful SSL handshake.

Collector ID: NETWORK_SVR_ENCRYPT_STATUS

Report ID: NETWORK_SVR_ENCRYPT_VERIFIED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Network Servers with Encryption Verified).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Network Servers with Failed or Unknown Encryption

This report displays remote servers on the system that return a failed or unknown status for an SSL handshake.

Collector ID: NETWORK_SVR_ENCRYPT_STATUS

Report ID: NETWORK_SVR_ENCRYPT_NOT_VERIF

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Network Servers with Failed or Unknown Encryption).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Object Management Changes

This report displays object management changes. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is OM.

Collector ID: JOURNAL_OM

Report ID: *BASE

Tip: For OM journal entries to be generated, the QAUDLVL system value must contain *OBJMGT.

PASS = OM journal entries were not found in QAUDJRN.

FAIL = OM journal entries were found in QAUDJRN.

Types of entries:

M - Object moved to a different library.

R - Object renamed.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Object Management Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

OfficeVision Mail Services Actions

This report displays information about mail actions in OfficeVision. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is ML.

Collector ID: JOURNAL_ML

Report ID: *BASE

Tip: For ML journal entries to be generated, the QAUDLVL system value must contain *OFCSRV.

PASS = ML Journal entries were not found in QAUDJRN.

FAIL = ML Journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (OfficeVision Mail Services Actions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Remote Power On and IPL

This report displays the value of the QRMTIPL (Remote Power On and IPL) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QRMTIPL

PASS = System value QRMTIPL is set to 0.

FAIL = System value QRMTIPL is to 1.

The Remote Power On system value defines whether or not turning on power to the system can be done from a remote location.

The recommended value is 0.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Remote Service Attribute

This report displays the value of the QRMTSRVATR (Remote Service Attribute) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QRMTSRVATR

PASS = System value QRMTSRVATR is set to 0.

FAIL = System value QRMTSRVATR is to 1.

The Remote service attribute system value specifies if service attributes can be changed from a remote location.

The recommended value is 0.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Network Management Reports

Remote Sign-on Control

This report displays the value of the QRMTSIGN (Remote Sign-on Control) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QRMTSIGN

PASS = System value QRMTSIGN is set to 1.

FAIL = System value QRMTSIGN is to 0.

The Remote Sign-on Control system value specifies how the system handles remote sign-on requests.

The recommended value is 1.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Remote Sign-on Control).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Secure Socket Connections

This report displays information about Secure Socket Connections. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SK.

Collector ID: JOURNAL_SK

Report ID: *BASE

Tip: For SK journal entries to be generated, the QAUDLVL system value must contain *NETCMN, *NETFAIL, and *NETSCK.

PASS = SK journal entries were not found in QAUDJRN.

FAIL = SK journal entries were found in QAUDJRN.

Types of entries:

A - Accept

C - Connect

D - DHCP address assigned

F - Filtered mail

P - Port unavailable

R - Reject mail

U - DHCP address not assigned

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (Secure Socket Connections).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Server Sessions Started or Ended

This report displays Server Sessions that started or ended. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VS.

Collect ID: JOURNAL_VS

Report ID: *BASE

Tip: For VS journal entries to be generated, the QAUDLVL system value must contain *JOBDTA.

FAIL = VS journal entries were found in QAUDJRN.

Types of entries:

E - End session

S - Start session

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **17** (Server Sessions Started or Ended).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Service Status Change Events

This report displays changes to Service Status. The data relating to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VV.

Collector ID: JOURNAL_VV

Report ID: *BASE

Tip: For VV journal entries to be generated, the QAUDLVL system value must contain *SERVICE.

PASS = VV Journal entries were not found in QAUDJRN.

FAIL = VV Journal entries were found in QAUDJRN.

Types of entries:

C - Service status changed

E - Server stopped

P - Server paused

R - Server restarted

S - Server started

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (Service Status Change Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Sockets-related Exit Points Not Secured

This report evaluates whether or not exit programs are installed on the sockets-related exit points.

Collector ID: EXIT_POINTS

Report ID: SOCKET_EXITS

PASS = Exit point programs are installed on sockets-related exit points or server is i5/OS release less than 7.1.

FAIL = No exit point programs are installed on socket-related exit points.

Clients for newer remote servers, such as Secure File Transfer Protocol (SFTP) and Secure Shell (SSH), communicate with i5/OS through sockets instead of the more well-known remote server exit points. There are also many applications that connect directly to the IBM i through proprietary protocols using socket communication. Since i5/OS 7.1, there are socket-related exit points available to help monitor and secure network traffic through sockets on your system.

At a minimum, exit point programs should be installed on socket-related exit points so you can monitor who is accessing the data on your system.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Sockets-related Exit Points Not Secured).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

SSL Cipher Control and Specification List

This report displays the values of the QSSLCSL (SSL Cipher Specification List) and QSSLCSLCTL (SSL Specification List) system values if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: SECURE_SOCKET

PASS = System value QSSLCSL is *OPSYS and QSSLCSLCTL is *OPSYS.

FAIL = System value QSSLCSL is not *OPSYS and system value QSSLCSLCTL is not *OPSYS.

The Secure Sockets Layer (SSL) cipher specification list specifies the list of cipher suites that are supported by System SSL. The shipped value is *RSA_AES_128_CBC_SHA, *RSA_RC4_128_SHA, *RSA_RC4_128_MD5, *RSA_AES_256_CBC_SHA, *RSA_3DES_EDE_CBC_SHA, *RSA_DES_CBC_SHA, *RSA_EXPORT_RC4_40_MD5, *RSA_EXPORT_RC2_CBC_40_MD5, *RSA_NULL_SHA, and *RSA_NULL_MD5.

You must have *IOSYSCFG, *ALLOBJ, and *SECADM special authorities to change this system value.

System SSL uses the sequence of the values in QSSLCSL to order the System SSL default cipher specification list. The default cipher specification list entries are system defined and can change on release boundaries. A default cipher removed from QSSLCSL results in the cipher's removal from the default list. The default cipher is added back to the default cipher specification list when it is added back into QSSLCSL. It is not possible to add other ciphers to the default list beyond the system-defined set for the release.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (SSL Cipher Control and Specification List).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Network Management Reports

TCP_IP IPv4 Stack Attributes

This report displays TCP/IP stack attribute information for IPv4 communication.

Collector ID: NETWORK_TCPIP_IPV4

Report ID: TCPIP_IPV4_STACK_ATTRIBUTES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **14** (TCP/IP IPv4 Stack Attributes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

TCP_IP IPv6 Stack Attributes

This report displays TCP/IP stack attribute information for IPv6 communication.

Collector ID: NETWORK_TCPIP_IPV6

Report ID: TCPIP_IPV6_STACK_ATTRIBUTES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (TCP/IP IPv6 Stack Attributes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

TELNET Server Attributes

This report displays a list of modifications to the TELNET server attributes.

Collector ID: QSYS2.TELNET_ATTRIB

Report ID: QSYS2.TELNET_ATTRIB

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Configuration Management Reports

Unsecured Remote Server Exit Points

This report evaluates whether or not exit programs are installed on remote server exit points.

Collector ID: EXIT_POINTS

Report ID: UNSECURED_REMOTE_EXITS

PASS = Exit programs are installed on remote server exit points.

FAIL = Exit programs are NOT installed on all remote server exit points.

Communication for ODBC, FTP, and TELNET transactions, along with transactions for numerous other remote servers such as RMTCMD, DDM, etc., pass through remote server exit points. Exit programs can be installed on remote server exit points to monitor and secure transactions. It is important to know who is accessing the data on your system so you can verify if the access is authorized or not.

While it is best to implement object-level and Integrated File System (IFS) security to protect your system, sometimes, due to application limitations, it may not be possible to implement this type of security effectively and an application may break if object-level security is implemented. In a situation like this, it is recommended you monitor all your remote connections and the data access. Remote server exit points are your only option in these scenarios.

At a minimum, it is recommended to have exit point programs monitoring remote server exit points so you can review who is accessing your data.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Network Settings Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Unsecured Remote Server Exit Points).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you can search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Network Management Reports

Profile Management Reports

This section includes descriptions of the following **Profile Management** reports:

- All User Profiles
- Authority Failures
- Authority Restored for User Profiles
- Block Password Change
- Changes to Service Tools Profiles
- Connection Verifications
- Directory Server Extensions
- Disable Profile After Maximum Failed Signon Attempts
- Duplicate Password Control
- Enabled IBM Profiles
- Exceeded Account Limit Events
- Group Profile Information
- Group Profiles with *ALLOBJ *SECADM or *SERVICE Special Authorities
- Group Profiles with Passwords
- Group Profiles with Special Authorities
- IBM Profile Details Report
- Identity Token Events
- Inactive Job Message Queue
- Inactive Job Time-out
- Invalid Sign-on Attempts
- Limit Adjacent Digits in Password
- Limit Characters in Password
- Limit Password Character Positions
- Limit Repeating Characters in Password
- Limit Security Officer Device Access
- Maximum Password Length
- Minimum Password Length
- Network Attribute Changes
- Network Log on and Logoff Events
- Network Password Errors
- Network Profile Changes
- Object Authorities of User Profiles
- Ownership Changes for Restored Objects0
- Password Expiration Interval
- Password Expiration Warning
- Password Level
- Password Rules
- Password Validation Program
- Powerful User Profiles
- Profile Object Auditing Values
- Profile with Password Expiration Interval not *SYSVAL
- Profiles that are *DISABLED
- Profiles with Expired Passwords
- Profiles with Limit Capabilities = *NO
- Profiles with Multiple Groups

- Profiles with Pwd = *NONE or *DISABLED
- Publicly Accessible User Profiles
- Require Digit in Password
- Security Officer Profiles
- Service Tool Security Attributes
- Swap Profile Events
- System Service Tools Users
- User Profile = Password
- User Profiles Not Used in 90 Days
- Users with Job Control Special Authority
- Users with Save System Special Authority
- Users with Unlimited Device Sessions

See also

TGAudit Report Reference Introduction

All User Profiles

This report displays a list of all the user profiles that exist on the system and their associated settings.

Collector ID: USER_PROFILES

Report ID: AllUSERS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (All User Profiles).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Authority Failures

This report displays information about restoring user profiles. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is AF.

Collector ID: JOURNAL_AF

Report ID: *BASE

Tip: For AF journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL and *PGMFAIL.

PASS = AF journal entries were not found in QAUDJRN.

FAIL = AF journal entries were found in QAUDJRN.

Types of failures

A - Not authorized to object

B - Restricted instruction

C - Validation failure

D - Use of unsupported interface, object domain failure

E - Hardware storage protection error, program constant space violation

F - ICAPI authorization error

G - ICAPI authentication error

H - Scan exit program

I - System Java inheritance not allowed

J - Submit job profile error

K - Special authority violation

N - Profile token not a regenerable token

O - Optical Object Authority Failure

P - Profile swap error

R - Hardware protection error

S - Default sign-on attempt

T - Not authorized to TCP/IP port

U - User permission request not valid

V - Profile token not valid for generating new profile token

W - Profile token not valid for swap

X - System violation

Y - Not authorized to the current JUID field during a clear JUID operation.

Z - Not authorized to the current JUID field during a set JUID operation

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (All Authority Failures).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Block Password Change

This report displays the value of the QPWDCHGBLK (Block Password Change) system value if a vulnerability is found.

Collector ID: JOURNAL_CA

Report ID: *BASE

PASS = System value QPWDCHGBLK is set to a value other than *NONE

FAIL = System value QPWDCHGBLK is set to *NONE.

The Block Password Change system value specifies the time period during which a password is blocked from being changed following the prior successful password change operation. This system value does not restrict password changes made by the Change User Profile (CHGUSRPRF) command.

Consider changing this value from 1-99 to specify the number of hours before the next password change can be made after a successful password change.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Block Password Change).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Connection Verifications

This report displays information about Connection Verification events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CV.

Collector ID: JOURNAL_CV

Report ID: *BASE

Tip: For CV journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *NETBAS, *NETCMN, and *SECURITY.

PASS = CV journal entries were not found in QAUDJRN.

FAIL = CV journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **3** (Network Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Network Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Connection Verifications).
9) Press **Enter**.

Note: The criteria allow you to limit the data returned n the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Directory Server Extensions

This report displays changes to Directory Server Extensions. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is XD.

Collector ID: JOURNAL_XD

Report ID: *BASE

Tip: For XD journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *CREATE, and *DELETE.

PASS = XD journal entries were not found in QAUDJRN.

FAIL = XD journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (System Configuration Changes Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **22** (Directory Server Extensions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Disable Profile After Maximum Failed Signon Attempts

This report displays the value of the QMAXSGNACN (Action to Take for Failed Sign-on Attempts) system value if the value is 1 (Disable Device Only).

Collector ID: SYSTEM_VALUES

Report ID: QMAXSGNACN

PASS = System value QMAXSGNACN is set to 2 or 3.

FAIL = System value QMAXSGNACN is not set to 1.

The Action to Take for Failed Sign-on Attempts system value specifies how the system reacts when the maximum number of consecutive, incorrect, sign-on attempts (see system value QMAXSIGN) is reached. A change to this system value takes effect the next time someone attempts to sign on the system.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Profile Management Reports

Duplicate Password Control

This report displays the value of the QPWDRQDDIF (Duplicate Password Control) system value if the value is 0 or is greater than 4.

Collector ID: SYSTEM_VALUES

Report ID: QPWDRQDDIF

PASS = System value QPWDRQDDIF is set to 1, 2, or 3.

FAIL = System value QPWDRQDDIF is set to 0 or a value greater than 4.

The Duplicate Password Control system value limits how often a user can repeat the use of a password.

0 = Can be the same as old passwords

1 = Cannot be the same as last 32

2 = Cannot be the same as last 24

3 = Cannot be the same as last 18

4 = Cannot be the same as last 12

5 = Cannot be the same as last 10

6 = Cannot be the same as last 8

7 = Cannot be the same as last 6

8 = Cannot be the same as last 4

It is recommended to set this system value to 1, 2, or 3 to increase password security on your system.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **12** (Duplicate Password Control).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Enabled IBM Profiles

This report displays a list of user profiles on the system that begin with Q and have a *ENABLED status. IBM profiles are shipped with the operating system and are used for system application functions.

Collector ID: USER_PROFILES

Report ID: ENABLED_IBM_PROFILES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Enabled IBM Profiles).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Exceeded Account Limit Events

This report displays information about Account Limit Exceeded events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VL.

(*Obsolete in 7.2.)

Collect ID: JOURNAL_VL

Report ID: *BASE

Tip: For VL journal entries to be generated, the QAUDLVL system value must contain *SYSMGT.

PASS = VL journal entries were not found in QAUDJRN.

FAIL = VL journal entries were found in QAUDJRN.

Types of entries

A - Account expired

D - Account disabled

L - Logon hours exceeded

U - Unknown or unavailable

W - Workstation not valid

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Exceeded Account Limit Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Group Profiles with *ALLOBJ *SECADM or *SERVICE Special Authorities

This report displays configuration information for group profiles on the system that have all object, security administrator, or service special authorities. User profiles that are members of these group profiles will inherit these powerful special authorities. The number of user profiles on the system that have these special authorities should be limited as much as possible since they have access to all resources on the system and can perform critical system operations.

Collector ID: USER_PROFILES

Report ID: GROUP_PROFILE_ALL_SEC_SRV

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **2** (Profile Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **17** (Group Profiles with *ALLOBJ *SECADM or *SERVICE Special Authorities).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Group Profiles with Passwords

This report displays configuration information for group profiles on the system that have passwords defined.

Collector ID: USER_PROFILES

Report ID: GROUP_PROFILE_PASSWORDs

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Profile Management Reports

Group Profiles with Special Authorities

This report displays configuration information for group profiles on the system that have any special authorities. Since user profiles who are members of these group profiles will inherit the special authorities of their groups, it is critical to evaluate and make sure the group profiles have the least amount of authority required for their specific job functions.

Collector ID: USER_PROFILES

Report ID: GROUP_PROFILE_SPECIAL_AUTH

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Group Profiles with Special Authorities).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

IBM Profile Details Report

This report displays configuration information for the Q* IBM user profiles on the system.

Collector ID: USER_PROFILES

Report ID: IBM_PROFILE_DETAILS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (IBM Profile Details Report).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

[Profile Management Reports]

Identity Token Events

This report displays Identity Token events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is X1.

Collector ID: JOURNAL_X1

Report ID: *BASE

Tip: For X1 journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *SECURITY, and *SECVFY.

PASS = X1 journal entries were not found in QAUDJRN.

FAIL = X1 journal entries were found in QAUDJRN.

Types of entries

D - Delegate of identity token was successful

F - Delegate of identity token failed

G - Get user from identity token was successful

U - Get user from identity token failed

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Identity Token Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Inactive Job Message Queue

This report displays the value of the QINACTMSGQ (Inactive Job Message Queue) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QINACTMSGQ

PASS = System value QINACTMSGQ is *ENDJOB or *DSCJOB.

FAIL = System value QINACTMSGQ is set to a message queue.

The Inactive Message Queue system value specifies the action the system takes when an interactive job has been inactive for an interval of time (the time interval is specified by the system value QINACTITV). The interactive job can be ended, disconnected, or message CPI1126 can be sent to the message queue you specify. The message queue must exist in the system auxiliary storage pool (ASP) or in a basic user ASP.

If the specified message queue does not exist or is damaged when the inactive time-out interval is reached, the messages are sent to the QSYSOPR message queue.

All of the messages in the specified message queue are cleared during an IPL. If you assign a user's message queue to be QINACTMSGQ, the user loses all messages that are in the user's message queue during each IPL.

A change to this system value takes effect immediately. The shipped value is *ENDJOB.

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **30** (Work with Reports).

3) Press **Enter**. The **Work with Reports** interface is displayed.

4) Locate the desired report using the search and sort options available.

5) In the **Opt** field for the desired report, enter **7** (Run).

6) Press **Enter**.

7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Profile Management Reports

Inactive Job Time-out

This report displays the value of the QINACTITV (Inactive Job Time-out) system value if the value is *NONE.

Collector ID: SYSTEM_VALUES

Report ID: QINACTITV

PASS = System value QINACTITV is not *NONE.

FAIL = System value QINACTITV is *NONE.

The Inactive Job Time-out system value specifies when the system takes action on inactive interactive jobs. The system value QINACTMSGQ determines the action the system takes. Local jobs that are currently signed-on to a remote system are excluded. For example, a work station is directly attached to system A, and system A has QINACTITV set on. If display station pass-through or TELNET is used to sign on to system B, this work station is not affected by the QINACTITV value set on system A.

Note: A change to this system value takes effect immediately.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Profile Management Reports

Limit Adjacent Digits in Password

This report displays the value of the QPWDLMTAJC (Limit Adjacent Digits in Password) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QPWDLMTCHR

PASS = System value QPWDLMTAJC is set to 1 or higher.

FAIL = System value QPWDLMTAJC is set to 0.

The Limit Adjacent Digits in Password system value specifies whether adjacent numbers are allowed in passwords. This makes it difficult to guess passwords by preventing the use of dates or social security numbers as passwords.

Consider setting the value to limit adjacent digits in passwords to 1 or more, according to your password policy. Be sure to balance complexity and usability in your password policy.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Limit Adjacent Digits in Password).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Limit Characters in Password

This report displays the value of the QPWDLMTCHR (Limit Characters in Password) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QPWDLMTCHR

PASS = System value QPWDLMTCHR is set to a value other than *NONE.

FAIL = System value QPWDLMTCHR is set to *NONE.

The Limit Characters in a Password system value provides password security by preventing certain characters (vowels, for example) from being in a password. This makes it difficult to guess passwords by preventing the use of common words or names as passwords.

Consider setting the value to limit characters in passwords to 1 or more, according to your password policy. Be sure to balance complexity and usability in your password policy.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Limit Characters in Password).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Limit Password Character Positions

Limit Repeating Characters in Password

This report displays the value of the QPWDLMTREP (Limit Repeating Characters in Password) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QPWDLMTREP

PASS = System value QPWDLMTREP is not set to 0.

FAIL = System value QPWDLMTREP is set to 0.

The Limit Repeating Characters in Password system value prevents a user from using the same character more than once in the same password. (For example, AAAA.)

Tip: Consider limiting repeating characters in passwords and set this value to a value higher than 0, according to your password policy. Be sure to balance complexity and usability in your password policy.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Limit repeating Characters in Password).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Maximum Password Length

This report displays the value of the QPWDMAXLEN (Maximum Password Length) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QPWDMAXLEN

PASS = System value QPWDMAXLEN is set to 10 or higher.

FAIL = System value QPWDMAXLEN is set less than 10.

The Maximum Password Length system value specifies the maximum number of characters in a password.

Tip: It is recommended to set this value to a minimum of 10.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Maximum Password Length).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Network Log on and Logoff Events

This report displays logon or logoff operations on the network. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VN.

(*Obsolete in 7.2.)

Collector ID: JOURNAL_VN

Report ID: *BASE

Tip: For VN journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL and *JOBDTA.

PASS = VN journal entries were not found in QAUDJRN.

FAIL = VN journal entries were found in QAUDJRN.

Types of entries

F - Logoff requested

O - Logon requested

R - Logon rejected

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Network Log On and Off Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Network Password Errors

This report displays events where incorrect network passwords were used. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VP.

Collector ID: JOURNAL_VP

Report ID: *BASE

Tip: For VP journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL.

PASS = VP journal entries were not found in QAUDJRN.

FAIL = VP journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Network Password Errors).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Network Profile Changes

This report displays changes to network profiles. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VU.

Collector ID: JOURNAL_VU

Report ID: *BASE

Tip: For VU journal entries to be generated, the QAUDLVL system value must contain *SECCFG and *SECURITY.

PASS = VU journal entries were not found in QAUDJRN.

FAIL = VU journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Network Profile Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Password Expiration Interval

This report displays the value of the QPWDEXPITV (Password Expiration Interval) system value if the value is *NOMAX or greater than 90.

Collector ID: SYSTEM_VALUES

Report ID: QPWDEXPITV

PASS = System value QPWDEXPITV is set to 90 or less.

FAIL = System value QPWDEXPITV is set to *NOMAX or a value greater than 90.

The Password Expiration Interval system value specifies the number of days for which passwords are valid. This provides password security by requiring users to change their passwords after a specified number of days. If the password is not changed within the specified number of days, the user cannot sign-on until the password is changed.

Seven days before the password ends, you are warned at sign-on time, even if you are not displaying sign-on information (see system value QDSPSGNINF).

Tip: 90 days is a good standard for the password expiration interval.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Password Expiration Interval).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Password Expiration Warning

This report displays the value of the QPWDEXPWRN (Password Expiration Warning) system value if the value is less than 14.

Collector ID: SYSTEM_VALUES

Report ID: QPWDEXPWRN

PASS = System value QPWDEXPWRN is 14 or greater.

FAIL = System value QPWDEXPWRN is set to less than 14.

The Password Expiration Warning system value controls the number of days prior to a password expiring to begin displaying password expiration warning messages on the Sign-on Information display.

Tip: It is recommended to set this value to 14 days or more.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Password Expiration Warning).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Password Level

This report displays the value of the QPWDLVL (Password Level) system value if the value is set to 0.

Collector ID: SYSTEM_VALUES

Report ID: QPWDLVL

PASS = System value QPWDLVL is not set to 0.

FAIL = System value QPWDLVL is set to 0.

The Password Level system value specifies the level of password support on the system. The password level of the system can be set to allow user profile passwords of 1-10 characters or to allow user profile passwords of 1-128 characters.

The password level can be set to allow a 'passphrase' as the password value. The term 'passphrase' is sometimes used in the computer industry to describe a password value which can be very long and has few, if any, restrictions on the characters used in the password value. Blanks can be used between letters in a passphrase, which allows you to have a password value that is a sentence or sentence fragment.

Changing the password level of the system from 1-10 character passwords or 1-128 character passwords requires careful consideration. If your system communicates with other systems in a network, then all systems must be able to handle the longer passwords.

A change to this system value takes effect at the next IPL. To see the current and pending password level values, use the CL command Display Security Attributes (DSPSECA). The shipped value is 0.

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **2** (Profile Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **7** (Password Level).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Password Rules

This report displays the value of the QPWDRULES (Password Rules) system value if the value is not *PWDSYSVAL.

Collector ID: SYSTEM_VALUES

Report ID: QPWDRULES

PASS = System value QPWDRULES is set to *PWDSYSVAL.

FAIL = System value QPWDRULES is not set to *PWDSYSVAL.

The Password Rules system value specifies the rules used to check whether a password is formed correctly.

Note: Changes made to this system value take effect the next time a password is changed. The shipped value is *PWDSYSVAL.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (Password Rules).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Password Validation Program

This report displays the value of the QPWDVLDPGM (Password Validation Program) system value if the value is not *NONE.

Collector ID: SYSTEM_VALUES

Report ID: QPWDVLDPGM

PASS = System value QPWDVLDPGM is set to *NONE.

FAIL = System value QPWDVLDPGM is not set to *NONE.

The Password Validation Program system value provides the ability for a user-written program to do additional validation on passwords. The program must exist in the system auxiliary storage pool (ASP) or in a basic user ASP.

Since a password validation program receives passwords in clear text, there is a risk of the program capturing and storing passwords. These programs should be used with extreme caution.

Tip: It is recommended to set this value to *NONE. If a password validation program must exist, ensure it is designed securely and is from a trusted source.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **14** (Password Validation Program).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Powerful User Profiles

This report displays information about the user profiles on your system that have *SECOFR user class or have *ALLOBJ or *SECADM special authorities.

Collector ID: USER_PROFILES

Report ID: POWER_USERS

PASS = 3 or fewer user profiles with *SECOFR user class or *ALLOBJ or *SECADM special authorities were found on your system.

FAIL = More than three user profiles with *SECOFR user class or *ALLOBJ or *SECADM special authorities were found on your system.

Special authorities determine the level of access a user profile has on the system.

Types of Special Authorities

*ALLOBJ – All object authority

*SECADM – Security administrator authority

*JOBCTL – Job control authority

*SPLCTL – Spool control authority

*SAVSYS – Save system authority

*SERVICE – Service authority

*AUDIT – Audit authority

*IOSYSCFG – System configuration authority

Tip: It is recommended to minimize the number of user profiles with special authorities on your system. Assign the minimum authority necessary when creating user profiles. Also, periodically review user profiles to ensure assigned special authorities are still required.

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **2** (Profile Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **1** (Powerful User Profiles).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Profile Object Auditing Values

This report displays profile information for users that have object auditing turned on.

Collector ID: USER_PROFILES

Report ID: PROFILE_OBJECT_AUDIT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **21** (Profile Object Auditing Values).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Profile with Password Expiration Interval not *SYSVAL

This report displays user profile configuration information for profiles that do not have the typical system standard of *SYSVAL for the Password Expiration Interval. If a user profile has a non-standard value for this setting, they may be attempting to bypass the system security policy. Ensure any non-standard settings are reviewed and approved.

Collector ID: USER_PROFILES

Report ID: USERS_PWDEXPITV

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Profile with Password Expiration Interval not *SYSVAL).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Profiles that are *DISABLED

This report displays user profiles that have a status of *DISABLED. These users cannot sign on to the system. Disabled users should be evaluated to determine if they should be deleted from the system due to inactivity. They should also be evaluated to check for instances of hacking attempts since typical system configuration is to disable users after 3 invalid sign-on attempts.

Collector ID: USER_PROFILES

Report ID: PROFILES_DISABLED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (Profiles that are *DISABLED).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Profiles with Pwd = *NONE or *DISABLED

This report displays profile information for users with no password or users that are disabled. These users cannot sign on to the system and should be cleaned up on a regular basis. If these profiles are no longer needed, make sure they are removed.

Collector ID: USER_PROFILES

Report ID: PROFILES_PWD_NONE_DISABLED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **19** (Profiles with Pwd = *NONE or *DISABLED).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Publicly Accessible User Profiles

This report displays user profiles where the *PUBLIC authority to the user profile object is not set to *EXCLUDE. In other words, for these users, the general "public" on the system have access to the user profile objects. Typically, the *PUBLIC authority on all user profile objects should be set to *EXCLUDE so unintentional or malicious changes to user profile objects cannot be made to corrupt user profile integrity.

Collector ID: USER_OBJECT_AUTHORITIES

Report ID: USERS_WITH_PUBLIC_ACCESS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **22** (Publicly Accessible User Profiles).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Require Digit in Password

This report displays the value of the QPWDRQDDGT (Require digit in password) system value if the value is set to 0.

Collector ID: SYSTEM_VALUES

Report ID: QPWDRQDDGT

Note: The Require Digit in Password system value specifies whether a digit is required in a new password. This prevents the user from only using alphabetic characters.

PASS = System value QPWDRQDDGT is not set to 0.

FAIL = System value QPWDRQDDGT is set to 0.

Tip: It is recommended to require at least 1 digit in passwords. Be sure to balance complexity and usability in your password policy.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Password-related System Values).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (Require Digit in Password).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Security Officer Profiles

This report displays user profile information about user profiles with the security officer (*SECOFR) user class.

Collector ID: USER_PROFILES

Report ID: SECURITY_OFFICER

Note: User profiles with security officer class authority typically have all object authority and have little to no restrictions on the system.

PASS = Three or fewer user profiles with *SECOFR user class exist on the system.

FAIL = More than three user profiles with *SECOFR user class exist on the system.

Tip: The number of user-profiles with security officer privileges should be very minimal and reserved only for authorized administrators in your organization.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Security Officer Profiles).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Swap Profile Events

This report displays information about any time a profile swap occurs on the system. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is PS.

Collector ID: JOURNAL_PS

Report ID: *BASE

> **Note**: For PS journal entries to be generated, the QAUDLVL system value must contain *SECURITY and *SECVFY.

PASS = PS journal entries were not found in QAUDJRN.

FAIL = PS journal entries were found in QAUDJRN.

Types of entries

A - Profile swap during pass-through

E - End work on behalf of relationship

H - Profile handle generated by the QSYGETPH API

I - All profile tokens were invalidated

M - Maximum number of profile tokens have been generated

P - Profile token generated for user

R - All profile tokens for a user have been removed

S - Start work on behalf of relationship

V - User profile authenticated

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Swap Profile Events).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

User Profiles Not Used in 90 Days

This report displays user profile information for users on your system that have not been used in 90 days.

Collector ID: USER_PROFILES

Report ID: NOT_USED_90_DAYS

PASS = No users exist that have not been used in 90 days.

FAIL = Users exist on your system that have not been used in 90 days.

User profiles that have not been used in three months are typically no longer necessary on the system and are often leftover from employees that are no longer with the organization. The more of these unnecessary profiles that exist on your system, the higher the risk of someone exploiting access to your system.

Tip: It is recommended to disable and eventually delete user profiles not being used.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (User Profiles Not Used in 90 Days).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Users with Job Control Special Authority

This report displays user profile information for users with Job Control (*JOBCTL) special authority.

Collector ID: USER_PROFILES

Report ID: USERS_JOBCTL

PASS = Three or fewer user profiles with *JOBCTL special authority.

FAIL = More than three user profiles with *JOBCTL special authority.

User profiles with *JOBCTL special authority can change, display, hold, release, cancel, and clear all jobs that are running on the system or that are on a job queue or output queue that has OPRCTL (*YES) specified. The user also has the authority to start writers and stop active subsystems.

Tip: The number of user profiles with Job Control special authority should be very minimal and reserved only for authorized administrators in your organization.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (Users with Job Control Special Authority).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Users with Save System Special Authority

This report displays user profile information for users that have the Save System (*SAVSYS) special authority.

Collector ID: USER_PROFILES

Report ID: USERS_SAVSYS

PASS = Three or fewer user profiles with *SAVSYS special authority.

FAIL = More than three user profiles with *SAVSYS special authority.

User profiles with *SAVSYS authority have the authority to save, restore, and free storage for all objects on the system, with or without object management authority.

Tip: The number of user profiles with Save System special authority should be very minimal and reserved only for authorized administrators in your organization.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Users with Save System Special Authority).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Users with Unlimited Device Sessions

This report displays user profile information for users on your system that have the Limit Device Sessions (LMTDEVSSN) parameter set to *NO.

Collector ID: USER_PROFILES

Report ID: USERS_LIMIT_DEVICE

PASS = All users have the Limit Device Sessions parameter set to a value other than *NO.

FAIL = Users exist on your system that have the Limit Device Sessions parameter set to *NO.

Setting the Limit Device Sessions parameter to *NO is considered bad practice since it enables profiles to be shared more easily. If sessions are not limited, the same user profile can sign on at any number of device sessions.

Tip: It is recommended to set the Limit Device Sessions parameter to *YES or *SYSVAL.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **2** (Profile Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Profile Configuration Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Users with Unlimited Device Sessions).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Profile Management Reports

Resource Management Reports

This section includes descriptions of the following **Resource Management** reports:

- *PUBLIC User with *RWX Authorities -*PUBLIC with *ALL
- Actions on Validation Lists
- Allow Object Restore Option
- Allow User Domain Objects in Libraries
- ASCII Files Stored in the IFS
- Attributes for QSYS.LIB
- Authorization List Details
- Authorization Lists with Public Access
- Authorized Users via Authorization Lists
- Change Request Descriptors Restored
- Changed Data Files in Last 30 Days
- Close Operations on Server Files
- Commands Available in QSH
- Commands Executed
- Configuration Files
- Create Operations
- Damages Objects
- Data Queue Entries
- Database Files Larger than 100Mb
- Database Files with Over 1,000,000 Read Operations
- Database Files with Over 100,000 Delete Operations
- Database Files with Over 100,000 Insert Operations
- Database Files with 10000 Delete Records
- Database Monitoring
- Db2 Mirror Communication Services
- Db2 Mirror Product Services
- Db2 Mirror Replication Services
- Db2 Mirror Replication State
- Db2 Mirror Setup Tools
- Delete Operations
- Directory Link, Unlink, and Search Operations
- Directory Search Violations
- DLO Object Changes
- DLO Object Reads
- Dual Optical Object Accesses
- Exit Point Maintenance Operations
- File Statistics
- File Usage Information
- Files Checked Out Status
- Files Not Secured by Authorization Lists
- Files Not Used in the Last 30 Days
- Files with RWX Authorities
- HTTP Server and Web Files Status
- HTTP Server File Authorities
- IFS Directory Information

- IFS Files Being Journaled
- Integrated File System Content
- Integrated File System Security
- Job Changes
- Job Descriptions - USER Parameter Changes
- Journaled Files
- Journaled Objects
- Largest Files Report >100Mb
- LDAP Operations
- Library QGPL Database Files not Backed up in 30 Days
- Library Statistics
- Maximum sign-on attempts allowed is NOMAX
- Network Resource Accesses
- New Data Files in Last 30 Days
- New Library in Last 30 Days
- New Objects in the Last 30 Days
- Object Authority
- Object Changes
- Object Details
- Object Ownership Changes
- Object Reads
- Object Source
- Object Statistics
- Objects Changed in the Last 30 Days
- Objects Created in the Last 30 Days
- Objects Larger than 100MB
- Objects Owned by QSECOFR
- Objects Restored
- Objects Used in the Last 30 Days
- Optical Volume Accesses
- Primary Group Changes
- Printer Output Changes
- Program Reference Details
- Programs that Adopt Authority
- PTF Object Changes
- PTF Operations
- Public Access to Commands in QSYS
- Public Access to Devices
- Public Access to Journal Receivers in QGPL
- Public Access to Objects in QGPL
- Regular Files on the IFS
- Restored Objects in the Last 30 Days
- Root *PUBLIC User with *RWX Authorities
- Single Optical Object Accesses
- Socket Descriptor Details
- Source Changes in Last 30 Days
- Spooled File Actions
- System Directory Changes
- System Security Audit Journal Exists
- TGAudit Report Configuration

- TGCentral Agent Configuration
- Unsaved Objects in the Last 30 Days
- User-defined File Systems (UDFS's)
- Verify Object on Restore

See also

TGAudit Report Reference Introduction

*PUBLIC User with *RWX Authorities -*PUBLIC with *ALL

This report displays the public and private authorities associated with the objects that have the User Data Authority attribute set to *RWX for the *PUBLIC user. In the QSYS.LIB file system, this is the equivalent of having object authorities set to *ALL for *PUBLIC.

Collector ID: IFS_AUTHORITIES

Report ID: PUBLIC_USER_AUTH_FILES

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **4** (Resource Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **19** (*PUBLIC User with RWX Authorities - *PUBLIC with *ALL).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Actions on Validation Lists

This report displays actions on validation lists. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VO.

Collector ID: JOURNAL_VO

Report ID: *BASE

Tip: For VO journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *SECURITY, and *SECVLDL.

PASS = VO journal entries were not found in QAUDJRN.

FAIL = VO journal entries were found in QAUDJRN.

Types of entries

A - Add validation list entry

C -Change validation list entry

F -Find validation list entry

R -Remove validation list entry

U -Unsuccessful verify of a validation list entry

V -Successful verify of a validation list entry

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (Actions on Validation Lists).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Allow Object Restore Option

This report displays the value of the QALWOBJRST (Allow Object Restore Option) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QALWOBJRST

PASS = System value QALWOBJRST is set to *NONE.

FAIL = System value QALWOBJRST is not set to *NONE.

The QALWOBJRST system value controls how the system handles attempts to restore objects with security-sensitive attributes. The value can be set to *ALL, *NONE, or a list of values. If *ALL is specified, any object can be restored to the system. If *NONE is specified, no objects with security-sensitive attributes can be restored.

Tip: It is recommended to set this value to *NONE so objects with security-sensitive attributes cannot be unknowingly restored on your system. If there is a legitimate need for a security-sensitive object to be restored on your system, you will need to change this system value to allow the restore and then change it back to *NONE. This will prevent instances such as potentially harmful programs that inherit security officer authorities from being restored to your system without your knowledge. Always ensure security-sensitive objects are from trusted sources and designed correctly to avoid creating system vulnerabilities such as basic users being able to access the command line with security officer authorities.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Allow User Domain Objects in Libraries

This report displays the value of the QALWUSRDMN (Allow User Domain Objects in Libraries) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QALWUSRDMN

PASS = System value QALWUSRDMN is not set to *ALL.

FAIL = System value QALWUSRDMN is set to *ALL.

This system value controls which libraries may contain user domain user (*USRxxx) objects. You can specify up to 50 individual libraries or all libraries on the system.

Tip: It is recommended you specify a list of libraries which is allowed to store object types such as user indexes (*USRIDX) and user spaces (*USRSPC).

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

ASCII Files Stored in the IFS

This report displays details about ASCII files in the Integrated File System (IFS). ASCII files are determined by the CCSID and codepage attributes. These files contain stream file data and are in directory structures similar to Windows or Unix operating system environments.

Collector ID: IFS_ATTRIBUTES

Report ID: ASCII_FILES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (ASCII Files Stored in the IFS).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Attributes for QSYS.LIB

This report displays attributes of objects found in QSYS.LIB.

Collector ID: IFS_ATTRIBUTES

Report ID: QSYS.LIB_ATTRIBUTES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **14** (Attributes for /QSYS.LIB).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Authorization List Details

This report displays all authorization lists that exist on the system.

Collector ID: AUTHORITIES_LIST

Report ID: AUTHORITIES_LIST_DETAILS

Tip: Unnecessary authorization lists should be deleted. Verify the necessary authorization lists are used to secure sensitive data.

PASS = N/A

FAIL = N/A

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Authorization List Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Authorization Lists with Public Access

This report displays authorization lists that do not have *PUBLIC authority set to *EXCLUDE.

Collector ID: AUTHORITIES_LIST

Report ID: AUTHORITY_LIST_PUBLIC

PASS = *PUBLIC authority for authorization lists is set to *EXCLUDE.

FAIL = *PUBLIC authority for authorization lists is not set to *EXCLUDE.

Tip: *PUBLIC represents all the users on the system. Allowing *PUBLIC access to authorization lists can be a security risk. If an individual user or group of users require access to objects secured by an authorization list, add the user or group to the authorization list.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Authorization Lists with Public Access).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Authorized Users via Authorization Lists

This report displays the user authorities of an object granted through authorization lists. If an object is secured by an authorization list, the users in the authorization list and their related authorities will be displayed for that object.

Collector ID: AUTH_USERS_VIA_AUTH_LISTS

Report ID: AUTH_USERS_VIA_AUTH_LISTS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Changed Data Files in Last 30 Days

Use this report to list the data file changes that occurred in the last 30 days.

Collector ID: OBJECT_DETAILS

Report ID: CHANGED_FILES_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.
10) Press **Enter**.

See also

Resource Management Reports

Close Operations on Server Files

This report displays Close of Server Files. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VF.

Collector ID: JOURNAL_VF

Report ID: *BASE

Tip: For VF journal entries to be generated, use the Change User Auditing (CHGUSRAUD) to start auditing commands or use the Change Object Auditing (CHGOBJAUD) command.

PASS = VF journal entries were not found in QAUDJRN.

FAIL = VF journal entries were found in QAUDJRN.

Types of entries:

A - Administrative disconnection

N - Normal client disconnection

S - Session disconnection

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **17** (Close Operations on Server Files).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Commands Available in QSH

This report displays all binary commands available in the QSH and PASE environments. These commands are Unix operating system commands.

Collector ID: IFS_STATUS

Report ID: QSH_COMMANDS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **23** (Commands Available in QSH).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Commands Executed

This report displays command executions. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is CD.

Collector ID: JOURNAL_CD

Report ID: *BASE

Tip: For CD journal entries to be generated, use the Change User Auditing (CHGUSRAUD) to start auditing commands or use the Change Object Auditing (CHGOBJAUD) command. QAUDCTL must also be set to *OBJAUD in order for CD journal entries to be generated.

PASS = CD journal entries were not found in QAUDJRN.

FAIL = CD journal entries were found in QAUDJRN.

Types of entries:

C - Command run

L - OCL statement

O - Operator control command

P - S/36 procedure

S - Command run after command substitution took place

U - Utility control statement

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Commands Executed).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Damages Objects

Use this report to list all the objects with a damaged status. For recovery of damaged object you need to restore the object from another system or a backup.

Collector ID: OBJECT_DETAILS

Report ID: OBJECTS_DAMAGED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Data Queue Entries

This report displays one or more messages from the specified data queue. The messages are not removed from the data queue. The message data is returned as characters, UTF-8, and binary data.

Collector ID: QSYS2.DATA_QUEUE_ENTRIES

Report ID: DATA_QUEUE_ENTRIES

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Database Files Larger than 100Mb

This report returns database files with over 100,000 delete operations.

Collector ID: SYSTABLESTAT

Report ID: SYSTABLESTAT_LARGE_FILES

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Database Files with Over 1,000,000 Read Operations

This report returns database files larger with over 100,000 read operations.

Collector ID: SYSTABLESTAT

Report ID: SYSTABLESTAT_READ_OPERATIONS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Database Files with Over 100,000 Insert Operations

This report returns database files larger with over 100,000 insert operations.

Collector ID: SYSTABLESTAT

Report ID: SYSTABLESTAT_INSERT_OPERATIONS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Database Files with 10000 Delete Records

This report returns database files larger with 10,000 delete records.

Collector ID: SYSTABLESTAT

Report ID: SYSTABLESTAT_DELETELD_RECORDS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Db2 Mirror Communication Services

This report returns Db2 mirror communication services details

Collector ID: JOURNAL_M6

Report ID: *BASE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Data Mirroring Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Db2 Mirror Communication Services).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Db2 Mirror Product Services

This report returns Db2 mirror product services details.

Important: This report is only available for OS 7.4 or higher.

Collector ID: JOURNAL_M8

Report ID: *BASE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Data Mirroring Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Db2 Mirror Product Services).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Db2 Mirror Replication Services

This report returns Db2 mirror replication services details.

Important: This report is only available for OS 7.4 or higher.

Collector ID: JOURNAL_M7

Report ID: *BASE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Data Mirroring Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Db2 Mirror Replication Services).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Db2 Mirror Replication State

This report returns Db2 mirror replication state details.

Important: This report is only available for OS 7.4 or higher.

Collector ID: JOURNAL_M9

Report ID: *BASE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Data Mirroring Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Db2 Mirror Replication State).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Db2 Mirror Setup Tools

This report returns the Db2 mirror setup tool details.

Important: This report is only available for OS 7.4 or higher.

Collector ID: JOURNAL_M0

Report ID: *BASE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **4** (Data Mirroring Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Db2 Mirror Setup Tools).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Directory Search Violations

This report displays directory search filter violations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is ND.

Collector ID: JOURNAL_ND

Report ID: *BASE

Tip: For ND journal entries to be generated, the QAUDLVL system value must contain *NETBAS and *NETCMN.

PASS = ND journal entries were not found in QAUDJRN.

FAIL = ND journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Directory Search Violations).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

DLO Object Changes

This report displays change details for DLO objects. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is YC.

Collector ID: JOURNAL_YC

Report ID: *BASE

Tip: For YC journal entries to be generated, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = YC journal entries were not found in QAUDJRN.

FAIL = YC journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (DLO Object Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

DLO Object Reads

This report displays read details for DLO objects. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is YR.

Collector ID: JOURNAL_YR

Report ID: *BASE

For YR journal entries to be generated, object auditing on the object must be set to *ALL. To set object auditing, use the CHGOBJAUD command.

PASS = YR journal entries were not found in QAUDJRN.

FAIL = YR journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (DLO Object Reads).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Dual Optical Object Accesses

This report displays optical object access details. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is O2.

Collector ID: JOURNAL_02

Report ID: *BASE

Tip: For O2 journal entries to be generated, the QAUDLVL system value must contain *OPTICAL.

PASS = 02 journal entries were not found in QAUDJRN.

FAIL = O2 journal entries were found in QAUDJRN.

Types of entries

C - Copy

R - Rename

B - Backup Dir or File

S - Save Held File

M - Move File

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (Dual Optical Object Accesses).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Exit Point Maintenance Operations

This report displays exit point maintenance events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is GR.

Collector ID: JOURNAL_GR

Report ID: *BASE

Tip: For GR journal entries to be generated, the QAUDLVL system value must contain *AUTFAIL, *SECCFG, and *SECURITY.

PASS = GR journal entries were not found in QAUDJRN.

FAIL = GR journal entries were found in QAUDJRN.

Types of entries

A - Exit program added

C - Operations Resource Monitoring and Control Operations

D - Exit program removed

F - Function registration operations

R - Exit program replaced

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **4** (Exit Point Maintenance Operations).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

File Statistics

This report contains the list of statistics related to an object (files).

Collector ID: OBJECT_STAT

Report ID: FILE_STAT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **9** (File Statistics).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

Report Column Description

Column	Description
OBJNAME	Name assigned to the object
OBJTYPE	Type of object *FILE -
OBJOWNER	Owner of the object
OBJDEFINER	Definer of object
OBJCREATED	Date on which object was created
OBJSIZE	Object size
OBJTEXT	Descriptive of object

See also

Resource Management Reports

File Usage Information

This report displays file usage information for files stored in the IFS. Fields returned indicate how often an object is used. Usage has different meanings according to the specific file system and according to the individual object types supported within a file system. Usage count is updated for operations such as opening and closing of a file or can refer to adding links, renaming, restoring, or checking out an object.

Collector ID: IFS_ATTRIBUTES

Report ID: FILE_USAGE_INFORMATION

The attributes returned include

- Days used count: The number of days an object has been used.
- Date object was most recently used: The date the object was last used.
- Date Days_used_cnt was Reset: The date the days used count was the last reset to zero (0).

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **12** (File Usage Information).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Files Checked Out Status

This report displays files checked out by users. When an object is checked out, other users can only read and copy the object. Only the user who has the object checked out can change the object.

Collector ID: IFS_ATTRIBUTES

Report ID: CHECKED_OUT_FILES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Files Checked Out Status).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Files Not Secured by Authorization Lists

This report displays IFS files that are not secured by authorization lists. This report will also show public and private authorities associated with the files.

Collector ID: IFS_AUTHORITIES

Report ID: FILES_NOT_SECURED_WITH_AUTL

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Files not Secured by Authorization Lists).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Files Not Used in the Last 30 Days

Use this report to list files not used in the last 30 days.

Collector ID: OBJECT_DETAILS

Report ID: FILE_USAGE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Files with RWX Authorities

This report displays the public and private authorities associated with the IFS files that have User Data Authority set to *RWX. The User Data Authority attribute defines what permissions the user has to the file.

*RWX - Allows all operations on the object except those that are limited to the owner or controlled by the object rights

Collector ID: IFS_AUTHORITIES

Report ID: FILES_RWX_ENABLED

IFS uses the following to grant rights:

*R - Read

*W - Write

*X - Execute rights respectively.

Tip: Read, write, and execute rights can be used in combined, so *RWX gives the equivalent of *ALL authority.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **17** (Files with RWX Authorities).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

HTTP Server and Web Files Status

This report displays status information for the HTTP server and related web files in the "/www" directory.

Collector ID: IFS_STATUS

Report ID: HTTP_WEB_FILES_STATUS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **22** (HTTP Server and Web Files Status).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

[Resource Management Reports]

HTTP Server File Authorities

This report displays authorities for files in the "/www" IFS folder.

Collector ID: IFS_AUTHORITIES

Report ID: HTTP_SERVER_FILES_AUTH

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **18** (HTTP Server File Authorities).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

IFS Directory Information

This report displays all the directories on the Integrated File System (IFS). Only objects with type *DIR will be shown.

Collector ID: IFS_ATTRIBUTES

Report ID: DIRECTORY_INFORMATION

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **11** (IFS Directory Information).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

IFS Files Being Journaled

This report displays the extended journaling information for objects.

Collector ID: IFS_JOURNALING

Report ID: FILES_BEING_JOURNALED

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **20** (IFS Files Being Journaled).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Integrated File System Content

This report returns content from the Integrated File System (IFS).

Collector ID: IFS_CONTENT

Report ID: IFS_CONTENT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **26** (Integrated File System Content).
9) Press **Enter**.
10) Modify the run criteria as necessary.
11) Press **Enter**.

See also

Resource Management Reports

Integrated File System Security

This report displays the value of the QSCANFSCTL (Scan File Systems) system value if a vulnerability is found.

Note: Review the Scan File Systems (QSCANFS) system value and choose a value that is appropriate for your environment. Ensure QSCANFS is not set to *NONE.

Collector ID: SYSTEM_VALUES

Report ID: INTEGRATED_FILE_SECURITY

Tip: Although the i5/OS is a virus-free system, if you do not monitor the IFS, it could be a virus carrier and affect your entire network. In fact, i5/OS IFS is a good hiding place for viruses.

PASS = System value QSCANFS is not set to *NONE.

FAIL = System value QSCANFS is set to *NONE.

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **4** (Resource Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **1** (Integrated File System Security).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

[Resource Management Reports]

Job Changes

This report displays job change events. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is JS.

Collector ID: JOURNAL_JS

Report ID: *BASE

Tip: For JS journal entries to be generated, the QAUDLVL system value must contain *JOBBAS, *JOBCHGUSR, and *JOBDTA.

PASS = JS journal entries were not found in QAUDJRN.

FAIL = JS journal entries were found in QAUDJRN.

Types of entries

A - ENDJOBABN command

B - Submit

C - Change

E - End

H - Hold

I - Disconnect

J - The current job is attempting to interrupt another job

K - The current job is about to be interrupted

L - The interruption of the current job has completed

M - Change profile or group profile

N - ENDJOB command

P - Attach prestart or batch immediate job

Q - Change query attributes

R - Release

S - Start

T - Change profile or group profile using a profile token.

U - CHGUSRTRC

V - Virtual device changed by QWSACCDS API

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **4** (Resource Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **6** (Job Changes).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Job Descriptions - USER Parameter Changes

This report displays user parameter changes.

Collector ID: JOURNAL_JD

Report ID: *BASE

Tip: For JD journal entries to be generated, use the Change User Auditing (CHGUSRAUD) to start auditing commands or use the Change Object Auditing (CHGOBJAUD) command.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Journaled Files

Use this report to list all database files associated with a journal.

Collector ID: OBJECT_DETAILS

Report ID: JOURNALED_FILES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Largest Files Report >100Mb

This report displays stream files that are larger than 100Mb.

Collector ID: IFS_ATTRIBUTES

Report ID: LARGE_FILES_ON_IFS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **13** (Largest Files Report > 100Mb).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

LDAP Operations

This report displays the Lightweight Directory Access Protocol (LDAP) operations. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is DI.

Collector ID: JOURNAL_DI

Report ID: *BASE

Tip: Object Auditing should also be enabled by using the CHGOBJAUD command.

PASS = DI journal entries were not found in QAUDJRN.

FAIL = DI journal entries were found in QAUDJRN.

For DI journal entries to be generated, the QAUDLVL system value must contain:

- *AUTFAIL
- *CREATE
- *DELETE
- *OBJMGT
- *SECDIRSRV
- *SECURITY
- *SYSMGT

Types of LDAP operations

CI - Create an instance

CO - Object creation

CP - Password change

DI - Delete instance

DO - Object delete

EX - LDAP directory export

IM - LDAP directory import

OM - Object management (rename)

OW - Ownership change

PO - Policy change

PW - Password fail

RM - Replication management

UB - Successful unbind

ZC - Object change

ZR - Object read

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (LDAP Operations).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Library QGPL Database Files not Backed up in 30 Days

This report displays file information for physical files in the QGPL library that have not been saved in 30 days. It is good practice to ensure critical system files are backed up on a regular basis to ensure system availability.

Collector ID: OBJECT_DETAILS

Report ID: DATABASE_QGPL_30_DAYS

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Library Statistics

This report contains the list of statistics related to a library.

Collector ID: LIBRARY_STAT

Report ID: LIBRARY_STAT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **10** (Library Statistics).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

Report Column Description

Column	Description
OBJNAME	Name assigned to object
OBJTYPE	Type of object: *LIB
OBJOWNER	Owner of object
OBJDEFINER	Creator of object
OBJCREATED	Date on which object was created
OBJSIZE	Size of object
OBJTEXT	Description of object

See also

Resource Management Reports

Maximum sign-on attempts allowed is NOMAX

This report displays the value of the QMAXSIGN (Maximum Sign-on Attempts Allowed) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QMAXSIGN

Tip: The Maximum Sign-on Attempts Allowed system value controls the number of times a user can incorrectly attempt to sign on to the system. This value should be set to a reasonably low number to guard against unauthorized access attempts to your system.

PASS = System value QMAXSIGN is set to a value other than *NOMAX.

FAIL = System value QMAXSIGN is set to *NOMAX.

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **30** (Work with Reports).

3) Press **Enter**. The **Work with Reports** interface is displayed.

4) Locate the desired report using the search and sort options available.

5) In the **Opt** field for the desired report, enter **7** (Run).

6) Press **Enter**.

7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Network Resource Accesses

This report displays network resource access details. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is VR.

Collector ID: JOURNAL_VR

Report ID: *BASE

For VR journal entries to be generated, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = VR journal entries were not found in QAUDJRN.

FAIL = VR journal entries were found in QAUDJRN.

Types of entries

F - Resource access failed

S - Resource access succeeded

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **19** (Network Resource Accesses).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

New Data Files in Last 30 Days

Use this report to list new data files created in the last 30 days.

Collector ID: OBJECT_DETAILS

Report ID: NEW_DATA_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

New Objects in the Last 30 Days

Use this report to list the new objects created in the last 30 days. The object creation date is used to select data included in this report.

Collector ID: OBJECT_DETAILS

Report ID: OBJECTS_NEW_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Object Authority

This report contains the list of details related to an authority object.

Collector ID: OBJECT_AUTHORITY

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **2** (Object Authority).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Object Changes

This report displays change operations to objects. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is ZC.

Collector ID: JOURNAL_ZC

Report ID: *BASE

Tip: For ZC journal entries to be generated, object auditing on the object must be set to *CHANGE. To set object auditing, use the CHGOBJAUD command.

PASS = ZC journal entries were not found in QAUDJRN

FAIL = ZC journal entries were found in QAUDJRN

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **7** (Object Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Object Details

This report contains the list of details related to system objects.

Collector ID: OBJECT_DETAILS

Report ID: *NONE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **1** (Object Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Object Reads

This report displays the read operations for objects. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is ZR.

Collector ID: JOURNAL_ZR

Report ID: *BASE

Tip: For ZR journal entries to be generated, object auditing on the object must be set to *ALL. To set object auditing, use the CHGOBJAUD command.

PASS = ZR journal entries were not found in QAUDJRN.

FAIL = ZR journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Object Reads).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Object Source

Use this report to list objects that were created using source files.

Collector ID: OBJECT_DETAILS

Report ID: OBJECT_SOURCE

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Changed in the Last 30 Days

Use this report to list objects that have changed in the last 30 days.

Collector ID: OBJECT_DETAILS

Report ID: OBJECT_CHANGED_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Created in the Last 30 Days

Use this report to list objects create in the last 30 days. The report is sorted by the object creator's name.

Collector ID: OBJECT_DETAILS

Report ID: OBJECT_CREATED_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Larger than 100MB

Use this report to list all objects larger than 100 MB (megabytes). The list is sorted by size in descending order.

Collector ID: OBJECT_DETAILS

Report ID: LARGEST_OBJECTS

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Owned by QSECOFR

Use this report to list objects owned by QSECOFR.

Collector ID: OBJECT_DETAILS

Report ID: OBJECT_OWNED_QSECOFR

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Restored

This report displays objects restored. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is OR.

Collector ID: JOURNAL_OR

Report ID: *BASE

Tip: For OR journal entries to be generated, the QAUDLVL system value must contain *SAVRST.

PASS = OR journal entries were not found in QAUDJRN.

FAIL = OR journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (Objects Restored).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Objects Used in the Last 30 Days

Use this report to list objects used in the last 30 days.

Collector ID: OBJECT_DETAILS

Report ID: OBJECT_USED_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Optical Volume Accesses

This report displays optical volume access details. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is O3.

Collector ID: JOURNAL_03

Report ID: *BASE

Tip: For O3 journal entries to be generated, the QAUDLVL system value must contain *OPTICAL.

PASS = O3 journal entries were not found in QAUDJRN.

FAIL = O3 journal entries were found in QAUDJRN.

Types of entries

A - Change Volume Attributes

B - Backup Volume

C - Convert Backup Volume to Primary

E - Export

I - Initialize

K - Check Volume

L - Change Authorization List

M - Import

N - Rename

R - Absolute Read

To run this report

1) Access the TGAudit main menu.

2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).

3) Press **Enter**.

4) At the **Selection or command** prompt, enter the **4** (Resource Reports).

5) Press **Enter**.

6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).

7) Press **Enter**.

8) At the **Selection or command** prompt, enter the **12** (Optical Volume Accesses).

9) Press **Enter**.

10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Printer Output Changes

This report displays printer output changes. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is PO.

Collector ID: JOURNAL_PO

Report ID: *BASE

Tip: For PO journal entries to be generated, the QAUDLVL system value must contain *PRTDTA.

PASS = PO journal entries were not found in QAUDJRN.

FAIL = PO journal entries were found in QAUDJRN.

Types of output

D - Direct print

R - Sent to remote system for printing

S - Spooled file printed

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (Printer Output Changes).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Program Reference Details

This report displays information about objects that are referenced by programs. The data shown in this report is similar to what is displayed through the Display Program Reference (DSPPGMREF) command.

Collector ID: PROGRAM_REFERENCE_DATA

Report ID: PROGRAM_REFERENCE_DATA

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **6** (Program Reference Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

> **Note**: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

> **Alternatively**, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Programs that Adopt Authority

This report contains the list of programs that adopted authority from previous call levels. Adopt Authority allows a user to run programs with higher privileges; therefore, ensure that all programs listed are known programs. If you see any unknown programs in the list, you might want to investigate and remove the adoption capability for those programs. You can perform this by running the Change Program Command (CHGPGM) and setting the Use Adopted Authority (USEADPAUT) option to *NO.

Collector ID: PROGRAM_ADOPT

Report ID: PROGRAMS_ADOPT_AUTHORITY

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **2** (Object Information Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **3** (Program Adopt Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

PTF Operations

This report displays Program Temporary Fix (PTF) operations such as loading, applying, or removing a PTF. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is PF.

Collector ID: JOURNAL_PF

Report ID: *BASE

Tip: For PF journal entries to be generated, the QAUDLVL system value must contain *PTFOPR.

PASS = PF journal entries were not found in QAUDJRN.

FAIL = PF journal entries were found in QAUDJRN.

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **1** (Configuration Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **8** (PTF Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **8** (PTF Operation).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Public Access to Commands in QSYS

This report displays information about commands in the QSYS library that do not have *PUBLIC authority set to *EXCLUDE or *AUTL.

Collector ID: OBJECT_AUTHORITIES

Report ID: COMMAND_AUTHORITY_QSYS

Tip: *PUBLIC represents all the users on the system. Allowing *PUBLIC access to commands in QSYS can be a security risk. If an individual user or a group of users requires access to commands, authorization lists should be used to secure the objects. Make sure the *PUBLIC authority on the authorization list is set to *EXCLUDE as well.

PASS = *PUBLIC authority for commands in QSYS is set to *EXCLUDE or *AUTL.

FAIL = *PUBLIC authority for commands in QSYS is not set to *EXCLUDE or *AUTL.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Public Access to Devices

This report displays information about devices that do not have *PUBLIC authority set to *EXCLUDE or *AUTL.

Collector ID: OBJECT_AUTHORITIES

Report ID: DEVICE_AUTHORITY

Tip: *PUBLIC represents all the users on the system. Allowing *PUBLIC access to devices can be a security risk. If an individual user or a group of users requires access to devices, authorization lists should be used to secure the objects. Make sure the *PUBLIC authority on the authorization list is set to *EXCLUDE as well.

PASS = *PUBLIC authority for devices is set to *EXCLUDE or *AUTL.

FAIL = *PUBLIC authority for devices is not set to *EXCLUDE or *AUTL.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Public Access to Journal Receivers in QGPL

This report displays information about journal receivers that do not have *PUBLIC authority set to *EXCLUDE or *AUTL.

Collector ID: OBJECT_AUTHORITIES

Report ID: JOURNAL_AUTHORITY_QGPL

Tip: *PUBLIC represents all the users on the system. Allowing *PUBLIC access to journal receivers can be a security risk since there can be sensitive data contained in journal receiver. If an individual user or a group of users requires access to journal receivers, authorization lists should be used to secure the objects. Make sure the *PUBLIC authority on the authorization list is set to *EXCLUDE as well.

PASS = *PUBLIC authority for journal receivers in QGPL is set to *EXCLUDE or *AUTL.

FAIL = *PUBLIC authority for journal receivers in QGPL is not set to *EXCLUDE or *AUTL.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Public Access to Objects in QGPL

This report displays objects in the QGPL library that do not have *PUBLIC authority set to *EXCLUDE or *AUTL.

Collector ID: OBJECT_AUTHORITIES

Report ID: OBJECT_AUTH_QGPL

Tip: *PUBLIC represents all the users on the system. Allowing *PUBLIC access to program and data can be a security risk. If an individual user or a group of users requires access to programs or data, authorization lists should be used to secure the objects. Make sure the *PUBLIC authority on the authorization list is set to *EXCLUDE as well.

PASS = *PUBLIC authority for objects in the QGPL library is set to *EXCLUDE or *AUTL.

FAIL = *PUBLIC authority for objects in the QGPL library is not set to *EXCLUDE or *AUTL.

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **30** (Work with Reports).

3) Press **Enter**. The **Work with Reports** interface is displayed.

4) Locate the desired report using the search and sort options available.

5) In the **Opt** field for the desired report, enter **7** (Run).

6) Press **Enter**.

7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Regular Files on the IFS

This report displays the file status for regular files on the IFS. Regular is defined in the Property field. This report will look at files 3 levels deep from root.

Collector ID: IFS_STATUS

Report ID: REGULAR_FILES

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **24** (Regular Files on the IFS).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Root *PUBLIC User with *RWX Authorities

This report displays the public and private authorities associated with the objects that have the Root attribute set to *RWX for the *PUBLIC user.

Collector ID: IFS_AUTHORITIES

Report ID: ROOT_PUBLIC_USER_AUTH_FILES

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

See also

Resource Management Reports

Socket Descriptor Details

This report displays socket descriptor details. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is GS.

Collector ID: JOURNAL_GS

Report ID: *BASE

Tip: For GS journal entries to be generated, the QAUDLVL system value must contain *SECSCKD and *SECURITY.

PASS = GS journal entries were not found in QAUDJRN.

FAIL = GS journal entries were found in QAUDJRN.

Types of entries:

G - Give descriptor

R - Received descriptor

U - Unable to use the descriptor

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **5** (Socket Descriptor Details).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Spooled File Actions

This report display changes made to spooled output files. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SF.

Collector ID: JOURNAL_SF

Report ID: *BASE

Tip: For SF journal entries to be generated, the QAUDLVL system value must contain *SPLFDTA.

PASS = SF journal entries were not found in QAUDJRN.

FAIL = SF journal entries were found in QAUDJRN.

Types of entries

A - Spooled file read by someone other than the owner of the spooled file

C - Spooled file created

D - Spooled file deleted

H - Spooled file held

I - Create of inline file

R - Spooled file released

S - Spooled file saved

T - Spooled file restored

U - Security-relevant spooled file attributes changed

V - Only non-security-relevant spooled file attributes changed

X - Spooled file operation rejected by exit program

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **1** (Object Activity Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **16** (Spooled File Actions).
9) Press **Enter**.

10) Modify the run criteria as necessary.

Note:

The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

System Directory Changes

This report displays System Directory changes. The data related to this report is retrieved from the system security audit journal (QAUDJRN). The journal entry type associated with this event is SD.

Collector ID: JOURNAL_SD

Report ID: *BASE

Tip: For SD journal entries to be generated, the QAUDLVL system value must contain *OFCSRV.

PASS = SD journal entries were not found in QAUDJRN.

FAIL = SD journal entries were found in QAUDJRN.

Types of entries

ADD - Add directory entry

CHG - Change directory entry

COL - Collector entry

DSP - Display directory entry

OUT - Output file request

PRT - Print directory entry

RMV - Remove directory entry

RNM - Rename directory entry

RTV - Retrieve details

SUP - Supplier entry

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **30** (Work with Reports).

3) Press **Enter**. The **Work with Reports** interface is displayed.

4) Locate the desired report using the search and sort options available.

5) In the **Opt** field for the desired report, enter **7** (Run).

6) Press **Enter**.

7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

System Security Audit Journal Exists

This report displays object details for the System Security Audit Journal (QAUDJRN) if it exists on the system.

Collector ID: OBJECT_DETAILS

Report ID: SYSTEM_JOURNAL_EXISTS

Tip: If the System Security Audit Journal (QAUDJRN) does not exist, it guarantees there is no auditing of system events happening on the system at all. This is a big risk for the entire system. Without an audit journal for system events, there is no data repository to gather forensic information from if a security event should occur.

PASS = System Security Audit Journal exists.

FAIL = System Security Audit Journal does not exist.

To run this report

1) Access the TGAudit **Main** menu.
2) At the **Selection or command** prompt, enter **30** (Work with Reports).
3) Press **Enter**. The **Work with Reports** interface is displayed.
4) Locate the desired report using the search and sort options available.
5) In the **Opt** field for the desired report, enter **7** (Run).
6) Press **Enter**.
7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

TGAudit Report Configuration

This report returns TGAudit configuration details.

Collector ID: IFS_CONTENT

Report ID: IFS_TGAUDIT_RPT_CNFG

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **27** (TGAudit Report Configuration).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

Report Column Description

Column	Description
Home	Home path to TG product installation
Headings	Number of headings
Label	Label type
Encode	Encode status
Schema	Schema status
Field Delimiter	Field delimiter type
Output CCSID	Coded character set identifier

See also

Resource Management Reports

TGCentral Agent Configuration

This report returns the TG Central configuration details.

Collector ID: IFS_CONTENT

Report ID: IFS_TGCENTRAL_AGENT

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **28** (TGCentral Report Configuration).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

Report Column Description

Column	Description
TGcentral_IP1	IP address for TGCentral
TGCenral_Name1	Name of TGCentral instance
TGCentral_Port1	Port used for TGCentral Integration
SSL	Secure socket layer certificate indicator
Poll_Time_Get	Ping value for get
Poll_Time_Set	Ping value for set
Page_Size	Page size
Debug_Level	Level at which to debug

JSONConv	JSON settings
LogFileAgtPath	Path to agent log file
LogFileSetPath	Path to set log file
LogFileGetPath	Path to get log file
LogFileJamPath	Path to Jam log file
LogFileSize	Log file size
LogArchiveFiles	Number of archive files
SendIncTrx	TRX indicator
BufferTriggers	Path to buffer t rigger file
PollTime	Ping value for poll time trigger
LogFileTgrPath	Path to trigger log file
SendDetAlr	Send TGDetect alert indicator
PollTimeGet	Ping value for get
PollTimeSet	Ping value for set

See also

Resource Management Reports

Unsaved Objects in the Last 30 Days

Use this report to list objects that have not been saved in the last 30 days. It is recommended that you regularly backup your mission-critical data.

Collector ID: OBJECT_DETAILS

Report ID: UNSAVED OBJECT_30

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **5** (Object Detail Reports).
7) Press **Enter**.
9) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

10) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

User-defined File Systems (UDFS's)

This report displays details about user-defined file systems (UDFS's). A user-defined file system *TYPE2 has high-performance file access. It has a minimum object size of 4096 bytes and a maximum object size of approximately one terabyte in the "root" QOpenSys and user-defined file systems. Otherwise, the maximum is approximately 256 gigabytes. A *TYPE2 *STMF is capable of memory mapping as well as the ability to specify an attribute to optimize disk storage allocation.

Note: This report returns IFS attributes of objects that are *TYPE2 format.

Collector ID: IFS_ATTRIBUTES

Report ID: USER_DEFINED_FILE_SYSTEM

To run this report

1) Access the TGAudit main menu.
2) At the **Selection or command** prompt, enter the **1** (Security and Configuration Reports).
3) Press **Enter**.
4) At the **Selection or command** prompt, enter the **4** (Resource Reports).
5) Press **Enter**.
6) At the **Selection or command** prompt, enter the **3** (Integrated File System Reports).
7) Press **Enter**.
8) At the **Selection or command** prompt, enter the **15** (User-defined File Systems (UDFS's)).
9) Press **Enter**.
10) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

11) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Verify Object on Restore

This report displays the value of the QVFYOBJRST (Verify Object on Restore) system value if a vulnerability is found.

Collector ID: SYSTEM_VALUES

Report ID: QVFYOBJRST

PASS = System value is set to 3 or higher.

FAIL = System value is set to 1 or 2.

This system value specifies the policy to be used for object signature verification during a restore operation.

These values apply to objects of types:

*CMD

*PGM

*SRVPGM

*SQLPKG

*MODULE

It also applies to *STMF objects which contain Java programs. This value also specifies the policy for PTFs applied to the system, including Licensed Internal Code fixes.

If Digital Certificate Manager is not installed on the system, all objects are treated as unsigned when determining the effects of this system value on those objects during a restore operation.

Program, service program and module objects that are created on a system with a release prior to V6R1 will be treated as unsigned when they are restored to a V6R1 or later system. Likewise, program, service program and module objects created or converted on a V6R1 or later release will be treated as unsigned when they are restored to a release previous to V6R1.

When an attempt is made to restore an object onto the system, three system values work together as filters to determine if the object is allowed to be restored, or if it is converted during the restore. The first filter is the verify object on restore (QVFYOBJRST) system value. It is used to control the restore of some objects that can be digitally signed. The second filter is the force conversion on restore QFRCCVNRST system value. This system value allows you to specify whether or not to convert programs, service programs, SQL packages, and module objects during the restore. It can also prevent some objects from being restored. Only objects that can get past the first two filters are processed by the third filter. The third filter is the allow object on restore QALWOBJRST system value. It specifies whether or not objects with security-sensitive attributes can be restored.

Tip: It is recommended to set this system value to 3 or higher.

To run this report

1) Access the TGAudit **Main** menu.

2) At the **Selection or command** prompt, enter **30** (Work with Reports).

3) Press **Enter**. The **Work with Reports** interface is displayed.

4) Locate the desired report using the search and sort options available.

5) In the **Opt** field for the desired report, enter **7** (Run).

6) Press **Enter**.

7) Modify the run criteria as necessary.

Note: The criteria allow you to limit the data returned in the report and choose the desired output format.

8) Press **Enter**.

Alternatively, you search for any report using the **Work with Reports** (TGWRKRPT) interface.

See also

Resource Management Reports

Version 4.2 - TGAudit Report Reference

There were no major updates to the TGAudit Report Reference for this release.

Version 4.1 - TGAudit Report Reference

There were no major updates to the TGAudit Report Reference for this release.

Version 4.0 - TGAudit Report Reference

There were no major updates to the TGAudit Report Reference for this release.

Version 3.4 - TGAudit Report Reference

Version 3.3 - TGAudit Report Reference

There were no major updates to the TGAudit Report Reference for this release.

Version 3.2 - TGAudit Report Reference

There were no major updates to the TGAudit Report Reference for this release.

Version 2.5 - TGAudit Report Reference

This release includes the following:

Enhancements

Collectors

The following new collectors are now available:

- DATABASE_MONITOR
- JOB_DATABASE_ACTIVITY

Reports

The following new reports are available:

- Database Monitor Activity report
- Job and Database Activity report

Version 2.4 - TGAudit Report Reference

This release includes the following:

Enhancements

Collectors

The following new collectors are now available:

- SYS_VAL_CONFIG
- SYS_VAL_DEFAULT
- SYS_VAL_VALID
- NETSERVER_CONFIG
- NETSERVER_SHARES
- QSYS2.DATA_QUEUE_ENTRIES
- QSYS2.EXIT_POINT_INFO
- QSYS2.EXIT_PROGRAM_INFO
- QSYS2.JOURNALED_OBJECTS
- QSYS2.SERVER_SHARE_INFO
- QSYS2.SOFTWARE_PRODUCT

Reports

Configuration Reports

The following new **Configuration** reports are now available:

- Exit Point Information
- Exit Program Information
- Software Product Information
- System Value Configuration Changes
- System Value Configuration Details
- System Value Default Changes
- System Value Defaults
- System Value Valid Value Changes
- System Value Valid Values

Network Reports

- NetServer Shares
- NetServer Configuration
- Server Share Information

Resource Reports

- Data Queue Entries
- Journaled Objects

Version 2.3 - TGAudit Report Reference

This release includes the following:

Enhancements

Collectors

The following new collectors are available:

- DATABASE_FIELD_ACTIVITY
- ENCRYPT_DATABASE_FIELD
- ENCRYPT_DATABASE_FILE
- ENCRYPT_DATABASE_FILTER
- ENCRYPT_DATABASE_RULES
- ENCRYPTION_DEFAULTS
- QHST.MSG_INFO
- QSYS2.MESSAGE_QUEUE_INFO

Reports

The following new reports are available:

- QHST Message Information
- QHST Messages with Severity Greater than 40
- Message Queue Data by Date Range
- Columns with Field Procedures

Version 2.2 - TGAudit Report Reference

This release includes the following:

Enhancements

Collectors

The following new collectors are now available for use:

- AUTHORITY_COL_ALI
- AUTHORITY_COL_IFS
- AUTHORITY_COL_OBJECT
- DATABASE_ACCESS
- DATABASE_OPERATIONS
- DTBASE_OPERATIONS_JRN
- QHST_MSG_INFO
- SENSITIVE_DATABASE_CONTENT

Authority Collection Reports

The following new reports are now available for use:

- Authority Collection for Object IFS Report
- Authority Collection for Object Native Report
- Authority Collection Report (*ALL)

Configuration Reports

The following new reports are now available for use:

- QHST Message Information
- QHST Messages with Severity Greater Than 40

Data Level Reports

The following new reports are now available for use:

- Database Access
- Database Operations
- Database Operations by Journal
- Sensitive Database Content

Resource Reports

The following new reports are now available for use:

- Changed Data Files in Last 30 Days
- Damages Objects
- Files Not Used in the Last 30 Days
- Journaled Files
- New Data Files in Last 30 Days
- New Library in Last 30 Days

- New Objects in the Last 30 Days
- Object Source
- Objects Changed in the Last 30 Days
- Objects Created in the Last 30 Days
- Objects Larger than 100MB
- Objects Owned by QSECOFR
- Objects Used in the Last 30 Days
- Restored Objects in the Last 30 Days
- Source Changes in Last 30 Days
- Unsaved Objects in the Last 30 Days

Note: The new **Resource** reports use the existing Object_Details collector.

Version 2.1 - TGAudit Report Reference

This release includes the following:

Enhancements

Collectors

The following new collectors are now available for use:

- DATABASE_CONTENT
- IFS_CONTENT
- JOURNAL_M0
- JOURNAL_M6
- JOURNAL_M7
- JOURNAL_M8
- JOURNAL_M9
- NETWORK_TRANS_SHOWCASE
- SERVICE_TOOL_SECURITY_ATTR
- TGMOBJINF

Note: See APPENDIX - TGAudit Collectors for a complete list of available collectors.

Reports

The following new reports are now available for use:

Configuration Reports

- Database Content
- Cross Reference Physical File
- Schedule Master File

Profile Reports

- Service Tool Security Attributes

Resources Reports

- Db2 Mirror Communication Services
- Db2 Mirror Product Services
- Db2 Mirror Replication Services
- Db2 Mirror Replication State
- Db2 Mirror Setup Tools
- File Statistics
- Integrated File System Content
- Library Statistics
- Object Statistics
- TGAudit Report Configuration

- TGCentral Agent Configuration

APPENDIX - TGAudit Collectors

Collector ID	Collector Name	Collector Category	Platform
ACCESS_ESCAL_ACC_CONTROLS	Access Escalation Access Controls	Network	IBMi
ACCESS_ESCAL_DEFAULTS	Access Escalation Defaults	Network	IBMi
ACCESS_ESCAL_ENTITLEMENTS	Access Escalation Entitlements	Network	IBMi
ACCESS_ESCAL_FILE_EDITORS	Access Escalation File Editors	Network	IBMi
ACCESS_ESCALATION_DETAILS	Access Escalation Details	Network	IBMi
ACCESS_ESCALATION_USAGE	Access Escalation Usage	Network	IBMi
AUTH_USERS_VIA_AUTH_LISTS	Authorized Users through Authorization Lists	Resource	IBMi
AUTHORITY_COL_ALI	Authority Collection Report (*ALL)	Resources	IBMi
AUTHORITY_COL_IFS	Auth Collection For Objects IFS Report	Resources	IBMi
AUTHORITY_COL_OBJECT	Auth Collection For Objects Native Report	Resources	IBMi
AUTHORITY_COLLECTION	Authority Collection Data	Journal	IBMi
AUTHORITY_COMPLIANCE	Authority Compliance	Resource	IBMi
AUTHORITY_LIST	Authority List Data	System	IBMi
BLUEPRINT_3RD_PARTY_FILE	Blueprint 3rd Party Integration File	Profile	IBMi
BLUEPRINT_AUTH_SETTINGS_FILE	Blueprint Authority List Settings File	Profile	IBMi
BLUEPRINT_MASTER	Blueprint Master	Profile	IBMi
BLUEPRINT_NON_COMPLIANCE_USER	Blueprint Non-Compliance User Profiles	Profile	IBMi
BLUEPRINT_OBJECT_AUTH_FILE	Blueprint Object Authority File	Profile	IBMi
BLUEPRINT_PARAMETER_FILE	Blueprint Parameter File	Profile	IBMi
BLUEPRINT_PERMISSION_FILE	Blueprint Permission File	Profile	IBMi
CMD_SEC_COMMANDS	Commands Allowed/Rejected via Command Security	Resources	IBMi
CMD_SEC_CONF_SETTINGS	Command Security Config Settings	Resources	IBMi
CMD_SEC_PARAM_LEVEL	Command Security Parameter Level	Resources	IBMi
CMD_SEC_RULES	Command Security Config Settings	Resources	IBMi
CONTROLLER_ATTACHED_DEVICES	Command Security Parameter Level	Network	IBMi
CONTROLLER_DESCRIPTION_DATA	Controller Description Information	Network	IBMi
DATA_AREA_AUDITING	Audit data area changes	Network	IBMi

DATABASE ACCESS	Database File Access	N/A	IBMi
DATABASE_AUDITING	Monitor Database changes	Network	IBMi
DATABASE_CONTENT	Database Content	Configuration	IBMi
DATABASE_FIELD_ACTIVITY	Database Field Activity	Resources	IBMi
DATABASE_MONITORING	Database Monitoring	Resources	IBMi
DATABASE_OPERATIONS	Database Operations	N/A	IBMi
DET_ACT_HISTORY	Detect Activity History	Network	IBMi
DET_DEFAULTS	Detect Defaults	Configuration	IBMi
DET_CMD_RULES	Command Monitor Rules	Configuration	IBMi
DET_JRN_SEIM_RULES	Journal Monitor Rules for SEIM	Configuration	IBMi
DET_JRNMON_ALERTS	Journal Monitor Alerts	Configuration	IBMi
DET_JRNMON_RULES	Journal Monitor Rules	Configuration	IBMi
DET_MON_MASTER	Monitor Master	Configuration	IBMi
DET_MSQ_CMD_ALR	Message Queue and Command Alerts	Configuration	IBMi
DET_MSQ_RULES	Message Queue Rules	Configuration	IBMi
DET_SEIM_PROVIDERS	SEIM Providers	Configuration	IBMi
DET_SNMP_TRP_PCKG	SNMP Trap Packages	Configuration	IBMi
DEVICE_DESCRIPTION_APPC	Device Description APPC Information	Network	IBMi
DEVICE_DESCRIPTION_DATA	Device Description Information	Network	IBMi
DTBASE_OPERATIONS_JRN	Database Operations by Journal	N/A	IBMi
ENCRYPT_DATABASE_FIELD	Encryption Database Field Details	Resource	IBMi
ENCRYPT_DATABASE_FILE	Encryption Database File Details	Resource	IBMi
ENCRYPT_DATABASE_FILTER	Encryption Database File Details	Resource	IBMi
ENCRYPT_DATABASE_RULES	Encryption Database Rule Details	Resource	IBMi
ENCRYPTION_DEFAULTS	Encryption Defaults	Resource	IBMi
EXIT_POINTS	Display Exit Point Data	Network	IBMi
FIELD_AUTHORITY	Display Field Level Authorities	Object	IBMi
IFS_ATTRIBUTES	Display the attributes for the IFS objects	Resource	IBMi
IFS_AUTHORITIES	Display the public and private authorities associated with the object	Resource	IBMi
IFS_CONTENT	IFS Content	Configuration	IBMi

IFS_JOURNALING	Display extended journaling information for the IFS object	Resource	IBMi
IFS_STATUS	Display status information about an IFS file	Resource	IBMi
INACTIVITY_DISCONNECTS	Inactivity Disconnections	Configuration	IBMi
INCOMING_TRANSACTIONS	Incoming Transactions	Network	IBMi
ISL_CONFIGURATION_SETTINGS	ISL Configuration Settings	Network	IBMi
ISL_DISCONNECT_OPTIONS	ISL Disconnect Options	Network	IBMi
ISL_RULES	ISL Inclusion Exclusion Rules	Network	IBMi
JOB_ACTIVITY_DETAILS	Job Activity Details	Log	IBMi
JOB_ACTIVITY_SUMMARY	Job Activity Summary	Log	IBMi
JOB_DATABASE_ACTIVITY	Job and Database Activity	Configuration	IBMi
JOB_DESCRIPTIONS	Job Description Data	Configuration	IBMi
JOURNAL_AD	Object Auditing Attribute Changes	Configuration	IBMi
JOURNAL_AF	Authority Failures	Profile	IBMi
JOURNAL_AP	Programs that Adopt Authority were Executed	Configuration	IBMi
JOURNAL_AU	EIM Attribute Changes	Configuration	IBMi
JOURNAL_AX	Row and Column Access Control	Resource	IBMi
JOURNAL_C3	Advanced Analysis Command Configuration	Resource	IBMi
JOURNAL_CA	Authorization List or Object Authority Changes	Profile	IBMi
JOURNAL_CD	Commands Executed	Resource	IBMi
JOURNAL_CO	Create Operations	Resource	IBMi
JOURNAL_CP	User Profile Changes	Configuration	IBMi
JOURNAL_CQ	Change Request Descriptor Changes	Configuration	IBMi
JOURNAL_CU	Cluster Operation	Network	IBMi
JOURNAL_CV	Connection Verification	Profile	IBMi
JOURNAL_CY	Cryptographic Configuration Changes	Configuration	IBMi
JOURNAL_DI	LDAP Operations	Resource	IBMi
JOURNAL_DO	Delete Operations	Resource	IBMi
JOURNAL_DS	Changes to Service Tools Profiles	Profile	IBMi

JOURNAL_EV	Environment Variable Changes	Profile	IBMi
JOURNAL_FT	FTP Client Operations - Certificate data	Network	IBMi
JOURNAL_GR	Exit Point Maintenance Operations	Resource	IBMi
JOURNAL_GS	Socket Descriptor Details	Resource	IBMi
JOURNAL_IM	Intrusion Monitor Events	Network	IBMi
JOURNAL_IP	Inter-process Communication Events	Network	IBMi
JOURNAL_IR	Actions to IP Rules	Network	IBMi
JOURNAL_IS	Internet Security Management Events	Network	IBMi
JOURNAL_JD	Job Descriptions – USER Parameter Changes	Resource	IBMi
JOURNAL_JS	Job Changes	Resource	IBMi
JOURNAL_KF	Key Ring File Changes	Configuration	IBMi
JOURNAL_LD	Directory Link, Unlink, and Search Operations	Resource	IBMi
JOURNAL_M0	Db2 Mirror Setup Tools	Resource	IBMi
JOURNAL_M6	Db2 Mirror Communication Services	Resource	IBMi
JOURNAL_M7	Db2 Mirror Replication Services	Resource	IBMi
JOURNAL_M8	Db2 Mirror Product Services	Resource	IBMi
JOURNAL_M9	Db2 Mirror Replication State	Resource	IBMi
JOURNAL_ML	OfficeVision Mail Services Actions	Configuration	IBMi
JOURNAL_NA	Network Attribute Changes	Profile	IBMi
JOURNAL_ND	Directory Search Violations	Resource	IBMi
JOURNAL_NE	APPN Endpoint Filter Violations	Network	IBMi
JOURNAL_O1	Single Optical Object Accesses	Resource	IBMi
JOURNAL_O2	Dual Optical Object Accesses	Resource	IBMi
JOURNAL_O3	Optical Volume Accesses	Resource	IBMi
JOURNAL_OM	Object Management Changes	Resource	IBMi
JOURNAL_OR	Objects Restored	Resource	IBMi
JOURNAL_OW	Object Ownership Changes	Resource	IBMi
JOURNAL_PA	Program Changes to Adopt Owner Authority	Configuration	IBMi

JOURNAL_PF	PTF Operations	Resource	IBMi
JOURNAL_PG	Primary Group Changes	Resource	IBMi
JOURNAL_PO	Printer Output Changes	Resource	IBMi
JOURNAL_PS	Swap Profile Events	Configuration	IBMi
JOURNAL_PU	PTF Object Changes	Profile	IBMi
JOURNAL_PW	Invalid Sign-on Attempts	Profile	IBMi
JOURNAL_RA	Authority Changes to Restored Objects	Configuration	IBMi
JOURNAL_RJ	Job Descriptions that Contain User Profile Names were Restored	Configuration	IBMi
JOURNAL_RO	Ownership Changes for Restored Objects	Profile	IBMi
JOURNAL_RP	Programs Restored that Adopt Owner Authority	Configuration	IBMi
JOURNAL_RQ	Change Request Descriptors Restored	Resource	IBMi
JOURNAL_RU	Authority Restored for User Profiles	Profile	IBMi
JOURNAL_RZ	Primary Group Changes for Restored Objects	Configuration	IBMi
JOURNAL_SD	System Directory Changes	Resource	IBMi
JOURNAL_SE	Subsystem Routing Entry Changes	Configuration	IBMi
JOURNAL_SF	Spooled File Actions	Resource	IBMi
JOURNAL_SG	Asynchronous Signals Processed	Network	IBMi
JOURNAL_SK	Secure Socket Connections	Network	IBMi
JOURNAL_SM	Systems Management Changes	Configuration	IBMi
JOURNAL_SO	Server Security User Information Actions	Configuration	IBMi
JOURNAL_ST	Service Tools Actions	Configuration	IBMi
JOURNAL_SV	System Values Changes	Configuration	IBMi
JOURNAL_VA	Access Control List Changes	Configuration	IBMi
JOURNAL_VC	Connections Started, Ended, or Rejected	Network	IBMi
JOURNAL_VF	Close Operations on Server Files	Resource	IBMi
JOURNAL_VL	Exceeded Account Limit Events	Profile	IBMi
JOURNAL_VN	Network Log On and Off Events	Configuration	IBMi

JOURNAL_VO	Actions on Validation Lists	Resource	IBMi
JOURNAL_VP	Network Password Errors	Profile	IBMi
JOURNAL_VR	Network Resource Accesses	Resource	IBMi
JOURNAL_VS	Server Sessions Started or Ended	Network	IBMi
JOURNAL_VU	Network Profile Changes	Profile	IBMi
JOURNAL_VV	Service Status Change Events	Network	IBMi
JOURNAL_X0	Network Authentication Events	Network	IBMi
JOURNAL_X1	Identity Token Events	Profile	IBMi
JOURNAL_XD	Directory Server Extensions	Profile	IBMi
JOURNAL_YC	DLO Object Changes	Resource	IBMi
JOURNAL_YR	DLO Object Reads	Resource	IBMi
JOURNAL_ZC	Object Changes	Resource	IBMi
JOURNAL_ZR	Object Reads	Resource	IBMi
KEYSTORE_DATA	KeyStore	Configuration	IBMi
LIBRARY_STAT	Library Statistics	Resources	IBMi
LINE_DESCRIPTION_DATA	Line Description Information	Configuration	IBMi
MESSAGE_QUEUE	Message Queue Details	Configuration	IBMi
MESSAGE_QUEUE_DATA	Message Queue Data	Configuration	IBMi
NETSERVER_CONFIG	NetServer Configuration	Network	IBMi
NETSERVER_SHARES	NetServer Shares	Network	IBMi
NETWORK_ATTRIBUTES	Network Attribute Information	Network	IBMi
NETWORK_CONNECTIONS	Network Connections Ipv4 and Ipv6	Network	IBMi
NETWORK_EXIT_CONFIG	Exit Point Configuration Report	Network	IBMi
NETWORK_INTERFACE_IPV4	Network Interface Data Ipv4	Network	IBMi
NETWORK_INTERFACE_IPV6	Network Interface Data Ipv6	Network	IBMi
NETWORK_ROUTE_IPV4	Network Route Data Ipv4	Network	IBMi
NETWORK_ROUTE_IPV6	Network Route Data Ipv6	Network	IBMi
NETWORK_SERVER_DESCRIPTIONS	Network Server Description Data	Network	IBMi
NETWORK_SVR_ENCRYPT_STATUS	Network Server Encryption Status	Network	IBMi

NETWORK_TCPIP_IPV4	TCP/IP Ipv4 Stack Attributes/Remote Exit Rule	Network	IBMi
NETWORK_TCPIP_IPV6	TCP/IP Ipv6 Stack Attributes/Remote Exit Rule	Network	IBMi
NETWORK_TRANS_CENTRAL	Central Server Transactions	Network	IBMi
NETWORK_TRANS_COMMAND	Remote Command Transactions	Network	IBMi
NETWORK_TRANS_DATABASE	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_DATAQ	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_DDM	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_FILE	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_FTP_REXEC	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_PRINTER	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_SHOWCASE	Network Trans Showcase	Network	IBMi
NETWORK_TRANS_SIGNON	Remote Exit Rules	Network	IBMi
NETWORK_TRANS_TELNET	Remote Exit Rules	Network	IBMi
OBJECT_AUTHORITY	Display Object Authority	Resource	IBMi
OBJECT_DETAILS	Display Object Details	Resource	IBMi
OBJECT_STAT	Object/File Statistics	Resource	IBMi
OUTPUT_QUEUE	Output Queue Information	Configuration	IBMi
PRODUCT_INFO	Basic Information about a software product	Configuration	IBMi
PROFILE_COMPLIANCE	Profile Compliance Data	Profile	IBMi
PROFILE_INACTIVITY_SETTINGS	Profile Inactivity Settings	Profile	IBMi
PROFILE_MANAGER_DEFAULTS	Profile Manager Defaults	Profile	IBMi
PROGRAM_ADOPT	Programs that Adopt Authority	Resource	IBMi
PROGRAM_REFERENCE_DATA	Program Reference Data	Resource	IBMi
PTF_DATA	Program Temporary Fix Data	Configuration	IBMi
QHST_MSG_INFO	QHST History Log Information	Configuration	IBMi
QSYS2.ACTIVE_JOB_INFO	Active job information	Configuration	IBMi
QSYS2.DATA_QUEUE_ENTRIES	Data Queue Entries	Resource	IBMi
QSYS2.DRDA_AUTHENTICATION	DRDA and DDM User access	Configuration	IBMi
QSYS2.EXIT_POINT_INFO	Exit Point Information	Configuration	IBMi

QSYS2.EXIT_PROGRAM_INFO	Exit Program Information	Configuration	IBMi
QSYS2.FUNCTION_INFO	Function usage identifiers	Configuration	IBMi
QSYS2.FUNCTION_USAGE	Function usage configuration details.	Configuration	IBMi
QSYS2.GROUP_PTF_INFO	Group PTFs Information	Configuration	IBMi
QSYS2.JOURNAL_INFO	Journal and remote journal information	Configuration	IBMi
QSYS2.JOURNALED_OBJECTS	Journal object information	Resource	IBMi
QSYS2.LICENSE_INFO	Products license information.	Configuration	IBMi
QSYS2.MEDIA_LIBRARY_INFO	Media Library Status details	Configuration	IBMi
QSYS2.MEMORY_POOL	Memory pool details	Configuration	IBMi
QSYS2.MEMORY_POOL_INFO	Active memory pools	Configuration	IBMi
QSYS2.MESSAGE_QUEUE_INFO	Message Queue	Configuration	IBMi
QSYS2.NETSTAT_JOB_INFO	IPv4 and IPv6 network connection details.	Configuration	IBMi
QSYS2.OBJECT_LOCK_INFO	Object lock information	Configuration	IBMi
QSYS2.OUTPUT_QUEUE_ENTRIES	Spooled file in output queue	Configuration	IBMi
QSYS2.RECORD_LOCK_INFO	Record lock information	Configuration	IBMi
QSYS2.REPLY_LIST_INFO	Current job's reply list entry information	Configuration	IBMi
QSYS2.SCHEDULED_JOB_INFO	Job Schedule Entry information	Configuration	IBMi
QSYS2.SECURITY_CONFIG	Security Configuration Information	Configuration	IBMi
QSYS2.SERVER_SBS_ROUTING	Alternate subsystem configurations	Configuration	IBMi
QSYS2.SERVER_SHARE_INFO	Server Share Information	Configuration	IBMi
QSYS2.SOFTWARE_PRODUCT	Server Software Product information	Configuration	IBMi
QSYS2.SYSCONTROLS	Permissions or column mask defined	Configuration	IBMi
QSYS2.SYSCONTROLSDEP	Dependencies of row permissions and column masks	Configuration	IBMi
QSYS2.SYSDISKSTAT	Disk Information	Configuration	IBMi
QSYS2.SYSTEM_STATUS_INFO	Partition information	Configuration	IBMi
QSYS2.SYSTMPSTG	IBM i temporary storage pool detail	Configuration	IBMi
QSYS2.TELNET_ATTRIB	TELNET Server Attributes	Network	IBMi
QSYS2.USER_INFO	User Profile Information	Configuration	IBMi
QSYS2.USER_STORAGE	Storage usage by user profile	Configuration	IBMi

REMOTE_TRAN_SUMMARY_BY_SERVER	Remote Summary Server	Network	IBMi
REMOTE_TRAN_SUMMARY_BY_USER	Remote Summary User	Network	IBMi
RSC_MGR_COMPLIANCE_DATA	Resource Manager Authority Out of compliance data	Network	IBMi
RSC_MGR_CONFIG	Resource Manager Configuration	Network	IBMi
RSC_MGR_SCHEMA_DETAILS	Resource Manager Authority Schema Details	Network	IBMi
RSC_MGR_SCHEMA_HEADER	Resource Manager Authority Schema Header	Network	IBMi
SENSITIVE_DATABASE_CONTENT	Sensitive Database Content	Profile	IBMi
SERVICE_TOOL_SECURITY_ATTR	Service Tool Security Attributes	Profile	IBMi
SERVICE_TOOL_USERS	Service Tool User Data	Profile	IBMi
SOCKET_SUMMARY_BY_SERVER	Socket Summary by Server	Network	IBMi
SOCKET_SUMMARY_BY_USER	Socket Summary by User	Network	IBMi
SOCKET_TRAN_RULES	Socket Rules	Network	IBMi
SOCKET_TRANSACTIONS	Socket Transactions	Network	IBMi
SOFTWARE_RESOURCES	Installed Software Resources Data	Configuration	IBMi
SUBSYSTEM_AUTOSTART	Subsystem Autostart Jobs	Configuration	IBMi
SUBSYSTEM_COMMUNICATIONS	Subsystem Communication Entries	Configuration	IBMi
SUBSYSTEM_INFORMATION	Subsystem Information Details	Configuration	IBMi
SUBSYSTEM_JOB_QUEUE	Subsystem Job Queue	Configuration	IBMi
SUBSYSTEM_POOL_DATA	Subsystem Pool Data	Configuration	IBMi
SUBSYSTEM_PRESTART	Subsystem Prestart Jobs	Configuration	IBMi
SUBSYSTEM_REMOTE	Subsystem Remote Entries	Configuration	IBMi
SUBSYSTEM_ROUTING	Subsystem Routing Entries	Configuration	IBMi
SUBSYSTEM_WORKSTATION_NAMES	Subsystem Workstation Names	Configuration	IBMi
SUBSYSTEM_WORKSTATION_TYPES	Subsystem Workstation Types	Configuration	IBMi
SYS_VAL_CONFIG	System Value Configuration	Configuration	IBMi
SYS_VAL_DEFAULT	System Value Default	Configuration	IBMi
SYS_VAL_VALID	System Value Default	Configuration	IBMi
SYSCOLAUTH	Privileges Granted on a Column	Configuration	IBMi
SYSCONTROLS	Permission or Column Mask Defined	Configuration	IBMi

SYSCONTROLSDEP	Dependencies of Row Permissions and Column Masks	Configuration	IBMi
SYSCONTROLSDEP	Privileges Granted on a Row	Configuration	IBMi
SYSFIELDS	Columns with Field Procedures	Configuration	IBMi
SYSPACKAGEAUTH	Privileges Granted on a Package	Configuration	IBMi
SYSPROGRAMSTAT	Program, Service Program, and Module with SQL Statements	Configuration	IBMi
SYSROUTINEAUTH	Privileges Granted on a Routine	Configuration	IBMi
SYSSCHEMAAUTH	Privileges Granted on a Schema	Configuration	IBMi
SYSSEQUENCEAUTH	Privileges Granted on a Sequence	Configuration	IBMi
SYSTABAUTH	Privileges Granted on a Table or View	Configuration	IBMi
SYSTABLESTAT	Table Statistics Include all Partitions and Members	Configuration	IBMi
SYSTEM_VALUES	Display System Value Data	System	IBMi
SYSTOOLS.GROUP_PTF_CURRENCY	PTF Groups Installed per IBM Recommendations	Configuration	IBMi
SYSTOOLS.GROUP_PTF_DETAILS	PTFs within PTF Groups Installed per IBM Recommendations	Configuration	IBMi
SYSUDTAUTH	Privileges Granted on a Type	Configuration	IBMi
SYSVARIABLEAUTH	Privileges Granted on a Global Variable	Configuration	IBMi
SYSXSROBJECTAUTH	Privileges Granted on an XML Schema	Configuration	IBMi
TGMOBJINF	Object Information	Resource	IBMi
TG_NETWORK_GROUPS	TG Network Groups	Network	IBMi
TG_OBJECT_GROUPS	TG Object Groups	Network	IBMi
TG_OPERATION_GROUPS	TG Operation Groups	Network	IBMi
TG_USER_GROUPS	TG User Groups	Network	IBMi
USER_OBJECT_AUTHORITIES	User Profile Object Authorities	Profile	IBMi
USER_PRF_VIA_BLUEPRINT	User Profile via Blueprint	Profile	IBMi
USER_PROFILE_ACTIVITY	User Profile Activity	Profile	IBMi
USER_PROFILE_ARCHIVE	User Profile Archive	Profile	IBMi
USER_PROFILE_EXCLUSIONS	User Profile Exclusions	Profile	IBMi

USER_PROFILES	Display User Profile Data	Profile	IBMi